



Threagile

Agile Threat Modeling

Threat Model Report

Ship Connected Operations

29 May 2026

threatmod-automation

Table of Contents

Results Overview

Management Summary	5
Impact Analysis of 24 Initial Risks in 10 Categories	6
Risk Mitigation	8
Impact Analysis of 24 Remaining Risks in 10 Categories	9
Application Overview	11
Data-Flow Diagram	12
Security Requirements	14
Abuse Cases	15
Tag Listing	16
STRIDE Classification of Identified Risks	17
Assignment by Function	19
RAA Analysis	21
Data Mapping	23
Out-of-Scope Assets: 0 Assets	24
Potential Model Failures: 3 / 3 Risks	25
Questions: 3 / 3 Questions	26

Risks by Vulnerability Category

Identified Risks by Vulnerability Category	27
Cross-Site Scripting (XSS): 5 / 5 Risks	28
SQL/NoSQL-Injection: 3 / 3 Risks	30
Server-Side Request Forgery (SSRF): 1 / 1 Risk	32
Cross-Site Request Forgery (CSRF): 2 / 2 Risks	34
Missing Cloud Hardening: 1 / 1 Risk	36
Missing Hardening: 6 / 6 Risks	39
Missing Build Infrastructure: 1 / 1 Risk	41
Missing Identity Store: 1 / 1 Risk	43
Missing Network Segmentation: 3 / 3 Risks	45
Missing Vault (Secret Storage): 1 / 1 Risk	47

Risks by Technical Asset

Identified Risks by Technical Asset	49
Autopilot Controller: 1 / 1 Risk	50
Bridge Firewall: 1 / 1 Risk	53
ECDIS Workstation: 3 / 3 Risks	56
Machinery Firewall: 1 / 1 Risk	61
Machinery HMI: 3 / 3 Risks	64

Maritime Cloud API: 1 / 1 Risk	68
Ship Core Router: 1 / 1 Risk	71
Ship IT Server: 2 / 2 Risks	74
Shore Operations API: 3 / 3 Risks	78
Fleet Data Lake: 2 / 2 Risks	81
Security Log Store: 2 / 2 Risks	83
Voyage Data Recorder: 2 / 2 Risks	85
AIS Transceiver: 1 / 1 Risk	87
Bridge Officer: 0 / 0 Risks	89
Chief Engineer: 0 / 0 Risks	91
Engine PLC: 0 / 0 Risks	93
GNSS Receiver: 0 / 0 Risks	95
Power Management System: 0 / 0 Risks	97
Radar Processor: 0 / 0 Risks	99
Satcom Terminal: 0 / 0 Risks	101
Ship Identity Service: 0 / 0 Risks	103
Shore Operator: 0 / 0 Risks	105

Data Breach Probabilities by Data Asset

Identified Data Breach Probabilities by Data Asset	107
Autopilot records steering mode: 3 / 3 Risks	108
Cloud API stores fleet telemetr: 5 / 5 Risks	109
Satcom terminal sends telemetry: 2 / 2 Risks	110
Ship IT server stores security: 4 / 4 Risks	111
Shore operations exchanges voya: 2 / 2 Risks	112
Shore operator reviews fleet st: 2 / 2 Risks	113
AIS transceiver provides vessel: 3 / 3 Risks	114
Bridge firewall permits selecte: 2 / 2 Risks	115
Bridge officer plans routes and: 3 / 3 Risks	116
Chief engineer monitors machine: 3 / 3 Risks	117
ECDIS forwards approved voyage: 4 / 4 Risks	118
ECDIS sends approved waypoint a: 3 / 3 Risks	119
GNSS receiver sends position, t: 3 / 3 Risks	120
Machinery HMI forwards selected: 4 / 4 Risks	121
Machinery HMI sends operator-ap: 3 / 3 Risks	122
Machinery firewall permits sele: 2 / 2 Risks	123
Power management reports breake: 3 / 3 Risks	124
Radar processor provides target: 3 / 3 Risks	125
Ship core router delivers filte: 2 / 2 Risks	126
Identity service provides crew: 1 / 1 Risk	127

Ship IT server forwards compres: 1 / 1 Risk	128
Engine PLC publishes load and g: 0 / 0 Risks	129

Trust Boundaries

Bridge OT Zone	130
Machinery OT Zone	130
Satcom DMZ	130
Ship Core Network Zone	130
Ship IT Zone	131
Shore Cloud Zone	131
Vessel Exterior Zone	131

About Threagile


Risk Rules Checked by Threagile	133
Disclaimer	146

Management Summary

Threagile toolkit was used to model the architecture of "Ship Connected Operations" and derive risks by analyzing the components and data flows. The risks identified during this analysis are shown in the following chapters. Identified risks during threat modeling do not necessarily mean that the vulnerability associated with this risk actually exists: it is more to be seen as a list of potential risks and threats, which should be individually reviewed and reduced by removing false positives. For the remaining risks it should be checked in the design and implementation of "Ship Connected Operations" whether the mitigation advices have been applied or not.

Each risk finding references a chapter of the OWASP ASVS (Application Security Verification Standard) audit checklist. The OWASP ASVS checklist should be considered as an inspiration by architects and developers to further harden the application in a Defense-in-Depth approach. Additionally, for each risk finding a link towards a matching OWASP Cheat Sheet or similar with technical details about how to implement a mitigation is given.

In total **24 initial risks** in **10 categories** have been identified during the threat modeling process:



Baseline connected-vessel architecture covering bridge navigation, machinery control, shipboard IT, shore operations, and cloud telemetry paths for dynamic threat modeling.

Impact Analysis of 24 Initial Risks in 10 Categories

The most prevalent impacts of the **24 initial risks** (distributed over **10 risk categories**) are (taking the severity ratings into account and using the highest for each category):

Risk finding paragraphs are clickable and link to the corresponding chapter.

Elevated: Cross-Site Scripting (XSS): 5 Initial Risks - Exploitation likelihood is *Likely with Medium impact*.

If this risk remains unmitigated, attackers might be able to access individual victim sessions and steal or modify user data.

Elevated: SQL/NoSQL-Injection: 3 Initial Risks - Exploitation likelihood is *Very Likely with Medium impact*.

If this risk is unmitigated, attackers might be able to modify SQL/NoSQL queries to steal and modify data and eventually further escalate towards a deeper system penetration via code executions.

Elevated: Server-Side Request Forgery (SSRF): 1 Initial Risk - Exploitation likelihood is *Likely with Medium impact*.

If this risk is unmitigated, attackers might be able to access sensitive services or files of network-reachable components by modifying outgoing calls of affected components.

Medium: Cross-Site Request Forgery (CSRF): 2 Initial Risks - Exploitation likelihood is *Very Likely with Low impact*.

If this risk remains unmitigated, attackers might be able to trick logged-in victim users into unwanted actions within the web application by visiting an attacker controlled web site.

Medium: Missing Cloud Hardening: 1 Initial Risk - Exploitation likelihood is *Unlikely with Medium impact*.

If this risk is unmitigated, attackers might access cloud components in an unintended way.

Medium: Missing Hardening: 6 Initial Risks - Exploitation likelihood is *Likely with Low impact*.

If this risk remains unmitigated, attackers might be able to easier attack high-value targets.

Low: Missing Build Infrastructure: 1 Initial Risk - Exploitation likelihood is *Unlikely with Low impact*.

If this risk is unmitigated, attackers might be able to exploit risks unseen in this threat model due to critical build infrastructure components missing in the model.

Low: Missing Identity Store: 1 Initial Risk - Exploitation likelihood is *Unlikely with Low impact*.

If this risk is unmitigated, attackers might be able to exploit risks unseen in this threat model in the identity provider/store that is currently missing in the model.

Low: Missing Network Segmentation: 3 Initial Risks - Exploitation likelihood is *Unlikely with Low impact*.


If this risk is unmitigated, attackers successfully attacking other components of the system might have an easy path towards more valuable targets, as they are not separated by network segmentation.

Low: **Missing Vault (Secret Storage)**: 1 Initial Risk - Exploitation likelihood is *Unlikely* with *Low* impact.

If this risk is unmitigated, attackers might be able to easier steal config secrets (like credentials, private keys, client certificates, etc.) once a vulnerability to access files is present and exploited.



Risk Mitigation

The following chart gives a high-level overview of the risk tracking status (including mitigated risks):



After removal of risks with status *mitigated* and *false positive* the following 24 remain unmitigated:

- 0 unmitigated critical risk
- 0 unmitigated high risk
- 9 unmitigated elevated risk
- 9 unmitigated medium risk
- 6 unmitigated low risk
- 0 business side related
- 3 architecture related
- 11 development related
- 10 operations related



Impact Analysis of 24 Remaining Risks in 10 Categories

The most prevalent impacts of the **24 remaining risks** (distributed over **10 risk categories**) are (taking the severity ratings into account and using the highest for each category):

Risk finding paragraphs are clickable and link to the corresponding chapter.

Elevated: **Cross-Site Scripting (XSS)**: 5 Remaining Risks - Exploitation likelihood is *Likely with Medium impact*.

If this risk remains unmitigated, attackers might be able to access individual victim sessions and steal or modify user data.

Elevated: **SQL/NoSQL-Injection**: 3 Remaining Risks - Exploitation likelihood is *Very Likely with Medium impact*.

If this risk is unmitigated, attackers might be able to modify SQL/NoSQL queries to steal and modify data and eventually further escalate towards a deeper system penetration via code executions.

Elevated: **Server-Side Request Forgery (SSRF)**: 1 Remaining Risk - Exploitation likelihood is *Likely with Medium impact*.

If this risk is unmitigated, attackers might be able to access sensitive services or files of network-reachable components by modifying outgoing calls of affected components.

Medium: **Cross-Site Request Forgery (CSRF)**: 2 Remaining Risks - Exploitation likelihood is *Very Likely with Low impact*.

If this risk remains unmitigated, attackers might be able to trick logged-in victim users into unwanted actions within the web application by visiting an attacker controlled web site.

Medium: **Missing Cloud Hardening**: 1 Remaining Risk - Exploitation likelihood is *Unlikely with Medium impact*.

If this risk is unmitigated, attackers might access cloud components in an unintended way.

Medium: **Missing Hardening**: 6 Remaining Risks - Exploitation likelihood is *Likely with Low impact*.

If this risk remains unmitigated, attackers might be able to easier attack high-value targets.

Low: **Missing Build Infrastructure**: 1 Remaining Risk - Exploitation likelihood is *Unlikely with Low impact*.

If this risk is unmitigated, attackers might be able to exploit risks unseen in this threat model due to critical build infrastructure components missing in the model.

Low: **Missing Identity Store**: 1 Remaining Risk - Exploitation likelihood is *Unlikely with Low impact*.

If this risk is unmitigated, attackers might be able to exploit risks unseen in this threat model in the identity provider/store that is currently missing in the model.

Low: **Missing Network Segmentation**: 3 Remaining Risks - Exploitation likelihood is *Unlikely with Low impact*.

If this risk is unmitigated, attackers successfully attacking other components of the system might have an easy path towards more valuable targets, as they are not separated by network segmentation.

Low: **Missing Vault (Secret Storage)**: 1 Remaining Risk - Exploitation likelihood is *Unlikely* with *Low* impact.

If this risk is unmitigated, attackers might be able to easier steal config secrets (like credentials, private keys, client certificates, etc.) once a vulnerability to access files is present and exploited.

Application Overview

Business Criticality

The overall business criticality of "Ship Connected Operations" was rated as:

(archive | operational | **IMPORTANT** | critical | mission-critical)

Business Overview

Baseline connected-vessel architecture covering bridge navigation, machinery control, shipboard IT, shore operations, and cloud telemetry paths for dynamic threat modeling.


Technical Overview

The vessel has segmented bridge, machinery, ship IT, and satellite communications networks. Shore operations receives operational telemetry but does not directly command safety-critical controllers in this baseline. Crew identity, audit logging, and backup workflows are represented at architecture level and need implementation detail during review.

Data-Flow Diagram

The following diagram was generated by Threagile based on the model input and gives a high-level overview of the data-flow between technical assets. The RAA value is the calculated *Relative Attacker Attractiveness* in percent. For a full high-resolution version of this diagram please refer to the PNG image file alongside this report.

Data-Flow Diagram - Ship Connected Operations



Security Requirements

This chapter lists the custom security requirements which have been defined for the modeled target.

This list is not complete and regulatory or law relevant security requirements have to be taken into account as well. Also custom individual security requirements might exist for the project.

Abuse Cases

This chapter lists the custom abuse cases which have been defined for the modeled target.

This list is not complete and regulatory or law relevant abuse cases have to be taken into account as well. Also custom individual abuse cases might exist for the project.

Tag Listing

This chapter lists what tags are used by which elements.

data-store

Fleet Data Lake, Security Log Store, Voyage Data Recorder

human-user

Bridge Officer, Chief Engineer, Shore Operator

it-service

Maritime Cloud API, Ship IT Server, Ship Identity Service, Shore Operations API

network-infrastructure

Bridge Firewall, Machinery Firewall, Satcom Terminal, Ship Core Router

operational-technology

AIS Transceiver, Autopilot Controller, ECDIS Workstation, Engine PLC, GNSS Receiver, Machinery HMI, Power Management System, Radar Processor, Voyage Data Recorder

STRIDE Classification of Identified Risks

This chapter clusters and classifies the risks by STRIDE categories: In total **24 potential risks** have been identified during the threat modeling process of which **3 in the Spoofing** category, **16 in the Tampering** category, **0 in the Repudiation** category, **2 in the Information Disclosure** category, **0 in the Denial of Service** category, and **3 in the Elevation of Privilege** category.

Risk finding paragraphs are clickable and link to the corresponding chapter.

Spoofing

Medium: **Cross-Site Request Forgery (CSRF)**: 2 / 2 Risks - Exploitation likelihood is *Very Likely* with *Low* impact.

When a web application is accessed via web protocols Cross-Site Request Forgery (CSRF) risks might arise.

Low: **Missing Identity Store**: 1 / 1 Risk - Exploitation likelihood is *Unlikely* with *Low* impact.

The modeled architecture does not contain an identity store, which might be the risk of a model missing critical assets (and thus not seeing their risks).

Tampering

Elevated: **Cross-Site Scripting (XSS)**: 5 / 5 Risks - Exploitation likelihood is *Likely* with *Medium* impact.

For each web application Cross-Site Scripting (XSS) risks might arise. In terms of the overall risk level take other applications running on the same domain into account as well.

Elevated: **SQL/NoSQL-Injection**: 3 / 3 Risks - Exploitation likelihood is *Very Likely* with *Medium* impact.

When a database is accessed via database access protocols SQL/NoSQL-Injection risks might arise. The risk rating depends on the sensitivity technical asset itself and of the data assets processed or stored.

Medium: **Missing Cloud Hardening**: 1 / 1 Risk - Exploitation likelihood is *Unlikely* with *Medium* impact.

Cloud components should be hardened according to the cloud vendor best practices. This affects their configuration, auditing, and further areas.

Medium: **Missing Hardening**: 6 / 6 Risks - Exploitation likelihood is *Likely* with *Low* impact.

Technical assets with a Relative Attacker Attractiveness (RAA) value of 55 % or higher should be explicitly hardened taking best practices and vendor hardening guides into account.

Low: **Missing Build Infrastructure**: 1 / 1 Risk - Exploitation likelihood is *Unlikely* with *Low* impact.

The modeled architecture does not contain a build infrastructure (devops-client, sourcecode-repo, build-pipeline, etc.), which might be the risk of a model missing critical assets (and thus not seeing their risks). If the architecture contains custom-developed parts, the pipeline where code

gets developed and built needs to be part of the model.

Repudiation

n/a

Information Disclosure

Elevated: Server-Side Request Forgery (SSRF): 1 / 1 Risk - Exploitation likelihood is *Likely* with *Medium* impact.

When a server system (i.e. not a client) is accessing other server systems via typical web protocols Server-Side Request Forgery (SSRF) or Local-File-Inclusion (LFI) or Remote-File-Inclusion (RFI) risks might arise.

Low: Missing Vault (Secret Storage): 1 / 1 Risk - Exploitation likelihood is *Unlikely* with *Low* impact.

In order to avoid the risk of secret leakage via config files (when attacked through vulnerabilities being able to read files like Path-Traversal and others), it is best practice to use a separate hardened process with proper authentication, authorization, and audit logging to access config secrets (like credentials, private keys, client certificates, etc.). This component is usually some kind of Vault.

Denial of Service

n/a

Elevation of Privilege

Low: Missing Network Segmentation: 3 / 3 Risks - Exploitation likelihood is *Unlikely* with *Low* impact.

Highly sensitive assets and/or datastores residing in the same network segment than other lower sensitive assets (like webservers or content management systems etc.) should be better protected by a network segmentation trust-boundary.

Assignment by Function

This chapter clusters and assigns the risks by functions which are most likely able to check and mitigate them: In total **24 potential risks** have been identified during the threat modeling process of which **0 should be checked by Business Side**, **3 should be checked by Architecture**, **11 should be checked by Development**, and **10 should be checked by Operations**.

Risk finding paragraphs are clickable and link to the corresponding chapter.

Business Side

n/a

Architecture

Low: **Missing Build Infrastructure**: 1 / 1 Risk - Exploitation likelihood is *Unlikely* with *Low* impact.

Include the build infrastructure in the model.

Low: **Missing Identity Store**: 1 / 1 Risk - Exploitation likelihood is *Unlikely* with *Low* impact.

Include an identity store in the model if the application has a login.

Low: **Missing Vault (Secret Storage)**: 1 / 1 Risk - Exploitation likelihood is *Unlikely* with *Low* impact.

Consider using a Vault (Secret Storage) to securely store and access config secrets (like credentials, private keys, client certificates, etc.).

Development

Elevated: **Cross-Site Scripting (XSS)**: 5 / 5 Risks - Exploitation likelihood is *Likely* with *Medium* impact.

Try to encode all values sent back to the browser and also handle DOM-manipulations in a safe way to avoid DOM-based XSS. When a third-party product is used instead of custom developed software, check if the product applies the proper mitigation and ensure a reasonable patch-level.

Elevated: **SQL/NoSQL-Injection**: 3 / 3 Risks - Exploitation likelihood is *Very Likely* with *Medium* impact.

Try to use parameter binding to be safe from injection vulnerabilities. When a third-party product is used instead of custom developed software, check if the product applies the proper mitigation and ensure a reasonable patch-level.

Elevated: **Server-Side Request Forgery (SSRF)**: 1 / 1 Risk - Exploitation likelihood is *Likely* with *Medium* impact.

Try to avoid constructing the outgoing target URL with caller controllable values. Alternatively use a mapping (whitelist) when accessing outgoing URLs instead of creating them including caller controllable values. When a third-party product is used instead of custom developed software,

check if the product applies the proper mitigation and ensure a reasonable patch-level.

Medium: Cross-Site Request Forgery (CSRF): 2 / 2 Risks - Exploitation likelihood is *Very Likely* with *Low* impact.

Try to use anti-CSRF tokens or the double-submit patterns (at least for logged-in requests). When your authentication scheme depends on cookies (like session or token cookies), consider marking them with the same-site flag. When a third-party product is used instead of custom developed software, check if the product applies the proper mitigation and ensure a reasonable patch-level.

Operations

Medium: Missing Cloud Hardening: 1 / 1 Risk - Exploitation likelihood is *Unlikely* with *Medium* impact.

Apply hardening of all cloud components and services, taking special care to follow the individual risk descriptions (which depend on the cloud provider tags in the model).

Medium: Missing Hardening: 6 / 6 Risks - Exploitation likelihood is *Likely* with *Low* impact.

Try to apply all hardening best practices (like CIS benchmarks, OWASP recommendations, vendor recommendations, DevSec Hardening Framework, DBSAT for Oracle databases, and others).

Low: Missing Network Segmentation: 3 / 3 Risks - Exploitation likelihood is *Unlikely* with *Low* impact.

Apply a network segmentation trust-boundary around the highly sensitive assets and/or datastores.

RAA Analysis

For each technical asset the **"Relative Attacker Attractiveness"** (RAA) value was calculated in percent. The higher the RAA, the more interesting it is for an attacker to compromise the asset. The calculation algorithm takes the sensitivity ratings and quantities of stored and processed data into account as well as the communication links of the technical asset. Neighbouring assets to high-value RAA targets might receive an increase in their RAA value when they have a communication link towards that target ("Pivoting-Factor").

The following lists all technical assets sorted by their RAA value from highest (most attacker attractive) to lowest. This list can be used to prioritize on efforts relevant for the most attacker-attractive technical assets:

Technical asset paragraphs are clickable and link to the corresponding chapter.

ECDIS Workstation: RAA 100%

Imported from UML element 'ECDIS Workstation' of kind 'component'.

Machinery HMI: RAA 64%

Imported from UML element 'Machinery HMI' of kind 'component'.

Ship IT Server: RAA 64%

Imported from UML element 'Ship IT Server' of kind 'service'.

Fleet Data Lake: RAA 58%

Imported from UML element 'Fleet Data Lake' of kind 'database'.

Security Log Store: RAA 58%

Imported from UML element 'Security Log Store' of kind 'database'.

Voyage Data Recorder: RAA 58%

Imported from UML element 'Voyage Data Recorder' of kind 'database'.

Ship Core Router: RAA 39%

Imported from UML element 'Ship Core Router' of kind 'node'.

Shore Operations API: RAA 36%

Imported from UML element 'Shore Operations API' of kind 'cloud'.

Power Management System: RAA 22%

Imported from UML element 'Power Management System' of kind 'service'.

Autopilot Controller: RAA 22%

Imported from UML element 'Autopilot Controller' of kind 'device'.

Maritime Cloud API: RAA 22%

Imported from UML element 'Maritime Cloud API' of kind 'cloud'.

Bridge Firewall: RAA 20%

Imported from UML element 'Bridge Firewall' of kind 'component'.

Machinery Firewall: RAA 20%

Imported from UML element 'Machinery Firewall' of kind 'component'.

Satcom Terminal: RAA 20%

Imported from UML element 'Satcom Terminal' of kind 'device'.

Engine PLC: RAA 18%

Imported from UML element 'Engine PLC' of kind 'device'.

AIS Transceiver: RAA 8%

Imported from UML element 'AIS Transceiver' of kind 'device'.

Bridge Officer: RAA 8%

Imported from UML element 'Bridge Officer' of kind 'actor'.

GNSS Receiver: RAA 8%

Imported from UML element 'GNSS Receiver' of kind 'device'.

Radar Processor: RAA 8%

Imported from UML element 'Radar Processor' of kind 'device'.

Chief Engineer: RAA 5%

Imported from UML element 'Chief Engineer' of kind 'actor'.

Ship Identity Service: RAA 5%


Imported from UML element 'Ship Identity Service' of kind 'service'.

Shore Operator: RAA 3%

Imported from UML element 'Shore Operator' of kind 'actor'.

Data Mapping

The following diagram was generated by Threagile based on the model input and gives a high-level distribution of data assets across technical assets. The color matches the identified data breach probability and risk level (see the "Data Breach Probabilities" chapter for more details). A solid line stands for *data is stored by the asset* and a dashed one means *data is processed by the asset*. For a full high-resolution version of this diagram please refer to the PNG image file alongside this report.



Out-of-Scope Assets: 0 Assets

This chapter lists all technical assets that have been defined as out-of-scope. Each one should be checked in the model whether it should better be included in the overall risk analysis:

Technical asset paragraphs are clickable and link to the corresponding chapter.

No technical assets have been defined as out-of-scope.

Potential Model Failures: 3 / 3 Risks

This chapter lists potential model failures where not all relevant assets have been modeled or the model might itself contain inconsistencies. Each potential model failure should be checked in the model against the architecture design:

Risk finding paragraphs are clickable and link to the corresponding chapter.

Low: Missing Build Infrastructure: 1 / 1 Risk - Exploitation likelihood is *Unlikely* with *Low* impact. The modeled architecture does not contain a build infrastructure (devops-client, sourcecode-repo, build-pipeline, etc.), which might be the risk of a model missing critical assets (and thus not seeing their risks). If the architecture contains custom-developed parts, the pipeline where code gets developed and built needs to be part of the model.

Low: Missing Identity Store: 1 / 1 Risk - Exploitation likelihood is *Unlikely* with *Low* impact. The modeled architecture does not contain an identity store, which might be the risk of a model missing critical assets (and thus not seeing their risks).

Low: Missing Vault (Secret Storage): 1 / 1 Risk - Exploitation likelihood is *Unlikely* with *Low* impact.

In order to avoid the risk of secret leakage via config files (when attacked through vulnerabilities being able to read files like Path-Traversal and others), it is best practice to use a separate hardened process with proper authentication, authorization, and audit logging to access config secrets (like credentials, private keys, client certificates, etc.). This component is usually some kind of Vault.

Questions: 3 / 3 Questions

This chapter lists custom questions that arose during the threat modeling process.

Flow auth and replay controls?

- answer pending -

Identity and secrets admin?

- answer pending -

Safety critical assets?

- answer pending -

Identified Risks by Vulnerability Category

In total **24 potential risks** have been identified during the threat modeling process of which **0 are rated as critical, 0 as high, 9 as elevated, 9 as medium, and 6 as low.**

These risks are distributed across **10 vulnerability categories**. The following sub-chapters of this section describe each identified risk category.

Cross-Site Scripting (XSS): 5 / 5 Risks

Description (Tampering): [CWE 79](#)

For each web application Cross-Site Scripting (XSS) risks might arise. In terms of the overall risk level take other applications running on the same domain into account as well.

Impact

If this risk remains unmitigated, attackers might be able to access individual victim sessions and steal or modify user data.

Detection Logic

In-scope web applications.

Risk Rating

The risk rating depends on the sensitivity of the data processed or stored in the web application.

False Positives

When the technical asset is not accessed via a browser-like component (i.e not by a human user initiating the request that gets passed through all components until it reaches the web application) this can be considered a false positive.

Mitigation (Development): XSS Prevention

Try to encode all values sent back to the browser and also handle DOM-manipulations in a safe way to avoid DOM-based XSS. When a third-party product is used instead of custom developed software, check if the product applies the proper mitigation and ensure a reasonable patch-level.

ASVS Chapter: [V5 - Validation, Sanitization and Encoding Verification Requirements](#)

Cheat Sheet: [Cross Site Scripting Prevention Cheat Sheet](#)

Check

Are recommendations from the linked cheat sheet and referenced ASVS chapter applied?

Risk Findings

The risk **Cross-Site Scripting (XSS)** was found **5 times** in the analyzed architecture to be potentially possible. Each spot should be checked individually by reviewing the implementation whether all controls have been applied properly in order to mitigate each risk.

Risk finding paragraphs are clickable and link to the corresponding chapter.

Elevated Risk Severity

Cross-Site Scripting (XSS) risk at Bridge Firewall: Exploitation likelihood is *Likely* with *Medium* impact.

[cross-site-scripting@bridge-firewall](#)

Unchecked

Cross-Site Scripting (XSS) risk at ECDIS Workstation: Exploitation likelihood is *Likely* with *Medium* impact.

[cross-site-scripting@ecdis-workstation](#)

Unchecked

Cross-Site Scripting (XSS) risk at Machinery Firewall: Exploitation likelihood is *Likely* with *Medium* impact.

[cross-site-scripting@machinery-firewall](#)

Unchecked

Cross-Site Scripting (XSS) risk at Machinery HMI: Exploitation likelihood is *Likely* with *Medium* impact.

[cross-site-scripting@machinery-hmi](#)

Unchecked

Cross-Site Scripting (XSS) risk at Ship Core Router: Exploitation likelihood is *Likely* with *Medium* impact.

[cross-site-scripting@ship-core-router](#)

Unchecked

SQL/NoSQL-Injection: 3 / 3 Risks

Description (Tampering): [CWE 89](#)

When a database is accessed via database access protocols SQL/NoSQL-Injection risks might arise. The risk rating depends on the sensitivity technical asset itself and of the data assets processed or stored.

Impact

If this risk is unmitigated, attackers might be able to modify SQL/NoSQL queries to steal and modify data and eventually further escalate towards a deeper system penetration via code executions.

Detection Logic

Database accessed via typical database access protocols by in-scope clients.

Risk Rating

The risk rating depends on the sensitivity of the data stored inside the database.

False Positives

Database accesses by queries not consisting of parts controllable by the caller can be considered as false positives after individual review.

Mitigation (Development): SQL/NoSQL-Injection Prevention

Try to use parameter binding to be safe from injection vulnerabilities. When a third-party product is used instead of custom developed software, check if the product applies the proper mitigation and ensure a reasonable patch-level.

ASVS Chapter: [V5 - Validation, Sanitization and Encoding Verification Requirements](#)

Cheat Sheet: [SQL_Injection_Prevention_Cheat_Sheet](#)

Check

Are recommendations from the linked cheat sheet and referenced ASVS chapter applied?

Risk Findings

The risk **SQL/NoSQL-Injection** was found **3 times** in the analyzed architecture to be potentially possible. Each spot should be checked individually by reviewing the implementation whether all controls have been applied properly in order to mitigate each risk.

Risk finding paragraphs are clickable and link to the corresponding chapter.

Elevated Risk Severity

SQL/NoSQL-Injection risk at **Autopilot Controller** against database **Voyage Data Recorder** via **Flow 6**: Exploitation likelihood is *Very Likely* with *Medium* impact.

[sql-nosql-injection@autopilot-controller@vdr-recorder@autopilot-controller>flow-6](#)

Unchecked

SQL/NoSQL-Injection risk at **Maritime Cloud API** against database **Fleet Data Lake** via **Flow 22**: Exploitation likelihood is *Very Likely* with *Medium* impact.

[sql-nosql-injection@maritime-cloud-api@fleet-data-lake@maritime-cloud-api>flow-22](#)

Unchecked

SQL/NoSQL-Injection risk at **Ship IT Server** against database **Security Log Store** via **Flow 16**: Exploitation likelihood is *Very Likely* with *Medium* impact.

[sql-nosql-injection@ship-it-server@security-log-store@ship-it-server>flow-16](#)

Unchecked

Server-Side Request Forgery (SSRF): 1 / 1 Risk

Description (Information Disclosure): [CWE 918](#)

When a server system (i.e. not a client) is accessing other server systems via typical web protocols Server-Side Request Forgery (SSRF) or Local-File-Inclusion (LFI) or Remote-File-Inclusion (RFI) risks might arise.

Impact

If this risk is unmitigated, attackers might be able to access sensitive services or files of network-reachable components by modifying outgoing calls of affected components.

Detection Logic

In-scope non-client systems accessing (using outgoing communication links) targets with either HTTP or HTTPS protocol.

Risk Rating

The risk rating (low or medium) depends on the sensitivity of the data assets receivable via web protocols from targets within the same network trust-boundary as well on the sensitivity of the data assets receivable via web protocols from the target asset itself. Also for cloud-based environments the exploitation impact is at least medium, as cloud backend services can be attacked via SSRF.

False Positives

Servers not sending outgoing web requests can be considered as false positives after review.

Mitigation (Development): SSRF Prevention

Try to avoid constructing the outgoing target URL with caller controllable values. Alternatively use a mapping (whitelist) when accessing outgoing URLs instead of creating them including caller controllable values. When a third-party product is used instead of custom developed software, check if the product applies the proper mitigation and ensure a reasonable patch-level.

ASVS Chapter: [V12 - File and Resources Verification Requirements](#)

Cheat Sheet: [Server_Side_Request_Forgery_Prevention_Cheat_Sheet](#)

Check

Are recommendations from the linked cheat sheet and referenced ASVS chapter applied?

Risk Findings

The risk **Server-Side Request Forgery (SSRF)** was found **1 time** in the analyzed architecture to be potentially possible. Each spot should be checked individually by reviewing the implementation whether all controls have been applied properly in order to mitigate each risk.

Risk finding paragraphs are clickable and link to the corresponding chapter.

Elevated Risk Severity

Server-Side Request Forgery (SSRF) risk at **Shore Operations API** server-side web-requesting the target **Maritime Cloud API** via **Flow 21**: Exploitation likelihood is *Likely* with *Medium* impact.

server-side-request-forgery@shore-operations-api@maritime-cloud-api@shore-operations-api>flow-21

Unchecked

Cross-Site Request Forgery (CSRF): 2 / 2 Risks

Description (Spoofing): [CWE 352](#)

When a web application is accessed via web protocols Cross-Site Request Forgery (CSRF) risks might arise.

Impact

If this risk remains unmitigated, attackers might be able to trick logged-in victim users into unwanted actions within the web application by visiting an attacker controlled web site.

Detection Logic

In-scope web applications accessed via typical web access protocols.

Risk Rating

The risk rating depends on the integrity rating of the data sent across the communication link.

False Positives

Web applications passing the authentication state via custom headers instead of cookies can eventually be false positives. Also when the web application is not accessed via a browser-like component (i.e not by a human user initiating the request that gets passed through all components until it reaches the web application) this can be considered a false positive.

Mitigation (Development): CSRF Prevention

Try to use anti-CSRF tokens or the double-submit patterns (at least for logged-in requests). When your authentication scheme depends on cookies (like session or token cookies), consider marking them with the same-site flag. When a third-party product is used instead of custom developed software, check if the product applies the proper mitigation and ensure a reasonable patch-level.

ASVS Chapter: [V4 - Access Control Verification Requirements](#)

Cheat Sheet: [Cross-Site_Request_Forgery_Prevention_Cheat_Sheet](#)

Check

Are recommendations from the linked cheat sheet and referenced ASVS chapter applied?

Risk Findings

The risk **Cross-Site Request Forgery (CSRF)** was found **2 times** in the analyzed architecture to be potentially possible. Each spot should be checked individually by reviewing the implementation whether all controls have been applied properly in order to mitigate each risk.

Risk finding paragraphs are clickable and link to the corresponding chapter.

Medium Risk Severity

Cross-Site Request Forgery (CSRF) risk at ECDIS Workstation via Flow 1 from Bridge Officer: Exploitation likelihood is *Very Likely* with *Low* impact.

[cross-site-request-forgery@ecdis-workstation@bridge-officer>flow-1](#)

Unchecked

Cross-Site Request Forgery (CSRF) risk at Machinery HMI via Flow 7 from Chief Engineer: Exploitation likelihood is *Very Likely* with *Low* impact.

[cross-site-request-forgery@machinery-hmi@chief-engineer>flow-7](#)

Unchecked

Missing Cloud Hardening: 1 / 1 Risk

Description (Tampering): [CWE 1008](#)

Cloud components should be hardened according to the cloud vendor best practices. This affects their configuration, auditing, and further areas.

Impact

If this risk is unmitigated, attackers might access cloud components in an unintended way.

Detection Logic

In-scope cloud components (either residing in cloud trust boundaries or more specifically tagged with cloud provider types).

Risk Rating

The risk rating depends on the sensitivity of the technical asset itself and of the data assets processed and stored.

False Positives

Cloud components not running parts of the target architecture can be considered as false positives after individual review.

Mitigation (Operations): Cloud Hardening

Apply hardening of all cloud components and services, taking special care to follow the individual risk descriptions (which depend on the cloud provider tags in the model).

For **Amazon Web Services (AWS)**: Follow the *CIS Benchmark for Amazon Web Services* (see also the automated checks of cloud audit tools like "PacBot", "CloudSploit", "CloudMapper", "ScoutSuite", or "Prowler AWS CIS Benchmark Tool").

For EC2 and other servers running Amazon Linux, follow the *CIS Benchmark for Amazon Linux* and switch to IMDSv2.

For S3 buckets follow the *Security Best Practices for Amazon S3* at

<https://docs.aws.amazon.com/AmazonS3/latest/dev/security-best-practices.html> to avoid accidental leakage.

Also take a look at some of these tools: <https://github.com/toniblyx/my-arsenal-of-aws-security-tools>

For **Microsoft Azure**: Follow the *CIS Benchmark for Microsoft Azure* (see also the automated checks of cloud audit tools like "CloudSploit" or "ScoutSuite").

For **Google Cloud Platform**: Follow the *CIS Benchmark for Google Cloud Computing Platform* (see also the automated checks of cloud audit tools like "*CloudSploit*" or "*ScoutSuite*").

For **Oracle Cloud Platform**: Follow the hardening best practices (see also the automated checks of cloud audit tools like "*CloudSploit*").

ASVS Chapter: [V1 - Architecture, Design and Threat Modeling Requirements](#)

Cheat Sheet: [Attack_Surface_Analysis_Cheat_Sheet](#)

Check

Are recommendations from the linked cheat sheet and referenced ASVS chapter applied?

Risk Findings

The risk **Missing Cloud Hardening** was found **1 time** in the analyzed architecture to be potentially possible. Each spot should be checked individually by reviewing the implementation whether all controls have been applied properly in order to mitigate each risk.

Risk finding paragraphs are clickable and link to the corresponding chapter.

Medium Risk Severity

Missing Cloud Hardening risk at **Shore Cloud Zone**: Exploitation likelihood is *Unlikely* with *Medium* impact.

[missing-cloud-hardening@shore-cloud-zone](#)

Unchecked

Missing Hardening: 6 / 6 Risks

Description (Tampering): [CWE 16](#)

Technical assets with a Relative Attacker Attractiveness (RAA) value of 55 % or higher should be explicitly hardened taking best practices and vendor hardening guides into account.

Impact

If this risk remains unmitigated, attackers might be able to easier attack high-value targets.

Detection Logic

In-scope technical assets with RAA values of 55 % or higher. Generally for high-value targets like datastores, application servers, identity providers and ERP systems this limit is reduced to 40 %

Risk Rating

The risk rating depends on the sensitivity of the data processed or stored in the technical asset.

False Positives

Usually no false positives.

Mitigation (Operations): System Hardening

Try to apply all hardening best practices (like CIS benchmarks, OWASP recommendations, vendor recommendations, DevSec Hardening Framework, DBSAT for Oracle databases, and others).

ASVS Chapter: [V14 - Configuration Verification Requirements](#)

Cheat Sheet: [Attack_Surface_Analysis_Cheat_Sheet](#)

Check

Are recommendations from the linked cheat sheet and referenced ASVS chapter applied?

Risk Findings

The risk **Missing Hardening** was found **6 times** in the analyzed architecture to be potentially possible. Each spot should be checked individually by reviewing the implementation whether all controls have been applied properly in order to mitigate each risk.

Risk finding paragraphs are clickable and link to the corresponding chapter.

Medium Risk Severity

Missing Hardening risk at **ECDIS Workstation**: Exploitation likelihood is *Likely* with *Low* impact.

[missing-hardening@ecdis-workstation](#)

Unchecked

Missing Hardening risk at **Fleet Data Lake**: Exploitation likelihood is *Likely* with *Low* impact.

[missing-hardening@fleet-data-lake](#)

Unchecked

Missing Hardening risk at **Machinery HMI**: Exploitation likelihood is *Likely* with *Low* impact.

[missing-hardening@machinery-hmi](#)

Unchecked

Missing Hardening risk at **Security Log Store**: Exploitation likelihood is *Likely* with *Low* impact.

[missing-hardening@security-log-store](#)

Unchecked

Missing Hardening risk at **Ship IT Server**: Exploitation likelihood is *Likely* with *Low* impact.

[missing-hardening@ship-it-server](#)

Unchecked

Missing Hardening risk at **Voyage Data Recorder**: Exploitation likelihood is *Likely* with *Low* impact.

[missing-hardening@vdr-recorder](#)

Unchecked

Missing Build Infrastructure: 1 / 1 Risk

Description (Tampering): [CWE 1127](#)

The modeled architecture does not contain a build infrastructure (devops-client, sourcecode-repo, build-pipeline, etc.), which might be the risk of a model missing critical assets (and thus not seeing their risks). If the architecture contains custom-developed parts, the pipeline where code gets developed and built needs to be part of the model.

Impact

If this risk is unmitigated, attackers might be able to exploit risks unseen in this threat model due to critical build infrastructure components missing in the model.

Detection Logic

Models with in-scope custom-developed parts missing in-scope development (code creation) and build infrastructure components (devops-client, sourcecode-repo, build-pipeline, etc.).

Risk Rating

The risk rating depends on the highest sensitivity of the in-scope assets running custom-developed parts.

False Positives

Models not having any custom-developed parts can be considered as false positives after individual review.

Mitigation (Architecture): Build Pipeline Hardening

Include the build infrastructure in the model.

ASVS Chapter: [V1 - Architecture, Design and Threat Modeling Requirements](#)

Cheat Sheet: [Attack_Surface_Analysis_Cheat_Sheet](#)

Check

Are recommendations from the linked cheat sheet and referenced ASVS chapter applied?

Risk Findings

The risk **Missing Build Infrastructure** was found **1 time** in the analyzed architecture to be potentially possible. Each spot should be checked individually by reviewing the implementation whether all controls have been applied properly in order to mitigate each risk.

Risk finding paragraphs are clickable and link to the corresponding chapter.

Low Risk Severity

Missing Build Infrastructure in the threat model (referencing asset **Shore Operations API** as an example): Exploitation likelihood is *Unlikely* with *Low* impact.

[missing-build-infrastructure@shore-operations-api](#)

Unchecked

Missing Identity Store: 1 / 1 Risk

Description (Spoofing): [CWE 287](#)

The modeled architecture does not contain an identity store, which might be the risk of a model missing critical assets (and thus not seeing their risks).

Impact

If this risk is unmitigated, attackers might be able to exploit risks unseen in this threat model in the identity provider/store that is currently missing in the model.

Detection Logic

Models with authenticated data-flows authorized via enduser-identity missing an in-scope identity store.

Risk Rating

The risk rating depends on the sensitivity of the enduser-identity authorized technical assets and their data assets processed and stored.

False Positives

Models only offering data/services without any real authentication need can be considered as false positives after individual review.

Mitigation (Architecture): Identity Store

Include an identity store in the model if the application has a login.

ASVS Chapter: [V2 - Authentication Verification Requirements](#)

Cheat Sheet: [Authentication_Cheat_Sheet](#)

Check

Are recommendations from the linked cheat sheet and referenced ASVS chapter applied?

Risk Findings

The risk **Missing Identity Store** was found **1 time** in the analyzed architecture to be potentially possible. Each spot should be checked individually by reviewing the implementation whether all controls have been applied properly in order to mitigate each risk.

Risk finding paragraphs are clickable and link to the corresponding chapter.

Low Risk Severity

Missing Identity Store in the threat model (referencing asset **Shore Operations API** as an example): Exploitation likelihood is *Unlikely* with *Low* impact.

[missing-identity-store@shore-operations-api](#)

Unchecked

Missing Network Segmentation: 3 / 3 Risks

Description (Elevation of Privilege): [CWE 1008](#)

Highly sensitive assets and/or datastores residing in the same network segment than other lower sensitive assets (like webserver or content management systems etc.) should be better protected by a network segmentation trust-boundary.

Impact

If this risk is unmitigated, attackers successfully attacking other components of the system might have an easy path towards more valuable targets, as they are not separated by network segmentation.

Detection Logic

In-scope technical assets with high sensitivity and RAA values as well as datastores when surrounded by assets (without a network trust-boundary in-between) which are of type client-system, web-server, web-application, cms, web-service-rest, web-service-soap, build-pipeline, sourcecode-repository, monitoring, or similar and there is no direct connection between these (hence no requirement to be so close to each other).

Risk Rating

Default is low risk. The risk is increased to medium when the asset missing the trust-boundary protection is rated as strictly-confidential or mission-critical.

False Positives

When all assets within the network segmentation trust-boundary are hardened and protected to the same extend as if all were containing/processing highly sensitive data.

Mitigation (Operations): Network Segmentation

Apply a network segmentation trust-boundary around the highly sensitive assets and/or datastores.

ASVS Chapter: [V1 - Architecture, Design and Threat Modeling Requirements](#)

Cheat Sheet: [Attack_Surface_Analysis_Cheat_Sheet](#)

Check

Are recommendations from the linked cheat sheet and referenced ASVS chapter applied?

Risk Findings

The risk **Missing Network Segmentation** was found **3 times** in the analyzed architecture to be potentially possible. Each spot should be checked individually by reviewing the implementation whether all controls have been applied properly in order to mitigate each risk.

Risk finding paragraphs are clickable and link to the corresponding chapter.

Low Risk Severity

Missing Network Segmentation to further encapsulate and protect **Fleet Data Lake** against unrelated lower protected assets in the same network segment, which might be easier to compromise by attackers: Exploitation likelihood is *Unlikely* with *Low* impact.

[missing-network-segmentation@fleet-data-lake](#)

Unchecked

Missing Network Segmentation to further encapsulate and protect **Security Log Store** against unrelated lower protected assets in the same network segment, which might be easier to compromise by attackers: Exploitation likelihood is *Unlikely* with *Low* impact.

[missing-network-segmentation@security-log-store](#)

Unchecked

Missing Network Segmentation to further encapsulate and protect **Voyage Data Recorder** against unrelated lower protected assets in the same network segment, which might be easier to compromise by attackers: Exploitation likelihood is *Unlikely* with *Low* impact.

[missing-network-segmentation@vdr-recorder](#)

Unchecked

Missing Vault (Secret Storage): 1 / 1 Risk

Description (Information Disclosure): [CWE 522](#)

In order to avoid the risk of secret leakage via config files (when attacked through vulnerabilities being able to read files like Path-Traversal and others), it is best practice to use a separate hardened process with proper authentication, authorization, and audit logging to access config secrets (like credentials, private keys, client certificates, etc.). This component is usually some kind of Vault.

Impact

If this risk is unmitigated, attackers might be able to easier steal config secrets (like credentials, private keys, client certificates, etc.) once a vulnerability to access files is present and exploited.

Detection Logic

Models without a Vault (Secret Storage).

Risk Rating

The risk rating depends on the sensitivity of the technical asset itself and of the data assets processed and stored.

False Positives

Models where no technical assets have any kind of sensitive config data to protect can be considered as false positives after individual review.

Mitigation (Architecture): Vault (Secret Storage)

Consider using a Vault (Secret Storage) to securely store and access config secrets (like credentials, private keys, client certificates, etc.).

ASVS Chapter: [V6 - Stored Cryptography Verification Requirements](#)

Cheat Sheet: [Cryptographic_Storage_Cheat_Sheet](#)

Check

Is a Vault (Secret Storage) in place?

Risk Findings

The risk **Missing Vault (Secret Storage)** was found **1 time** in the analyzed architecture to be potentially possible. Each spot should be checked individually by reviewing the implementation whether all controls have been applied properly in order to mitigate each risk.

Risk finding paragraphs are clickable and link to the corresponding chapter.

Low Risk Severity

Missing Vault (Secret Storage) in the threat model (referencing asset **AIS Transceiver** as an example): Exploitation likelihood is *Unlikely* with *Low* impact.

[missing-vault@ais-transceiver](#)

Unchecked

Identified Risks by Technical Asset

In total **24 potential risks** have been identified during the threat modeling process of which **0 are rated as critical, 0 as high, 9 as elevated, 9 as medium, and 6 as low.**

These risks are distributed across **22 in-scope technical assets**. The following sub-chapters of this section describe each identified risk grouped by technical asset. The RAA value of a technical asset is the calculated "Relative Attacker Attractiveness" value in percent.

Autopilot Controller: 1 / 1 Risk

Description

Imported from UML element 'Autopilot Controller' of kind 'device'.

Identified Risks of Asset

Risk finding paragraphs are clickable and link to the corresponding chapter.

Elevated Risk Severity

SQL/NoSQL-Injection risk at Autopilot Controller against database Voyage Data Recorder via Flow 6: Exploitation likelihood is *Very Likely* with *Medium* impact.

`sql-nosql-injection@autopilot-controller@vdr-recorder@autopilot-controller>flow-6`

Unchecked

Asset Information

ID:	autopilot-controller
Type:	process
Usage:	business
RAA:	22 %
Size:	component
Technology:	iot-device
Tags:	operational-technology
Internet:	false
Machine:	physical
Encryption:	none
Multi-Tenant:	false
Redundant:	false
Custom-Developed:	false
Client by Human:	false
Data Processed:	Autopilot records steering mode, ECDIS sends approved waypoint a
Data Stored:	none
Formats Accepted:	none of the special data formats accepted

Asset Rating

Owner:	Imported from UML
Confidentiality:	restricted (rated 3 in scale of 5)

Integrity:	important	(rated 3 in scale of 5)
Availability:	important	(rated 3 in scale of 5)
CIA-Justification:	This asset was inferred automatically from the UML model and needs manual CIA review.	

Outgoing Communication Links: 1

Target technical asset names are clickable and link to the corresponding chapter.

Flow 6 (outgoing)

Autopilot records steering mode, heading commands, and status.

Target:	Voyage Data Recorder
Protocol:	binary
Encrypted:	false
Authentication:	none
Authorization:	none
Read-Only:	false
Usage:	business
Tags:	none
VPN:	false
IP-Filtered:	false
Data Sent:	Autopilot records steering mode
Data Received:	none

Incoming Communication Links: 1

Source technical asset names are clickable and link to the corresponding chapter.

Flow 5 (incoming)

ECDIS sends approved waypoint and track guidance to autopilot.

Source:	ECDIS Workstation
Protocol:	binary
Encrypted:	false
Authentication:	none
Authorization:	none
Read-Only:	false
Usage:	business
Tags:	none
VPN:	false

IP-Filtered: false
Data Received: ECDIS sends approved waypoint a
Data Sent: none

Bridge Firewall: 1 / 1 Risk

Description

Imported from UML element 'Bridge Firewall' of kind 'component'.

Identified Risks of Asset

Risk finding paragraphs are clickable and link to the corresponding chapter.

Elevated Risk Severity

Cross-Site Scripting (XSS) risk at **Bridge Firewall**: Exploitation likelihood is *Likely* with *Medium* impact.

[cross-site-scripting@bridge-firewall](#)

Unchecked

Asset Information

ID:	bridge-firewall
Type:	process
Usage:	business
RAA:	20 %
Size:	component
Technology:	web-application
Tags:	network-infrastructure
Internet:	false
Machine:	virtual
Encryption:	none
Multi-Tenant:	false
Redundant:	false
Custom-Developed:	true
Client by Human:	false
Data Processed:	Bridge firewall permits selecte, ECDIS forwards approved voyage
Data Stored:	none
Formats Accepted:	none of the special data formats accepted

Asset Rating

Owner:	Imported from UML
Confidentiality:	restricted (rated 3 in scale of 5)

Integrity:	important	(rated 3 in scale of 5)
Availability:	important	(rated 3 in scale of 5)
CIA-Justification:	This asset was inferred automatically from the UML model and needs manual CIA review.	

Outgoing Communication Links: 1

Target technical asset names are clickable and link to the corresponding chapter.

Flow 13 (outgoing)

Bridge firewall permits selected navigation telemetry to ship core.

Target:	Ship Core Router
Protocol:	binary-encrypted
Encrypted:	true
Authentication:	none
Authorization:	none
Read-Only:	false
Usage:	business
Tags:	none
VPN:	false
IP-Filtered:	false
Data Sent:	Bridge firewall permits selecte
Data Received:	none

Incoming Communication Links: 1

Source technical asset names are clickable and link to the corresponding chapter.

Flow 11 (incoming)

ECDIS forwards approved voyage data and logs toward ship core.

Source:	ECDIS Workstation
Protocol:	binary-encrypted
Encrypted:	true
Authentication:	none
Authorization:	none
Read-Only:	false
Usage:	business
Tags:	none
VPN:	false

IP-Filtered: false
Data Received: ECDIS forwards approved voyage
Data Sent: none

ECDIS Workstation: 3 / 3 Risks

Description

Imported from UML element 'ECDIS Workstation' of kind 'component'.

Identified Risks of Asset

Risk finding paragraphs are clickable and link to the corresponding chapter.

Elevated Risk Severity

Cross-Site Scripting (XSS) risk at **ECDIS Workstation**: Exploitation likelihood is *Likely* with *Medium* impact.

[cross-site-scripting@ecdis-workstation](#)

Unchecked

Medium Risk Severity

Cross-Site Request Forgery (CSRF) risk at **ECDIS Workstation** via **Flow 1** from **Bridge Officer**: Exploitation likelihood is *Very Likely* with *Low* impact.

[cross-site-request-forgery@ecdis-workstation@bridge-officer>flow-1](#)

Unchecked

Missing Hardening risk at **ECDIS Workstation**: Exploitation likelihood is *Likely* with *Low* impact.

[missing-hardening@ecdis-workstation](#)

Unchecked

Asset Information

ID:	ecdis-workstation
Type:	process
Usage:	business
RAA:	100 %
Size:	component
Technology:	web-application
Tags:	operational-technology
Internet:	false
Machine:	virtual
Encryption:	none
Multi-Tenant:	false
Redundant:	false

Custom-Developed: true
Client by Human: false
Data Processed: AIS transceiver provides vessel, Bridge officer plans routes and, ECDIS forwards approved voyage, ECDIS sends approved waypoint a, GNSS receiver sends position, t, Radar processor provides target
Data Stored: none
Formats Accepted: none of the special data formats accepted

Asset Rating

Owner: Imported from UML
Confidentiality: restricted (rated 3 in scale of 5)
Integrity: important (rated 3 in scale of 5)
Availability: important (rated 3 in scale of 5)
CIA-Justification: This asset was inferred automatically from the UML model and needs manual CIA review.

Outgoing Communication Links: 2

Target technical asset names are clickable and link to the corresponding chapter.

Flow 5 (outgoing)

ECDIS sends approved waypoint and track guidance to autopilot.

Target: Autopilot Controller
Protocol: binary
Encrypted: false
Authentication: none
Authorization: none
Read-Only: false
Usage: business
Tags: none
VPN: false
IP-Filtered: false
Data Sent: ECDIS sends approved waypoint a
Data Received: none

Flow 11 (outgoing)

ECDIS forwards approved voyage data and logs toward ship core.

Target:	Bridge Firewall
Protocol:	binary-encrypted
Encrypted:	true
Authentication:	none
Authorization:	none
Read-Only:	false
Usage:	business
Tags:	none
VPN:	false
IP-Filtered:	false
Data Sent:	ECDIS forwards approved voyage
Data Received:	none

Incoming Communication Links: 4

Source technical asset names are clickable and link to the corresponding chapter.

Flow 3 (incoming)

Radar processor provides target overlays and radar tracks.

Source:	Radar Processor
Protocol:	binary
Encrypted:	false
Authentication:	none
Authorization:	none
Read-Only:	false
Usage:	business
Tags:	none
VPN:	false
IP-Filtered:	false
Data Received:	Radar processor provides target
Data Sent:	none

Flow 2 (incoming)

GNSS receiver sends position, time, and fix quality to ECDIS.

Source:	GNSS Receiver
Protocol:	binary
Encrypted:	false

Authentication:	none
Authorization:	none
Read-Only:	false
Usage:	business
Tags:	none
VPN:	false
IP-Filtered:	false
Data Received:	GNSS receiver sends position, t
Data Sent:	none

Flow 1 (incoming)

Bridge officer plans routes and acknowledges navigation alerts.

Source:	Bridge Officer
Protocol:	https
Encrypted:	true
Authentication:	none
Authorization:	none
Read-Only:	false
Usage:	business
Tags:	none
VPN:	false
IP-Filtered:	false
Data Received:	Bridge officer plans routes and
Data Sent:	none

Flow 4 (incoming)

AIS transceiver provides vessel identity and target messages.

Source:	AIS Transceiver
Protocol:	binary
Encrypted:	false
Authentication:	none
Authorization:	enduser-identity-propagation
Read-Only:	false
Usage:	business
Tags:	none
VPN:	false
IP-Filtered:	false
Data Received:	AIS transceiver provides vessel

Data Sent: none

Machinery Firewall: 1 / 1 Risk

Description

Imported from UML element 'Machinery Firewall' of kind 'component'.

Identified Risks of Asset

Risk finding paragraphs are clickable and link to the corresponding chapter.

Elevated Risk Severity

Cross-Site Scripting (XSS) risk at **Machinery Firewall**: Exploitation likelihood is *Likely* with *Medium* impact.

[cross-site-scripting@machinery-firewall](#)

Unchecked

Asset Information

ID:	machinery-firewall
Type:	process
Usage:	business
RAA:	20 %
Size:	component
Technology:	web-application
Tags:	network-infrastructure
Internet:	false
Machine:	virtual
Encryption:	none
Multi-Tenant:	false
Redundant:	false
Custom-Developed:	true
Client by Human:	false
Data Processed:	Machinery HMI forwards selected, Machinery firewall permits sele
Data Stored:	none
Formats Accepted:	none of the special data formats accepted

Asset Rating

Owner:	Imported from UML
Confidentiality:	restricted (rated 3 in scale of 5)

Integrity:	important	(rated 3 in scale of 5)
Availability:	important	(rated 3 in scale of 5)
CIA-Justification:	This asset was inferred automatically from the UML model and needs manual CIA review.	

Outgoing Communication Links: 1

Target technical asset names are clickable and link to the corresponding chapter.

Flow 14 (outgoing)

Machinery firewall permits selected machinery telemetry to ship core.

Target:	Ship Core Router
Protocol:	binary-encrypted
Encrypted:	true
Authentication:	none
Authorization:	none
Read-Only:	false
Usage:	business
Tags:	none
VPN:	false
IP-Filtered:	false
Data Sent:	Machinery firewall permits sele
Data Received:	none

Incoming Communication Links: 1

Source technical asset names are clickable and link to the corresponding chapter.

Flow 12 (incoming)

Machinery HMI forwards selected alarms and machinery telemetry.

Source:	Machinery HMI
Protocol:	binary-encrypted
Encrypted:	true
Authentication:	none
Authorization:	none
Read-Only:	false
Usage:	business
Tags:	none
VPN:	false

IP-Filtered: false
Data Received: Machinery HMI forwards selected
Data Sent: none

Machinery HMI: 3 / 3 Risks

Description

Imported from UML element 'Machinery HMI' of kind 'component'.

Identified Risks of Asset

Risk finding paragraphs are clickable and link to the corresponding chapter.

Elevated Risk Severity

Cross-Site Scripting (XSS) risk at **Machinery HMI**: Exploitation likelihood is *Likely* with *Medium* impact.

[cross-site-scripting@machinery-hmi](#)

Unchecked

Medium Risk Severity

Cross-Site Request Forgery (CSRF) risk at **Machinery HMI** via **Flow 7** from **Chief Engineer**: Exploitation likelihood is *Very Likely* with *Low* impact.

[cross-site-request-forgery@machinery-hmi@chief-engineer>flow-7](#)

Unchecked

Missing Hardening risk at **Machinery HMI**: Exploitation likelihood is *Likely* with *Low* impact.

[missing-hardening@machinery-hmi](#)

Unchecked

Asset Information

ID:	machinery-hmi
Type:	process
Usage:	business
RAA:	64 %
Size:	component
Technology:	web-application
Tags:	operational-technology
Internet:	false
Machine:	virtual
Encryption:	none
Multi-Tenant:	false
Redundant:	false
Custom-Developed:	true

Client by Human: false
Data Processed: Chief engineer monitors machine, Machinery HMI forwards selected, Machinery HMI sends operator-ap, Power management reports break
Data Stored: none
Formats Accepted: none of the special data formats accepted

Asset Rating

Owner: Imported from UML
Confidentiality: restricted (rated 3 in scale of 5)
Integrity: important (rated 3 in scale of 5)
Availability: important (rated 3 in scale of 5)
CIA-Justification: This asset was inferred automatically from the UML model and needs manual CIA review.

Outgoing Communication Links: 2

Target technical asset names are clickable and link to the corresponding chapter.

Flow 8 (outgoing)

Machinery HMI sends operator-approved engine commands.

Target: Engine PLC
Protocol: binary-encrypted
Encrypted: true
Authentication: none
Authorization: enduser-identity-propagation
Read-Only: false
Usage: business
Tags: none
VPN: false
IP-Filtered: false
Data Sent: Machinery HMI sends operator-ap
Data Received: none

Flow 12 (outgoing)

Machinery HMI forwards selected alarms and machinery telemetry.

Target: Machinery Firewall

Protocol:	binary-encrypted
Encrypted:	true
Authentication:	none
Authorization:	none
Read-Only:	false
Usage:	business
Tags:	none
VPN:	false
IP-Filtered:	false
Data Sent:	Machinery HMI forwards selected
Data Received:	none

Incoming Communication Links: 2

Source technical asset names are clickable and link to the corresponding chapter.

Flow 10 (incoming)

Power management reports breaker, generator, and load-shed status.

Source:	Power Management System
Protocol:	binary-encrypted
Encrypted:	true
Authentication:	none
Authorization:	none
Read-Only:	false
Usage:	business
Tags:	none
VPN:	false
IP-Filtered:	false
Data Received:	Power management reports breake
Data Sent:	none

Flow 7 (incoming)

Chief engineer monitors machinery state and acknowledges alarms.

Source:	Chief Engineer
Protocol:	https
Encrypted:	true
Authentication:	none
Authorization:	none

Read-Only: false
Usage: business
Tags: none
VPN: false
IP-Filtered: false
Data Received: Chief engineer monitors machine
Data Sent: none

Maritime Cloud API: 1 / 1 Risk

Description

Imported from UML element 'Maritime Cloud API' of kind 'cloud'.

Identified Risks of Asset

Risk finding paragraphs are clickable and link to the corresponding chapter.

Elevated Risk Severity

SQL/NoSQL-Injection risk at **Maritime Cloud API** against database **Fleet Data Lake** via **Flow 22**: Exploitation likelihood is *Very Likely* with *Medium* impact.

[sql-nosql-injection@maritime-cloud-api@fleet-data-lake@maritime-cloud-api>flow-22](#)

Unchecked

Asset Information

ID:	maritime-cloud-api
Type:	process
Usage:	business
RAA:	22 %
Size:	system
Technology:	web-service-rest
Tags:	it-service
Internet:	true
Machine:	virtual
Encryption:	none
Multi-Tenant:	false
Redundant:	false
Custom-Developed:	true
Client by Human:	false
Data Processed:	Cloud API stores fleet telemetr, Shore operations exchanges voya
Data Stored:	none
Formats Accepted:	none of the special data formats accepted

Asset Rating

Owner:	Imported from UML
Confidentiality:	restricted (rated 3 in scale of 5)

Integrity:	important	(rated 3 in scale of 5)
Availability:	important	(rated 3 in scale of 5)
CIA-Justification:	This asset was inferred automatically from the UML model and needs manual CIA review.	

Outgoing Communication Links: 1

Target technical asset names are clickable and link to the corresponding chapter.

Flow 22 (outgoing)

Cloud API stores fleet telemetry, alerts, and voyage summaries.

Target:	Fleet Data Lake
Protocol:	binary
Encrypted:	false
Authentication:	none
Authorization:	technical-user
Read-Only:	false
Usage:	business
Tags:	none
VPN:	false
IP-Filtered:	false
Data Sent:	Cloud API stores fleet telemetr
Data Received:	none

Incoming Communication Links: 1

Source technical asset names are clickable and link to the corresponding chapter.

Flow 21 (incoming)

Shore operations exchanges voyage and maintenance summaries with cloud services.

Source:	Shore Operations API
Protocol:	https
Encrypted:	true
Authentication:	none
Authorization:	technical-user
Read-Only:	false
Usage:	business
Tags:	none
VPN:	false

IP-Filtered: false

Data Received: Shore operations exchanges voya

Data Sent: none

Ship Core Router: 1 / 1 Risk

Description

Imported from UML element 'Ship Core Router' of kind 'node'.

Identified Risks of Asset

Risk finding paragraphs are clickable and link to the corresponding chapter.

Elevated Risk Severity

Cross-Site Scripting (XSS) risk at **Ship Core Router**: Exploitation likelihood is *Likely* with *Medium* impact.

[cross-site-scripting@ship-core-router](#)

Unchecked

Asset Information

ID:	ship-core-router
Type:	process
Usage:	business
RAA:	39 %
Size:	system
Technology:	web-application
Tags:	network-infrastructure
Internet:	false
Machine:	virtual
Encryption:	none
Multi-Tenant:	false
Redundant:	false
Custom-Developed:	true
Client by Human:	false
Data Processed:	Bridge firewall permits selecte, Machinery firewall permits sele, Ship core router delivers filte
Data Stored:	none
Formats Accepted:	none of the special data formats accepted

Asset Rating

Owner:	Imported from UML
--------	-------------------

Confidentiality:	restricted	(rated 3 in scale of 5)
Integrity:	important	(rated 3 in scale of 5)
Availability:	important	(rated 3 in scale of 5)
CIA-Justification:	This asset was inferred automatically from the UML model and needs manual CIA review.	

Outgoing Communication Links: 1

Target technical asset names are clickable and link to the corresponding chapter.

Flow 15 (outgoing)

Ship core router delivers filtered OT telemetry to ship IT services.

Target:	Ship IT Server
Protocol:	binary-encrypted
Encrypted:	true
Authentication:	none
Authorization:	technical-user
Read-Only:	false
Usage:	business
Tags:	none
VPN:	false
IP-Filtered:	false
Data Sent:	Ship core router delivers filte
Data Received:	none

Incoming Communication Links: 2

Source technical asset names are clickable and link to the corresponding chapter.

Flow 14 (incoming)

Machinery firewall permits selected machinery telemetry to ship core.

Source:	Machinery Firewall
Protocol:	binary-encrypted
Encrypted:	true
Authentication:	none
Authorization:	none
Read-Only:	false
Usage:	business
Tags:	none

VPN: false
IP-Filtered: false
Data Received: Machinery firewall permits sele
Data Sent: none

Flow 13 (incoming)

Bridge firewall permits selected navigation telemetry to ship core.

Source: Bridge Firewall
Protocol: binary-encrypted
Encrypted: true
Authentication: none
Authorization: none
Read-Only: false
Usage: business
Tags: none
VPN: false
IP-Filtered: false
Data Received: Bridge firewall permits selecte
Data Sent: none

Ship IT Server: 2 / 2 Risks

Description

Imported from UML element 'Ship IT Server' of kind 'service'.

Identified Risks of Asset

Risk finding paragraphs are clickable and link to the corresponding chapter.

Elevated Risk Severity

SQL/NoSQL-Injection risk at **Ship IT Server** against database **Security Log Store** via **Flow 16**: Exploitation likelihood is *Very Likely* with *Medium* impact.

`sql-nosql-injection@ship-it-server@security-log-store@ship-it-server>flow-16`

Unchecked

Medium Risk Severity

Missing Hardening risk at **Ship IT Server**: Exploitation likelihood is *Likely* with *Low* impact.

`missing-hardening@ship-it-server`

Unchecked

Asset Information

ID:	ship-it-server
Type:	process
Usage:	business
RAA:	64 %
Size:	service
Technology:	web-service-rest
Tags:	it-service
Internet:	false
Machine:	virtual
Encryption:	none
Multi-Tenant:	false
Redundant:	false
Custom-Developed:	true
Client by Human:	false
Data Processed:	Identity service provides crew, Ship IT server forwards compres, Ship IT server stores security, Ship core router delivers filte
Data Stored:	none

Formats Accepted: none of the special data formats accepted

Asset Rating

Owner: Imported from UML

Confidentiality: restricted (rated 3 in scale of 5)

Integrity: important (rated 3 in scale of 5)

Availability: important (rated 3 in scale of 5)

CIA-Justification: This asset was inferred automatically from the UML model and needs manual CIA review.

Outgoing Communication Links: 2

Target technical asset names are clickable and link to the corresponding chapter.

Flow 18 (outgoing)

Ship IT server forwards compressed telemetry through satcom.

Target: Satcom Terminal

Protocol: binary-encrypted

Encrypted: true

Authentication: none

Authorization: none

Read-Only: false

Usage: business

Tags: none

VPN: false

IP-Filtered: false

Data Sent: Ship IT server forwards compres

Data Received: none

Flow 16 (outgoing)

Ship IT server stores security events and operational audit records.

Target: Security Log Store

Protocol: binary

Encrypted: false

Authentication: none

Authorization: none

Read-Only: false

Usage:	business
Tags:	none
VPN:	false
IP-Filtered:	false
Data Sent:	Ship IT server stores security
Data Received:	none

Incoming Communication Links: 2

Source technical asset names are clickable and link to the corresponding chapter.

Flow 17 (incoming)

Identity service provides crew and service authentication assertions.

Source:	Ship Identity Service
Protocol:	binary-encrypted
Encrypted:	true
Authentication:	none
Authorization:	enduser-identity-propagation
Read-Only:	false
Usage:	business
Tags:	none
VPN:	false
IP-Filtered:	false
Data Received:	Identity service provides crew
Data Sent:	none

Flow 15 (incoming)

Ship core router delivers filtered OT telemetry to ship IT services.

Source:	Ship Core Router
Protocol:	binary-encrypted
Encrypted:	true
Authentication:	none
Authorization:	technical-user
Read-Only:	false
Usage:	business
Tags:	none
VPN:	false
IP-Filtered:	false

Data Received: Ship core router delivers filte
Data Sent: none

Shore Operations API: 3 / 3 Risks

Description

Imported from UML element 'Shore Operations API' of kind 'cloud'.

Identified Risks of Asset

Risk finding paragraphs are clickable and link to the corresponding chapter.

Elevated Risk Severity

Server-Side Request Forgery (SSRF) risk at **Shore Operations API** server-side web-requesting the target **Maritime Cloud API** via **Flow 21**: Exploitation likelihood is *Likely* with *Medium* impact.

[server-side-request-forgery@shore-operations-api@maritime-cloud-api@shore-operations-api>flow-21](#)

Unchecked

Low Risk Severity

Missing Build Infrastructure in the threat model (referencing asset **Shore Operations API** as an example): Exploitation likelihood is *Unlikely* with *Low* impact.

[missing-build-infrastructure@shore-operations-api](#)

Unchecked

Missing Identity Store in the threat model (referencing asset **Shore Operations API** as an example): Exploitation likelihood is *Unlikely* with *Low* impact.

[missing-identity-store@shore-operations-api](#)

Unchecked

Asset Information

ID:	shore-operations-api
Type:	process
Usage:	business
RAA:	36 %
Size:	system
Technology:	web-service-rest
Tags:	it-service
Internet:	true
Machine:	virtual
Encryption:	none
Multi-Tenant:	false

Redundant: false
Custom-Developed: true
Client by Human: false
Data Processed: Satcom terminal sends telemetry, Shore operations exchanges voya, Shore operator reviews fleet st
Data Stored: none
Formats Accepted: none of the special data formats accepted

Asset Rating

Owner: Imported from UML
Confidentiality: restricted (rated 3 in scale of 5)
Integrity: important (rated 3 in scale of 5)
Availability: important (rated 3 in scale of 5)
CIA-Justification: This asset was inferred automatically from the UML model and needs manual CIA review.

Outgoing Communication Links: 1

Target technical asset names are clickable and link to the corresponding chapter.

Flow 21 (outgoing)

Shore operations exchanges voyage and maintenance summaries with cloud services.

Target: Maritime Cloud API
Protocol: https
Encrypted: true
Authentication: none
Authorization: technical-user
Read-Only: false
Usage: business
Tags: none
VPN: false
IP-Filtered: false
Data Sent: Shore operations exchanges voya
Data Received: none

Incoming Communication Links: 2

Source technical asset names are clickable and link to the corresponding chapter.

Flow 20 (incoming)

Shore operator reviews fleet status and advisory alerts.

Source:	Shore Operator
Protocol:	https
Encrypted:	true
Authentication:	none
Authorization:	enduser-identity-propagation
Read-Only:	false
Usage:	business
Tags:	none
VPN:	false
IP-Filtered:	false
Data Received:	Shore operator reviews fleet st
Data Sent:	none

Flow 19 (incoming)

Satcom terminal sends telemetry to shore operations API.

Source:	Satcom Terminal
Protocol:	binary-encrypted
Encrypted:	true
Authentication:	none
Authorization:	technical-user
Read-Only:	false
Usage:	business
Tags:	none
VPN:	false
IP-Filtered:	false
Data Received:	Satcom terminal sends telemetry
Data Sent:	none

Fleet Data Lake: 2 / 2 Risks

Description

Imported from UML element 'Fleet Data Lake' of kind 'database'.

Identified Risks of Asset

Risk finding paragraphs are clickable and link to the corresponding chapter.

Medium Risk Severity

Missing Hardening risk at **Fleet Data Lake**: Exploitation likelihood is *Likely* with *Low* impact.

[missing-hardening@fleet-data-lake](#)

Unchecked

Low Risk Severity

Missing Network Segmentation to further encapsulate and protect **Fleet Data Lake** against unrelated lower protected assets in the same network segment, which might be easier to compromise by attackers: Exploitation likelihood is *Unlikely* with *Low* impact.

[missing-network-segmentation@fleet-data-lake](#)

Unchecked

Asset Information

ID:	fleet-data-lake
Type:	datastore
Usage:	business
RAA:	58 %
Size:	component
Technology:	database
Tags:	data-store
Internet:	true
Machine:	virtual
Encryption:	transparent
Multi-Tenant:	false
Redundant:	false
Custom-Developed:	false
Client by Human:	false
Data Processed:	Cloud API stores fleet telemetr
Data Stored:	Cloud API stores fleet telemetr

Formats Accepted: none of the special data formats accepted

Asset Rating

Owner:	Imported from UML	
Confidentiality:	restricted	(rated 3 in scale of 5)
Integrity:	important	(rated 3 in scale of 5)
Availability:	important	(rated 3 in scale of 5)
CIA-Justification:	This asset was inferred automatically from the UML model and needs manual CIA review.	

Incoming Communication Links: 1

Source technical asset names are clickable and link to the corresponding chapter.

Flow 22 (incoming)

Cloud API stores fleet telemetry, alerts, and voyage summaries.

Source:	Maritime Cloud API
Protocol:	binary
Encrypted:	false
Authentication:	none
Authorization:	technical-user
Read-Only:	false
Usage:	business
Tags:	none
VPN:	false
IP-Filtered:	false
Data Received:	Cloud API stores fleet telemetr
Data Sent:	none

Security Log Store: 2 / 2 Risks

Description

Imported from UML element 'Security Log Store' of kind 'database'.

Identified Risks of Asset

Risk finding paragraphs are clickable and link to the corresponding chapter.

Medium Risk Severity

Missing Hardening risk at **Security Log Store**: Exploitation likelihood is *Likely* with *Low* impact.

[missing-hardening@security-log-store](#)

Unchecked

Low Risk Severity

Missing Network Segmentation to further encapsulate and protect **Security Log Store** against unrelated lower protected assets in the same network segment, which might be easier to compromise by attackers: Exploitation likelihood is *Unlikely* with *Low* impact.

[missing-network-segmentation@security-log-store](#)

Unchecked

Asset Information

ID:	security-log-store
Type:	datastore
Usage:	business
RAA:	58 %
Size:	component
Technology:	database
Tags:	data-store
Internet:	false
Machine:	virtual
Encryption:	transparent
Multi-Tenant:	false
Redundant:	false
Custom-Developed:	false
Client by Human:	false
Data Processed:	Ship IT server stores security

Data Stored: Ship IT server stores security
Formats Accepted: none of the special data formats accepted

Asset Rating

Owner: Imported from UML
Confidentiality: restricted (rated 3 in scale of 5)
Integrity: important (rated 3 in scale of 5)
Availability: important (rated 3 in scale of 5)
CIA-Justification: This asset was inferred automatically from the UML model and needs manual CIA review.

Incoming Communication Links: 1

Source technical asset names are clickable and link to the corresponding chapter.

Flow 16 (incoming)

Ship IT server stores security events and operational audit records.

Source:	Ship IT Server
Protocol:	binary
Encrypted:	false
Authentication:	none
Authorization:	none
Read-Only:	false
Usage:	business
Tags:	none
VPN:	false
IP-Filtered:	false
Data Received:	Ship IT server stores security
Data Sent:	none

Voyage Data Recorder: 2 / 2 Risks

Description

Imported from UML element 'Voyage Data Recorder' of kind 'database'.

Identified Risks of Asset

Risk finding paragraphs are clickable and link to the corresponding chapter.

Medium Risk Severity

Missing Hardening risk at **Voyage Data Recorder**: Exploitation likelihood is *Likely* with *Low* impact.

[missing-hardening@vdr-recorder](#)

Unchecked

Low Risk Severity

Missing Network Segmentation to further encapsulate and protect **Voyage Data Recorder** against unrelated lower protected assets in the same network segment, which might be easier to compromise by attackers: Exploitation likelihood is *Unlikely* with *Low* impact.

[missing-network-segmentation@vdr-recorder](#)

Unchecked

Asset Information

ID:	vdr-recorder
Type:	datastore
Usage:	business
RAA:	58 %
Size:	component
Technology:	database
Tags:	data-store, operational-technology
Internet:	false
Machine:	virtual
Encryption:	transparent
Multi-Tenant:	false
Redundant:	false
Custom-Developed:	false
Client by Human:	false
Data Processed:	Autopilot records steering mode

Data Stored: Autopilot records steering mode
Formats Accepted: none of the special data formats accepted

Asset Rating

Owner: Imported from UML
Confidentiality: restricted (rated 3 in scale of 5)
Integrity: important (rated 3 in scale of 5)
Availability: important (rated 3 in scale of 5)
CIA-Justification: This asset was inferred automatically from the UML model and needs manual CIA review.

Incoming Communication Links: 1

Source technical asset names are clickable and link to the corresponding chapter.

Flow 6 (incoming)

Autopilot records steering mode, heading commands, and status.

Source: Autopilot Controller
Protocol: binary
Encrypted: false
Authentication: none
Authorization: none
Read-Only: false
Usage: business
Tags: none
VPN: false
IP-Filtered: false
Data Received: Autopilot records steering mode
Data Sent: none

AIS Transceiver: 1 / 1 Risk

Description

Imported from UML element 'AIS Transceiver' of kind 'device'.

Identified Risks of Asset

Risk finding paragraphs are clickable and link to the corresponding chapter.

Low Risk Severity

Missing Vault (Secret Storage) in the threat model (referencing asset **AIS Transceiver** as an example): Exploitation likelihood is *Unlikely* with *Low* impact.

[missing-vault@ais-transceiver](#)

Unchecked

Asset Information

ID:	ais-transceiver
Type:	process
Usage:	business
RAA:	8 %
Size:	component
Technology:	iot-device
Tags:	operational-technology
Internet:	false
Machine:	physical
Encryption:	none
Multi-Tenant:	false
Redundant:	false
Custom-Developed:	false
Client by Human:	false
Data Processed:	AIS transceiver provides vessel
Data Stored:	none
Formats Accepted:	none of the special data formats accepted

Asset Rating

Owner:	Imported from UML
Confidentiality:	restricted (rated 3 in scale of 5)

Integrity:	important	(rated 3 in scale of 5)
Availability:	important	(rated 3 in scale of 5)
CIA-Justification:	This asset was inferred automatically from the UML model and needs manual CIA review.	

Outgoing Communication Links: 1

Target technical asset names are clickable and link to the corresponding chapter.

Flow 4 (outgoing)

AIS transceiver provides vessel identity and target messages.

Target:	ECDIS Workstation
Protocol:	binary
Encrypted:	false
Authentication:	none
Authorization:	enduser-identity-propagation
Read-Only:	false
Usage:	business
Tags:	none
VPN:	false
IP-Filtered:	false
Data Sent:	AIS transceiver provides vessel
Data Received:	none

Bridge Officer: 0 / 0 Risks

Description

Imported from UML element 'Bridge Officer' of kind 'actor'.

Identified Risks of Asset

No risks were identified.

Asset Information

ID:	bridge-officer
Type:	external-entity
Usage:	business
RAA:	8 %
Size:	system
Technology:	client-system
Tags:	human-user
Internet:	false
Machine:	physical
Encryption:	none
Multi-Tenant:	false
Redundant:	false
Custom-Developed:	false
Client by Human:	true
Data Processed:	Bridge officer plans routes and
Data Stored:	none
Formats Accepted:	none of the special data formats accepted

Asset Rating

Owner:	Imported from UML	
Confidentiality:	restricted	(rated 3 in scale of 5)
Integrity:	important	(rated 3 in scale of 5)
Availability:	important	(rated 3 in scale of 5)
CIA-Justification:	This asset was inferred automatically from the UML model and needs manual CIA review.	

Outgoing Communication Links: 1

Target technical asset names are clickable and link to the corresponding chapter.

Flow 1 (outgoing)

Bridge officer plans routes and acknowledges navigation alerts.

Target:	ECDIS Workstation
Protocol:	https
Encrypted:	true
Authentication:	none
Authorization:	none
Read-Only:	false
Usage:	business
Tags:	none
VPN:	false
IP-Filtered:	false
Data Sent:	Bridge officer plans routes and
Data Received:	none

Chief Engineer: 0 / 0 Risks

Description

Imported from UML element 'Chief Engineer' of kind 'actor'.

Identified Risks of Asset

No risks were identified.

Asset Information

ID:	chief-engineer
Type:	external-entity
Usage:	business
RAA:	5 %
Size:	system
Technology:	client-system
Tags:	human-user
Internet:	false
Machine:	physical
Encryption:	none
Multi-Tenant:	false
Redundant:	false
Custom-Developed:	false
Client by Human:	true
Data Processed:	Chief engineer monitors machine
Data Stored:	none
Formats Accepted:	none of the special data formats accepted

Asset Rating

Owner:	Imported from UML	
Confidentiality:	restricted	(rated 3 in scale of 5)
Integrity:	important	(rated 3 in scale of 5)
Availability:	important	(rated 3 in scale of 5)
CIA-Justification:	This asset was inferred automatically from the UML model and needs manual CIA review.	

Outgoing Communication Links: 1

Target technical asset names are clickable and link to the corresponding chapter.

Flow 7 (outgoing)

Chief engineer monitors machinery state and acknowledges alarms.

Target:	Machinery HMI
Protocol:	https
Encrypted:	true
Authentication:	none
Authorization:	none
Read-Only:	false
Usage:	business
Tags:	none
VPN:	false
IP-Filtered:	false
Data Sent:	Chief engineer monitors machine
Data Received:	none

Engine PLC: 0 / 0 Risks

Description

Imported from UML element 'Engine PLC' of kind 'device'.

Identified Risks of Asset

No risks were identified.

Asset Information

ID:	engine-plc
Type:	process
Usage:	business
RAA:	18 %
Size:	component
Technology:	iot-device
Tags:	operational-technology
Internet:	false
Machine:	physical
Encryption:	none
Multi-Tenant:	false
Redundant:	false
Custom-Developed:	false
Client by Human:	false
Data Processed:	Engine PLC publishes load and g, Machinery HMI sends operator-ap
Data Stored:	none
Formats Accepted:	none of the special data formats accepted

Asset Rating

Owner:	Imported from UML
Confidentiality:	restricted (rated 3 in scale of 5)
Integrity:	important (rated 3 in scale of 5)
Availability:	important (rated 3 in scale of 5)
CIA-Justification:	This asset was inferred automatically from the UML model and needs manual CIA review.

Outgoing Communication Links: 1

Target technical asset names are clickable and link to the corresponding chapter.

Flow 9 (outgoing)

Engine PLC publishes load and generator status to power management.

Target:	Power Management System
Protocol:	binary-encrypted
Encrypted:	true
Authentication:	none
Authorization:	none
Read-Only:	false
Usage:	business
Tags:	none
VPN:	false
IP-Filtered:	false
Data Sent:	Engine PLC publishes load and g
Data Received:	none

Incoming Communication Links: 1

Source technical asset names are clickable and link to the corresponding chapter.

Flow 8 (incoming)

Machinery HMI sends operator-approved engine commands.

Source:	Machinery HMI
Protocol:	binary-encrypted
Encrypted:	true
Authentication:	none
Authorization:	enduser-identity-propagation
Read-Only:	false
Usage:	business
Tags:	none
VPN:	false
IP-Filtered:	false
Data Received:	Machinery HMI sends operator-ap
Data Sent:	none

GNSS Receiver: 0 / 0 Risks

Description

Imported from UML element 'GNSS Receiver' of kind 'device'.

Identified Risks of Asset

No risks were identified.

Asset Information

ID:	gnss-receiver
Type:	process
Usage:	business
RAA:	8 %
Size:	component
Technology:	iot-device
Tags:	operational-technology
Internet:	false
Machine:	physical
Encryption:	none
Multi-Tenant:	false
Redundant:	false
Custom-Developed:	false
Client by Human:	false
Data Processed:	GNSS receiver sends position, t
Data Stored:	none
Formats Accepted:	none of the special data formats accepted

Asset Rating

Owner:	Imported from UML	
Confidentiality:	restricted	(rated 3 in scale of 5)
Integrity:	important	(rated 3 in scale of 5)
Availability:	important	(rated 3 in scale of 5)
CIA-Justification:	This asset was inferred automatically from the UML model and needs manual CIA review.	

Outgoing Communication Links: 1

Target technical asset names are clickable and link to the corresponding chapter.

Flow 2 (outgoing)

GNSS receiver sends position, time, and fix quality to ECDIS.

Target:	ECDIS Workstation
Protocol:	binary
Encrypted:	false
Authentication:	none
Authorization:	none
Read-Only:	false
Usage:	business
Tags:	none
VPN:	false
IP-Filtered:	false
Data Sent:	GNSS receiver sends position, t
Data Received:	none

Power Management System: 0 / 0 Risks

Description

Imported from UML element 'Power Management System' of kind 'service'.

Identified Risks of Asset

No risks were identified.

Asset Information

ID:	power-management-system
Type:	process
Usage:	business
RAA:	22 %
Size:	service
Technology:	web-service-rest
Tags:	operational-technology
Internet:	false
Machine:	virtual
Encryption:	none
Multi-Tenant:	false
Redundant:	false
Custom-Developed:	true
Client by Human:	false
Data Processed:	Engine PLC publishes load and g, Power management reports breake
Data Stored:	none
Formats Accepted:	none of the special data formats accepted

Asset Rating

Owner:	Imported from UML	
Confidentiality:	restricted	(rated 3 in scale of 5)
Integrity:	important	(rated 3 in scale of 5)
Availability:	important	(rated 3 in scale of 5)
CIA-Justification:	This asset was inferred automatically from the UML model and needs manual CIA review.	

Outgoing Communication Links: 1

Target technical asset names are clickable and link to the corresponding chapter.

Flow 10 (outgoing)

Power management reports breaker, generator, and load-shed status.

Target:	Machinery HMI
Protocol:	binary-encrypted
Encrypted:	true
Authentication:	none
Authorization:	none
Read-Only:	false
Usage:	business
Tags:	none
VPN:	false
IP-Filtered:	false
Data Sent:	Power management reports breake
Data Received:	none

Incoming Communication Links: 1

Source technical asset names are clickable and link to the corresponding chapter.

Flow 9 (incoming)

Engine PLC publishes load and generator status to power management.

Source:	Engine PLC
Protocol:	binary-encrypted
Encrypted:	true
Authentication:	none
Authorization:	none
Read-Only:	false
Usage:	business
Tags:	none
VPN:	false
IP-Filtered:	false
Data Received:	Engine PLC publishes load and g
Data Sent:	none

Radar Processor: 0 / 0 Risks

Description

Imported from UML element 'Radar Processor' of kind 'device'.

Identified Risks of Asset

No risks were identified.

Asset Information

ID:	radar-processor
Type:	process
Usage:	business
RAA:	8 %
Size:	component
Technology:	iot-device
Tags:	operational-technology
Internet:	false
Machine:	physical
Encryption:	none
Multi-Tenant:	false
Redundant:	false
Custom-Developed:	false
Client by Human:	false
Data Processed:	Radar processor provides target
Data Stored:	none
Formats Accepted:	none of the special data formats accepted

Asset Rating

Owner:	Imported from UML	
Confidentiality:	restricted	(rated 3 in scale of 5)
Integrity:	important	(rated 3 in scale of 5)
Availability:	important	(rated 3 in scale of 5)
CIA-Justification:	This asset was inferred automatically from the UML model and needs manual CIA review.	

Outgoing Communication Links: 1

Target technical asset names are clickable and link to the corresponding chapter.

Flow 3 (outgoing)

Radar processor provides target overlays and radar tracks.

Target:	ECDIS Workstation
Protocol:	binary
Encrypted:	false
Authentication:	none
Authorization:	none
Read-Only:	false
Usage:	business
Tags:	none
VPN:	false
IP-Filtered:	false
Data Sent:	Radar processor provides target
Data Received:	none

Satcom Terminal: 0 / 0 Risks

Description

Imported from UML element 'Satcom Terminal' of kind 'device'.

Identified Risks of Asset

No risks were identified.

Asset Information

ID:	satcom-terminal
Type:	process
Usage:	business
RAA:	20 %
Size:	component
Technology:	iot-device
Tags:	network-infrastructure
Internet:	false
Machine:	physical
Encryption:	none
Multi-Tenant:	false
Redundant:	false
Custom-Developed:	false
Client by Human:	false
Data Processed:	Satcom terminal sends telemetry, Ship IT server forwards compres
Data Stored:	none
Formats Accepted:	none of the special data formats accepted

Asset Rating

Owner:	Imported from UML	
Confidentiality:	restricted	(rated 3 in scale of 5)
Integrity:	important	(rated 3 in scale of 5)
Availability:	important	(rated 3 in scale of 5)
CIA-Justification:	This asset was inferred automatically from the UML model and needs manual CIA review.	

Outgoing Communication Links: 1

Target technical asset names are clickable and link to the corresponding chapter.

Flow 19 (outgoing)

Satcom terminal sends telemetry to shore operations API.

Target:	Shore Operations API
Protocol:	binary-encrypted
Encrypted:	true
Authentication:	none
Authorization:	technical-user
Read-Only:	false
Usage:	business
Tags:	none
VPN:	false
IP-Filtered:	false
Data Sent:	Satcom terminal sends telemetry
Data Received:	none

Incoming Communication Links: 1

Source technical asset names are clickable and link to the corresponding chapter.

Flow 18 (incoming)

Ship IT server forwards compressed telemetry through satcom.

Source:	Ship IT Server
Protocol:	binary-encrypted
Encrypted:	true
Authentication:	none
Authorization:	none
Read-Only:	false
Usage:	business
Tags:	none
VPN:	false
IP-Filtered:	false
Data Received:	Ship IT server forwards compres
Data Sent:	none

Ship Identity Service: 0 / 0 Risks

Description

Imported from UML element 'Ship Identity Service' of kind 'service'.

Identified Risks of Asset

No risks were identified.

Asset Information

ID:	ship-identity-service
Type:	process
Usage:	business
RAA:	5 %
Size:	service
Technology:	web-service-rest
Tags:	it-service
Internet:	false
Machine:	virtual
Encryption:	none
Multi-Tenant:	false
Redundant:	false
Custom-Developed:	true
Client by Human:	false
Data Processed:	Identity service provides crew
Data Stored:	none
Formats Accepted:	none of the special data formats accepted

Asset Rating

Owner:	Imported from UML	
Confidentiality:	restricted	(rated 3 in scale of 5)
Integrity:	important	(rated 3 in scale of 5)
Availability:	important	(rated 3 in scale of 5)
CIA-Justification:	This asset was inferred automatically from the UML model and needs manual CIA review.	

Outgoing Communication Links: 1

Target technical asset names are clickable and link to the corresponding chapter.

Flow 17 (outgoing)

Identity service provides crew and service authentication assertions.

Target:	Ship IT Server
Protocol:	binary-encrypted
Encrypted:	true
Authentication:	none
Authorization:	enduser-identity-propagation
Read-Only:	false
Usage:	business
Tags:	none
VPN:	false
IP-Filtered:	false
Data Sent:	Identity service provides crew
Data Received:	none

Shore Operator: 0 / 0 Risks

Description

Imported from UML element 'Shore Operator' of kind 'actor'.

Identified Risks of Asset

No risks were identified.

Asset Information

ID:	shore-operator
Type:	external-entity
Usage:	business
RAA:	3 %
Size:	system
Technology:	client-system
Tags:	human-user
Internet:	true
Machine:	physical
Encryption:	none
Multi-Tenant:	false
Redundant:	false
Custom-Developed:	false
Client by Human:	true
Data Processed:	Shore operator reviews fleet st
Data Stored:	none
Formats Accepted:	none of the special data formats accepted

Asset Rating

Owner:	Imported from UML	
Confidentiality:	restricted	(rated 3 in scale of 5)
Integrity:	important	(rated 3 in scale of 5)
Availability:	important	(rated 3 in scale of 5)
CIA-Justification:	This asset was inferred automatically from the UML model and needs manual CIA review.	

Outgoing Communication Links: 1

Target technical asset names are clickable and link to the corresponding chapter.

Flow 20 (outgoing)

Shore operator reviews fleet status and advisory alerts.

Target:	Shore Operations API
Protocol:	https
Encrypted:	true
Authentication:	none
Authorization:	enduser-identity-propagation
Read-Only:	false
Usage:	business
Tags:	none
VPN:	false
IP-Filtered:	false
Data Sent:	Shore operator reviews fleet st
Data Received:	none

Identified Data Breach Probabilities by Data Asset

In total **24 potential risks** have been identified during the threat modeling process of which **0 are rated as critical, 0 as high, 9 as elevated, 9 as medium, and 6 as low.**

These risks are distributed across **22 data assets**. The following sub-chapters of this section describe the derived data breach probabilities grouped by data asset.

Technical asset names and risk IDs are clickable and link to the corresponding chapter.

Autopilot records steering mode: 3 / 3 Risks

Inferred from the data flow between Autopilot Controller and Voyage Data Recorder.

ID:	flow-data-6	
Usage:	business	
Quantity:	many	
Tags:	none	
Origin:	Autopilot Controller	
Owner:	Voyage Data Recorder	
Confidentiality:	restricted	(rated 3 in scale of 5)
Integrity:	important	(rated 3 in scale of 5)
Availability:	important	(rated 3 in scale of 5)
CIA-Justification:	This data asset was inferred automatically from a UML flow and needs manual refinement.	
Processed by:	Autopilot Controller, Voyage Data Recorder	
Stored by:	Voyage Data Recorder	
Sent via:	Flow 6	
Received via:	none	
Data Breach:	probable	
Data Breach Risks:	This data asset has data breach potential because of 3 remaining risks:	

Probable: `sql-nosql-injection@autopilot-controller@vdr-recorder@autopilot-controller>flow-6`

Improbable: `missing-hardening@vdr-recorder`

Improbable: `missing-network-segmentation@vdr-recorder`

Cloud API stores fleet telemetr: 5 / 5 Risks

Inferred from the data flow between Maritime Cloud API and Fleet Data Lake.

ID:	flow-data-22	
Usage:	business	
Quantity:	many	
Tags:	none	
Origin:	Maritime Cloud API	
Owner:	Fleet Data Lake	
Confidentiality:	restricted	(rated 3 in scale of 5)
Integrity:	important	(rated 3 in scale of 5)
Availability:	important	(rated 3 in scale of 5)
CIA-Justification:	This data asset was inferred automatically from a UML flow and needs manual refinement.	
Processed by:	Fleet Data Lake, Maritime Cloud API	
Stored by:	Fleet Data Lake	
Sent via:	Flow 22	
Received via:	none	
Data Breach:	probable	
Data Breach Risks:	This data asset has data breach potential because of 5 remaining risks:	
	Probable: missing-cloud-hardening@shore-cloud-zone	
	Probable: sql-nosql-injection@maritime-cloud-api@fleet-data-lake@maritime-cloud-api>flow-22	
	Possible: server-side-request-forgery@shore-operations-api@maritime-cloud-api@shore-operations-api>flow-21	
	Improbable: missing-hardening@fleet-data-lake	
	Improbable: missing-network-segmentation@fleet-data-lake	

Satcom terminal sends telemetry: 2 / 2 Risks

Inferred from the data flow between Satcom Terminal and Shore Operations API.

ID:	flow-data-19	
Usage:	business	
Quantity:	many	
Tags:	none	
Origin:	Satcom Terminal	
Owner:	Shore Operations API	
Confidentiality:	restricted	(rated 3 in scale of 5)
Integrity:	important	(rated 3 in scale of 5)
Availability:	important	(rated 3 in scale of 5)
CIA-Justification:	This data asset was inferred automatically from a UML flow and needs manual refinement.	
Processed by:	Satcom Terminal, Shore Operations API	
Stored by:	none	
Sent via:	Flow 19	
Received via:	none	
Data Breach:	probable	
Data Breach Risks:	This data asset has data breach potential because of 2 remaining risks:	

Probable: missing-cloud-hardening@shore-cloud-zone

Possible: server-side-request-forgery@shore-operations-api@maritime-cloud-api@shore-operations-api>flow-21

Ship IT server stores security: 4 / 4 Risks

Inferred from the data flow between Ship IT Server and Security Log Store.

ID:	flow-data-16	
Usage:	business	
Quantity:	many	
Tags:	none	
Origin:	Ship IT Server	
Owner:	Security Log Store	
Confidentiality:	restricted	(rated 3 in scale of 5)
Integrity:	important	(rated 3 in scale of 5)
Availability:	important	(rated 3 in scale of 5)
CIA-Justification:	This data asset was inferred automatically from a UML flow and needs manual refinement.	
Processed by:	Security Log Store, Ship IT Server	
Stored by:	Security Log Store	
Sent via:	Flow 16	
Received via:	none	
Data Breach:	probable	
Data Breach Risks:	This data asset has data breach potential because of 4 remaining risks:	
	Probable: sql-nosql-injection@ship-it-server@security-log-store@ship-it-server>flow-16	
	Improbable: missing-hardening@security-log-store	
	Improbable: missing-hardening@ship-it-server	
	Improbable: missing-network-segmentation@security-log-store	

Shore operations exchanges voya: 2 / 2 Risks

Inferred from the data flow between Shore Operations API and Maritime Cloud API.

ID:	flow-data-21	
Usage:	business	
Quantity:	many	
Tags:	none	
Origin:	Shore Operations API	
Owner:	Maritime Cloud API	
Confidentiality:	restricted	(rated 3 in scale of 5)
Integrity:	important	(rated 3 in scale of 5)
Availability:	important	(rated 3 in scale of 5)
CIA-Justification:	This data asset was inferred automatically from a UML flow and needs manual refinement.	
Processed by:	Maritime Cloud API, Shore Operations API	
Stored by:	none	
Sent via:	Flow 21	
Received via:	none	
Data Breach:	probable	
Data Breach Risks:	This data asset has data breach potential because of 2 remaining risks:	

Probable: missing-cloud-hardening@shore-cloud-zone

Possible: server-side-request-forgery@shore-operations-api@maritime-cloud-api@shore-operations-api>flow-21

Shore operator reviews fleet st: 2 / 2 Risks

Inferred from the data flow between Shore Operator and Shore Operations API.

ID:	flow-data-20
Usage:	business
Quantity:	many
Tags:	none
Origin:	Shore Operator
Owner:	Shore Operations API
Confidentiality:	restricted (rated 3 in scale of 5)
Integrity:	important (rated 3 in scale of 5)
Availability:	important (rated 3 in scale of 5)
CIA-Justification:	This data asset was inferred automatically from a UML flow and needs manual refinement.
Processed by:	Shore Operations API, Shore Operator
Stored by:	none
Sent via:	Flow 20
Received via:	none
Data Breach:	probable
Data Breach Risks:	This data asset has data breach potential because of 2 remaining risks:

Probable: missing-cloud-hardening@shore-cloud-zone

Possible: server-side-request-forgery@shore-operations-api@maritime-cloud-api@shore-operations-api>flow-21

AIS transceiver provides vessel: 3 / 3 Risks

Inferred from the data flow between AIS Transceiver and ECDIS Workstation.

ID:	flow-data-4	
Usage:	business	
Quantity:	many	
Tags:	none	
Origin:	AIS Transceiver	
Owner:	ECDIS Workstation	
Confidentiality:	restricted	(rated 3 in scale of 5)
Integrity:	important	(rated 3 in scale of 5)
Availability:	important	(rated 3 in scale of 5)
CIA-Justification:	This data asset was inferred automatically from a UML flow and needs manual refinement.	
Processed by:	AIS Transceiver, ECDIS Workstation	
Stored by:	none	
Sent via:	Flow 4	
Received via:	none	
Data Breach:	possible	
Data Breach Risks:	This data asset has data breach potential because of 3 remaining risks:	

Possible: cross-site-scripting@ecdis-workstation

Improbable: cross-site-request-forgery@ecdis-workstation@bridge-officer>flow-1

Improbable: missing-hardening@ecdis-workstation

Bridge firewall permits selecte: 2 / 2 Risks

Inferred from the data flow between Bridge Firewall and Ship Core Router.

ID:	flow-data-13	
Usage:	business	
Quantity:	many	
Tags:	none	
Origin:	Bridge Firewall	
Owner:	Ship Core Router	
Confidentiality:	restricted	(rated 3 in scale of 5)
Integrity:	important	(rated 3 in scale of 5)
Availability:	important	(rated 3 in scale of 5)
CIA-Justification:	This data asset was inferred automatically from a UML flow and needs manual refinement.	
Processed by:	Bridge Firewall, Ship Core Router	
Stored by:	none	
Sent via:	Flow 13	
Received via:	none	
Data Breach:	possible	
Data Breach Risks:	This data asset has data breach potential because of 2 remaining risks:	
	Possible: cross-site-scripting@bridge-firewall	
	Possible: cross-site-scripting@ship-core-router	

Bridge officer plans routes and: 3 / 3 Risks

Inferred from the data flow between Bridge Officer and ECDIS Workstation.

ID: flow-data-1
Usage: business
Quantity: many
Tags: none
Origin: Bridge Officer
Owner: ECDIS Workstation
Confidentiality: restricted (rated 3 in scale of 5)
Integrity: important (rated 3 in scale of 5)
Availability: important (rated 3 in scale of 5)
CIA-Justification: This data asset was inferred automatically from a UML flow and needs manual refinement.
Processed by: Bridge Officer, ECDIS Workstation
Stored by: none
Sent via: Flow 1
Received via: none
Data Breach: **possible**
Data Breach Risks: This data asset has data breach potential because of 3 remaining risks:

Possible: cross-site-scripting@ecdis-workstation

Improbable: cross-site-request-forgery@ecdis-workstation@bridge-officer>flow-1

Improbable: missing-hardening@ecdis-workstation

Chief engineer monitors machine: 3 / 3 Risks

Inferred from the data flow between Chief Engineer and Machinery HMI.

ID:	flow-data-7	
Usage:	business	
Quantity:	many	
Tags:	none	
Origin:	Chief Engineer	
Owner:	Machinery HMI	
Confidentiality:	restricted	(rated 3 in scale of 5)
Integrity:	important	(rated 3 in scale of 5)
Availability:	important	(rated 3 in scale of 5)
CIA-Justification:	This data asset was inferred automatically from a UML flow and needs manual refinement.	
Processed by:	Chief Engineer, Machinery HMI	
Stored by:	none	
Sent via:	Flow 7	
Received via:	none	
Data Breach:	possible	
Data Breach Risks:	This data asset has data breach potential because of 3 remaining risks:	

Possible: cross-site-scripting@machinery-hmi

Improbable: cross-site-request-forgery@machinery-hmi@chief-engineer>flow-7

Improbable: missing-hardening@machinery-hmi

ECDIS forwards approved voyage: 4 / 4 Risks

Inferred from the data flow between ECDIS Workstation and Bridge Firewall.

ID:	flow-data-11		
Usage:	business		
Quantity:	many		
Tags:	none		
Origin:	ECDIS Workstation		
Owner:	Bridge Firewall		
Confidentiality:	restricted	(rated 3 in scale of 5)	
Integrity:	important	(rated 3 in scale of 5)	
Availability:	important	(rated 3 in scale of 5)	
CIA-Justification:	This data asset was inferred automatically from a UML flow and needs manual refinement.		
Processed by:	Bridge Firewall, ECDIS Workstation		
Stored by:	none		
Sent via:	Flow 11		
Received via:	none		
Data Breach:	possible		
Data Breach Risks:	This data asset has data breach potential because of 4 remaining risks:		
	Possible: cross-site-scripting@bridge-firewall		
	Possible: cross-site-scripting@ecdis-workstation		
	Improbable: cross-site-request-forgery@ecdis-workstation@bridge-officer>flow-1		
	Improbable: missing-hardening@ecdis-workstation		

ECDIS sends approved waypoint a: 3 / 3 Risks

Inferred from the data flow between ECDIS Workstation and Autopilot Controller.

ID:	flow-data-5	
Usage:	business	
Quantity:	many	
Tags:	none	
Origin:	ECDIS Workstation	
Owner:	Autopilot Controller	
Confidentiality:	restricted	(rated 3 in scale of 5)
Integrity:	important	(rated 3 in scale of 5)
Availability:	important	(rated 3 in scale of 5)
CIA-Justification:	This data asset was inferred automatically from a UML flow and needs manual refinement.	
Processed by:	Autopilot Controller, ECDIS Workstation	
Stored by:	none	
Sent via:	Flow 5	
Received via:	none	
Data Breach:	possible	
Data Breach Risks:	This data asset has data breach potential because of 3 remaining risks:	

Possible: cross-site-scripting@ecdis-workstation

Improbable: cross-site-request-forgery@ecdis-workstation@bridge-officer>flow-1

Improbable: missing-hardening@ecdis-workstation

GNSS receiver sends position, t: 3 / 3 Risks

Inferred from the data flow between GNSS Receiver and ECDIS Workstation.

ID:	flow-data-2	
Usage:	business	
Quantity:	many	
Tags:	none	
Origin:	GNSS Receiver	
Owner:	ECDIS Workstation	
Confidentiality:	restricted	(rated 3 in scale of 5)
Integrity:	important	(rated 3 in scale of 5)
Availability:	important	(rated 3 in scale of 5)
CIA-Justification:	This data asset was inferred automatically from a UML flow and needs manual refinement.	
Processed by:	ECDIS Workstation, GNSS Receiver	
Stored by:	none	
Sent via:	Flow 2	
Received via:	none	
Data Breach:	possible	
Data Breach Risks:	This data asset has data breach potential because of 3 remaining risks:	

Possible: cross-site-scripting@ecdis-workstation

Improbable: cross-site-request-forgery@ecdis-workstation@bridge-officer>flow-1

Improbable: missing-hardening@ecdis-workstation

Machinery HMI forwards selected: 4 / 4 Risks

Inferred from the data flow between Machinery HMI and Machinery Firewall.

ID:	flow-data-12	
Usage:	business	
Quantity:	many	
Tags:	none	
Origin:	Machinery HMI	
Owner:	Machinery Firewall	
Confidentiality:	restricted	(rated 3 in scale of 5)
Integrity:	important	(rated 3 in scale of 5)
Availability:	important	(rated 3 in scale of 5)
CIA-Justification:	This data asset was inferred automatically from a UML flow and needs manual refinement.	
Processed by:	Machinery Firewall, Machinery HMI	
Stored by:	none	
Sent via:	Flow 12	
Received via:	none	
Data Breach:	possible	
Data Breach Risks:	This data asset has data breach potential because of 4 remaining risks:	
	Possible: cross-site-scripting@machinery-firewall	
	Possible: cross-site-scripting@machinery-hmi	
	Improbable: cross-site-request-forgery@machinery-hmi@chief-engineer>flow-7	
	Improbable: missing-hardening@machinery-hmi	

Machinery HMI sends operator-ap: 3 / 3 Risks

Inferred from the data flow between Machinery HMI and Engine PLC.

ID:	flow-data-8	
Usage:	business	
Quantity:	many	
Tags:	none	
Origin:	Machinery HMI	
Owner:	Engine PLC	
Confidentiality:	restricted	(rated 3 in scale of 5)
Integrity:	important	(rated 3 in scale of 5)
Availability:	important	(rated 3 in scale of 5)
CIA-Justification:	This data asset was inferred automatically from a UML flow and needs manual refinement.	
Processed by:	Engine PLC, Machinery HMI	
Stored by:	none	
Sent via:	Flow 8	
Received via:	none	
Data Breach:	possible	
Data Breach Risks:	This data asset has data breach potential because of 3 remaining risks:	

Possible: cross-site-scripting@machinery-hmi

Improbable: cross-site-request-forgery@machinery-hmi@chief-engineer>flow-7

Improbable: missing-hardening@machinery-hmi

Machinery firewall permits sele: 2 / 2 Risks

Inferred from the data flow between Machinery Firewall and Ship Core Router.

ID:	flow-data-14	
Usage:	business	
Quantity:	many	
Tags:	none	
Origin:	Machinery Firewall	
Owner:	Ship Core Router	
Confidentiality:	restricted	(rated 3 in scale of 5)
Integrity:	important	(rated 3 in scale of 5)
Availability:	important	(rated 3 in scale of 5)
CIA-Justification:	This data asset was inferred automatically from a UML flow and needs manual refinement.	
Processed by:	Machinery Firewall, Ship Core Router	
Stored by:	none	
Sent via:	Flow 14	
Received via:	none	
Data Breach:	possible	
Data Breach Risks:	This data asset has data breach potential because of 2 remaining risks:	
	Possible: cross-site-scripting@machinery-firewall	
	Possible: cross-site-scripting@ship-core-router	

Power management reports breake: 3 / 3 Risks

Inferred from the data flow between Power Management System and Machinery HMI.

ID:	flow-data-10	
Usage:	business	
Quantity:	many	
Tags:	none	
Origin:	Power Management System	
Owner:	Machinery HMI	
Confidentiality:	restricted	(rated 3 in scale of 5)
Integrity:	important	(rated 3 in scale of 5)
Availability:	important	(rated 3 in scale of 5)
CIA-Justification:	This data asset was inferred automatically from a UML flow and needs manual refinement.	
Processed by:	Machinery HMI, Power Management System	
Stored by:	none	
Sent via:	Flow 10	
Received via:	none	
Data Breach:	possible	
Data Breach Risks:	This data asset has data breach potential because of 3 remaining risks:	

Possible: cross-site-scripting@machinery-hmi

Improbable: cross-site-request-forgery@machinery-hmi@chief-engineer>flow-7

Improbable: missing-hardening@machinery-hmi

Radar processor provides target: 3 / 3 Risks

Inferred from the data flow between Radar Processor and ECDIS Workstation.

ID:	flow-data-3	
Usage:	business	
Quantity:	many	
Tags:	none	
Origin:	Radar Processor	
Owner:	ECDIS Workstation	
Confidentiality:	restricted	(rated 3 in scale of 5)
Integrity:	important	(rated 3 in scale of 5)
Availability:	important	(rated 3 in scale of 5)
CIA-Justification:	This data asset was inferred automatically from a UML flow and needs manual refinement.	
Processed by:	ECDIS Workstation, Radar Processor	
Stored by:	none	
Sent via:	Flow 3	
Received via:	none	
Data Breach:	possible	
Data Breach Risks:	This data asset has data breach potential because of 3 remaining risks:	

Possible: cross-site-scripting@ecdis-workstation

Improbable: cross-site-request-forgery@ecdis-workstation@bridge-officer>flow-1

Improbable: missing-hardening@ecdis-workstation

Ship core router delivers filter: 2 / 2 Risks

Inferred from the data flow between Ship Core Router and Ship IT Server.

ID:	flow-data-15	
Usage:	business	
Quantity:	many	
Tags:	none	
Origin:	Ship Core Router	
Owner:	Ship IT Server	
Confidentiality:	restricted	(rated 3 in scale of 5)
Integrity:	important	(rated 3 in scale of 5)
Availability:	important	(rated 3 in scale of 5)
CIA-Justification:	This data asset was inferred automatically from a UML flow and needs manual refinement.	
Processed by:	Ship Core Router, Ship IT Server	
Stored by:	none	
Sent via:	Flow 15	
Received via:	none	
Data Breach:	possible	
Data Breach Risks:	This data asset has data breach potential because of 2 remaining risks:	
	Possible: cross-site-scripting@ship-core-router	
	Improbable: missing-hardening@ship-it-server	

Identity service provides crew: 1 / 1 Risk

Inferred from the data flow between Ship Identity Service and Ship IT Server.

ID:	flow-data-17	
Usage:	business	
Quantity:	many	
Tags:	none	
Origin:	Ship Identity Service	
Owner:	Ship IT Server	
Confidentiality:	restricted	(rated 3 in scale of 5)
Integrity:	important	(rated 3 in scale of 5)
Availability:	important	(rated 3 in scale of 5)
CIA-Justification:	This data asset was inferred automatically from a UML flow and needs manual refinement.	
Processed by:	Ship IT Server, Ship Identity Service	
Stored by:	none	
Sent via:	Flow 17	
Received via:	none	
Data Breach:	improbable	
Data Breach Risks:	This data asset has data breach potential because of 1 remaining risk:	

Improbable: missing-hardening@ship-it-server

Ship IT server forwards compres: 1 / 1 Risk

Inferred from the data flow between Ship IT Server and Satcom Terminal.

ID:	flow-data-18	
Usage:	business	
Quantity:	many	
Tags:	none	
Origin:	Ship IT Server	
Owner:	Satcom Terminal	
Confidentiality:	restricted	(rated 3 in scale of 5)
Integrity:	important	(rated 3 in scale of 5)
Availability:	important	(rated 3 in scale of 5)
CIA-Justification:	This data asset was inferred automatically from a UML flow and needs manual refinement.	
Processed by:	Satcom Terminal, Ship IT Server	
Stored by:	none	
Sent via:	Flow 18	
Received via:	none	
Data Breach:	improbable	
Data Breach Risks:	This data asset has data breach potential because of 1 remaining risk:	

Improbable: missing-hardening@ship-it-server

Engine PLC publishes load and g: 0 / 0 Risks

Inferred from the data flow between Engine PLC and Power Management System.

ID:	flow-data-9	
Usage:	business	
Quantity:	many	
Tags:	none	
Origin:	Engine PLC	
Owner:	Power Management System	
Confidentiality:	restricted	(rated 3 in scale of 5)
Integrity:	important	(rated 3 in scale of 5)
Availability:	important	(rated 3 in scale of 5)
CIA-Justification:	This data asset was inferred automatically from a UML flow and needs manual refinement.	
Processed by:	Engine PLC, Power Management System	
Stored by:	none	
Sent via:	Flow 9	
Received via:	none	
Data Breach:	none	
Data Breach Risks:	This data asset has no data breach potential.	

Trust Boundaries

In total **7 trust boundaries** have been modeled during the threat modeling process.

Bridge OT Zone

Bridge OT Zone

ID: bridge-ot-zone
Type: [network-on-prem](#)
Tags: none
Assets inside: AIS Transceiver, Autopilot Controller, Bridge Firewall, Bridge Officer, ECDIS Workstation, GNSS Receiver, Radar Processor, Voyage Data Recorder
Boundaries nested: none

Machinery OT Zone

Machinery OT Zone

ID: machinery-ot-zone
Type: [network-on-prem](#)
Tags: none
Assets inside: Chief Engineer, Engine PLC, Machinery Firewall, Machinery HMI, Power Management System
Boundaries nested: none

Satcom DMZ

Satcom DMZ

ID: satcom-dmz
Type: [network-on-prem](#)
Tags: none
Assets inside: Satcom Terminal
Boundaries nested: none

Ship Core Network Zone

Ship Core Network Zone

ID: ship-core-network-zone

Type: [network-on-prem](#)
Tags: none
Assets inside: Ship Core Router
Boundaries nested: Bridge OT Zone, Machinery OT Zone

Ship IT Zone

Ship IT Zone

ID: ship-it-zone
Type: [network-on-prem](#)
Tags: none
Assets inside: Security Log Store, Ship Identity Service, Ship IT Server
Boundaries nested: none

Shore Cloud Zone

Shore Cloud Zone

ID: shore-cloud-zone
Type: [network-cloud-provider](#)
Tags: none
Assets inside: Fleet Data Lake, Maritime Cloud API, Shore Operations API, Shore Operator
Boundaries nested: none

Vessel Exterior Zone

Vessel Exterior Zone

ID: vessel-exterior-zone
Type: [network-on-prem](#)
Tags: none
Assets inside: none
Boundaries nested: Bridge OT Zone

Shared Runtimes

In total **0 shared runtime** has been modeled during the threat modeling process.

Risk Rules Checked by Threagile

Threagile Version: 1.0.0

Threagile Build Timestamp: 20240730113903

Threagile Execution Timestamp: 20260529105903

Model Filename: /dev/shm/threagile-input-3364084124/threagile-model-1422835535

Model Hash (SHA256): 3211f037062e35fde1c3037c5d7302e4936091a131142b96927409f4236cb5f9

Threagile (see <https://threagile.io> for more details) is an open-source toolkit for agile threat modeling, created by Christian Schneider (<https://christian-schneider.net>): It allows to model an architecture with its assets in an agile fashion as a YAML file directly inside the IDE. Upon execution of the Threagile toolkit all standard risk rules (as well as individual custom rules if present) are checked against the architecture model. At the time the Threagile toolkit was executed on the model input file the following risk rules were checked:

Accidental Secret Leak

accidental-secret-leak

STRIDE: Information Disclosure

Description: Sourcecode repositories (including their histories) as well as artifact registries can accidentally contain secrets like checked-in or packaged-in passwords, API tokens, certificates, crypto keys, etc.

Detection: In-scope sourcecode repositories and artifact registries.

Rating: The risk rating depends on the sensitivity of the technical asset itself and of the data assets processed and stored.

Code Backdooring

code-backdooring

STRIDE: Tampering

Description: For each build-pipeline component Code Backdooring risks might arise where attackers compromise the build-pipeline in order to let backdoored artifacts be shipped into production. Aside from direct code backdooring this includes backdooring of dependencies and even of more lower-level build infrastructure, like backdooring compilers (similar to what the XcodeGhost malware did) or dependencies.

Detection: In-scope development relevant technical assets which are either accessed by out-of-scope unmanaged developer clients and/or are directly accessed by any kind of internet-located (non-VPN) component or are themselves directly located on the internet.

Rating: The risk rating depends on the confidentiality and integrity rating of the code being handled and deployed as well as the placement/calling of this technical asset on/from the internet.

Container Base Image Backdooring

container-baseimage-backdooring

STRIDE: Tampering

Description: When a technical asset is built using container technologies, Base Image Backdooring risks might arise where base images and other layers used contain vulnerable components or backdoors.

Detection: In-scope technical assets running as containers.

Rating: The risk rating depends on the sensitivity of the technical asset itself and of the data assets.

Container Platform Escape

container-platform-escape

STRIDE: Elevation of Privilege

Description: Container platforms are especially interesting targets for attackers as they host big parts of a containerized runtime infrastructure. When not configured and operated with security best practices in mind, attackers might exploit a vulnerability inside an container and escape towards the platform as highly privileged users. These scenarios might give attackers capabilities to attack every other container as owning the container platform (via container escape attacks) equals to owning every container.

Detection: In-scope container platforms.

Rating: The risk rating depends on the sensitivity of the technical asset itself and of the data assets processed and stored.

Cross-Site Request Forgery (CSRF)

cross-site-request-forgery

STRIDE: Spoofing

Description: When a web application is accessed via web protocols Cross-Site Request Forgery (CSRF) risks might arise.

Detection: In-scope web applications accessed via typical web access protocols.

Rating: The risk rating depends on the integrity rating of the data sent across the communication link.

Cross-Site Scripting (XSS)

cross-site-scripting

STRIDE: Tampering

Description: For each web application Cross-Site Scripting (XSS) risks might arise. In terms of the overall risk level take other applications running on the same domain into account as well.

Detection: In-scope web applications.

Rating: The risk rating depends on the sensitivity of the data processed or stored in the web application.

DoS-risky Access Across Trust-Boundary

dos-risky-access-across-trust-boundary

STRIDE: Denial of Service

Description: Assets accessed across trust boundaries with critical or mission-critical availability rating are more prone to Denial-of-Service (DoS) risks.

Detection: In-scope technical assets (excluding load-balancer) with availability rating of critical or higher which have incoming data-flows across a network trust-boundary (excluding devops usage).

Rating: Matching technical assets with availability rating of critical or higher are at low risk. When the availability rating is mission-critical and neither a VPN nor IP filter for the incoming data-flow nor redundancy for the asset is applied, the risk-rating is considered medium.

Incomplete Model**incomplete-model**

STRIDE: Information Disclosure

Description: When the threat model contains unknown technologies or transfers data over unknown protocols, this is an indicator for an incomplete model.

Detection: All technical assets and communication links with technology type or protocol type specified as unknown.

Rating: low

LDAP-Injection**ldap-injection**

STRIDE: Tampering

Description: When an LDAP server is accessed LDAP-Injection risks might arise. The risk rating depends on the sensitivity of the LDAP server itself and of the data assets processed or stored.

Detection: In-scope clients accessing LDAP servers via typical LDAP access protocols.

Rating: The risk rating depends on the sensitivity of the LDAP server itself and of the data assets processed or stored.

Missing Authentication**missing-authentication**

STRIDE: Elevation of Privilege

Description: Technical assets (especially multi-tenant systems) should authenticate incoming requests when the asset processes or stores sensitive data.

Detection: In-scope technical assets (except load-balancer, reverse-proxy, service-registry, waf, ids, and ips and in-process calls) should authenticate incoming requests when the asset processes or stores sensitive data. This is especially the case for all multi-tenant assets (there even non-sensitive ones).

Rating: The risk rating (medium or high) depends on the sensitivity of the data sent across

the communication link. Monitoring callers are exempted from this risk.

Missing Two-Factor Authentication (2FA)

missing-authentication-second-factor

STRIDE: Elevation of Privilege

Description: Technical assets (especially multi-tenant systems) should authenticate incoming requests with two-factor (2FA) authentication when the asset processes or stores highly sensitive data (in terms of confidentiality, integrity, and availability) and is accessed by humans.

Detection: In-scope technical assets (except load-balancer, reverse-proxy, waf, ids, and ips) should authenticate incoming requests via two-factor authentication (2FA) when the asset processes or stores highly sensitive data (in terms of confidentiality, integrity, and availability) and is accessed by a client used by a human user.

Rating: medium

Missing Build Infrastructure

missing-build-infrastructure

STRIDE: Tampering

Description: The modeled architecture does not contain a build infrastructure (devops-client, sourcecode-repo, build-pipeline, etc.), which might be the risk of a model missing critical assets (and thus not seeing their risks). If the architecture contains custom-developed parts, the pipeline where code gets developed and built needs to be part of the model.

Detection: Models with in-scope custom-developed parts missing in-scope development (code creation) and build infrastructure components (devops-client, sourcecode-repo, build-pipeline, etc.).

Rating: The risk rating depends on the highest sensitivity of the in-scope assets running custom-developed parts.

Missing Cloud Hardening

missing-cloud-hardening

STRIDE: Tampering

Description: Cloud components should be hardened according to the cloud vendor best practices. This affects their configuration, auditing, and further areas.

Detection: In-scope cloud components (either residing in cloud trust boundaries or more specifically tagged with cloud provider types).

Rating: The risk rating depends on the sensitivity of the technical asset itself and of the data assets processed and stored.

Missing File Validation

missing-file-validation

STRIDE: Spoofing

- Description:** When a technical asset accepts files, these input files should be strictly validated about filename and type.
- Detection:** In-scope technical assets with custom-developed code accepting file data formats.
- Rating:** The risk rating depends on the sensitivity of the technical asset itself and of the data assets processed and stored.

Missing Hardening

missing-hardening

- STRIDE:** Tampering
- Description:** Technical assets with a Relative Attacker Attractiveness (RAA) value of 55 % or higher should be explicitly hardened taking best practices and vendor hardening guides into account.
- Detection:** In-scope technical assets with RAA values of 55 % or higher. Generally for high-value targets like datastores, application servers, identity providers and ERP systems this limit is reduced to 40 %
- Rating:** The risk rating depends on the sensitivity of the data processed or stored in the technical asset.

Missing Identity Propagation

missing-identity-propagation

- STRIDE:** Elevation of Privilege
- Description:** Technical assets (especially multi-tenant systems), which usually process data for endusers should authorize every request based on the identity of the enduser when the data flow is authenticated (i.e. non-public). For DevOps usages at least a technical-user authorization is required.
- Detection:** In-scope service-like technical assets which usually process data based on enduser requests, if authenticated (i.e. non-public), should authorize incoming requests based on the propagated enduser identity when their rating is sensitive. This is especially the case for all multi-tenant assets (there even less-sensitive rated ones). DevOps usages are exempted from this risk.
- Rating:** The risk rating (medium or high) depends on the confidentiality, integrity, and availability rating of the technical asset.

Missing Identity Provider Isolation

missing-identity-provider-isolation

- STRIDE:** Elevation of Privilege
- Description:** Highly sensitive identity provider assets and their identity datastores should be isolated from other assets by their own network segmentation trust-boundary (execution-environment boundaries do not count as network isolation).
- Detection:** In-scope identity provider assets and their identity datastores when surrounded by other (not identity-related) assets (without a network trust-boundary in-between).

This risk is especially prevalent when other non-identity related assets are within the same execution environment (i.e. same database or same application server).

Rating: Default is high impact. The impact is increased to very-high when the asset missing the trust-boundary protection is rated as strictly-confidential or mission-critical.

Missing Identity Store

missing-identity-store

STRIDE: Spoofing

Description: The modeled architecture does not contain an identity store, which might be the risk of a model missing critical assets (and thus not seeing their risks).

Detection: Models with authenticated data-flows authorized via enduser-identity missing an in-scope identity store.

Rating: The risk rating depends on the sensitivity of the enduser-identity authorized technical assets and their data assets processed and stored.

Missing Network Segmentation

missing-network-segmentation

STRIDE: Elevation of Privilege

Description: Highly sensitive assets and/or datastores residing in the same network segment than other lower sensitive assets (like webserver or content management systems etc.) should be better protected by a network segmentation trust-boundary.

Detection: In-scope technical assets with high sensitivity and RAA values as well as datastores when surrounded by assets (without a network trust-boundary in-between) which are of type client-system, web-server, web-application, cms, web-service-rest, web-service-soap, build-pipeline, sourcecode-repository, monitoring, or similar and there is no direct connection between these (hence no requirement to be so close to each other).

Rating: Default is low risk. The risk is increased to medium when the asset missing the trust-boundary protection is rated as strictly-confidential or mission-critical.

Missing Vault (Secret Storage)

missing-vault

STRIDE: Information Disclosure

Description: In order to avoid the risk of secret leakage via config files (when attacked through vulnerabilities being able to read files like Path-Traversal and others), it is best practice to use a separate hardened process with proper authentication, authorization, and audit logging to access config secrets (like credentials, private keys, client certificates, etc.). This component is usually some kind of Vault.

Detection: Models without a Vault (Secret Storage).

Rating: The risk rating depends on the sensitivity of the technical asset itself and of the data assets processed and stored.

Missing Vault Isolation

missing-vault-isolation

STRIDE: Elevation of Privilege

Description: Highly sensitive vault assets and their datastores should be isolated from other assets by their own network segmentation trust-boundary (execution-environment boundaries do not count as network isolation).

Detection: In-scope vault assets when surrounded by other (not vault-related) assets (without a network trust-boundary in-between). This risk is especially prevalent when other non-vault related assets are within the same execution environment (i.e. same database or same application server).

Rating: Default is medium impact. The impact is increased to high when the asset missing the trust-boundary protection is rated as strictly-confidential or mission-critical.

Missing Web Application Firewall (WAF)

missing-waf

STRIDE: Tampering

Description: To have a first line of filtering defense, security architectures with web-services or web-applications should include a WAF in front of them. Even though a WAF is not a replacement for security (all components must be secure even without a WAF) it adds another layer of defense to the overall system by delaying some attacks and having easier attack alerting through it.

Detection: In-scope web-services and/or web-applications accessed across a network trust boundary not having a Web Application Firewall (WAF) in front of them.

Rating: The risk rating depends on the sensitivity of the technical asset itself and of the data assets processed and stored.

Mixed Targets on Shared Runtime

mixed-targets-on-shared-runtime

STRIDE: Elevation of Privilege

Description: Different attacker targets (like frontend and backend/datastore components) should not be running on the same shared (underlying) runtime.

Detection: Shared runtime running technical assets of different trust-boundaries is at risk. Also mixing backend/datastore with frontend components on the same shared runtime is considered a risk.

Rating: The risk rating (low or medium) depends on the confidentiality, integrity, and availability rating of the technical asset running on the shared runtime.

Path-Traversal

path-traversal

STRIDE: Information Disclosure

Description: When a filesystem is accessed Path-Traversal or Local-File-Inclusion (LFI) risks might arise. The risk rating depends on the sensitivity of the technical asset itself

and of the data assets processed or stored.

Detection: Filesystems accessed by in-scope callers.

Rating: The risk rating depends on the sensitivity of the data stored inside the technical asset.

Push instead of Pull Deployment

push-instead-of-pull-deployment

STRIDE: Tampering

Description: When comparing push-based vs. pull-based deployments from a security perspective, pull-based deployments improve the overall security of the deployment targets. Every exposed interface of a production system to accept a deployment increases the attack surface of the production system, thus a pull-based approach exposes less attack surface relevant interfaces.

Detection: Models with build pipeline components accessing in-scope targets of deployment (in a non-readonly way) which are not build-related components themselves.

Rating: The risk rating depends on the highest sensitivity of the deployment targets running custom-developed parts.

Search-Query Injection

search-query-injection

STRIDE: Tampering

Description: When a search engine server is accessed Search-Query Injection risks might arise.

Detection: In-scope clients accessing search engine servers via typical search access protocols.

Rating: The risk rating depends on the sensitivity of the search engine server itself and of the data assets processed or stored.

Server-Side Request Forgery (SSRF)

server-side-request-forgery

STRIDE: Information Disclosure

Description: When a server system (i.e. not a client) is accessing other server systems via typical web protocols Server-Side Request Forgery (SSRF) or Local-File-Inclusion (LFI) or Remote-File-Inclusion (RFI) risks might arise.

Detection: In-scope non-client systems accessing (using outgoing communication links) targets with either HTTP or HTTPS protocol.

Rating: The risk rating (low or medium) depends on the sensitivity of the data assets receivable via web protocols from targets within the same network trust-boundary as well on the sensitivity of the data assets receivable via web protocols from the target asset itself. Also for cloud-based environments the exploitation impact is at least medium, as cloud backend services can be attacked via SSRF.

Service Registry Poisoning

service-registry-poisoning**STRIDE:** Spoofing**Description:** When a service registry used for discovery of trusted service endpoints Service Registry Poisoning risks might arise.**Detection:** In-scope service registries.**Rating:** The risk rating depends on the sensitivity of the technical assets accessing the service registry as well as the data assets processed or stored.**SQL/NoSQL-Injection****sql-nosql-injection****STRIDE:** Tampering**Description:** When a database is accessed via database access protocols SQL/NoSQL-Injection risks might arise. The risk rating depends on the sensitivity technical asset itself and of the data assets processed or stored.**Detection:** Database accessed via typical database access protocols by in-scope clients.**Rating:** The risk rating depends on the sensitivity of the data stored inside the database.**Unchecked Deployment****unchecked-deployment****STRIDE:** Tampering**Description:** For each build-pipeline component Unchecked Deployment risks might arise when the build-pipeline does not include established DevSecOps best-practices. DevSecOps best-practices scan as part of CI/CD pipelines for vulnerabilities in source- or byte-code, dependencies, container layers, and dynamically against running test systems. There are several open-source and commercial tools existing in the categories DAST, SAST, and IAST.**Detection:** All development-relevant technical assets.**Rating:** The risk rating depends on the highest rating of the technical assets and data assets processed by deployment-receiving targets.**Unencrypted Technical Assets****unencrypted-asset****STRIDE:** Information Disclosure**Description:** Due to the confidentiality rating of the technical asset itself and/or the processed data assets this technical asset must be encrypted. The risk rating depends on the sensitivity technical asset itself and of the data assets stored.**Detection:** In-scope unencrypted technical assets (excluding reverse-proxy, load-balancer, waf, ids, ips and embedded components like library) storing data assets rated at least as confidential or critical. For technical assets storing data assets rated as strictly-confidential or mission-critical the encryption must be of type data-with-enduser-individual-key.

Rating: Depending on the confidentiality rating of the stored data-assets either medium or high risk.

Unencrypted Communication

unencrypted-communication

STRIDE: Information Disclosure

Description: Due to the confidentiality and/or integrity rating of the data assets transferred over the communication link this connection must be encrypted.

Detection: Unencrypted technical communication links of in-scope technical assets (excluding monitoring traffic as well as local-file-access and in-process-library-call) transferring sensitive data.

Rating: Depending on the confidentiality rating of the transferred data-assets either medium or high risk.

Unguarded Access From Internet

unguarded-access-from-internet

STRIDE: Elevation of Privilege

Description: Internet-exposed assets must be guarded by a protecting service, application, or reverse-proxy.

Detection: In-scope technical assets (excluding load-balancer) with confidentiality rating of confidential (or higher) or with integrity rating of critical (or higher) when accessed directly from the internet. All web-server, web-application, reverse-proxy, waf, and gateway assets are exempted from this risk when they do not consist of custom developed code and the data-flow only consists of HTTP or FTP protocols. Access from monitoring systems as well as VPN-protected connections are exempted.

Rating: The matching technical assets are at low risk. When either the confidentiality rating is strictly-confidential or the integrity rating is mission-critical, the risk-rating is considered medium. For assets with RAA values higher than 40 % the risk-rating increases.

Unguarded Direct Datastore Access

unguarded-direct-datastore-access

STRIDE: Elevation of Privilege

Description: Datastores accessed across trust boundaries must be guarded by some protecting service or application.

Detection: In-scope technical assets of type datastore (except identity-store-ldap when accessed from identity-provider and file-server when accessed via file transfer protocols) with confidentiality rating of confidential (or higher) or with integrity rating of critical (or higher) which have incoming data-flows from assets outside across a network trust-boundary. DevOps config and deployment access is excluded from this risk.

Rating: The matching technical assets are at low risk. When either the confidentiality rating is strictly-confidential or the integrity rating is mission-critical, the risk-rating is considered medium. For assets with RAA values higher than 40 % the risk-rating increases.

Unnecessary Communication Link

unnecessary-communication-link

STRIDE: Elevation of Privilege

Description: When a technical communication link does not send or receive any data assets, this is an indicator for an unnecessary communication link (or for an incomplete model).

Detection: In-scope technical assets' technical communication links not sending or receiving any data assets.

Rating: low

Unnecessary Data Asset

unnecessary-data-asset

STRIDE: Elevation of Privilege

Description: When a data asset is not processed or stored by any data assets and also not transferred by any communication links, this is an indicator for an unnecessary data asset (or for an incomplete model).

Detection: Modelled data assets not processed or stored by any data assets and also not transferred by any communication links.

Rating: low

Unnecessary Data Transfer

unnecessary-data-transfer

STRIDE: Elevation of Privilege

Description: When a technical asset sends or receives data assets, which it neither processes or stores this is an indicator for unnecessarily transferred data (or for an incomplete model). When the unnecessarily transferred data assets are sensitive, this poses an unnecessary risk of an increased attack surface.

Detection: In-scope technical assets sending or receiving sensitive data assets which are neither processed nor stored by the technical asset are flagged with this risk. The risk rating (low or medium) depends on the confidentiality, integrity, and availability rating of the technical asset. Monitoring data is exempted from this risk.

Rating: The risk assessment is depending on the confidentiality and integrity rating of the transferred data asset either low or medium.

Unnecessary Technical Asset

unnecessary-technical-asset

STRIDE: Elevation of Privilege

Description: When a technical asset does not process or store any data assets, this is an

indicator for an unnecessary technical asset (or for an incomplete model). This is also the case if the asset has no communication links (either outgoing or incoming).

Detection: Technical assets not processing or storing any data assets.

Rating: low

Untrusted Deserialization

untrusted-deserialization

STRIDE: Tampering

Description: When a technical asset accepts data in a specific serialized form (like Java or .NET serialization), Untrusted Deserialization risks might arise.

Detection: In-scope technical assets accepting serialization data formats (including EJB and RMI protocols).

Rating: The risk rating depends on the sensitivity of the technical asset itself and of the data assets processed and stored.

Wrong Communication Link Content

wrong-communication-link-content

STRIDE: Information Disclosure

Description: When a communication link is defined as readonly, but does not receive any data asset, or when it is defined as not readonly, but does not send any data asset, it is likely to be a model failure.

Detection: Communication links with inconsistent data assets being sent/received not matching their readonly flag or otherwise inconsistent protocols not matching the target technology type.

Rating: low

Wrong Trust Boundary Content

wrong-trust-boundary-content

STRIDE: Elevation of Privilege

Description: When a trust boundary of type network-policy-namespace-isolation contains non-container assets it is likely to be a model failure.

Detection: Trust boundaries which should only contain containers, but have different assets inside.

Rating: low

XML External Entity (XXE)

xml-external-entity

STRIDE: Information Disclosure

Description: When a technical asset accepts data in XML format, XML External Entity (XXE) risks might arise.

Detection: In-scope technical assets accepting XML data formats.

Rating: The risk rating depends on the sensitivity of the technical asset itself and of the data

assets processed and stored. Also for cloud-based environments the exploitation impact is at least medium, as cloud backend services can be attacked via SSRF (and XXE vulnerabilities are often also SSRF vulnerabilities).

Disclaimer

threatmod-automation conducted this threat analysis using the open-source Threagile toolkit on the applications and systems that were modeled as of this report's date. Information security threats are continually changing, with new vulnerabilities discovered on a daily basis, and no application can ever be 100% secure no matter how much threat modeling is conducted. It is recommended to execute threat modeling and also penetration testing on a regular basis (for example yearly) to ensure a high ongoing level of security and constantly check for new attack vectors.

This report cannot and does not protect against personal or business loss as the result of use of the applications or systems described. threatmod-automation and the Threagile toolkit offers no warranties, representations or legal certifications concerning the applications or systems it tests. All software includes defects: nothing in this document is intended to represent or warrant that threat modeling was complete and without error, nor does this document represent or warrant that the architecture analyzed is suitable to task, free of other defects than reported, fully compliant with any industry standards, or fully compatible with any operating system, hardware, or other application. Threat modeling tries to analyze the modeled architecture without having access to a real working system and thus cannot and does not test the implementation for defects and vulnerabilities. These kinds of checks would only be possible with a separate code review and penetration test against a working system and not via a threat model.

By using the resulting information you agree that threatmod-automation and the Threagile toolkit shall be held harmless in any event.

This report is confidential and intended for internal, confidential use by the client. The recipient is obligated to ensure the highly confidential contents are kept secret. The recipient assumes responsibility for further distribution of this document.

In this particular project, a timebox approach was used to define the analysis effort. This means that the author allotted a prearranged amount of time to identify and document threats. Because of this, there is no guarantee that all possible threats and risks are discovered. Furthermore, the analysis applies to a snapshot of the current state of the modeled architecture (based on the architecture information provided by the customer) at the examination time.

Report Distribution

Distribution of this report (in full or in part like diagrams or risk findings) requires that this disclaimer as well as the chapter about the Threagile toolkit and method used is kept intact as part of the distributed report or referenced from the distributed parts.