





# Progress Report

Alexander Maringele

June 15th, 2016

# References

-  Robert Nieuwenhuis, Thomas Hillenbrand, Alexandre Riazanov, and Andrei Voronkov, *On the evaluation of indexing techniques for theorem proving*, Automated Reasoning (Rajeev Goré, Alexander Leitsch, and Tobias Nipkow, eds.), Lecture Notes in Computer Science, vol. 2083, Springer Berlin Heidelberg, 2001, pp. 257–271.
-  Alexandre Riazanov and Andrei Voronkov, *Efficient instance retrieval with standard and relational path indexing*, Automated Deduction – CADE-19 (Franz Baader, ed.), Lecture Notes in Computer Science, vol. 2741, Springer Berlin Heidelberg, 2003, pp. 380–396.
-  R. Sekar, I. V. Ramakrishnan, and Andrei Voronkov, *Term indexing*, Handbook of Automated Reasoning (Alan Robinson and Andrei Voronkov, eds.), Elsevier Science Publishers B. V., Amsterdam, The Netherlands, 2001, pp. 1853–1964.
-  Harald Zankl, Nao Hirokawa, and Aart Middeldorp, *KBO Orientability*, Journal of Automated Reasoning **43** (2000), no. 2, pp. 173–201.

$$x = a \vee x \neq a$$

$$f(a) \neq f(b)$$

$$R = \{x = a\} \text{ is ground complete}$$

$$\sigma = \{x \mapsto b\} \ (x = a)\sigma = a \rightarrow b \text{ with } a > b \ f(a) \neq b$$

$$\perp = \perp \vee \perp \neq \perp$$

$$f(\perp) \neq f(a)$$

$P(a), \neg P(f(a, b)), f(x, b) = x$

$P(a), \neg P(f(a, b)), f(\perp, b) = \perp$

$\{f(x, b) = x\}$  is ground complete and with  $\{x \mapsto a\}$  we get  $\neg P(a)$