

# Quick primer on Matlab for IACV

**MATlab** : Matrix Laboratory can be used as a scripting language any variable is a matrix (a scalar is a special case of a multidimensional array)

Credits:

- Alessandro Giusti [alessandrogiusti@idsia.ch](mailto:alessandrogiusti@idsia.ch)
- Giacomo Boracchi [giacomo.boracchi@polimi.it](mailto:giacomo.boracchi@polimi.it) - September 28th, 2020

Edits: Luca Magri - September 19th, 2023

Clear the workspace and close all the figure and clear the command window

```
close all % close all the figures
clear % clear the workspace
clc % clear the command window
```

Print to the command window

```
disp('For enquiry, please send an email to luca.magri@polimi.it');
```

For enquiry, please send an email to [luca.magri@polimi.it](mailto:luca.magri@polimi.it)

```
fprintf('there is also a C-like printing function\n%s %dth, %d', 'September', 20, 2018)
```

there is also a C-like printing function  
September 20th, 2018

## Dealing with variables:

all the variables are stored in matrix with proper dimensions. Scalar are treated as 1x1 matrix.

Variables are created by assignments, the size of a variable is the dimension of the matrix representing it.

```
v = 12;
c = 'c';
size(v)
```

```
ans = 1x2
      1      1
```

```
size(c)
```

```
ans = 1x2
      1      1
```

```
% use ; at the end of instruction not to display results
% in command line
v = 7;
```

Data types are automatically defined depending on the assigned value and can be checked using `whos`

```
whos
```

Name	Size	Bytes	Class	Attributes
v	1x1	8	double	

Variables have datatypes (usually you can forget, but not when dealing with images).

Most common types we will consider are:

- *double* (i.e., double-precision floating point),
- *uint8* (i.e., unsigned integers with 8 bits, [0 255] range),
- *logical* (i.e., boolean)

We can explicitly cast a double to a `uint8` type

```
v = uint8(v)
```

```
v = uint8
7
```

```
whos
```

Name	Size	Bytes	Class	Attributes
v	1x1	1	uint8	

## Arrays

can be row or column vector.

```
% a row vector (commas can be omitted)
r = [1, 2, 3, 4]
```

```
r = 1x4
1    2    3    4
```

```
size(r)
```

```
ans = 1x2
1    4
```

It is important to remember the index start from 1.

```
r(1)
```

```
ans = 1
```

```
%r(0) %raises an error! Array indices must be positive integers or logical values.
r(2) % returns the first element of the array r
```

```
ans = 2
```

```
% a column vector  
c = [1; 2; 3; 4]
```

```
c = 4x1  
    1  
    2  
    3  
    4
```

```
size(c)
```

```
ans = 1x2  
     4     1
```

You can define vectors by regular increment operator: [start : step : end]

```
a = [1 : 2 : 10]
```

```
a = 1x5  
    1     3     5     7     9
```

when omitted, step is equal to 1

```
a2 = [1 : 10]
```

```
a2 = 1x10  
    1     2     3     4     5     6     7     8     9    10
```

## Matrices

```
v=[1 2; 3 4]
```

```
v = 2x2  
    1     2  
    3     4
```

```
size(v)
```

```
ans = 1x2  
     2     2
```

## Array concatenation

you can concatenate matrices or vectors as far as their sizes are consistent. ' denotes the transpose operation

```
B = [v', v']
```

```
B = 2x4  
    1     3     1     3  
    2     4     2     4
```

```
C = [v ; v]
```

```
C = 4x2
     1     2
     3     4
     1     2
     3     4
```

```
% the dimension of the data, visible also typing whos
dim = size(C)
```

```
dim = 1x2
     4     2
```

```
num_rows = size(C,1)
```

```
num_rows = 4
```

```
num_cols = size(C,2)
```

```
num_cols = 2
```

```
% this is not allowed
disp('K = [r,c]: this is not allowed')
```

```
K = [r,c]: this is not allowed
```

```
%K = [r,c]
```

Other examples of array concatenation:

```
my_vec1 = [1 2 3];
my_vec2 = 4:6;
```

```
my_matrix = [my_vec1; my_vec2]
```

```
my_matrix = 2x3
     1     2     3
     4     5     6
```

```
size(my_matrix)
```

```
ans = 1x2
     2     3
```

```
my_long_vector = [my_vec1 my_vec2]
```

```
my_long_vector = 1x6
     1     2     3     4     5     6
```

```
size(my_long_vector)
```

```
ans = 1×2
      1      6
```

`C = cat(dim,A,B)` concatenates B to the end of A along dimension dim when A and B have compatible sizes (the lengths of the dimensions match except for the operating dimension dim).

```
my_matrix = cat(1,my_vec1,my_vec2)
```

```
my_matrix = 2×3
      1      2      3
      4      5      6
```

```
my_long_vector = cat(2,my_vec1,my_vec2)
```

```
my_long_vector = 1×6
      1      2      3      4      5      6
```

```
my_3d_matrix = cat(3,my_vec1,my_vec2)
```

```
my_3d_matrix =
my_3d_matrix(:,:,1) =
      1      2      3
```

```
my_3d_matrix(:,:,2) =
      4      5      6
```

```
size(my_3d_matrix)
```

```
ans = 1×3
      1      3      2
```

```
%% indexing (starts from 1)
my_vec = (1:10)';
my_vec(1)
```

```
ans = 1
```

```
my_matrix = [1:4;5:8;9:12]
```

```
my_matrix = 3×4
      1      2      3      4
      5      6      7      8
      9     10     11     12
```

```
my_matrix(3,2)
```

```
ans = 10
```

```
% column-wise linear indexing for matrices  
my_matrix(6)
```

```
ans = 10
```

## Subarray

`v(indexes)` returns a vector of all the elements of `v` at locations in array indexes

```
% you can reference single or multiple values in an array:  
my_matrix(2,3) % first row and second column (row and column indices are 1-based)
```

```
ans = 7
```

```
my_matrix(:,2) % the second column of my_matrix
```

```
ans = 3x1  
     2  
     6  
    10
```

```
my_matrix(1,2) % the first row of my_matrix
```

```
ans = 3x1  
     2  
     6  
    10
```

```
B = my_matrix(:,[1,3]) % some of the columns
```

```
B = 3x2  
     1     3  
     5     7  
     9    11
```

You can extend vectors / matrices by assigning some element out of the range

```
my_matrix(:,5)=1
```

```
my_matrix = 3x5  
     1     2     3     4     1  
     5     6     7     8     1  
     9    10    11    12     1
```

You can use `end` to specify the last row/columns

```
my_matrix(1:3,[2 4])
```

```
ans = 3x2
     2     4
     6     8
    10    12
```

```
my_matrix(1:end,[2 4])
```

```
ans = 3x2
     2     4
     6     8
    10    12
```

```
my_matrix(:,[2 4])
```

```
ans = 3x2
     2     4
     6     8
    10    12
```

```
my_matrix(1:2,[2 4])
```

```
ans = 2x2
     2     4
     6     8
```

```
my_matrix(1:end-1,[2 4])
```

```
ans = 2x2
     2     4
     6     8
```

You can unfold a matrix columnwise

```
my_vector = my_matrix(:)
```

```
my_vector = 15x1
     1
     5
     9
     2
     6
    10
     3
     7
    11
     4
     ⋮
```

## Operations

on vectors are from linear algebra common operations work on matrices (careful about multiplication and division)

```
v = [1 2 3]
```

```
v = 1x3  
    1     2     3
```

```
v*v'
```

```
ans = 14
```

```
v'*v
```

```
ans = 3x3  
    1     2     3  
    2     4     6  
    3     6     9
```

There are also element-wise operators

```
[1 2 3].*[4 5 6]
```

```
ans = 1x3  
    4    10    18
```

```
[1 2 3] + 5
```

```
ans = 1x3  
    6     7     8
```

```
[1 2 3] * 2 % no need to use element-wise operator with scalars
```

```
ans = 1x3  
    2     4     6
```

```
[1 2 3] .* 2 %explicit element-wise multiplication
```

```
ans = 1x3  
    2     4     6
```

```
[1 2 3] / 2
```

```
ans = 1x3  
    0.5000    1.0000    1.5000
```

```
[1 2 3] ./ 2 %explicit element-wise division
```

```
ans = 1x3  
    0.5000    1.0000    1.5000
```

```
[1 2 3] .^ 2 %explicit element-wise power
```

```
ans = 1x3  
    1     4     9
```



```
[1 2 3] * [4 5 6]' % this matrix product, returns a scalar (it is the inner product)
```

```
ans = 32
```

```
[1 2 3]' * [4 5 6] % this is the matrix product, returns a 3 x 3 matrix
```

```
ans = 3x3
     4     5     6
     8    10    12
    12    15    18
```

```
% rounding functions
ceil(10.56)
```

```
ans = 11
```

```
floor(10.56)
```

```
ans = 10
```

```
round(10.56)
```

```
ans = 11
```

```
ceil(0:0.1:1)
```

```
ans = 1x11
     0     1     1     1     1     1     1     1     1     1     1
```

```
% arithmetic functions
sum([1 2 3 4])
```

```
ans = 10
```

```
sum([1:4;5:8])
```

```
ans = 1x4
     6     8    10    12
```

```
sum([1:4;5:8],2)
```

```
ans = 2x1
    10
    26
```

```
sum(sum([1:4;5:8]))
```

```
ans = 36
```

```
my_matrix = [1:4;5:8];  
sum(my_matrix(:))
```

```
ans = 36
```

## Printing

```
disp('Hello World!');
```

```
Hello World!
```

```
disp(['Hello ', 'World!']);
```

```
Hello World!
```

```
% string concatenation in printf.  
disp(['number of columns in the matrix: ', num2str(size(my_matrix,2))]);
```

```
number of columns in the matrix: 2 4
```

```
fprintf('number of columns in the matrix: %f\n',size(my_matrix,2));
```

```
number of columns in the matrix: 4.000000
```

## Logicals

you can compare a vector via the customary relational operators and obtain a vector of logicals (i.e. b)

```
b = v>2
```

```
b = 1x3 logical array  
 0  0  1
```

```
whos b
```

Name	Size	Bytes	Class	Attributes
b	1x3	3	logical	