nora-lends

AUTHORIZATION Bearer Token		
Token <token></token>		
POST login	Example Request	login
localhost:8080:4080/login	<pre>curllocationrequest POST 'localhost:8888:4080/login' \ data-raw '{</pre>	
AUTHORIZATION Bearer Token	"username": "alethetxin", "password": "871419" }*	
This request is using Bearer Token from collection nore-lends		
BODY raw		
{ "username": "alethetxin", "password": "871419" }		
GET Get All Personas	Example Request	Get All Personas
localhost:8080:4080/personas	curllocationrequest GET 'localhost:8080:4080/personas'	
AUTHORIZATION Bearer Token This request is using Bearer Token from collection nora-lends		
	Example Request	Get Persona By ld
GET Get Persona By Id		
localhost:8080:4080/personas/d4ed5fdf-63ef-4b13-9b30-8da4a6d9a18e		
AUTHORIZATION Bearer Token		
This request is using Bearer Token from collection nore-lends		
DEL Delete Persona	Example Request	Delete Persona
localhost:8080.4080/personas/2fbdb0eb-b474-4daa-a59e-08286044ce71	curllocationrequest DELETE 'localhost:8088:4080/personas/2fbdb0eb-b474-4daa-a59e-08286844ce71'	
AUTHORIZATION Bearer Token		
This request is using Bearer Token from collection nore-lends		
2007 Guide Bourse	Example Request	Create Persona
POST Create Persona localhost 8080-4080/personas	curllocationrequest POST 'localhost:8888:4080/personas' \	
	data-raw '("username": "emanoxxx", "emall": "emanoxxx(genanoxxx.com",	
AUTHORIZATION Bearer Token	"nombre": "Emanoxxx", "password": "Amary34"	
This request is using Bearer Token from collection nore-lends BODY raw	y	
BODT 10W		

```
NORA-LENDS
Introduction
POST login
GET Get Persona By Id
```

GET Get All Personas

DEL Delete Persona

POST Create Persona

PUT Update Persona

GET Get Eventos

DEL Delete Evento

POST Create Evento

GET Get Notas

POST Create Nota

PUT Update Nota

DEL Delete Nota

POST Get Intent Chat

```
"username": "emanoxxx",
"email": "emanoxxx@emanoxxx.com",
"nombre": "Emanoxxx".
"password": "Amary34"
```

```
localhost:80804080/personas/d4ed5fdf-63ef-4b13-9b30-8da4a6d9a18e
```

AUTHORIZATION Bearer Token

PUT Update Persona

This request is using Bearer Token from collection nora-lends

BODY raw

```
"username": "usuario1-updated",
"email": "usuario1@ejemplo.com",
"nombre": "José Pérez",
"password": "jose123"
```

```
GET Get Eventos
```

localhost:8080:4081/eventos/ AUTHORIZATION Bearer Token

Token

<token>

<token>

```
DEL Delete Evento
```

localhost:8080:4081/eventos/:id

AUTHORIZATION Bearer Token

This request is using Bearer Token from collection nora-lends

PATH VARIABLES

POST Create Evento

localhost:8080:4081/eventos

AUTHORIZATION Bearer Token

Token

BODY raw

```
"titulo": "Clase de william",
 "fechaDeInicio": "2022-05-20T14:21:00+02:00",
 "fechaDeFinalizacion": "2020-08-19T14:21:00+02:00"
```

PUT Update Evento

localhost:8080:4081/eventos/:id

AUTHORIZATION Bearer Token

```
Example Request
```

```
curl --location --request PUT localhost:80804080/personas/d4ed5fdf-63ef-4b13-9b30-8da4a6d9a18e
--data-raw '{
    "username": "usuario1-updated",
   "email": "usuario1@ejemplo.com",
"nombre": "José Pérez",
   "password": "jose123"
```

Example Request

curl --location --request GET 'localhost:8080:4081/eventos/'

Example Request

curl --location --request DELETE 'localhost:8080:4081/eventos/:id'

Example Request

curl --location --request POST 'localhost:8080:4081/eventos' \ --data-raw '{
 "titulo": "Clase de william", "fechaDeInicio": "2022-05-20T14:21:00+02:00",
"fechaDeFinalizacion": "2020-08-19T14:21:00+02:00"

Example Request

Update Evento

Update Persona

Get Eventos

Delete Evento

Create Evento

```
This request is using Bearer Token from collection nora-lends
                                                                                                                                                                                 curl --location --request PUT 'localhost:8080:4081/eventos/:id' \setminus
                                                                                                                                                                                  --data-raw '{
    "titulo": "titulo",
PATH VARIABLES
                                                                                                                                                                                     "fechaDeInicio": "2022-05-20T14:21:00+02:00",
"fechaDeFinalizacion": "2020-08-19T14:21:00+02:00"
id
BODY raw
      "titulo": "titulo",
      "fechaDeInicio": "2022-05-20T14:21:00+02:00",
      "fechaDeFinalizacion": "2020-08-19T14:21:00+02:00"
                                                                                                                                                                                 Example Request
GET Get Notas
                                                                                                                                                                                 curl --location --request GET 'localhost:8080:4082/eventos/e39941a9-b620-4a12-aab8-47114b6304f5/notas' \
  localhost:8080:4082/eventos/e39941a9-b620-4a12-aab8-47114b6304f5/notas
                                                                                                                                                                                     "titulo": "Primera nota".
                                                                                                                                                                                     "contenido": "El cuerpo de la primera nota",
"eventoId": "0766d4c2-d35a-4a25-8cdb-1522ebf5da8c"
AUTHORIZATION Bearer Token
This request is using Bearer Token from collection nora-lends
BODY raw
     "titulo": "Primera nota",
      "contenido": "El cuerpo de la primera nota",
       "eventoId": "0766d4c2-d35a-4a25-8cdb-1522ebf5da8c"
                                                                                                                                                                                 Example Request
                                                                                                                                                                                                                                                                                                                                                  Create Nota
POST Create Nota
                                                                                                                                                                                 curl --location --request POST 'localhost:8080:4082/notas' \setminus
  localhost:8080:4082/notas
                                                                                                                                                                                  --data-raw '{
                                                                                                                                                                                     "titulo": "Primera nota",
                                                                                                                                                                                     "contenido": "El cuerpo de la primera nota",
"eventoId": "0766d4c2-d35a-4a25-8cdb-1522ebf5da8c'
AUTHORIZATION Bearer Token
This request is using Bearer Token from collection nora-lends
BODY raw
      "contenido": "El cuerpo de la primera nota",
      "eventoId": "0766d4c2-d35a-4a25-8cdb-1522ebf5da8c"
                                                                                                                                                                                 Example Request
                                                                                                                                                                                                                                                                                                                                                  Update Nota
PUT Update Nota
                                                                                                                                                                                 curl --location --request PUT 'localhost:8080:8082/notas/:id' \
  localhost:8080:8082/notas/:id
                                                                                                                                                                                 --data-raw '{
    "titulo": "Primera nota",
                                                                                                                                                                                     "contenido": "El cuerpo de la primera nota",
AUTHORIZATION Bearer Token
                                                                                                                                                                                      "eventoId": "0766d4c2-d35a-4a25-8cdb-1522ebf5da8c"
This request is using Bearer Token from collection nora-lends
PATH VARIABLES
id
BODY raw
      "titulo": "Primera nota",
      "contenido": "El cuerpo de la primera nota",
      "eventoId": "0766d4c2-d35a-4a25-8cdb-1522ebf5da8c"
```

Example Request

curl --location --request DELETE 'localhost:8080:4082/notas/:id'

DEL Delete Nota

localhost:8080:4082/notas/:id

AUTHORIZATION Bearer Token

Delete Nota

This request is using Bearer Token from collection nora-lends

PATH VARIABLES

id

POST Get Intent Chat

localhost:8080:8000

AUTHORIZATION Bearer Token

This request is using Bearer Token from collection nora-lends

BODY raw

Example Request Get Intent Chat