

Reader Supplement to *Triangle Hypersurfaces and a Sharp Identifiability Boundary for Level-2 K3P Networks*

Alec Kriebel

ORCID: [0009-0001-9320-500X](https://orcid.org/0009-0001-9320-500X)

August 2026

This supplement is a reader-facing map of the exact proof package. It gives the formulas, finite censuses, witness selections, and hash bindings needed to audit the article without reproducing raw JSON ledgers. All paths are relative to the project root `k3p_level2_identifiability_final/`. The machine-readable files, not line-broken values in this document, are canonical for exact replay.

1 Dependency graph

The necessity and sufficiency chains are:

K3P domain + root invariance

- > true-cut rank ≤ 4 + generic noncut recovery
- > `Cut(target)` subset `Cut(source)`
- > crossing-split dichotomy + 204 pointwise one-active directions
- > `Cut(source)` subset `Cut(target)`
- > common labelled reduced bridge tree
- > three-sector bridge fibre + physical local product
- > marginal submersion + finite target-type localization
- > 14-orbit theorem + restoration + coherent probes
- > necessity: topology equivalence modulo ordinary triangles

H14 quartic + three rank-14 orientation sections

- > common relative triangle germ
- > one labelled contextual contraction
- > simultaneous principal/CT bridge gluing
- > sufficiency and symmetric common full-dimensional germ

main classification + finite topology set + semialgebraic stratification

- > proper exceptional set
- > generic identifiability + terminating exact reconstruction

weak-not-strong topology census + Krawczyk equality box + two rank-15 maps

- > base ambient-open common germ
- > six-dimensional identical-cherry inverse
- > all- n dimension $6n-3$

all active theorem branches + final claim lock

- > integrated K3P-SAME classification gate
- > 18/18 fail-closed integrated mutations
- > CERTIFIED_K3P_SAME mathematics; publication engineering remains separate

The cut-transfer chain uses neither a common bridge tree nor the fourteen-orbit classification. The local classification is invoked only after cut equality has been proved.

2 Theorem-to-certificate crosswalk

claim	minimal active evidence and replay boundary
K3P inverse Fourier formulas, $\mathcal{D}_{3,+}$, $\mathcal{D}_{3,CT}$, subdivision, root movement	<code>model_domain/primary_exact_evidence.json</code> ; primary exact replay.
Cycle-theta primitive topology, no-omnian grammar, and strong repairs	<code>input_frozen/referenced_chat_manuscripts/jc_level2_source.tex</code> and <code>input_frozen/referenced_chat_manuscripts/k2p_level2_source.tex</code> , with the graph-only import boundary fixed by <code>COMPANION_DEPENDENCY_LOCK.json</code> and independently rebuilt in the clean-room, restoration, and probe replays.
True-cut rank and generic noncut recovery	article derivation; frozen JC cut theorem only on the relatively open strict JC locus in the isotropic slice, not on an open subset of full K3P; <code>cut_recovery/adversarial/</code> preserves the failed universal shortcut.
204 pointwise one-active directions	<code>cut_recovery/strong_crossbridge/final_certificate/STRONG_CROSSBRIDGE_FINAL_CERTIFICATE.json</code> and its producer-independent verifier.
Strong-class cut-set equality under containment	<code>cut_recovery/strong_crossbridge/global_transfer/THEOREM_MANIFEST.json</code> and <code>cut_recovery/strong_crossbridge/global_transfer/GLOBAL_TRANSFER_AUDIT.md</code> ; independent adversarial replay.
Tree-sunlet separation and triangle rank	<code>three_port/primary_exact_evidence.json</code> , <code>three_port/literal_separator_v2/K3P_TREE_SUNLET_LITERAL_SEPARATOR_V2.json</code> , its independent literal-map verifier, and its cyclic-renaming mutation suite. The frozen v1 file is retained only as superseded provenance.
H_{14} , irreducibility, smooth common germ, contextualization	<code>triangle_h14/K3P_H14_CONTEXT_CERTIFICATE.json</code> .
Three-sector bridge fibre and physical product	<code>bridge_fibre/K3P_BRIDGE_FIBRE_CERTIFICATE.json</code> .
Marginal descriptors and physical submersions	<code>marginals/K3P_MARGINAL_SUBMERSION_CERTIFICATE.json</code> .
Fourteen orbits and two sink swaps	<code>four_port_atlas/primary_exact_evidence.json</code> ; <code>clean_room/H21_01_TRANSPORT_AUDIT.json</code> .
Fixed-full restoration	<code>restoration/RESTORATION_MANIFEST.json</code> , <code>restoration/K3P_RESTORATION_THEOREM_REPORT.md</code> , ledger, proof registry, <code>restoration/K3P_RESTORATION_INDEPENDENT_VERIFICATION.json</code> , and <code>restoration/K3P_RESTORATION_MUTATION_CERTIFICATE.json</code> ; the independent replay passes and all 20 fail-closed restoration mutations are rejected.
One-/two-port coherence	<code>probes/K3P_PROBE_COHERENCE_CERTIFICATE.json</code> , independent streaming replay, mutation certificate, and the v2 K3P restoration binding <code>probes/RESTORATION_MANIFEST.json</code> .
Global gluing, genericity, reconstruction	<code>global_infrastructure/K3P_GLOBAL_GLUE_AND_RECONSTRUCTION_CERTIFICATE.json</code> , <code>global_infrastructure/GLOBAL_INFRASTRUCTURE_MANIFEST.json</code> , and its independent replay, read together with the active cut-transfer and restoration bindings. The integrated primary gate passes all 28 entries.

claim	minimal active evidence and replay boundary
Final K3P-SAME classification promotion	<code>reproducibility/K3P_SAME_CLASSIFICATION_GATE_REPORT.json</code> has schema <code>k3p-same-integrated-classification-gate-v2</code> , status <code>CERTIFIED_K3P_SAME</code> , and no remaining mathematical gates; <code>reproducibility/K3P_SAME_CLASSIFICATION_MUTATION_REPORT.json</code> rejects all 18 integrated fail-closed mutations.
Weak-class sharpness and all n	<code>sharpness/K3P_SHARPNESS_KRAWCZYK_CERTIFICATE.json</code> and <code>sharpness/K3P_SHARPNESS_TOPOLOGY_ALL_N_CERTIFICATE.json</code> .
Outer tree-double-theta obstruction, including strict-CT deformation	<code>input_frozen/referenced_chat_manuscripts/tree_theta_collision_source.tex</code> contains the exact tangent and analytic implicit-function argument; <code>topology/primary_double_theta_evidence.json</code> and <code>topology/primary_rooting_census_evidence.json</code> bind the collision rank, dimension, and exclusion from weak tree-childness in the active primary replay.

3 Exact model domains

For an edge spectrum $(1, c, g, t)$, inverse Fourier transformation gives

$$\frac{1}{4}(1 + c + g + t), \quad \frac{1}{4}(1 + c - g - t), \quad \frac{1}{4}(1 - c + g - t), \quad \frac{1}{4}(1 - c - g + t).$$

Thus

$$\mathcal{D}_{3,+} = \{(c, g, t) \in (0, 1)^3 : 1 + c - g - t > 0, 1 - c + g - t > 0, 1 - c - g + t > 0\}.$$

Strict continuous time is

$$\mathcal{D}_{3,CT} = \{(c, g, t) \in (0, 1)^3 : c > gt, g > ct, t > cg\}.$$

For strict subdivision, choose

$$r > \max\{c, g, t, g + t - c, c + t - g, c + g - t\}$$

in the principal domain, or additionally $r > \max\{gt/c, ct/g, cg/t\}$ in continuous time, and use

$$(c, g, t) = (r, r, r) \odot (c/r, g/r, t/r).$$

For a serial class the selected descriptor is

$$((c_i, g_i, t_i))_{i=1}^m \mapsto \left(\prod_i c_i, \prod_i g_i, \prod_i t_i \right).$$

Its Jacobian has three disjoint positive rows and rank three.

4 Balanced noncut compression handoff

For the reverse cut inclusion, a balanced two-color assignment on one active cycle or theta factor is reduced without changing its status. Retain the primitive core, a rigid support Q consisting of one complete minimum strong repair and every path-sink child, and at least two actual labels of each color. Since $|Q| \leq 4$, choosing at most four further actual labels gives at most eight ports; all other compulsory roles remain as zero-character completion ports. No blob edge is a bridge and no pendant arm isolates a complete color class, so the restriction remains noncut.

If a segment has three color runs c, d, c , the middle attachment lies on the path between the outer two in every switching, giving a direct all-switching obstruction. Otherwise reduce each segment to one actual label per run, with palette

$$(), (0), (1), (0, 1), (1, 0),$$

and double a singleton run when required to retain two labels of a color. Any coloring displayed by every switching before restriction would survive this reduction. Independent graph/switching enumeration finds zero survivors in the compressed palette. A failing switching and the ordinary tree quartet criterion therefore produce two actual labels of each color in one of the finite wrong-quartet directions.

The active census checksum is five primitive cores, 72 active-labelled records, 216 split entries, 12 displayed-by-all entries, and 204 certified wrong directions. These counts verify the exhaustive replay; the combinatorial reduction above is the premise of the handoff.

5 The H_{14} coordinate chart and quartic

The conservation-supported coordinate order is

$$(000, 0CC, 0GG, 0TT, C0C, CC0, CGT, CTG, G0G, GCT, GG0, GTC, T0T, TCG, TGC, TT0).$$

With $q_{000} = 1$, the ambient chart is $\mathbb{A}^{15}$. The exact quartic is

$$\begin{aligned} F_{H_{14}} = & q_{000}q_{CGT}q_{GTC}q_{TCG} - q_{000}q_{CTG}q_{GCT}q_{TGC} \\ & - q_{0CC}q_{CGT}q_{G0G}q_{TT0} + q_{0CC}q_{CTG}q_{GG0}q_{T0T} \\ & + q_{0GG}q_{C0C}q_{GCT}q_{TT0} - q_{0GG}q_{CC0}q_{GTC}q_{T0T} \\ & - q_{0TT}q_{C0C}q_{GG0}q_{TCG} + q_{0TT}q_{CC0}q_{G0G}q_{TGC}. \end{aligned}$$

The common tensor in this order is

$$(1, \frac{1}{12}, \frac{1}{12}, \frac{1}{12}, \frac{1}{12}, \frac{1}{12}, \frac{1}{48}, \frac{1}{48}, \frac{1}{12}, \frac{1}{48}, \frac{1}{12}, \frac{1}{48}, \frac{1}{12}, \frac{1}{48}, \frac{1}{12}).$$

At this point $F = 0$ and six normalized gradient coordinates are nonzero, each with absolute value $1/6912$. The irreducibility certificate treats the quartic as linear in q_{0CC} , with coefficient $-q_{CGT}q_{G0G}q_{TT0} + q_{CTG}q_{GG0}q_{T0T}$; a specialization kills that coefficient but leaves remainder -1 .

6 Triangle rank witnesses

All three common preimages have edge order (a, b, c, d, e, f) , spectra $(1/2, 1/2, 1/2)$ on the first five edges, $(1/3, 1/3, 1/3)$ on f , and inheritance $1/2$.

orientation	normalized output rows	parameter columns	determinant
1	(1, 2, 3, 4, 6, 8, 7, 10, 12, 9, 13, 5, 11, 15)	(0, 1, 2, 3, 4, 5, 6, 7, 8, 9, 10, 15, 16, 17)	$-1/760840571584512$
2	(4, 8, 12, 5, 7, 3, 6, 1, 10, 9, 11, 2, 13, 15)	same	$-1/760840571584512$
3	(4, 8, 12, 5, 6, 3, 7, 1, 10, 11, 9, 2, 13, 15)	same	$1/760840571584512$

The tree rank-9 witness uses output rows $(4, 8, 12, 5, 6, 3, 7, 1, 10)$, parameter columns $0, \dots, 8$, and determinant $8192/28940625$.

7 Tree-sunlet six-circuit certificate

Write $I(L; R) = \prod_{u \in L} q_u - \prod_{v \in R} q_v$ and use the literal map

$$q_{xyz} = a_x b_y c_z [\lambda f_y d_z + (1 - \lambda) f_x e_z].$$

Put $\mu = \lambda(1 - \lambda)$ and

$$\begin{aligned} M_1 &= a_C a_G b_G b_T c_C c_T, & M_2 &= a_C a_T b_G b_T c_C c_G, & M_3 &= a_G a_T b_C b_G c_C c_T, \\ M_4 &= a_G a_T b_C b_T c_C c_G, & M_5 &= a_C a_G b_C b_T c_G c_T, & M_6 &= a_C a_T b_C b_G c_G c_T. \end{aligned}$$

The six exact left-minus-right pullbacks are:

$L; R$	exact literal pullback
$I_1 \quad 000, CGT, GTC; 0TT, C0C, GG0$	$\mu M_1(f_C f_T - f_G)(d_C e_T - d_T e_C f_G)$
$I_2 \quad 000, CTG, TGC; 0GG, C0C, TT0$	$\mu M_2(f_C f_G - f_T)(d_C e_G - d_G e_C f_T)$
$I_3 \quad 000, GCT, TGC; 0CC, GG0, T0T$	$-\mu M_3(f_C f_T - f_G)(d_C e_T f_G - d_T e_C)$
$I_4 \quad 000, GTC, TCG; 0CC, G0G, TT0$	$-\mu M_4(f_C f_G - f_T)(d_C e_G f_T - d_G e_C)$
$I_5 \quad 000, CTG, GCT; 0TT, CC0, G0G$	$-\mu M_5(f_C - f_G f_T)(d_G e_T - d_T e_G f_C)$
$I_6 \quad 000, CGT, TCG; 0GG, CC0, T0T$	$\mu M_6(f_C - f_G f_T)(d_G e_T f_C - d_T e_G)$

All six vanish on a tree. On a strict sunlet all μM_i are positive. If the shared first factor in a pair is nonzero, simultaneous vanishing of (I_1, I_3) , (I_2, I_4) , or (I_5, I_6) forces, respectively, $f_G^2 = 1$, $f_T^2 = 1$, or $f_C^2 = 1$, all impossible. If all three composition margins vanish, then $f_G = f_C f_T$, $f_T = f_C f_G$, and $f_C = f_G f_T$, so $p = f_C f_G f_T$ satisfies $p = p^2$ with $p \in (0, 1)$, again impossible. Hence $\sum_{j=1}^6 I_j^2 > 0$. The active v2 certificate expands these six eight-term identities directly from the displayed map and rejects any unannounced cyclic renaming of d, e, f .

8 Three-sector incidence normalizers

For an unmarked component of degree $d \geq 3$, the one-sector exponent matrix has rows $e_1 + e_2, e_1 + e_3, e_2 + e_3, e_1 + e_4, \dots, e_1 + e_d$. Its leading block is

$$B_3 = \begin{pmatrix} 1 & 1 & 0 \\ 1 & 0 & 1 \\ 0 & 1 & 1 \end{pmatrix}, \quad \det B_3 = -2,$$

and every later row introduces one new column, so $\text{rank } B_d = d$. The full K3P normalizer matrix is

$$\text{diag}(B_d, B_d, B_d),$$

with rank $3d$ and leading determinant -8 . In each sector,

$$a_1 = \sqrt{r_{12} r_{13} / r_{23}}, \quad a_2 = \sqrt{r_{12} r_{23} / r_{13}}, \quad a_3 = \sqrt{r_{13} r_{23} / r_{12}}, \quad a_k = r_{1k} / a_1.$$

9 Capped simultaneous bridge gluing

On finitely many compactly contained local germs, let $0 < L \leq A_h \leq U$ bound every endpoint-incidence product. The active construction uses

$$\varepsilon = \min \left\{ \frac{1}{4}, \frac{L^2}{8U} \right\}, \quad z = (\varepsilon, \varepsilon, \varepsilon), \quad x_h = \frac{\varepsilon}{A_h}.$$

The effective coordinate z has principal margins at least $3/4$ and continuous-time margins at least $3\varepsilon/4$. The actual physical bridge satisfies

$$\frac{\varepsilon}{U} \leq x_h \leq \frac{\varepsilon}{L} \leq \frac{1}{8},$$

so its principal margins are at least $3/4$, while cyclically

$$x_C - x_G x_T \geq \frac{\varepsilon}{U} - \frac{\varepsilon^2}{L^2} \geq \frac{7\varepsilon}{8U} > 0.$$

Strict uniformity leaves a common three-dimensional neighborhood in which the effective coordinates vary freely and $x_h = z_h / A_h$ remains physical; this supplies the bridge-coordinate rank used in the global germ.

10 Genericity incidence argument

Let

$$R_N = \{\theta : \text{rank } D\Phi_N(\theta) < d_N\}.$$

A finite Nash constant-rank stratification of R_N gives $\dim \Phi_N(R_N) \leq d_N - 1$. Thus a full d_N -dimensional physical intersection cannot lie entirely in the source rank-drop image. For a competitor N' , stratify the incidence correspondence

$$Z_{N'} = \{(q, \theta') : q = \Phi_{N'}(\theta'), q \in \mathcal{M}_{3,+}(N)\}$$

compatibly with the regular source image and target rank loci. If the physical intersection had dimension d_N , one incidence stratum would project with rank d_N onto a relatively open regular source-image germ. The analytic constant-rank theorem gives a physical target section $s(q)$; on a regular source-parameter neighborhood, $\sigma = s \circ \Phi_N$ is exactly the section required by directed containment.

Semialgebraic dimension agrees with real-Zariski-closure dimension. If $A = \mathbb{R}[x]/I_{\mathbb{R}}(C)$, the finite faithfully flat integral extension $A \rightarrow A \otimes_{\mathbb{R}} \mathbb{C}$ preserves Krull dimension, so the corresponding complex closure is also proper. This proves that the rank-drop image, inequivalent intersections, and certified reconstruction zero loci form a proper exceptional set rather than merely a measure-zero set.

11 Fourteen-orbit and 38+2 census

The symbols S0–S4, T80, and T822 are deterministic compiler enumeration keys, not additional topology types. Explicitly, S0–S4 denote (θ_0, r_0) , (θ_0, r_1) , (θ_1, r_0) , (θ_1, r_1) , and (θ_3, r_0) ; T80 denotes the (θ_0, r_1) completion, and T822 the (θ_3, r_1) completion with selected incoming port, both sink-child ports, and the segment-4 repair port. A four-digit word gives the literal port relabeling $i \mapsto p_i$.

orbit	source	target; port permutation	rank	raw	result
H21-01	S1 (θ_0, r_1)	T80 $(\theta_0, r_1; 0132)$	$21 \rightarrow 21$	4	quartic
H21-02	S1	T80 0213	$21 \rightarrow 21$	4	rank
H21-03	S1	T80 0231	$21 \rightarrow 21$	4	quartic
H21-04	S1	T80 0312	$21 \rightarrow 21$	4	quartic
H21-05	S1	T80 0321	$21 \rightarrow 21$	2	quartic
H21-06	S1	T80 1032	$21 \rightarrow 21$	4	quartic
L20-01	S0 (θ_0, r_0)	T822 $(\theta_3, r_1; 1203)$	$20 \rightarrow 24$	2	quartic
L20-02	S0	T822 1230	$20 \rightarrow 24$	2	rank
L21a-01	S2 (θ_1, r_0)	T822 0123	$21 \rightarrow 24$	2	quartic
L21a-02	S2	T822 0132	$21 \rightarrow 24$	2	rank
L21b-01	S3 (θ_1, r_1)	T822 0123	$21 \rightarrow 24$	2	quartic
L21b-02	S3	T822 0132	$21 \rightarrow 24$	2	rank
L23-01	S4 (θ_3, r_0)	T822 0123	$23 \rightarrow 24$	2	rank
L23-02	S4	T822 0132	$23 \rightarrow 24$	2	quartic

Raw membership sums to 38. Two rank-24 (θ_3, r_1) sink swaps on the T822 rigid support, with port permutations 0132 and 1023, are separately quartic-separated. Thus $40 = 38 + 2$, with zero unresolved rows.

12 Two sink-swap records

The two post-quadratic records not absorbed into the fourteen canonical orbits compare two labelled presentations of the same rigid (θ_3, r_1) support just described. Their port permutations are 0132 and 1023. Neither transport is a labelled mixed-graph isomorphism. For each record the target pullback of Q_{23} is zero, while the source pullback has 160 terms and is nonzero at a strict rational point of minimum physical margin 7/31. The common source-pullback SHA-256 is abbreviated as `c1f4289be568...0c6f4a`. Consequently neither record yields a new symmetric move or a directed containment.

13 Polynomial separator data

For four-port coordinates, indices $0, \dots, 63$ use the lexicographic conservation-supported order

0000, 00CC, 00GG, 00TT, 0C0C, 0CC0, 0CGT, 0CTG, 0G0G, 0GCT, 0GG0, 0GTC,
 0T0T, 0TCG, 0TGC, 0TT0, C00C, C0C0, C0GT, C0TG, CC00, CCCC, CCGG, CCTT,
 CG0T, CGCG, CGGC, CGT0, CT0G, CTCT, CTG0, CTTC, G00G, G0CT, G0G0, G0TC,
 GC0T, GCCG, GCGC, GCT0, GG00, GGCC, GGGG, GGTT, GT0C, GTC0, GTGT, GTTG,
 T00T, T0CG, T0GC, T0T0, TC0G, TCCT, TCG0, TCTC, TG0C, TGC0, TGGT, TGTG,
 TT00, TTCC, TTGG, TTTT.

Each body below is a signed sum of eight degree-four monomials. A tuple (i, j, k, l) denotes $q_i q_j q_k q_l$.

body	signed index monomials
$Q_{H,a}$	$+(0, 24, 44, 52) - (0, 28, 36, 56) - (4, 24, 32, 60) + (4, 28, 40, 48)$ $+(8, 16, 36, 60) - (8, 20, 44, 48) - (12, 16, 40, 52) + (12, 20, 32, 56)$
$Q_{H,b}$	$+(0, 18, 35, 49) - (0, 19, 33, 50) - (1, 18, 32, 51) + (1, 19, 34, 48)$ $+(2, 16, 33, 51) - (2, 17, 35, 48) - (3, 16, 34, 49) + (3, 17, 32, 50)$
Q_{20}	$+(0, 10, 35, 61) - (0, 11, 34, 61) + (0, 14, 41, 51) - (0, 15, 41, 50)$ $-(1, 10, 35, 60) + (1, 11, 34, 60) - (1, 14, 40, 51) + (1, 15, 40, 50)$
Q_{21}	$+(0, 10, 44, 55) + (0, 11, 38, 60) - (0, 14, 40, 55) - (0, 15, 38, 56)$ $-(4, 10, 44, 51) - (4, 11, 34, 60) + (4, 14, 40, 51) + (4, 15, 34, 56)$
Q_{23}	$+(0, 8, 45, 53) + (0, 9, 37, 60) - (0, 12, 37, 57) - (0, 13, 40, 53)$ $-(5, 8, 45, 48) - (5, 9, 32, 60) + (5, 12, 32, 57) + (5, 13, 40, 48)$

The per-orbit transport and nonvanishing summary is:

orbit	body	marginal/representative transport	source terms	strict margin	source pullback SHA-256
H21-01	$Q_{H,a}$	omit 2; retain (0, 1, 3)	1080	2/9	ef5ed407624b...f451f81f
H21-03	$Q_{H,b}$	omit 1; retain (0, 2, 3)	192	2/9	14f7d8b5683d...a8b9da28
H21-04	$Q_{H,a}$	omit 2; retain (0, 1, 3)	1080	2/9	ef5ed407624b...f451f81f
H21-05	$Q_{H,b}$	omit 1; retain (0, 2, 3)	192	2/9	14f7d8b5683d...a8b9da28
H21-06	$Q_{H,a}$	omit 2; retain (0, 1, 3)	1080	2/9	ef5ed407624b...f451f81f
L20-01	Q_{20}	representative 1203	270	5/23	34aee883f27a...502a371
L21a-01	Q_{21}	representative 0123	270	7/31	ff97c8b01748...c97521d0
L21b-01	Q_{21}	representative 0123	270	5/23	ff97c8b01748...c97521d0
L23-02	Q_{23}	representative 0132	96	2/9	fd18a85829e2...67bbe338

All H21 character transports are the identity on the ordered labels C, G, T ; only physical ports move. Every target pullback is exactly zero. The two sink swaps use Q_{23} , have 160-term source pullbacks, strict margin 7/31, and common pullback hash `c1f4289be568...0c6f4a`. Full hashes and exact rational source values are in the bound JSON files; abbreviations above are for page fit only.

14 Directed-rank witnesses

The table gives the selected output-row set, source minor columns, strict source rank, target generator upper bound, and target compression. Exact rational determinants and labels are in `input_frozen/k3p_cloud_artifacts/k3p_directed_rank_obstructions.json` (SHA-256 `fa0ac74cde903edc422a90b5e490bd639b2e2b4c758d9d3ec10a794f1a044f42`).

orbit	selected output rows	source columns	gap	target factorization
H21-02	(3, 12, 15, 20, 27, 39, 40, 48, 51, 60, 63)	(2, 3, 4, 5, 6, 7, 8, 11, 14, 20, 23)	11 > 10	ten generators $U, V, Z, D, I, A_0, B_0, A, B, \rho$, saturated at $e_{2C}e_{2G}DI \neq 0$
L20-02	(5, 10, 15, 17, 20, 27, 30, 34, 39, 40, 45, 51, 54, 57, 60)	(3, 4, 5, 6, 7, 8, 9, 10, 11, 12, 13, 14, 18, 19)	14 > 12	ordinary-sunlet compression; omit port 3
L21a-02	(5, 15, 17, 20, 27, 39, 40, 45, 51, 57, 60)	(3, 4, 5, 6, 7, 8, 9, 10, 11, 15, 16)	11 > 10	sunlet generators with A_G, B_G absent; omit port 3
L21b-02	same as L21a-02	same	11 > 10	same ten-generator support; omit port 3
L23-01	(4, 8, 12, 16, 20, 24, 28, 32, 36, 40, 44, 48, 52, 56, 60)	(3, 4, 5, 6, 7, 8, 9, 10, 11, 12, 13, 14, 21, 22)	14 > 12	ordinary-sunlet compression; omit port 2

The exact target minors have ranks 10, 12, 10, 10, 12, respectively, and the function-field formulas prove these are upper bounds, not merely sampled ranks. These are directional selected-projection obstructions, not total model-dimension comparisons: a target can have equal or larger total rank while its indicated observable projection has function-field dimension at most 10 or 12. The H21 function-field calculation is made after saturation away from the declared physical factors, which are nonzero throughout the strict physical domain.

For H21-02, L21a-02, and L21b-02, the source minor uses the complete displayed row set. For L20-02 and L23-01, it uses the displayed set with row 60 deleted. The bound JSON records the determinant-sensitive row order and the exact nonzero rational determinant for every source minor.

15 Restoration census

certificate	minimal first layer	complete redundant forest
displayed quartet	35,758	36,006
K3P tree-sunlet SOS	606	614
K3P multihomogeneous quadratic	148	148
active K3P marginal quartic	56	56
edges/terminal rows	36,568	36,824

The imported graph forest has 997 parents, 36,568 first edges, 32 legacy structural continuation nodes, 256 depth-two edges, and 36,792 legacy leaves, with maximum depth two. K3P quartics terminate all 32 continuations at depth one, so the active minimal proof has 36,568 terminal rows. The depth-two replay remains as a redundant graph-and-algebra audit. There are zero missing/duplicate children, cycles, broken transports, or unresolved rows. The 56 all-edge K3P quartics split as 24 formerly transported quartic rows plus the 32 legacy continuation nodes, all regenerated and checked in the active K3P coordinate system.

The producer-independent replay passed with canonical payload 91a29973bcd333c05270ffd379427a8c949285f791fd5db299a83c46934e82b1. The mutation suite rejected all 20 mutations, with payload f770cecb54b459b3ff11d85b0df780e10c07b8fff92dee553ce0feb91120a9c1. The sealed manifest payload is b35346386300bb3f0816a2bbe671280f92f28ee1c5fa2eb9829e6f9fe0863c39.

16 Probe census

The 176 anchors comprise 143 isomorphisms and 33 triangle relations in 39 canonical classes.

category	one port	two ports
displayed quartet	27,758	511,266
K3P tree-sunlet SOS	99	576
isomorphism	1,915	30,969
triangle	192	1,760
raw rows	29,964	544,571
equality survivors	2,107	32,729
unresolved	0	0

The transport package has 67,741 exact transport rows and 4,379 parent restrictions, with zero incoherent choices. Ordered ledger roots and compressed-ledger SHA-256 values are in `probes/ONE_PORT_PROBE_MANIFEST.json`, `probes/TWO_PORT_PROBE_MANIFEST.json`, and `probes/GLOBAL_TRANSPORT_MANIFEST.json`.

The coherence layer is sealed against the complete replacement K3P restoration theorem by `probes/RESTORATION_MANIFEST.json`, schema `k3p-restoration-manifest-v2`, status `PASS`, with canonical payload `8c7eeeb77c09a64925fd604358b5660decca4699bd7a2fe04a0a52469a740fa7`. This binding distinguishes the 36,568 active K3P terminal rows from the 36,792 legacy/full-forest leaves and excludes historical K2P algebra.

17 Krawczyk certificate summary

The equality slice has 15 scaled pivot variables, 49 frozen direct parameters, and rational box radius 10^{-50} . The fifteen exact sparse equations have term counts

$$(5, 5, 4, 4, 3, 3, 7, 5, 4, 2, 5, 3, 7, 4, 3).$$

The maximum scaled residual at the rational center is approximately $3.02838161 \times 10^{-89}$. The exact center Jacobian determinant is approximately $-3.05693250 \times 10^{-2}$. With exact $Y = J_F(y_0)^{-1}$,

$$\max_j \frac{|K_j - y_{0,j}|}{10^{-50}} = 9.74099938 \times 10^{-41}, \quad \|I - Y J_F(X)\|_\infty \leq 8.07702308 \times 10^{-47}.$$

Both inequalities are rigorous rational interval bounds. The first is a strict Krawczyk inclusion; the second gives uniqueness inside the selected slice.

18 Sharpness rank witnesses

map	selected local columns	point determinant (decimal summary)	uniform Neumann bound
W	(0, 1, 2, 6, 7, 8, 9, 10, 11, 12, 13, 14, 15, 16, 18)	$1.30773104 \times 10^{-336}$	$1.54315210 \times 10^{-45}$
W'	(0, 1, 2, 6, 7, 8, 9, 10, 11, 12, 13, 14, 15, 16, 17)	$-6.74132416 \times 10^{-325}$	$4.58271952 \times 10^{-45}$

The smallest certified edge-eigenvalue lower bounds are approximately 4.96448×10^{-10} and 1.39520×10^{-9} ; the smallest continuous-time lower bounds are approximately 4.96448×10^{-10} and 1.39520×10^{-9} . Exact rational intervals for every edge, transition entry, inheritance probability, and minor are stored in the 9.9 MB Krawczyk certificate.

The exhaustive topology censuses are $W : (5, 2, 3)$, $W' : (7, 2, 5)$, and outer collision reference $(7, 0, 7)$.

19 Cherry determinant and all- n extension

Let ℓ be the old leaf replaced by the labelled cherry a, b , choose a retained outside leaf j , and write q' for the enlarged tensor. For $h = C, G, T$, the observable coordinates are

$$R_h = \frac{q'_{j=h, a=h, b=0, \text{others}=0}}{q'_{j=h, a=0, b=h, \text{others}=0}} = \frac{u_h q_{\ell=h, j=h, \text{others}=0}}{v_h q_{\ell=h, j=h, \text{others}=0}} = \frac{u_h}{v_h},$$

$$P_h = q'_{a=h, b=h, \text{others}=0} = u_h v_h q_{\ell=0, \text{others}=0} = u_h v_h.$$

The common factor in the ratio is strictly positive and $q_0 = 1$. Direct formal Laurent differentiation gives

$$\det \frac{\partial(R_C, P_C, R_G, P_G, R_T, P_T)}{\partial(u_C, v_C, u_G, v_G, u_T, v_T)} = \frac{8u_C u_G u_T}{v_C v_G v_T}.$$

At $u = (2/5, 4/9, 3/7)$, $v = (3/7, 5/11, 4/9)$, this is $176/25$. The smallest exact strict physical margins at these two spectra are $83/630$ and $367/2772$. The positive inverse is $u_h = \sqrt{R_h P_h}$, $v_h = \sqrt{P_h / R_h}$. Each cherry adds exactly six dimensions, yielding $15 + 6(n - 3) = 6n - 3$.

20 Clean-room architecture and H21-01 repair

The historical clean-room verifier is preserved at SHA-256 `ee5e29a2cd795d9389e8e1257ebdb9eeaa4256fb5d03e07f230bf82ba555ef91`.

It reproduces the H21-01 failure. The defect was mathematical, not a change in the expected orbit: it used rooted-DAG automorphisms instead of root-suppressed semi-directed mixed-graph automorphisms and did not conjugate the base target automorphism into the displayed frame. The corrected replay:

- binds five frozen inputs by hard-coded SHA-256 before parsing;
- reconstructs source and target incoming roles, repairs, physical ports, and port permutations from literal graphs;
- computes all seven H21 double cosets and the six nonisomorphic ones;
- replays all 38 raw Fourier-coordinate transports;
- binds each rank label to a square minor, selected rows and columns; and
- independently derives every target function-field rank upper bound.

The corrected verifier has zero Python assertion nodes and refuses optimized mode before reading inputs.

21 Mutation summary

The integrated primary verifier passes 28 of 28 active evidence entries. The final classification gate then reports `CERTIFIED_K3P_SAME` with no remaining mathematical gates. Its own fail-closed suite rejects 18 of 18 integrated mutations. The active component suites also include:

component	rejected	representative mutations
H21/fourteen-orbit gate	10	port/incoming changes, weakened rank bounds, nonsquare minor, selected-row change, optimized mode, input byte change
H21 adversarial re-audit	25	raw coverage, target conjugation, coordinate transport, graph-role and exact-identity corruptions
cross-bridge local theorem	34	missing target, partition overlap, changed single/pair/cyclic identities, record-43/60 bindings
global cut transfer	30+32	circular dependency, crossing compatibility, side-blob physicality, target openness, tree-coloring counterexamples
integrated cut claim boundary	12	universal-pointwise substitution, claim-scope drift, circular dependencies, and ordinary/optimized modes
global analytic infrastructure	18	old uncapped bridge formula, selected-minor-only genericity, $C = T$, state permutation, missing domain inequality, rank-15 triangle, orientation-specific context
probe coherence	17	missing anchor/probe/parent, reversed order, broken transport, new/inconsistent triangle, $C = T$, optimized mode
sharpness	18	rooting census, graph status, Krawczyk data, interval rank, physical margins, cherry determinant and persistence
restoration	20	missing/duplicated child, wrong parent, K2P algebra, altered SOS/quadratic/quartic, broken marginal transport
final integrated K3P-SAME gate	18	universal-pointwise substitution, rank-15 triangle, proper directed containment, stale restoration binding, K2P leakage, reversed CT transfer, missing coherent boundary transport, weakened all- n sharpness, submission-ready and optimized-mode bypasses

Each campaign records the expected and observed diagnostic; a stale hash alone is not accepted as the intended mathematical rejection when the suite is designed to rebind mutated inputs.

22 Reproduction commands

From the project root, the component-level commands used by this draft are:

```

.venv/bin/python reproducibility/verify_k3p_same_classification.py
.venv/bin/python reproducibility/test_k3p_same_classification_mutations.py

bash reproducibility/verify_primary.sh
bash clean_room/verify_clean_room.sh

.venv/bin/python \
  cut_recovery/strong_crossbridge/final_certificate/build_final_certificate.py
.venv/bin/python \
  cut_recovery/strong_crossbridge/final_certificate/verify_final_certificate.py
.venv/bin/python \
  cut_recovery/strong_crossbridge/global_transfer/verify_release.py

.venv/bin/python \
  three_port/literal_separator_v2/generate_literal_separator_v2.py
.venv/bin/python \
  three_port/literal_separator_v2/verify_literal_separator_v2.py
.venv/bin/python \
  three_port/literal_separator_v2/test_literal_separator_v2_mutations.py

.venv/bin/python restoration/regenerate_k3p_restoration.py --fresh
.venv/bin/python restoration/verify_k3p_restoration.py
.venv/bin/python restoration/test_k3p_restoration_mutations.py

.venv/bin/python probes/regenerate_k3p_probes.py
mkdir -p release/work/regeneration_ephemeral
.venv/bin/python probes/verify_k3p_probes.py --output \
  release/work/regeneration_ephemeral/K3P_PROBE_INDEPENDENT_VERIFICATION.json
.venv/bin/python probes/test_k3p_probe_mutations.py --no-write-report
.venv/bin/python probes/seal_probe_manifests.py

.venv/bin/python global_infrastructure/generate_global_infrastructure.py
.venv/bin/python global_infrastructure/verify_global_infrastructure.py
.venv/bin/python global_infrastructure/test_global_infrastructure_mutations.py

.venv/bin/python sharpness/independent_krawczyk_replay.py
.venv/bin/python sharpness/independent_topology_alln_replay.py

```

The first two commands are the sealed final mathematical classification gate and its 18-mutation fail-closed suite. The longer producer commands are listed only for component replay. The canonical clean-checkout wrappers are `reproducibility/verify_quick.sh`, `reproducibility/verify_full.sh`, and the explicit-confirmation 45-command `reproducibility/verify_regenerate_all.sh`; the last includes the hour-scale probe producer and must be allowed to finish without a second invocation. No release-archive or submission gate is claimed here.

23 Artifact hashes

artifact	SHA-256
model_domain/primary_exact_evidence.json	ac21e4f795537f251377411841d670c1bad4ce06a69ed24f596252c11cb7afb6
three_port/primary_exact_evidence.json	152e7fa25d3c81fc7c27e46e93dbb6ee11e1c96be570d5fe7a6b61eae2cc513d
three_port/literal_separator_v2/K3P_TREE_SUNLET_LITERAL_SEPARATOR_V2.json	5746324b4281a1738267ce116b3122e9156d48a6b5df37d5988451604e5f3557
bridge_fibre/K3P_BRIDGE_FIBRE_CERTIFICATE.json	bdd8e8f74a896b5031a50cad9ac97a82a03f4f821f2dc793cfb386415b1df532
marginals/K3P_MARGINAL_SUBMERSION_CERTIFICATE.json	9a90ba2e075fd20a4867e8a169aa933546b8fbca6feab23a2be7d25a24935d94

artifact	SHA-256
four_port_atlas/primary_exact_evidence.json	f4e02c74e4b4f9fbb063b13da65033a46ef45f2eecaad2b9efc1895b63afadab
clean_room/H21_01_TRANSPORT_AUDIT.json	b8a1c52a01ce0bb1b50a8ffaf78f5a300be52fde976671b2b1cc91e8fe2d7229
triangle_h14/K3P_H14_CONTEXT_CERTIFICATE.json	082f24cd26be08f248ddc6d0cf804059a27ad96477b06df0c56f8a89818bb9b9
cut_recovery/strong_crossbridge/final_certificate/STRONG_CROSSBRIDGE_FINAL_CERTIFICATE.json	643c29780219a538a5a127341ea91363aa5899d6f0f6fa1dac034889a7fdf06b
cut_recovery/strong_crossbridge/global_transfer/THEOREM_MANIFEST.json	dd0ffea14051b9f45764a87d1a96b78d8199883417ce9a4321bfef4d612e8e51
global_infrastructure/GLOBAL_INFRASTRUCTURE_MANIFEST.json	30a0040d5a3a08d4a81700bb9a6a8c29ed9f7e37b1cdb0bb1f41701389ff203e
global_infrastructure/MUTATION_CERTIFICATE.json	1fbae962f130a25ab52b065df21246a83d220d35d97472433ac7e1afe7f57888
reproducibility/primary_gate_report.json	9631325d3d08d46c25408cc002ab8503874ff027cf23009a350b1aae2cf2e703
reproducibility/K3P_SAME_CLASSIFICATION_GATE_REPORT.json	df6c41d08f40b758887ca55430a3a5dfc80579121f08df07d744340ac3ef79c1
reproducibility/K3P_SAME_CLASSIFICATION_MUTATION_REPORT.json	1305e295667408cc5dc8deed2714c06246b050e6c4fb53915c0ead74d630b52a
restoration/RESTORATION_MANIFEST.json	d8b27a5013f5ce19f5b318bf647c698600b61bdc14b812931a6fdd2fc7422fbe
restoration/K3P_RESTORATION_THEOREM_REPORT.md	9c3ea74acdc5dc4eff24d50c9f2db845215bde6b8276c72faf0a6d150f4bf7f0
restoration/K3P_RESTORATION_INDEPENDENT_VERIFICATION.json	a83454f25f37c6a83617cc8fb9360b130626564cb290b5ba6dd6bcf5bf33ac4c
restoration/K3P_RESTORATION_MUTATION_CERTIFICATE.json	f283c87ba304b43d45fff53fdca287bfb9d006956e50120b38ebb76c39a90e75
probes/K3P_PROBE_COHERENCE_CERTIFICATE.json	5c0534a0844de7362830f6ec31c1193db1b7f1c428224350b8d76d02f311b82f
probes/RESTORATION_MANIFEST.json	eec38a695fae1a8c1867fdd25e63928717f430ab6efd2a48eba23fffb94afad6
sharpness/K3P_SHARPNESS_KRAWCZYK_CERTIFICATE.json	8187174b3e0c0b3a0a55fa32595c211811c357dc223ada7a74b3033f7cae3941
sharpness/K3P_SHARPNESS_TOPOLOGY_ALL_N_CERTIFICATE.json	aa08837777445541398bed943881405530c9b5bb4f0451794a4b56b289beabc7

These are the frozen active hashes at this revision, including the final mathematical classification gate. A later release manifest must supersede this typeset table if packaging changes any byte; no release archive or submission package is asserted here.