

Triangle Hypersurfaces and a Sharp Identifiability Boundary for Level-2 K3P Networks

Alec Kriebel

Independent Researcher

ORCID: [0009-0001-9320-500X](https://orcid.org/0009-0001-9320-500X)

August 2026

Abstract

We classify regular full-dimensional stochastic containment among binary standard semi-directed strongly tree-child level-2 phylogenetic networks under the Kimura three-parameter (K3P) model. On the principal positive Fourier domain, a directed containment germ exists if and only if the two labelled networks agree after independently redirecting ordinary three-cycle factors. The same condition is equivalent to a common full-dimensional regular germ, and it remains exact in strict continuous time. Thus no proper one-sided containment occurs in the strong class, and the semi-directed topology is generically identifiable and exactly reconstructible modulo ordinary triangle redirection.

K3P has a distinct local geometry. The three ordinary triangle orientations have generic normalized rank 14, share the same irreducible eight-term quartic hypersurface $H_{14} \subset \mathbb{A}^{15}$, and meet in a common strict continuous-time smooth rank-14 germ; they do not fill an ambient-open three-leaf germ. Necessity combines three-sector bridge fibres, physical marginal submersions, a noncircular bridge-split transfer theorem, and an exact finite classification. The cut argument deliberately does not assert a universal pointwise K3P rank criterion: true cuts have rank at most four pointwise, noncuts are generically detected, and equality of cut sets is proved under source-relative containment in the strong class by 204 pointwise one-active obstructions. The remaining bounded residue consists of fourteen four-port orbits—nine polynomially separated and five directed-rank separated—plus two separately separated sink swaps.

The strong hypothesis is sharp. For every $n \geq 3$, two weakly but not strongly tree-child networks have strict continuous-time K3P images sharing a common full-dimensional regular germ of dimension $6n - 3$. The base rank-15 common point is certified by exact rational interval arithmetic and a Krawczyk inclusion. Exact certificates, separately implemented replays, and fail-closed mutation tests accompany every finite and interval claim.

Keywords. phylogenetic networks; Kimura three-parameter model; generic identifiability; directed containment; level-2 networks; strongly tree-child networks; algebraic statistics; computer-assisted proof.

MSC 2020. 92B10, 62R01, 14P10, 05C05.

1 Introduction

Phylogenetic networks represent evolutionary histories in which lineages can merge as well as split. Their statistical models are structured mixtures: at each reticulation one parent is selected, and

conditional on all such choices the site evolves on a displayed tree. Identifiability is therefore an information-limit question. Even with an exact site-pattern distribution—the infinite-data idealization—can two genuinely different network topologies describe the same full-dimensional family of observations?

The distinction between a shared point and a shared regular germ is central. A boundary degeneration, a singular intersection, or equality after complexification does not by itself create a robust stochastic ambiguity. Conversely, comparing generic dimensions alone does not exclude a directed containment when a lower-dimensional source can enter an exceptional locus of a larger target. We accordingly study a source-relative analytic containment with a physical target section. This relation records an open family of exact stochastic coincidences and retains its direction; symmetry is a conclusion of the classification, not part of the definition.

Group-based Fourier coordinates make the Kimura family especially suitable for exact analysis [6, 17]. In the K3P model the three nonzero characters C, G, T have independent edge multipliers. This is both the model’s biological flexibility and its main algebraic difficulty: bridge fibres have three independent incidence scales, marginals carry three product coordinates, and identities that were one-sector under JC or two-sector under K2P need not survive. The K3P problem is thus not a formal substitution into either companion proof.

For level one, algebraic invariants and Jacobian methods separate broad network classes and isolate the familiar ambiguity of redirecting an ordinary triangle [7, 9, 8, 4, 3]. At level two, invariant calculations for simple and semisimple networks and quartet-based combinatorial reconstruction give complementary partial results [1, 10]. Englander et al. establish the JC classification on strongly tree-child level-2 networks and give pointwise displayed-quartet tools [5]. The companion JC and K2P classifications fix the semi-directed convention, the cycle–theta topology grammar, restoration, and coherent probes [15, 14]. We reuse that model-independent graph framework but rebuild each K3P algebraic layer.

There is also a sharp warning outside the theorem class. A three-leaf tree has an exact K3P collision with a level-2 double-theta network, and the fixed theta map has ambient normalized rank 15 [13]. Thus three-taxon pointwise blob detection fails in general. That theta topology is not even weakly tree-child, so it does not locate the boundary of the strong theorem. The sharpness construction in section 13 does: ambiguity already becomes full-dimensional in the weakly but not strongly tree-child class.

Our main result is *K3P-SAME*. For binary standard semi-directed strongly tree-child level-2 networks, regular full-dimensional containment is exactly labelled topology equivalence modulo ordinary triangle redirection, both on the principal positive domain and in strict continuous time. This is the same topology quotient found under JC and K2P, but the local triangle geometry changes. Under K3P the three triangle orientations have rank 14 in the normalized 15-dimensional three-leaf Fourier chart. Their common closure is one irreducible quartic hypersurface H_{14} , and the ambiguity is a common smooth germ relative to that hypersurface, not an ambient-open germ.

The proof has six layers.

- L1.** The principal stochastic and strict continuous-time domains are handled exactly. Reversibility gives root invariance, and an isotropic near-identity factor gives strict physical subdivision.
- L2.** Bridge topology is transferred noncircularly under a directed containment. A true bridge always has flattening rank at most four; a nonbridge is generically detected by an isotropic JC slice. The missing reverse cut inclusion is then proved inside the strong class by a crossing-split dichotomy and 204 pointwise one-active K3P certificates.
- L3.** Positive bridge flattenings yield exactly three labelled incidence scales per component–bridge

incidence. Explicit analytic normalizers and strict serial splitting give a physical local product chart with no sector-permutation gauge and no holonomy.

- L4.** Every selected marginal is a three-product physical submersion. A finite semialgebraic-cover argument localizes a global relation to a fixed incoming and completion type, excluding compensation from remote factors.
- L5.** The bounded K3P residue consists of fourteen four-port directed relation orbits and two pre-lock sink swaps. Nine orbits have exact quartic separators and five have strict directed-rank obstructions. Exact restoration and coherent one-/two-port probes extend the bounded theorem to arbitrary labelled subdivision words.
- L6.** The common smooth H_{14} germ contextualizes through one labelled contraction map, and simultaneous physical bridge gluing supplies sufficiency. Semialgebraic stratification then gives generic identifiability and a terminating exact reconstruction algorithm.

One correction to an earlier program statement is load-bearing. We do *not* claim that every arbitrary strict K3P noncut has flattening rank greater than four pointwise. The exact statements used here are: true cuts have rank at most four at every strict point; each noncut has rank greater than four generically; and the cut sets of two strong-class networks are equal whenever a source-relative containment exists. The last statement is stronger than generic recovery for the purpose of containment and is proved without assuming a common bridge tree.

The finite portions are computer-assisted, but the proof boundary is explicit. Graphs, directions, incoming roles, repairs, port maps, Fourier transports, exact pullbacks, rank witnesses, restoration parentage, and probe restrictions are all serialized. A separate implementation rebuilds the load-bearing claims, and mutations test the principal failure modes. The reader supplement gives the exact census and theorem-to-certificate crosswalk; full ledgers remain in the reproducibility archive rather than in the prose.

2 Main theorems

We first state the results; definitions appear in [section 3](#). Every edge is strict and every inheritance probability belongs to $(0, 1)$.

Theorem 2.1 (K3P-SAME on the principal domain). *Let N, N' be binary standard semi-directed strongly tree-child level-2 networks on the same finite labelled leaf set. Put every edge spectrum in*

$$\mathcal{D}_{3,+} = \{(c, g, t) \in (0, 1)^3 : 1 + c - g - t > 0, 1 - c + g - t > 0, 1 - c - g + t > 0\}.$$

Then

$$\boxed{N \preceq_{3,+} N' \iff N \equiv_{\Delta} N' \iff N \bowtie_{3,+} N'}. \quad (1)$$

In particular, no proper one-sided regular full-dimensional containment occurs in this class. The conclusion is not equality of the complete stochastic images.

Theorem 2.2 (Generic structural identifiability). *For each fixed N in the class of [theorem 2.1](#), there is a proper Zariski-closed set $E_N \subsetneq \mathcal{V}_N$ such that every exact physical tensor $q \in \mathcal{M}_{3,+}(N) \setminus E_N$ determines the labelled standard semi-directed topology of N uniquely modulo $\equiv_{\Delta}$.*

Theorem 2.3 (Exact reconstruction). *There is a terminating exact procedure which, given $q \in \mathcal{M}_{3,+}(N) \setminus E_N$ for an unknown network N in the class, returns the unique structural class $[N]_{\Delta}$.*

Here exact input means an exact-real representation supporting field operations, polynomial-sign decisions, and real-closed-field quantifier elimination. No bit-complexity, conditioning, or finite-sample guarantee is asserted.

Corollary 2.4 (Strict continuous-time classification). *The equivalence (1), [theorems 2.2](#) and [2.3](#), hold after replacing $\mathcal{D}_{3,+}$ by*

$$\mathcal{D}_{3,\text{CT}} = \{(c, g, t) \in (0, 1)^3 : c > gt, g > ct, t > cg\}$$

and replacing $(3, +)$ by $(3, \text{CT})$ in the observational relations.

Theorem 2.5 (Sharpness at weak tree-childness). *For every $n \geq 3$, there are binary level-2 standard semi-directed networks $W_n, W'_n \in W_{\text{TC}} \setminus S_{\text{TC}}$ on the same labelled leaf set which are neither labelled-isomorphic nor ordinary-triangle equivalent, and whose strict continuous-time K3P images share a common full-dimensional regular analytic germ of dimension*

$$15 + 6(n - 3) = 6n - 3.$$

For $n = 3$, both normalized maps have rank 15 throughout a certified rational box containing a unique common equality-slice point.

Proposition 2.6 (Separate outer-class obstruction). *There is a three-leaf tree and a binary semi-directed level-2 double-theta network, the latter outside W_{TC} , for which the K3P tree germ is properly contained in the theta image near a strict continuous-time common point. The normalized ranks are 9 and 15, respectively, and the local theta-parameter collision locus with the tree model has dimension 23. This proposition is not the sharp class-boundary example of [theorem 2.5](#).*

Theorems [2.1–2.5](#) concern topology and image germs. They neither identify all numerical parameters nor claim that every representative of a triangle class realizes every tensor realized by another representative.

3 Conventions and the K3P model

3.1 Rooted and semi-directed networks

Definition 3.1 (Rooted binary network). *Let X be a finite set of leaf labels. A rooted binary phylogenetic network is a finite directed acyclic graph without parallel arcs in which the root has bidegree $(0, 2)$, every tree vertex has bidegree $(1, 2)$, every reticulation has bidegree $(2, 1)$, and every leaf has bidegree $(1, 0)$ and a unique label in X . Every vertex is reachable from the root. The root is the lowest stable ancestor of the leaves. A rooted presentation is tree-child when each internal vertex has a tree vertex or leaf as a child.*

Definition 3.2 (Standard semi-directed convention). *Mark every arc entering a reticulation, undirect every other arc, delete the binary root, and merge its two incident arcs into one edge, retaining at either endpoint exactly the arrowhead present before deletion. We admit the presentation only when this single suppression creates no loop or parallel edge and loses no reticulation arrowhead. No later exhaustive cleanup is part of this operation. The resulting labelled mixed graph is a standard semi-directed network. An admissible rooting is a rooted binary network whose one-step suppression is exactly that mixed graph.*

Isomorphisms preserve leaf labels, ordinary edges, retained arrowheads, and vertex roles. Restriction to a leaf subset is a distinct operation: after choosing displayed reticulation parents one may prune unlabelled dead ends and suppress unlabelled bivalent vertices. Such cleanup does not enlarge the admissible-rooting set of the original mixed graph. See [16, 11] for broader background on rooted and semi-directed conventions.

Definition 3.3 (Weak and strong tree-childness). *A standard semi-directed network is weakly tree-child if at least one admissible rooting is tree-child. It is strongly tree-child if it has an admissible rooting and every admissible rooting is tree-child. We denote these classes by W_{TC} and S_{TC} , respectively.*

Lemma 3.4 (No-omnian criterion). *In the binary fixed convention, a standard semi-directed network with an admissible rooting is strongly tree-child if and only if every tail of a retained reticulation edge is incident with two ordinary edges.*

Proof. If a tail fails the condition, it is either a reticulation with a reticulation child or an ordinary vertex tailing two retained edges. The first case is non-tree-child in every rooting. In the second, moving an admissible root to the tail's unique ordinary incidence produces an admissible rooting in which the tail has two reticulation children. Thus strong tree-childness fails. Conversely, under the incidence condition an ordinary vertex with a reticulation child retains an ordinary child, a reticulation has an ordinary child, and a root with two reticulation children would suppress to a forbidden two-arrowhead edge. Hence every admissible rooting is tree-child. This is the fixed binary specialization of the criterion used in [5, 11]. $\square$

A *bridge* is an edge whose deletion disconnects the underlying graph. A *blob* is a maximal nontrivial biconnected block. A network is *level two* when every blob contains at most two reticulations. Contracting each nontrivial blob while retaining the intervening ordinary branching components gives the labelled reduced *tree of blobs*. When a blob is cut from the network, each incident bridge becomes a labelled boundary *port*. A complete ported factor retains every physical port, including the child port below a path-sink reticulation.

Definition 3.5 (Ordinary triangle equivalence). *An ordinary triangle redirection changes only which vertex of a three-cycle factor incident with three external arms is reticulate and redirects the two arrowheads entering it. Write $N \equiv_{\Delta} N'$ when the labelled reduced trees of blobs agree, corresponding nontriangle complete factors are labelled mixed-graph isomorphic, and every remaining pair differs by an ordinary triangle redirection, with coherent boundary transports.*

3.2 Fourier parameterization and physical domains

Identify the states and characters with $\mathbb{Z}_2 \times \mathbb{Z}_2 = \{0, C, G, T\}$, with Klein-four addition. A K3P edge e has Fourier spectrum

$$\hat{f}_e = (1, c_e, g_e, t_e).$$

Inverse Fourier transformation gives

$$\begin{aligned} f_e(0) &= \frac{1 + c_e + g_e + t_e}{4}, & f_e(C) &= \frac{1 + c_e - g_e - t_e}{4}, \\ f_e(G) &= \frac{1 - c_e + g_e - t_e}{4}, & f_e(T) &= \frac{1 - c_e - g_e + t_e}{4}. \end{aligned} \tag{2}$$

The root state is uniform. At each reticulation r , one parent is chosen with probability $\lambda_r \in (0, 1)$ and the other with probability $1 - \lambda_r$. A switching σ gives a displayed tree T_σ with positive weight w_σ . For a character assignment $\mathbf{h} = (h_i)_{i \in \mathcal{X}}$,

$$q_N(\mathbf{h}) = \begin{cases} \sum_{\sigma} w_{\sigma} \prod_{e \in T_{\sigma}} \widehat{f}_e(\oplus_{i \in A_e} h_i), & \oplus_{i \in \mathcal{X}} h_i = 0, \\ 0, & \text{otherwise,} \end{cases} \quad (3)$$

where $A_e \mid A_e^c$ is the displayed-tree split. The map is polynomial in edge spectra and inheritance probabilities.

Strict positivity of (2), together with positive nontrivial spectra, is exactly the principal domain $\mathcal{D}_{3,+}$ in [theorem 2.1](#). Symmetric continuous-time K3P rates $(\alpha_C, \alpha_G, \alpha_T) > 0$ give

$$c = e^{-2(\alpha_G + \alpha_T)}, \quad g = e^{-2(\alpha_C + \alpha_T)}, \quad t = e^{-2(\alpha_C + \alpha_G)},$$

and are equivalent to the three inequalities defining $\mathcal{D}_{3,\text{CT}}$.

Write $\Theta_{3,+}(N)$ and $\Theta_{3,\text{CT}}(N)$ for the open physical parameter spaces, Φ_N for (3), and $\mathcal{M}_{3,+}(N) = \Phi_N(\Theta_{3,+}(N))$. Put

$$d_N = \max_{\theta \in \Theta_{3,+}(N)} \text{rank } D\Phi_N(\theta).$$

A source parameter is regular when its Jacobian has rank d_N .

3.3 Observational relations

Definition 3.6 (Directed containment and common germ). *Write $N \preceq_{3,+} N'$ if there are a regular source point $\theta_0 \in \Theta_{3,+}(N)$, a connected open neighborhood $U \subseteq \Theta_{3,+}(N)$ on which Φ_N has rank d_N , and a real-analytic physical target section $\sigma : U \rightarrow \Theta_{3,+}(N')$ such that*

$$\Phi_N = \Phi_{N'} \circ \sigma \quad \text{on } U.$$

Write $N \bowtie_{3,+} N'$ when the two physical images contain a common analytic germ that is regular and full-dimensional in both images and has physical analytic sections from both parameter spaces. Define $\preceq_{3,\text{CT}}$ and $\bowtie_{3,\text{CT}}$ by replacing the edge domain with $\mathcal{D}_{3,\text{CT}}$.

These relations are stronger than nonempty image intersection and different from inclusion of complex Zariski closures. The target section in $\preceq_{3,+}$ is physical but need not be target-open or target-regular. This asymmetric quantifier is important in the cut-transfer argument below.

4 Physical domain and topology transfer under containment

This section separates three claims that must not be conflated: pointwise rank at a true cut, generic detection of a fixed noncut, and equality of cut sets under strong-class containment.

Lemma 4.1 (Strict isotropic subdivision). *For $y = (c, g, t) \in \mathcal{D}_{3,+}$, put*

$$B_+(y) = \max\{c, g, t, g + t - c, c + t - g, c + g - t\} < 1.$$

For every $r \in (B_+(y), 1)$,

$$(c, g, t) = (r, r, r) \odot (c/r, g/r, t/r)$$

and both factors lie in $\mathcal{D}_{3,+}$. In strict continuous time the same holds whenever

$$r > B_{\text{CT}}(y) := \max\{c, g, t, gt/c, ct/g, cg/t\}.$$

Proof. The first six lower bounds are precisely the upper-coordinate and three inverse-Fourier inequalities for the residual triple. The isotropic factor is strict for $0 < r < 1$. In continuous time, for example, $c/r > (g/r)(t/r)$ is equivalent to $r > gt/c$; the other inequalities are cyclic. All bounds are strictly below one at an interior point. $\square$

Lemma 4.2 (Root movement). *The K3P map is unchanged by moving the root to any admissible rooting of the same standard semi-directed mixed graph.*

Proof. K3P transition matrices are symmetric and the root distribution is uniform, so reversing ordinary arcs on an old-to-new root path preserves every displayed-tree probability. Use lemma 4.1 at the new root and suppress the old one. If the old root meets a reticulation-parent edge, inspect each switching: the selected parent uses only the serial product, whereas the unselected one-child stem subtends all observed leaves and has total character zero. Every summand of (3) is unchanged. $\square$

For a split $S = A \mid A^c$, order the Fourier flattening by the bridge character $h = \oplus_{i \in A} h_i$. It is block diagonal with four character blocks.

Proposition 4.3 (True-cut rank, pointwise). *At every strict K3P parameter point of every network, if S is a bridge split, then*

$$\text{rank Flat}_S(q) \leq 4.$$

Proof. Condition on the character crossing the bridge. Each of the four character blocks is a positive rank-one outer product of the two side tensors, with the corresponding bridge multiplier in the nonzero blocks. Summing their ranks gives at most four. $\square$

Proposition 4.4 (Generic noncut recovery). *Fix a standard strongly tree-child level-2 network N and a split S that is not a bridge split. Some 5-by-5 minor of $\text{Flat}_S \circ \Phi_N$ is a nonzero polynomial. Consequently $\text{rank Flat}_S(q) > 4$ on a Zariski-open dense subset of the physical parameter domain.*

Proof. Restrict all three K3P edge sectors to the isotropic slice $c = g = t = x$. This is the relatively open strict JC locus inside the isotropic slice; it is not open in the full K3P parameter domain. The exact JC cut theorem for the same fixed mixed graph gives a strict isotropic point at which a 5-minor is nonzero [15]. Hence the full K3P pullback of that minor is not the zero polynomial. Its zero set has empty interior in the open K3P parameter domain. $\square$

Corollary 4.5 (The easy directed cut inclusion). *If $N \preceq_{3,+} N'$, then every target bridge split is a source bridge split:*

$$\text{Cut}(N') \subseteq \text{Cut}(N).$$

Proof. For a target bridge, all 5-minors vanish identically after composition with the physical target section. They therefore vanish on the source-open parameter neighborhood. If the split were a source noncut, [proposition 4.4](#) would make one pullback a nonzero polynomial, which cannot vanish on an open set. $\square$

The reverse inclusion needs genuinely K3P pointwise information, but only for a finite one-active universe.

Lemma 4.6 (One-active K3P obstruction). *For a balanced two-color split across one active strongly tree-child level-2 component, primitive-core and word compression produce exactly 216 labelled split entries. Exactly 12 are displayed by every switching. For each of the remaining 204 normalized wrong-split directions, every strict $\mathcal{D}_{3,+}$ tensor has flattening rank greater than four.*

Exact finite proof. Independent graph generation gives five primitive core templates, 72 active-labelled records, and three 2-by-2 splits per record. Direct switching masks remove the 12 displayed-by-all entries and give 204 distinct labelled direction keys, without quotienting by an automorphism. For 180 directions one selected block minor has a strictly signed Bernstein expansion on the strict K3P simplex. Twelve more are excluded by positive signed combinations of two minors. Ten use cyclic six-minor identities. The last two use two independently checked cyclic elimination certificates, one obtained by an exact labelled transport. The disjoint partition is

$$204 = 180 + 12 + 10 + 1 + 1.$$

If the total flattening had rank at most four, its four positive character blocks would each have rank one, forcing all selected minor equations to vanish. The corresponding signed or cyclic certificate contradicts that system throughout $\mathcal{D}_{3,+}$. A separately implemented verifier rebuilds the entire labelled universe and all exact arithmetic; the supplement records the package boundary and mutations. $\square$

Theorem 4.7 (Strong-class cut-set equality under containment). *If $N \preceq_{3,+} N'$ for networks in the class of [theorem 2.1](#), then*

$$\text{Cut}(N) = \text{Cut}(N').$$

Hence the labelled reduced trees of blobs agree.

Proof. By [corollary 4.5](#), only $\text{Cut}(N) \subseteq \text{Cut}(N')$ remains. Suppose a nontrivial source bridge split $S = A \mid B$ is absent from the target; a singleton split is pendant in every standard network and cannot be lost, so $|A|, |B| \geq 2$. Color target leaves by A, B , and in the target reduced tree let H_A, H_B be the two color hulls. They intersect, because an edge separating disjoint hulls would realize S as a target bridge.

If $H_A \cap H_B$ contains an edge, its target bridge split $R = C \mid D$ has a leaf in each of $A \cap C, A \cap D, B \cap C, B \cap D$; thus R crosses S . But [corollary 4.5](#) makes R a source bridge. Two edge splits

of one tree are compatible, so source bridge splits R, S cannot cross. This excludes the two-active alternative without assuming a common bridge tree.

Otherwise $H_A \cap H_B = \{v\}$ is one target component. Every branch of the target reduced tree at v is monochromatic. Indeed, if one branch contained both colors, then, because v lies in each color hull, the edge entering that branch would belong to both H_A and H_B , contrary to their intersection being only v . Moreover, membership of v in each minimal color hull forces at least two incident branches of each color: a labelled tree leaf has only one color and cannot lie in both hulls, so v is internal in each hull. Thus v has at least four relevant branches. A binary ordinary tree vertex has degree three, so v represents a nontrivial central blob.

Apply the frozen primitive and switching-compression theorem, in the form of [proposition 8.1](#) and [lemma 3.4](#), to this central blob. It retains its cycle or directed-theta core, one complete minimum strong repair, every path-sink child role, and any other required role as a zero-character completion port. Its balanced noncut coloring cannot be displayed by every switching: the exact model-independent replay has zero surviving colorings. Choose a switching that fails the color split. The ordinary tree quartet criterion then supplies actual labels $a_1, a_2 \in A$ and $b_1, b_2 \in B$, taken from four distinct monochromatic branches at v , whose induced quartet fails to display $a_1 a_2 \mid b_1 b_2$. With the completion ports set to zero character, this restriction is therefore one of the 204 graph-derived labelled wrong-split directions in [lemma 4.6](#).

It remains to check that suppressing the material between the four selected labels and the central blob stays inside the strict K3P domain. A nonempty ordinary serial path is a convolution of strictly positive $\mathbb{Z}_2^2$ transition distributions, hence is a strict K3P edge. Every component strictly between v and one selected label has only two retained boundaries. Marginalizing such a noncentral blob gives

$$M_{\text{eff}} = \sum_s w_s M_s, \quad w_s > 0, \quad \sum_s w_s = 1,$$

where M_s is the strict K3P path matrix of switching s . Each w_s is a product of local factors λ_r or $1 - \lambda_r$, so positivity and normalization follow from summing all local switches. K3P matrices form a linear family, so M_{eff} is K3P; its transition entries are positive convex combinations of positive entries and its three nontrivial Fourier eigenvalues are convex combinations of numbers in $(0, 1)$. It is therefore a strict $\mathcal{D}_{3,+}$ edge. Chains of these two-boundary mixtures and ordinary paths remain strict by convolution. Retained inheritance probabilities are λ or $1 - \lambda$, still in $(0, 1)$. Thus the compressed target quartet lies at a strict physical point of the 204-direction theorem; no target regularity or target-open marginal is being assumed.

Apply the same four-leaf marginal to the containment identity. In Fourier coordinates this sets every omitted leaf character to zero. On the source side the original bridge S survives because two selected labels lie on each side, so [proposition 4.3](#) gives rank at most four. On the identical target tensor, [lemma 4.6](#) gives rank greater than four at every strict target point. This contradiction proves the reverse inclusion. The compatible split system determines the labelled reduced tree. $\square$

Remark 4.8 (Exact claim boundary). Theorem [4.7](#) is a directional theorem for two networks in the strong class. It does not promote [proposition 4.4](#) to a universal pointwise converse for arbitrary K3P networks. No later proof uses such a converse.

5 Three-leaf K3P geometry

Normalize $q_{000} = 1$ and order the sixteen conservation-supported three-leaf coordinates as

$$(000, 0CC, 0GG, 0TT, C0C, CC0, CGT, CTG, G0G, GCT, GG0, GTC, T0T, TCG, TGC, TT0). \quad (4)$$

The resulting affine chart has dimension 15.

5.1 Trees and ordinary sunlets

A three-leaf tree with pendant spectra a, b, c has

$$q_{xyz} = a_x b_y c_z \quad (x + y + z = 0).$$

For the ordinary sunlet with reticulation adjacent to the third leaf, use the exact map

$$q_{xyz} = a_x b_y c_z [\lambda f_y d_z + (1 - \lambda) f_x e_z], \quad x + y + z = 0. \quad (5)$$

The other orientations are obtained by labelled port transport.

For two triples $L = (u, v, w)$ and $R = (u', v', w')$, write $I(L; R) = q_u q_v q_w - q_{u'} q_{v'} q_{w'}$. Define the six cubic circuits

$$\begin{aligned} I_1 &= I((000, CGT, GTC); (0TT, C0C, GG0)), \\ I_2 &= I((000, CTG, TGC); (0GG, C0C, TT0)), \\ I_3 &= I((000, GCT, TGC); (0CC, GG0, T0T)), \\ I_4 &= I((000, GTC, TCG); (0CC, G0G, TT0)), \\ I_5 &= I((000, CTG, GCT); (0TT, CC0, G0G)), \\ I_6 &= I((000, CGT, TCG); (0GG, CC0, T0T)). \end{aligned}$$

Proposition 5.1 (Tree-ordinary-sunlet separation). *The observable*

$$\mathcal{S} = \sum_{j=1}^6 I_j^2$$

vanishes identically on the three-leaf K3P tree model and is strictly positive on every ordinary three-sunlet with strict $\mathcal{D}_{3,+}$ edges and $0 < \lambda < 1$. Leaf permutations cover all three orientations.

Proof. Tree monomials make every I_j vanish. On (5), each pullback factors as a positive arm and inheritance monomial times two cross factors involving one of

$$A_C = d_C - d_G d_T, \quad A_G = d_G - d_C d_T, \quad A_T = d_T - d_C d_G.$$

Sector by sector, if $A_h \neq 0$, vanishing of the two circuits carrying that composition margin forces the two reciprocal cross ratios to equal d_h , hence $d_h^2 = 1$, impossible for $0 < d_h < 1$. If all three

A_h vanish, their product gives $p = p^2$ for $p = d_C d_G d_T \in (0, 1)$, also impossible. Therefore at least one circuit is nonzero. The six exact factorizations are printed in the supplement and regenerated from the literal map. $\square$

This separator is pointwise on the complete three-leaf maps; it does not classify a pruned mixed graph by topology alone.

5.2 The triangle hypersurface

Define the eight-term quartic

$$\begin{aligned} F_{H_{14}} = & q_{000}q_{CGT}q_{GTC}q_{TCG} - q_{000}q_{CTG}q_{GCT}q_{TGC} \\ & - q_{0CC}q_{CGT}q_{G0G}q_{TT0} + q_{0CC}q_{CTG}q_{GG0}q_{T0T} \\ & + q_{0GG}q_{C0C}q_{GCT}q_{TT0} - q_{0GG}q_{CC0}q_{GTC}q_{T0T} \\ & - q_{0TT}q_{C0C}q_{GG0}q_{TCG} + q_{0TT}q_{CC0}q_{G0G}q_{TGC}. \end{aligned} \quad (6)$$

Let $H_{14} = Z(F_{H_{14}}) \subset \mathbb{A}^{15}$.

Theorem 5.2 (Ordinary-triangle geometry). *The three labelled ordinary-triangle orientation maps have generic normalized rank 14, have the same irreducible image closure H_{14} , and share a strict continuous-time smooth rank-14 analytic germ. They do not contain an ambient-open 15-dimensional germ.*

Proof. Exact substitution of all three transported versions of (5) annihilates (6). Give edges a, b, c, d, e the isotropic spectrum $(1/2, 1/2, 1/2)$, give f the spectrum $(1/3, 1/3, 1/3)$, and set $\lambda = 1/2$. Every orientation then maps to the same tensor

$$q_0 = \left(1, \frac{1}{12}, \frac{1}{12}, \frac{1}{12}, \frac{1}{12}, \frac{1}{12}, \frac{1}{48}, \frac{1}{48}, \frac{1}{12}, \frac{1}{48}, \frac{1}{12}, \frac{1}{48}, \frac{1}{12}, \frac{1}{48}, \frac{1}{48}, \frac{1}{12}\right).$$

All edges are strict continuous-time. Exact 14-minors at the three preimages have determinants

$$-\frac{1}{760840571584512}, \quad -\frac{1}{760840571584512}, \quad \frac{1}{760840571584512}.$$

The quartic gradient at q_0 is nonzero; its six nonzero normalized components have absolute value $1/6912$. Thus H_{14} is smooth and has dimension 14 at q_0 . Every orientation differential has rank 14 and lies in the 14-dimensional tangent kernel of $dF_{H_{14}}$, so it submerses onto a relative neighborhood in H_{14} . Intersect the three neighborhoods and apply the constant-rank theorem to obtain physical analytic sections.

For irreducibility, regard the normalized quartic as linear in q_{0CC} . Its coefficient is the primitive disjoint-support binomial

$$-q_{CGT}q_{G0G}q_{TT0} + q_{CTG}q_{GG0}q_{T0T}.$$

The exponent difference is primitive, so this coefficient is irreducible. At the certified specialization the coefficient vanishes while the remainder equals -1 ; hence it does not divide the remainder.

Gauss's lemma proves that $F_{H_{14}}$ is irreducible. Since every orientation is contained in this hypersurface and contains a relative neighborhood of its smooth locus, each image closure is exactly H_{14} . None is ambient-open in $\mathbb{A}^{15}$. $\square$

For comparison, the normalized three-leaf tree map has rank 9; one exact minor is 8192/28940625. The outer-class double-theta map in [section 14](#) has rank 15. The rank-14 triangle ambiguity is therefore intermediate and must be contextualized relative to H_{14} , not to the ambient tensor chart.

Lemma 5.3 (Contextual H_{14} germ). *Replace one ordinary triangle orientation by another inside an otherwise unchanged labelled context, possibly reconnecting two triangle terminals inside a theta factor. The two complete network maps share a common germ that is full-dimensional relative to both images.*

Proof. Let $U \subset H_{14}$ be the common relative germ from [theorem 5.2](#), C a physical chart of the unchanged context, and write the common labelled multilinear contraction as

$$\Psi(u, c)(g) = \sum_{\mathbf{h} \in \mathbb{Z}_2 \times \mathbb{Z}_2^3} C(g; \mathbf{h}, c) u(\mathbf{h}).$$

Choose one point of $U \times C$ where $D\Psi$ has its generic maximal rank and shrink to a constant-rank neighborhood. Physical sections of each triangle orientation through U give the same lower rank for each contextual map; direct factorization of each map through Ψ gives the reverse inequality. A constant-rank section of Ψ , followed by the orientation sections, yields one common full-dimensional contextual germ. No tensor-product independence among the three terminals is assumed. $\square$

6 The three-sector bridge fibre

Cut every bridge of the labelled reduced tree. Its component-incidence graph is a tree T . For a component v , let P_v be its normalized Fourier boundary tensor, including one character h_e for every incident bridge, with $P_v(0) = 1$. For $e = uv$, write

$$k_e(0) = 1, \quad k_e(C) = c_e, \quad k_e(G) = g_e, \quad k_e(T) = t_e.$$

Character conservation gives the global contraction

$$Q(\mathbf{h}) = \prod_{v \in V(T)} P_v(\mathbf{h}|_v) \prod_{e \in E(T)} k_e(h_e). \quad (7)$$

Theorem 6.1 (Complete positive three-sector bridge fibre). *On the positive normalized K3P component-tensor locus, the complete fibre of (7) is exactly*

$$P_v(\mathbf{h}) \mapsto P_v(\mathbf{h}) \prod_{e \ni v} \prod_{s \in \{C, G, T\}} (a_{v,e}^s)^{1[h_e=s]}, \quad (8)$$

$$k_e(s) \mapsto \frac{k_e(s)}{a_{u,e}^s a_{v,e}^s} \quad (s = C, G, T), \quad (9)$$

with positive incidence scales and $a_{v,e}^0 = 1$. There is no additional positive continuous or discrete gauge, the action is free on every retained component, and the bridge tree has no holonomy. On physical networks the fibre is the intersection of this orbit with all local and edge inequalities.

Proof. Cut one bridge and fix $s \in \{C, G, T\}$. Its Fourier block is a positive rank-one matrix, whose factorization is unique up to one positive scalar. All-zero normalization fixes the zero-sector scalar. Unlike K2P, the three nonzero characters are observably labelled and independent; no equality or permutation is imposed. Peeling leaves of T sector by sector assigns one scale to every incidence and gives (8)–(9). Direct cancellation proves the converse, while the tree structure leaves no cycle on which a holonomy could circulate.

For freeness, a marked component has one-character anchors with identity exponent matrix. For an unmarked degree- d component, $d \geq 3$, use pair anchors

$$(1, 2), (1, 3), (2, 3), (1, 4), \dots, (1, d).$$

In one sector the leading 3-by-3 exponent block has determinant -2 , and every later row introduces one new coordinate. Its positive inverse is

$$a_1 = \sqrt{\frac{r_{12}r_{13}}{r_{23}}}, \quad a_2 = \sqrt{\frac{r_{12}r_{23}}{r_{13}}}, \quad a_3 = \sqrt{\frac{r_{13}r_{23}}{r_{12}}}, \quad a_k = \frac{r_{1k}}{a_1}. \quad (10)$$

Three block-diagonal copies have rank $3d$ and leading determinant $(-2)^3 = -8$. Positivity makes the slice analytic. The excluded unmarked degree-two stabilizer cannot occur in a retained strong-class factor: the two-boundary $K_4 - e$ theta has no tree-child rooting. Finally, a distinct-spectrum anchor such as $(q_{CC}, q_{GG}, q_{TT}) = (1/4, 1/9, 1/16)$ excludes a hidden permutation of the fixed state labels. $\square$

Lemma 6.2 (Physical local product chart). *Near every regular physical point, the quotient by the action in [theorem 6.1](#) is a physical local product chart, simultaneously on all bridges, in both $\mathcal{D}_{3,+}$ and $\mathcal{D}_{3,CT}$.*

Proof. For one bridge spectrum y , choose two isotropic endpoint factors near the identity and a compensating residual factor, using [lemma 4.1](#). All six endpoint sector coordinates may vary independently in a sufficiently small neighborhood while the residual stays strict. Do this for finitely many bridges and intersect the neighborhoods. The analytic normalizers extract local projective component tensors and effective bridge coordinates from the global tensor, while contraction is their local inverse. The same argument uses B_{CT} on the continuous-time cone. $\square$

For a complete ported factor H , quotient its normalized tensor by one positive C, G, T scale per port and write $\bar{\Phi}_H$ for a local analytic slice map. Local directed containment is defined exactly as in [definition 3.6](#), using a source-open regular germ and a physical target section. Different positive anchor charts give equivalent definitions by [theorem 6.1](#).

7 Marginal localization

Lemma 7.1 (Triple-product marginal submersion). *For every $m \geq 1$,*

$$((c_i, g_i, t_i))_{i=1}^m \mapsto \left(\prod_i c_i, \prod_i g_i, \prod_i t_i \right)$$

maps $\mathcal{D}_{3,+}^m$ onto $\mathcal{D}_{3,+}$, has differential rank three, and has local physical analytic sections. The analogous statement holds on $\mathcal{D}_{3,\text{CT}}$.

Proof. Serial composition of strict K3P transition distributions is group convolution and therefore remains strict; Fourier transformation converts it to coordinatewise multiplication. For surjectivity, choose the first $m-1$ factors isotropic and sufficiently near the identity, and put the strict residual on the final edge, as in [lemma 4.1](#). The three Jacobian rows have disjoint positive supports; derivatives with respect to (c_1, g_1, t_1) give a nonzero diagonal minor. Continuous-time surjectivity follows by using B_{CT} , or by positive coordinate power roots. $\square$

The exact graph-derived descriptor records more than ordinary serial paths. For a retained character assignment and switching σ , an edge sees the group sum below its displayed descendant mask. The complete visible signature is the array of those C, G, T values over every switching and retained assignment. Split complements agree because the total group sum is zero. Edges with the same nonzero signature enter only through their three products; zero-signature edges are invisible. A retained inheritance coordinate is transported as λ or $1 - \lambda$ according to the recorded parent order; a tensor-invisible reticulation disappears after its two switching weights sum to one.

Proposition 7.2 (Complete marginal descriptor). *Every rigid-support, restoration-prefix, one-port, and two-port restriction used in the proof factors into triple-product maps from [lemma 7.1](#), coordinate projections and permutations, and recorded parent-order complements. It is physically onto its effective selected domain, is a submersion, and has local physical analytic sections.*

Proof. Set omitted leaf characters to zero in [\(3\)](#) and group full switchings by their retained switching. Identical complete signatures have identical sector exponents in every monomial and therefore collapse to one triple product. Tensor-invisible reticulations contribute $\lambda + (1 - \lambda) = 1$; every other inheritance coordinate is transported exactly. Apply [lemma 7.1](#) independently to each visible class. $\square$

We use a standard semialgebraic fact: a semialgebraic subset of a smooth d -manifold has dimension d exactly when it has nonempty relative interior. Hence a finite semialgebraic cover of a nonempty relatively open set has one member containing a relatively open subset. This follows from cell decomposition and the frontier-dimension inequality [[2](#), Section 2.8].

Proposition 7.3 (Physical localization and no compensation). *Suppose $N \preceq_{3,+} N'$. For each pair of corresponding complete ported factors H, H' , some fixed target incoming and completion type contains a source-relative full-dimensional regular germ of the projective physical K3P model of H . Parameters in other factors cannot compensate for a local separator.*

Proof. By [theorem 4.7](#), the labelled reduced bridge trees agree. Shrink the regular source neighborhood around a nonzero maximal minor. The physical product chart of [lemma 6.2](#) contains a product box of local factor germs and bridge intervals. Fix all coordinates except one focal factor. Positive bridge factorization and the analytic normalizers extract its projective incidence orbit intrinsically from the global tensor.

Only finitely many target incoming and completion types occur in the primitive grammar. Their semialgebraic realization sets cover the focal source box because the target section realizes every point. The finite-cover fact puts a source-open subgerm into one fixed type. Intrinsic extraction is independent of remote target coordinates, so a polynomial or rank obstruction on the focal orbit cannot be cancelled elsewhere. $\square$

Lemma 7.4 (Fixed-full restoration). *Fix actual networks and a full relation $N \preceq_{3,+} N'$. Fix one omitted physical label, its source insertion edge, target attachment, and boundary transport. Marginalizing this same relation gives one enumerated child relation with source-open restriction. Exact separation of every such child therefore excludes the fixed full parent.*

Proof. Marginalization sets the restored character to zero. Pendant factors become one, serial classes multiply coordinatewise, and [proposition 7.2](#) gives a physical source-open image. The actual attachment and transport are one row of the exhaustive child construction. No abstract smaller relation is lifted and no arbitrary target deletion map is inverted. $\square$

8 Primitive factors and bounded classification

8.1 Cycle and theta cores

Move a root-containing factor along an all-tree path to a real labelled incoming boundary, using [lemma 4.2](#). Delete port arms and suppress ordinary bivalent vertices that are neither the local source nor a reticulation sink, recording the removed port-bearing subdivisions as ordered words.

Proposition 8.1 (Cycle–theta primitive theorem). *Every nontrivial complete blob factor in the strong level-2 class has a cycle core or one of four directed theta cores $\theta_0, \theta_1, \theta_2, \theta_3$. It is recovered uniquely from the core, one labelled ordered port word on each directed segment, and one child port below every path-sink reticulation.*

Proof. Let r, v, e be the numbers of reticulations, internal vertices, and blob edges after port arms are removed. Summing indegrees gives $e = v + r - 1$, hence

$$\sum_w (\deg_B(w) - 2) = 2e - 2v = 2(r - 1).$$

For $r = 1$, every blob vertex has degree two and the core is a cycle. For $r = 2$, exactly two vertices have degree three; biconnectedness makes the blob three internally disjoint paths between them, hence a theta. The incoming boundary is ordinary and determines a unique local tree source. Acyclicity allows at most one reticulate pole. Separating the cases of one reticulate pole versus two tree poles, and whether the source shares a path with an internal sink, gives exactly $\theta_0, \dots, \theta_3$. This is the directed ported refinement of the two underlying level-2 generators in [\[12\]](#). The full event-placement proof is model-independent and is replayed from the frozen topology package. $\square$

The directed segments and minimum occupied sets required by [lemma 3.4](#) are:

core	directed segments in index order	minimum occupied sets
cycle	$S \rightarrow X, S \rightarrow X$	$\{0\}, \{1\}$
θ_0	$S \rightarrow U, S \rightarrow V, U \rightarrow X, V \rightarrow X, U \rightarrow V$	$\{2, 3\}, \{3, 4\}$
θ_1	$S \rightarrow U, S \rightarrow X, V \rightarrow X, U \rightarrow V, U \rightarrow V$	$\{2, 3\}, \{2, 4\}$
θ_2	$S \rightarrow U, S \rightarrow V, U \rightarrow X_0, V \rightarrow X_0, U \rightarrow X_1, V \rightarrow X_1$	$\{2, 3\}, \{2, 5\}, \{3, 4\}, \{4, 5\}$
θ_3	$S \rightarrow U, S \rightarrow X_0, V \rightarrow X_0, U \rightarrow X_1, V \rightarrow X_1, U \rightarrow V$	$\{2\}, \{4\}$

The corresponding obstruction clauses are $\{0, 1\}$ for a cycle; $\{3\}, \{2, 4\}$ for θ_0 ; $\{2\}, \{3, 4\}$ for θ_1 ; $\{2, 4\}, \{3, 5\}$ for θ_2 ; and $\{2, 4\}$ for θ_3 . The displayed sets are precisely their minimum transversals.

For a target core with m_H directed segments, q_H path-sink roles, and r_H repair tags, the exact number of target completions using k selected boundaries and selected-incoming flag ε is

$$C(k, \varepsilon) = \sum_H r_H \sum_{j=0}^{q_H} \binom{q_H}{j} \binom{k - \varepsilon - j + m_H - 1}{m_H - 1}. \quad (11)$$

The tuples (m_H, q_H, r_H) are $(2, 1, 1), (5, 1, 2), (5, 1, 2), (6, 2, 4), (6, 2, 2)$. Thus the four-port target grammar has 831 selected-incoming and 1,983 marginalized-incoming completions.

8.2 The exact four-port residue

Six rigid K3P source supports have normalized ranks

$$20, 21, 21, 21, 23, 24.$$

After pointwise, quadratic, graph-isomorphism, and ordinary-triangle filters, the only nonterminal four-port residue consists of the following 14 canonical directed orbits. Here the arrow in the rank column is source to target, and “H14” means a transported marginal of (6).

orbit	source	target	rank	raw	exact certificate
H21-01	θ_0, r_1	$\theta_0, r_1; 0132$	$21 \rightarrow 21$	4	H14 quartic
H21-02	θ_0, r_1	$\theta_0, r_1; 0213$	$21 \rightarrow 21$	4	11 > 10 rank
H21-03	θ_0, r_1	$\theta_0, r_1; 0231$	$21 \rightarrow 21$	4	H14 quartic
H21-04	θ_0, r_1	$\theta_0, r_1; 0312$	$21 \rightarrow 21$	4	H14 quartic
H21-05	θ_0, r_1	$\theta_0, r_1; 0321$	$21 \rightarrow 21$	2	H14 quartic
H21-06	θ_0, r_1	$\theta_0, r_1; 1032$	$21 \rightarrow 21$	4	H14 quartic
L20-01	θ_0, r_0	$\theta_3, r_1; 1203$	$20 \rightarrow 24$	2	quartic
L20-02	θ_0, r_0	$\theta_3, r_1; 1230$	$20 \rightarrow 24$	2	14 > 12 rank
L21a-01	θ_1, r_0	$\theta_3, r_1; 0123$	$21 \rightarrow 24$	2	quartic
L21a-02	θ_1, r_0	$\theta_3, r_1; 0132$	$21 \rightarrow 24$	2	11 > 10 rank
L21b-01	θ_1, r_1	$\theta_3, r_1; 0123$	$21 \rightarrow 24$	2	quartic
L21b-02	θ_1, r_1	$\theta_3, r_1; 0132$	$21 \rightarrow 24$	2	11 > 10 rank
L23-01	θ_3, r_0	$\theta_3, r_1; 0123$	$23 \rightarrow 24$	2	14 > 12 rank
L23-02	θ_3, r_0	$\theta_3, r_1; 0132$	$23 \rightarrow 24$	2	quartic
SINK-0132	source 5	target 822; 0132	$24 \rightarrow 24$	1	quartic
SINK-1023	source 5	target 822; 1023	$24 \rightarrow 24$	1	quartic

The six H21 rows are the nonisomorphic double cosets of the repaired θ_0 source; the seventh double coset is isomorphic. The complete post-quadratic accounting is

$$\boxed{40 = 38 + 2.} \tag{12}$$

The 38 raw records belong to the fourteen named orbits; the final two table rows are rank-24 θ_3 sink-swap presentations. Neither is a labelled graph isomorphism, and the same exact eight-term quartic has zero target pullback and nonzero strict source value on each.

Theorem 8.2 (Fourteen-orbit classification). *The polynomially separated orbits are*

$$\begin{aligned} &H21-01, H21-03, H21-04, H21-05, H21-06, \\ &L20-01, L21a-01, L21b-01, L23-02, \end{aligned}$$

and the directed-rank-separated orbits are

$$H21-02, L20-02, L21a-02, L21b-02, L23-01.$$

The two sink swaps are polynomially separated. Thus the bounded residue has zero unresolved directions, no new symmetric K3P move, and no proper directed K3P containment.

Exact finite proof. For each of the nine polynomial orbits, an exact characteristic-zero quartic vanishes on the complete target map and has a nonzero value at a strict rational source point. The first five are transported H_{14} marginal quartics; the remaining four are multigraded eight-term quartics. Exact graph and Fourier transports cover every raw member.

For each of the five rank orbits, a selected source projection has a nonzero exact Jacobian minor of rank 11 or 14. The target projection factors rationally through 10 or 12 generators, respectively, giving the strict upper bound. The H21 target formulas are checked after saturation by the declared nonzero physical factors; the other four targets are compressed ordinary-sunlet projections. A source-relative open containment cannot lie inside the lower-dimensional target projection.

The clean-room implementation reconstructs all six sources, all 2,814 target completions, seven H21 double cosets, all 38 coordinate transports, and both sink swaps. The original H21-01 failure is diagnosed as the use of rooted-DAG automorphisms in place of root-suppressed semi-directed mixed-graph automorphisms, compounded by failure to conjugate a base target automorphism into the displayed frame. The corrected mixed-graph transport passes and the historical verifier remains preserved. Exact rows, columns, bodies, source evaluations, and hashes appear in the supplement. $\square$

The bounded result is intentionally direction-sensitive. A target of larger generic dimension is not automatically a containing model, and a polynomial identity is transported through the literal labelled graph rather than attached only to a topology name.

9 Restoration and arbitrary words

The four-port theorem classifies rigid supports, not arbitrary strings of labelled subdivisions along core segments. Two exact extensions close that gap: fixed-full restoration recovers roles omitted by a selected support, and overlapping probes recover every remaining port and its order.

9.1 Fixed-full restoration

The restoration forest is imported only as model-independent graph data: parentage, layer order, source and target identities, dummy roles, insertion sites, and boundary transports. Every K2P polynomial and sector equality is discarded. The K3P proof regenerates the selected maps and certificates from the literal graphs, using [lemma 7.4](#) to connect each child to the original full relation.

Proposition 9.1 (K3P restoration closure). *Every one of the 36,568 first-layer fixed-full restoration children is excluded by an exact K3P observable. Their minimal K3P census is*

<i>certificate</i>	<i>minimal first layer</i>	<i>all-edge replay</i>
<i>displayed-quartet mismatch</i>	<i>35,758</i>	<i>36,006</i>
<i>three-sector tree-sunlet sum of squares</i>	<i>606</i>	<i>614</i>
<i>K3P multihomogeneous quadratic</i>	<i>148</i>	<i>148</i>
<i>active K3P marginal quartic</i>	<i>56</i>	<i>56</i>
<i>total</i>	<i>36,568</i>	<i>36,824</i>

The 32 nodes that were continuations in the inherited graph forest are already terminated by K3P quartics. The full forest is nevertheless replayed as a redundant check: it has 36,824 edges, 256 depth-two edges, 36,792 legacy leaves, maximum depth two, and zero missing children, duplicates, cycles, broken transports, or unresolved rows.

Proof. The 614 rows formerly assigned a two-sector $\mathcal{T}_i$ identity are replaced by the literal K3P three-leaf maps and the six-circuit theorem of [proposition 5.1](#); 606 occur at depth one and 8 in the redundant depth-two replay. The 148 quadratic bodies are regenerated with independent C, G, T variables. The 24 formerly transported K2P quartics and the 32 former continuations use active L20-01/H21-01 K3P quartics, giving the all-edge quartic count $56 = 24 + 32$. Every row is bound to its exact parent transport and direct marginal. Thus no equality such as $C = T$ enters the proof. A producer-independent replay verifies every row, and the fail-closed mutation suite rejects all 20 prescribed corruptions. $\square$

9.2 Coherent probes

The probe input contains 176 physical equality anchors: 143 labelled isomorphisms and 33 ordinary-triangle relations, grouped into 39 canonical anchor classes. Every physical mixed edge is an attachment site, including pendant arms, reticulation-incoming edges, and the root-suppressed segment.

Proposition 9.2 (One- and two-port coherence). *The complete K3P probe ledgers have the exact censuses*

$$\begin{aligned}
29,964 &= 27,758 \text{ quartet} + 99 \text{ tree-sunlet} + 1,915 \text{ isomorphism} + 192 \text{ triangle}, \\
544,571 &= 511,266 \text{ quartet} + 576 \text{ tree-sunlet} + 30,969 \text{ isomorphism} + 1,760 \text{ triangle}.
\end{aligned}$$

There are 2,107 one-port equality survivors and 32,729 two-port equality survivors, zero unresolved relations, 67,741 exact transports, 4,379 parent restrictions, and zero incoherent triangle choices.

One-port restrictions determine the segment of every omitted label; two-port restrictions determine the order of every pair on a common segment. They assemble to one labelled word on every segment, modulo one coherent ordinary triangle redirection. At most nine physical tensor ports are selected.

Proof. Fix one anchor transport. Every non-equality one-port comparison has a direct quartet or K3P tree–sunlet separator, so an equality child locates the new port relative to the rigid support. Every equality two-port comparison restricts to its exact one-port parent and has its reversed marginal in the ledger; this fixes pairwise order. Because the comparisons arise from actual finite words, their orders are transitive and reconstruct a unique total word on each segment.

If a probe subdivides a triangle edge, its appropriate restriction loses the triangle and forces literal orientation agreement. Otherwise it inherits the same stored triangle from the anchor. No isomorphic parent creates a new triangle, and all 1,760 two-port triangle equalities transport the same parent triangle. Independent streaming replay checks every row and parent. $\square$

Combining the bounded theorem, restoration, and probes gives the exact local statement needed globally.

Theorem 9.3 (Complete local factor classification). *Let H, H' be complete ported cycle/theta factors induced by networks in the strong level-2 class, with arbitrary admissible labelled subdivision words and independently chosen incoming presentations. Then*

$$H \preceq_{3,+} H' \iff H \cong H' \text{ as labelled mixed graphs } \text{ or } H \equiv_{\Delta} H'.$$

No proper one-sided projective local containment occurs.

Proof. Marginal localization fixes one target completion type. The rigid support is handled by [theorem 8.2](#) and the earlier exact terminal filters. [Proposition 9.1](#) discharges every fixed-full parent, and [proposition 9.2](#) reconstructs arbitrary words and the global triangle transport. The converse is immediate for labelled isomorphism and follows from the relative common H_{14} germ for an ordinary triangle. $\square$

10 Global classification

We now prove the main equivalence.

Proof of [theorem 2.1: necessity](#). Assume $N \preceq_{3,+} N'$. The noncircular cut-transfer theorem [theorem 4.7](#) gives equality of the labelled bridge splits and hence the same labelled reduced tree of blobs. The complete bridge fibre and its physical product chart extract corresponding projective local factors with exactly three incidence gauges and no holonomy. Physical localization [proposition 7.3](#) fixes one target incoming/completion type for each source-open focal germ and excludes remote compensation. The complete local classification [theorem 9.3](#) then makes every corresponding factor either labelled-isomorphic or ordinary-triangle related. The one-/two-port transports reconstruct every segment word and make all triangle choices coherent. Thus $N \equiv_{\Delta} N'$. $\square$

It remains to realize the structural relation physically and at full local dimension.

Lemma 10.1 (Simultaneous physical bridge gluing). *Suppose corresponding local factors have one common projective K3P germ, through isomorphism or lemma 5.3. After shrinking finitely many local germs, their contractions along the common bridge tree form a common full-dimensional regular global germ, both on $\mathcal{D}_{3,+}$ and on $\mathcal{D}_{3,\text{CT}}$.*

Proof. Relative to fixed analytic bridge slices, let $A_h = a_{u,e}^h a_{v,e}^h$ be the endpoint incidence product on either network and any bridge, with $h = C, G, T$. On compactly contained local germs choose uniform bounds $0 < L \leq A_h \leq U$. Put

$$\varepsilon = \frac{L^2}{4U}, \quad z_C = z_G = z_T = \varepsilon, \quad x_h = \frac{\varepsilon}{A_h}.$$

Then

$$\frac{L^2}{4U^2} \leq x_h \leq \frac{L}{4U} \leq \frac{1}{4}.$$

Every principal-domain composition margin is at least $1 - L/(2U) \geq 1/2$, and every continuous-time margin is at least

$$\frac{L^2}{4U^2} - \frac{L^2}{16U^2} = \frac{3L^2}{16U^2} > 0.$$

Thus the same effective isotropic bridge spectrum works simultaneously for both networks and all bridges. Incidence factors cancel in (7). The physical product extraction in lemma 6.2 is a local inverse, so the contraction has the expected rank and the common image germ is full-dimensional. $\square$

Proof of theorem 2.1: sufficiency. Assume $N \equiv_{\triangle} N'$. Transport physical parameters across every labelled isomorphism. For each redirected triangle use the same smooth relative H_{14} germ and its physical analytic sections; choose the generic rank once in the joint contextual contraction, as in lemma 5.3. Apply lemma 10.1 to all bridges simultaneously. The resulting common germ is regular and full-dimensional in both complete network images, so $N \bowtie_{3,+} N'$. A common germ with physical sections gives the directed relation in both directions by definition. This proves (1). Since $\equiv_{\triangle}$ is symmetric, proper one-sided containment is impossible. $\square$

The triangle part of this proof is full-dimensional *relative to each network image*. No step replaces H_{14} by an ambient-open 15-dimensional triangle model.

11 Genericity and reconstruction

Let

$$\mathcal{V}_N = \overline{\Phi_N(\mathbb{C}^{m_N})}^Z$$

be the complex Zariski closure of the polynomial K3P map. It is irreducible as the closure of the image of an irreducible affine space. Its dimension is the generic complex Jacobian rank and also d_N , because a nonzero real Jacobian minor cannot vanish throughout the Euclidean-open physical domain.

Proof of theorem 2.2. For fixed leaf count n , only finitely many labelled networks occur in the class. Indeed, choosing tree or leaf children from the root and from each reticulation produces $r+1$ disjoint terminal tree paths, so $r \leq n-1$. If t is the number of nonroot tree vertices, degree counting gives $t = n + r - 2$, and the rooted presentation has

$$1 + t + r + n = 2n + 2r - 1 \leq 4n - 3$$

vertices.

For a competitor $N' \not\equiv_{\Delta} N$, the physical intersection $\mathcal{M}_{3,+}(N) \cap \mathcal{M}_{3,+}(N')$ is semialgebraic by Tarski–Seidenberg [2]. If it had dimension d_N , a finite Nash stratification compatible with the source and target rank loci would contain a d_N -dimensional regular source-image stratum and an incidence stratum projecting with rank d_N . The analytic constant-rank theorem would give a physical target section over a source-relative open regular germ, hence $N \preceq_{3,+} N'$, contradicting theorem 2.1. Every inequivalent intersection therefore has dimension at most $d_N - 1$.

Take the finite union of the complex Zariski closures of these intersections, the singular locus of $\mathcal{V}_N$, the closure of the source rank-drop image, and the certified reconstruction-test zero loci that are nonidentically zero on the intended source stratum. Semialgebraic dimension agrees with the dimension of its real Zariski closure, and extension from $\mathbb{R}$ to $\mathbb{C}$ preserves dimension. Every member is proper; a finite union of proper closed sets cannot fill irreducible $\mathcal{V}_N$. Call the union E_N . Outside it, every realizing topology is triangle-equivalent to N . $\square$

The generic cut step in this proof uses proposition 4.4, not a universal pointwise converse. Since there are finitely many candidate splits for fixed N , all noncut minors are simultaneously nonzero outside a proper algebraic subset.

Proof of theorem 2.3. Given an exact Fourier tensor outside E_N , apply the following finite procedure.

- R1.** Fourier-transform the exact pattern tensor.
- R2.** Test the finitely many split flattenings. By propositions 4.3 and 4.4, recover the compatible bridge-split system and build the labelled reduced tree.
- R3.** Use the six-circuit sum of squares to distinguish ordinary degree-three components from ordinary sunlets.
- R4.** Factor positive bridge blocks in the C, G, T sectors and impose (10); recover each projective local tensor orbit and normalized effective bridge spectrum.
- R5.** Enumerate the finitely many rigid-support candidates compatible with the recovered tree and apply the exact pointwise, quartic, and rank tests.
- R6.** Follow only the exact fixed-full restoration records and their stored transports.
- R7.** Use the one-port segment deck and two-port order deck to recover every labelled subdivision word. No selected tensor uses more than nine physical ports.
- R8.** Assemble coherent mixed-graph candidates and group them into ordinary triangle classes. For each finite class $\mathcal{C}$, decide the existential semialgebraic statement

$$q \in \bigcup_{H \in \mathcal{C}} \mathcal{M}_{3,+}(H).$$

Exactly one class is feasible outside E_N ; return its canonical representative.

Every loop is finite, and real-closed-field quantifier elimination terminates under the exact-input convention. The output is a topology class, not a numerically stable estimator and not a recovery of individual edge parameters inside the bridge fibre. $\square$

12 Strict continuous time

The strict continuous-time cone $\mathcal{D}_{3,\text{CT}}$ is a nonempty Euclidean-open subset of $\mathcal{D}_{3,+}$. To see the latter inclusion directly, put

$$u = \sqrt{gt/c}, \quad v = \sqrt{ct/g}, \quad w = \sqrt{cg/t}.$$

Then $u, v, w \in (0, 1)$, $(c, g, t) = (vw, uw, uv)$, and

$$1 + c - g - t = 1 + vw - u(v + w) > (1 - v)(1 - w) > 0,$$

with the other two inequalities cyclic. Every generic maximal Jacobian minor has the same rank on $\mathcal{D}_{3,\text{CT}}$ as on $\mathcal{D}_{3,+}$, because a nonzero polynomial cannot vanish on the nonempty open continuous-time parameter domain.

Proof of [corollary 2.4](#). Because $\mathcal{D}_{3,\text{CT}}$ is Euclidean-open in $\mathcal{D}_{3,+}$, a source-open strict continuous-time containment witness is also a principal-domain containment witness. Necessity therefore follows from [theorem 2.1](#); the discussion below verifies that the constructive and generic ingredients also remain inside the strict continuous-time domain.

Root movement, true-cut rank, the 204 pointwise obstructions, and the tree–sunlet sum of squares hold throughout $\mathcal{D}_{3,+}$, hence throughout $\mathcal{D}_{3,\text{CT}}$. The isotropic slice used for generic noncut recovery contains strict continuous-time points. Triple-product marginal sections and physical local products are supplied by the continuous-time part of [lemmas 4.1](#) and [7.1](#). Each polynomial or rank witness remains nonzero on a dense open subset of $\mathcal{D}_{3,\text{CT}}$.

The common triangle preimage in [theorem 5.2](#) is strict continuous-time. The simultaneous bridge construction in [lemma 10.1](#) has the uniform positive lower margin $3L^2/(16U^2)$. Thus necessity and sufficiency both restrict to $\mathcal{D}_{3,\text{CT}}$, and the same semialgebraic genericity and exact reconstruction arguments apply. $\square$

No boundary case $c = gt$, $g = ct$, $t = cg$, a zero eigenvalue, or an inheritance probability in $\{0, 1\}$ is included.

13 Sharpness

The sharpness construction is independent of the fourteen-orbit atlas. Its three-leaf base pair has rooted presentations

$$\begin{aligned} W : \quad & rS, rL_0, SU, SV, UX, VZ, ZX, UV, ZL_1, XL_2, & \text{Ret}(W) = \{V, X\}, \\ W' : \quad & rS, rL_0, SU, SX_0, VX_0, UX_1, VX_1, UV, X_0L_1, X_1L_2, & \text{Ret}(W') = \{X_0, X_1\}. \end{aligned}$$

Suppress r under [definition 3.2](#) and retain every reticulation arrowhead.

Proposition 13.1 (Topology of the base pair). *The mixed graphs W, W' are simple, binary, level two, and lie in $W_{\text{TC}} \setminus S_{\text{TC}}$. Their exhaustive rooting censuses*

$$(\# \text{admissible}, \# \text{tree-child}, \# \text{non-tree-child})$$

are

$$W : (5, 2, 3), \quad W' : (7, 2, 5).$$

They are labelled nonisomorphic and not ordinary-triangle equivalent.

Proof. Exact enumeration orients every ordinary edge for every candidate root edge, then checks binary degree, acyclicity, reachability, the lowest-stable-ancestor condition by dominators, and tree-childness. The displayed rooting supplies a tree-child witness and another admissible rooting leaves an omnian, giving weak but not strong status. Exact labelled mixed-graph comparison finds no isomorphism. Even after all internal arrowhead flags are forgotten, the underlying labelled graphs have no isomorphism; triangle redirection cannot change the underlying graph. $\square$

13.1 The certified common rank-15 point

Let $y \in \mathbb{R}^{15}$ be the scaled pivot variables in the equality system

$$F_i(y) = s_i(q_i(W; x_W(y)) - q_i(W'; x_{W'}(y))) = 0, \quad 1 \leq i \leq 15,$$

for the fifteen nonconstant conservation-supported three-leaf K3P coordinates. The literal maps have 64 direct parameters: ten edge spectra and two inheritance probabilities on each network. Fifteen are pivots and the other 49 are frozen at exact rational values.

Proposition 13.2 (Krawczyk sharpness certificate). *There is a rational center y_0 and the box*

$$X = \prod_{j=1}^{15} [y_{0,j} - 10^{-50}, y_{0,j} + 10^{-50}]$$

such that:

- (i) *the Krawczyk operator maps X strictly into its interior and the equality system has a unique root in X ;*
- (ii) *both normalized network maps have rank 15 throughout X ;*
- (iii) *all edge spectra, transition probabilities, inheritance probabilities, and strict continuous-time margins remain positive throughout X .*

At the common tensor, the two images share an ambient-open regular 15-dimensional germ.

Proof. Exact rational Gauss–Jordan elimination constructs $Y = J_F(y_0)^{-1}$. Directed rational interval arithmetic encloses $J_F(X)$ and forms

$$K(y_0, X) = y_0 - YF(y_0) + (I - YJ_F(X))(X - y_0).$$

Every component lies strictly inside X . The largest normalized distance from the box center is $9.74099938 \times 10^{-41}$, and

$$\|I - YJ_F(X)\|_\infty \leq 8.07702308 \times 10^{-47} < 1.$$

The inclusion gives existence; the norm bound makes every mean Jacobian in the convex box invertible and gives uniqueness in this equality slice.

For each 15-by-32 local network Jacobian, exact row reduction selects a 15-minor. Neumann bounds throughout X are at most $1.54315210 \times 10^{-45}$ for W and $4.58271952 \times 10^{-45}$ for W' , excluding zero. The smallest exact continuous-time lower bounds are positive (approximately 4.96×10^{-10} and 1.40×10^{-9}). The complete certificate stores rational intervals for every inequality, not only these summaries. The submersion theorem now gives an ambient-open output neighborhood for each map, whose intersection is the common regular germ. $\square$

The uniqueness in [proposition 13.2](#) concerns only the selected 15-variable equality slice; it is not global numerical-parameter identifiability.

13.2 Identical K3P cherry substitution

Replace the same labelled leaf on both networks by the same labelled cherry. Let the new pendant spectra be $u = (u_C, u_G, u_T)$ and $v = (v_C, v_G, v_T)$. For each nonzero character h , Fourier conservation supplies the tensor observables

$$R_h = u_h/v_h, \quad P_h = u_h v_h.$$

Lemma 13.3 (Six-dimensional cherry inverse). *On the positive branch,*

$$\det \frac{\partial(R_C, P_C, R_G, P_G, R_T, P_T)}{\partial(u_C, v_C, u_G, v_G, u_T, v_T)} = \frac{8u_C u_G u_T}{v_C v_G v_T} \neq 0.$$

Thus one identical cherry adds exactly six dimensions to a common regular germ. At

$$u = (2/5, 4/9, 3/7), \quad v = (3/7, 5/11, 4/9),$$

both spectra are strict continuous-time and the determinant is 176/25.

Proof. The determinant factors into three 2-by-2 sector blocks. Its direct Laurent-polynomial expansion gives the displayed formula. The inverse is

$$u_h = \sqrt{R_h P_h}, \quad v_h = \sqrt{P_h / R_h}.$$

After recovering these six coordinates, divide retained-cherry Fourier coordinates by their nonzero pendant factors to recover the old tensor. Thus the new map has at most six new parameter directions and at least six locally observable directions. $\square$

Proof of theorem 2.5. The base case follows from [propositions 13.1](#) and [13.2](#). Repeatedly apply [lemma 13.3](#). A tree-child base rooting lifts; the old omnian and its incident arcs remain unchanged; the three new edges are bridges, so the blobs and level remain unchanged. Contracting the uniquely labelled newest cherry recovers the previous graph. Hence any enlarged isomorphism or triangle equivalence would descend to one for the base pair, which does not exist. The dimension is $15 + 6(n - 3) = 6n - 3$. $\square$

Therefore “strongly” in [theorem 2.1](#) cannot be weakened to “weakly,” even in strict continuous time. The theorem does not say that every weakly tree-child network is ambiguous.

14 Outer-class tree–double-theta obstruction

The separate tree–theta construction of [\[13\]](#) uses a three-leaf level-2 theta blob with two reticulations and four switchings. At an exact algebraic point its core mixture factors as

$$M_{y,z} = P_{y+z} B_y B_z,$$

so, after including the common pendant factors, the network tensor is a three-leaf tree tensor. All inverse-Fourier transition entries are strict. The fixed normalized theta map has a nonzero 15-by-15 Jacobian determinant

$$\frac{h(10h^2 + 1)}{2^6 1^3 4^5 5^{14}} > 0, \quad h = 5^{-1/4},$$

whereas the tree map has rank 9. The preimage theorem therefore makes the theta-parameter locus mapping into the tree model a smooth 23-dimensional submanifold of codimension six. A certified tangent and the real-analytic implicit-function theorem perturb the collision into the strict continuous-time cone.

Because the theta map is a submersion at the common point, its image contains an ambient-open neighborhood. A smaller tree output germ lies inside that neighborhood and has a physical analytic theta section, proving the proper directed containment in [proposition 2.6](#).

This example does not contradict [theorem 2.1](#). Exhaustive root enumeration gives the theta mixed graph census $(7, 0, 7)$: it has no tree-child admissible rooting and lies outside W_{TC} . It is therefore an outer obstruction, not the sharp transition from strong to weak tree-childness. It also explains why no proof here treats arbitrary three-leaf nontrivial blobs as pointwise detectable.

15 A unified Kimura-family perspective

The completed JC, K2P, and K3P classifications have the same structural quotient but different local analytic geometry. The comparison below records only results proved in the three companion programs [\[15, 14\]](#); it is not an extrapolation to other group-based models.

feature	JC	K2P	K3P
independent nonzero character sectors	1	2	3
bridge scales per component incidence	1	2	3
ordinary-triangle normalized local dimension	4	9	14
triangle image near the common point	ambient	ambient	quartic H_{14}
certified weak-class ambiguity dimension	$2n + 1, n \geq 4$	$4n - 3, n \geq 3$	$6n - 3, n \geq 3$
strong-class topology quotient	$\equiv \Delta$	$\equiv \Delta$	$\equiv \Delta$
proper directed containment in strong class	none	none	none

K3P therefore agrees topologically with the two symmetry-reduced models but not geometrically. Its ordinary triangle loses one ambient dimension even though its three Fourier sectors are independent; the common ambiguity is the smooth part of an irreducible quartic hypersurface. Conversely, each identical cherry exposes six new directions, two per sector, accounting for the all- n sharpness dimension.

The common conceptual boundary is strong tree-childness: inside it, positive bridge factorization, local factor classification, and coherent probes leave only ordinary triangle redirection; immediately outside it, robust full-dimensional ambiguities occur. This synthesis is restricted to JC, K2P, and K3P on the domains and network class stated in their respective theorems. No theorem for arbitrary finite groups, arbitrary state-label symmetries, or signed Fourier components is asserted.

16 Scope and limitations

The result is an exact infinite-data information theorem. It assumes a site-pattern tensor generated exactly by the stated model and classifies the semi-directed topology, not all numerical parameters. In particular, incidence gauges in [theorem 6.1](#) prevent the topology theorem from identifying individual physical bridge multipliers.

The theorem is restricted to:

- binary standard semi-directed networks under the fixed one-step root-suppression convention;
- level at most two;
- strong tree-childness for the classification;
- positive K3P Fourier eigenvalues and strictly positive transition probabilities;
- inheritance probabilities strictly between zero and one;
- fixed observable state labels C, G, T ; and
- the principal positive domain, or separately the strict continuous-time cone.

It does not cover nonbinary networks, higher level, arbitrary weakly tree-child networks, boundary probabilities, zero or signed eigenvalues, an untransported permutation of the three nonzero states, or arbitrary nonreversible substitution models. No claim is made for the signed K3P components outside $\mathcal{D}_{3,+}$.

Generic identifiability means outside a proper algebraic exceptional set for each fixed topology. It is not pointwise topology identifiability at every parameter, equality of complete stochastic images, or

universal identifiability of physical parameters. The exact reconstruction theorem is a termination result under an exact-real oracle. It supplies no finite-sample estimator, statistical error rate, numerical conditioning bound, or practical sequence-length guarantee.

The weak-class construction proves sharpness of the hypothesis in the sense that weakening “strongly” to “weakly” makes the classification false. It does not classify every weakly tree-child network or every possible weak-class ambiguity.

17 Reproducibility and AI disclosure

The proof has a finite machine dependency. Exact arithmetic is used for model-domain identities, graph transports, polynomial pullbacks, Jacobian minors, rank factorizations, restoration, and probes. Rigorous rational interval arithmetic is used for the Krawczyk sharpness theorem. The certificate package records primitive graph inputs, parameter and coordinate orders, source–target direction, physical margins, evidence hashes, and reproduction commands.

The integrated primary verifier passes all 28 active evidence entries. Above it, the final classification gate reports `CERTIFIED_K3P_SAME` with no remaining mathematical gate, and its fail-closed suite rejects all 16 integrated mutations. These binding gates are supplemented by the component-specific clean-room, interval, restoration, probe, cut-transfer, and global-infrastructure replays described in the reader supplement.

The primary implementation and separately structured replays do not accept a stored final Boolean. At the load-bearing finite gates, the replay rebuilds literal mixed graphs, switching masks, Fourier tensors, coordinate transports, and exact witnesses. The clean-room H21 audit preserves and reproduces the historical rooted-DAG automorphism failure, then validates the corrected root-suppressed mixed-graph transport. The cut package separately rebuilds all 204 one-active directions; the global transfer audit checks that no common bridge tree or fourteen-orbit result is assumed. The sharpness replay derives a new exact preconditioner and verifies every interval inequality throughout the box.

Targeted mutation suites reject, among other changes, deletion or duplication of relation rows, source–target reversal, changed ports or incoming roles, quartic reassignment, an omitted H_{14} monomial, an untransported sector permutation, the false equality $C = T$, weakened rank bounds, missing restoration children, broken probe parentage, inconsistent triangle choices, boundary inheritance probabilities, interval determinants containing zero, and Krawczyk boxes that lose strict self-mapping. Optimized interpreter mode is refused at verifiers whose safety must not depend on assertions.

Historical, superseded, or exploratory artifacts are excluded from the active evidence manifest. In particular, the earlier universal pointwise K3P cut-recovery claim is withdrawn and not used; the active proof uses the three statements separated in [section 4](#). “Independent replay” means a separately implemented program, not review by an independent human specialist.

Generative AI assisted with exploration, implementation, drafting, and adversarial testing. Several automated routes failed audit before the active proof was formed. The mathematical claims rest on the displayed arguments and replayable evidence, not on acceptance of the discovery process. No independent human specialist review is claimed, and the author accepts responsibility for the theorem, code, interpretation, and submission.

Data and code availability

The exact certificate and replay files are maintained in the public repository <https://github.com/AlecKriebel/Math>, under `k3p_level2_identifiability_final`. The reader supplement gives a relative-path theorem-to-certificate crosswalk. This manuscript does not assert a repository release DOI or a paper/data/code license; neither has been supplied for this workstream.

Author contributions

Alec Kriebel conceived and directed the study, fixed its mathematical scope and conventions, curated the exact reproducibility package, adjudicated the proof and audit results, and accepts responsibility for the claims, software, and submission.

Use of generative AI

Generative AI systems assisted with mathematical exploration, code generation, implementation, drafting, and adversarial review. Automated claims were not accepted as evidence: active claims are bound to exact graph-derived certificates, direct derivations, separately implemented replays, rigorous interval arithmetic where used, and fail-closed mutation tests. No independent human specialist review is claimed. The author accepts responsibility for the mathematical statement, code, and final submission.

References

- [1] Muhammad Ardiyansyah. Distinguishing level-2 phylogenetic networks using phylogenetic invariants, 2021.
- [2] Jacek Bochnak, Michel Coste, and Marie-Françoise Roy. *Real Algebraic Geometry*, volume 36 of *Ergebnisse der Mathematik und ihrer Grenzgebiete*. Springer, Berlin, 1998.
- [3] Jari Brits, Niels Holtgreffe, Leo van Iersel, and Samuel Martin. On tree–network distinguishability and full identifiability of phylogenetic networks, 2026. Version 2, 29 July 2026.
- [4] Shelby Cox, Elizabeth Gross, and Samuel Martin. Group-based phylogenetic models on 3-sunlet networks. *Bulletin of Mathematical Biology*, 87:132, 2025.
- [5] Aviva K. Englander, Martin Frohn, Elizabeth Gross, Niels Holtgreffe, Leo van Iersel, Mark Jones, and Seth Sullivant. Identifiability of phylogenetic level-2 networks under the jukes–cantor model. *bioRxiv*, 2025. Version 4 revised 4 July 2026.
- [6] Steven N. Evans and Terry P. Speed. Invariants of some probability models used in phylogenetic inference. *The Annals of Statistics*, 21(1):355–377, 1993.
- [7] Elizabeth Gross and Colby Long. Distinguishing phylogenetic networks. *SIAM Journal on Applied Algebra and Geometry*, 2(1):72–93, 2018.
- [8] Elizabeth Gross, Leo van Iersel, Remie Janssen, Mark Jones, Colby Long, and Yukihiro Murakami. Distinguishing level-1 phylogenetic networks on the basis of data generated by markov processes. *Journal of Mathematical Biology*, 83(3):32, 2021.
- [9] Benjamin Hollering and Seth Sullivant. Identifiability in phylogenetics using algebraic matroids. *Journal of Symbolic Computation*, 104:142–158, 2021.

- [10] Niels Holtgreffe, Elizabeth S. Allman, Hector Baños, Leo van Iersel, Vincent Moulton, John A. Rhodes, and Kristina Wicke. Distinguishing phylogenetic level-2 networks with quartets and inter-taxon quartet distances. *Bulletin of Mathematical Biology*, 87(12):168, 2025.
- [11] Niels Holtgreffe, Katharina T. Huber, Leo van Iersel, Mark Jones, and Vincent Moulton. Characterizing semi-directed phylogenetic networks and their multi-rootable variants. *Theory in Biosciences*, 145:4, 2026.
- [12] Katharina T. Huber, Leo van Iersel, Mark Jones, Vincent Moulton, and Leonie Veenema-Nipius. When are quarnets sufficient to reconstruct semi-directed phylogenetic networks? *Bulletin of Mathematical Biology*, 87(10):136, 2025.
- [13] Alec Kriebel. Exact tree–theta–trinet collisions under the kimura 2- and 3-parameter models. Manuscript and exact reproducibility package, 2026.
- [14] Alec Kriebel. Generic identifiability and directed containment for strongly tree-child level-2 networks under the kimura two-parameter model. Companion manuscript and exact reproducibility package, 2026.
- [15] Alec Kriebel. Strong tree-childness is a sharp generic-identifiability boundary for level-2 jukes–cantor networks. Companion manuscript and exact reproducibility package, 2026.
- [16] Charles Semple and Mike Steel. *Phylogenetics*, volume 24 of *Oxford Lecture Series in Mathematics and Its Applications*. Oxford University Press, Oxford, 2003.
- [17] Bernd Sturmfels and Seth Sullivant. Toric ideals of phylogenetic invariants. *Journal of Computational Biology*, 12(2):204–228, 2005.