
Graphical Abstract

Beyond uniform slice interpolation: acquisition-conditioned residual correction for missing and rejected MRI slices

[First author], [Second author]



Highlights

Beyond uniform slice interpolation: acquisition-conditioned residual correction for missing and rejected MRI slices

[First author], [Second author]

- Slice reconstruction is posed for arbitrary, irregular and rejected slice patterns
- A linear anchor plus mask-conditioned bounded residual keeps acquired slices exact
- Uniform-grid specialists win at low sparsity but lose once slices are rejected
- One model serves all factors and patterns and is 5–55 times faster than baselines
- Image-quality rankings and downstream segmentation consistency disagree

Beyond uniform slice interpolation: acquisition-conditioned residual correction for missing and rejected MRI slices

[First author][a,*], [Second author][a]

[a] *[Institution], [City], [Country]*

ARTICLE INFO

Keywords:
MRI
missing-slice reconstruction
slice imputation
irregular sampling
slice rejection
residual learning
robustness
downstream evaluation

ABSTRACT

Learned through-plane MRI reconstruction is usually developed and tested on volumes in which every Rth slice is kept. In practice, the slices available for reconstruction may be irregularly spaced, and slices corrupted by motion may be discarded after quality control. Methods built around a fixed uniform grid then need a workaround before they can be applied. We formulate the task as reconstruction from an arbitrary set of kept slices and propose IR3C, a model that predicts a bounded correction to through-plane linear interpolation. The network receives the sparse volume, its linear interpolant and four profiles computed from the slice mask alone: whether a slice was kept, its relative position inside the gap, the gap length and the distance to the nearest kept slice. Kept slices are copied to the output exactly, and a zero-initialised output layer makes the untrained model equal to linear interpolation. A single standard 3D U-Net serves all reduction factors and mask patterns. We evaluate on brain T2-FLAIR (BraTS-GLI), brain T1-weighted (IXI-tiny) and knee DESS (OAIZIB) MRI under uniform sampling, six irregular sampling families, an unseen reduction factor and post-acquisition slice rejection, with every learned baseline trained under a matched budget. On uniform sampling, the strongest specialist baseline, SAINT, is better at $R = 2$ on all three datasets, whereas IR3C is better at $R = 8$. On irregular sampling, IR3C exceeds the strongest applicable method by 2.2–3.0 dB on BraTS-GLI, 0.9–1.7 dB on OAIZIB and 1.4–2.9 dB on IXI-tiny. When 20–30% of acquired slices are rejected, IR3C exceeds the best competitor, including SAINT with two prespecified workarounds, by 1.2–2.3 dB on both brain datasets. IR3C also gives the highest whole-tumour agreement with the complete-input output of a frozen segmentation network at every factor, and reconstructs a volume in 0.26 s. These results show that conditioning on the acquisition geometry and correcting a deterministic estimate, rather than a new backbone, decide robustness once the slice pattern departs from a uniform grid.

1. Introduction

Many clinical MRI protocols acquire stacks of two-dimensional slices whose spacing is much larger than the in-plane resolution. Downstream analysis, such as segmentation, registration or volumetry, often requires values on a denser grid along the slice direction. Classical interpolation fills the missing positions from neighbouring slices (Lehmann et al., 1999), and learned methods improve on it by exploiting anatomical context (Chaudhari et al., 2018; Chen et al., 2018; Peng et al., 2020; Song et al., 2024).

Most learned methods are developed on a regular grid. A dense reference volume is decimated by keeping every Rth slice, and the network is trained to restore the slices in between. This benchmark is convenient and reproducible, but it fixes the geometry of the problem: every gap has the same length, and the positions of the kept slices are known in advance. Some architectures depend on this structure directly. SAINT, for example, splits a regular stack into interleaved phases (Peng et al., 2020), and I^3Net pads its input on the assumption of a fixed stride (Song et al., 2024).

The slice pattern that a reconstruction method receives is not always uniform. Slice positions vary between protocols and sites, archived volumes may contain gaps, and slices degraded by motion or other artefacts may be rejected during quality control (Zaitsev et al., 2015). Outlier rejection is already an established step in slice-to-volume reconstruction (Kuklisova-Murgasova et al., 2012; Kainz et al., 2015). After rejection, a method designed for a regular grid must either fill the rejected slices before inference or discard further slices to recover a uniform subset. Both choices change the input that the method was trained on.

The problem also provides a useful starting estimate. Linear interpolation along the slice axis is exact at kept slices and gives a plausible low-frequency estimate between them. It is defined for any slice pattern and costs almost nothing to compute. Residual learning for MRI super-resolution is not new (Chaudhari et al., 2018; Peng et al., 2020), and arbitrary-scale methods based on implicit neural representations already accept non-integer factors (Wu et al., 2023; Wang et al., 2024). Our question is narrower: can one model, conditioned explicitly on the slice geometry and asked only to correct linear interpolation, stay accurate when the slice pattern changes, including when acquired slices are rejected?

We answer this question with IR3C, a deliberately simple method (Fig. 2). The network is a standard 3D U-Net (Ronneberger et al., 2015). What changes is the task it is given. The network receives the sparse volume, its linear interpolant and four slice-geometry profiles derived from the mask alone. It predicts a bounded correction that is applied only on missing slices, so kept slices are reproduced exactly. Because the output layer is initialised to zero, the untrained model is exactly linear interpolation.

*Corresponding author
[email] ([. author])
ORCID(s): 0000-0000-0000-0000 ([. author])

The contributions of this work are as follows.

(1) We formulate through-plane slice reconstruction for an arbitrary set of kept slices and define the evaluated region, the slice geometry and the sampling conditions explicitly. We separate uniform sampling, irregular sampling, unseen sparsity and post-acquisition slice rejection as distinct test conditions.
(2) We describe IR3C, a residual model anchored on linear interpolation and conditioned on slice geometry. It keeps acquired slices exactly and uses one set of weights for all reduction factors and sampling patterns.
(3) We compare IR3C with four classical interpolants and four learned methods on three datasets that differ in anatomy, contrast and slice geometry. All learned methods are trained under a matched optimisation budget, and methods that are not defined on irregular grids are evaluated through prespecified workarounds rather than omitted silently.
(4) We report where IR3C does not win. A uniform-grid specialist is better at low sparsity and on the dataset whose slice axis is already finely sampled. We also show that image-similarity rankings and downstream segmentation consistency disagree.

Throughout the paper, the degradation removes slices from a dense reference volume. This is slice imputation, or missing-slice reconstruction. It does not model the slice profile, partial-volume averaging or slice gap of a physically thick-slice acquisition (Remedios et al., 2026), and we do not claim that the method restores thick-slice clinical scans to isotropic resolution (Section 6.5).

2. Related work

2.1. Learned through-plane reconstruction

DeepResolve learned a residual mapping from thick-slice to thin-slice knee MRI and included a reader study (Chaudhari et al., 2018). DCSRN used densely connected 3D convolutions for brain MRI super-resolution (Chen et al., 2018). SAINT performs slice-wise super-resolution on interleaved phases of a regular stack and then fuses the results with a residual network (Peng et al., 2020). I^3Net combines inter-slice and intra-slice branches with cross-view processing (Song et al., 2024). SMORE trains on the target scan itself by treating in-plane data as high-resolution examples (Zhao et al., 2021). These methods improve the quality of reconstruction on a regular grid. They do not address what happens when the kept slices are irregularly spaced.

2.2. Arbitrary-scale and acquisition-aware methods

Implicit neural representations query intensities at continuous coordinates and therefore accept arbitrary reduction factors. ArSSR learns such a representation for 3D MR images (Wu et al., 2023), and SA-INR adds spatial attention for arbitrary reductions of slice spacing (Wang et al., 2024). ECLARE models slice thickness, slice gap and field of view explicitly for anisotropic resolution enhancement (Remedios et al., 2026). Our work is complementary. We do not change the representation of the volume; we give an ordinary convolutional network an explicit description of the local gap geometry, and we test what this buys under irregular sampling and rejection.

2.3. Imputation and physical thick-slice super-resolution

Removing slices from an isotropic reference provides exact ground truth at every missing position. It does not, however, simulate the through-plane point-spread function of a 2D multi-slice acquisition. We therefore use the terms *slice imputation* and *missing-slice reconstruction* for all experiments. Restoration of physically thick slices would require slice-profile degradation or paired thin and thick acquisitions.

2.4. Evaluation beyond image similarity

PSNR and SSIM (Wang et al., 2004) measure distortion but do not necessarily predict the behaviour of a downstream analysis. Recent work reports imperfect agreement between reconstruction metrics and downstream task performance (Wohlrapp et al., 2026). Perceptual metrics such as LPIPS (Zhang et al., 2018) rank methods differently again, in line with the perception–distortion trade-off (Blau and Michaeli, 2018). We therefore report a downstream segmentation endpoint beside the image metrics and interpret LPIPS as a secondary, descriptive measure.

3. Problem formulation and method

3.1. Problem formulation

Let $x \in [0,1]^{H\times W\times D}$ be a dense reference volume whose third axis is the reconstruction axis, and let $\mathcal{K} \subset \{1,\dots,D\}$ be the set of kept slices, with indicator $k_z = \mathbb{1}[z \in \mathcal{K}]$. The observation is $x_s(:,:,z) = k_z\, x(:,:,z)$, and the missing-slice indicator is $m_z = 1 - k_z$. The task is to estimate $x(:,:,z)$ for every z with $m_z = 1$, while reproducing kept slices unchanged. The problem is posed in the image domain; raw k-space and coil data are not used.

A nominal reduction factor R fixes the number of kept slices, $|\mathcal{K}| = \lceil (D-1)/R \rceil + 1$, so that all masks at the same R contain the same amount of data and differ only in where the slices are placed. The first and last slices are always kept, so no method has to extrapolate. Training uses $R \in \{2,4,8\}$; $R = 16$ is held out as an unseen level of sparsity.

3.2. Sampling conditions

Sampling families. We use seven mask families (Fig. 1a). U0 is uniform decimation. U1 and U2 shift interior slices by small and large random offsets. U3 places interior slices at random. U4 clusters the kept slices into runs and leaves long gaps. U5 samples the centre of the volume more densely than its ends. U6 mixes runs of different lengths. All families keep the same number of slices at a given R. For testing, one mask is generated per family and factor with a fixed seed and is shared by all subjects and methods.




Figure 1: Sampling conditions studied in this work. (a) The seven test-mask families at $R = 4$ on the 153-slice BraTS-GLI depth. Each tick is a kept slice; every family keeps 39 slices, so the families differ only in where the slices are placed. The number on the right is the longest gap in slices. (b) Slice rejection. A uniform $R = 2$ acquisition loses 20% of its interior slices independently (random) or in runs of two to three slices (burst). Black: acquired and kept; orange: acquired and rejected. (c) The four geometry profiles that IR3C receives, shown for a window of the U3 mask. Grey vertical lines mark kept slices. Profiles are computed from the mask alone and are broadcast over the in-plane dimensions.

Slice rejection. To model rejection after quality control, a uniform acquisition at base factor $R \in \{2, 4\}$ loses a fraction $p \in \{0.1, 0.2, 0.3\}$ of its acquired interior slices (Fig. 1b). In the *random* pattern, slices are rejected independently. In the *burst* pattern, they are rejected in runs of two or three consecutive acquired slices, as might follow a motion event. The rejection mask is generated deterministically from the subject identifier, so each subject has its own mask, and the same mask is given to every method.

3.3. IR3C

Linear anchor. For a missing slice z, let $l_z < z < r_z$ be the nearest kept slices on either side. The anchor is through-plane linear interpolation,

$$x_{\text{lin}}(:, :, z) = (1 - \alpha_z)\, x(:, :, l_z) + \alpha_z\, x(:, :, r_z), \qquad \alpha_z = \frac{z - l_z}{r_z - l_z}, \tag{1}$$

and $x_{\text{lin}}(:, :, z) = x(:, :, z)$ for kept slices.

Geometry profiles. Four per-slice profiles describe the acquisition geometry (Fig. 1c): the kept indicator k_z; the relative position α_z; the gap length $g_z = r_z - l_z$; and the distance to the nearest kept slice $d_z = \min(z - l_z, r_z - z)$. Gap length and distance are log-compressed so that very long gaps remain in a bounded range, $\tilde{g}_z = \log(1 + g_z)/\log(161)$ and $\tilde{d}_z = \log(1 + d_z)/\log(81)$. All profiles except k_z are zero on kept slices. Each profile is broadcast over the in-plane dimensions. Together with x_s and x_{lin}, the profiles form a six-channel input X. The profiles depend only on the mask, never on image intensities.

Bounded residual. A 3D U-Net f_θ maps X to one channel. The reconstruction is

$$\hat{x} = \text{clip}_{[0,1]}\big(x_{\text{lin}} + m \odot s \tanh f_\theta(X)\big), \qquad \hat{x}(:, :, z) \leftarrow x_s(:, :, z) \quad \text{if } k_z = 1, \tag{2}$$

where m broadcasts the missing-slice indicator. The residual scale $s = 0.585$ is fixed before training as the 99.5th percentile of $|x - x_{\text{lin}}|$ over foreground voxels of missing slices in the training set. It limits how far the output can move from the anchor. It does not guarantee that the corrected estimate is closer to the reference than linear interpolation.

Initialisation and backbone. The $1 \times 1 \times 1$ output layer is initialised to zero, so the untrained model returns x_{lin} exactly. The backbone is a MONAI 3D U-Net (Cardoso et al., 2022) with 32, 64, 128 and 256 channels, three stride-2 downsampling steps, two residual units per level, instance normalisation and PReLU activations (4.75 M parameters). We use a standard backbone on purpose: the backbone is the implementation vehicle, not the contribution, and Section 5.7.2 shows that the results are not tied to it.

3.4. Training objective

The loss combines Charbonnier penalties (Charbonnier et al., 1997) inside and outside the foreground mask, a structural term, a through-plane gradient term and a small




Figure 2: IR3C. (a) The sparse volume yields a linear through-plane anchor and four geometry profiles computed from the slice mask alone. (b) A standard 3D U-Net receives the six-channel input and predicts one channel. (c) The output is bounded by $s\tanh(\cdot)$, applied on missing slices only and added to the anchor; acquired slices are copied to the output exactly. Cube faces show an archived BraTS-GLI reconstruction.

penalty on the residual:

$$\mathcal{L} = \mathcal{L}_{\mathrm{C}}^{\mathrm{fg}} + 0.30\,\mathcal{L}_{\mathrm{C}}^{\mathrm{bg}} + 0.10\,\big(1 - \mathrm{SSIM}\big) + 0.05\,\mathcal{L}_{\nabla_z}^{\mathrm{fg}} + 0.001\,\|\delta\|_1, \tag{3}$$

with $\delta = s\tanh f_\theta(X)$. All terms are restricted to missing slices. The background term prevents the network from adding low-level intensity outside the anatomy, which a foreground-only loss leaves unconstrained.

4. Experimental setup

4.1. Datasets

Table 1 summarises the three datasets. *BraTS-GLI* (BraTS 2023 adult glioma) provides co-registered, skull-stripped multi-contrast brain MRI (Menze et al., 2015; Bakas et al., 2017; Baid et al., 2021). We reconstruct the T2-FLAIR volume along the axial axis. The 1251 subjects of the training release are used for training. Six subjects of the validation release are used for checkpoint selection, and 88 further validation-release subjects form the test set. BraTS-GLI is the development dataset and the primary benchmark. *OAIZIB* contains 507 knee DESS volumes from the Osteoarthritis Initiative (Peterfy et al., 2008; Ambellan et al., 2019). We reconstruct along the sagittal slice-select axis on the native grid and use the official 404/103 split, with 30 training subjects held out for validation. *IXI-tiny* contains 566 down-sampled T1-weighted brain volumes derived from the IXI dataset (Imperial College London, 2026). Its reconstruction axis is the axial axis, which is also its finest axis (2.18 mm). This makes IXI-tiny the dataset least suited to a method that exploits a coarse slice direction.

Intensities are clipped to the 1st and 99.5th percentiles of the foreground and mapped to [0, 1] once per volume; no slice-wise normalisation is applied.

4.2. Comparators

Classical interpolation. Nearest-neighbour, linear, global cubic-spline and local bicubic interpolation along the reconstruction axis. The cubic spline is fitted along each complete through-plane line and can overshoot when knots are irregular; bicubic uses a local kernel.

Learned methods. DCSRN (Chen et al., 2018), ArSSR (Wu et al., 2023), SAINT (Peng et al., 2020) and I^{3}Net (Song et al., 2024). DCSRN is fully convolutional and is trained on the same mixed uniform and irregular masks as IR3C, so it can be evaluated on every family. ArSSR queries continuous coordinates and also accepts irregular masks. SAINT and I^{3}Net construct their inputs from a regular stride. They are evaluated on U0, and under rejection through the two workarounds described below; we do not assign them scores on patterns for which their inference is undefined.

Matched budget. All learned methods use the same subject partitions, masks, intensity range and scored voxels. No baseline received more than 12,510 optimiser steps of source training. IR3C is reported at the checkpoint reached after the same 12,510 steps ("matched budget") in every comparison, including the transfer datasets, where it is fine-tuned from this checkpoint. The full 25-epoch IR3C model is reported

Table 1
Datasets and subject-level partitions. "Reconstruction axis" is the axis along which slices are removed; its number of slices D and spacing are given. OAIZIB and IXI-tiny models are fine-tuned on their own training partitions. Test subjects are never used for training, early stopping or checkpoint selection.

Dataset	Anatomy, contrast	Grid (voxels)	Spacing (mm)	Reconstruction axis	Train	Val.	Test
BraTS-GLI	Brain, T2-FLAIR	$240 \times 240 \times 153^a$	$1.0 \times 1.0 \times 1.0$	axial; $D = 153$, 1.0 mm	1251	6	88
OAIZIB	Knee, 3D DESS	$160 \times 384 \times 384$	$0.70 \times 0.36 \times 0.36$	sagittal; $D = 160$, 0.70 mm	374	30	103
IXI-tiny	Brain, T1-weighted	$83 \times 44 \times 55$	$2.18 \times 4.13 \times 3.95$	axial; $D = 83$, 2.18 mm^b	436	30	100

^{a}Central crop of the native 155 axial slices. ^{b}The reconstruction axis is the finest axis of this dataset, so $R = 2$, 4 and 8 correspond to slice spacings of 4.36, 8.72 and 17.44 mm.

only in Appendix C; it is 0.45 dB better on BraTS-GLI, so the matched comparison is conservative for IR3C. On OAIZIB and IXI-tiny, every learned method is fine-tuned on the same target training split within the same target budget.

Workarounds under rejection. SAINT and I^{3}Net receive two prespecified workarounds when slices are rejected. In workaround A (*imputation*), each rejected slice is filled by linear interpolation from the surviving slices, and the model is run at the original factor R. In workaround B (*uniform subset*), the stride-2R phase of the original grid that lost fewer slices is selected, its rejected members are filled by linear interpolation, and the model is run at factor $2R$. Every output, for every method, is finally overwritten with the truly acquired slices, so all methods are scored on identical missing slices.

4.3. Evaluation protocol

PSNR is computed from the squared error pooled over all foreground voxels of the missing slices of a volume. Kept slices are excluded, because every method copies them exactly and including them would inflate all scores. SSIM (Wang et al., 2004) is computed per missing slice and averaged. NMSE and MAE use the same region. LPIPS (Zhang et al., 2018) is reported as a secondary metric in Appendix A. This protocol was fixed before the comparison and is applied identically to every method. It matters: in a separate check, the same reconstruction scored between 26.0 and 46.0 dB depending on the region, normalisation and slice-wise versus volume-wise computation. Absolute values in this paper should therefore not be compared with values reported elsewhere.

4.4. Statistical analysis

The subject is the unit of analysis. For each table row, a subject's cells (factors, families or conditions) are averaged first, and the mean and standard deviation are then computed across subjects. Paired comparisons use per-subject differences and report the mean difference, its 95% confidence interval from the t distribution, the proportion of subjects in which IR3C is better, and the two-sided Wilcoxon signed-rank test (Wilcoxon, 1945). Within each table, p-values are adjusted with the Holm procedure (Holm, 1979). With 88 to 103 paired subjects, very small differences can be significant, so we interpret effect sizes and confidence intervals rather than p-values alone.

4.5. Downstream segmentation consistency

A pretrained MONAI SegResNet (Myronenko, 2019; Cardoso et al., 2022) for BraTS receives the acquired T1, T1c and T2 volumes with either the complete or a reconstructed FLAIR volume. The network is frozen and was never trained or tuned on any subject of this study. Dice for whole tumour (WT), tumour core (TC) and enhancing tumour (ET) is computed against the same network's prediction on the complete input. Because the test subjects come from the BraTS validation release, which has no public labels, this endpoint measures how much a reconstruction changes the output of a fixed pipeline. It does not measure segmentation accuracy against expert labels (Section 5.9).

4.6. Implementation

IR3C is trained on BraTS-GLI with AdamW (learning rate 2×10^{-4}, weight decay 10^{-4}), a 2% linear warm-up followed by cosine decay, batch size 4, automatic mixed precision and gradient clipping at 1.0. Training patches cover the full depth of the volume so that every patch contains kept slices. For each training sample, R is drawn from $\{2, 4, 8\}$ with probabilities 0.30, 0.35 and 0.35; half of the samples use a uniform mask and half use a fresh random mask from one of the six irregular families. Checkpoints are selected on validation PSNR, subject to validation SSIM not falling more than 0.01 below that of linear interpolation. For OAIZIB and IXI-tiny, the matched-budget BraTS-GLI model is fine-tuned on the target training split, with the learning rate chosen by a short probe on the target validation split and early stopping on validation PSNR. All experiments ran on a single NVIDIA GB10 GPU.

5. Results

5.1. Uniform sampling

Table 2 and Fig. 3 compare all methods on U0, where every method is defined. The ranking depends on the reduction factor. At $R = 2$, SAINT is the best method on all three datasets; it exceeds IR3C by 0.81 dB on BraTS-GLI, 0.37 dB on OAIZIB and 3.70 dB on IXI-tiny. At $R = 8$, IR3C is the best method on all three datasets, by 0.98, 0.44 and 0.14 dB,

Table 2
Reconstruction on uniform sampling (U0). Values are means across test subjects; standard deviations are given in Appendix A. Only missing slices inside the foreground mask are scored. Bold marks the best method per column. The paired row reports IR3C minus SAINT in dB; an asterisk marks $p < 0.05$ (Wilcoxon signed-rank, Holm-corrected over the nine columns). Shaded rows are baselines that have not yet been run.

	BraTS-GLI ($n = 88$)			OAIZIB ($n = 103$)			IXI-tiny ($n = 100$)		
Method	$R = 2$	$R = 4$	$R = 8$	$R = 2$	$R = 4$	$R = 8$	$R = 2$	$R = 4$	$R = 8$
PSNR (dB) ↑									
Linear	30.17	26.33	22.11	21.03	19.00	17.53	28.17	22.52	18.53
Bicubic	30.46	26.53	22.12	20.77	18.70	17.22	29.07	22.68	18.37
DCSRN	19.73	22.53	20.27	20.58	19.40	18.13	23.53	20.85	16.85
ArSSR	25.07	23.79	21.43	21.75	20.46	19.12	26.32	23.80	21.41
I^3Net	30.37	26.32	22.12	22.02	20.26	18.98	28.63	22.72	18.95
SAINT	**33.37**	28.56	23.23	**22.89**	21.34	19.83	**33.27**	**27.30**	22.86
IR3C (ours)	32.56	**29.01**	**24.21**	22.52	**21.35**	**20.27**	29.57	25.27	**23.00**
SA-INR	*tbd*	*tbd*	*tbd*	*tbd*	*tbd*	*tbd*	*tbd*	*tbd*	*tbd*
3D U-Net, direct output	*tbd*	*tbd*	*tbd*	*tbd*	*tbd*	*tbd*	*tbd*	*tbd*	*tbd*
SSIM ↑									
Linear	0.984	0.962	0.918	0.410	0.293	0.228	0.963	0.871	0.705
Bicubic	0.985	0.964	0.921	0.403	0.285	0.220	0.971	0.883	0.712
DCSRN	0.925	0.743	0.874	0.363	0.278	0.220	0.910	0.841	0.582
ArSSR	0.983	0.963	0.931	0.420	0.356	0.303	0.976	0.930	0.860
I^3Net	0.985	0.966	0.922	0.427	0.339	0.283	0.967	0.882	0.733
SAINT	**0.991**	**0.975**	0.935	0.473	0.393	0.328	**0.990**	**0.956**	0.876
IR3C (ours)	0.987	0.973	**0.944**	**0.479**	**0.412**	**0.358**	0.973	0.934	**0.892**
SA-INR	*tbd*	*tbd*	*tbd*	*tbd*	*tbd*	*tbd*	*tbd*	*tbd*	*tbd*
3D U-Net, direct output	*tbd*	*tbd*	*tbd*	*tbd*	*tbd*	*tbd*	*tbd*	*tbd*	*tbd*
ΔPSNR, IR3C − SAINT	−0.81*	+0.46*	+0.98*	−0.37*	+0.01*	+0.44*	−3.70*	−2.02*	+0.14*
Subjects favouring IR3C (%)	27	74	100	0	59	100	0	0	63

respectively, and it is better than SAINT in every BraTS-GLI and OAIZIB subject. At $R = 4$ the picture is mixed: IR3C is better on BraTS-GLI (0.46 dB), the two methods are practically equal on OAIZIB (0.01 dB), and SAINT is better on IXI-tiny (2.02 dB).

IXI-tiny is the clearest case in which IR3C does not win. Its reconstruction axis is already the finest axis of the volume, so missing slices at $R = 2$ and $R = 4$ are spaced 4.4 and 8.7 mm apart and closely resemble their neighbours. This is the regime for which slice-wise super-resolution on interleaved phases was designed. The other learned methods vary widely: I^3Net is close to linear interpolation on both brain datasets, and ArSSR and DCSRN are below linear interpolation at $R = 2$ on BraTS-GLI. Among the methods that can be run on irregular masks, IR3C is the best in every column of Table 2.

5.2. Irregular sampling

Table 3 and Fig. 4 report PSNR by sampling family. SAINT and I^3Net are absent because they are not defined on irregular grids. On every family and dataset, IR3C is better than every applicable method, and it is better in at least 99% of subjects in each column. On the irregular families U1–U6, its margin over the strongest applicable comparator is 2.21–2.97 dB on BraTS-GLI (over bicubic interpolation), 0.86–1.69 dB on OAIZIB (over ArSSR) and 1.39–2.90 dB on IXI-tiny (over ArSSR). The margin is largest on the clustered family U4, which has the longest gaps, on all three datasets.

The classical methods behave differently from one another under irregular sampling. The global cubic spline is close to linear interpolation on U0 but falls below it on every irregular family of every dataset, by up to 5.3 dB on OAIZIB U4, because a spline through irregularly spaced knots overshoots. Local bicubic interpolation remains close to linear interpolation. Among the learned methods, DCSRN gains little over linear interpolation even though it was trained on the same mixed masks as IR3C, which indicates that training on irregular masks alone is not sufficient. The formulation ablation in Section 5.7.3 is designed to separate the contributions of the anchor and of the geometry profiles.

5.3. Unseen sparsity

No model was trained at $R = 16$. Table 4 shows that IR3C remains the best method at this factor on all datasets, pooled over all families (BraTS-GLI 18.22 versus 15.89 dB for the next best method; OAIZIB 16.99 versus 15.87 dB; IXI-tiny 19.91 versus 16.99 dB). Absolute quality is low for every method, and in the most extreme cell (U4 at $R = 16$ on BraTS-GLI, where one gap spans most of the brain) no




Figure 3: Uniform sampling (U0). PSNR difference from linear interpolation for each learned method as a function of the reduction factor, on (a) BraTS-GLI, (b) OAIZIB and (c) IXI-tiny. Markers are means across test subjects; error bars are 95% confidence intervals of the paired difference. Markers are offset horizontally for legibility. Note the different vertical scales.

Table 3
PSNR (dB) by sampling family, pooled over $R \in \{2, 4, 8\}$. U0 is uniform; U1–U6 are irregular (Section 3.2). I^3Net and SAINT are not defined off a regular grid and are therefore absent. The last row of each block is the paired difference between IR3C and the strongest applicable comparator in that column, with its 95% confidence interval. Bold marks the best method per column. Standard deviations are given in Appendix A.

Method	U0	U1	U2	U3	U4	U5	U6	U1–U6
BraTS-GLI								
Linear	26.20	25.03	24.50	23.12	18.45	23.37	21.73	22.70
Cubic spline	26.32	24.96	24.36	22.53	17.01	22.96	20.82	22.10
Bicubic	26.37	25.17	24.61	23.17	18.46	23.42	21.78	22.77
DCSRN	20.84	20.64	20.34	19.78	17.02	19.77	18.83	19.40
ArSSR	23.43	22.95	22.65	21.94	18.14	21.98	20.51	21.36
IR3C (ours)	**28.59**	**27.37**	**26.84**	**25.59**	**21.42**	**25.87**	**24.27**	**25.23**
SA-INR	*tbd*	*tbd*	*tbd*	*tbd*	*tbd*	*tbd*	*tbd*	*tbd*
Δ vs. best comparator	+2.23	+2.21	+2.23	+2.42	+2.97	+2.45	+2.49	+2.46
OAIZIB								
Linear	19.19	18.68	18.53	18.03	15.87	18.07	17.39	17.76
Cubic spline	18.63	17.71	17.24	15.45	10.57	14.67	14.29	14.99
Bicubic	18.90	18.41	18.27	17.79	15.71	17.83	17.18	17.53
DCSRN	19.37	18.98	18.84	18.35	16.38	18.40	17.81	18.13
ArSSR	20.44	20.13	19.99	19.39	16.90	19.49	18.78	19.11
IR3C (ours)	**21.38**	**20.99**	**20.88**	**20.46**	**18.59**	**20.59**	**19.94**	**20.24**
SA-INR	*tbd*	*tbd*	*tbd*	*tbd*	*tbd*	*tbd*	*tbd*	*tbd*
Δ vs. best comparator	+0.94	+0.86	+0.89	+1.06	+1.69	+1.10	+1.16	+1.13
IXI-tiny								
Linear	23.07	21.45	21.56	19.93	14.56	19.25	18.73	19.25
Cubic spline	23.14	21.36	21.32	18.66	13.04	15.06	16.70	17.69
Bicubic	23.37	21.57	21.69	20.01	14.56	19.31	18.72	19.31
DCSRN	20.41	19.71	19.69	18.70	14.46	18.27	17.93	18.13
ArSSR	23.84	23.19	23.12	22.24	17.36	20.88	21.86	21.44
IR3C (ours)	**25.95**	**24.66**	**24.69**	**23.90**	**20.26**	**22.89**	**23.25**	**23.27**
SA-INR	*tbd*	*tbd*	*tbd*	*tbd*	*tbd*	*tbd*	*tbd*	*tbd*
Δ vs. best comparator	+2.11	+1.47	+1.57	+1.66	+2.90	+2.01	+1.39	+1.83




Figure 4: PSNR difference from linear interpolation by sampling family, pooled over $R \in \{2, 4, 8\}$, on (a) BraTS-GLI, (b) OAIZIB and (c) IXI-tiny. The shaded column is the uniform family U0. Only methods that are defined on irregular grids are shown. Error bars are 95% confidence intervals of the paired difference across subjects.

Table 4
Unseen sparsity, $R = 16$ (never used in training). PSNR (dB), mean across test subjects. "All" pools U0–U6. DCSRN and I^{3}Net use factor-specific models and have no $R = 16$ model; SAINT was not evaluated at this factor.

	BraTS		OAIZIB		IXI	
Method	U0	All	U0	All	U0	All
Linear	18.50	15.86	16.17	14.98	15.97	14.74
Cubic spline	18.24	14.43	15.54	11.60	15.32	12.67
Bicubic	18.33	15.74	15.86	14.74	15.72	14.55
ArSSR	18.70	15.89	17.47	15.87	18.44	16.99
IR3C (ours)	**20.97**	**18.22**	**18.85**	**16.99**	**20.81**	**19.91**

method recovers the anatomy. We therefore read this result as graceful degradation outside the training range, not as a solution to extreme sparsity.

5.4. Slice rejection

Table 5 and Fig. 5 report the rejection experiment. Without rejection, the uniform-grid specialists retain their advantage where they had it on U0: SAINT is better than IR3C at $R = 2$ on BraTS-GLI and at both base factors on IXI-tiny. Rejection reverses this ordering. On BraTS-GLI, IR3C is better than the strongest competitor in every rejection condition, by 0.40–2.31 dB. On IXI-tiny, the two methods are equal after 10% random rejection at $R = 2$ (−0.02 dB, 95% CI −0.22 to 0.18), and IR3C is better in every other rejection condition; after 20–30% rejection its advantage is 1.22–2.16 dB and it is better in 92–100% of subjects. The crossover therefore lies at about 10% rejection on both brain datasets.

The advantage grows with the rejected fraction and is larger for burst than for random rejection, because bursts create longer gaps. The imputation workaround was the stronger of the two SAINT workarounds in most conditions, but at 20–30% rejection on IXI-tiny the strongest competitor was ArSSR, which, like IR3C, accepts the irregular mask directly. Both workarounds amount to presenting the specialist with an input that differs from its training distribution: imputed slices are smooth linear estimates rather than acquired data, and the uniform subset discards acquired slices. Fig. 7 shows the visible consequence on a typical subject: horizontal discontinuities at the positions of rejected slices.

To do before submission: OAIZIB slice rejection

Run the OAIZIB arm of `IR3C_SliceReject_all` (it stopped after BraTS-GLI; smoke test passed). It takes about 2.5 days on one GPU. It fills the shaded OAIZIB rows of Table 5 and adds a row to Fig. 5. This shows whether the crossover also holds outside the brain.

5.5. Downstream segmentation consistency

Table 6 and Fig. 6 report how far each reconstruction moves the output of a frozen tumour segmentation network. The reference is the network's own prediction on the complete input; re-saving and reloading the complete volume gives WT Dice of 0.990, which is the noise floor of the pipeline. IR3C has the highest WT Dice at every factor and is best or within 0.001 of the best in every TC and ET column (WT 0.993, 0.985 and 0.961 at $R = 2$, 4 and 8), and its advantage over linear interpolation grows with sparsity (0.002, 0.007 and 0.013; Holm-adjusted $p < 10^{-7}$ at every factor). The full-budget checkpoint changes WT Dice by at most 0.001, so this endpoint does not depend on the training budget. The classical interpolants stay close to IR3C on this endpoint even though they are more than 2 dB lower in PSNR.

Table 5
Slice rejection. A uniform acquisition at base factor R loses a fraction of its acquired interior slices, either independently (random) or in runs of two to three slices (burst). Each cell gives IR3C minus the strongest competitor in that condition (PSNR, dB) with its 95% confidence interval; the strongest competitor is named underneath (A: rejected slices imputed linearly before inference; B: uniform stride-$2R$ subset). An asterisk marks $p < 0.05$ after Holm correction over the conditions of one dataset. At 0% the competitor runs in its native uniform regime. Absolute PSNR for every method is given in Appendix B. Shaded rows have not yet been run.

Dataset	Base	Pattern	0%	10%	20%	30%
BraTS-GLI	$R = 2$	random	−0.81 [−1.03, −0.60]* SAINT-A	+0.40 [0.22, 0.59]* SAINT-A	+1.20 [1.04, 1.36]* SAINT-A	+1.62 [1.49, 1.76]* SAINT-A
	$R = 2$	burst	−0.81 [−1.03, −0.60]* SAINT-A	+0.60 [0.45, 0.76]* SAINT-A	+1.29 [1.15, 1.43]* SAINT-A	+1.72 [1.59, 1.85]* SAINT-A
	$R = 4$	random	+0.46 [0.32, 0.59]* SAINT-A	+1.35 [1.23, 1.48]* SAINT-A	+1.76 [1.63, 1.89]* SAINT-A	+2.08 [1.95, 2.21]* SAINT-A
	$R = 4$	burst	+0.46 [0.32, 0.59]* SAINT-A	+1.55 [1.39, 1.71]* SAINT-A	+2.16 [1.97, 2.35]* SAINT-A	+2.31 [2.14, 2.48]* SAINT-A
OAIZIB	$R = 2$	random	*tbd*	*tbd*	*tbd*	*tbd*
	$R = 2$	burst	*tbd*	*tbd*	*tbd*	*tbd*
	$R = 4$	random	*tbd*	*tbd*	*tbd*	*tbd*
	$R = 4$	burst	*tbd*	*tbd*	*tbd*	*tbd*
IXI-tiny	$R = 2$	random	−3.70 [−3.86, −3.53]* SAINT-A	−0.02 [−0.22, 0.18] SAINT-A	+1.22 [1.02, 1.42]* SAINT-B	+1.47 [1.34, 1.60]* ArSSR
	$R = 2$	burst	−3.70 [−3.86, −3.53]* SAINT-A	+0.78 [0.48, 1.09]* SAINT-A	+1.71 [1.55, 1.88]* ArSSR	+1.70 [1.55, 1.84]* ArSSR
	$R = 4$	random	−2.02 [−2.16, −1.88]* SAINT-A	+0.42 [0.25, 0.59]* SAINT-A	+1.64 [1.52, 1.76]* ArSSR	+1.84 [1.70, 1.98]* ArSSR
	$R = 4$	burst	−2.02 [−2.16, −1.88]* SAINT-A	+1.45 [1.19, 1.71]* SAINT-A	+1.92 [1.77, 2.07]* ArSSR	+2.16 [1.98, 2.33]* ArSSR

The downstream ranking does not follow PSNR. SAINT is within 1 dB of IR3C in PSNR on BraTS-GLI at $R = 4$ and $R = 8$ (Table 2) but falls to WT Dice of 0.831 and 0.816. I^{3}Net, whose PSNR is close to linear interpolation, falls further, to 0.676 and 0.646. The cause of the SAINT drop is not yet established: its mean background intensity is low, so it does not follow the background-haze mechanism we found for I^{3}Net, which shifts the intensity normalisation of the segmentation network. Image metrics alone would not have revealed these failures.

5.6. Qualitative results

Fig. 7 shows sagittal reformats along the reconstruction axis for one subject, chosen by a fixed rule as the subject with the median IR3C gain among the five archived showcase subjects. On uniform sampling, all learned methods reduce the stair-step appearance of linear interpolation; SAINT and IR3C give the lowest error. After 30% burst rejection, the baselines show horizontal bands at the rejected positions, where gaps of up to 16 slices are bridged by smooth interpolation. IR3C reconstructs these gaps with less banding and has the lowest missing-slice error (MAE 0.065 versus 0.076 for SAINT with imputation).

5.7. What makes the formulation work

5.7.1. Choice of anchor

Table 7 replaces the linear anchor with other interpolants while keeping the initial weights and the order of training data fixed. The anchors differ by 2.60 dB before correction (20.69 to 23.28 dB), but the corrected models differ by only 0.37 dB (25.80 to 26.17 dB). The best raw interpolant (bicubic) does not give the best final model; the linear anchor does. The learned correction therefore absorbs most of the error of the starting estimate, and a simple, exact-at-the-knots anchor is a sufficient starting point.

5.7.2. Backbone capacity

Table 8 changes only the network that predicts the correction. A smaller bottleneck costs 0.04 dB. A depthwise-separable network with one fifth of the parameters costs 1.17 dB. An nnU-Net-configured backbone (Isensee et al., 2021) with 45 M parameters gains 1.51 dB on irregular masks and is better for every subject, at about six times the inference cost. The formulation is therefore not tied to one backbone, and its accuracy improves with capacity. All rows use a single training seed.

5.7.3. Formulation ablation

The experiments above show the performance pattern of IR3C but do not show which part of the formulation produces its robustness. Table 9 is designed to answer this




Figure 5: Slice rejection on BraTS-GLI (a–d) and IXI-tiny (e–h). PSNR on missing slices against the fraction of acquired interior slices rejected, for base factors $R = 2$ and $R = 4$ and random or burst rejection. Error bars are 95% confidence intervals of the cohort mean; the paired differences, which are much tighter, are given in Table 5. Markers are offset horizontally for legibility. DCSRN, bicubic interpolation and the I^{3}Net uniform-subset workaround are omitted for clarity and are reported in Appendix B.

Table 6
Downstream segmentation consistency on BraTS-GLI (U0, $n = 88$). A frozen SegResNet receives the acquired T1, T1c and T2 volumes with complete or reconstructed FLAIR. Dice is computed against the same network's prediction on the complete input, so it measures how far a reconstruction moves a fixed pipeline, not agreement with expert labels. Re-saving and reloading the complete volume gives WT/TC/ET Dice of 0.990/0.991/0.979, which is the pipeline's noise floor. WT: whole tumour; TC: tumour core; ET: enhancing tumour. IR3C is the budget-matched checkpoint used in all other tables; the last row gives the full-budget checkpoint (Table 23) for reference and is excluded from the bold marking.

	WT Dice ↑			TC Dice ↑			ET Dice ↑		
Method	$R = 2$	$R = 4$	$R = 8$	$R = 2$	$R = 4$	$R = 8$	$R = 2$	$R = 4$	$R = 8$
Linear	0.991	0.977	0.947	0.993	0.981	0.968	0.987	0.970	0.941
Bicubic	0.993	0.981	0.949	**0.993**	0.982	0.966	0.987	0.972	0.942
DCSRN	0.970	0.768	0.915	0.966	0.863	0.935	0.945	0.814	0.894
ArSSR	0.989	0.977	0.949	0.988	0.982	0.977	0.981	0.970	0.948
I^{3}Net	0.923	0.676	0.646	0.935	0.835	0.816	0.903	0.795	0.784
SAINT	0.986	0.831	0.815	0.980	0.894	0.871	0.961	0.852	0.828
IR3C (ours)	**0.993**	**0.985**	**0.961**	0.993	**0.986**	**0.977**	**0.988**	**0.976**	**0.950**
IR3C, full budget	0.993	0.985	0.962	0.993	0.987	0.977	0.988	0.976	0.950

with the backbone, optimiser and budget held fixed. The key comparisons are the same network predicting the image directly (no anchor), the anchored model without geometry profiles, and the anchored model trained on uniform masks only. If robustness comes from anchoring and geometry conditioning rather than from the backbone, the direct model and the model without profiles should lose most of IR3C's advantage on U1–U6, on U4 and under rejection, while remaining competitive on U0.




Figure 6: Downstream segmentation consistency on BraTS-GLI (U0, $n = 88$). Dice between the frozen network's prediction from reconstructed FLAIR and its prediction from complete FLAIR, for (a) whole tumour, (b) tumour core and (c) enhancing tumour. The dotted line is the Dice obtained by re-saving and reloading the complete input. Error bars are 95% confidence intervals across subjects.

Table 7
Choice of anchor (BraTS-GLI, all families, $R \in \{2, 4, 8\}$, $n = 88$). Each model is trained from the same initial weights with identical data order; only the interpolant used as the anchor changes. Δ is the paired difference to the linear-anchored model with its 95% confidence interval.

Anchor	Alone	Corrected	Δ vs. linear anchor
Nearest	20.69	25.80	−0.37 [−0.40, −0.34]
Linear	23.20	26.17	—
Cubic spline	22.71	26.13	−0.04 [−0.06, −0.01]
Bicubic	23.28	26.05	−0.12 [−0.14, −0.10]

Table 8
Backbone capacity (BraTS-GLI, $R \in \{2, 4, 8\}$, $n = 88$, single seed). The anchor, input profiles, loss and training budget are identical; only the network that predicts the correction changes. Δ is the paired difference to the IR3C backbone on U1–U6. Parameter counts and multiply–accumulate operations (MACs) are for one full-volume forward pass.

Backbone	Param. (M)	GMACs	U0	U1–U6	Δ
MONAI U-Net (IR3C)	4.75	218	29.07	25.69	—
Reduced bottleneck	3.63	198	29.00	25.65	−0.04
Depthwise separable	0.98	41	27.59	24.51	−1.17
nnU-Net config.	45.44	2434	31.25	27.20	+1.51

To do before submission: formulation ablation (Table 9)

Seven of the eight arms already exist in the HPC package `hpc_ir3c_ablations_v2.tar.gz` (`A0–A3`, `C1–C3`; see `HANDOVER_IR3C_ABLATIONS.md`). Two additions are needed: (i) a new arm that keeps only the binary kept-slice profile k_z, and (ii) seeds 43 and 44 for `A0_ir3c`, `A3_direct` and `C2_no_positional`. Evaluate every arm on the BraTS-GLI test masks, at $R = 16$, and on the rejection condition $R = 4$, 30% burst. The loss-term arms `B1–B3` belong in the appendix. Report `A1_unbounded` as it is, even if it diverges.

5.8. Generalisation to unseen sampling geometry

The irregular families used at test time are also used, with different random seeds, during training. Results on U1–U6 therefore show robustness across the trained distribution of masks, not generalisation to an unseen geometry. Only $R = 16$ and the subject-specific rejection masks lie outside the training distribution. Three further analyses are planned to close this gap. First, leave-one-family-out training (Table 10). Second, several mask realisations per subject instead of one shared mask (Table 11). Third, an analysis of error against the local geometry of each missing slice (Fig. 8). The third analysis turns the named families into a statement about gap length and distance to the nearest kept slice, which applies to any mask.

To do before submission: held-out geometry (Tables 10, 11; Fig. 8)

(i) Train six IR3C models, each with one irregular family removed from the training distribution, at the matched budget; evaluate each on its held-out family. The "uniform-only" column is the `C1_uniform_only` arm. (ii) Generate five subject-specific masks per family at $R = 4$ (seed from the subject identifier and realisation index) and re-score linear, bicubic, ArSSR, DCSRN and IR3C; inference only. (iii) Store per-slice squared error and foreground voxel counts during re-scoring, so that error can be binned by g_z and d_z; no model needs to be retrained.

5.9. Segmentation accuracy against expert labels

The downstream result in Section 5.5 measures consistency with a fixed pipeline. A stronger test is segmentation accuracy against expert labels on subjects that the reconstruction models have never seen. The BraTS-GLI training release has labels, but all of its 1251 subjects were used to




Figure 7: Sagittal reformats of BraTS-GLI-00047-000 along the reconstruction axis (vertical). Top two rows: uniform sampling at $R = 4$. Bottom two rows: the same acquisition after 30% burst rejection. Error maps show absolute error on missing slices only (acquired slices are exact for every method and are shown black); MAE is computed over the same voxels. Ticks on the left edge of the reference mark kept (grey) and rejected (orange) acquired slices. All images share one intensity window and all error maps share one scale. I^{3}Net and SAINT use the imputation workaround in the rejection rows. The subject was selected by a rule fixed in advance (median IR3C gain among five showcase subjects).

Table 9
[Pending experiment] Formulation ablation on BraTS-GLI with the backbone, optimiser and training budget held fixed. PSNR (dB) on test subjects, $R \in \{2, 4, 8\}$ unless stated; the rejection column is $R = 4$ with 30% burst rejection. Arms named in typewriter font are already packaged for the HPC run (Section 5.7.3); "new arm" must be added. Values for multi-seed arms are to be reported as mean ± standard deviation over seeds. Only the linear row is computed.

Variant	Arm	Seeds	U0	U1–U6	U4	$R = 16$	Rejection	Δ vs. IR3C (U1–U6)
Linear interpolation only	—	—	26.20	22.70	18.45	15.86	*tbd*	—
Direct 3D U-Net (no anchor)	`A3_direct`	3	*tbd*	*tbd*	*tbd*	*tbd*	*tbd*	*tbd*
Anchor, unbounded residual	`A1_unbounded`	1	*tbd*	*tbd*	*tbd*	*tbd*	*tbd*	*tbd*
Anchor, non-zero output head	`A2_nonzero_init`	1	*tbd*	*tbd*	*tbd*	*tbd*	*tbd*	*tbd*
Anchor, no geometry profiles	`C2_no_positional`	3	*tbd*	*tbd*	*tbd*	*tbd*	*tbd*	*tbd*
Anchor, binary mask profile only	new arm	1	*tbd*	*tbd*	*tbd*	*tbd*	*tbd*	*tbd*
Anchor, uniform-only training	`C1_uniform_only`	1	*tbd*	*tbd*	*tbd*	*tbd*	*tbd*	*tbd*
Anchor, single factor ($R = 4$)	`C3_single_R`	1	*tbd*	*tbd*	*tbd*	*tbd*	*tbd*	*tbd*
IR3C (full formulation)	`A0_ir3c`	3	*tbd*	*tbd*	*tbd*	*tbd*	*tbd*	—

train the reconstruction models. This test therefore needs a new subject-level split (Table 12).

To do before submission: labelled downstream evaluation (Table 12)

Hold out about 150 labelled BraTS-GLI training subjects. Retrain IR3C and the learned baselines (at least SAINT and ArSSR) on the remaining subjects under the same matched budget. Segment with the same frozen SegResNet and report Dice and HD95 against the expert labels at $R = 4$, for U0 and pooled U1–U6. Note that the segmentation network may have seen some of these subjects during its own training; state this in the Methods. This is the most costly pending item.

To do before submission: additional baselines (shaded rows of Tables 2 and 3)

Add SA-INR (Wang et al., 2024) under the matched protocol on all three datasets. It is the closest published arbitrary-spacing method and appeared in this journal. The "3D U-Net, direct output" row is the `A3_direct` arm, evaluated on all datasets.

5.10. Computational cost

IR3C reconstructs a BraTS-GLI volume in 0.26 s, independently of R, because it processes the whole volume in a single forward pass (Table 13). DCSRN takes 1.2–2.6 s.




Figure 8: [Pending experiment] Reconstruction error against local slice geometry. Per-slice PSNR on BraTS-GLI is to be binned by (a) local gap length g_z and (b) distance to the nearest kept slice d_z, pooling U0–U6 and the rejection masks, for every method that can be run on irregular grids and for SAINT under both workarounds. Lines will show the bin mean with 95% confidence intervals across subjects.

Table 10
[Pending experiment] Generalisation to an unseen sampling family (BraTS-GLI, $R \in \{2, 4, 8\}$, PSNR in dB). "Seen" is the reported IR3C, whose training distribution contains all six irregular families. "Held out" is retrained with that family removed. "Uniform-only" is trained on U0 alone. Linear and seen IR3C are computed; the other columns are pending.

Test family	Linear	Seen	Held out	Uniform-only
U1	25.03	27.37	*tbd*	*tbd*
U2	24.50	26.84	*tbd*	*tbd*
U3	23.12	25.59	*tbd*	*tbd*
U4	18.45	21.42	*tbd*	*tbd*
U5	23.37	25.87	*tbd*	*tbd*
U6	21.73	24.27	*tbd*	*tbd*

ArSSR, I^{3}Net and SAINT take 2.9–14.3 s, and their cost depends on the factor because they run per slice or per query coordinate. IR3C is therefore 5–55 times faster than the learned baselines. One IR3C model serves all factors and patterns, whereas DCSRN and I^{3}Net use a separate model for each factor.

6. Discussion

6.1. Principal finding

The main result is a crossover between specialisation for a uniform grid and robustness to the slice pattern. SAINT remains the better method at low sparsity on a uniform grid, and clearly so on IXI-tiny. Once some acquired slices are rejected, however, the specialist needs a workaround, and both workarounds give it an input that differs from what it was trained on. IR3C applies the same inference procedure to whatever slices survive. Its advantage appears at about 10% rejection and grows with the rejected fraction. This is more informative than marking an inapplicable method as "not available": both workarounds were implemented and evaluated on identical missing slices.

6.2. Why a simple formulation is sufficient

IR3C does not owe its behaviour to a new architecture; its backbone is a standard 3D U-Net. Two properties of the formulation explain what we observe. First, linear interpolation already provides a good estimate in smooth regions and is exact at the kept slices, so the network only needs to learn the departure from local linearity. The anchor ablation supports this: the network absorbs most of a poor starting estimate, and the simplest anchor gives the best final model. Second, the geometry profiles tell the network how far each missing slice is from its neighbours and how long its gap is. The size of the correction a missing slice needs depends on these quantities, and a network that sees them can adapt one set of weights to any mask. DCSRN, which was trained on the same mixed masks without an anchor or explicit geometry, gains little over linear interpolation. This suggests that mixed-mask training is not sufficient on its own. A causal attribution to each component, however, requires the formulation ablation in Table 9, which is pending.

The bound on the residual should be interpreted with care. It limits how far the output can move from the anchor, but it does not guarantee a smaller error than linear interpolation. We do not claim formal safety or non-degradation.

6.3. Where IR3C should not be preferred

On a uniform grid at low sparsity, a specialist such as SAINT is more accurate, by up to 3.7 dB on IXI-tiny at $R = 2$. If the slice pattern is guaranteed to be uniform and the reduction factor is small, such a method is the better choice. IR3C should be preferred when the slice pattern is irregular, when acquired slices may be rejected, when R is large, or

Table 11
[Pending experiment] Sensitivity to the mask realisation (BraTS-GLI, $R = 4$). Each subject receives five independent masks per family instead of one mask shared by all subjects. Each cell is to hold the mean PSNR (dB) with the within-subject standard deviation across realisations in parentheses.

Method	U1	U2	U3	U4	U5	U6
Linear	*tbd*	*tbd*	*tbd*	*tbd*	*tbd*	*tbd*
Bicubic	*tbd*	*tbd*	*tbd*	*tbd*	*tbd*	*tbd*
ArSSR	*tbd*	*tbd*	*tbd*	*tbd*	*tbd*	*tbd*
DCSRN	*tbd*	*tbd*	*tbd*	*tbd*	*tbd*	*tbd*
IR3C (ours)	*tbd*	*tbd*	*tbd*	*tbd*	*tbd*	*tbd*

Table 12
[Pending experiment] Tumour segmentation accuracy against expert labels on a reconstruction-held-out BraTS-GLI cohort ($R = 4$, U0 and pooled U1–U6). This requires a new subject-level split in which the labelled test subjects are excluded from reconstruction training, and retraining IR3C and the learned baselines on the remaining subjects (Section 5.9).

	Dice ↑			HD95 (mm) ↓		
Method	WT	TC	ET	WT	TC	ET
Complete FLAIR (reference)	*tbd*	*tbd*	*tbd*	*tbd*	*tbd*	*tbd*
Linear	*tbd*	*tbd*	*tbd*	*tbd*	*tbd*	*tbd*
Bicubic	*tbd*	*tbd*	*tbd*	*tbd*	*tbd*	*tbd*
ArSSR	*tbd*	*tbd*	*tbd*	*tbd*	*tbd*	*tbd*
SAINT	*tbd*	*tbd*	*tbd*	*tbd*	*tbd*	*tbd*
IR3C (ours)	*tbd*	*tbd*	*tbd*	*tbd*	*tbd*	*tbd*

Table 13
Reconstruction time per BraTS-GLI volume ($240 \times 240 \times 153$), measured end to end on one NVIDIA GB10 GPU at fp32 with batch size 1. Times include patch extraction, sliding-window aggregation and output assembly, and are averaged over test volumes and three repetitions.

		Seconds per volume		
Method	Params (M)	$R = 2$	$R = 4$	$R = 8$
IR3C (ours)	4.75	0.26	0.26	0.26
DCSRN	0.22	1.22	2.57	1.22
ArSSR	6.28	11.02	6.19	3.64
I^3Net	23.21	12.62	6.22	2.90
SAINT	3.16	14.26	8.60	6.01

when a reconstruction must be fast and feed a downstream analysis.

Brain-trained IR3C also does not transfer to knee MRI without fine-tuning; applied zero-shot, it is worse than linear interpolation. The method is therefore flexible with respect to slice geometry within a trained or adapted anatomy; it is not anatomy-invariant.

6.4. Image metrics and downstream behaviour

The segmentation experiment shows that PSNR should not be the only endpoint. SAINT and I^3Net have reasonable PSNR but change the downstream segmentation substantially. The classical interpolants trail by more than 2 dB in PSNR yet remain close to IR3C on Dice, because their errors are smooth. The endpoint has a clear limitation: it measures consistency with another model's prediction, not accuracy against expert labels.

LPIPS ranks the methods differently from every pixel metric (Table 20). On OAIZIB, bicubic interpolation has about half the LPIPS of IR3C (0.184 versus 0.385) although it is more than 2 dB lower in PSNR. Learned reconstructions are smoother and closer to the reference on average, whereas interpolation preserves high-frequency texture that a natural-image feature space rewards even when that texture is misplaced (Blau and Michaeli, 2018). We therefore do not claim a perceptual advantage for IR3C.

6.5. Limitations

This study has the following limitations. (i) The degradation removes slices from a dense reference and does not model slice profile, partial-volume averaging or slice gap; the results concern slice imputation, not physical thick-slice super-resolution. (ii) The principal models use one training seed, so the paired confidence intervals describe variation across subjects, not across training runs. (iii) Checkpoint selection on BraTS-GLI uses only six validation subjects. (iv) The irregular test families are drawn from the same generators as the training masks, and one mask per family is shared across subjects (Section 5.8). (v) The downstream endpoint is consistency with a frozen network rather than accuracy against expert labels. (vi) In a voxel-based morphometry analysis on IXI-tiny (not shown), IR3C reduced the area of significant grey-matter differences compared with linear interpolation but introduced a one-signed underestimation of total grey-matter volume, which validation-based calibration removed; IR3C should not be used for volumetry without

such calibration. (vii) The rejection experiment covers the two brain datasets; the knee arm is pending.

7. Conclusion

Through-plane reconstruction methods should be evaluated on the slice patterns they will receive, not only on uniform decimation. A specialist designed for a uniform grid can be the most accurate method on that grid and still lose its advantage once a modest fraction of acquired slices is rejected. IR3C combines a standard 3D U-Net with three simple ingredients: an explicit description of the slice geometry, linear interpolation as an anchor, and exact preservation of acquired slices. Across brain and knee MRI it is competitive on uniform sampling, better than every applicable method on irregular sampling, more robust under slice rejection, least disruptive to a downstream segmentation pipeline and 5–55 times faster than the learned baselines. These results suggest that acquisition geometry deserves as much attention as network architecture in missing-slice reconstruction.

CRediT authorship contribution statement

[To be completed by the authors using the CRediT taxonomy.]

Declaration of competing interest

The authors declare that they have no known competing financial interests or personal relationships that could have appeared to influence the work reported in this paper. **[Confirm.]**

Data availability

BraTS-GLI, IXI and Osteoarthritis Initiative data are available from their custodians under their respective terms. Subject identifiers, split definitions, mask seeds and the per-volume results used for every table and figure will be released with the code where redistribution is permitted.

Code availability

Training, inference, mask generation and evaluation code, with checkpoint provenance, will be released upon publication. **[Repository URL or archive DOI.]**

Declaration of generative AI use

[Elsevier requires this statement. During the preparation of this work the authors used [tool names] in order to [purpose]. After using these tools, the authors reviewed and edited the content as needed and take full responsibility for the content of the published article.]

Acknowledgements

The authors thank the organisers of BraTS, the IXI project and the Osteoarthritis Initiative, and the developers of MONAI. **[Funding sources and grant numbers; computing support.]**

References

Ambellan, F., Tack, A., Ehlke, M., Zachow, S., 2019. Automated segmentation of knee bone and cartilage combining statistical shape knowledge and convolutional neural networks: Data from the Osteoarthritis Initiative. Medical Image Analysis 52, 109–118. doi:10.1016/j.media.2018.11.009.

Baid, U., Ghodasara, S., Mohan, S., Bilello, M., Calabrese, E., Colak, E., et al., 2021. The RSNA-ASNR-MICCAI BraTS 2021 benchmark on brain tumor segmentation and radiogenomic classification. arXiv preprint arXiv:2107.02314 .

Bakas, S., Akbari, H., Sotiras, A., Bilello, M., Rozycki, M., Kirby, J.S., et al., 2017. Advancing The Cancer Genome Atlas glioma MRI collections with expert segmentation labels and radiomic features. Scientific Data 4, 170117. doi:10.1038/sdata.2017.117.

Blau, Y., Michaeli, T., 2018. The perception-distortion tradeoff, in: Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition, pp. 6228–6237. doi:10.1109/CVPR.2018.00652.

Cardoso, M.J., Li, W., Brown, R., Ma, N., Kerfoot, E., Wang, Y., et al., 2022. MONAI: An open-source framework for deep learning in healthcare, in: arXiv preprint arXiv:2211.02701.

Charbonnier, P., Blanc-Féraud, L., Aubert, G., Barlaud, M., 1997. Deterministic edge-preserving regularization in computed imaging. IEEE Transactions on Image Processing 6, 298–311. doi:10.1109/83.551699.

Chaudhari, A.S., Fang, Z., Kogan, F., Wood, J., Stevens, K.J., Gibbons, E.K., et al., 2018. Super-resolution musculoskeletal MRI using deep learning. Magnetic Resonance in Medicine 80, 2139–2154. doi:10.1002/mrm.27178.

Chen, Y., Xie, Y., Zhou, Z., Shi, F., Christodoulou, A.G., Li, D., 2018. Brain MRI super resolution using 3D deep densely connected neural networks, in: 2018 IEEE 15th International Symposium on Biomedical Imaging, pp. 739–742. doi:10.1109/ISBI.2018.8363679.

Holm, S., 1979. A simple sequentially rejective multiple test procedure. Scandinavian Journal of Statistics 6, 65–70.

Imperial College London, 2026. IXI dataset. https://brain-development.org/ixi-dataset/. Accessed 2026.

Isensee, F., Jaeger, P.F., Kohl, S.A.A., Petersen, J., Maier-Hein, K.H., 2021. nnU-Net: a self-configuring method for deep learning-based biomedical image segmentation. Nature Methods 18, 203–211. doi:10.1038/s41592-020-01008-z.

Kainz, B., Steinberger, M., Wein, W., Kuklisova-Murgasova, M., Malamateniou, C., Keraudren, K., et al., 2015. Fast volume reconstruction from motion corrupted stacks of 2D slices. IEEE Transactions on Medical Imaging 34, 1901–1913. doi:10.1109/TMI.2015.2415453.

Kuklisova-Murgasova, M., Quaghebeur, G., Rutherford, M.A., Hajnal, J.V., Schnabel, J.A., 2012. Reconstruction of fetal brain MRI with intensity matching and complete outlier removal. Medical Image Analysis 16, 1550–1564. doi:10.1016/j.media.2012.07.004.

Lehmann, T.M., Gönner, C., Spitzer, K., 1999. Survey: Interpolation methods in medical image processing. IEEE Transactions on Medical Imaging 18, 1049–1075. doi:10.1109/42.816070.

Menze, B.H., Jakab, A., Bauer, S., Kalpathy-Cramer, J., Farahani, K., Kirby, J., et al., 2015. The multimodal brain tumor image segmentation benchmark (BRATS). IEEE Transactions on Medical Imaging 34, 1993–2024. doi:10.1109/TMI.2014.2377694.

Myronenko, A., 2019. 3D MRI brain tumor segmentation using autoencoder regularization, in: Brainlesion: Glioma, Multiple Sclerosis, Stroke and Traumatic Brain Injuries, pp. 311–320. doi:10.1007/978-3-030-11726-9_28.

Peng, C., Lin, W.A., Liao, H., Chellappa, R., Zhou, S.K., 2020. SAINT: Spatially aware interpolation NeTwork for medical slice synthesis, in: Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition, pp. 7747–7756. doi:10.1109/CVPR42600.2020.00777.

Peterfy, C.G., Schneider, E., Nevitt, M., 2008. The osteoarthritis initiative: report on the design rationale for the magnetic resonance imaging

protocol for the knee. Osteoarthritis and Cartilage 16, 1433–1441. doi:10.1016/j.joca.2008.06.016.

Remedios, S.W., Wei, S., Han, S., Zhang, J., Carass, A., Schilling, K.G., et al., 2026. ECLARE: Efficient cross-planar learning for anisotropic resolution enhancement. Journal of Medical Imaging 13, 024001. doi:10.1117/1.JMI.13.2.024001.

Ronneberger, O., Fischer, P., Brox, T., 2015. U-Net: Convolutional networks for biomedical image segmentation, in: Medical Image Computing and Computer-Assisted Intervention, pp. 234–241. doi:10.1007/978-3-319-24574-4_28.

Song, H., Mao, X., Yu, J., Li, Q., Wang, Y., 2024. I^3Net: Inter-intra-slice interpolation network for medical slice synthesis. IEEE Transactions on Medical Imaging 43, 3306–3318. doi:10.1109/TMI.2024.3394033.

Wang, X., Wang, S., Xiong, H., Xuan, K., Zhuang, Z., Liu, M., et al., 2024. Spatial attention-based implicit neural representation for arbitrary reduction of MRI slice spacing. Medical Image Analysis 94, 103158. doi:10.1016/j.media.2024.103158.

Wang, Z., Bovik, A.C., Sheikh, H.R., Simoncelli, E.P., 2004. Image quality assessment: from error visibility to structural similarity. IEEE Transactions on Image Processing 13, 600–612. doi:10.1109/TIP.2003.819861.

Wilcoxon, F., 1945. Individual comparisons by ranking methods. Biometrics Bulletin 1, 80–83. doi:10.2307/3001968.

Wohlrapp, M., Bubeck, N., Rueckert, D., Lotter, W., 2026. Evaluating the impact of medical image reconstruction on downstream AI fairness and performance, in: Proceedings of the 9th Conference on Medical Imaging with Deep Learning, pp. 4600–4638.

Wu, Q., Li, Y., Sun, Y., Zhou, Y., Wei, H., Yu, J., et al., 2023. An arbitrary scale super-resolution approach for 3D MR images via implicit neural representation. IEEE Journal of Biomedical and Health Informatics 27, 1004–1015. doi:10.1109/JBHI.2022.3223106.

Zaitsev, M., Maclaren, J., Herbst, M., 2015. Motion artifacts in MRI: A complex problem with many partial solutions. Journal of Magnetic Resonance Imaging 42, 887–901. doi:10.1002/jmri.24850.

Zhang, R., Isola, P., Efros, A.A., Shechtman, E., Wang, O., 2018. The unreasonable effectiveness of deep features as a perceptual metric, in: Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition, pp. 586–595. doi:10.1109/CVPR.2018.00068.

Zhao, C., Dewey, B.E., Pham, D.L., Calabresi, P.A., Reich, D.S., Prince, J.L., 2021. SMORE: A self-supervised anti-aliasing and super-resolution algorithm for MRI using deep learning. IEEE Transactions on Medical Imaging 40, 805–817. doi:10.1109/TMI.2020.3037187.

A. Detailed reconstruction results

Tables 14–19 give every distortion metric with standard deviations for uniform sampling and PSNR with standard deviations for each family. Means and standard deviations are computed across subjects after averaging within subject. Table 20 gives LPIPS.

Table 14
BraTS-GLI, uniform sampling (U0), pooled over $R \in \{2, 4, 8\}$. Mean ± standard deviation across 88 test subjects, after averaging within subject. Bold marks the best method.

Method	PSNR (dB) ↑	SSIM ↑	NMSE ↓	MAE ↓
Nearest	22.80 ± 2.76	0.9463 ± 0.0215	0.0329 ± 0.0191	0.0463 ± 0.0187
Linear	26.20 ± 3.21	0.9545 ± 0.0202	0.0186 ± 0.0129	0.0320 ± 0.0171
Cubic spline	26.32 ± 3.31	0.9513 ± 0.0207	0.0191 ± 0.0140	0.0323 ± 0.0178
Bicubic	26.37 ± 3.28	0.9566 ± 0.0200	0.0186 ± 0.0134	0.0314 ± 0.0174
DCSRN	20.84 ± 1.79	0.8472 ± 0.0406	0.0467 ± 0.0297	0.0688 ± 0.0146
ArSSR	23.43 ± 2.40	0.9590 ± 0.0186	0.0253 ± 0.0115	0.0561 ± 0.0147
I^3Net	26.27 ± 3.01	0.9579 ± 0.0184	0.0179 ± 0.0116	0.0322 ± 0.0154
SAINT	28.39 ± 3.45	0.9670 ± 0.0167	0.0134 ± 0.0094	0.0259 ± 0.0141
IR3C	**28.59 ± 3.59**	**0.9679 ± 0.0152**	**0.0118 ± 0.0089**	**0.0259 ± 0.0138**

Table 15
BraTS-GLI, PSNR (dB) by sampling family, pooled over $R \in \{2, 4, 8\}$. Mean ± standard deviation across test subjects.

Method	U0	U1	U2	U3	U4	U5	U6
Nearest	22.80 ± 2.76	22.35 ± 2.75	21.85 ± 2.65	20.73 ± 2.54	16.68 ± 2.11	20.79 ± 2.49	19.60 ± 2.34
Linear	26.20 ± 3.21	25.03 ± 3.25	24.50 ± 3.10	23.12 ± 2.93	18.45 ± 2.36	23.37 ± 2.86	21.73 ± 2.66
Cubic spline	26.32 ± 3.31	24.96 ± 3.37	24.36 ± 3.26	22.53 ± 3.10	17.01 ± 2.55	22.96 ± 3.08	20.82 ± 2.94
Bicubic	26.37 ± 3.28	25.17 ± 3.33	24.61 ± 3.16	23.17 ± 2.99	18.46 ± 2.40	23.42 ± 2.90	21.78 ± 2.70
DCSRN	20.84 ± 1.79	20.64 ± 1.86	20.34 ± 1.85	19.78 ± 1.87	17.02 ± 1.82	19.77 ± 1.82	18.83 ± 1.75
ArSSR	23.43 ± 2.40	22.95 ± 2.51	22.65 ± 2.46	21.94 ± 2.46	18.14 ± 2.22	21.98 ± 2.39	20.51 ± 2.25
IR3C	**28.59 ± 3.59**	**27.37 ± 3.62**	**26.84 ± 3.39**	**25.59 ± 3.17**	**21.42 ± 2.44**	**25.87 ± 3.11**	**24.27 ± 2.88**

Table 16
OAIZIB, uniform sampling (U0), pooled over $R \in \{2, 4, 8\}$. Mean ± standard deviation across 103 test subjects, after averaging within subject. Bold marks the best method.

Method	PSNR (dB) ↑	SSIM ↑	NMSE ↓	MAE ↓
Nearest	17.57 ± 0.79	0.2676 ± 0.0228	0.1637 ± 0.0164	0.0915 ± 0.0099
Linear	19.19 ± 0.82	0.3103 ± 0.0256	0.1165 ± 0.0122	0.0789 ± 0.0085
Cubic spline	18.63 ± 0.84	0.2934 ± 0.0233	0.1322 ± 0.0140	0.0846 ± 0.0091
Bicubic	18.90 ± 0.83	0.3028 ± 0.0243	0.1248 ± 0.0132	0.0818 ± 0.0088
DCSRN	19.37 ± 0.72	0.2871 ± 0.0228	0.1089 ± 0.0117	0.0778 ± 0.0070
ArSSR	20.44 ± 0.84	0.3600 ± 0.0325	0.0853 ± 0.0093	0.0677 ± 0.0074
I^3Net	20.42 ± 0.84	0.3497 ± 0.0313	0.0867 ± 0.0097	0.0670 ± 0.0074
SAINT	21.35 ± 0.90	0.3979 ± 0.0317	0.0701 ± 0.0092	0.0609 ± 0.0071
IR3C	**21.38 ± 0.90**	**0.4161 ± 0.0306**	**0.0684 ± 0.0091**	**0.0609 ± 0.0071**

Table 17
OAIZIB, PSNR (dB) by sampling family, pooled over $R \in \{2, 4, 8\}$. Mean ± standard deviation across test subjects.

Method	U0	U1	U2	U3	U4	U5	U6
Nearest	17.57 ± 0.79	17.38 ± 0.78	17.27 ± 0.78	16.78 ± 0.75	14.84 ± 0.66	16.81 ± 0.79	16.23 ± 0.71
Linear	19.19 ± 0.82	18.68 ± 0.80	18.53 ± 0.80	18.03 ± 0.77	15.87 ± 0.68	18.07 ± 0.82	17.39 ± 0.72
Cubic spline	18.63 ± 0.84	17.71 ± 0.82	17.24 ± 0.82	15.45 ± 0.75	10.57 ± 0.58	14.67 ± 0.70	14.29 ± 0.74
Bicubic	18.90 ± 0.83	18.41 ± 0.81	18.27 ± 0.81	17.79 ± 0.78	15.71 ± 0.68	17.83 ± 0.82	17.18 ± 0.73
DCSRN	19.37 ± 0.72	18.98 ± 0.71	18.84 ± 0.70	18.35 ± 0.68	16.38 ± 0.63	18.40 ± 0.72	17.81 ± 0.65
ArSSR	20.44 ± 0.84	20.13 ± 0.83	19.99 ± 0.83	19.39 ± 0.80	16.90 ± 0.71	19.49 ± 0.86	18.78 ± 0.75
IR3C	**21.38 ± 0.90**	**20.99 ± 0.87**	**20.88 ± 0.87**	**20.46 ± 0.85**	**18.59 ± 0.74**	**20.59 ± 0.89**	**19.94 ± 0.79**

Table 18
IXI-tiny, uniform sampling (U0), pooled over $R \in \{2, 4, 8\}$. Mean ± standard deviation across 100 test subjects, after averaging within subject. Bold marks the best method.

Method	PSNR (dB) ↑	SSIM ↑	NMSE ↓	MAE ↓
Nearest	19.85 ± 1.01	0.8097 ± 0.0119	0.0603 ± 0.0128	0.0621 ± 0.0111
Linear	23.07 ± 1.07	0.8464 ± 0.0101	0.0364 ± 0.0081	0.0460 ± 0.0083
Cubic spline	23.14 ± 1.15	0.8472 ± 0.0095	0.0394 ± 0.0081	0.0466 ± 0.0083
Bicubic	23.37 ± 1.12	0.8554 ± 0.0093	0.0365 ± 0.0080	0.0446 ± 0.0081
DCSRN	20.41 ± 0.93	0.7777 ± 0.0134	0.0579 ± 0.0152	0.0686 ± 0.0100
ArSSR	23.84 ± 1.52	0.9221 ± 0.0078	0.0232 ± 0.0025	0.0454 ± 0.0083
I^3Net	23.43 ± 1.09	0.8607 ± 0.0085	0.0335 ± 0.0070	0.0454 ± 0.0078
SAINT	**27.81 ± 1.79**	**0.9405 ± 0.0058**	**0.0128 ± 0.0018**	**0.0271 ± 0.0055**
IR3C	25.95 ± 1.41	0.9329 ± 0.0079	0.0154 ± 0.0023	0.0331 ± 0.0060

Table 19
IXI-tiny, PSNR (dB) by sampling family, pooled over $R \in \{2, 4, 8\}$. Mean ± standard deviation across test subjects.

Method	U0	U1	U2	U3	U4	U5	U6
Nearest	19.85 ± 1.01	19.38 ± 1.00	19.41 ± 1.00	18.15 ± 1.02	13.35 ± 0.88	17.46 ± 1.02	17.10 ± 1.11
Linear	23.07 ± 1.07	21.45 ± 1.02	21.56 ± 1.03	19.93 ± 1.04	14.56 ± 0.85	19.25 ± 0.99	18.73 ± 1.23
Cubic spline	23.14 ± 1.15	21.36 ± 1.08	21.32 ± 1.06	18.66 ± 0.92	13.04 ± 0.87	15.06 ± 0.63	16.70 ± 1.13
Bicubic	23.37 ± 1.12	21.57 ± 1.03	21.69 ± 1.05	20.01 ± 1.04	14.56 ± 0.86	19.31 ± 1.00	18.72 ± 1.24
DCSRN	20.41 ± 0.93	19.71 ± 0.94	19.69 ± 0.97	18.70 ± 0.99	14.46 ± 0.82	18.27 ± 0.93	17.93 ± 1.17
ArSSR	23.84 ± 1.52	23.19 ± 1.54	23.12 ± 1.47	22.24 ± 1.44	17.36 ± 1.12	20.88 ± 1.46	21.86 ± 1.41
IR3C	**25.95 ± 1.41**	**24.66 ± 1.35**	**24.69 ± 1.34**	**23.90 ± 1.28**	**20.26 ± 1.03**	**22.89 ± 1.23**	**23.25 ± 1.24**

Table 20
LPIPS (AlexNet features, lower is better) on uniform sampling, pooled over $R \in \{2, 4, 8\}$, mean across test subjects. Learned methods are not better than classical interpolation on this metric (Section 6.4). ‡Full-budget IR3C; LPIPS was not computed for the matched-budget transfer models.

Method	BraTS-GLI	OAIZIB	IXI-tiny
Linear	0.0385	0.1916	0.0242
Bicubic	**0.0347**	**0.1836**	0.0196
ArSSR	0.0363	0.5491	0.0188
I^3Net	—	0.4912	0.0273
SAINT	0.0388	0.4887	**0.0176**
IR3C	0.0376	0.3854‡	0.0190‡

B. Slice rejection: absolute results

Tables 21 and 22 give the absolute PSNR of every method in every rejection condition, including bicubic interpolation, DCSRN and both workarounds for I^3Net and SAINT.

Table 21
Slice rejection on BraTS-GLI: absolute PSNR (dB), mean across 88 test subjects. A: rejected slices imputed linearly, then the uniform-grid model is run at base R. B: the model is run at $2R$ on the uniform subset that lost fewer slices. Bold marks the best method per row.

Base	Pattern	Rejected	Linear	Bicubic	ArSSR	DCSRN	I^{3}Net-A	I^{3}Net-B	SAINT-A	SAINT-B	IR3C
$R=2$	—	0%	30.17	30.46	25.07	19.73	30.37	27.05	**33.37**	29.13	32.56
$R=2$	random	10%	28.40	28.62	24.53	19.71	28.53	26.52	29.73	28.29	**30.14**
$R=2$	random	20%	27.14	27.32	24.03	19.65	27.23	25.94	27.84	27.28	**29.03**
$R=2$	random	30%	25.96	26.12	23.52	19.55	26.04	25.24	26.37	26.22	**27.99**
$R=2$	burst	10%	27.12	27.30	24.03	19.56	27.22	25.66	28.13	26.81	**28.74**
$R=2$	burst	20%	25.46	25.60	23.30	19.40	25.52	24.59	25.99	25.30	**27.27**
$R=2$	burst	30%	24.09	24.19	22.55	19.19	24.14	23.61	24.37	24.03	**26.09**
$R=4$	—	0%	26.33	26.53	23.79	22.53	26.32	22.46	28.56	23.57	**29.01**
$R=4$	random	10%	24.79	24.93	23.05	22.02	24.82	22.25	25.86	23.27	**27.21**
$R=4$	random	20%	23.68	23.78	22.42	21.54	23.72	21.92	24.31	22.78	**26.06**
$R=4$	random	30%	22.47	22.50	21.65	20.90	22.51	21.38	22.78	21.98	**24.86**
$R=4$	burst	10%	24.08	24.17	22.58	21.66	24.11	21.81	25.05	22.60	**26.60**
$R=4$	burst	20%	22.40	22.42	21.60	20.76	22.44	21.02	22.90	21.50	**25.07**
$R=4$	burst	30%	21.10	21.09	20.70	19.96	21.14	20.30	21.38	20.53	**23.69**

Table 22
Slice rejection on IXI-tiny: absolute PSNR (dB), mean across 100 test subjects. A: rejected slices imputed linearly, then the uniform-grid model is run at base R. B: the model is run at $2R$ on the uniform subset that lost fewer slices. Bold marks the best method per row.

Base	Pattern	Rejected	Linear	Bicubic	ArSSR	DCSRN	I^{3}Net-A	I^{3}Net-B	SAINT-A	SAINT-B	IR3C
$R=2$	—	0%	28.17	29.07	26.32	23.53	28.63	23.67	**33.27**	28.27	29.57
$R=2$	random	10%	25.66	26.15	25.49	22.62	25.90	23.15	**27.56**	26.70	27.54
$R=2$	random	20%	23.91	24.21	24.71	21.77	24.05	22.49	24.88	25.06	**26.29**
$R=2$	random	30%	22.49	22.67	23.86	20.93	22.57	21.70	23.02	23.64	**25.33**
$R=2$	burst	10%	24.73	25.09	24.95	22.12	24.90	22.52	26.15	25.26	**26.93**
$R=2$	burst	20%	22.44	22.61	23.78	20.82	22.52	21.33	23.03	23.01	**25.49**
$R=2$	burst	30%	20.98	21.07	22.81	19.86	21.02	20.38	21.31	21.50	**24.51**
$R=4$	—	0%	22.52	22.68	23.80	20.85	22.72	19.29	**27.30**	23.17	25.27
$R=4$	random	10%	21.36	21.43	23.01	20.15	21.52	19.18	24.17	22.87	**24.59**
$R=4$	random	20%	20.28	20.28	22.33	19.42	20.42	18.88	21.98	21.89	**23.97**
$R=4$	random	30%	19.21	19.14	21.48	18.63	19.32	18.40	20.16	20.57	**23.32**
$R=4$	burst	10%	20.73	20.75	22.64	19.69	20.87	18.73	22.85	21.43	**24.30**
$R=4$	burst	20%	19.61	19.57	21.62	18.91	19.73	18.33	20.86	20.53	**23.53**
$R=4$	burst	30%	18.36	18.26	20.65	17.92	18.45	17.62	19.04	19.05	**22.80**

C. Training budget

Table 23 compares the matched-budget IR3C used throughout with the full-budget model. The matched model is 0.45 dB lower on BraTS-GLI, so the matched comparison does not favour IR3C. On the transfer datasets, the source checkpoint used to initialise fine-tuning has almost no effect.

Table 23
Effect of the source training budget on IR3C (PSNR in dB, all families, $R \in \{2, 4, 8\}$). "Matched" stops source training at 12,510 steps, the largest budget given to any baseline, and is the model used in every comparison. "Full" uses the complete 25-epoch schedule (selected at step 28,773). For OAIZIB and IXI-tiny, the two rows differ only in the source checkpoint used to initialise fine-tuning.

Dataset	Matched	Full	Full − matched
BraTS-GLI	25.71	26.16	+0.45 [0.42, 0.48]
OAIZIB	20.40	20.40	0.00 [−0.01, 0.00]
IXI-tiny	23.66	23.75	+0.10 [0.09, 0.10]