

PRODUCT SUMMARY

PCU-8E Display Unit

The PCU-8E is a lightweight driver display module designed for motorsport applications. It is designed to connect to a host ECU via CAN and present the driver with information on a 4.3" backlit LCD display and LED lamps. The display is suitable for use in direct sunlight and at night. The configuration PC software tool is supplied with the unit. There are 100 pages available that are selectable by a CAN message and each page layout is fully customisable.

APPLICATION

- Typically installed within the steering wheel, although can be remotely mounted

KEY FEATURES

- Data Display and warning lamps
- Viewable area 95mm x 54mm
- 480 x 272 pixel resolution
- Brightness adjustable via CAN message for low-light conditions.
- Sixteen gauge types for displaying data, include bar tach, rev lights and variable text
- Alarm pages or user-configurable text warnings can be triggered by CAN messages.

COMMUNICATIONS

- One CAN interface (1Mbps) with no internal termination
- One USB interface for configuration only

CONNECTION DEFINITION

- Un-terminated flying lead only (no connector fitted), length 1m

Wire Colours	Description	Wire Gauge
Orange	Unit Supply Positive	26AWG
Brown	Unit Supply Ground	26AWG
White	CAN +	26AWG
Blue	CAN -	26AWG
Green	USB +	24AWG
White	USB -	24AWG
Red	USB 5V	22AWG
Black	USB Ground	22AWG
(Drain)	USB Screen (internally connected to supply ground)	28AWG
Grey	CAN address selection input	26AWG
Yellow	Reset input	26AWG

- USB wires are contained within a cable screen, with the other wires coiled round the USB screened cables.
- Note the unit supply is required when configuring. The unit cannot be powered by USB.



INPUTS

- One reset input (active low with internal pull-up; can be left unconnected if not required)
- One CAN address selection analogue input (connect an external resistor to unit supply ground)

ELECTRICAL

- Supply voltage 8V to 16V DC
- Supply current operating (screen and all LEDs on) <0.6A typical at 13.8V

MECHANICAL

- Aluminium Case (hard black anodised)
- Weight 230g

ENVIRONMENTAL AND COOLING

- Splash resistant to standard motorsport fluids
- Lid has a rubber seal, case fixings are sealed with silicone sealant
- Maximum humidity 95% non-condensing
- Operating Temperature 0°C to +50°C
- Storage temperature -25°C to +85°C
- Vibration 100 to 1000Hz, all axes, 24 hours
- Vibration isolation is recommended

ELECTRO MAGNETIC COMPATIBILITY

- Complies with the essential protection requirements of 2004/108/EEC.

BASE UNIT

[illegible]

Email: applied_enquiries@mclaren.com www.mclarenapplied.com