

Symptoms: Users are unable to access the application. Web and mobile clients are failing to load data. The application appears to be slow or unresponsive. Some users report intermittent success, but most requests fail. The service disruption begins unexpectedly. No visible errors are presented to end users, only failed loading states. The issue affects multiple features of the application.

1. Verifying API-service status.

Analysis: Activating (auto-restart) indicates systemd is continuously attempting to restart the service due to repeated startup failures. Main PID: ... (code exited, status=1/FAILURE) confirms the process is crashing on startup, triggering systemd restarts, though the specific root cause is not yet identified.

- Analysis:** The root cause is identified by the line `OSError: [Errno 98] Address already in use`, meaning the application is trying to bind to port 8080, but another process is already using that port. This confirms a port collision.

- Analysis:** The output confirms that port 8080 is being used by python3 PID 1374.

4. Determining what started python process PID 1374 to verify whether it is legitimate or stale.

```
[jay@mainserver:~$ sudo ps -fp 1374
UID          PID    PPID  C STIME TTY          TIME CMD
root         1374      1   0  18:29 ?           00:00:00 api-service -m http.server 8080
```

Analysis: PID 1374 is a leftover python HTTP server holding port 8080. Its PPID=1 means it was orphaned and is no longer managed by a parent process. This confirms a stale process is causing the port conflict and blocking API-service from starting.

5. Terminating the stale process occupying port 8080 to allow api-service to start.

```
[jay@mainserver:~$ sudo kill 1374
```

6. Verifying API-service status.

```
[jay@mainserver:~$ sudo systemctl status api-service
● api-service.service - API Service
   Loaded: loaded (/etc/systemd/system/api-service.service; disabled; preset: enabled)
   Active: active (running) since Thu 2026-04-30 19:59:30 UTC; 7min ago
     Main PID: 4837 (python3)
       Tasks: 1 (limit: 4544)
      Memory: 9.1M (peak: 9.6M)
         CPU: 181ms
    CGroup: /system.slice/api-service.service
            └─4837 /usr/bin/python3 -m http.server 8080
```

Analysis: API-service successfully binds to port 8080.

7. Verifying the API-service with curl from both the server and a remote client.

```
[jay@mainserver:~$ curl http://localhost:8080
<!DOCTYPE HTML>
<html lang="en">
<head>
<meta charset="utf-8">
<title>Directory listing for /</title>
</head>
<body>
<h1>Directory listing for /</h1>
<hr>

[alejandrorabadan@Mac ~ % curl http://192.168.64.10:8080
<!DOCTYPE HTML>
<html lang="en">
<head>
<meta charset="utf-8">
<title>Directory listing for /</title>
</head>
<body>
<h1>Directory listing for /</h1>
```

Analysis: API-service fully functional. The issues is resolved.

Conclusion: The API-service outage was caused by a port conflict on port 8080. The service failed to start due to OSError: [Errno 98] Address already in use, caused by a stale orphaned python HTTP server (PID 1374) still binding the port. After identifying and terminating the conflicting process, API-service successfully restarted, bound to port 8080, and full functionality was restored. Remote and local verification confirmed normal operation.