

HTML DOM Properties	Description
accessKey	The “ accessKey ” sets or returns the accesskey HTML DOM property.
attributes	The “ attributes ” HTML DOM property outputs a NamedNodeMap of the attribute of an HTML element.
activeElement	The “ activeElement ” property gets the element that is currently active.
childElementCount	The “ childElementCount ” HTML DOM property is utilized for displaying the total number of an HTML element’s child elements.
childNodes	The “ childNodes ” HTML DOM property outputs the child nodes of an HTML element.
classList	The “ classList ” HTML DOM property returns an element’s class name.
className	The “ className ” HTML DOM property is utilized for changing or displaying the HTML class name value.
clientHeight	The “ clientHeight ” HTML DOM property outputs the HTML element’s height.
clientLeft	The “ clientLeft ” HTML DOM property is utilized for displaying the left border’s width of an HTML element.
clientTop	The “ clientTop ” HTML DOM property is utilized for displaying the top border’s width of an HTML element.
clientWidth	The “ clientWidth ” property returns or outputs the width of an element, which includes padding.
contentEditable	The “ contentEditable ” HTML DOM property sets or returns whether an element’s content is editable or not.
dir	The “ dir ” HTML DOM property is utilized for changing or displaying an element’s dir value.
firstChild	The “ firstChild ” HTML DOM property is utilized for displaying the first child node of an HTML element.
firstElementChild	The “ firstElementChild ” HTML DOM property is utilized for displaying the first child element of an HTML element.
id	The “ id ” HTML DOM property is utilized for changing and

	displaying an element's id attribute value.
innerHTML	The “ innerHTML ” HTML DOM property is utilized for changing and displaying the element's content.
innerText	The “ innerText ” HTML DOM property is utilized for changing and displaying the node's text content and its descendants.
isContentEditable	The “ isContentEditable ” HTML DOM property is utilized for checking if an element's content is editable or not.
lang	The “ lang ” HTML DOM property is utilized for setting the lang attribute's value of an HTML element.
lastChild	The “ lastChild ” property returns an elements' last child node.
lastElementChild	The “ lastElementChild ” HTML DOM property is utilized to display an element's last child element.
namespaceURI	The “ namespaceURL ” HTML DOM property is utilized to output the namespace URI of an HTML element.
nextSibling	The “ nextSibling ” HTML DOM property is utilized for displaying the next node in a tree level.
nextElementSibling	The “ nextElementSibling ” HTML DOM property is utilized for displaying the next HTML element in a tree level.
nodeName	The “ nodeName ”HTML DOM property outputs the node name.
nodeType	The “ nodeType ” HTML DOM property is utilized for displaying the node type.
nodeValue	The “ nodeValue ” HTML DOM property is utilized for displaying or changing the node value.
ownerDocument	The “ ownerDocument ” property sets or returns the root element or document object for an element.
parentNode	The “ parentNode ” HTML DOM property is utilized for displaying the parent node of an element.
parentElement	The “ parentElement ” HTML DOM property is utilized for displaying the HTML element's parent element.
previousSibling	The “ previousSibling ” HTML DOM property is utilized for displaying the HTML element's previous sibling.

<code>previousElementSibling</code>	The “ previousElementSibling ” HTML DOM property is utilized for displaying the sibling of the previous HTML element.
<code>scrollHeight</code>	The “ scrollHeight ” HTML DOM property is utilized for displaying the height of an HTML element.
<code>style</code>	The “ style ” HTML DOM property is utilized for changing or displaying the attribute’s value of an HTML element.
<code>tabIndex</code>	The “ tabIndex ” HTML DOM property is utilized for changing or displaying the attribute’s tab index value of an HTML element.
<code>tagName</code>	The “ tagName ” HTML DOM property is utilized for displaying an element’s tag name.
<code>textContent</code>	The “ textContent ” HTML DOM property is utilized for changing or displaying a node’s textual content.
<code>title</code>	The “ title ” is utilized for changing or displaying the title attribute’s value of the HTML element.
<code>scripts</code>	The “ scripts ” property is used to get all the script elements.
<code>strictErrorChecking</code>	The “ strictErrorChecking ” property is utilized for setting the error checking to strict mode.
<code>URL</code>	The “ URL ” HTML DOM property is utilized for getting the full URL of an HTML document.