PC MAX TX Split Phase Online UPS 6-10KVA

- DSP control, with excellent performance and comprehensive protections
- Output power factor1.0, offering more stronger load capability
- Output with isolation transformer
- Most advanced 3 level inverter technology, 94% efficiency in normal mode
- Ultra Wide Input: 110V-300Vac , well compatible with Gen-set
- IBM charger 1-12A settable,extending battery lifespan and satisfying fast charging requirement
- Standard model with external battery interface for extending back up time
- Battery test and EOD voltage settable on LCD
- Simple design for fast and easy maintenance
- Default equipped with battery breaker for safety and convenient operation
- Compact design to save installation space
- Configurable output function 110/220Vac or 120/240Vac by LCD
- AC and cold start
- .Double switch input breaker with DC breaker
- Standard USB&RS232 interface,and EPO, SNMP card （optional）
- Conformal coating PCB for more critical operation environment(optional)
- Convertible frequency (input 60Hz, output 50Hz, vice versa)
- Manual bypass (optional)

Technical Specification:

Model		PCM6KL-TX	PCM6KS-TX	PCM10KL-TX	PCM10KS-TX
Capacity(kVA/kW)		6kVA/6kW		10kVA/10kW	
Input PF		≥0.99			
Input voltage	Phase	2 Lines			
	Low transfer	L-L:176 VAC ± 3% @ 100% load;110 VAC ± 3% @ 50% load			
	Low back	L-L188 VAC ± 3% @ 100% load,142 VAC ± 3% @ 50% load			
	High transfer	L-L 300 VAC ± 3%			
	High back	L-L:280 VAC ± 3%			
Input frequency		50/60Hz+/-10%			
THDi		≤3%(linear load),≤5%(non-linear load)			
Battery					
Quantity		16 ,18 or 20PCS*12Vdc settable			
Back up time		Standard model : 5-12mins depends on load Long run model:depends on external Battery			
DC voltage		192,216 or 240Vdc ,settable			
Charge voltage		220/248/275Vdc			
Recharging current		1-12A adjustable			
Output					
Output P.F		1.0			
Output voltage		104/208Vac,110/220Vac or 120/240Vac +/-1%(settable)			
Frequency		46~54Hz or 56~64Hz (Line mode) 50/60Hz ± 0.1Hz (Battery mode)			
Crest factor		3:1(max)			
Wave distortion		Less than 3%(linear load), Less than 5% Non-linear load			
Over load		105%<load<125% for 1mins ,125%<load<150% for 30sec			
Efficiency		≥94%(Line mode)			
		≥93%(battery mode)			
		≥98%(ECO mode)			
Transfer time		0ms (AC-Battery);			
		0 ms(bypass-inverter)			
Alarms					
Battery mode		Sounding every 4 seconds(can mute)			
Low battery		Sounding every second			
Overload		Sounding every second			
Faulty		Continuously sounding			
Management					
Smart RS-232/USB		Supports Windows® 2000/2003/XP/Vista/2008, Windows® 7, Linux, Unix, and MAC			

Optional	SNMP/AS400			
Environment				
Operation Humidity	0-90 % RH (non-condensing) @ 0- 40°C			
Noise Level	Less than 55dBA @ 1 Meter		Less than 60dBA @ 1 Meter	
Physical				
Model	**PCM6KL-TX**	**PCM6KS-TX**	**PCM10KL-TX**	**PCM10KS-TX**
Net Weight (KG)	54	93	65	112
Gross Weight(KG)	59	100	70	119
UPS (D*W*H)mm	460*200*360	460*200*720	460*200*360	460*200*720
Packing (D*W*H)mm	680*380*834	680*380*1074	680*380*834	680*380*1074

Remark: Specification is subject to change without further notice.