A Project Report on

STATISTICAL ANALASIS AND PERSONALIZED BOOK RECOMMENDATION SYSTEM USING USER PREFERENCE DATA



UNIVERSITY POST GRADUATE COLLEGE (OU)
SECUNDERABAD

(A Constituent College of Osmania University)

DEPARTMENT OF DATA SCIENCE

M.SC.DATA SCIENCE II YEAR

[2025-2026]

Submited By

VARKOLU ALEKHYA **101024559035**

Under the Guidance Of

K . Satyanna

(Assistant Professor(c), Dept of Computer Science)

UNIVERSITY POST GRADUATE COLLEGE OU SECUNDERABAD

(A Constitution College of Osmaniya University)

Established in 1947

S.P.Road, Paradise, Secunderabad-500003, Telangana, India

Tel: 8331997328, **Website**: www.upgcs.ac.in,

Email : oupgcs@gmail.com

CERTIFICATE

This is to certify that the mini project work report entitled "**Statistical Analasis and Personalized Book Recommendation System using User Preference Data**" submitted by **Varkolu Alekhya** bearing Roll Number:1010-24-559-035 respectively, studying in MSc. Data Science IV Semester, to the Department of Data Science, University Post Graduate College OU Secunderabad, Hyderabad, is record of the original project work carried out by them under my guidance and supervision during the IV semester of MSc. Data Science program. The work embodied in this project work has not been submitted fully or in part anywhere else

Guide	Head
K. Satyanna	Dr. B. Suresh
Assistant Professor	Assistant Professor

Department of Data Science

Name and Signature of External Examiner

DECLARTION

I’m Varkolu Alekhya (Roll No: 1010-24-559-035) here by declare that the technical report entitled “**Statistical Analasis and Personalized Book Recommendation System using User Preference Data**” is done by me, submitted in partial fulfilment of the requirements for the award of the degree of MSc. Data Science in the year 2025-2026.

Date:

Place: SECUNDERABAD Varkolu Alekhya - 1010-24-559-035

AKNOWLEDGEMENT

I express my sincere gratitude to **Prof. S. Kavitha Devi Principal**, OUPGCS, for providing and excellent academic environment in the college. I express my gratitude to **Dr. B. Suresh**, Assistant Professor Head of the Department, for providing with both time and amenities to make this project a success within the time schedule. I take a unique privilege to express my thanks to **K.Satyanna**, **Assistant Professor** internal guide, for his valuable guidance and encouragement given to me throughout this project. It has been a highly encouraging and knowledge gaining experience which has been a source of inspiration throughout the project and has helped me with all my problems. During this work I have gained both practical as well as theoretical knowledge of great significance. I am greatly thankful to all faculty members of PG College who have helped me through this work. I am greatly obliged to **K.Satyanna**, **Assistant Professor** for his suggestions and help apart from that we are highly obliged to our internal guide.

K.Satyanna, **Assistant Professor**

I extend my thanks to all the people, who have helped me a lot directly or indirectly in the completion of academic projects.

Best regards

Abstract

A statistical analysis and personalized book recommendation system based on user preference data are presented in this dissertation. A Book Recommendation Dataset including data on books, readers, and ratings is used in the study. To find significant trends in user ratings and preferences, the data is preprocessed and examined. To analyze user rating behavior and relationships within the data, statistical methods including descriptive statistics, Pearson correlation, independent-samples t-test, and one-way ANOVA are used.

By integrating content-based filtering using TF-IDF and cosine similarity with collaborative filtering using SVD, a hybrid recommendation method is created. While a cold-start method offers popular book suggestions for customers with little rating history, the system creates customized Top-N book recommendations depending on user preferences. RMSE and MAE are used to assess the recommendation performance. The study shows how relevant and customized book suggestions may be produced by combining statistical analysis with hybrid recommendation approaches.

TABLE OF CONTENTS

1.INTRODUCTION

1.1 Introduction _____1

1.2 Motivation To Topic _____2-3

1.3 Significance and need of the study _____4-7

1.4 Problem Statement _____7-9

1.5 Objectives of the study_____9-12

1.6 Chapter wise summary _____12

2. REVIEW OF LITERATURE

2.1 Introduction_____13

2.2 Authors Contributed Related to the Study _____14-17

2.3 Comparison Analysis _____18-19

3. DATA DOMAIN

3.1 Introduction _____20-21

3.2 Domain Knowledge _____22-25

3.3 About the Dataset _____26-27

3.4 Data Collection Process _____27-28

3.5 Dataset Characteristics _____28-30

3.6 Dataset Variables _____30-34

4 . STATISTICAL TOOLS AND SOFTWARE'S USED

4.1 Introduction_____ 35

4.2 Statistical Software Used_____35-36

4.3 Basic Statistical Tools Used _____ 37-40

4.4 Advanced Statistical Techniques Used _____40-44

4.5 Chapter Summary 44-45

5 DATA VISULIZATION

5.1 Introduction 46

5.2 Statistical Data Visualization and Interpretation 46-53

5.3 Overall Results Interpretation 53

5.4 Chapter Summary 54

6. EXPLORATORY DATA ANALYIS

6.1 Introduction 55

6.2 Dataset Overview 55-57

6.3 Descriptive Statistics 58-59

6.4 Exploratory Data Analysis 59-63

6.5 Key Findings from Exploratory Data Analysis 6 64

6.6 Chapter Summary 65

7. ADVANCED STATISTICAL ANALYSIS AND MODEL BUILDING

7.1 Introduction 66

7.2 Analysis of Variance (ANOVA) 67-69

7.3 Pearson Correlation Analysis 70-71

7.4 Independent Sample *t*-Test 72-74

7.5 Descriptive Statistical Analysis 74-77

7.6 Statistical Findings and Model Justification 77-78

7.7 Chapter Summary 79

8. CONCLUSIONS AND FUTURE SCOPE

8.1 Conclusion 80-81

8.2 Future Scope 81-82

9. APPENDIX

9.1 Program Code for Implementation_____83-105

10. BIBLIOGRAPHY

10.1 References_____ 106-109

11. Plagarism Report_____110

1.INTRODUCTION

1.1 Introduction:

Readers now have access to thousands of books thanks to the quick development of digital libraries, e-commerce sites, and online reading apps. Users frequently struggle to find books that fit their interests because of this huge collection. By evaluating users' interests and suggesting books they are likely to like, a book recommendation system assists users in finding relevant books. By cutting down on search time and recommending books based on individual reading preferences, personalized recommendation systems enhance user experience.

This project combines content-based and collaborative filtering methods to create a hybrid personalized book recommendation system. Based on the tastes of users who share similar interests, Collaborative Filtering makes book recommendations. In this research, the user-book rating matrix is analyzed using the Singular Value Decomposition (SVD) algorithm to forecast ratings for books that users have not yet evaluated. Content-Based Filtering suggests books that a user has loved in the past. Book details like title, author, and publisher are converted into numerical features using TF-IDF (Term Frequency–Inverse Document Frequency), and the similarity across books is measured using Cosine Similarity. The accuracy and personalization of recommendations are increased when these two methods are combined.

The Cold Start Problem and Data Sparsity are two significant issues in recommendation systems that are addressed by the suggested approach. When a new user or book has little to no rating history, it can be challenging to provide tailored recommendations. This is known as the "Cold Start Problem." Because most users only rate a small number of books, the user-book rating matrix has a large number of missing values, which leads to data sparsity. The system use SVD to infer missing ratings from current user behavior and popularity-based suggestions for new users in order to mitigate these problems.

By examining user rating trends, comprehending the connections between variables, and assessing the recommendation system's effectiveness, statistical analysis is crucial to this project. Prediction accuracy and suggestion quality are evaluated using descriptive statistics, correlation analysis, data visualization, and assessment metrics including RMSE, MAE, Precision, and Recall. These statistical methods aid in assessing how well the system anticipates user preferences and produces pertinent recommendations.

The project's goal is to create a scalable and effective hybrid recommendation system that offers precise, tailored, and comprehensible book recommendations. The system seeks to enhance user happiness, recommendation quality, and overall decision-making in book recommendation applications by fusing statistical analysis with machine learning approaches.

1.2 Motivation To Topic

The availability of books through online bookstores, digital libraries, and e-learning platforms has greatly grown due to the quick development of digital technology. Every year, thousands of books are released and made accessible to readers, making it more challenging for users to choose books that fit their tastes and interests. Because of this, people frequently spend a lot of time looking for appropriate books, which causes information overload and lowers user happiness. The demand for intelligent recommendation systems that can help consumers find suitable books quickly has arisen as a result of this expanding difficulty.

A single recommendation method, such Collaborative Filtering or Content-Based Filtering, is typically used by traditional book recommendation systems. Despite their widespread use, these techniques have a number of drawbacks. Collaborative Filtering relies on past user ratings and encounters issues like the Cold Start Problem, which prevents recommendations for freshly uploaded books or new users from being created efficiently because there is no

rating history. Additionally, it has a lot of missing values in the user-book rating matrix because most users only rate a small number of books due to data sparsity. Conversely, Content-Based Filtering suggests books based on their features or content, however it may result in recommendations that are too similar to the user's prior selections, decreasing the variety of recommendations.

The creation of a hybrid book recommendation system, which combines the advantages of content-based and collaborative filtering, was spurred by these constraints. In this study, TF-IDF and Cosine Similarity are utilized to assess book content and find comparable books, while Singular Value Decomposition (SVD) is used to forecast missing user ratings by discovering hidden relationships in the user–book rating matrix. By combining these methods, the system reduces the effects of Cold Start and Data Sparsity issues while producing recommendations that are more precise, customized, and dependable.

The chance to use statistical analysis to solve a practical recommended issue is another important reason for choosing this subject. Understanding user behavior, examining rating distributions, determining correlations between variables, and assessing the efficacy of recommendation systems all depend heavily on statistics.

The quality and accuracy of the generated suggestions are evaluated using methods including correlation analysis, exploratory data analysis, descriptive statistics, and performance evaluation metrics like RMSE, MAE, precision, and recall. This experiment shows how statistical techniques can help machine learning models make data-driven, meaningful decisions.

Recommendation systems are becoming a crucial part of contemporary digital platforms including online bookstores, streaming services, e-commerce websites, and digital libraries,

which is another reason the topic was chosen. Enhancing suggestion accuracy and personalization improves user experience, boosts user engagement, and makes it easier for users to find relevant material. In addition to helping users, a well-designed recommendation system aids businesses in raising customer happiness and advertising related products and services.

The overall goal of this research is to combine statistical analysis and machine learning methods to create a scalable, effective, and customized book recommendation system. The suggested hybrid strategy seeks to increase recommendation accuracy, get beyond the drawbacks of conventional recommendation techniques, and offer relevant book recommendations depending on user preferences. This work is highly applicable to the fields of statistics and data science since it also shows how statistical concepts can be used practically to solve a real-world issue.

1.3 Significance and need of the study

The way individuals access books and reading materials has changed as a result of the internet's broad use and the quick development of information technology. Millions of books in many languages and genres are now accessible to users through digital libraries, online retailers, and e-learning platforms. While this abundance of options gives readers more options than ever before, it also makes choosing books that suit their tastes and interests extremely difficult. The method is challenging and ineffective since users frequently spend a significant amount of time looking through big collections. An intelligent recommendation system that can evaluate user preferences and offer tailored book recommendations is therefore becoming more and more necessary. By creating a hybrid book recommendation system that helps consumers find pertinent books fast and precisely, this study fills this demand.

This study's proposal for a Hybrid Book Recommendation System, which combines Collaborative Filtering (Singular Value Decomposition, or SVD) and Content-Based Filtering (TF-IDF and Cosine Similarity), is one of its main contributions. Conventional recommendation systems typically just use one recommendation method, which frequently leads to recommendations that are not very accurate or personalized. Collaborative Filtering makes book suggestions based on user rating patterns, however it has issues like the Cold Start Problem, which prevents recommendations from being generated for new users or freshly uploaded books because rating history is missing. Due to the fact that the majority of users only rate a limited number of books, the user-book rating matrix has many missing values, which is another issue with data sparsity.

Conversely, content-based filtering makes book recommendations based on textual properties, but it may frequently suggest books with similar qualities, which lowers the diversity of recommendations. The suggested hybrid model improves suggestion quality, dependability, and personalization by combining the advantages of both methods while reducing their respective drawbacks.

The use of statistical analysis in the realm of recommendation systems is another significant aspect of this research. Understanding user behavior, spotting trends in rating data, and assessing recommendation models' efficacy all depend heavily on statistical techniques. While exploratory data analysis and data visualization approaches assist in identifying trends, distributions, and correlations among users, books, and ratings, descriptive statistics are employed in this study to describe the features of the dataset.

The associations between variables are examined using correlation analysis, and the suggested model's prediction accuracy and recommendation quality are evaluated using performance evaluation measures like Root Mean Square Error (RMSE), Mean Absolute Error (MAE),

Precision, and Recall. The successful application of statistical methods to real-world situations requiring big datasets is demonstrated by the integration of statistical analysis with machine learning techniques.

The fact that this study advances recommendation systems' scalability and efficiency makes it noteworthy as well. High computing resources are frequently needed to process and generate recommendations for large-scale datasets. Preprocessing methods, dimensionality reduction using SVD, and feature extraction using TF-IDF all contribute to the optimization of the recommendation process in this project by lowering computational complexity without sacrificing suggestion accuracy.

The suggested system can effectively handle massive volumes of book and user preference data, which makes it appropriate for real-world deployment. This illustrates how machine learning and statistical methods can be successfully integrated to create scalable and computationally effective recommendation systems.

Online bookstores, digital libraries, educational institutions, publishing businesses, and e-learning platforms are just a few of the digital platforms that can benefit from the study's conclusions. The suggested approach shortens the time needed to find relevant books, improves the reading experience overall, and assists users in finding books that align with their interests by offering tailored book recommendations. From a commercial standpoint, tailored suggestions can boost customer happiness, boost user engagement, promote recurring use of digital platforms, and facilitate better decision-making. Based on students' interests and reading inclinations, the recommendation system can also help libraries and educational institutions select relevant learning materials. From an academic standpoint, this work shows how statistical techniques and Python programming may be used practically to analyze vast amounts of consumer preference data

It demonstrates how user behavior can be understood and the efficacy of the suggested recommendation system evaluated using statistical methods such descriptive statistics, exploratory data analysis, correlation analysis, and performance evaluation. By emphasizing the significance of hybrid recommendation techniques and statistical evaluation methods, the study also lays the groundwork for future research in recommendation systems. To further enhance recommendation quality, researchers can expand this work by adding deep learning models, sophisticated artificial intelligence approaches, real-time user behavior monitoring, and other user demographic or contextual data.

All things considered, the study's importance stems from its capacity to integrate statistical analysis with hybrid recommendation methods to create a precise, customized, scalable, and effective book recommendation system. The suggested approach shows the usefulness of statistics in analyzing user preference data and assessing suggestion performance in addition to addressing significant issues like Cold Start and Data Sparsity. This study advances intelligent recommendation systems and its applications in contemporary digital settings by increasing suggestion accuracy and user pleasure.

1.4 Problem Statement

The proliferation of digital libraries, online bookstores, and e-learning platforms has significantly expanded the availability of books to readers. Although this expansion offers users a diverse array of options, it also complicates the process of identifying books that align with their interests and preferences. Users frequently need to sift through thousands of books to find relevant ones, a process that is both time-consuming and prone to information overload. As the volume of accessible data continues to grow, manual searching becomes increasingly inefficient, underscoring the necessity for an effective recommendation system capable of automatically suggesting appropriate books based on user preferences. Current book

recommendation systems predominantly employ Collaborative Filtering or Content-Based Filtering to generate suggestions. Despite their widespread use, these methods exhibit several limitations that impact the quality and reliability of the recommendations. Collaborative Filtering, for instance, generates recommendations by analyzing the ratings and preferences of users with similar interests.

Nonetheless, this method relies extensively on past rating data. When a new user enters the system or a new book is introduced, there is not enough data to produce valuable recommendations. This issue is referred to as the Cold Start Problem, which greatly diminishes the recommendation system's efficiency for newcomers and newly added books. Another significant issue encountered by Collaborative Filtering is Data Sparsity. In practical datasets, most users rate only a few books, leading to a user–book rating matrix with numerous gaps. Due to this limited interaction data, finding similarities among users or books becomes challenging, resulting in less precise recommendations. Sparse data also impacts the overall prediction accuracy of the recommendation system, particularly when handling extensive datasets. Similarly, Content-Based Filtering suggests books by matching their attributes, such as title, author, or textual description, with those of books the user has previously liked.

While this method does not depend on user ratings, it frequently suggests books that closely resemble those already chosen by the user, thereby diminishing the diversity of recommendations. Furthermore, its effectiveness is contingent upon the availability and quality of book information. Incomplete or inadequate book descriptions or metadata can lead to a decline in recommendation quality. Another significant challenge involves the efficient management of large-scale datasets. As the number of users and books grows, recommendation systems demand increased computational resources and processing time. Without appropriate preprocessing and optimization techniques, generating recommendations for a substantial user

base becomes computationally intensive and less efficient. Consequently, enhancing scalability and computational efficiency is a crucial requirement for contemporary recommendation systems. Given these limitations, it is imperative to develop a recommendation system capable of addressing the challenges of Cold Start, Data Sparsity, limited recommendation diversity, and computational efficiency, while ensuring accurate and personalized recommendations.

In order to overcome these issues, his study suggests a Hybrid Personalized Book Recommendation System that combines Content-Based Filtering (TF-IDF and Cosine Similarity) with Collaborative Filtering (SVD). Additionally, statistical analysis is used to analyze user preference data, comprehend rating trends, and assess the recommendation system's effectiveness using relevant statistical metrics. Based on user preference data, the suggested method seeks to offer a more efficient way to produce dependable and customized book recommendations.

1.5 Objectives of the study

Objective 1: Development of a Hybrid Book Recommendation System

Description: This study's main goal is to create a hybrid book recommendation system that offers precise, dependable, and personalized book suggestions by combining Collaborative Filtering and Content-Based Filtering. The approach seeks to enhance recommendation quality by employing both user rating behavior and book content, as opposed to relying solely on one recommendation method.

Approach:

- Obtained and prepared the Book-Crossing dataset.
- To find books that are comparable, TF-IDF and Cosine Similarity were used.
- Singular Value Decomposition, or SVD, was used to forecast the absence of user ratings.
- combined the two methods to produce ranked and customized book suggestions.

Objective 2: Handling Cold Start and Data Sparsity Problems

Description: This goal is to lessen the effects of two prevalent issues in recommendation systems: the Cold Start Problem and Data Sparsity. The goal is to deliver trustworthy suggestions even in situations where user rating data is scarce.

Approach:

- Popular books are suggested for new users based on the average rating and rating count.
- To increase the dependability of recommendations, books with a rating count of at least 50 were chosen.
- To estimate missing ratings and lessen the effect of sparse user-book interactions, the SVD technique was used.

Objective 3: Enhancing Personalization Using User Preference Data

Description: By examining user preferences and rating patterns, the goal is to enhance suggestion personalization. The technology creates personalized book recommendations based on each user's preferences.

Approach:

- examined rating trends and user demographic data.
- used statistical analysis to examine user preference data.
- SVD-based Collaborative Filtering was used to forecast book evaluations for individual users.
- created tailored suggestions based on anticipated preferences.

Objective 4: Improving Scalability and Computational Efficiency

Description: In order to process huge datasets with less processing time and memory use while preserving suggestion quality, this objective is to increase the recommendation system's scalability and computational efficiency.

Approach:

- chosen the texts that were most pertinent to the analysis.
- During preprocessing, duplicate book records were eliminated.
- TF-IDF vectorization was used to effectively transform textual input into numerical characteristics.
- optimized data processing to produce less computationally complex recommendations.

Objective 5: Evaluating Recommendation Quality and System Performance

Description: The ultimate goal is to use statistical performance metrics to assess the suggested recommendation system's efficacy. This aids in evaluating the hybrid model's overall dependability, forecast accuracy, and suggestion quality.

Approach:

- RMSE and MAE were used to assess prediction accuracy.
- Precision and recall were used to evaluate the quality of recommendations.
- analyzed user rating trends statistically.
- evaluated the hybrid recommendation system's performance by interpreting the evaluation's findings.

1.6 Chapter wise summary

The study on the Statistical Analysis of a Personalized Book Recommendation System Based on User Preference Data is thoroughly introduced in this chapter. It starts by outlining the idea of book recommendation systems, its significance in assisting users in finding pertinent books from extensive digital collections, and the increasing demand for tailored recommendations in online bookstores and digital libraries.

The chapter discusses the growing number of books available, the difficulties readers encounter in locating appropriate books, and the necessity of intelligent recommendation systems in order

to explain why the topic was chosen. The need of tailored recommendations, the use of statistical analysis to comprehend user preferences, and the usefulness of the suggested approach for digital platforms and educational applications are all highlighted in the explanation of the study's necessity and significance.

The chapter also establishes the problem statement by outlining the main limitations with current recommendation systems, such as the restricted diversity of recommendations, data sparsity, the cold start problem, and scalability problems. It highlights the need for a more efficient hybrid recommendation system that can solve these issues and offer precise and customized book recommendations.

The chapter concludes by outlining the study's goals, which include creating a hybrid recommendation system, resolving data sparsity and cold start problems, boosting personalization, increasing computing efficiency, and assessing the system using statistical performance metrics. Overall, this chapter lays a solid basis for the project's next chapters by establishing the study's background, goal, scope, and direction.

2. REVIEW OF LITERATURE

2.1 Introduction

Any research study must include a literature review since it offers a complete overview on the source of information available on the research subject. It makes it possible for researchers to analyze various approaches, contrast their results, highlight their advantages and disadvantages, and discover research gaps that require more study. Many researchers have put out many methods in the field of recommendation systems to enhance computing efficiency, scalability, personalization, and suggestion accuracy.

Book recommendation systems have grown in importance as a field of study due to the quick expansion of digital libraries, online bookstores, and e-learning platforms. Finding books that fit their interests and tastes has become more challenging for users due to the growing number of books available. Researchers have created a number of recommendation methods, including Collaborative Filtering, Content-Based Filtering, Hybrid Recommendation Systems, Tag Mining, Semantic Relationship Analysis, and Matrix Factorization, to tackle this problem. These methods assist in making book recommendations based on user preferences, book attributes, or both.

Recommendation systems have come a long way, but there are still a number of obstacles to overcome, such as the Cold Start Problem, data sparsity, limited recommendation diversity, and computational complexity. In order to enhance suggestion performance, recent research has concentrated on combining several recommendation strategies and using statistical analysis. By utilizing Collaborative Filtering (SVD) and Content-Based Filtering (TF-IDF and Cosine Similarity), the current study expands on previous contributions by creating a Hybrid Personalized Book Recommendation System. The contributions of earlier scholars whose work serves as the foundation for the proposed study are reviewed in the part that follows.

2.2 Authors Contributed Related to the Study

1. F. Wayesa, M. Leranso, G. Asefa, and A. Kedir (2023)

Title: Pattern-Based Hybrid Book Recommendation System Using Semantic Relationships

Method Description

The authors presented a Pattern-Based Hybrid Recommendation System that integrates Semantic Relationship Analysis, Collaborative Filtering, and Content-Based Filtering. To comprehend the contextual similarity between books, semantic linkages between them are extracted. To provide customized recommendations, user preferences and book content are combined. The hybrid technique uses both rating data and semantic knowledge to increase the quality of recommendations.

Key Points

- created a recommendation model that is hybrid.
- Semantic relationship analysis was used to quantify similarity more accurately.
- combined book features and user ratings.
- increased diversity and accuracy of recommendations.
- lessened the effect of sparse data.
- generated recommendations for individual books.

Limitation

- need extensive metadata and semantic information.
- Compared to conventional methods, computational complexity is higher.

Relation to Study

This study encourages the use of Collaborative Filtering and Content-Based Filtering in the suggested system and promotes the usage of a hybrid recommendation strategy.

2. K. Mankar, S. Pawar, H. Agarwal, T. Sangale, and S. Kulkarni (2023)

Title: Web-Based Book Recommendation System Using Collaborative Filtering

Method Description

The authors used Collaborative Filtering to create a web-based recommendation system in which rating patterns are used to determine user similarities. By recognizing people who share similar interests and estimating the books they might like, recommendations are produced.

Key Points

- Collaborative filtering based on user input was put into practice.
- created customized suggestions based on past evaluations.
- increased relevancy of recommendations.
- appropriate for web-based programs.
- showed how to compute similarity effectively.
- Simple to use and keep up.

Limitation

- The cold start issue is a problem.
- Sparse rating data results in lower performance.

Relation to Present Study

The foundation for using Collaborative Filtering is presented in this study, which also emphasizes the necessity of using a hybrid strategy to get over its drawbacks.

3. Z. Wang and Y. Wang (2024)

Title: Digital Library Book Recommendation System Based on Tag Mining

Methodology

In order to determine user interests and suggest books with related subjects, the authors suggested a Tag Mining-based recommendation system that examined user-generated tags and metadata.

Key Findings

- Tag analysis leads to more relevant recommendations.
- improved comprehension of consumer preferences.
- a greater variety of recommendations.
- used metadata for recommendations in an efficient manner.
- appropriate for settings in digital libraries.

Limitations

- largely relies on tags created by users.
- Incomplete metadata reduces performance.
- For users without marking history, it is less effective.

Research Gap

The study did not use rating prediction models or hybrid recommendation techniques; instead, it mostly relied on metadata and tag information.

Relevance to the Present Study

The suggested study incorporates Collaborative Filtering for improved personalization and expands text analysis utilizing TF-IDF and Cosine Similarity.

4. V. K. Kavitha and S. Murugesan (2024)

Title: An Effective Book Recommendation System Using Weighted Alternating Least Square (WALS) Approach

Methodology

The Weighted Alternating Least Squares (WALS) algorithm, a matrix factorization method that finds latent associations between users and books to forecast missing user ratings, was used by the authors.

Key Findings

- increased accuracy of predictions.
- lessened the influence of sparse datasets.

- improved scalability for big data sets.
- Missing ratings were accurately predicted.
- did well on tasks including recommendations.

Limitations

- requires adjusting the parameters.
- Larger datasets result in higher computational costs.
- mostly concentrates on rating prediction.

Research Gap

The study did not integrate content-based data or carry out a thorough statistical analysis, despite the fact that WALS enhanced rating prediction.

Relevance to the Present Study

The current work uses statistical analysis, content-based filtering, and SVD, another matrix factorization method.

5. S. Malakul and P. Songmuang (2026)

Title: A Book Recommender System for Enhancing Reading Engagement: A Systematic Review

Methodology

By looking at current recommendation methods, datasets, assessment metrics, and research trends in book recommendation systems, the authors carried out a thorough study of the literature.

Key Findings

- compared different methods of recommendation.
- emphasized how successful hybrid recommendation systems are
- found frequent issues with recommendation systems.
- examined the assessment metrics employed in earlier research.
- recommendations for further lines of inquiry.

Limitations

- did not create or put into practice a recommendation model.
- restricted to reviewing the body of current literature.

Research Gap

Hybrid recommendation systems that combine several recommendation strategies and thorough performance evaluation are required, according to the review.

Relevance to the Present Study

This study offers a basis for choosing appropriate evaluation metrics and supports the suggested hybrid recommendation strategy.

2.3 Comparison Analysis

Author(s)	Year	Research Focus	Methodology	Key Findings	Research Gap
F. Wayesa et al.	2023	Hybrid Book Recommendation using Semantic Relationships	Hybrid Recommendation (Collaborative +Content-Based + Semantic Analysis)	Improved recommendation accuracy, personalization, and diversity	Lacked detailed statistical evaluation and complete handling of Cold Start.
K. Mankar et al.	2023	Web-Based Book Recommendation	Collaborative Filtering	Personalized recommendations based on user similarity	Suffered from Cold Start and Data Sparsity; no hybrid approach.
Z. Wang & Y. Wang	2024	Digital Library Recommendation	Tag Mining	Improved recommendation relevance using metadata	Relied mainly on tags; did not integrate rating prediction or hybrid methods.
V. K. Kavitha & S. Murugesan	2024	Book Recommendation using WALS	Matrix Factorization (WALS)	Better prediction accuracy and scalability	Did not combine content-based information or comprehensive statistical evaluation.
S. Malakul & P. Songmuang	2026	Systematic Review of Book Recommendation Systems	Literature Review	Identified hybrid methods as more effective and summarized evaluation techniques	Did not propose or implement a practical recommendation model.

Comparision Analasis

The examined works show that many approaches, such as Collaborative Filtering, Content-Based Filtering, Hybrid Recommendation Systems, Tag Mining, and Matrix Factorization,

have been investigated by researchers for creating book recommendation systems. In general, hybrid techniques outperformed single-method systems in terms of suggestion accuracy and customization. While tag mining improved content comprehension, matrix factorization techniques like WALS improved rating prediction.

Nevertheless, the majority of research focused solely on particular facets of recommendation systems and failed to concurrently address issues like the Cold Start Problem, data sparsity, personalization, and computing efficiency. Furthermore, only a small number of research used thorough statistical analysis to assess suggestion performance and user behavior.

The current study combines Collaborative Filtering (SVD) and Content-Based Filtering (TF-IDF and Cosine Similarity) to create a Hybrid Personalized Book Recommendation System in order to fill these shortcomings. Additionally, the study evaluates the efficacy of the suggested recommendation system using statistical methods and evaluation metrics including RMSE, MAE, Precision, and Recall. While addressing the shortcomings noted in earlier research, this integrated strategy seeks to produce more precise, customized, and trustworthy book suggestions.

3. DATA DOMAIN

3.1 Introduction

The most essential element of any statistical analysis and recommendation system is data. The quality and completeness of the data used have a significant impact on the quality, accuracy, and dependability of the outcomes produced by a recommendation system. The interactions between users and items—such as ratings, reviews, preferences, and other descriptive information—are represented by data in recommendation systems. It is feasible to spot trends in user behavior and produce tailored suggestions by examining these exchanges. Thus, choosing a suitable dataset and comprehending its features are crucial stages in creating a successful recommendation system.

The Book Recommendation Dataset used in this work was gathered from Kaggle, a well-known website that offers publicly accessible datasets for data science, machine learning, and research. The dataset is appropriate for creating an individualized book recommendation system since it includes data about books, users, and user ratings.

More than two lakh rating records and roughly six to eight variables, such as User-ID, Book-ID (ISBN), Book Title, Book Author, Publisher, Year of Publication, and Book Rating, are included. These variables offer enough data to examine book features, assess recommendation performance using statistical methods, and analyze user preferences. Researchers can learn how people express their preferences through ratings thanks to the dataset, which depicts real-world interactions between users and books. It is easy to find reading trends and similarities between users and books because each rating in the dataset represents a user's assessment of a certain book. These details serve as the foundation for creating personalized book recommendations that are tailored to each user's interests and preferences. The dataset offers a realistic setting for statistical research and recommendation model testing due to its size and diversity.

An application created to suggest books that closely align with readers' interests and preferences is known as a book recommendation system. To create individualized recommendations, it examines available data, including user ratings, book details, and past reading habits. The goal is to minimize the work needed to search through large collections while assisting readers in finding books they might appreciate.

The dataset used for this study falls under the category of book recommendation systems, which are extensively utilized in online bookstores, digital libraries, educational platforms, and reading applications. These methods lessen the time and effort needed to search through large book collections while assisting users in finding books that align with their interests. Users get recommendations based on their past reading habits and rating patterns rather than having to painstakingly go through thousands of books. Recommendation systems thereby raise user pleasure and improve the reading experience in general.

The dataset was subjected to a number of preparation procedures to enhance its consistency and quality prior to statistical analysis. Duplicate records were eliminated, missing values were found and dealt with appropriately, and the data was organized into a manner that could be analyzed. These pretreatment steps made sure the dataset was trustworthy, clean, and prepared for additional statistical analysis. Accurate analytical results and minimizing the impact of mistakes or inconsistencies during the recommendation process depend on a well-prepared dataset.

Gaining a thorough understanding of the dataset utilized in the project is the major goal of researching the data domain. The dataset's source, domain, structure, variables, features, preparation methods, and sample data are all explained in this chapter. It also explains why the chosen dataset is appropriate for the current investigation and outlines its advantages and disadvantages. The following chapters, which concentrate on data visualization, exploratory

data analysis, model construction, and performance evaluation of the personalized book recommendation system, are strongly supported by a solid grasp of the data domain.

3.2 Domain Knowledge

3.2.1 Introduction to the Domain

The current work falls under the category of Book Recommendation Systems, a subfield of data analytics that focuses on giving readers tailored recommendations according to their interests and preference. Readers now have access to a vast quantity of books due to the quick expansion of digital libraries, online bookstores, educational repositories, and e-learning platforms. This gives customers a lot of options, but it also makes it challenging to choose books that fit their personal interests. Recommendation algorithms are becoming a crucial tool for effectively assisting consumers in finding appropriate books.

A recommendation system is an intelligent decision-support system that makes recommendations for products that customers are likely to like based on past user interactions, including ratings, reviews, past purchases, and browsing patterns. These suggestions are produced in book recommendation systems by examining user preference information and book attributes. Users receive tailored recommendations that shorten search times and enhance their overall reading experience rather than having to manually browse through thousands of books.

From a statistical standpoint, recommendation systems analyze user activity, find trends in rating data, quantify user-book similarities, and assess suggestion performance using statistical metrics. As a result, recommendation systems are a significant practical use of statistical data analysis.

3.2.2 Book Recommendation System

An application created to suggest books that closely align with readers' interests and preferences is known as a book recommendation system. To create individualized

recommendations, it examines available data, including user ratings, book details, and past reading habits. The goal is to lessen the work needed to search through large collections while assisting readers in finding books they might appreciate.

Book recommendation systems are widely used in:

- Digital libraries
- Online bookstores
- Educational institutions
- University library management systems
- E-learning platforms
- Mobile reading applications

By suggesting books that are appropriate for each user rather than showing the same books to every reader, these systems increase user happiness. By introducing users to books that align with their interests, personalized suggestions boost user engagement and promote ongoing reading.

3.2.3 Types of Recommendation Systems

Over time, a number of recommendation methods have been created, each with unique benefits and drawbacks.

Collaborative Filtering

By examining the tastes and ratings of people who share similar interests, Collaborative Filtering makes book recommendations. The fundamental premise is that people who have previously enjoyed comparable books are probably going to have similar tastes in the future.

Advantages:

- generates recommendations that are specific to each individual.
- automatically picks up on user behavior.
- doesn't need in-depth book descriptions.

Limitations:

- has a cold start issue.
- Sparse rating data results in lower performance.
- needs enough user ratings from the past.

Content-Based Filtering

Content-Based Filtering makes book recommendations based on attributes including title, author, publisher, genre, and textual description. The technology finds books that are comparable to the user's past favorites.

Advantages:

- Ideal for suggesting recently published books.
- regardless of the preferences of other users.
- makes suggestions based on the characteristics of the book.

Limitations:

- There might not be enough diversity in recommendations.
- The quality of the book metadata is a determining factor.
- Users cannot be introduced to completely new kinds of books with ease.

Hybrid Recommendation Systems

To get beyond the drawbacks of each recommendation methodology, a hybrid recommendation system combines many of them. The method makes use of both user preference data and book information to produce more precise and trustworthy recommendations by combining Collaborative Filtering with Content-Based Filtering.

The current study uses a hybrid technique that combines content-based filtering using TF-IDF vectorization and cosine similarity with collaborative filtering using singular value decomposition (SVD). This integration lessens the impact of data sparsity and the cold start issue while improving suggestion quality.

3.2.4 User Preference Data

The interactions between users and books are represented by user preference data. It plays a crucial part in creating tailored suggestions and offers insightful data about users' interests.

In this study, user preference data primarily consists of:

- User identification numbers
- Book identification numbers
- Book titles
- Author names
- User ratings
- Publication details

User ratings are the most significant of these factors since they show how much a user enjoys a specific book. These evaluations can be statistically analyzed to find user similarities, popular books, and reading habits.

3.2.5 Importance of Recommendation Systems

Because recommendation algorithms make it easier to choose pertinent books from vast collections, their significance has grown.

Their importance includes:

- Reducing information overload.
- Providing personalized recommendations.
- Improving user satisfaction.
- Increasing user engagement.
- Helping users discover new books.
- Supporting decision-making.
- Improving the efficiency of digital libraries and online bookstores.

In the current study, statistical methods are used to comprehend user preferences and assess the recommendation system's efficacy using performance metrics including Precision, Recall, RMSE, and MAE.

3.3 About the Dataset

The Book Recommendation Dataset, which was retrieved via the Kaggle platform, was the dataset utilized in this research. Researchers, students, and data analysts frequently use Kaggle, one of the top global repositories for publicly accessible datasets, for statistical analysis and predictive modeling.

The chosen dataset includes real-world user, book, and user rating data. User-ID, Book-ID (ISBN), Book Title, Book Author, Publisher, Year of Publication, and Book Rating are among the roughly 6–8 factors that make up the more than 2 lakh rating data. The dataset is ideal for examining reading preferences and creating customized recommendation systems since each record depicts a user's interaction with a book. Numerous statistical studies are made possible by the dataset's combination of numerical and category variables. While categorical factors like book title, author, and publisher are helpful for content-based recommendation methods, numerical variables like ratings and release year facilitate descriptive and exploratory statistical analysis.

This dataset's enormous sample size is one of its main advantages. There is enough information in a dataset with more than two lakh observations to find significant patterns and correlations between variables. Because they capture a greater variety of user preferences, large datasets typically yield more dependable statistical results and enhance recommendation system performance.

The dataset's representation of actual user interactions as opposed to data that was created intentionally is another crucial aspect. Since the evaluations are submitted by genuine users, the dataset reflects realistic reading behavior and preferences. Because of this, it is very suitable

for analyzing recommendation methods and gauging how well they work in real-world scenarios.

Dataset Information

Particular	**Description**
Dataset Name	Book Recommendation Dataset
Source	Kaggle
Domain	Book Recommendation System
Data Type	Structured Dataset
File Format	CSV
Number of Samples	More than 2,00,000 ratings
Number of Variables	Approximately 6–8
Nature of Data	Real-world user preference data

The dataset was chosen because it meets the study's objectives by offering enough observations, pertinent variables, and accurate user preference data required for statistical analysis and suggestion creation.

3.4 Data Collection Process

The Kaggle platform, which offers publicly accessible datasets for scholarly research and analytical applications, was the source of the data used in this study. The Book Recommendation Dataset was downloaded in CSV format and put into the Python environment for additional processing and analysis.

The Book Recommendation Dataset was downloaded in CSV format and put into the Python environment for additional processing and analysis.

After obtaining the dataset, the files were loaded into Python using the Pandas package. Initially, the structure of the dataset was reviewed to understand the available variables, data

kinds, and overall quality of the data. This preliminary review helped discover missing data, duplicate records, and discrepancies that required preprocessing before statistical analysis.

After that, a number of preparation procedures were carried out to enhance the dataset's dependability and quality. Duplicate records were eliminated, missing values were found and dealt with appropriately, and variables were changed into appropriate data types as needed. To guarantee that the dataset adequately reflected user-book interactions, unnecessary entries and inconsistencies were removed. These preprocessing procedures decreased mistakes and made the data ready for further examination.

The dataset was cleaned and then put into a structured format that could be used for statistical analysis and the creation of recommendation models. The processed dataset was subsequently used for descriptive statistics, data visualization, exploratory data analysis, and the creation of the hybrid book recommendation system. Accurate tailored book recommendations and dependable analytical results are based on a well-prepared dataset.

3.5 Dataset Characteristics

The structured, real-world Book Recommendation Dataset used in this study includes data on users, books, and ratings. The dataset, which was acquired from Kaggle, is frequently utilized in statistical analysis, data analytics, and recommendation systems research. Since it comprises genuine user-book interactions, it provides a realistic setting for investigating user preferences and constructing tailored recommendation models.

This dataset's enormous sample size—more than 2 lakh rating records—is one of its main advantages. By offering enough observations to find significant patterns and relationships, a large dataset enhances the validity and reliability of statistical research. Additionally, by exposing the model to a wide variety of users and books, it improves recommendation systems' effectiveness.

The dataset comprises of both numerical and category variables. User ratings and the year of publication are examples of numerical variables; ISBN, book title, author name, and publisher are examples of categorical variables. Numerous statistical methods, including descriptive statistics, exploratory data analysis, visualization, correlation analysis, and recommendation modeling, can be applied thanks to this mix of variable types.

The dataset's representation of user-item interaction data is another crucial feature. The dataset is appropriate for collaborative filtering approaches because each record represents a user rating for a particular book. Additionally, content-based filtering techniques are made possible by book-related details like the author and title. As a result, the dataset facilitates the deployment of a hybrid recommendation system.

The dataset has duplicate records and missing values, just as many real-world datasets. To enhance data quality and guarantee trustworthy analytical results, these problems were fixed during preprocessing. Preparing the dataset for analysis reduces errors and improves the recommendation system's overall performance.

Because the dataset includes enough observations, a variety of variables, and actual user behavior, it is ideal for statistical analysis. These features make it a perfect option for researching recommendation systems and assessing their effectiveness with statistical metrics.

Table 3.1 Dataset Characteristics

Characteristic	**Description**
Dataset Name	Book Recommendation Dataset
Source	Kaggle
Domain	Book Recommendation System
Dataset Type	Structured Data
File Format	CSV

Number of Records	More than 2 lakh ratings
Number of Variables	Approximately 6–8
Data Nature	User–Book Interaction Data
Variable Types	Numerical and Categorical
Rating Scale	0–10
Sample Size	Large-scale Dataset
Missing Values	Present and handled during preprocessing
Duplicate Records	Removed during preprocessing
Recommendation Type	Hybrid Recommendation System

3.6 Dataset Variables

The depth and effectiveness of statistical analysis depend on the variables present in a dataset. Every variable offers distinct data that helps realize user preferences and produce tailored recommendations. The Book Recommendation Dataset comprises variables describing users, books, and ratings. Together, these characteristics constitute the foundation for suggestion creation and statistical evaluation.

The variables employed in this study include User-ID, ISBN (Book-ID), Book Title, Book Author, Publisher, Year of Publication, and Book Rating. These variables can be used in a variety of statistical analyses because they are measured using a variety of scales and data sources.

3.6.1 User-ID

Every user in the dataset is given a unique numerical identity called the User-ID. It sets each user apart and enables the recommendation engine to determine each person's unique reading interests. User-ID is crucial for building the user-item rating matrix used in collaborative

filtering, even though it does not offer demographic data. The evaluations of each user aid in identifying user shared characteristics and producing customized recommendations.

Role in the Study:

- Identifies certain users.
- Tracks user rating history.
- Used in collaborative filtering.
- Contributes to the creation of the user-book interaction matrix.

3.6.2 ISBN (Book-ID)

Every book in the dataset is individually identified by its ISBN (International Standard Book Number). It guarantees accurate differentiation between various book editions or versions. ISBN acts as the primary key for identifying books during recommendation generation and data processing.

Role in the Study:

- Books are uniquely identified.
- Links book information with user ratings.
- Applied to the creation of recommendations.

3.6.3 Book Title

The names of all the books in the dataset are represented by the Book Title. It is one of the most informative textual variables because readers primarily recognize books by their titles. The recommendation system's Content-Based Filtering feature makes use of book titles. TF-IDF Vectorization is used to convert titles into numerical vectors during preprocessing, and Cosine Similarity is used to determine how similar books are to one another.

Role in the Study:

- Displays recommendation results.
- Supports content-based recommendation.

- Used in TF-IDF vectorization.
- Measures similarity between books.

3.6.4 Book Author

Each book's author is identified by the Book Author variable. Author information is useful for recommendations since readers frequently favor books authored by authors they have previously appreciated. When making recommendations, author names also play a role in content similarity.

Role in the Study:

- Provides author information.
- Improves content similarity.
- Supports personalized recommendations.

3.6.5 Publisher

The company in charge of publishing each book is identified by the Publisher variable. Publisher information can be helpful in analyzing publication patterns and offers additional descriptive information, even if it has little impact on suggestion accuracy.

Role in the Study:

- gives more book metadata.
- Assists descriptive statistical analysis.
- ensures the completeness of the dataset.

3.6.6 Year of Publication

The year a book was published is indicated by the Year of Publication. This variable helps assess publication trends and identify older or freshly published books. Additionally, it can be used for exploratory data analysis to look at how books are distributed over time.

Role in the Study:

- examines patterns in publications.

- Supports descriptive statistics.
- beneficial for visualization.

3.6.7 Book Rating

The dataset's most significant variable is the book rating since it represents user preferences. Better ratings on a scale of 0 to 10 denote better levels of user satisfaction.

These ratings are used by the recommendation system to determine user preferences and forecast ratings for unread books. The recommendation system is further evaluated using RMSE, MAE, Precision, and Recall based on rating values.

Role in the Study:

- reflects the preferences of the user.
- The recommendation's target variable.
- Used for model evaluation.
- allows for cooperative filtering.

Table 3.2 Variable Description

Variable Name	Description	Data Type	Measurement Scale	Role in Study
User-ID	Unique identifier for users	Integer	Nominal	Identifies users
ISBN (Book-ID)	Unique identifier for books	String	Nominal	Identifies books
Book Title	Name of the book	String	Nominal	Content-based recommendation
Book Author	Author of the book	String	Nominal	Measures book similarity
Publisher	Publishing organization	String	Nominal	Book information

Year of Publication	Publication year	Integer	Interval	Trend analysis
Book Rating	User rating (0–10)	Integer	Ordinal	Target variable

Importance of Dataset Variables

Each variable contributes uniquely to the recommendation process. Collaborative Filtering is based on User-ID and Book Rating, whereas Content-Based Filtering is supported by Book Title and Book Author. ISBN ensures reliable identification of books, and Publisher and Year of Publication provide further information for descriptive and exploratory research. Together, these variables offer a full understanding of user preferences and facilitate the creation of an effective hybrid recommendation system. The dataset is well suited for the goals of this project because of the combination of numerical and categorical variables, which also permits the application of statistical techniques like descriptive statistics, visualization, correlation analysis, exploratory data analysis, and recommendation model evaluation.

4 . STATISTICAL TOOLS AND SOFTWARE'S USED

4.1 Introduction

When creating a recommendation system, statistical analysis is crucial since it facilitates data processing, pattern recognition, and precise decision-making. Using the Book Recommendation Dataset gathered from Kaggle, statistical techniques are employed in this research to analyze rating trends, comprehend user behavior, and assess the recommendation model's effectiveness.

The project is implemented using Python and its statistical modules for data analysis, visualization, and model construction. The dataset is analyzed using fundamental statistical techniques as One-Way ANOVA, Correlation Analysis, Independent Sample t-test, and Descriptive Statistics. To create customized book recommendations, sophisticated techniques including Collaborative Filtering (SVD), TF-IDF, Cosine Similarity, and a Hybrid Recommendation System are used. Root Mean Square Error (RMSE) and Mean Absolute Error (MAE) are used to assess the model's performance. The objective and application of the statistical software, fundamental statistical tools, and sophisticated techniques employed in the study are presented in this chapter.

4.2 Statistical Software Used

By facilitating effective data administration, visualization, statistical method implementation, and analytical model evaluation, statistical software plays a significant role in data analysis. Python was utilized as the main statistical programming language in this study because to its ease of use, adaptability, and large library for data analysis and recommendation system creation. The study was carried out using the Jupyter Notebook environment, which offers an interactive platform for creating, running, and recording Python programs.

Different phases of the analysis were carried out using a number of Python libraries. The dataset was imported, cleaned, combined, and altered using Pandas, while matrix operations

and numerical calculations were handled by NumPy. Matplotlib and Seaborn were applied to build statistical graphs and visualizations for analyzing data patterns. SciPy was used to execute statistical hypothesis tests such as the Independent Sample t-test and One-Way ANOVA. Tools for applying TF-IDF Vectorization and Cosine Similarity in the content-based recommendation model were made available by Scikit-learn. The recommendation model was assessed and Collaborative Filtering using the Singular Value Decomposition (SVD) technique was implemented using the Surprise library. Tools for applying TF-IDF Vectorization and Cosine Similarity in the content-based recommendation model were made available by Scikit-learn. The recommendation model was assessed and Collaborative Filtering using the Singular Value Decomposition (SVD) technique was implemented using the Surprise library.

The combination of Python and its libraries provided an efficient environment for statistical analysis, recommendation model construction, and performance evaluation. The statistical software and libraries utilized in this investigation are listed in Table 4.1.

Table 4.1: Statistical Software and Libraries Used

Software / Library	**Purpose in the Study**
Python	Programming language used for implementing the complete recommendation system.
Jupyter Notebook	Interactive environment for coding, analysis, and documentation.
Pandas	Data importing, cleaning, merging, and manipulation.
NumPy	Numerical computations and matrix operations.
Matplotlib	Data visualization through charts and graphs.
Seaborn	Statistical visualization and correlation plots.
SciPy	Hypothesis testing using Independent Sample *t*-test and One-Way ANOVA.
Scikit-learn	Implementation of TF-IDF Vectorization and Cosine Similarity.

4.3 Basic Statistical Tools Used

Before creating the recommendation model, it is crucial to comprehend the features of the dataset using fundamental statistical methods. They aid in data summarization, variable connection analysis, and statistical hypothesis testing. In order to analyze user evaluations, comprehend data distribution, and aid in decision-making during model construction, this study used fundamental statistical approaches. The Independent Sample t-test, One-Way ANOVA, Correlation Analysis, and Descriptive Statistics are among the statistical techniques employed.

4.3.1 Descriptive Statistics

Introduction

Using numerical measurements, descriptive statistics are used to highlight and describe a dataset's key features. Without making inferential judgments, they offer a clear grasp of the data's distribution and variability. Descriptive statistics were employed in this study to analyze the book rating variable and derive a general understanding of user rating.

Statistical Measures Used

- Mean
- Median
- Mode
- Minimum
- Maximum
- Variance
- Standard Deviation

Procedure

1. Open Python and import the combined dataset.
2. Choose the Book Rating variable.
3. Use the Pandas library to compute the descriptive statistical metrics.
4. To comprehend the rating distribution, interpret the results.

Purpose in the Study

A summary of user ratings is given by descriptive statistics, which also aid in determining the general rating behavior. This data forms the basis for additional statistical analysis and the creation of recommendation models.

4.3.2 Correlation Analysis

Introduction

A statistical method for determining the direction and intensity of a relationship between two numerical variables is correlation analysis. It assists in figuring out whether variations in one variable are related to variations in another. Correlation analysis was used in this research to look at the correlations between the dataset's numerical variables.

Statistical Method Used

Pearson Correlation Coefficient

Procedure

1. Choose the numerical variables from the dataset.
2. Determine the Pearson correlation coefficient.
3. Create a correlation matrix.
4. Make use of a heatmap to see the outcomes.
5. Analyze the relationships' direction and strength.

Purpose in the Study - Correlation analysis offers insights into user behavior and aids in the identification of correlations between variables. These results encourage a more thorough analysis of the dataset prior to the application of recommendation methods.

4.3.3 Independent Sample t-test

Introduction : The separate Sample t-test is a parametric statistical test used to compare the mean values of two separate groups. It establishes the statistical significance of the observed variation in group means.

Hypotheses

Null Hypothesis (H_0): The two groups' mean ratings do not differ significantly.

Alternative Hypothesis (H_1): The two groups' mean ratings differ significantly.

Procedure

1. Split the observations into two separate groups.
2. Determine each group's mean rating.
3. Use the SciPy library to run the Independent Sample t-test.
4. Compare the p-value to the selected significance threshold of 0.05.
5. The null hypothesis can be accepted or rejected.

Purpose in the Study

The t-test aids in identifying whether rating behavior varies significantly between user groups. The findings offer statistical support for examining variations in user preferences.

4.3.4 One-Way ANOVA

Introduction

Three or more independent groups' means can be compared using One-Way Analysis of Variance (ANOVA). It establishes whether at least one group is substantially different from the rest.

Hypotheses

The null hypothesis (H0) states that the means of every group are equal.

Alternative Hypothesis (H_1): There is a significant difference in at least one group mean.

Procedure

1. Split the dataset up into several groups.
2. Determine each group's mean.
3. Use the SciPy library to conduct a one-way ANOVA.
4. Calculate the F-statistic and p-value.

5. Compare the significance threshold (0.05) with the p-value.
6. Determine the proper statistical conclusion.

Purpose in the Study

Significant variations in user evaluations across several groups can be found using ANOVA. The research enhances the interpretation of the suggestion dataset and offers helpful insights into differences in user preferences.

Summary of Basic Statistical Tools

Before using complex recommendation techniques, this study's fundamental statistical tools offered a methodical comprehension of the Book Recommendation Dataset. The Independent Sample t-test compared the mean ratings of two groups, One-Way ANOVA explored differences between several groups, correlation analysis investigated correlations among numerical variables, and descriptive statistics detailed the features of user evaluations. When combined, these methods aided in the dataset's interpretation and offered a statistical framework for creating and assessing the hybrid book recommendation system.

4.4 Advanced Statistical Techniques Used

In order to increase the precision, effectiveness, and customization of recommendation systems, advanced statistical techniques are essential. Advanced techniques are used to find hidden patterns, forecast user preferences, and produce pertinent recommendations, in contrast to simple statistical tools that summarize and analyze data. Five main advanced techniques were used in this study to accomplish the research goals: Collaborative Filtering using Singular Value Decomposition (SVD), Content-Based Filtering using TF-IDF, Cosine Similarity, Hybrid Recommendation System, and Performance Evaluation using RMSE and MAE. Together, these techniques enhance suggestion quality, address real-world issues like data sparsity and cold start, and assess the efficacy of the suggested model.

4.4.1 Singular Value Decomposition (SVD) Collaborative Filtering Introduction

One of the most popular methods for making recommendations is collaborative filtering. Based on the tastes and rating patterns of users who share similar interests, it makes recommendations. In this project, ratings for books that users have not yet rated are predicted using the Singular Value Decomposition (SVD) technique from the Surprise library.

Procedure

1. Using the dataset, create a user-book rating matrix.
2. Create training and testing sets from the dataset.
3. Use the training data to train the SVD model.
4. Learn latent characteristics representing users and books.
5. Estimate ratings for books you haven't yet read.
6. Create tailored recommendations based on the anticipated ratings.

Purpose in the Study

By decreasing the dimensionality of the rating matrix, SVD is able to capture hidden correlations between users and books. Even when consumers have only reviewed a small number of books, it effectively predicts missing ratings and offers tailored recommendations.

4.4.2 Content-Based Filtering using TF-IDF

Introduction

Instead of relying on user choices, content-based filtering suggests books based on their qualities. In this research, textual data, including book titles and authors, is transformed into numerical feature vectors using TF-IDF (Term Frequency–Inverse Document Frequency).

Procedure

1. From the dataset, pick pertinent textual features.
2. Preprocess and clean the text.
3. To transform text into numerical vectors, use TF-IDF vectorization.

4. To calculate similarity, store the feature vectors.

Purpose in the Study

TF-IDF determines the significance of words in book titles or descriptions and translates them into numerical representations. Afterwards, books with similar content are found using these vectors.

4.4.3 Cosine Similarity

Introduction

One similarity metric for comparing two feature vectors is cosine similarity. The similarity between books is measured in this study following TF-IDF vectorization.

Procedure

1. Make use of the TF-IDF feature matrix.
2. Determine the cosine similarity between each book pair.
3. Use similarity scores to rank books.
4. The novels with the highest similarity values should be recommended.

Purpose in the Study

Cosine Similarity recognizes books with comparable textual features, enabling the system to offer books linked to those previously favored by the user.

4.4.4 Hybrid Recommendation System

Introduction

To enhance suggestion quality, a hybrid recommendation system integrates many recommendation strategies. To get beyond the drawbacks of employing each technique separately, this research integrates Collaborative Filtering (SVD) with Content-Based Filtering (TF-IDF with Cosine Similarity).

Procedure

1. Make suggestions by utilizing Collaborative Filtering.

2. Make suggestions by applying content-based filtering.
3. Integrate the suggestions from the two approaches.
4. Eliminate recommendations that are repeated.
5. Sort the final suggestions according to their importance.

Purpose in the Study

The hybrid technique increases suggestion accuracy by incorporating both user rating behaviour and book content. It offers more balanced recommendations and lessens the shortcomings of individual recommendation techniques.

4.4.5 Performance Evaluation using RMSE and MAE

Introduction

To determine the recommendation model's accuracy, performance evaluation is required. In this study, the anticipated and real user ratings are compared using Root Mean Square Error (RMSE) and Mean Absolute Error (MAE).

Procedure

1. Examine the differences between the actual and expected ratings.
2. Compute the RMSE.
3. Determine the MAE.
4. Analyze the incorrect values.
5. Compare the performance of the recommendation model.

Purpose in the Study

The recommendation system's prediction error is measured by RMSE and MAE. Better prediction accuracy and higher-quality recommendations are indicated by lower values.

Summary of Advanced Statistical Methods

The suggested Hybrid Book Recommendation System performs better overall thanks to the sophisticated statistical techniques used in this study. While TF-IDF and Cosine Similarity find

books with similar content, Collaborative Filtering (SVD) forecasts consumer preferences based on past ratings. A hybrid recommendation system combines several techniques to produce recommendations that are more precise and customized. Lastly, the model's prediction accuracy is assessed using RMSE and MAE. By improving personalization, boosting suggestion quality, boosting computational efficiency, and offering users trustworthy recommendations, these techniques together assist the research aims.

4.5 Chapter Summary

The statistical software, fundamental statistical tools, and sophisticated analytical techniques utilized in creating the suggested Hybrid Book Recommendation System were discussed in this chapter. Data analysis, visualization, statistical testing, and recommendation model implementation were carried out using Python and its associated libraries. To comprehend the information and analyze user rating behavior, fundamental statistical tools such as descriptive statistics, correlation analysis, independent sample t-test, and one-way ANOVA were used.

To create individualized book recommendations, sophisticated techniques like Collaborative Filtering (SVD), Content-Based Filtering using TF-IDF and Cosine Similarity, and the Hybrid Recommendation System were used. RMSE and MAE were used to evaluate the suggested model's performance in terms of prediction accuracy. All things considered, the statistical techniques and tools covered in this chapter offered a solid analytical framework for accomplishing the study goals and creating an effective, dependable, and customized book recommendation system.

5. DATA VISULIZATION

5.1 Introduction

An essential part of data analysis is data visualization, which turns complicated datasets into insightful graphical representations that facilitate the discovery of correlations, patterns, and trends in the data. Statistical visualizations in recommendation systems support data-driven decision-making and enhance dataset interpretation by offering insightful information about user behavior, book attributes, and rating trends.

Before evaluating the model, the Book Recommendation Dataset was analyzed using statistical visualization techniques. User demographics, rating distributions, book popularity, author and publisher details, and correlations between numerical data are all made easier to understand with the help of the visualizations. By confirming significant findings pertaining to the suggested Hybrid Book Recommendation System, these graphical analyses complement the research goals and offer a clear overview of the dataset.

The statistical visualizations produced with Python-based visualization packages are presented in this chapter together with their goal, explanations, findings, interpretation, and conclusion. The information gained from these visualizations provides a solid analytical basis for the statistical analysis and performance assessment of the recommendation system that follow.

5.2 Statistical Data Visualization and Interpretation

In order to enable meaningful interpretation of complicated information, statistical data visualization is a crucial analytical approach that transforms numerical and categorical data into graphical representations. In this study, statistical graphs were used to examine user demographics, rating behaviour, book popularity, author contributions, publisher distribution, and correlations among variables in the Book Recommendation Dataset. The creation of the suggested Hybrid Book Recommendation System is supported by these visualizations, which offer statistical proof for comprehending the dataset.

5.2.1 Histogram Analysis – User Age Distribution


Purpose

The histogram was utilized to analyze the user age distribution and comprehend the dataset's demographic makeup.

Justification

One significant demographic factor influencing reading choices is user age. Analyzing its distribution reveals the traits of the target audience and aids in identifying the predominant user groups.

Figure 5.1: Histogram of User Age Distribution



Results and Interpretation

The histogram shows that while fewer users are seen in the older age groups, the majority of users are in the young and middle-aged groups. This implies that these age groups' reading preferences have a major impact on the recommendation model. Additionally, the visualization verifies that the age data are acceptable for additional analysis and are evenly distributed following pretreatment.

In conclusion : The histogram facilitates the analysis of user behavior within the recommendation system and offers a clear picture of the demographic profile of users.

5.2.2 Count Plot Analysis – Distribution of Book Ratings


Purpose:

to examine the frequency and distribution of user-provided book ratings.

Justification:

The distribution of book ratings reveals if the dataset has sparse or balanced rating information, which is crucial for creating a successful recommendation system and aids in understanding user rating behavior.

Figure 5.2: Distribution of Book Ratings (Count Plot)



Results and Interpretation

The count plot reveals that explicit ratings ranging from 1 to 10 are less common, whereas a significant portion of entries have a rating value of 0. This suggests that there is a lot of implicit feedback in the dataset, which leads to a sparse user-book interaction matrix. Such a distribution encourages the use of a hybrid recommendation strategy and draws attention to the drawbacks of depending just on collaborative filtering.

Conclusion

In order to increase suggestion accuracy and customisation, the visualization supports the use of hybrid recommendation approaches and verifies the availability of sparse rating data.

5.2.3 Bar Chart Analysis – Top 10 Most Rated Books


Purpose

To determine which novels had the most user ratings, a bar chart was created.

Justification

Books with a big number of ratings give solid user preference information and are helpful for producing suggestions, particularly for new users.

Figure 5.3: The Top 10 Best-Rated Books



Results and Interpretation

The graphic demonstrates that a small number of books make up a substantial percentage of user interactions, suggesting that popular titles dominate reader choices. These books can be used for popularity-based suggestions and to lessen the cold-start issue because they include greater rating information.

Conclusion

The investigation shows that popular books greatly enhance suggestion coverage for consumers with little interaction history and add to recommendation quality.

5.2.4 Bar Chart Analysis – Top 10 Authors


Purpose:

To determine which ten writers have the most books in the dataset and evaluate their contributions to the collection as a whole.

Justification:

Author information is an important content attribute in a book recommendation system. By recording author-wise reading preferences, identifying the most represented authors promotes content-based suggestions that assist in understanding dataset composition.

Figure 5.4: Top 10 Authors by Number of Books (Bar Chart)



Results and Interpretation:

The top ten writers with the most books in the dataset are displayed in the bar chart. It implies that a few authors provide a much larger number of books than others, demonstrating their strong presence in the collection. Because these writers' books are more likely to show up in user interactions, author information is a useful tool for increasing the relevancy of recommendations.

Conclusion:

By adding author-based data, the study of the top 10 writers facilitates the creation of tailored recommendations and offers insights into the distribution of authors within the dataset.

5.2.5 Bar Chart Analysis – Top 10 Publishers


Purpose

The top ten publishers with the most books in the dataset were identified using the bar chart, and their contributions to the total book collection were examined.

Justification

An essential bibliographic feature that aids in comprehending the dataset's composition is publisher information. By adding publisher-related data, an analysis of the top 10 publishers improves content-based recommendation and offers insights into publication trends.

Figure 5.5: Top 10 Publishers by Number of Books (Bar Chart)



Results and Interpretation

The top 10 publishers with the most books available in the dataset are depicted in the bar chart. The findings indicate that while the remaining publishers have relatively less titles, a small number of publishers provide a significant amount of the book collection. This distribution shows that books from reputable publishers make up the majority of the dataset. An extra content feature for evaluating book attributes and enhancing the applicability of suggestions is publisher information.

Conclusion


In addition to supporting the creation of a more efficient and customized Hybrid Book Recommendation System, the analysis of the top 10 publishers offers a clear picture of the distribution of publications within the dataset.

5.2.6 Correlation Heatmap Analysis

Purpose

The associations between the numerical variables in the dataset were investigated using the correlation heatmap.

Figure 5.6: Correlation Heatmap



Justification

Correlation analysis supports statistical interpretation of the dataset and assists in determining whether numerical variables have significant linear correlations.

Results and Interpretation

The heatmap shows usually modest correlations between the numerical variables, indicating that no single element has a significant impact on user ratings. This result suggests that rather than relying just on individual factors, recommendation performance is dependent on the combined effect of several user and book attributes. The outcome encourages the use of a hybrid recommendation model that combines content-based methods with collaborative filtering.

Conclusion

The correlation analysis confirms that combining multiple recommendation approaches is preferable to relying just on a single variable, thus supporting the proposed Hybrid Book Recommendation System.

5.3 Overall Results Interpretation

Recommend the development of the statistical insights, and suggested hybrid book system, and presented in this chapter. The dataset is mostly made up of young and middle-aged users, according to the histogram analysis, suggesting that these age groups' preferences have a significant impact on recommendations. The high frequency of zero ratings in the count plot of book ratings demonstrated the existence of data sparsity and the necessity of a hybrid recommendation strategy.

The most frequently rated books, authors, and publishers were determined by the bar chart analyses, indicating that user interactions are focused on a small number of well-liked products. These results are helpful in making recommendations, especially for beginners and books with little interaction history. The correlation heatmap further demonstrated poor connections

among the numerical variables, suggesting that recommendation quality depended on the combined influence of several user and book features rather than a single variable.

Developing a personalized recommendation system is a personalized recommendation system. The hybrid model, which combines content-based and collaborative filtering to address issues like data sparsity and the cold-start problem, is also supported by the graphical analysis. Thus, the results from the statistical visualizations serve as a solid analytical foundation for the advanced statistical analysis and model evaluation presented in the next chapters.

5.4 Chapter Summary

This chapter provided the statistical visualizations derived from the Book Recommendation Dataset and highlighted their significance in understanding the properties of the data. User demographics, rating behavior, book popularity, author contributions, publisher distribution, and relationships among numerical data were all analyzed using a variety of visualization techniques, such as histograms, count plots, bar charts, and correlation heatmaps. The graphical analysis helped the creation of the suggested Hybrid Book Recommendation System, confirmed the research goals, and offered insightful information about the dataset. The results of these visualizations provide a solid basis for the next chapter, which focuses on advanced statistical analysis and exploratory data analysis (EDA) to further assess the dataset and the recommendation model's effectiveness.

6. EXPLORATORY DATA ANALYIS

6.1 Introduction

Before creating analytical models, exploratory data analysis (EDA) is a crucial stage in the data analysis process that focuses on comprehending the features, quality, and underlying patterns of a dataset. It assists in determining data distributions, statistical characteristics, correlations between variables, and possible patterns that affect how well data-driven applications operate. The Book Recommendation Dataset was subjected to exploratory data analysis in this research project in order to derive valuable insights into user ratings, book attributes, and demographic data. A brief description of the dataset, descriptive statistical analysis, and the interpretation of significant patterns found in the information are all included in the results. To investigate the distribution of numerical variables, assess the quality of the data, and comprehend the general structure of the dataset, a variety of statistical measures and analytical approaches were used. The construction of the suggested Hybrid Book Recommendation System is supported by the insights derived from the exploratory research, which offer a thorough comprehension of the dataset. The results in this chapter provide a solid analytical basis for the application and assessment of the recommendation model covered in the following chapters.

6.2 Dataset Overview

6.2.1 Dataset Description

The quality, diversity, and completeness of the dataset utilized for analysis and model creation have a significant impact on any recommendation system's success.The Kaggle platform provided the Book Recommendation Dataset used in the present research.Because it includes extensive data on books, users, and user ratings, the dataset is frequently utilized for academic research and recommendation system applications.

Through rating values, these databases offer comprehensive information on user demographic s, book qualities, and user preferences.Combining these datasets makes it possible to analyze

user behavior and facilitates the creation of customized book recommendation algorithms.

The ISBN, book title, author, year of publication, publisher, and image URLs of the books are among the bibliographic details included in the Books dataset.These characteristics offer descriptive data that may be applied to content-based recommendation systems.

User-ID, Location, and Age are among the demographic variables in the Users dataset. This data aids in analyzing demographic trends across the dataset and comprehending user characteristics.

User-book interactions are stored in the Ratings dataset. A User-ID, an ISBN, and a Book Rating between 0 and 10 are all included in each entry. While ratings ranging from 1 to 10 show clear user preferences, ratings of 0 imply implicit feedback, where consumers have engaged using a book without explicitly reviewing it.

The three datasets were combined using the shared properties ISBN and User-ID to enable thorough analysis, producing a single dataset appropriate for exploratory analysis and the creation of the suggested Hybrid Book Recommendation System.

6.2.2 Dataset Information

Three main datasets including data on books, users, and user ratings make up the Book Recommendation Dataset. In order to analyze user preferences and create tailored suggestions, each dataset provides distinct information.

271,360 books containing eight attributes—book title, author, year of release, publisher, and picture URLs—are included in the Books dataset. This dataset is the main source of content-related attributes and offers descriptive details about each book.

278,858 user entries with three attributes—User-ID, Location, and Age—are included in the Users dataset. These characteristics offer demographic data to aid in the study of user behavior.

1,149,780 rating records with three characteristics, which reflect user-book interactions, are

included in the Ratings collection. The ratings are given on a scale of 0 to 10, with numbers from 1 to 10 denoting explicit ratings and zero denoting implicit input.

A consolidated dataset with 1,031,136 records and 12 characteristics was produced after the three datasets were combined using the shared attributes User-ID and ISBN. The main dataset used to do exploratory data analysis and create the hybrid book recommendation system was this combined dataset.

Table 6.1 Dataset Information

Dataset	Number of Records	Number of Attributes	Description
Books	271,360	8	Contains book details such as ISBN, title, author, publication year, publisher, and image URLs.
Users	278,858	3	Contains user information including User-ID, location, and age.
Ratings	1,149,780	3	Contains user ratings assigned to books on a scale of 0–10.
Merged Dataset	1,031,136	12	Combined dataset used for exploratory data analysis and recommendation model development.

Both numerical and category characteristics are present in the combined dataset. Book Title, Book Author, Publisher, and Location are examples of categorical variables; Age and Book Rating are examples of numerical variables. Both statistical analysis and dataset exploration using visualization are made possible by this mix of factors.

The dataset is ideal for exploratory data analysis and recommendation system research because to its abundance of user-book interactions and comprehensive bibliographic and demographic data. Its quantity and variety offer enough data to determine user preferences, examine rating trends, and assess correlations between various dataset aspects.

6.3 Descriptive Statistics

In order to offer a statistical summary of the dataset, descriptive statistics is a crucial part of exploratory data analysis (EDA). Prior to doing in-depth exploratory research, it aids in comprehending the distribution, central tendency, and variability of numerical variables. Descriptive statistics makes it possible to identify significant features, trends, and patterns inside the information set by using statistical measurements to summarize the data.

The Book Recommendation Dataset had been subjected to descriptive statistical analysis in order to gain an overall overview of the numerical properties, namely the Book Rating variable. The Pandas describe() function was used to compute statistical metrics including count, mean, median, standard deviation, minimum, maximum, and quartile values. These metrics offer insightful information about how users rate and how ratings are distributed throughout the dataset.

Additionally, the descriptive analysis helps evaluate the dataset's suitability and quality for the creation of recommendation systems. It indicates the concentration of rating values, draws attention to the data's dispersion, and offers a statistical basis for understanding the exploratory studies covered in the sections that follow.

6.3.1 Statistical Summary

Purpose

Before doing a thorough exploratory study, the statistical summary aims to provide the main descriptive measures of the Book Rating variable and explain its general distribution.

Program Output

```
count    1.031136e+06
mean     2.839051e+00
std      3.854157e+00
min      0.000000e+00
25%      0.000000e+00
50%      0.000000e+00
75%      7.000000e+00
max      1.000000e+01
```

Results Analysis and Interpretation

The statistics summary shows that the dataset is appropriate for recommendation system study since it has a significant number of user rating records. The descriptive statistical analysis confirms that the Book Recommendation Dataset contains sufficient user rating information for analysis.The statistical measures reveal the presence of both implicit and explicit feedback, highlight the variability in user ratings, and support the suitability of the dataset for developing the proposed Hybrid Book Recommendation System.

When the median value is 0, it means that many users have not given explicit reviews, which has led to a high percentage of implicit input.The standard deviation reveals that user ratings differ significantly, suggesting a range of reading tastes.In accordance with the rating scale us ed in the dataset, the lowest and maximum values verify that ratings fall between 0 and 10. Additionally, the quartile values show that explicit ratings are less common than implicit inter actions and offer greater insight into the rating distribution. All things considered, the statistical summary offers a clear grasp of the dataset's numerical properties and lays a solid basis for the next exploratory investigations.

Conclusion

The Book Recommendation Dataset has enough user rating data for study, according to the descriptive statistical analysis. The statistical measurements corroborate the dataset's suitability for creating the suggested Hybrid Book Recommendation System, show the existence of both implicit and explicit feedback, and draw attention to the variation in user ratings.


6.4 Exploratory Data Analysis

To investigate the traits, trends, and connections found in the Book Recommendation Dataset, exploratory data analysis (EDA) is carried out.In order to comprehend user behavior, book p opularity, author and publisher distributions, and the relationship between numerical variable, the visuals from Chapter 5 (Data Visualization) are analyzed in this part.The study assists in

finding significant insights that enable the development of the proposed Hybrid Book Recom mendation System.

6.4.1 Analysis of Book Rating Distribution

Figure 6.1 – Distribution of Book Ratings




Purpose: To examine the distribution of user ratings and comprehend the dataset's general rati ng behavior.

Analysis and Interpretation:The bulk of book evaluations are focused at 0, as seen in Figur e 5.2, but explicit ratings between 1 and 10 are less common.This suggests that implicit feedb ack, as opposed to expressed opinions, makes up a significant amount of user interactions.Th ere is a significant imbalance in the distribution, with very few users giving evaluations. Recommendation datasets frequently exhibit this kind of sparsity, which poses difficulties for conventional collaborative filtering techniques.

Conclusion: The rating distribution supports the use of a hybrid book recommendation syste m that can handle sparse rating data and validates the existence of implicit feedback.

6.4.2 Analysis of Top 10 Most Rated Books

Figure 6.2 – Top 10 Most Rated Books




Purpose: To determine which books have the most user ratings and estimate their level of popularity.

Interpretation and Analysis : A small handful of novels have gotten noticeably higher ratings than others, as seen in Figure 5.3. This unequal distribution suggests that while many books obtain relatively low ratings, user interactions are focused on a select few popular publications. Recommendation performance is impacted by this popularity bias, which is frequently seen in recommendation datasets.

Conclusion: The research emphasizes the prevalence of popular novels within the dataset and gives useful insights into user reading patterns.

6.4.3 Analysis of Top 10 Authors

Figure 6.3 – Top 10 Authors




Purpose : To look at how the most well-represented writers' works are distributed.

Interpretation and Analysis : According to the research, a significant percentage of the books in the dataset are written by a limited number of writers. This implies that some writers are more well-represented and are probably going to draw higher user engagement. As a result, author information is crucial for comprehending the qualities of material and aiding in the creation of recommendations.

Conclusion : The author distribution study highlights the significance of author-related information in the recommendation process and illustrates the impact of well-known writers.

6.4.4 Analysis of User Age Distribution

Figure 6.4 – User Age Distribution




Purpose : To comprehend the age-based demographic distribution of consumers.

Interpretation and Analysis: The majority of users, as shown in Figure 5.1, are youthful and middle-aged, with comparatively fewer users falling into the younger and older age groups. This distribution implies that active adult users' reading choices are the dataset's primary representation. Comprehending user demographics facilitates the explanation of rating trends and user behavior in the recommendation system.

Conclusion : The age distribution helps to better understand the user population of the dataset and offers helpful demographic information.

6.4.5 Analysis of Top 10 Publishers

Figure 6.5 – Top 10 Publishers




Purpose : To evaluate publications' contributions to the dataset.

Interpretation and Analysis: The research reveals that a significant portion of the books in t he sample are published by alimited number of publishers.This suggests that publications are distributed unevenly, with some publishers controlling a large portion of the collection.Anoth er helpful content characteristic that might help with recommendation tactics is publisher info rmation.

Conclusion: The publisher analysis finds significant contributions to the accessible book colle ction and improves knowledge of dataset composition.

6.4.6 Correlation Analysis

Figure 6.6 – Correlation Matrix



Purpose: To investigate how the dataset's numerical variables relate to one another.

Interpretation and Analysis

Age has little bearing on users' rating behavior, according to the correlation matrix, which sho ws a very weak negative association between User Age and Book Rating.

This implies that in order to enhance suggestion quality, recommendations should take into ac count a variety of user and book features rather than just demographic data.

Conclusion

The correlation study supports the necessity for a hybrid recommendation strategy that takes i nto account a variety of information sources by confirming that there is no significant linear li nk between the numerical variables.

6.5 Key Findings from Exploratory Data Analysis

The Exploratory Data Analysis (EDA) revealed important information about the features and quality of the Book Recommendation Dataset. The dataset includes a significant number of books, users, and user ratings, making it ideal for creating a dependable Hybrid Book Recommendation System.

The descriptive statistical study found that Book Rating values vary from 0 to 10, with a sizable fraction of ratings centered around 0, indicating the presence of implicit user input. The statistical metrics also revealed significant diversity in user rating behavior, indicating various user preferences.

The examination of the visualizations revealed that user ratings are extremely uneven, with just a small number of books obtaining a high number of evaluations. In contrast, the Top 10 writers and Top 10 Publishers studies revealed that a small group of writers and publishers account for a significant amount of the dataset. The User Age Distribution demonstrated that the majority of users are youthful and middle-aged, whereas the Correlation Analysis showed a very weak association among user age and book ratings.

To summarize, the findings show that the dataset is extensive and well-suited to recommendation system development. The insights gained via EDA give a deeper knowledge of user behavior, book popularity, and dataset features, laying a solid foundation for the proposed Hybrid Book Recommendation System's implementation in the next chapter.

6.6 Chapter Summary

This chapter gave a detailed Exploratory Data Analysis (EDA) of the Book Recommendation Dataset to acquire a better knowledge of the data prior to developing the suggested Hybrid Book Recommendation System. The investigation concentrated on the dataset's structure, statistical features, and underlying trends, which are critical for interpreting user behavior and book-related information.

In the beginning, the dataset was described in full, including its source, structure, and constituent datasets (Books, Users, and Ratings). The dataset information emphasized the number of records, properties, and variable types, giving a clear picture of the data utilized in this study. This review set the framework for the future exploratory and statistical investigations.

The chapter next offered the Descriptive Statistical Analysis, which used statistical measures including count, mean, median, standard deviation, minimum, maximum, and quartiles to characterize the dataset's numerical properties. These tests revealed useful information about the distribution of book evaluations and verified the presence of both implicit and explicit user input. The statistical summary also showed the variety of user rating behaviour, indicating that the dataset is appropriate for recommendation system investigation.

Furthermore, the exploratory data analysis investigated key patterns and relationships in the dataset by analyzing the visualizations described in the preceding chapter. The examination of book rating distribution indicated an unequal distribution of ratings, however the popularity analysis found the most frequently rated novels. Similarly, examinations of writers and

publishers revealed that a small number of contributors dominated the dataset. The user age distribution gave demographic information about the user community, and the correlation analysis revealed that user age had a weak link with book ratings. These findings helped us better comprehend the dataset and its properties.

The primary findings from the exploratory research revealed that the Book Recommendation Dataset is extensive, diversified, and well-suited for constructing a recommendation system. The insights generated from statistical and exploratory studies improved comprehension of user preferences, rating behavior, and content distribution, assisting in the selection of an acceptable recommendation method.

To summarize, the Exploratory Data Analysis was an important component in this study since it converted the raw material into useful data via statistical summaries and analytical interpretation. The knowledge gained through this chapter serves as a solid logical pillar for the proposed Hybrid Book Recommendation System, which is described and assessed in the following chapter.

7. MODEL BUILDING / ADVANCED DATA ANALYSIS TECHNIQUES

7.1 Introduction

Advanced Statistical Analysis and Model Building are critical steps in the development of the proposed Personalized Hybrid Book Recommendation System based on User Preference Data. once you have completed reviewing the dataset's properties using Exploratory Data Analysis (EDA) in the previous chapter, statistical studies are required to acquire a deeper awareness of the correlations between the variables. These studies assist in identifying relevant trends in user activity, validating dataset properties, and providing statistical evidence to enable the creation of an accurate and reliable recommendation system.

The primary goal of this chapter is to use advanced statistical techniques to analyze the Book Recommendation Dataset and interpret the results in the context of customized book suggestions.Statistical analysis allows for the recognition of important correlations across variables, comparison among user groups, and assessment of the impact of demographic factors on user rating behaviour.These outcomes provide valuable knowledge into consumer needs and help us understand more fully the factors that affect recommendation quality.

In the current investigation, statistical strategies involving Analysis of Variance (ANOVA), Pearson Correlation Analysis, Independent Sample tTest, and Descriptive Statistical Analysis were carried out leveraging the Python programming language in the Jupyter Notebook envir onment.

The analyses were carried out using appropriate statistical libraries, and the outputs were gen erated accordingly.The outcomes of each of these methodologies are analyzed to assess rating patterns, examine relationships between variables, and determine the statistical significance of the findings.Every portion of the present chapter describes the statistical technique's purpo se, the software and libraries which were utilized, and the program output created during the i mplementation phase, followed by a comprehensive analysis, explanation of the results, and a

conclusion. This methodical approach guarantees that each statistical technique is presented in detail and closely relates to the goals of the suggested recommendation system.

This chapter's statistical results provide the analytical basis for the suggested Personalized Hybrid Book Recommendation System. They provide statistical validation of the dataset, explain why the recommendation technique was chosen, and show how statistical analysis helps to better understand user preferences and enhance recommendation performance. All things considered, this chapter lays out the research's statistical foundation and offers the assistance required to create a successful and customized book recommendation system.

7.2 Analysis of Variance (ANOVA)

7.2.1 Introduction

ANOVA was used to see if there existed any statistically significant variations in average book evaluations between user age groups. Studying these distinctions, in the context of the proposed Personalized Hybrid Book Recommendation System, aids in determining if age has a measurable affect on user rating behaviour. The findings of this investigation give statistical data that helps to understand user preferences and adds to the creation of more effective suggestion systems.

7.2.2 Objective

The ANOVA test is used to examine the possibility that mean book ratings vary substantially across several user age groups in the Book Recommendation Dataset.

7.2.3 Justification

Users of different ages may have varied reading and rating preferences. Identifying whether these changes are statistically significant is critical for understanding user preferences. ANOVA was chosen because it allows for the comparative comparison of mean scores across many groups, which make it appropriate for analyzing demographic variables in the dataset.

7.2.4 Software and Libraries Used

Software Used

- Python Programming Language
- Jupyter Notebook

Libraries Used

- Pandas
- NumPy
- SciPy (stats.f_oneway())

7.2.5 Implementation

The user age data was divided into three categories:

- **Group 1:** Users aged below 25 years
- **Group 2:** Users aged between 25 and 44 years
- **Group 3:** Users aged 45 years and above

The one-way ANOVA test was performed using the SciPy library's stats.f_oneway() function, which compared the average book ratings between all three of these age groups.

7.2.6 Program Output

```
========== ANOVA TEST ==========

F-Statistic: 287.62838364935726
P-Value: 1.316471911905554e-125
Result: Significant difference among age groups.
```

7.2.7 Results Analysis and Interpretation

The ANOVA test produced an **F-statistic of 287.6284** and a **p-value of 1.31647×10^{-125}**. Since the obtained p-value is considerably smaller than the commonly accepted significance level of **0.05**, the null hypothesis is rejected.

This finding shows that there exist statistically significant variations in average book evaluations between the age groups examined. In other words, consumers of different ages do

not rate similarly. However the differences in average ratings appear to be tiny, the statistical test indicates that these variances are significant due to the vast number of observations in the dataset.The findings indicate that age effects user rating behavior to some extent, and that various age groups may have diverse reading preferences. Younger users may score specific types of books differently than middle-aged or older users due to differences in interests, reading habits, and content preferences.

In contrast, the ANOVA results should not be construed as proof that age alone may provide correct suggestions. Instead, the data suggest that age might be used as a favorable demographic factor when analyzing user behavior. The proposed Hybrid Book Recommendation System is largely based on user-item interactions and book content, with demographic information serving as an extra aspect in determining user characteristics.

Overall, the ANOVA study offers useful statistical evidence on consumer choice variation and enhances the recommendation system's analytical base by confirming the existence of substantial variances across user groups.

7.2.8 Conclusion

The Analysis of Variance (ANOVA) reveals statistically significant variations in average book evaluations between user age groups. The collected results show that age has a meaningful impact on rating behavior and might give helpful information about user preferences. Though age is not the key recommendation factor, it does provide useful demographic information for the design and assessment of the proposed Personalized Hybrid Book Recommendation System.

7.3 Pearson Correlation Analysis

7.3.1 Introduction

The Pearson Correlation Analysis was used to determine the strength and direction of the linear association among User Age and Book Rating in the Book Recommendation Dataset.

Understanding this link aids in determining if age has a significant impact on users' rating behavior and whether demographic data needs to be used while constructing the proposed Personalized Hybrid Book Recommendation System.

In contrast to ANOVA, which examines mean ratings across age groups, Pearson Correlation Analysis determines if changes in one variable are related with improvements in another. The study presents statistical evidence for the degree of correlation among user age and book evaluations.

7.3.2 Objective

Finding out if there is a significant linear relationship among User Age and Book Rating in the dataset is the goal of Pearson Correlation Analysis.

7.3.3 Justification

One of the key demographic characteristics found in the Book Recommendation Dataset is user age. It is possible to determine the extent to which users of different ages display similar or distinct rating behaviors by examining its correlation with book ratings. Analyzing user preferences and assessing the significance of demographic characteristics in the suggested suggestion system are made easier with the use of this data.

7.3.4 Software and Libraries Used

Software Used

- Python Programming Language
- Jupyter Notebook

Libraries Used

- Pandas
- NumPy

7.3.5 Implementation : The Pandas library's corr() function was used to conduct Pearson Correlation Analysis. After preliminary processing of the dataset and addressing missing

values, the study determined the correlation coefficient over the Age and Book-Rating characteristics. The resultant coefficient falls between -1 and +1, with values near +1 denoting a strong positive association, values near -1 denoting a strong negative link, and values around 0 denoting little to no linear relationship.

7.3.6 Program Output

Output obtained from the notebook:

```
========== CORRELATION ANALYSIS ==========

Correlation between Age and Book Rating:
-0.024190945598175015
```

7.3.7 Results Analysis and Interpretation

User age and book rating had a connection value of -0.0242 according to the Pearson connection Analysis. Although the coefficient is very near to zero, indicating a very weak association, the negative value suggests a tiny inverse connection among the two variables.

This finding implies that there exists hardly any linear correlation between users' ages and the book evaluations they give. Practically speaking, people of different ages tend to rate books similarly, and age by itself has little bearing on book ratings.

The poor association suggests that user preferences cannot be reliably predicted using demographic data, such as age. Consequently, the quality of recommendations may be lowered if age-based suggestions are the sole ones used.

Rather, book content and user-item interactions offer more useful data for creating tailored suggestions.The results further endorse the design of the suggested Personalized Hybrid Book Recommendation System, which does not rely on a single demographic factor but rather blends content-based and collaborative filtering. The dataset shows a modest link between age and suggestion accuracy, despite the fact that age offers valuable past data about users.

As a whole, the Pearson Correlation Analysis supports the necessity for a hybrid recommendation method that takes into account both user behavior and book features by confirming that user preferences are impacted by a variety of factors beyond age.

7.3.8 Conclusion

Age has little bearing on users' rating behavior, according to the Pearson Correlation Analysis, which found a very small negative correlation (-0.0242) between User Age and Book Rating. The investigation shows that user choices cannot be accurately represented by demographic data alone. As a result, the suggested Personalized Hybrid Book Recommendation System treats age as a favorable parameter for comprehending user characteristics while focusing largely on user ratings and book qualities.

7.4 Independent Sample t-Test

7.4.1 Introduction

To find out if there exists a statistically significant difference in the average book ratings provided by two separate user groups depending on age, the Independent Sample t-Test was used. This analysis aids in determining whether demographic segmentation aids in comprehending user preferences and whether age affects users' rating behavior. The suggested Personalized Hybrid Book Recommendation System is supported statistically by the test's findings.

7.4.2 Objective

By comparing the mean book evaluations of two distinct age groups, the Independent Sample t-Test seeks to ascertain if the observed difference is statistically significant.

7.4.3 Justification : Analyzing user preferences requires knowing which of the various age groups display distinct rating behaviors. Because it is a suitable statistical method for testing the mean ratings of two independent groups, the Independent Sample t-Test was used. The results aid in determining if age should be taken into account when making recommendations.

7.4.4 Software and Libraries Used

Software Used

- Python Programming Language
- Jupyter Notebook

Libraries Used

- Pandas
- NumPy
- SciPy (stats.ttest_ind())

7.4.5 Implementation

For this analysis, the users were divided into two independent groups based on age:

- **Group 1:** Users aged **below 35 years**
- **Group 2:** Users aged **35 years and above**

The SciPy library's stats.ttest_ind() method was used to conduct the Independent Sample t-Test. To ascertain if a distinction in the two groups' mean book ratings was statistically significant, the test was compared to their average ratings.

7.4.6 Program Output

```
========== T-TEST ==========

T-Statistic: -1.838897372175017
P-Value: 0.06593056977967114
Result: No significant difference exists.
```

7.4.7 Results Analysis and Interpretation

The Independent Sample t-Test yielded a p-value of 0.0659 and a t-statistic of -1.8389. The null hypothesis cannot be rejected since the p-value is higher than the generally recognized significance level of 0.05.

The findings show that the average book ratings of users under 35 and those over 35 do not differ statistically significantly. The two groups' mean scores differ somewhat, but these changes are not statistically significant and might have been the result of random fluctuation in the data.

This result implies that consumers' ratings of books are not significantly influenced by age alone. Demographic data alone is inadequate to effectively forecast user preferences, as users from different age groups typically display comparable rating behavior.

The result validates the architecture of the suggested Personalized Hybrid Book Recommendation System, which places more emphasis on book features and user-item interactions than it does on demographic data. Personalized suggestions are more successfully produced by analyzing consumers' past ratings and book content, even if age might offer helpful contextual information.

7.4.8 Conclusion

The average book ratings for the two age groups under analysis do not differ statistically significantly, according to the Independent Sample t-Test. This implies that users' rating behavior is not primarily influenced by their age. Thus, in order to provide appropriate suggestions, the suggested Personalized Hybrid Book Recommendation System mainly relies on user preferences and book attributes; demographic data is only utilized as supporting data.

7.5 Descriptive Statistical Analysis

7.5.1 Introduction

The Book Recommendation Dataset's numerical features were compiled using descriptive statistical analysis. Understanding the distribution, variability, and central tendency of user ratings is crucial before using recommendation algorithms. These statistical metrics aid in identifying the general rating behavior of users and offer a comprehensive comprehension of the dataset.

In this research, the Book-Rating property was analyzed using Python to calculate descriptive statistics. Measures like mean, median, mode, variance, standard deviation, minimum value, and maximum value are all included in the study. These figures aid in the assessment of user preference trends and offer insightful information about the distribution of ratings.

7.5.2 Objective

Understanding the general distribution of user ratings in the dataset and summarizing the important statistical features of the Book-Rating variable are the goals of the descriptive statistical analysis.

7.5.3 Justification

By calculating the dataset's central tendency and dispersion, descriptive statistics offer a brief summary of the data. These metrics aid in identifying the range of user ratings, evaluating the variability within the dataset, and determining if the ratings are clustered around particular values. Before creating a customized recommendation system, this information is crucial for comprehending user behavior.

7.5.4 Software and Libraries Used

Software Used

- Python Programming Language
- Jupyter Notebook

Libraries Used

- Pandas
- NumPy

7.5.5 Program Output

```
========== DESCRIPTIVE STATISTICS ==========

Mean Rating:
2.839051298761754

Median Rating:
0.0

Mode Rating:
0

Variance:
14.854523368314254

Standard Deviation:
3.854156635155641

Minimum Rating:
0

Maximum Rating:
10
```

7.5.6 Results Analysis and Interpretation

The mean book rating, according to the descriptive statistical analysis, is 2.8391, indicating that the dataset's overall average rating is rather low. This is mostly due to the dataset's high percentage of zero ratings, which indicate implicit user interactions as opposed to explicit rating preferences.

Zero is an extremely common value in the dataset, as indicated by the median rating of 0 and the mode of 0. This demonstrates that a large number of people engaged with books without giving them specific evaluations. Recommendation datasets frequently have this distribution, which emphasizes the existence of sparse rating data.

Significant variety in user evaluations is indicated by the variance of 14.8545 and the standard deviation of 3.8542. Instead of grouping around a single rating, this indicates that readers have a variety of reading tastes and give ratings over a broad range of values.The dataset contains

the whole rating scale, as seen by the minimum rating of 0 and the greatest rating of 10. In addition to reflecting varying degrees of user happiness, this broad range of ratings offers enough variation for personalized recommendation algorithms to discover unique user preferences.

The dataset has a wide range of ratings with considerable variability, according to the descriptive statistical metrics. Higher ratings allow recommendation algorithms to find significant user-book interaction patterns, even while zero ratings predominate in the sample.

7.5.7 Conclusion

The Book Recommendation Dataset is thoroughly summarized by the Descriptive Statistical Analysis, which also emphasizes the general features of user evaluations. The findings show that while there is significant heterogeneity along the whole rating range, zero ratings predominate in the dataset. These results verify that the dataset is appropriate for creating a customized recommendation system, as the range of ratings enables collaborative and hybrid recommendation methods to determine user preferences and produce pertinent book suggestions.

7.6 Statistical Findings and Model Justification

7.6.1 Introduction

The statistical studies carried out in this study offer significant insights into the features of the Book Recommendation Dataset and user behavior while evaluating books. The dataset is validated and the construction of the suggested Personalized Hybrid Book Recommendation System is supported by the findings from Descriptive Statistical Analysis, Analysis of Variance (ANOVA), Pearson Correlation Analysis, and the Independent Sample t-Test. The main conclusions are outlined in this part along with an explanation of how they support the chosen recommendation strategy.

7.6.2 Statistical Findings

The dataset comprises a high number of user ratings with significant variance, according to the descriptive statistical analysis.While a large range of ratings reveals a variety of user preferences, the occurrence of zero ratings implies rating sparsity. The dataset is appropriate for customized recommendation modeling because of these features. The average ratings for each age group varied statistically significantly, according to the ANOVA results, suggesting that user age has some bearing on rating behavior. However, the Pearson association Analysis revealed a very weak negative association between book ratings and age, indicating that user preferences are not well predicted by age itself.

The average evaluations for the two chosen age groups did not differ statistically significantly, according to the Independent Sample t-Test. This result further demonstrates that users' reading preferences and rating behaviors cannot be adequately represented by demographic data alone.

7.6.3 Model Justification

The statistical results show that while demographic characteristics like age offer valuable information about consumers, they are not enough to produce precise individualized suggestions. Numerous factors, such as book attributes and prior rating behavior, affect user preferences.

As a result, the suggested Personalized Hybrid Book Recommendation System makes sense since it blends content-based and collaborative filtering to provide suggestions that are more pertinent. When in contrast to depending only on demographic characteristics, our hybrid approach improves suggestion quality by utilizing both user–item interactions and book features.

7.6.4 Conclusion

The suggested recommendation method is well supported by the statistical studies carried out in this chapter. The results show that while user ratings and book information are more

important in determining user preferences, demographic factors have less predictive ability. As a result, using a hybrid recommendation strategy is statistically justified and offers a solid basis for providing precise and customized book suggestions.

7.7 Chapter Summary

The highly advanced statistical studies were out on the Book Recommendation Dataset to investigate user rating behavior and verify the statistical properties of the data were given in this chapter. The findings developed a solid analytical basis for the suggested Personalized Hybrid Book Recommendation System and offered a greater knowledge of the correlations between factors. The mean book evaluations across age groups differ statistically significantly, according to the Analysis of Variance (ANOVA).

The results of the Pearson Correlation Analysis showed a very weak correlation between user age and book ratings, indicating that users' rating behavior is not significantly influenced by age alone. Accordingly, there was no statistically significant difference in the average ratings across the chosen age groups according to the Independent Sample t-Test, suggesting that user preferences cannot be predicted only from demographic data. The dataset's eligibility for recommendation system creation was confirmed by the descriptive statistical analysis, which described the rating distribution and emphasized the dataset's variety and sparsity. The aggregate statistical results showed that a variety of factors, as opposed to a single demographic characteristic, impact consumer choices.

These findings support the adoption of a hybrid recommendation strategy, which creates more precise and customized suggestions by fusing user-item interactions with book content. Additionally, the studies confirmed the dataset's quality and dependability, giving the suggested technique approval. All things considered, this chapter provided the research's statistical foundation and illustrated how cutting-edge statistical methods aid in the creation of a successful Personalized Hybrid Book Recommendation System.

8.CONCLUSION & FUTURE SCOPE

8.1 Conclusion

In order to give customers precise and customized book suggestions, this study described the design and development of a Personalized Hybrid Book Recommendation System based on User Preference Data. By integrating collaborative filtering and content-based filtering techniques, the research overcame the shortcomings of conventional recommendation algorithms and produced recommendations that were pertinent to both user rating behavior and book attributes.

The extensive data collecting and preparation of the Book Recommendation Dataset was the first step in the project. To increase the dataset's quality and dependability, data cleaning, management of missing values, duplication removal, and feature preparation were done. The distribution of user ratings, book popularity, author contributions, publisher information, user demographics, and the correlations between various factors were then examined using exploratory data analysis (EDA). According to the EDA results, the dataset has a wide range of user preferences and a lot of rating data, which makes it appropriate for developing a customized recommendation system.

Advanced statistical analysis were carried out to further verify the dataset. Although the Pearson Correlation Analysis revealed only a very weak correlation between user age and book ratings, the Analysis of Variance (ANOVA) showed statistically significant variations in book evaluations across various age groups. Age by itself does not substantially affect users' rating behavior, according to the Independent Sample t-Test. Descriptive statistical analysis also emphasized the existence of rating sparsity and user preference variation while summarizing the dataset's main statistical features. These results provided a solid statistical basis for the suggested recommendation system.

These investigations led to the development of a Hybrid Recommendation Model that combined content-based and collaborative filtering. This method successfully overcomes the drawbacks of individual recommendation systems by combining user-item interactions with book characteristics. By taking into account a variety of user interests rather than just one, the hybrid model is able to produce more tailored and relevant book suggestions.

Overall, this study's goals were satisfactorily met. The suggested Personalized Hybrid Book Recommendation System shows how statistical analysis and machine learning-based recommendation methods may greatly enhance suggestion quality. The study also emphasizes how crucial statistical validation, exploratory analysis, and data pretreatment are to creating trustworthy recommendation systems. The study's findings offer a solid basis for the use of tailored recommendation systems in online bookshops, digital libraries, learning environments, and other data retrieval systems.

8.2 Future Scope

Even though the study's goals were met by the suggested Personalized Hybrid Book Recommendation System, there are still a number of areas that might be improved upon and further investigated. In order to provide suggestions, the present system mainly uses book information and user ratings. By using cutting-edge machine learning and deep learning methods, the recommendation model may also be improved. To record complex links among users and books, algorithms like graph neural networks, deep autoencoders, transformer-dependent recommendation models, and neural collaborative filtering might be investigated. These methods could enhance the reliability of recommendations, especially for consumers with little rating history.

Using Natural Language Processing (NLP) tools to analyze book descriptions, summaries, genres, reviews, and user comments is another possible improvement. Additional contextual information may be obtained using sentiment analysis and semantic similarity techniques,

allowing the recommendation system to produce more insightful and content-aware recommendations.

Future studies may also concentrate on creating a real-time recommendation system that can dynamically update suggestions as consumers engage with books. Users might quickly receive tailored recommendations based on their most recent activity by connecting the recommendation engine with online or mobile applications. To further increase its success rate and scalability, the suggested model's performance may be assessed using bigger, more modern datasets, various assessment measures, and comparisons with cutting-edge recommendation algorithms.

To sum up, the suggested Personalized Hybrid Book Recommendation System offers a solid basis for further investigation into intelligent recommendation systems. Future iterations of the system can provide even more precise, scalable, and user-focused book suggestions throughout a variety of digital platforms by integrating more user behavior, sophisticated artificial intelligence algorithms, and real-time customisation.

9 . APPENDIX

Program Code for Implementation

```
!pip install pandas numpy matplotlib seaborn scipy scikit-learn scikit-surprise

import surprise

print("Surprise installed successfully!")

from surprise import Dataset, Reader, SVD

print("Library working correctly!")

import pandas as pd

import numpy as np

import matplotlib.pyplot as plt

import seaborn as sns

from scipy import stats

from sklearn.metrics.pairwise import cosine_similarity

from sklearn.feature_extraction.text import TfidfVectorizer

import pandas as pd

books = pd.read_csv("books.csv")

ratings = pd.read_csv("Ratings.csv")

users = pd.read_csv("Users.csv")

print("Books Shape:", books.shape)

print("Ratings Shape:", ratings.shape)

print("Users Shape:", users.shape)

books = pd.read_csv("books.csv", low_memory=False)

print(books.columns)

print(ratings.columns)

print(users.columns)
```

```
# Merge Ratings with Users
data = pd.merge(ratings, users, on='User-ID')
# Merge with Books
data = pd.merge(data, books, on='ISBN')
print("Merged Dataset Shape:", data.shape)
# Display first 5 rows
data.head()
print(data.isnull().sum())
# Remove duplicates
data.drop_duplicates(inplace=True)
# Fill missing ages with median
data['Age'] = data['Age'].fillna(data['Age'].median())
# Convert age to integer
data['Age'] = data['Age'].astype(int)
print(data.shape)
print(data['Book-Rating'].describe())
print("Mean Rating:",
    data['Book-Rating'].mean())
print("Median Rating:",
    data['Book-Rating'].median())
print("Standard Deviation:",
    data['Book-Rating'].std())
print(data.shape)
# MODULE 2: EXPLORATORY DATA ANALYSIS (EDA)
```

```
# PURPOSE:
# To understand user behavior, rating patterns,
# popular books, authors, publishers, and age distribution.
# This satisfies the EDA and Visualization requirements.
import matplotlib.pyplot as plt
import seaborn as sns
# 2.1 Rating Distribution Analysis
# PURPOSE:
# To analyze how users rate books and identify rating patterns.
plt.figure(figsize=(8,5))
sns.countplot(x='Book-Rating', data=data)
plt.title('Distribution of Book Ratings')
plt.xlabel('Rating')
plt.ylabel('Count')
plt.show()
# 2.2 Top 10 Most Rated Books
# PURPOSE:
# To identify the most popular books based on user ratings.
top_books = data['Book-Title'].value_counts().head(10)
plt.figure(figsize=(10,5))
sns.barplot(x=top_books.values, y=top_books.index)
plt.title('Top 10 Most Rated Books')
plt.xlabel('Number of Ratings')
plt.ylabel('Book Title')
plt.show()
```

```
# 2.3 Top Authors Analysis
# PURPOSE:
# To identify authors with the highest number of rated books.
top_authors = data['Book-Author'].value_counts().head(10)
plt.figure(figsize=(10,5))
sns.barplot(x=top_authors.values, y=top_authors.index)
plt.title('Top 10 Authors')
plt.xlabel('Books Count')
plt.ylabel('Author')
plt.show()
# 2.4 User Age Distribution
# PURPOSE:
# To study the age profile of users in the dataset.
plt.figure(figsize=(8,5))
sns.histplot(data['Age'], bins=30, kde=True)
plt.title('Age Distribution of Users')
plt.xlabel('Age')
plt.ylabel('Frequency')
plt.show()
# 2.5 Publisher Analysis
# PURPOSE:
# To identify publishers with the highest number of books.
top_publishers = data['Publisher'].value_counts().head(10)
plt.figure(figsize=(10,5))
sns.barplot(x=top_publishers.values, y=top_publishers.index)
```

```
plt.title('Top 10 Publishers')
plt.xlabel('Count')
plt.ylabel('Publisher')
plt.show()
# 2.6 Correlation Analysis
# PURPOSE:
# To examine the relationship between Age and Book Rating.
numeric_cols = data[['Book-Rating', 'Age']]
plt.figure(figsize=(6,4))
sns.heatmap(
    numeric_cols.corr(),
    annot=True,
    cmap='coolwarm'
)
plt.title('Correlation Matrix')
plt.show()
# MODULE 3: DESCRIPTIVE STATISTICS & HYPOTHESIS TESTING
# PURPOSE:
# To analyze the statistical characteristics of the dataset.
import numpy as np
from scipy import stats
# 3.1 DESCRIPTIVE STATISTICS
# PURPOSE:
# To summarize the rating data using statistical measures.
print("========== DESCRIPTIVE STATISTICS ==========\n")
```

```
print("Mean Rating:")
print(data['Book-Rating'].mean())
print("\nMedian Rating:")
print(data['Book-Rating'].median())
print("\nMode Rating:")
print(data['Book-Rating'].mode()[0])
print("\nVariance:")
print(data['Book-Rating'].var())
print("\nStandard Deviation:")
print(data['Book-Rating'].std())
print("\nMinimum Rating:")
print(data['Book-Rating'].min())
print("\nMaximum Rating:")
print(data['Book-Rating'].max())
# 3.2 CORRELATION ANALYSIS
# PURPOSE:
# To determine the relationship between Age and Book Rating.
print("\n========== CORRELATION ANALYSIS ==========\n")
correlation = data['Age'].corr(data['Book-Rating'])
print("Correlation between Age and Book Rating:")
print(correlation)
# 3.3 T-TEST
# PURPOSE:
# To compare ratings between younger and older users.
print("\n========== T-TEST ==========\n")
```

```
young_users = data[data['Age'] < 35]['Book-Rating']
older_users = data[data['Age'] >= 35]['Book-Rating']
t_stat, p_value = stats.ttest_ind(
    young_users,
    older_users,
    nan_policy='omit'
)
print("T-Statistic:", t_stat)
print("P-Value:", p_value)
if p_value < 0.05:
    print("Result: Significant difference exists.")
else:
    print("Result: No significant difference exists.")
# 3.4 ANOVA TEST
# PURPOSE:
# To compare ratings across multiple age groups.
print("\n========== ANOVA TEST ==========\n")
group1 = data[data['Age'] < 25]['Book-Rating']
group2 = data[(data['Age'] >= 25) & (data['Age'] < 45)]['Book-Rating']
group3 = data[data['Age'] >= 45]['Book-Rating']
f_stat, p_value = stats.f_oneway(
    group1,
    group2,
    group3
)
```

```
print("F-Statistic:", f_stat)
print("P-Value:", p_value)
if p_value < 0.05:
    print("Result: Significant difference among age groups.")
else:
    print("Result: No significant difference among age groups.")
# 3.5 AGE GROUP ANALYSIS
# PURPOSE:
# To calculate average ratings for different age groups.
print("\n========== AGE GROUP ANALYSIS ==========\n")
data['Age_Group'] = pd.cut(
    data['Age'],
    bins=[0,18,30,45,60,100],
    labels=['0-18','19-30','31-45','46-60','60+']
)
age_group_ratings = data.groupby(
    'Age_Group',
    observed=False
)['Book-Rating'].mean()
print(age_group_ratings)
# MODULE 4: COLLABORATIVE FILTERING
# PURPOSE:
# Generate personalized recommendations using user ratings.
from surprise import Dataset
from surprise import Reader
```

```
from surprise import SVD
from surprise.model_selection import train_test_split
from surprise.accuracy import rmse
# 4.1 PREPARE DATA FOR COLLABORATIVE FILTERING
# PURPOSE:
# Convert ratings data into Surprise library format.
ratings_data = ratings[['User-ID', 'ISBN', 'Book-Rating']]
reader = Reader(rating_scale=(0,10))
dataset = Dataset.load_from_df(
    ratings_data,
    reader
)
# 4.2 SPLIT DATA
# PURPOSE:
# Create training and testing datasets.
trainset, testset = train_test_split(
    dataset,
    test_size=0.2,
    random_state=42
)
# 4.3 TRAIN SVD(Sigular Value Decomposition) MODEL
# PURPOSE:
# Learn user-book interaction patterns.
svd_model = SVD()
svd_model.fit(trainset)
```

```
print("Collaborative Filtering Model Trained Successfully!")
# 4.4 PREDICT RATINGS
# PURPOSE:
# Predict unseen user ratings.
predictions = svd_model.test(testset)
print("Prediction Completed!")
# 4.5 EVALUATE MODEL
# PURPOSE:
# Measure recommendation accuracy.
rmse_value = rmse(predictions)
#rmse= root mean square error
print("RMSE:", rmse_value)
# 4.6 SAMPLE PREDICTION
# PURPOSE:
# Predict rating for a specific user-book pair.
sample_user = ratings['User-ID'].iloc[0]
sample_book = ratings['ISBN'].iloc[0]
prediction = svd_model.predict(
    sample_user,
    sample_book
)
print("\nSample Prediction")
print("User ID:", sample_user)
print("ISBN:", sample_book)
print("Predicted Rating:", prediction.est)
```

```
# MODULE 5: CONTENT-BASED FILTERING (FINAL VERSION)
# PURPOSE:
# Recommend similar books based on Title, Author, and Publisher.
# Memory-Optimized version for the Book-Crossing Dataset.
# OBJECTIVES COVERED:
# ☑ Objective 1 - Hybrid Recommendation System
# ☑ Objective 3 - Personalization
# ☑ Objective 4 - Computational Efficiency
# ☑ Objective 5 - Recommendation Quality & Explainability
from sklearn.feature_extraction.text import TfidfVectorizer
from sklearn.metrics.pairwise import linear_kernel
import pandas as pd
# 5.1 SELECT MOST POPULAR BOOKS
# PURPOSE:
# Reduce memory usage by selecting top 5000 books.
popular_books = data['ISBN'].value_counts().head(5000).index
books_small = books[
    books['ISBN'].isin(popular_books)
].copy()
print("Books Used For Content-Based Filtering:")
print(books_small.shape)
# 5.2 REMOVE DUPLICATE BOOK TITLES
# PURPOSE:
# Prevent duplicate index errors.
books_small = books_small.drop_duplicates(
```

```
    subset='Book-Title'
).reset_index(drop=True)
print("\nAfter Removing Duplicate Titles:")
print(books_small.shape)
# 5.3 CREATE FEATURE COLUMN
# PURPOSE:
# Combine Title, Author, and Publisher into one text field.
books_small['Features'] = (
    books_small['Book-Title'].fillna('') + ' ' +
    books_small['Book-Author'].fillna('') + ' ' +
    books_small['Publisher'].fillna('')
)
print("\nFeature Column Created Successfully!")
# 5.4 TF-IDF VECTORIZATION
# PURPOSE:
# Convert text features into numerical vectors.
tfidf = TfidfVectorizer(
    stop_words='english'
)
tfidf_matrix = tfidf.fit_transform(
    books_small['Features']
)
print("\nTF-IDF Matrix Shape:")
print(tfidf_matrix.shape)
```

```
# ------------------------------------------------------------
# 5.5 CREATE INDEX MAPPING
# PURPOSE:
# Map book titles to unique indices.
indices = pd.Series(
    books_small.index,
    index=books_small['Book-Title']
)
print("\nIndex Mapping Created Successfully!")
# 5.6 RECOMMENDATION FUNCTION
# PURPOSE:
# Return top N similar books.
def recommend_books(book_title, top_n=5):
    if book_title not in indices.index:
        print("Book not found in dataset.")
        return None
    idx = int(indices[book_title])
    cosine_scores = linear_kernel(
        tfidf_matrix[idx:idx+1],
        tfidf_matrix
    ).flatten()
    sim_scores = sorted(
        list(enumerate(cosine_scores)),
        key=lambda x: x[1],
        reverse=True
```

```
    )
    sim_scores = sim_scores[1:top_n+1]
    book_indices = [
        i[0]
        for i in sim_scores
    ]
    recommendations = books_small.iloc[
        book_indices
    ][
        ['Book-Title',
         'Book-Author',
         'Publisher']
    ]
            return recommendations
# 5.7 TEST THE MODEL
# PURPOSE:
# Generate recommendations for a sample book.
sample_book = books_small[
    'Book-Title'
].iloc[0]
print("\n==========================================")
print("SELECTED BOOK")
print("==========================================")
print(sample_book)
print("\n==========================================")
```

```
print("RECOMMENDED BOOKS")
print("==========================================")
recommended_books = recommend_books(
    sample_book,
    top_n=5
)
print(recommended_books)
# MODULE 6: HYBRID RECOMMENDATION SYSTEM
# PURPOSE:
# Combine Collaborative Filtering and Content-Based Filtering
# for better recommendation accuracy.
# 6.1 CONTENT-BASED RECOMMENDATIONS
content_recommendations = recommend_books(
    sample_book,
    top_n=5
)
print("CONTENT-BASED RECOMMENDATIONS")
print(content_recommendations)
# 6.2 COLLABORATIVE FILTERING PREDICTION
# PURPOSE:
# Predict rating for recommended books.
print("\nCOLLABORATIVE FILTERING SCORES")
hybrid_results = []
for _, row in content_recommendations.iterrows():
    title = row['Book-Title']
```

```
    isbn_match = books[
        books['Book-Title'] == title
    ]['ISBN']
    if len(isbn_match) > 0:
        isbn = isbn_match.iloc[0]
        pred = svd_model.predict(
            sample_user,
            isbn
        )
        hybrid_results.append([
            title,
            pred.est
        ])
# 6.3 FINAL HYBRID RECOMMENDATIONS
# PURPOSE:
# Rank recommendations using predicted ratings.
hybrid_df = pd.DataFrame(
    hybrid_results,
    columns=[
        'Book Title',
        'Predicted Rating'
    ]
)
hybrid_df = hybrid_df.sort_values(
    by='Predicted Rating',
```

```
    ascending=False
)
print("\nFINAL HYBRID RECOMMENDATIONS")
print(hybrid_df)
# MODULE 7: COLD START HANDLING
# PURPOSE:
# Recommend popular books for new users with no ratings.
# 7.1 CALCULATE BOOK POPULARITY
# PURPOSE:
# Find books with high average ratings and many ratings.
popular_df = data.groupby('Book-Title').agg({
    'Book-Rating': ['count', 'mean']
})
popular_df.columns = ['Rating_Count', 'Average_Rating']
popular_df = popular_df.reset_index()
# 7.2 FILTER POPULAR BOOKS
# PURPOSE:
# Keep books with sufficient ratings.
popular_books = popular_df[
    popular_df['Rating_Count'] >= 50
]
popular_books = popular_books.sort_values(
    by=['Average_Rating', 'Rating_Count'],
    ascending=False
)
```

```
# 7.3 TOP 10 RECOMMENDATIONS

# PURPOSE:

# Generate recommendations for new users.

top10_books = popular_books.head(10)

print("================================================")

print("TOP 10 RECOMMENDATIONS FOR NEW USERS")

print("================================================")

print(

   top10_books[

      ['Book-Title',

       'Average_Rating',

       'Rating_Count']

   ]

)

# MODULE 8: EVALUATION & EXPLAINABILITY

# PURPOSE:

# Evaluate recommendation quality and explain recommendations.

from surprise.accuracy import rmse, mae

# 8.1 MODEL EVALUATION

# PURPOSE:

# Measure prediction accuracy using RMSE and MAE.

print("================================================")

print("MODEL EVALUATION")

print("================================================")

rmse_score = rmse(predictions, verbose=False)
```

```
mae_score = mae(predictions, verbose=False)
print(f"RMSE Score : {rmse_score:.4f}")
print(f"MAE Score  : {mae_score:.4f}")
# 8.2 HYBRID RECOMMENDATION RESULTS
# PURPOSE:
# Display final recommendations generated by the hybrid model.
print("\n================================================")
print("FINAL HYBRID RECOMMENDATIONS")
print("================================================")
print(hybrid_df)
# 8.3 EXPLAINABILITY
# PURPOSE:
# Explain why books are recommended.
print("\n================================================")
print("RECOMMENDATION EXPLANATIONS")
print("================================================")
for _, row in hybrid_df.iterrows():
    print(f"\nBook: {row['Book Title']}")
    print(f"Predicted Rating: {row['Predicted Rating']:.2f}")
    print(
        "Reason: Recommended because it is "
        "similar to the selected book and "
        "has a high predicted preference score."
    )
# 8.4 PROJECT SUMMARY
```

```
# PURPOSE:
# Display completion status of all objectives.
print("\n==============================================")
print("PROJECT OBJECTIVES STATUS")
print("==============================================")
print("Objective 1 : Hybrid Recommendation System      ☑")
print("Objective 2 : Cold Start Handling              ☑")
print("Objective 3 : Personalization                  ☑")
print("Objective 4 : Scalability & Efficiency         ☑")
print("Objective 5 : Recommendation Quality           ☑")
# MODULE 9: PRECISION & RECALL EVALUATION
# PURPOSE:
# Evaluate Top-N Recommendation Quality
from collections import defaultdict
# STEP 1: CHECK IF PREDICTIONS EXIST
try:
    predictions
except NameError:
    print("ERROR: 'predictions' not found.")
    print("Run Module 4 (Collaborative Filtering) first.")
else:
    print("Predictions Found Successfully!")
    print("Total Predictions:", len(predictions))
    # STEP 2: PRECISION & RECALL FUNCTION
    def precision_recall_at_k(predictions,
```

```
                    k=10,
                    threshold=6):
    user_est_true = defaultdict(list)
    for uid, iid, true_r, est, _ in predictions:
        user_est_true[uid].append((est, true_r))
    precisions = dict()
    recalls = dict()
    for uid, user_ratings in user_est_true.items():
        # Sort by estimated rating
        user_ratings.sort(
            key=lambda x: x[0],
            reverse=True
        )
        # Relevant Items
        n_rel = sum(
            (true_r >= threshold)
            for (_, true_r) in user_ratings
        )
        # Recommended Items in Top-K
        n_rec_k = sum(
            (est >= threshold)
            for (est, _) in user_ratings[:k]
        )
        # Relevant & Recommended
        n_rel_and_rec_k = sum(
```

```
            (
                (true_r >= threshold)
                and
                (est >= threshold)
            )
            for (est, true_r)
            in user_ratings[:k]
        )
        precisions[uid] = (
            n_rel_and_rec_k / n_rec_k
            if n_rec_k != 0
            else 0
        )
        recalls[uid] = (
            n_rel_and_rec_k / n_rel
            if n_rel != 0
            else 0    )
    return precisions, recalls
# STEP 3: CALCULATE PRECISION & RECALL
precisions, recalls = precision_recall_at_k(
    predictions,
    k=10,
    threshold=6
)
avg_precision = (
```

```
    sum(precisions.values())
    / len(precisions)
)
avg_recall = (
    sum(recalls.values())
    / len(recalls)
)
# STEP 4: DISPLAY RESULTS
print("\n====================================")
print("PRECISION & RECALL EVALUATION")
print("====================================")
print("Average Precision:",
      round(avg_precision, 4))
print("Average Recall:",
      round(avg_recall, 4))
# STEP 5: INTERPRETATION
print("\n====================================")
print("INTERPRETATION")
print("====================================")
print("Precision measures how many")
print("recommended books were actually relevant.")
print("\nRecall measures how many")
print("relevant books were successfully recommended.")
print("\nHigher values indicate")
print("better recommendation quality.")
```

10. BIBLIOGRAPHY

1. F. Wayesa, M. Leranso, G. Asefa, and A. Kedir, "Pattern-Based Hybrid Book Recommendation System Using Semantic Relationships," *Scientific Reports*, vol. 13, 2023. DOI: 10.1038/s41598-023-30987-0.
2. V. K. Kavitha and S. Murugesan, "An Effective Book Recommendation System Using Weighted Alternating Least Square (WALS) Approach," *International Journal of Advanced Computer Science and Applications*, vol. 15, no. 4, 2024. DOI: 10.14569/IJACSA.2024.0150463.
3. K. Mankar, S. Pawar, H. Agarwal, T. Sangale, and S. Kulkarni, "Web-Based Book Recommendation System Using Collaborative Filtering," *2023 IEEE International Conference on Emerging Smart Computing and Informatics (ESCI)*, 2023. DOI: 10.1109/ESCI56872.2023.10099750.
4. Z. Wang and Y. Wang, "Digital Library Book Recommendation System Based on Tag Mining," *Journal of Artificial Intelligence Research*, vol. 1, no. 1, pp. 10–16, 2024.
5. S. Malakul and P. Songmuang, "A Book Recommender System for Enhancing Reading Engagement: A Systematic Review," *Discover Artificial Intelligence*, 2026.
6. A. Bhajantri *et al.*, "Personalized Book Recommendations: A Hybrid Approach Leveraging Collaborative Filtering, Association Rule Mining, and Content-Based Filtering," *EAI Endorsed Transactions on Internet of Things*, vol. 10, 2024. DOI: 10.4108/eetiot.6996.
7. Y. Tian, B. Zheng, Y. Wang, Y. Zhang, and W. Qi, "College Library Personalized Recommendation System Based on Hybrid Recommendation Algorithm," *Procedia CIRP*, vol. 83, pp. 490–494, 2019. DOI: 10.1016/j.procir.2019.04.126.
8. A. Vats, Y. Agrawal, and N. Tyagi, "A Hybrid Book Recommendation System Using Collaborative Filtering and Content-Based Filtering with Neural Embeddings," *2025*

IEEE 7th International Conference on Computing, Communication and Automation (ICCCA), 2025. DOI: 10.1109/ICCCA66364.2025.11325340.

9. M. S. Pera and Y.-K. Ng, "With a Little Help from My Friends: Generating Personalized Book Recommendations Using Data Extracted from a Social Website," *2011 IEEE/WIC/ACM International Conference on Web Intelligence and Intelligent Agent Technology*, 2011. DOI: 10.1109/WI-IAT.2011.9.
10. P. C. Vaz, D. M. de Matos, B. Martins, and P. Calado, "Improving an Hybrid Literary Book Recommendation System through Author Ranking," 2012.
11. G. Adomavicius and A. Tuzhilin, "Toward the Next Generation of Recommender Systems: A Survey of the State-of-the-Art and Possible Extensions," *IEEE Transactions on Knowledge and Data Engineering*, vol. 17, no. 6, pp. 734–749, Jun. 2005.
12. Y. Koren, R. Bell, and C. Volinsky, "Matrix Factorization Techniques for Recommender Systems," *Computer*, vol. 42, no. 8, pp. 30–37, Aug. 2009.
13. Y. Koren, "Factorization Meets the Neighborhood: A Multifaceted Collaborative Filtering Model," in *Proc. 14th ACM SIGKDD Int. Conf. Knowledge Discovery and Data Mining (KDD)*, 2008, pp. 426–434.
14. X. He, L. Liao, H. Zhang, L. Nie, X. Hu, and T.-S. Chua, "Neural Collaborative Filtering," in *Proc. 26th Int. Conf. World Wide Web (WWW)*, 2017, pp. 173–182.
15. Y. Hu, Y. Koren, and C. Volinsky, "Collaborative Filtering for Implicit Feedback Datasets," in *Proc. IEEE Int. Conf. Data Mining (ICDM)*, 2008, pp. 263–272.
16. X. Su and T. M. Khoshgoftaar, "A Survey of Collaborative Filtering Techniques," *Advances in Artificial Intelligence*, vol. 2009, Article ID 421425, 2009.
17. M. Balabanović and Y. Shoham, "Fab: Content-Based, Collaborative Recommendation," *Communications of the ACM*, vol. 40, no. 3, pp. 66–72, Mar. 1997.

18. R. Burke, “Hybrid Recommender Systems: Survey and Experiments,” *User Modeling and User-Adapted Interaction*, vol. 12, nos. 4–5, pp. 331–370, 2002.
19. P. Cremonesi, Y. Koren, and R. Turrin, “Performance of Recommender Algorithms on Top-N Recommendation Tasks,” in *Proc. 4th ACM Conference on Recommender Systems (RecSys)*, 2010, pp. 39–46.
20. H. Steck, “Training and Testing of Recommender Systems on Data Missing Not at Random,” in *Proc. 16th ACM SIGKDD Int. Conf. Knowledge Discovery and Data Mining (KDD)*, 2010, pp. 713–722.
21. S. Rendle, C. Freudenthaler, Z. Gantner, and L. Schmidt-Thieme, “BPR: Bayesian Personalized Ranking from Implicit Feedback,” in *Proc. 25th Conf. Uncertainty in Artificial Intelligence (UAI)*, 2009, pp. 452–461.
22. S. Rendle, “Factorization Machines,” in *Proc. IEEE Int. Conf. Data Mining (ICDM)*, 2010, pp. 995–1000.
23. E. Çano and M. Morisio, “Hybrid Recommender Systems: A Systematic Literature Review,” *Intelligent Data Analysis*, vol. 23, no. 6, pp. 1487–1524, 2019.
24. D. Jannach, P. Resnick, A. Tuzhilin, and M. Zanker, “Recommender Systems—Beyond Matrix Completion,” *Communications of the ACM*, vol. 59, no. 11, pp. 94–102, 2016.
25. R. Mehta, S. Mishra, and S. Saha, “Non-Negative Matrix Factorization in Recommender Models: Concept, Survey, and Future Direction,” *IEEE Access*, vol. 13, pp. 192492–192517, 2025.
26. E. Hasan, M. Rahman, C. Ding, J. X. Huang, and S. Raza, “Review-Based Recommender Systems: A Survey of Approaches, Challenges and Future Perspectives,” *ACM Computing Surveys*, vol. 58, no. 1, 2025.

27. Y. Shi, M. Larson, and A. Hanjalic, “Collaborative Filtering Beyond the User–Item Matrix: A Survey of the State of the Art and Future Challenges,” *ACM Computing Surveys*, vol. 47, no. 1, Article 3, 2014.
28. J. Konstan and J. Riedl, “Recommender Systems: From Algorithms to User Experience,” *User Modeling and User-Adapted Interaction*, vol. 22, nos. 1–2, pp. 101–123, 2012.
29. G. Linden, B. Smith, and J. York, “Amazon.com Recommendations: Item-to-Item Collaborative Filtering,” *IEEE Internet Computing*, vol. 7, no. 1, pp. 76–80, Jan.–Feb. 2003.
30. D. Goldberg, D. Nichols, B. M. Oki, and D. Terry, “Using Collaborative Filtering to Weave an Information Tapestry,” *Communications of the ACM*, vol. 35, no. 12, pp. 61–70, Dec. 1992.

11. PLAGARISM REPORT

