

root@centos7:/etc/httpd/conf.d

```
[root@centos7 conf.d]# systemctl status httpd
● httpd.service - The Apache HTTP Server
   Loaded: loaded (/usr/lib/systemd/system/httpd.service; disabled; vendor preset: disabled)
   Active: active (running) since Вт 2022-03-28 21:08:23 MSK; 2h 53min ago
     Docs: man:httpd(8)
           man:apachectl(8)
  Process: 2660 ExecReload=/usr/sbin/httpd $OPTIONS -k graceful (code=exited, status=0/SUCCESS)
 Main PID: 2428 (httpd)
    Status: "Total requests: 0; Current requests/sec: 0; Current traffic:  0 B/sec"
   CGroup: /system.slice/httpd.service
           └─2428 /usr/sbin/httpd -DFOREGROUND
             └─2661 /usr/sbin/httpd -DFOREGROUND
               └─2662 /usr/sbin/httpd -DFOREGROUND
                 └─2663 /usr/sbin/httpd -DFOREGROUND
                   └─2664 /usr/sbin/httpd -DFOREGROUND
                     └─2665 /usr/sbin/httpd -DFOREGROUND

MAR 28 21:08:23 centos7 systemd[1]: Starting The Apache HTTP Server...
MAR 28 21:08:23 centos7 httpd[2428]: AH00558: httpd: Could not reliably determine the server's fully qualified domain name, using fe80::dbcc:294d:84d1:c664. Set the 'ServerName' directive glob...ss this message
MAR 28 21:08:23 centos7 systemd[1]: Started The Apache HTTP Server.
MAR 28 22:17:34 centos7 systemd[1]: Reloading The Apache HTTP Server.
MAR 28 22:17:34 centos7 httpd[2660]: AH00112: Warning: DocumentRoot [/var/www/html1] does not exist
MAR 28 22:17:34 centos7 httpd[2660]: AH00112: Warning: DocumentRoot [/var/www/html2] does not exist
MAR 28 22:17:34 centos7 httpd[2660]: AH00558: httpd: Could not reliably determine the server's fully qualified domain name, using fe80::dbcc:294d:84d1:c664. Set the 'ServerName' directive glob...ss this message
MAR 28 22:17:34 centos7 systemd[1]: Reloaded The Apache HTTP Server.
Hint: Some lines were ellipsized, use -l to show in full.
[root@centos7 conf.d]# systemctl status nginx
● nginx.service - The nginx HTTP and reverse proxy server
   Loaded: loaded (/usr/lib/systemd/system/nginx.service; enabled; vendor preset: disabled)
   Active: active (running) since Вт 2022-03-28 19:59:33 MSK; 4h 2min ago
  Process: 2617 ExecReload=/usr/sbin/nginx -s reload (code=exited, status=0/SUCCESS)
 Main PID: 2058 (nginx)
   CGroup: /system.slice/nginx.service
           └─2058 nginx: master process /usr/sbin/nginx
             └─2618 nginx: worker process

MAR 28 19:59:33 centos7 systemd[1]: Starting The nginx HTTP and reverse proxy server...
MAR 28 19:59:33 centos7 nginx[2053]: nginx: the configuration file /etc/nginx/nginx.conf syntax is ok
MAR 28 19:59:33 centos7 nginx[2053]: nginx: configuration file /etc/nginx/nginx.conf test is successful
MAR 28 19:59:33 centos7 systemd[1]: Started The nginx HTTP and reverse proxy server.
MAR 28 21:59:32 centos7 systemd[1]: Reloading The nginx HTTP and reverse proxy server.
MAR 28 21:59:32 centos7 systemd[1]: Reloading The nginx HTTP and reverse proxy server.
MAR 28 22:08:55 centos7 systemd[1]: Reloading The nginx HTTP and reverse proxy server.
MAR 28 22:08:55 centos7 systemd[1]: Reloading The nginx HTTP and reverse proxy server.
[root@centos7 conf.d]#
```

root@centos7:/var/www/html2

```
root 400 0,0 0,0 0 0 ? S< 16:43 0:00 \ [xfs-data/dm-0]
root 401 0,0 0,0 0 0 ? S< 16:43 0:00 \ [xfs-conv/dm-0]
root 402 0,0 0,0 0 0 ? S< 16:43 0:00 \ [xfs-cil/dm-0]
root 403 0,0 0,0 0 0 ? S< 16:43 0:00 \ [xfs-reclaim/dm-]
root 404 0,0 0,0 0 0 ? S< 16:43 0:00 \ [xfs-log/dm-0]
root 405 0,0 0,0 0 0 ? S< 16:43 0:00 \ [xfs-eofblocks/d]
root 406 0,0 0,0 0 0 ? S 16:43 0:08 \ [xfsaild/dm-0]
root 714 0,0 0,0 0 0 ? S< 16:43 0:00 \ [xfs-buf/sda1]
root 716 0,0 0,0 0 0 ? S< 16:43 0:00 \ [xfs-data/sda1]
root 718 0,0 0,0 0 0 ? S< 16:43 0:00 \ [xfs-conv/sda1]
root 719 0,0 0,0 0 0 ? S< 16:43 0:00 \ [xfs-cil/sda1]
root 721 0,0 0,0 0 0 ? S< 16:43 0:00 \ [xfs-reclaim/sda]
root 723 0,0 0,0 0 0 ? S< 16:43 0:00 \ [xfs-log/sda1]
root 724 0,0 0,0 0 0 ? S< 16:43 0:00 \ [xfs-eofblocks/s]
root 725 0,0 0,0 0 0 ? S 16:43 0:00 \ [xfsaild/sda1]
root 2620 0,0 0,0 0 0 ? S 22:08 0:00 \ [kworker/u2:0]
root 2670 0,0 0,0 0 0 ? S 22:20 0:00 \ [kworker/0:0]
root 2684 0,0 0,0 0 0 ? S 22:30 0:00 \ [kworker/0:1]
root 2685 0,0 0,0 0 0 ? S 22:35 0:00 \ [kworker/0:2]
root 1 0,0 0,7 194116 7256 ? Ss 16:43 0:02 /usr/lib/systemd/systemd --switched-root --system --deserialize 22
root 484 0,0 0,2 37208 3004 ? Ss 16:43 0:01 /usr/lib/systemd/systemd-journald
root 505 0,0 0,4 127372 4104 ? Ss 16:43 0:00 /usr/sbin/lvmstat -f
root 515 0,0 0,5 48628 5144 ? Ss 16:43 0:00 /usr/lib/systemd/systemd-udev
root 763 0,0 0,0 55532 864 ? S<sl 16:43 0:00 /sbin/auditd
root 787 0,0 0,5 228276 5672 ? Ss 16:43 0:00 /usr/sbin/abrt-d -d -s
root 788 0,0 0,4 225980 4904 ? Ss 16:43 0:00 /usr/bin/abrt-watch-log -F BUG: WARNING: at WARNING: CPU: INFO: possible recursive locking detected ernel BUG at list_del corruption list_add corrup
dbus 792 0,0 0,2 66452 2596 ? Ssl 16:43 0:00 /usr/bin/dbus-daemon --system --address=systemd: --nofork --nopidfile --systemd-activation
chrony 801 0,0 0,1 117808 1860 ? S 16:43 0:00 /usr/sbin/chronyd
root 806 0,0 0,1 26384 1780 ? Ss 16:43 0:00 /usr/lib/systemd/systemd-logind
polkitd 807 0,0 1,3 613008 14012 ? Ssl 16:43 0:00 /usr/lib/polkit-1/polkitd --no-debug
root 828 0,0 0,1 126384 1664 ? Ss 16:43 0:00 /usr/sbin/crond -n
root 832 0,0 0,2 96572 2468 ? Ss 16:43 0:00 login -- root
root 1003 0,0 0,2 115540 2112 tty1 Ss+ 16:43 0:00 \ -bash
root 834 0,0 0,8 548856 9076 ? Ssl 16:43 0:01 /usr/sbin/NetworkManager --no-daemon
root 1516 0,0 0,5 102988 5540 ? S 18:21 0:00 \ /sbin/dhclient -d -q -sf /usr/libexec/nm-dhcp-helper -pf /var/run/dhclient-enp0s3.pid -lf /var/lib/NetworkManager/dhclient-70cb9ef4-3803-4c67-b7
root 1205 0,0 1,7 574288 17460 ? Ssl 16:43 0:05 /usr/bin/python2 -Es /usr/sbin/tuned -l -P
root 1206 0,0 0,4 112984 4328 ? Ss 16:43 0:00 /usr/sbin/sshd -D
root 2441 0,0 0,5 158976 6060 ? Ss 21:13 0:02 \ sshd: root@pts/0
root 2446 0,0 0,2 115556 2112 pts/0 Ss 21:13 0:00 \ -bash
root 2530 0,0 0,0 108072 360 pts/0 T 21:38 0:00 \ cat
root 2687 0,0 0,1 155584 1952 pts/0 R+ 22:38 0:00 \ ps auxf
root 1208 0,0 0,7 220892 7644 ? Ssl 16:43 0:03 /usr/sbin/rsyslogd -n
root 1435 0,0 0,2 89788 2204 ? Ss 16:43 0:00 /usr/libexec/postfix/master -w
postfix 1449 0,0 0,4 89960 4112 ? S 16:43 0:00 \ qmgr -l -t unix -u
postfix 2553 0,0 0,4 89892 4088 ? S 21:44 0:00 \ pickup -l -t unix -u
root 2058 0,0 0,2 39564 2412 ? Ss 19:59 0:00 nginx: master process /usr/sbin/nginx
nginx 2618 0,0 0,2 39812 2204 ? S 22:08 0:00 \ nginx: worker process
root 2428 0,0 0,5 230572 5364 ? Ss 21:08 0:00 /usr/sbin/httpd -DFOREGROUND
apache 2661 0,0 0,3 230572 3872 ? S 22:17 0:00 \ /usr/sbin/httpd -DFOREGROUND
apache 2662 0,0 0,3 230572 3872 ? S 22:17 0:00 \ /usr/sbin/httpd -DFOREGROUND
apache 2663 0,0 0,3 230572 3868 ? S 22:17 0:00 \ /usr/sbin/httpd -DFOREGROUND
apache 2664 0,0 0,3 230572 3876 ? S 22:17 0:00 \ /usr/sbin/httpd -DFOREGROUND
apache 2665 0,0 0,3 230572 3872 ? S 22:17 0:00 \ /usr/sbin/httpd -DFOREGROUND
```

[root@centos7 html2]#

`/etc/nginx/conf.d/default.conf`

```
upstream backend {
    server 127.0.0.1:8080 weight=2;
    server 127.0.0.1:8081;
    server 127.0.0.1:8082;
}

server {
    listen      80;
    listen      [::]:80;
    server_name _;
    root        /usr/share/nginx/html;

    include /etc/nginx/default.d/*.conf;

    location / {
        #try_files $uri $uri/ =404;
        proxy_pass http://backend;
        proxy_set_header Host $host;
        proxy_set_header X-Forwarded-For $proxy_add_x_forwarded_for;
        proxy_set_header X-Real-IP $remote_addr;
    }

    location ~ \.php$ {
        include fastcgi_params;
        root /var/www/html;

        fastcgi_pass unix:/run/php/php7.4-fpm.sock;
        #fastcgi_pass 127.0.0.1:9000;
    }

    error_page 404 /404.html;
    location = /404.html {
    }

    error_page 500 502 503 504 /50x.html;
    location = /50x.html {
    }
}
```

1 Поиск

2 Разверн

3 Выход

4 Hex

5 Перейти

6

7 Поиск

8 Исходный

9 Формат

10 Выход

Обзор

PutTY SSH Client

Вт, 29 марта 18:04

en

mc [root@centos7]:/etc/httpd/conf.d

1597/1597

100%

```
/etc/httpd/conf.d/welcome.conf
Require all granted
</Directory>

Alias /noindex.html /usr/share/httpd/noindex/index.html
Alias /noindex/css/bootstrap.min.css /usr/share/httpd/noindex/css/bootstrap.min.css
Alias /noindex/css/open-sans.css /usr/share/httpd/noindex/css/open-sans.css
Alias /images/apache_pb.gif /usr/share/httpd/noindex/images/apache_pb.gif
Alias /images/poweredby.png /usr/share/httpd/noindex/images/poweredby.png

<VirtualHost *:8080>
    #ServerName www.example.com

    ServerAdmin webmaster@localhost
    DocumentRoot /var/www/html

    ErrorLog /var/log/httpd/error.log
    CustomLog /var/log/httpd/access.log combined
</VirtualHost>

*****

Listen 8081
<VirtualHost *:8081>
    #ServerName www.example.com

    ServerAdmin webmaster@localhost
    DocumentRoot /var/www/html1

    ErrorLog /var/log/httpd/error1.log
    CustomLog /var/log/httpd/access1.log combined
</VirtualHost>

*****

Listen 8082
<VirtualHost *:8082>
    #ServerName www.example.com

    ServerAdmin webmaster@localhost
    DocumentRoot /var/www/html2

    ErrorLog /var/log/httpd/error2.log
    CustomLog /var/log/httpd/access2.log combined
</VirtualHost>

*****
```

1

2

3

4

5

6

7

8

9

10

Помощь

Разверн

Выход

Hex

Перейти

Поиск

Сходный

Формат

Выход

Обзор

Putty SSH Client

Вт, 29 марта 18:06

en

root@centos7:/etc/httpd/conf.d

```
[root@centos7 conf.d]# ss -ntlp
State      Recv-Q Send-Q                  Local Address:Port                  Peer Address:Port
LISTEN     0      128                *:80                                 *:*
users:((("nginx",pid=2618,fd=6),("nginx",pid=2058,fd=6))
LISTEN     0      128                *:22                                 *:*
users:((("sshd",pid=1206,fd=3))
LISTEN     0      100             127.0.0.1:25                        *:*
users:((("master",pid=1435,fd=13))
LISTEN     0      128                [::]:8080                           [::]:*
users:((("httpd",pid=2665,fd=4),("httpd",pid=2664,fd=4),("httpd",pid=2663,fd=4),("httpd",pid=2662,fd=4),("httpd",pid=2661,fd=4),("httpd",pid=2428,fd=4))
LISTEN     0      128                [::]:80                              [::]:*
users:((("nginx",pid=2618,fd=7),("nginx",pid=2058,fd=7))
LISTEN     0      128                [::]:8081                           [::]:*
users:((("httpd",pid=2665,fd=6),("httpd",pid=2664,fd=6),("httpd",pid=2663,fd=6),("httpd",pid=2662,fd=6),("httpd",pid=2661,fd=6),("httpd",pid=2428,fd=6))
LISTEN     0      128                [::]:8082                           [::]:*
users:((("httpd",pid=2665,fd=9),("httpd",pid=2664,fd=9),("httpd",pid=2663,fd=9),("httpd",pid=2662,fd=9),("httpd",pid=2661,fd=9),("httpd",pid=2428,fd=9))
LISTEN     0      128                [::]:22                              [::]:*
users:((("sshd",pid=1206,fd=4))
LISTEN     0      100             [::]:1:25                          [::]:*
users:((("master",pid=1435,fd=14))
[root@centos7 conf.d]#
```

```
[root@centos7 htm12]# mc
<h1> Welcome 8082 </h>

[root@centos7 conf.d]# curl localhost
<h1> Welcome 8080 </h>
[root@centos7 conf.d]# curl localhost
<h1> Welcome 8081 </h>
[root@centos7 conf.d]# curl localhost
<h1> Welcome 8082 </h>
[root@centos7 conf.d]# curl localhost
<h1> Welcome 8080 </h>
[root@centos7 conf.d]# curl localhost
<h1> Welcome 8080 </h>
[root@centos7 conf.d]# curl localhost
<h1> Welcome 8081 </h>
[root@centos7 conf.d]# curl localhost
<h1> Welcome 8082 </h>
[root@centos7 conf.d]# curl localhost
<h1> Welcome 8080 </h>
[root@centos7 conf.d]# curl localhost
<h1> Welcome 8080 </h>
[root@centos7 conf.d]# curl localhost
<h1> Welcome 8081 </h>
[root@centos7 conf.d]# curl localhost
<h1> Welcome 8082 </h>
[root@centos7 conf.d]# curl localhost
<h1> Welcome 8080 </h>
[root@centos7 conf.d]# curl localhost
<h1> Welcome 8080 </h>
[root@centos7 conf.d]#
```