ONE-PAGE BRIEF

Post-quantum cryptography review: bitbox02-firmware @ ae548ef4e40f

Client: BitBox (Shift Crypto) — public repository (passive review) · Source: github.com/BitBoxSwiss/bitbox02-firmware, commit `ae548ef4e40f` · Reviewed: 2026-10-29 05:28 UTC · Risk profile: Crypto exchange, custodian or wallet

POST-QUANTUM MATURITY
Level 0 of 4
no post-quantum cryptography

FINDINGS
0 Critical **0** High **11** Medium
0 Low **6** Info

QUANTUM TIMELINE (MOSCA: X + Y − Z)
Key establishment: 10 + 5 − 8 = 7 → **too late**
Signatures: 10 + 5 − 8 = 7 → **too late**

Next step: Inventory where classical public-key cryptography protects long-lived data and keys, and choose the first migration: usually a hybrid TLS key exchange and wrapped keys.

WHAT MATTERS MOST

Medium QSI-2026-06365 **Transaction signing for 3 chain(s) relies on elliptic-curve signatures** confirmed by the analyst
What to do: Follow each chain's post-quantum roadmap, avoid public-key reuse, and keep signers ready to add post-quantum signature schemes as chains...

Medium QSI-2026-06356 **Quantum-vulnerable ECDSA: firmware and boot verification (root of trust) (3 file(s))** confirmed by the analyst
What to do: Plan a hybrid firmware signature (the classical one plus ML-DSA or SLH-DSA, both required) and the path to ship the new keys in a...

Medium QSI-2026-06362 **Quantum-vulnerable X25519: key wrapping and data encryption at rest (1 file(s))** confirmed by the analyst
What to do: Wrap keys with ML-KEM or a hybrid KEM (X25519 + ML-KEM-768) and re-wrap the stored keys; data that may already have been copied needs its...

Medium QSI-2026-06358 **Quantum-vulnerable X25519: channel key exchange (TLS, Noise, handshakes) (3 file(s))** confirmed by the analyst
What to do: Move the handshake to a hybrid key exchange (X25519MLKEM768 in TLS 1.3; a hybrid KEM in Noise-based protocols).

7 more in the full report.

WHAT THE QUANTUM-VULNERABLE CRYPTOGRAPHY PROTECTS

Role	Algorithms	What to do
Medium firmware and boot verification (root of trust)	ECDSA	Plan a hybrid firmware signature (the classical one plus ML-DSA or SLH-DSA, both required) and the path to...
Medium key wrapping and data encryption at rest	X25519	Wrap keys with ML-KEM or a hybrid KEM (X25519 + ML-KEM-768) and re-wrap the stored keys; data that may...
Medium channel key exchange (TLS, Noise, handshakes)	X25519	Move the handshake to a hybrid key exchange (X25519MLKEM768 in TLS 1.3; a hybrid KEM in Noise-based protocols)
Medium transaction and message signing	ECDSA, Schnorr (BIP-340), Ed25519	Follow each chain's post-quantum roadmap, avoid public-key reuse, and keep signers ready to add post-quantum...

KNOWN VULNERABLE COMPONENTS

Advisories for the versions in use: 4; unlikely to apply to this build: 4 (a Cargo feature that is off, affected functions not named in the code, or a platform that is not built); to review: 0.

Analyst review: 12 confirmed, 5 not applicable, 0 dismissed as false positives. (QSI review, 2026-10-28)

Static review of source code and manifests; files analysed: 721. No requests were sent to the owner's systems.

Full report, content SHA-256: `e44d8889bab3be9b82e9c666ede30732ce3cfc1ff7d9af3493fdcce64df8195c`

Full report signature (report.sig.json): Ed25519 key, SHA-256 fingerprint `5b3cf9c9bd0fa54447e2b5dfa7a6bab569bd0c666fa46949599e5c348d17083e`. bundle.sig.json lists the SHA-256 of every file in this bundle and is signed too; verify-bundle checks it offline.

Preliminary findings need confirmation in the code; the full report gives the evidence, the limits of each check and how to re-test.