ONE-PAGE BRIEF

Post-quantum cryptography review: jade @ a59d14c2b397

Client: Blockstream (Jade) — public repository (passive review) · Source: github.com/Blockstream/Jade, commit `a59d14c2b397` · Reviewed: 2026-10-28 21:17 UTC · Risk profile: Crypto exchange, custodian or wallet

POST-QUANTUM MATURITY

Level 0 of 4

no post-quantum cryptography

FINDINGS

0 Critical **0** High **7** Medium **0** Low **1** Info

QUANTUM TIMELINE (MOSCA: X + Y − Z)

Key establishment: 10 + 5 − 8 = 7 → **too late**

Signatures: 10 + 5 − 8 = 7 → **too late**

Next step: Inventory where classical public-key cryptography protects long-lived data and keys, and choose the first migration: usually a hybrid TLS key exchange and wrapped keys.

WHAT MATTERS MOST

Medium QSI-2026-06120	**Quantum-vulnerable RSA key (4096-bit) in components/libwally-core/upstream/SECURITY.md** What to do: Inventory and plan migration to ML-DSA (FIPS 204) or SLH-DSA (FIPS 205), in a hybrid/ composite form where the ecosystem supports it..
Medium QSI-2026-06121	**Quantum-vulnerable ECDSA: transaction and message signing (40 file(s))** preliminary What to do: Follow each chain's post-quantum roadmap, avoid public-key reuse, and keep signers ready to add post-quantum signature schemes as chains...
Medium QSI-2026-06123	**Quantum-vulnerable Schnorr (BIP-340): transaction and message signing (6 file(s))** preliminary What to do: Follow each chain's post-quantum roadmap, avoid public-key reuse, and keep signers ready to add post-quantum signature schemes as chains...
Medium QSI-2026-06122	**Quantum-vulnerable ECDSA: role not determined (2 file(s))** preliminary What to do: Classify each usage, record data lifetimes, and plan migration to ML-DSA (FIPS 204) or SLH-DSA (FIPS 205), in a hybrid/composite form...

3 more in the full report.

WHAT THE QUANTUM-VULNERABLE CRYPTOGRAPHY PROTECTS

Role	Algorithms	What to do
Medium transaction and message signing	ECDSA, Schnorr (BIP-340)	Follow each chain's post-quantum roadmap, avoid public-key reuse, and keep signers ready to add post-quantum...
Medium authentication and identity (certificates, tokens, device attestation)	ECDSA	Keep credentials short-lived and plan ML-DSA certificates, tokens and keys as the ecosystem supports them
Medium role not determined	ECDSA, ECDH, Schnorr (BIP-340)	Classify each usage, record data lifetimes, and plan migration to ML-DSA (FIPS 204) or SLH-DSA (FIPS 205)...

Static review of source code and manifests; files analysed: 568. No requests were sent to the owner's systems.

Full report, content SHA-256: `7942ddb55815a12070642368e6e3ea6fc9c02c06f4bad7fe1df427ff83cae3e3`

Full report signature (report.sig.json): Ed25519 key, SHA-256 fingerprint `5b3cf9c9bd0fa54447e2b5dfa7a6bab569bd0c666fa46949599e5c348d17083e`. bundle.sig.json lists the SHA-256 of every file in this bundle and is signed too; verify-bundle checks it offline.

Preliminary findings need confirmation in the code; the full report gives the evidence, the limits of each check and how to re-test.