ONE-PAGE BRIEF

Post-quantum cryptography review: embit @ 2b375a33bd89

Client: embit (SeedSigner, Krux) — public repository (passive review) · Source: github.com/diybitcoinhardware/embit, commit 2b375a33bd89 · Reviewed: 2026-10-29 20:14 UTC · Risk profile: Crypto exchange, custodian or wallet

POST-QUANTUM MATURITY
Level 0 of 4
no post-quantum cryptography

FINDINGS
0 Critical **0** High **4** Medium
0 Low **1** Info

QUANTUM TIMELINE (MOSCA: X + Y − Z)
Signatures: 10 + 5 − 8 = 7 → **too late**

Next step: Inventory where classical public-key cryptography protects long-lived data and keys, and choose the first migration: usually a hybrid TLS key exchange and wrapped keys.

WHAT MATTERS MOST

Medium QSI-2026-06825 **Quantum-vulnerable ECDSA: transaction and message signing (31 file(s))** confirmed by the analyst
What to do: Follow each chain's post-quantum roadmap, avoid public-key reuse, and keep signers ready to add post-quantum signature schemes as chains...

Medium QSI-2026-06826 **Quantum-vulnerable Schnorr (BIP-340): transaction and message signing (6 file(s))** confirmed by the analyst
What to do: Follow each chain's post-quantum roadmap, avoid public-key reuse, and keep signers ready to add post-quantum signature schemes as chains...

Medium QSI-2026-06828 **Quantum-vulnerable Pedersen commitment: threshold signing and MPC protocols (4 file(s))** confirmed by the analyst
What to do: Track post-quantum threshold signatures (NIST IR 8214C) and keep the protocol layer ready to swap the signature scheme; record which keys...

Medium QSI-2026-06827 **Quantum-vulnerable ECDSA: role not determined (4 file(s))** confirmed by the analyst
What to do: Classify each usage, record data lifetimes, and plan migration to ML-DSA (FIPS 204) or SLH-DSA (FIPS 205), in a hybrid/composite form...

WHAT THE QUANTUM-VULNERABLE CRYPTOGRAPHY PROTECTS

Role	Algorithms	What to do
Medium threshold signing and MPC protocols	Pedersen commitment	Track post-quantum threshold signatures (NIST IR 8214C) and keep the protocol layer ready to swap the...
Medium transaction and message signing	ECDSA, Schnorr (BIP-340)	Follow each chain's post-quantum roadmap, avoid public-key reuse, and keep signers ready to add post-quantum...
Medium role not determined	ECDSA	Classify each usage, record data lifetimes, and plan migration to ML-DSA (FIPS 204) or SLH-DSA (FIPS 205)...

Analyst review: 4 confirmed, 1 not applicable, 1 dismissed as false positives. (QSI review, 2026-10-29)

Static review of source code and manifests; files analysed: 142. No requests were sent to the owner's systems.

Full report, content SHA-256: `14c757ffe03c6a7fe308eb8fae17fa1c4950de88a24495fe5684d5853937e12e`

Full report signature (report.sig.json): Ed25519 key, SHA-256 fingerprint `5b3cf9c9bd0fa54447e2b5dfa7a6bab569bd0c666fa46949599e5c348d17083e`. bundle.sig.json lists the SHA-256 of every file in this bundle and is signed too; verify-bundle checks it offline.

Preliminary findings need confirmation in the code; the full report gives the evidence, the limits of each check and how to re-test.