QUANTUM SECURITY INTELLIGENCE

Security & Post-Quantum Readiness Audit Report

coinbase-cb-mpc-en @ 0b716706f998 · Coinbase — public repository (passive review)

Organization	QSI
Report date	2026-11-06 13:12 UTC
Report version	1
Audit run	02ce0659-1889-4ed5-a086-f177ea4dd951 · Document audit · 2026-11-06 13:12 UTC
Analyzer engine	qsi-engine 1.3.0
Risk profile	Crypto exchange, custodian or wallet
Content SHA-256	`2a966078eafc0c75aa33ede65be2e88b49931bcd3069f62145418b9799d8281d`
Signature key (Ed25519, SHA-256 fingerprint; the signature is the separate file report.sig.json)	`5b3cf9c9bd0fa54447e2b5dfa7a6bab569bd0c666fa46949599e5c348d17083e`

Contents

1. Executive summary
2. Scope and boundaries
3. Methodology
4. Assets examined and not examined
5. Architecture overview
6. Overall security posture
7. Findings by severity
8. Detailed findings
9. Evidence
10. Post-quantum assessment
11. Limitations and assumptions
12. Remediation plan
13. Priorities for 30, 60 and 90 days
14. Verification after remediation
15. Tools used
16. Sources and normative documents
17. Appendices

This report presents automated and documented analysis results for the stated scope. It is not a legal opinion, a certification or an attestation of compliance with any standard.

Executive summary

11	0	0	11	0
Findings in total	Critical	High	Medium	Low

Classification	Count
Confirmed technical vulnerability	0
Known vulnerable component	0
Confirmed configuration error	0
Potential cryptographic risk	0
Long-term post-quantum risk	11
Improvement recommendation	0
Insufficient data	0

Top 5

ID	Severity	Detailed findings	Priority score
QSI-2026-17972	Medium	Quantum-vulnerable ECDH: key wrapping and data encryption at rest (5 file(s)) confirmed by the analyst	43.4
QSI-2026-17967	Medium	Quantum-vulnerable Paillier: threshold signing and MPC protocols (15 file(s)) confirmed by the analyst	41.8
QSI-2026-17970	Medium	Quantum-vulnerable Threshold ECDSA: threshold signing and MPC protocols (13 file(s)) confirmed by the analyst	41.8
QSI-2026-17971	Medium	Quantum-vulnerable Ed25519: threshold signing and MPC protocols (9 file(s)) confirmed by the analyst	41.8
QSI-2026-17973	Medium	Quantum-vulnerable Pedersen commitment: threshold signing and MPC protocols (4 file(s)) confirmed by the analyst	41.8

Mosca's inequality (x + y > z): x = 10, y = 5, z = 8 → migration would finish too late under this scenario. z is a planning assumption chosen per risk profile, not a prediction. A cryptographically relevant quantum computer is not publicly known to exist today.

Analyst review: 10 confirmed, 0 not applicable, 0 dismissed as false positives.

Post-quantum maturity: Level 1 of 4 — post-quantum code present, not wired. Next step: Wire the existing post-quantum primitive into a critical path (key wrapping or the channel) behind a hybrid construction, and test interoperability.

Scope and boundaries

Mode: Document audit

Repository: https://github.com/coinbase/cb-mpc @ 0b716706f998633912ee2be9b9bf8909aed66088 — evidence links open the lines at this commit.

Supplied inputs

174 files, 1453052 bytes in total, 0 redaction(s); the per-file SHA-256 list is in appendix C.

Methodology

The audit was performed by the QSI engine 1.3.0. Each analyzer emits facts (rule, parameters, evidence); finding texts are generated from the rule catalog. Methodology sources are listed under "Sources and normative documents".

Prioritization uses an explainable weighted model (severity, exploitability, exposure, confidentiality/integrity/availability impact weighted by the "Crypto exchange, custodian or wallet" profile, asset criticality, urgency, ease of remediation) with a confidence multiplier. CVSS v3.1 is applied only to technical vulnerabilities with a defined vector. Long-term quantum risks use Mosca's inequality; their severity is capped at Medium and they are never presented as exploitable vulnerabilities.

Finding classes: confirmed technical vulnerability; known vulnerable component (a dependency version named in an advisory; whether the affected code is reachable is assessed separately, and a component confirmed by review becomes a vulnerability); confirmed configuration error; potential cryptographic risk; long-term post-quantum risk; improvement recommendation; insufficient data. Heuristic findings are marked preliminary; analyst decisions are shown next to the findings.

Coverage of checks

Area	Status	Count	Examples
source_code	checked	174	include-internal/cbmpc/internal/core/convert.h: 307 lines scanned with 16 rule patterns and 266 registry patterns; include-internal/cbmpc/internal/core/extended_uint.h: 54 lines scanned with 16 rule patterns and 266 registry patterns; include-internal/cbmpc/internal/core/log.h: 124 lines scanned with 16 rule patterns and 266 registry patterns
entropy	checked	1	random-number generation: 174 code files read with 24 macro definitions from the tree; 0 ineffective guard(s), 0 weak random-bytes provider(s), 0 weak key-generation site(s)

Long lists are grouped here; the full per-file list is in the JSON report, signed with the same key.

Assets examined and not examined

Supplied inputs: 175 (input files: C)

Architecture overview

Static review of the source tree coinbase-cb-mpc-en at 0b716706f998633912ee2be9b9bf8909aed66088. 174 files analysed; of 181 files, 0 are test, fuzzing, benchmark or example code and were left out, 7 are not read by any analyzer, 0 exceed the per-file limit and 0 did not fit the total limit. The review was restricted to 4 path(s) of the repository: CMakeLists.txt, include, include-internal, src; 962 files outside them were not read. Files no analyzer reads include: CMakeLists.txt, src/cbmpc/api/CMakeLists.txt, src/cbmpc/c_api/CMakeLists.txt, src/cbmpc/core/CMakeLists.txt, src/cbmpc/crypto/CMakeLists.txt. No requests were sent to the owner's systems.

Overall security posture


100
Indicative posture index (0–100)

86.1%
Quantum-vulnerable share of inventory

108
Cryptographic inventory

Derived from findings in scope (confirmed and potential issues weighted by severity). Indicative only; not comparable across differently scoped audits.

Findings by severity



ID	Detailed findings	Classification	Severity	Confidence
QSI-2026-17972	Quantum-vulnerable ECDH: key wrapping and data encryption at rest (5 file(s))	Long-term post-quantum risk	Medium	Medium
QSI-2026-17967	Quantum-vulnerable Paillier: threshold signing and MPC protocols (15 file(s))	Long-term post-quantum risk	Medium	Medium
QSI-2026-17970	Quantum-vulnerable Threshold ECDSA: threshold signing and MPC protocols (13 file(s))	Long-term post-quantum risk	Medium	Medium
QSI-2026-17971	Quantum-vulnerable Ed25519: threshold signing and MPC protocols (9 file(s))	Long-term post-quantum risk	Medium	Medium
QSI-2026-17973	Quantum-vulnerable Pedersen commitment: threshold signing and MPC protocols (4 file(s))	Long-term post-quantum risk	Medium	Medium
QSI-2026-17974	Quantum-vulnerable ECDSA: threshold signing and MPC protocols (3 file(s))	Long-term post-quantum risk	Medium	Medium
QSI-2026-17976	Quantum-vulnerable ECDSA: transaction and message signing (1 file(s))	Long-term post-quantum risk	Medium	Medium
QSI-2026-17968	Quantum-vulnerable ECDSA: role not determined (6 file(s))	Long-term post-quantum risk	Medium	Medium
QSI-2026-17975	Quantum-vulnerable Ed25519: role not determined (3 file(s))	Long-term post-quantum risk	Medium	Medium
QSI-2026-17977	Quantum-vulnerable RSA: role not determined (1 file(s))	Long-term post-quantum risk	Medium	Medium
QSI-2026-17969	Quantum-vulnerable Schnorr (BIP-340): role not determined (2 file(s))	Long-term post-quantum risk	Medium	Medium, preliminary

Detailed findings

QSI-2026-17972 · CODE-QV-ASYMMETRIC

Medium

Quantum-vulnerable ECDH: key wrapping and data encryption at rest (5 file(s))

Long-term post-quantum risk | Confidence: Medium

> **Analyst review (QSI review, 2026-10-28): confirmed by the analyst.** The highest-urgency class in this repository, and it is not signing. The anchors are the publicly verifiable encryption paths — include-internal/cbmpc/internal/protocol/pve_base.h:213 calls prv_key.ecdh(...) and checks a 32-byte output, and src/cbmpc/api/{pve_base_pke,pve_batch_ac, pve_batch_single_recipient}.cpp plus pve_internal.h:154 all guard on "missing HSM ECIES ECDH callback". PVE is how key shares are encrypted to a recipient for backup and escrow, so the ciphertexts are stored. Harvest-now-decrypt-later applies in full: a copy taken today of an encrypted share set becomes plaintext once a CRQC exists, and no later migration undoes that. Unlike a signature scheme, this can be fixed today by wrapping the share under a hybrid KEM, which makes it the first thing to do rather than the hardest — and nearer than it looks, because this repository already implements ML-KEM-768 without the PVE path using it. See the DEP-NO-PQC-LIBRARY decision below.

5 reference(s) to ECDH across 5 file(s), e.g. include-internal/cbmpc/internal/protocol/pve_base.h:213. Role, judged from paths, function names and nearby code: key wrapping and data encryption at rest. Keys or data encrypted to these public keys are stored: anyone who copies them now decrypts them once a CRQC exists (harvest now, decrypt later).

Affected asset	source-code:ECDH:key_wrapping
Data source	include-internal/cbmpc/internal/protocol/pve_base.h
Detection method	Regular-expression matching of crypto API patterns; the role comes from words in paths, enclosing function names and the lines around the matches.
Analyzer	source_code 1.3.0 · 2026-11-06 13:12 UTC
Priority score	43.4 / 100 (Crypto exchange, custodian or wallet)
CVSS v3.1	not applicable
Mosca's inequality (x + y > z)	x=10.0, y=5.0, z=8.0 → migration would finish too late under this scenario

POTENTIAL IMPACT

Long-term risk depends on what the algorithm protects: signatures (authenticity until migration) or key exchange/encryption (retroactive decryption of recorded data).

REPRODUCTION STEPS

```
Open include-internal/cbmpc/internal/protocol/pve_base.h:213 and inspect the quoted lines; the evidence lists further files.
```

EVIDENCE

file_excerpt · include-internal/cbmpc/internal/protocol/pve_base.h · line 213 · SHA-256 02f0b0e2dc3db13d... · File 26dcc28fef1f2733...

```
212 |     if (rv = prv_key.ecdh(prv_key.ctx, prv_key.dk_handle, kem_ct, dh)) return rv;
213 |     if (dh.size() != 32) return coinbase::error(E_CRYPTO, "invalid ECDH output size");
214 |
```

file_excerpt · src/cbmpc/api/pve_base_pke.cpp · line 325 · SHA-256 7a1b1fff636e81f0... · File 5639e943156dbf5e...

```
324 |   if (const error_t rv = coinbase::api::detail::validate_mem_arg(label, "label")) return rv;
325 |   if (!cb.ecdh) return coinbase::error(E_BADARG, "missing HSM ECIES ECDH callback");
326 |
```

file_excerpt · src/cbmpc/api/pve_batch_ac.cpp · line 308 · SHA-256 8e385b276c3dbb90... · File 8b8be49db0d9daba...

```
307 |   if (const error_t rv = coinbase::api::detail::validate_mem_arg(label, "label")) return rv;
308 |   if (!cb.ecdh) return coinbase::error(E_BADARG, "missing HSM ECIES ECDH callback");
309 |
```

file_excerpt · src/cbmpc/api/pve_batch_single_recipient.cpp · line 225 · SHA-256 862c1cebf150e177... · File c5572970684fdeff...

```
224 |   if (const error_t rv = coinbase::api::detail::validate_mem_arg(label, "label")) return rv;
225 |   if (!cb.ecdh) return coinbase::error(E_BADARG, "missing HSM ECIES ECDH callback");
226 |
```

file_excerpt · src/cbmpc/api/pve_internal.h · line 154 · SHA-256 3fa55d0a81efe46a... · File 47bce2585e9a7bf7...

```
153 |   error_t decrypt(mem_t dk_handle, mem_t label, mem_t ct, buf_t& out_plain) const override {
154 |     if (!cb_.ecdh) return coinbase::error(E_BADARG, "missing HSM ECIES ECDH callback");
155 |     coinbase::mpc::pve_ecies_p256_hsm_dk_t dk;
```

LIMITATIONS OF THE CHECK

This is a forward-looking risk that depends on the arrival of a cryptographically relevant quantum computer (CRQC). No such computer is publicly known to exist today; the timeline is uncertain. It is not a present-day exploitable vulnerability. Heuristic pattern match on source text without data-flow analysis. The usage context (security-relevant or not) must be confirmed manually; treat as preliminary.

RECOMMENDATION

Wrap keys with ML-KEM or a hybrid KEM (X25519 + ML-KEM-768) and re-wrap the stored keys; data that may already have been copied needs its own assessment.

RETEST PROCEDURE

Re-run the inventory after refactoring.

P. W. Shor — Polynomial-Time Algorithms for Prime Factorization and Discrete Logarithms on a Quantum Computer (SIAM J. Comput., 1997); NIST IR 8547 — Transition to Post-Quantum Cryptography Standards; M. Mosca — Cybersecurity in an Era with Quantum Computers: Will We Be Ready? (IEEE Security & Privacy, 2018)

QSI-2026-17967 · CODE-QV-ASYMMETRIC

Medium

Quantum-vulnerable Paillier: threshold signing and MPC protocols (15 file(s))

Long-term post-quantum risk | Confidence: Medium

> **Analyst review (QSI review, 2026-10-28): confirmed by the analyst.** Correct, with a parameter worth quoting: include-internal/cbmpc/internal/crypto/base_paillier.h declares class paillier_t with static constexpr int bit_size = 2048, so the modulus is 2048 bits and Shor's algorithm faces exactly the problem it faces for RSA-2048. The evidence is real implementation rather than a name match — base_paillier.h, zk/zk_paillier.h's valid_paillier_t, and the key structures in protocol/ecdsa_2p.h and hd_keyset_ecdsa_2p.h, which each hold a crypto::paillier_t and its c_key. This is the row that a post-quantum *signature* standard does not help with: Paillier is the homomorphic encryption the two-party ECDSA protocol is built on,

> so replacing it is a protocol redesign, and NIST's 2024 standards (ML-DSA, SLH-DSA) are single-signer schemes that do not offer a drop-in replacement.

352 reference(s) to Paillier across 15 file(s), e.g. include-internal/cbmpc/internal/crypto/base_bn.h:46. Role, judged from paths, function names and nearby code: threshold signing and MPC protocols. Paillier, Pedersen commitments and the discrete-logarithm proofs inside threshold ECDSA and EdDSA protocols all fall to Shor's algorithm; a post-quantum threshold scheme is a protocol change, not a parameter change.

Affected asset	source-code:Paillier:threshold_mpc
Data source	include-internal/cbmpc/internal/crypto/base_bn.h
Detection method	Regular-expression matching of crypto API patterns; the role comes from words in paths, enclosing function names and the lines around the matches.
Analyzer	source_code 1.3.0 · 2026-11-06 13:12 UTC
Priority score	41.8 / 100 (Crypto exchange, custodian or wallet)
CVSS v3.1	not applicable
Mosca's inequality (x + y > z)	x=10.0, y=5.0, z=8.0 → migration would finish too late under this scenario

POTENTIAL IMPACT

Long-term risk depends on what the algorithm protects: signatures (authenticity until migration) or key exchange/encryption (retroactive decryption of recorded data).

REPRODUCTION STEPS

```
Open include-internal/cbmpc/internal/crypto/base_bn.h:46 and inspect the quoted lines; the evidence lists further files.
```

EVIDENCE

file_excerpt · include-internal/cbmpc/internal/crypto/base_bn.h · line 46 · SHA-256 5b3069a225ca12ea… · File 2ab03b1f64160824…

```
45 | class mod_t;
46 | class paillier_t;
47 | class ecdsa_signature_t;
```

file_excerpt · include-internal/cbmpc/internal/crypto/base_bn.h · line 57 · SHA-256 ee1680c40ae2e30e… · File 2ab03b1f64160824…

```
56 |   friend class crypto::ecc_point_t;
57 |   friend class crypto::paillier_t;
58 |   friend class crypto::ecdsa_signature_t;
```

file_excerpt · include-internal/cbmpc/internal/crypto/base_paillier.h · line 8 · SHA-256 5e4a09314f2cd39e… · File 635074e16e9ac9d0…

```
 7 |
 8 | class paillier_t {
 9 |  public:
```

file_excerpt · include-internal/cbmpc/internal/crypto/base_paillier.h · line 29 · SHA-256 5f18c9d760a32724… · File 635074e16e9ac9d0…

```
28 |   static constexpr int bit_size = 2048;
29 |   paillier_t() : has_private(false) {}
30 |   ~paillier_t() {}
```

file_excerpt · include-internal/cbmpc/internal/crypto/base_paillier.h · line 30 · SHA-256 0cb26e46930009ca… · File 635074e16e9ac9d0…

```
29 |   paillier_t() : has_private(false) {}
30 |   ~paillier_t() {}
31 |
```

file_excerpt · include-internal/cbmpc/internal/protocol/ecdsa_2p.h · line 18 · SHA-256 ca851b698b030d55… · File bb2d45c7091bcb2d…

```
17 |   bn_t c_key;
18 |   crypto::paillier_t paillier;
19 | };
```

file_excerpt · include-internal/cbmpc/internal/protocol/ecdsa_2p.h · line 66 · SHA-256 0986d849de59c959… · File bb2d45c7091bcb2d…

```
65 |  */
66 | struct paillier_gen_interactive_t {
67 |   paillier_gen_interactive_t(const crypto::mpc_pid_t& pid) : range(pid), equal(pid) {}
```

file_excerpt · include-internal/cbmpc/internal/protocol/ecdsa_2p.h · line 67 · SHA-256 220d61e7527123b6… · File bb2d45c7091bcb2d…

```
66 | struct paillier_gen_interactive_t {
67 |   paillier_gen_interactive_t(const crypto::mpc_pid_t& pid) : range(pid), equal(pid) {}
68 |
```

file_excerpt · include-internal/cbmpc/internal/protocol/hd_keyset_ecdsa_2p.h · line 11 · SHA-256 6626153477cce1ab… · File 98cef577118dc981…

```
10 |   hd_root_t root;
11 |   coinbase::crypto::paillier_t paillier;
12 |   bn_t c_key;
```

file_excerpt · include-internal/cbmpc/internal/zk/zk_paillier.h · line 9 · SHA-256 b73ec02d5359acd4… · File 5ad37919ff30625b…

```
 8 | struct valid_paillier_t {
 9 |   using param = paillier_non_interactive_param_t;
10 |
```

LIMITATIONS OF THE CHECK

This is a forward-looking risk that depends on the arrival of a cryptographically relevant quantum computer (CRQC). No such computer is publicly known to exist today; the timeline is uncertain. It is not a present-day exploitable vulnerability. Heuristic pattern match on source text without data-flow analysis. The usage context (security-relevant or not) must be confirmed manually; treat as preliminary.

RECOMMENDATION

Track post-quantum threshold signatures (NIST IR 8214C) and keep the protocol layer ready to swap the signature scheme; record which keys and shares must stay valid for how long.

RETEST PROCEDURE

Re-run the inventory after refactoring.

P. W. Shor — Polynomial-Time Algorithms for Prime Factorization and Discrete Logarithms on a Quantum Computer (SIAM J. Comput., 1997); NIST IR 8547 — Transition to Post-Quantum Cryptography Standards; M. Mosca — Cybersecurity in an Era with Quantum Computers: Will We Be Ready? (IEEE Security & Privacy, 2018)

QSI-2026-17970 · CODE-QV-ASYMMETRIC

Medium

Quantum-vulnerable Threshold ECDSA: threshold signing and MPC protocols (13 file(s))

Long-term post-quantum risk | Confidence: Medium

> **Analyst review (QSI review, 2026-10-28): confirmed by the analyst.** The claim is right — cb-mpc is a threshold ECDSA library and these 13 files are its protocol surface (api/ecdsa_2p.h, api/ecdsa_mp.h, internal/protocol/ecdsa_2p.h, ecdsa_mp.h, hd_keyset_ecdsa_2p.h) — but the cited evidence is weaker than the claim and a reader should know which is which. Most anchors are namespace declarations and their closing braces (namespace coinbase::api::ecdsa_2p, coinbase::mpc::ecdsampc), so the row follows from the library's purpose rather than from the quoted line. The substantive evidence for this class is in the Paillier and Pedersen rows above, which cite implementations. Confirmed on that basis, and the detector would serve better by anchoring on the protocol functions.

102 reference(s) to Threshold ECDSA across 13 file(s), e.g. include-internal/cbmpc/internal/protocol/ecdsa_2p.h:10. Role, judged from paths, function names and nearby code: threshold signing and MPC protocols. Paillier, Pedersen commitments and the discrete-logarithm proofs inside threshold ECDSA and EdDSA protocols all fall to Shor's algorithm; a post-quantum threshold scheme is a protocol change, not a parameter change.

Affected asset	source-code:Threshold ECDSA:threshold_mpc
Data source	include-internal/cbmpc/internal/protocol/ecdsa_2p.h
Detection method	Regular-expression matching of crypto API patterns; the role comes from words in paths, enclosing function names and the lines around the matches.
Analyzer	source_code 1.3.0 · 2026-11-06 13:12 UTC
Priority score	41.8 / 100 (Crypto exchange, custodian or wallet)
CVSS v3.1	not applicable
Mosca's inequality (x + y > z)	x=10.0, y=5.0, z=8.0 → migration would finish too late under this scenario

POTENTIAL IMPACT

Long-term risk depends on what the algorithm protects: signatures (authenticity until migration) or key exchange/encryption (retroactive decryption of recorded data).

REPRODUCTION STEPS

```
Open include-internal/cbmpc/internal/protocol/ecdsa_2p.h:10 and inspect the quoted lines; the evidence lists further files.
```

EVIDENCE

file_excerpt · include-internal/cbmpc/internal/protocol/ecdsa_2p.h · line 10 · SHA-256 4f07cdced92dd607… · File bb2d45c7091bcb2d…

```
 9 |
10 | namespace coinbase::mpc::ecdsa2pc {
11 |
```

file_excerpt · include-internal/cbmpc/internal/protocol/ecdsa_2p.h · line 122 · SHA-256 eb44feaab487c809… · File bb2d45c7091bcb2d…

```
  121 |
  122 | }  // namespace coinbase::mpc::ecdsa2pc
```

file_excerpt · include-internal/cbmpc/internal/protocol/ecdsa_mp.h · line 9 · SHA-256 867210bf6da87290… · File 09e920ca00569b73…

```
    8 |
    9 | namespace coinbase::mpc::ecdsampc {
   10 |
```

file_excerpt · include-internal/cbmpc/internal/protocol/ecdsa_mp.h · line 129 · SHA-256 1733ee2e1cb11d10… · File 09e920ca00569b73…

```
  128 |
  129 | }  // namespace coinbase::mpc::ecdsampc
```

file_excerpt · include-internal/cbmpc/internal/protocol/hd_keyset_ecdsa_2p.h · line 3 · SHA-256 219e8141fa597210… · File 98cef577118dc981…

```
    2 | #include <cbmpc/internal/protocol/ec_dkg.h>
    3 | #include <cbmpc/internal/protocol/ecdsa_2p.h>
    4 | #include <cbmpc/internal/protocol/hd_tree_bip32.h>
```

file_excerpt · include-internal/cbmpc/internal/protocol/hd_keyset_ecdsa_2p.h · line 29 · SHA-256 a5b11e730725f117… · File 98cef577118dc981…

```
   28 |                             const std::vector<bip32_path_t>& non_hardened_paths, buf_t&
sid,
   29 |                             std::vector<ecdsa2pc::key_t>& derived_keys);
   30 |
```

file_excerpt · include/cbmpc/api/ecdsa_2p.h · line 12 · SHA-256 a78ce67e456bbade… · File 105375859252d5a6…

```
   11 |
   12 | namespace coinbase::api::ecdsa_2p {
   13 |
```

file_excerpt · include/cbmpc/api/ecdsa_2p.h · line 88 · SHA-256 2a83480fd5d03e50… · File 105375859252d5a6…

```
   87 |
   88 | }  // namespace coinbase::api::ecdsa_2p
```

file_excerpt · include/cbmpc/api/ecdsa_mp.h · line 15 · SHA-256 eb3d5758c2755f9f… · File ab364b34f5c08cdc…

```
   14 | // requirements.
   15 | namespace coinbase::api::ecdsa_mp {
   16 |
```

file_excerpt · include/cbmpc/api/ecdsa_mp.h · line 134 · SHA-256 6496220e2d358496… · File ab364b34f5c08cdc…

```
  133 |
  134 | }  // namespace coinbase::api::ecdsa_mp
```

LIMITATIONS OF THE CHECK

This is a forward-looking risk that depends on the arrival of a cryptographically relevant quantum computer (CRQC). No such computer is publicly known to exist today; the timeline is uncertain. It is not a present-day exploitable vulnerability. Heuristic pattern match on source text without data-flow analysis. The usage context (security-relevant or not) must be confirmed manually; treat as preliminary.

RECOMMENDATION

Track post-quantum threshold signatures (NIST IR 8214C) and keep the protocol layer ready to swap the signature scheme; record which keys and shares must stay valid for how long.

RETEST PROCEDURE

Re-run the inventory after refactoring.

P. W. Shor — Polynomial-Time Algorithms for Prime Factorization and Discrete Logarithms on a Quantum Computer (SIAM J. Comput., 1997); NIST IR 8547 — Transition to Post-Quantum Cryptography Standards; M. Mosca — Cybersecurity in an Era with Quantum Computers: Will We Be Ready? (IEEE Security & Privacy, 2018)

QSI-2026-17971 · CODE-QV-ASYMMETRIC

Medium

Quantum-vulnerable Ed25519: threshold signing and MPC protocols (9 file(s))

Long-term post-quantum risk | Confidence: Medium

> **Analyst review (QSI review, 2026-10-28): confirmed by the analyst.** Threshold EdDSA, which the library implements alongside threshold ECDSA: api/eddsa_2p.h, internal/protocol/eddsa.h (which includes schnorr_mp.h), hd_keyset_eddsa_2p.h and src/cbmpc/api/eddsa2pc.cpp, where blob_to_key validates the key blob role. Same conclusion as threshold ECDSA and the same caveat about namespace anchors; the protocol is a Schnorr-style multiparty scheme over Ed25519, so Shor breaks both the signature and the discrete-log proofs around it.

38 reference(s) to Ed25519 across 9 file(s), e.g. include-internal/cbmpc/internal/protocol/eddsa.h:6. Role, judged from paths, function names and nearby code: threshold signing and MPC protocols. Paillier, Pedersen commitments and the discrete-logarithm proofs inside threshold ECDSA and EdDSA protocols all fall to Shor's algorithm; a post-quantum threshold scheme is a protocol change, not a parameter change.

Affected asset	source-code:Ed25519:threshold_mpc
Data source	include-internal/cbmpc/internal/protocol/eddsa.h
Detection method	Regular-expression matching of crypto API patterns; the role comes from words in paths, enclosing function names and the lines around the matches.
Analyzer	source_code 1.3.0 · 2026-11-06 13:12 UTC
Priority score	41.8 / 100 (Crypto exchange, custodian or wallet)
CVSS v3.1	not applicable
Mosca's inequality (x + y > z)	x=10.0, y=5.0, z=8.0 → migration would finish too late under this scenario

POTENTIAL IMPACT

Long-term risk depends on what the algorithm protects: signatures (authenticity until migration) or key exchange/encryption (retroactive decryption of recorded data).

REPRODUCTION STEPS

```
Open include-internal/cbmpc/internal/protocol/eddsa.h:6 and inspect the quoted lines; the evidence lists further files.
```

EVIDENCE

file_excerpt · include-internal/cbmpc/internal/protocol/eddsa.h · line 6 · SHA-256 3c84aa793ed1f429… · File 1bae54da49de50c0…

```
 5 | #include <cbmpc/internal/protocol/schnorr_mp.h>
 6 | namespace coinbase::mpc::eddsa2pc {
 7 |
```

file_excerpt · include-internal/cbmpc/internal/protocol/eddsa.h · line 14 · SHA-256 b312965fb62a137d… · File 1bae54da49de50c0…

```
13 |
14 | }  // namespace coinbase::mpc::eddsa2pc
15 |
```

file_excerpt · include-internal/cbmpc/internal/protocol/hd_keyset_eddsa_2p.h · line 26 · SHA-256 ef05e73154048d30… · File 0ec98767b365b0bc…

```
25 |                             const std::vector<bip32_path_t>& non_hardened_paths, buf_t&
sid,
26 |                             std::vector<eddsa2pc::key_t>& derived_keys);
27 |
```

file_excerpt · include/cbmpc/api/eddsa_2p.h · line 8 · SHA-256 c37e0dee9fd8cf51… · File 16ec1fa4dcb7e197…

```
 7 |
 8 | namespace coinbase::api::eddsa_2p {
 9 |
```

file_excerpt · include/cbmpc/api/eddsa_2p.h · line 79 · SHA-256 1870990aac8e55e0… · File 16ec1fa4dcb7e197…

```
78 |
79 | }  // namespace coinbase::api::eddsa_2p
```

file_excerpt · src/cbmpc/api/eddsa2pc.cpp · line 1 · SHA-256 0d8efb61e1de8ae3… · File 277a7491b190d4e1…

```
 1 | #include <cbmpc/api/eddsa_2p.h>
 2 | #include <cbmpc/internal/core/convert.h>
```

file_excerpt · src/cbmpc/api/eddsa2pc.cpp · line 8 · SHA-256 c37e0dee9fd8cf51… · File 277a7491b190d4e1…

```
 7 |
 8 | namespace coinbase::api::eddsa_2p {
 9 |
```

file_excerpt · src/cbmpc/api/eddsa2pc.cpp · line 29 · SHA-256 bebfad4c5352b665… · File 277a7491b190d4e1…

```
28 |
29 | static error_t blob_to_key(const key_blob_v1_t& blob, coinbase::mpc::eddsa2pc::key_t& key) {
30 |   if (blob.role > 1) return coinbase::error(E_FORMAT, "invalid key blob role");
```

file_excerpt · src/cbmpc/api/hd_keyset_eddsa_2p.cpp · line 23 · SHA-256 f5e7d1db58a72a54… · File db69a2795c6ad2b9…

```
22 | // Mirror of the `coinbase::api::eddsa_2p` key blob format (see `src/cbmpc/api/
eddsa2pc.cpp`).
23 | constexpr uint32_t eddsa2pc_key_blob_version_v1 = 1;
24 | struct eddsa2pc_key_blob_v1_t {
```

file_excerpt · src/cbmpc/api/hd_keyset_eddsa_2p.cpp · line 24 · SHA-256 b14eb05d04888ba3… · File db69a2795c6ad2b9…

```
23 | constexpr uint32_t eddsa2pc_key_blob_version_v1 = 1;
24 | struct eddsa2pc_key_blob_v1_t {
25 |   uint32_t version = eddsa2pc_key_blob_version_v1;
```

LIMITATIONS OF THE CHECK

This is a forward-looking risk that depends on the arrival of a cryptographically relevant quantum computer (CRQC). No such computer is publicly known to exist today; the timeline is uncertain. It is not a present-day exploitable vulnerability. Heuristic pattern match on source text without data-flow analysis. The usage context (security-relevant or not) must be confirmed manually; treat as preliminary.

RECOMMENDATION

Track post-quantum threshold signatures (NIST IR 8214C) and keep the protocol layer ready to swap the signature scheme; record which keys and shares must stay valid for how long.

RETEST PROCEDURE

Re-run the inventory after refactoring.

P. W. Shor — Polynomial-Time Algorithms for Prime Factorization and Discrete Logarithms on a Quantum Computer (SIAM J. Comput., 1997); NIST IR 8547 — Transition to Post-Quantum Cryptography Standards; M. Mosca — Cybersecurity in an Era with Quantum Computers: Will We Be Ready? (IEEE Security & Privacy, 2018)

QSI-2026-17973 · CODE-QV-ASYMMETRIC

Medium

Quantum-vulnerable Pedersen commitment: threshold signing and MPC protocols (4 file(s))

Long-term post-quantum risk | Confidence: Medium

> **Analyst review (QSI review, 2026-10-28): confirmed by the analyst.** Correct and anchored on real parameter generation, not a mention: src/cbmpc/zk/zk_pedersen.cpp constructs pedersen_commitment_params_t with primes generated via BN_generate_prime_ex (the comment names the OpenSSL function), zk_pedersen.h:13 exposes get() and check_safe_prime_subgroup, and both src/cbmpc/protocol/ecdsa_2p.cpp:28 and src/cbmpc/zk/zk_paillier.cpp:537 pull those parameters. Stated precisely, because the distinction decides how bad this is: breaking the discrete log costs a Pedersen commitment its *binding* property, not its hiding — the commitment is perfectly hiding, so no committed value is recoverable from it even with a CRQC. The exposure is forgeability inside the proofs, i.e. future protocol soundness, not retroactive disclosure.

21 reference(s) to Pedersen commitment across 4 file(s), e.g. include-internal/cbmpc/internal/zk/zk_pedersen.h:8. Role, judged from paths, function names and nearby code: threshold signing and MPC protocols. Paillier, Pedersen commitments and the discrete-logarithm proofs inside threshold ECDSA and EdDSA protocols all fall to Shor's algorithm; a post-quantum threshold scheme is a protocol change, not a parameter change.

Affected asset	source-code:Pedersen commitment:threshold_mpc
Data source	include-internal/cbmpc/internal/zk/zk_pedersen.h
Detection method	Regular-expression matching of crypto API patterns; the role comes from words in paths, enclosing function names and the lines around the matches.
Analyzer	source_code 1.3.0 · 2026-11-06 13:12 UTC
Priority score	41.8 / 100 (Crypto exchange, custodian or wallet)
CVSS v3.1	not applicable
Mosca's inequality (x + y > z)	x=10.0, y=5.0, z=8.0 → migration would finish too late under this scenario

POTENTIAL IMPACT

Long-term risk depends on what the algorithm protects: signatures (authenticity until migration) or key exchange/encryption (retroactive decryption of recorded data).

REPRODUCTION STEPS

```
Open include-internal/cbmpc/internal/zk/zk_pedersen.h:8 and inspect the quoted lines; the evidence
lists further files.
```

EVIDENCE

file_excerpt · include-internal/cbmpc/internal/zk/zk_pedersen.h · line 8 · SHA-256 90f6fa4e7aa38c51... · File 899fad68ffd0cc05...

```
  7 |
  8 | struct pedersen_commitment_params_t {
  9 |   mod_t p, p_tag;
```

file_excerpt · include-internal/cbmpc/internal/zk/zk_pedersen.h · line 13 · SHA-256 beb6763be217e297... · File 899fad68ffd0cc05...

```
 12 |
 13 |   static const pedersen_commitment_params_t& get();
 14 |   error_t check_safe_prime_subgroup(const bn_t& x) const;
```

file_excerpt · include-internal/cbmpc/internal/zk/zk_pedersen.h · line 17 · SHA-256 4a5620026d361a84... · File 899fad68ffd0cc05...

```
 16 |  private:
 17 |   pedersen_commitment_params_t();
 18 | };
```

file_excerpt · src/cbmpc/protocol/ecdsa_2p.cpp · line 28 · SHA-256 f6cd7432a9262739... · File 676da782f28e8371...

```
 27 |
 28 |   const zk::pedersen_commitment_params_t& params = zk::pedersen_commitment_params_t::get();
 29 |   const mod_t& p_tag = params.p_tag;
```

file_excerpt · src/cbmpc/zk/zk_paillier.cpp · line 537 · SHA-256 cebe585f3f001af3... · File fd1dc137a7611808...

```
536 |                                     const bn_t& r, mem_t session_id, uint64_t aux) {
537 |   const pedersen_commitment_params_t& params = pedersen_commitment_params_t::get();
538 |   const mod_t& p_tag = params.p_tag;
```

file_excerpt · src/cbmpc/zk/zk_pedersen.cpp · line 6 · SHA-256 edeeb6e35af2f2df... · File 968641640c623fc2...

```
  5 |
  6 | pedersen_commitment_params_t::pedersen_commitment_params_t() {
  7 |   // this was generated using https://www.openssl.org/docs/man1.1.1/man3/
BN_generate_prime_ex.html
```

file_excerpt · src/cbmpc/zk/zk_pedersen.cpp · line 39 · SHA-256 59b6c7a5b07fdfda... · File 968641640c623fc2...

```
 38 |
 39 | const pedersen_commitment_params_t& pedersen_commitment_params_t::get() {
 40 |   static pedersen_commitment_params_t params;
```

file_excerpt · src/cbmpc/zk/zk_pedersen.cpp · line 40 · SHA-256 ad78a5b9a922f859... · File 968641640c623fc2...

```
 39 | const pedersen_commitment_params_t& pedersen_commitment_params_t::get() {
 40 |   static pedersen_commitment_params_t params;
 41 |   return params;
```

LIMITATIONS OF THE CHECK

This is a forward-looking risk that depends on the arrival of a cryptographically relevant quantum computer (CRQC). No such computer is publicly known to exist today; the timeline is uncertain. It is not a present-day exploitable vulnerability. Heuristic pattern match on source text without data-flow analysis. The usage context (security-relevant or not) must be confirmed manually; treat as preliminary.

RECOMMENDATION

Track post-quantum threshold signatures (NIST IR 8214C) and keep the protocol layer ready to swap the signature scheme; record which keys and shares must stay valid for how long.

RETEST PROCEDURE

Re-run the inventory after refactoring.

P. W. Shor — Polynomial-Time Algorithms for Prime Factorization and Discrete Logarithms on a Quantum Computer (SIAM J. Comput., 1997); NIST IR 8547 — Transition to Post-Quantum Cryptography Standards; M. Mosca — Cybersecurity in an Era with Quantum Computers: Will We Be Ready? (IEEE Security & Privacy, 2018)

QSI-2026-17974 · CODE-QV-ASYMMETRIC

Medium

Quantum-vulnerable ECDSA: threshold signing and MPC protocols (3 file(s))

Long-term post-quantum risk | Confidence: Medium

> **Analyst review (QSI review, 2026-10-28): confirmed by the analyst.** Plain (non-threshold) ECDSA on secp256k1 inside the Schnorr two-party API: src/cbmpc/api/schnorr2pc.cpp:31 and :48 validate and write blob.curve against curve_id::secp256k1 and serialise key.Q compressed. Key-blob handling for the signing keys, so the same migration item as the threshold rows; counted separately because it is the serialisation format, which is where a migration needs a version bump.

17 reference(s) to ECDSA across 3 file(s), e.g. src/cbmpc/api/schnorr2pc.cpp:31. Role, judged from paths, function names and nearby code: threshold signing and MPC protocols. Paillier, Pedersen commitments and the discrete-logarithm proofs inside threshold ECDSA and EdDSA protocols all fall to Shor's algorithm; a post-quantum threshold scheme is a protocol change, not a parameter change.

Affected asset	source-code:ECDSA:threshold_mpc
Data source	src/cbmpc/api/schnorr2pc.cpp
Detection method	Regular-expression matching of crypto API patterns; the role comes from words in paths, enclosing function names and the lines around the matches.
Analyzer	source_code 1.3.0 · 2026-11-06 13:12 UTC
Priority score	41.8 / 100 (Crypto exchange, custodian or wallet)
CVSS v3.1	not applicable
Mosca's inequality (x + y > z)	x=10.0, y=5.0, z=8.0 → migration would finish too late under this scenario

POTENTIAL IMPACT

Long-term risk depends on what the algorithm protects: signatures (authenticity until migration) or key exchange/encryption (retroactive decryption of recorded data).

REPRODUCTION STEPS

```
Open src/cbmpc/api/schnorr2pc.cpp:31 and inspect the quoted lines; the evidence lists further files.
```

EVIDENCE

file_excerpt · src/cbmpc/api/schnorr2pc.cpp · line 31 · SHA-256 781d30e36a4e8dc2... · File 9495eab05f3110ea...

```
   30 |   if (blob.role > 1) return coinbase::error(E_FORMAT, "invalid key blob role");
   31 |   if (static_cast<curve_id>(blob.curve) != curve_id::secp256k1)
   32 |     return coinbase::error(E_FORMAT, "invalid key blob curve");
```

file_excerpt · src/cbmpc/api/schnorr2pc.cpp · line 48 · SHA-256 70c0040ad2b59e8f... · File 9495eab05f3110ea...

```
   47 |   blob.role = static_cast<uint32_t>(key.role);
   48 |   blob.curve = static_cast<uint32_t>(curve_id::secp256k1);
   49 |   blob.Q_compressed = key.Q.to_compressed_bin();
```

file_excerpt · src/cbmpc/api/schnorr2pc.cpp · line 67 · SHA-256 8e0b65f6eab20ce3... · File 9495eab05f3110ea...

```
   66 |   if (const error_t rv = validate_job_2p(job)) return rv;
   67 |   if (curve != curve_id::secp256k1) return coinbase::error(E_BADARG, "unsupported curve");
   68 |
```

file_excerpt · src/cbmpc/api/schnorr_mp.cpp · line 46 · SHA-256 6b5c5538004c224d... · File bd909c04140c085c...

```
   45 |     return coinbase::error(E_FORMAT, "unsupported key blob version");
   46 |   if (static_cast<curve_id>(blob.curve) != curve_id::secp256k1)
   47 |     return coinbase::error(E_FORMAT, "invalid key blob curve");
```

file_excerpt · src/cbmpc/api/schnorr_mp.cpp · line 71 · SHA-256 6082a2958ef6b914... · File bd909c04140c085c...

```
   70 |   blob.version = version;
   71 |   blob.curve = static_cast<uint32_t>(curve_id::secp256k1);
   72 |   blob.party_name = key.party_name;
```

file_excerpt · src/cbmpc/api/schnorr_mp.cpp · line 117 · SHA-256 516efb1988607679... · File bd909c04140c085c...

```
  116 |     return coinbase::error(E_FORMAT, "unsupported key blob version: " +
std::to_string(blob.version));
  117 |   if (static_cast<curve_id>(blob.curve) != curve_id::secp256k1)
  118 |     return coinbase::error(E_FORMAT, "invalid key blob curve");
```

file_excerpt · src/cbmpc/protocol/schnorr_2p.cpp · line 82 · SHA-256 6933ccbb7668499b... · File a998fa463bf10815...

```
   81 |   if (variant == variant_e::BIP340) {
   82 |     if (curve != crypto::curve_secp256k1) return coinbase::error(E_BADARG, "BIP340 variant
requires secp256k1 curve");
   83 |     for (int i = 0; i < n_sigs; i++) {
```

file_excerpt · src/cbmpc/protocol/schnorr_2p.cpp · line 136 · SHA-256 a382d78dd9af5355... · File a998fa463bf10815...

```
  135 |         if (rv = crypto::bip340::verify(pub_key, msgs[i], candidate_sigs[i]))
  136 |           return coinbase::error(rv, "schnorr_2p: secp256k1 verify failed");
  137 |       } else {
```

LIMITATIONS OF THE CHECK

This is a forward-looking risk that depends on the arrival of a cryptographically relevant quantum computer (CRQC). No such computer is publicly known to exist today; the timeline is uncertain. It is not a present-day exploitable vulnerability.

Heuristic pattern match on source text without data-flow analysis. The usage context (security-relevant or not) must be confirmed manually; treat as preliminary.

RECOMMENDATION

Track post-quantum threshold signatures (NIST IR 8214C) and keep the protocol layer ready to swap the signature scheme; record which keys and shares must stay valid for how long.

RETEST PROCEDURE

Re-run the inventory after refactoring.

P. W. Shor — Polynomial-Time Algorithms for Prime Factorization and Discrete Logarithms on a Quantum Computer (SIAM J. Comput., 1997); NIST IR 8547 — Transition to Post-Quantum Cryptography Standards; M. Mosca — Cybersecurity in an Era with Quantum Computers: Will We Be Ready? (IEEE Security & Privacy, 2018)

QSI-2026-17976 · CODE-QV-ASYMMETRIC

Medium

Quantum-vulnerable ECDSA: transaction and message signing (1 file(s))

Long-term post-quantum risk | Confidence: Medium

> **Analyst review (QSI review, 2026-10-28): confirmed by the analyst.** Plain (non-threshold) ECDSA on secp256k1 inside the Schnorr two-party API: src/cbmpc/api/schnorr2pc.cpp:31 and :48 validate and write blob.curve against curve_id::secp256k1 and serialise key.Q compressed. Key-blob handling for the signing keys, so the same migration item as the threshold rows; counted separately because it is the serialisation format, which is where a migration needs a version bump.

45 reference(s) to ECDSA across 1 file(s), e.g. src/cbmpc/crypto/base_ecc_secp256k1.cpp:5. Role, judged from paths, function names and nearby code: transaction and message signing. A CRQC derives the private key from a public key that is already known (on chain after the first spend, in reused addresses): funds and approvals controlled by these keys need a migration path.

Affected asset	source-code:ECDSA:transaction_signing
Data source	src/cbmpc/crypto/base_ecc_secp256k1.cpp
Detection method	Regular-expression matching of crypto API patterns; the role comes from words in paths, enclosing function names and the lines around the matches.
Analyzer	source_code 1.3.0 · 2026-11-06 13:12 UTC
Priority score	41.8 / 100 (Crypto exchange, custodian or wallet)
CVSS v3.1	not applicable
Mosca's inequality (x + y > z)	x=10.0, y=5.0, z=8.0 → migration would finish too late under this scenario

POTENTIAL IMPACT

Long-term risk depends on what the algorithm protects: signatures (authenticity until migration) or key exchange/encryption (retroactive decryption of recorded data).

REPRODUCTION STEPS

```
Open src/cbmpc/crypto/base_ecc_secp256k1.cpp:5 and inspect the quoted lines; the evidence lists
further files.
```

EVIDENCE

file_excerpt · src/cbmpc/crypto/base_ecc_secp256k1.cpp · line 5 · SHA-256 872667182b513b2f… · File 31cabe4ca8532731…

```
4 | // clang-format off
5 | #include "secp256k1/src/assumptions.h"
6 | #include "secp256k1/src/field_impl.h"
```

file_excerpt · src/cbmpc/crypto/base_ecc_secp256k1.cpp · line 6 · SHA-256 080665ef1f83af11… · File 31cabe4ca8532731…

```
5 | #include "secp256k1/src/assumptions.h"
6 | #include "secp256k1/src/field_impl.h"
7 | #include "secp256k1/src/scalar_impl.h"
```

file_excerpt · src/cbmpc/crypto/base_ecc_secp256k1.cpp · line 7 · SHA-256 3fef17948caa87b9… · File 31cabe4ca8532731…

```
6 | #include "secp256k1/src/field_impl.h"
7 | #include "secp256k1/src/scalar_impl.h"
8 | #include "secp256k1/src/scratch_impl.h"
```

LIMITATIONS OF THE CHECK

This is a forward-looking risk that depends on the arrival of a cryptographically relevant quantum computer (CRQC). No such computer is publicly known to exist today; the timeline is uncertain. It is not a present-day exploitable vulnerability. Heuristic pattern match on source text without data-flow analysis. The usage context (security-relevant or not) must be confirmed manually; treat as preliminary.

RECOMMENDATION

Follow each chain's post-quantum roadmap, avoid public-key reuse, and keep signers ready to add post-quantum signature schemes as chains adopt them.

RETEST PROCEDURE

Re-run the inventory after refactoring.

P. W. Shor — Polynomial-Time Algorithms for Prime Factorization and Discrete Logarithms on a Quantum Computer (SIAM J. Comput., 1997); NIST IR 8547 — Transition to Post-Quantum Cryptography Standards; M. Mosca — Cybersecurity in an Era with Quantum Computers: Will We Be Ready? (IEEE Security & Privacy, 2018)

QSI-2026-17968 · CODE-QV-ASYMMETRIC

Medium

Quantum-vulnerable ECDSA: role not determined (6 file(s))

Long-term post-quantum risk | Confidence: Medium

> **Analyst review (QSI review, 2026-10-28): confirmed by the analyst.** Plain (non-threshold) ECDSA on secp256k1 inside the Schnorr two-party API: src/cbmpc/api/schnorr2pc.cpp:31 and :48 validate and write blob.curve against curve_id::secp256k1 and serialise key.Q compressed. Key-blob handling for the signing keys, so the same migration item as the threshold rows; counted separately because it is the serialisation format, which is where a migration needs a version bump.

12 reference(s) to ECDSA across 6 file(s), e.g. include-internal/cbmpc/internal/crypto/base_ecc.h:17. Role, judged from paths, function names and nearby code: role not determined. The code does not show what the keys protect; review decides the priority.

Affected asset	source-code:ECDSA:general
Data source	include-internal/cbmpc/internal/crypto/base_ecc.h
Detection method	Regular-expression matching of crypto API patterns; the role comes from words in paths, enclosing function names and the lines around the matches.

Analyzer	source_code 1.3.0 · 2026-11-06 13:12 UTC
Priority score	40.2 / 100 (Crypto exchange, custodian or wallet)
CVSS v3.1	not applicable
Mosca's inequality (x + y > z)	x=10.0, y=5.0, z=8.0 → migration would finish too late under this scenario

POTENTIAL IMPACT

Long-term risk depends on what the algorithm protects: signatures (authenticity until migration) or key exchange/encryption (retroactive decryption of recorded data).

REPRODUCTION STEPS

```
Open include-internal/cbmpc/internal/crypto/base_ecc.h:17 and inspect the quoted lines; the evidence lists further files.
```

EVIDENCE

file_excerpt · include-internal/cbmpc/internal/crypto/base_ecc.h · line 17 · SHA-256 1acb65be89f9287e... · File 4622c8393c4f4bf8...

```
  16 |
  17 | namespace secp256k1 {
  18 | typedef struct point_t* point_ptr_t;
```

file_excerpt · include-internal/cbmpc/internal/crypto/base_ecc.h · line 177 · SHA-256 32e38a7fe938b9f8... · File 4622c8393c4f4bf8...

```
 176 |   explicit ecc_point_t(ecurve_t curve, const ecp_storage_t& storage);
 177 |   explicit ecc_point_t(const secp256k1::point_ptr_t p);
 178 |
```

file_excerpt · include-internal/cbmpc/internal/crypto/base_ecc.h · line 246 · SHA-256 d6d38a0587aa30e2... · File 4622c8393c4f4bf8...

```
 245 |     EC_POINT* ptr = nullptr;
 246 |     secp256k1::point_ptr_t secp256k1;
 247 |     ecp_storage_t* storage;
```

file_excerpt · include/cbmpc/api/curve.h · line 9 · SHA-256 8bc94e0040057c98... · File 2facde4582730feb...

```
   8 | enum class curve_id : uint32_t {
   9 |   p256 = 1,       // NIST P-256 (aka prime256v1 / secp256r1)
  10 |   secp256k1 = 2,  // secp256k1
```

file_excerpt · include/cbmpc/api/curve.h · line 10 · SHA-256 0eb2996e7229d0e7... · File 2facde4582730feb...

```
   9 |   p256 = 1,       // NIST P-256 (aka prime256v1 / secp256r1)
  10 |   secp256k1 = 2,  // secp256k1
  11 |   ed25519 = 3,    // Edwards25519
```

file_excerpt · src/cbmpc/api/curve_util.h · line 13 · SHA-256 4a75918a0824abc5... · File 2b1ce8031d294bd7...

```
  12 |       return coinbase::crypto::curve_p256;
  13 |     case curve_id::secp256k1:
  14 |       return coinbase::crypto::curve_secp256k1;
```

file_excerpt · src/cbmpc/api/curve_util.h · line 30 · SHA-256 ea0e22518060778a... · File 2b1ce8031d294bd7...

```
  29 |   if (curve == coinbase::crypto::curve_secp256k1) {
  30 |     out = curve_id::secp256k1;
  31 |     return true;
```

file_excerpt · src/cbmpc/c_api/util.h · line 79 · SHA-256 e7c477a077d0efbf... · File 54e197b005d5bf85...

```
78 |     case CBMPC_CURVE_SECP256K1:
79 |       out = coinbase::api::curve_id::secp256k1;
80 |       return CBMPC_SUCCESS;
```

file_excerpt · src/cbmpc/crypto/base_ecc.cpp · line 673 · SHA-256 59055bc4efcd046e... · File dd31645addc8cf00...

```
672 |
673 | namespace secp256k1 {
674 | point_ptr_t new_point(const point_ptr_t);
```

file_excerpt · src/cbmpc/crypto/base_ecc.cpp · line 677 · SHA-256 8996735a795dea2a... · File dd31645addc8cf00...

```
676 |
677 | ecc_point_t::ecc_point_t(const secp256k1::point_ptr_t p)
678 |     : curve(curve_secp256k1)  // NOLINT:cppcoreguidelines-pro-type-member-init
```

LIMITATIONS OF THE CHECK

This is a forward-looking risk that depends on the arrival of a cryptographically relevant quantum computer (CRQC). No such computer is publicly known to exist today; the timeline is uncertain. It is not a present-day exploitable vulnerability. Heuristic pattern match on source text without data-flow analysis. The usage context (security-relevant or not) must be confirmed manually; treat as preliminary.

RECOMMENDATION

Classify each usage, record data lifetimes, and plan migration to ML-DSA (FIPS 204) or SLH-DSA (FIPS 205), in a hybrid/composite form where the ecosystem supports it; introduce an abstraction layer for crypto-agility.

RETEST PROCEDURE

Re-run the inventory after refactoring.

P. W. Shor — Polynomial-Time Algorithms for Prime Factorization and Discrete Logarithms on a Quantum Computer (SIAM J. Comput., 1997); NIST IR 8547 — Transition to Post-Quantum Cryptography Standards; M. Mosca — Cybersecurity in an Era with Quantum Computers: Will We Be Ready? (IEEE Security & Privacy, 2018)

QSI-2026-17975 · CODE-QV-ASYMMETRIC

Medium

Quantum-vulnerable Ed25519: role not determined (3 file(s))

Long-term post-quantum risk | Confidence: Medium

> **Analyst review (QSI review, 2026-10-28): confirmed by the analyst.** Threshold EdDSA, which the library implements alongside threshold ECDSA: api/eddsa_2p.h, internal/protocol/eddsa.h (which includes schnorr_mp.h), hd_keyset_eddsa_2p.h and src/cbmpc/api/eddsa2pc.cpp, where blob_to_key validates the key blob role. Same conclusion as threshold ECDSA and the same caveat about namespace anchors; the protocol is a Schnorr-style multiparty scheme over Ed25519, so Shor breaks both the signature and the discrete-log proofs around it.

27 reference(s) to Ed25519 across 3 file(s), e.g. src/cbmpc/crypto/base_ecc.cpp:420. Role, judged from paths, function names and nearby code: role not determined. The code does not show what the keys protect; review decides the priority.

Affected asset	source-code:Ed25519:general
Data source	src/cbmpc/crypto/base_ecc.cpp

Detection method	Regular-expression matching of crypto API patterns; the role comes from words in paths, enclosing function names and the lines around the matches.
Analyzer	source_code 1.3.0 · 2026-11-06 13:12 UTC
Priority score	40.2 / 100 (Crypto exchange, custodian or wallet)
CVSS v3.1	not applicable
Mosca's inequality (x + y > z)	x=10.0, y=5.0, z=8.0 → migration would finish too late under this scenario

POTENTIAL IMPACT

Long-term risk depends on what the algorithm protects: signatures (authenticity until migration) or key exchange/encryption (retroactive decryption of recorded data).

REPRODUCTION STEPS

```
Open src/cbmpc/crypto/base_ecc.cpp:420 and inspect the quoted lines; the evidence lists further
files.
```

EVIDENCE

file_excerpt · src/cbmpc/crypto/base_ecc.cpp · line 420 · SHA-256 bc97f1d43e02c893… · File dd31645addc8cf00…

```
  419 | void ecc_prv_key_t::set_ed_bin(mem_t ed_bin) {
  420 |   cb_assert(ed_bin.size == ed25519::prv_bin_size());
  421 |   this->curve = curve_ed25519;
```

file_excerpt · src/cbmpc/crypto/base_ecc.cpp · line 428 · SHA-256 7704d598e6d557af… · File dd31645addc8cf00…

```
  427 |   bn_t x = val;
  428 |   if (!ed_bin.empty()) x = ed25519::prv_key_to_scalar(ed_bin);
  429 |   return x % curve.order();
```

file_excerpt · src/cbmpc/crypto/base_eddsa.cpp · line 73 · SHA-256 098cb191d292ec1d… · File 45697966a1eb28d1…

```
   72 | void ecurve_ed_t::get_params(bn_t& p, bn_t& a, bn_t& b) const {
   73 |   a = ed25519::a();
   74 |   b = ed25519::b();
```

file_excerpt · src/cbmpc/crypto/base_eddsa.cpp · line 74 · SHA-256 6ac622113d6a0eee… · File 45697966a1eb28d1…

```
   73 |   a = ed25519::a();
   74 |   b = ed25519::b();
   75 |   p = ed25519::p();
```

file_excerpt · src/cbmpc/crypto/base_eddsa.cpp · line 75 · SHA-256 5456bbfafd04245e… · File 45697966a1eb28d1…

```
   74 |   b = ed25519::b();
   75 |   p = ed25519::p();
   76 | }
```

file_excerpt · src/cbmpc/protocol/schnorr_mp.cpp · line 169 · SHA-256 dbde3ddb4baf2c21… · File b7aa492e64186b64…

```
  168 |       for (size_t l = 0; l < msgs.size(); l++) {
  169 |         candidate_sigs[l] = R[l].to_compressed_bin() +
ss[l].to_bin(crypto::ed25519::prv_bin_size()).rev();
  170 |         if (rv = verify_key.verify(msgs[l], candidate_sigs[l])) return coinbase::error(rv,
"ed25519 verify failed");
```

LIMITATIONS OF THE CHECK

This is a forward-looking risk that depends on the arrival of a cryptographically relevant quantum computer (CRQC). No such computer is publicly known to exist today; the timeline is uncertain. It is not a present-day exploitable vulnerability.

Heuristic pattern match on source text without data-flow analysis. The usage context (security-relevant or not) must be confirmed manually; treat as preliminary.

RECOMMENDATION

Classify each usage, record data lifetimes, and plan migration to ML-DSA (FIPS 204) or SLH-DSA (FIPS 205), in a hybrid/composite form where the ecosystem supports it; introduce an abstraction layer for crypto-agility.

RETEST PROCEDURE

Re-run the inventory after refactoring.

P. W. Shor — Polynomial-Time Algorithms for Prime Factorization and Discrete Logarithms on a Quantum Computer (SIAM J. Comput., 1997); NIST IR 8547 — Transition to Post-Quantum Cryptography Standards; M. Mosca — Cybersecurity in an Era with Quantum Computers: Will We Be Ready? (IEEE Security & Privacy, 2018)

QSI-2026-17977 · CODE-QV-ASYMMETRIC

Medium

Quantum-vulnerable RSA: role not determined (1 file(s))

Long-term post-quantum risk | Confidence: Medium

> **Analyst review (QSI review, 2026-10-28): confirmed by the analyst.** Role resolved. src/cbmpc/crypto/base_rsa.cpp implements rsa_pub_key_t with encrypt_raw (deliberately RSA_NO_PADDING, because it is a primitive for a higher-level scheme rather than a general-purpose encryption API), verify_pkcs1, and EVP_RSA_gen(bits) for generation. It is included by internal/crypto/base_pki.h and internal/crypto/base_paillier.h and exercised by tests/unit/api/test_pve.cpp, so this is the PKI layer underneath publicly verifiable encryption and the modulus arithmetic that Paillier is built on. Same quantum exposure as the Paillier row, for the same reason: Shor factors the composite modulus. Because PVE ciphertexts are stored, this inherits the harvest-now-decrypt-later urgency of the ECDH row rather than the lower urgency of a signing path.

2 reference(s) to RSA across 1 file(s), e.g. src/cbmpc/crypto/base_rsa.cpp:96. Role, judged from paths, function names and nearby code: role not determined. The code does not show what the keys protect; review decides the priority.

Affected asset	source-code:RSA:general
Data source	src/cbmpc/crypto/base_rsa.cpp
Detection method	Regular-expression matching of crypto API patterns; the role comes from words in paths, enclosing function names and the lines around the matches.
Analyzer	source_code 1.3.0 · 2026-11-06 13:12 UTC
Priority score	40.2 / 100 (Crypto exchange, custodian or wallet)
CVSS v3.1	not applicable
Mosca's inequality (x + y > z)	x=10.0, y=5.0, z=8.0 → migration would finish too late under this scenario

POTENTIAL IMPACT

Long-term risk depends on what the algorithm protects: signatures (authenticity until migration) or key exchange/encryption (retroactive decryption of recorded data).

REPRODUCTION STEPS

```
Open src/cbmpc/crypto/base_rsa.cpp:96 and inspect the quoted lines; the evidence lists further
files.
```

EVIDENCE

file_excerpt · src/cbmpc/crypto/base_rsa.cpp · line 96 · SHA-256 db6acbfbb01b1b6b... · File ce1f7e2af4ab105d...

```
  95 |
  96 |   if (EVP_PKEY_id(pkey) != EVP_PKEY_RSA) {
  97 |     // Handle error: Not an RSA key
```

file_excerpt · src/cbmpc/crypto/base_rsa.cpp · line 201 · SHA-256 2a07b530bd9526bf... · File ce1f7e2af4ab105d...

```
 200 |   create();
 201 |   ptr = EVP_RSA_gen(bits);
 202 |   cb_assert(ptr);
```

LIMITATIONS OF THE CHECK

This is a forward-looking risk that depends on the arrival of a cryptographically relevant quantum computer (CRQC). No such computer is publicly known to exist today; the timeline is uncertain. It is not a present-day exploitable vulnerability. Heuristic pattern match on source text without data-flow analysis. The usage context (security-relevant or not) must be confirmed manually; treat as preliminary.

RECOMMENDATION

Classify each usage, record data lifetimes, and plan migration to ML-DSA (FIPS 204) or SLH-DSA (FIPS 205), in a hybrid/composite form where the ecosystem supports it; introduce an abstraction layer for crypto-agility.

RETEST PROCEDURE

Re-run the inventory after refactoring.

P. W. Shor — Polynomial-Time Algorithms for Prime Factorization and Discrete Logarithms on a Quantum Computer (SIAM J. Comput., 1997); NIST IR 8547 — Transition to Post-Quantum Cryptography Standards; M. Mosca — Cybersecurity in an Era with Quantum Computers: Will We Be Ready? (IEEE Security & Privacy, 2018)

QSI-2026-17969 · CODE-QV-ASYMMETRIC

Medium

Quantum-vulnerable Schnorr (BIP-340): role not determined (2 file(s))

Long-term post-quantum risk | Confidence: Medium | preliminary — requires further verification

4 reference(s) to Schnorr (BIP-340) across 2 file(s), e.g. include-internal/cbmpc/internal/crypto/base_ecc.h:299. Role, judged from paths, function names and nearby code: role not determined. The code does not show what the keys protect; review decides the priority.

Affected asset	source-code:Schnorr (BIP-340):general
Data source	include-internal/cbmpc/internal/crypto/base_ecc.h
Detection method	Regular-expression matching of crypto API patterns; the role comes from words in paths, enclosing function names and the lines around the matches.
Analyzer	source_code 1.3.0 · 2026-11-06 13:12 UTC
Priority score	34.2 / 100 (Crypto exchange, custodian or wallet)
CVSS v3.1	not applicable
Mosca's inequality (x + y > z)	x=10.0, y=5.0, z=8.0 → migration would finish too late under this scenario

POTENTIAL IMPACT

Long-term risk depends on what the algorithm protects: signatures (authenticity until migration) or key exchange/encryption (retroactive decryption of recorded data).

REPRODUCTION STEPS

```
Open include-internal/cbmpc/internal/crypto/base_ecc.h:299 and inspect the quoted lines; the
evidence lists further files.
```

EVIDENCE

file_excerpt · include-internal/cbmpc/internal/crypto/base_ecc.h · line 299 · SHA-256 28f82276a8490953… · File 4622c8393c4f4bf8…

```
298 |
299 |   error_t verify_schnorr(mem_t message, mem_t signature) const;
300 | };
```

file_excerpt · include-internal/cbmpc/internal/crypto/base_ecc.h · line 328 · SHA-256 7743eba94a1a6606… · File 4622c8393c4f4bf8…

```
327 |
328 |   buf_t sign_schnorr(mem_t hash) const;
329 |   sig_with_pub_key_t sign_and_output_pub_key(mem_t hash) const;
```

file_excerpt · src/cbmpc/crypto/base_ecc.cpp · line 373 · SHA-256 a6d9f37f314044dd… · File dd31645addc8cf00…

```
372 |
373 | error_t ecc_pub_key_t::verify_schnorr(mem_t message, mem_t signature) const {
374 |   if (signature.size != curve.size() * 2) return coinbase::error(E_FORMAT);
```

file_excerpt · src/cbmpc/crypto/base_ecc.cpp · line 485 · SHA-256 890e2d1fab1145ca… · File dd31645addc8cf00…

```
484 |
485 | buf_t ecc_prv_key_t::sign_schnorr(mem_t message) const {
486 |   const auto& G = curve.generator();
```

LIMITATIONS OF THE CHECK

This is a forward-looking risk that depends on the arrival of a cryptographically relevant quantum computer (CRQC). No such computer is publicly known to exist today; the timeline is uncertain. It is not a present-day exploitable vulnerability. Heuristic pattern match on source text without data-flow analysis. The usage context (security-relevant or not) must be confirmed manually; treat as preliminary.

RECOMMENDATION

Classify each usage, record data lifetimes, and plan migration to a post-quantum algorithm; introduce an abstraction layer for crypto-agility.

RETEST PROCEDURE

Re-run the inventory after refactoring.

P. W. Shor — Polynomial-Time Algorithms for Prime Factorization and Discrete Logarithms on a Quantum Computer (SIAM J. Comput., 1997); NIST IR 8547 — Transition to Post-Quantum Cryptography Standards; M. Mosca — Cybersecurity in an Era with Quantum Computers: Will We Be Ready? (IEEE Security & Privacy, 2018)

Evidence

ID	Type	Data source	SHA-256
QSI-2026-17972	file_excerpt	include-internal/cbmpc/internal/protocol/pve_base.h (line 213)	02f0b0e2dc3db13d04880ba70b571232395b33294953c92a27a9d1
QSI-2026-17972	file_excerpt	src/cbmpc/api/pve_base_pke.cpp (line 325)	7a1b1fff636e81f0627ac69da87fc93e1fcf0bf121c4e2297b0718
QSI-2026-17972	file_excerpt	src/cbmpc/api/pve_batch_ac.cpp (line 308)	8e385b276c3dbb900f226e3840ad803a3463b08dc1a1f91ea26225
QSI-2026-17972	file_excerpt	src/cbmpc/api/pve_batch_single_recipient.cpp (line 225)	862c1cebf150e17798084f5554fc57ca003f1addc2df7e38232744
QSI-2026-17972	file_excerpt	src/cbmpc/api/pve_internal.h (line 154)	3fa55d0a81efe46a0c8448fd5d5943231913648274934d50546cae
QSI-2026-17967	file_excerpt	include-internal/cbmpc/internal/crypto/base_bn.h (line 46)	5b3069a225ca12ea3e28ab0aeabfda51b549f1b3b9d656edc897fe
QSI-2026-17967	file_excerpt	include-internal/cbmpc/internal/crypto/base_bn.h (line 57)	ee1680c40ae2e30e376737e08f755915785323d13d53983ed66744
QSI-2026-17967	file_excerpt	include-internal/cbmpc/internal/crypto/base_paillier.h (line 8)	5e4a09314f2cd39ed8e8283c855838bd6ca755c5868d316db91eee
QSI-2026-17967	file_excerpt	include-internal/cbmpc/internal/crypto/base_paillier.h (line 29)	5f18c9d760a32724c050c5db7a67fbc655776bda0da0b20a58aad0
QSI-2026-17967	file_excerpt	include-internal/cbmpc/internal/crypto/base_paillier.h (line 30)	0cb26e46930009ca686d8c0d8cf27ded9d756b290f72260c02b479
QSI-2026-17967	file_excerpt	include-internal/cbmpc/internal/protocol/ecdsa_2p.h (line 18)	ca851b698b030d5580b83a036c3c776223f359db508a167eef1d50
QSI-2026-17967	file_excerpt	include-internal/cbmpc/internal/protocol/ecdsa_2p.h (line 66)	0986d849de59c959f92b00dd88d412729fbe9ff0da5f142cd1c102
QSI-2026-17967	file_excerpt	include-internal/cbmpc/internal/protocol/ecdsa_2p.h (line 67)	220d61e7527123b6ac429da5f9c81c381cf521d6a0dd872c9c236e
QSI-2026-17967	file_excerpt	include-internal/cbmpc/internal/protocol/hd_keyset_ecdsa_2p.h (line 11)	6626153477cce1abe743ecfb348e91e140577229a70e4d4dc32b35
QSI-2026-17967	file_excerpt	include-internal/cbmpc/internal/zk/zk_paillier.h (line 9)	b73ec02d5359acd4ea08e3bf49c6d23136c6a5d7bc3ff5e36548fa

QSI-2026-17970	file_excerpt	include-internal/cbmpc/internal/protocol/ecdsa_2p.h (line 10)	`4f07cdced92dd607c8b26f039382244c79cc890b96ad3e83064608`
QSI-2026-17970	file_excerpt	include-internal/cbmpc/internal/protocol/ecdsa_2p.h (line 122)	`eb44feaab487c80962c7a431cfbdf3361a9a37156029f2ec3d6219`
QSI-2026-17970	file_excerpt	include-internal/cbmpc/internal/protocol/ecdsa_mp.h (line 9)	`867210bf6da87290b3d8ca0486277ad9893eb8ba3d71cb1b0f72a3`
QSI-2026-17970	file_excerpt	include-internal/cbmpc/internal/protocol/ecdsa_mp.h (line 129)	`1733ee2e1cb11d10a703f1fc869b155110678b46904534af78db5d`
QSI-2026-17970	file_excerpt	include-internal/cbmpc/internal/protocol/hd_keyset_ecdsa_2p.h (line 3)	`219e8141fa597210bbafd00b034030aa8b243102ba810d0f7e1e7b`
QSI-2026-17970	file_excerpt	include-internal/cbmpc/internal/protocol/hd_keyset_ecdsa_2p.h (line 29)	`a5b11e730725f1172506a636b59dc27320599bd992208ea7d2320c`
QSI-2026-17970	file_excerpt	include/cbmpc/api/ecdsa_2p.h (line 12)	`a78ce67e456bbade8e40693fbf9637650f04faa2e8891063ddeebe`
QSI-2026-17970	file_excerpt	include/cbmpc/api/ecdsa_2p.h (line 88)	`2a83480fd5d03e50bebb35352c4cb14708fc498793961d1a8abf5d`
QSI-2026-17970	file_excerpt	include/cbmpc/api/ecdsa_mp.h (line 15)	`eb3d5758c2755f9f5a315a84c4a64733cdf65c78f998b14de387f2`
QSI-2026-17970	file_excerpt	include/cbmpc/api/ecdsa_mp.h (line 134)	`6496220e2d3584960750a9402b32c82c32f580a8ea5e20a24637f0`
QSI-2026-17971	file_excerpt	include-internal/cbmpc/internal/protocol/eddsa.h (line 6)	`3c84aa793ed1f42936617a69b2658887b6d94795e53413cf8e1516`
QSI-2026-17971	file_excerpt	include-internal/cbmpc/internal/protocol/eddsa.h (line 14)	`b312965fb62a137d3aae3bf51910e3d5803f05ece5bcf33078f902`
QSI-2026-17971	file_excerpt	include-internal/cbmpc/internal/protocol/hd_keyset_eddsa_2p.h (line 26)	`ef05e73154048d3043c22b41a17397906767a18a0b8cf741d1cf19`
QSI-2026-17971	file_excerpt	include/cbmpc/api/eddsa_2p.h (line 8)	`c37e0dee9fd8cf516ded4812f075b46479e94f71599bc145a46dd6`
QSI-2026-17971	file_excerpt	include/cbmpc/api/eddsa_2p.h (line 79)	`1870990aac8e55e075d1ff1db55dfa554b8413e8081ccb3390a7b8`
QSI-2026-17971	file_excerpt	src/cbmpc/api/eddsa2pc.cpp (line 1)	`0d8efb61e1de8ae34931c96eb484fc2f9c4ff617d0efa53fce450b`

QSI-2026-17971	file_excerpt	src/cbmpc/api/eddsa2pc.cpp (line 8)	c37e0dee9fd8cf516ded4812f075b46479e94f71599bc145a46dd6
QSI-2026-17971	file_excerpt	src/cbmpc/api/eddsa2pc.cpp (line 29)	bebfad4c5352b665f0c5800512a735abd85c681f783086cf92dba6
QSI-2026-17971	file_excerpt	src/cbmpc/api/hd_keyset_eddsa_2p.cpp (line 23)	f5e7d1db58a72a542c853835f4f649afc616439e30444f917e9a53
QSI-2026-17971	file_excerpt	src/cbmpc/api/hd_keyset_eddsa_2p.cpp (line 24)	b14eb05d04888ba3a76cb7c9a40d1ecaabd069bdadb57f2e0c8ec3
QSI-2026-17973	file_excerpt	include-internal/cbmpc/internal/zk/zk_pedersen.h (line 8)	90f6fa4e7aa38c51851aec3f52cc5042b5a7d6cb58864e285ff279
QSI-2026-17973	file_excerpt	include-internal/cbmpc/internal/zk/zk_pedersen.h (line 13)	beb6763be217e297856056988084ecbeb400ac2d7bf25b188e8104
QSI-2026-17973	file_excerpt	include-internal/cbmpc/internal/zk/zk_pedersen.h (line 17)	4a5620026d361a84899501efab6d448f6aaca1ec3470c5f81cf655
QSI-2026-17973	file_excerpt	src/cbmpc/protocol/ecdsa_2p.cpp (line 28)	f6cd7432a9262739e96d7886c92f3c7506f35897ea1c58e6393e83
QSI-2026-17973	file_excerpt	src/cbmpc/zk/zk_paillier.cpp (line 537)	cebe585f3f001af319bb63895f689e137cb8b6b68d327245e8efe2
QSI-2026-17973	file_excerpt	src/cbmpc/zk/zk_pedersen.cpp (line 6)	edeeb6e35af2f2dfeb59c3d504b58d0c9676130e51cab7743e716f
QSI-2026-17973	file_excerpt	src/cbmpc/zk/zk_pedersen.cpp (line 39)	59b6c7a5b07fdfda0bfbf3c3cf9123cee14bec4790d944ee6da5b7
QSI-2026-17973	file_excerpt	src/cbmpc/zk/zk_pedersen.cpp (line 40)	ad78a5b9a922f859724ed7a18381e655d3c93f4063474ab5e7f836
QSI-2026-17974	file_excerpt	src/cbmpc/api/schnorr2pc.cpp (line 31)	781d30e36a4e8dc2b8788c3413940215330fa9c99e7ede1cd51753
QSI-2026-17974	file_excerpt	src/cbmpc/api/schnorr2pc.cpp (line 48)	70c0040ad2b59e8fc028bfe2b304bf1e5c190dcd9bd81c45122946
QSI-2026-17974	file_excerpt	src/cbmpc/api/schnorr2pc.cpp (line 67)	8e0b65f6eab20ce3e7beabdf092159341fdbb8bce48e0965e11375
QSI-2026-17974	file_excerpt	src/cbmpc/api/schnorr_mp.cpp (line 46)	6b5c5538004c224df21888f2ab7eb3b2283655671ec668e89d3b44
QSI-2026-17974	file_excerpt	src/cbmpc/api/schnorr_mp.cpp (line 71)	6082a2958ef6b9148a404e06a13378b5ddeabf80c823bc9a75ba85
QSI-2026-17974	file_excerpt	src/cbmpc/api/schnorr_mp.cpp (line 117)	516efb19886076797c71fe18d00e39cff6d00e5b16854aee71e290
QSI-2026-17974	file_excerpt	src/cbmpc/protocol/schnorr_2p.cpp (line 82)	6933ccbb7668499bfc93936f9461308c76da160293ca96d96dc726

QSI-2026-17974	file_excerpt	src/cbmpc/protocol/schnorr_2p.cpp (line 136)	a382d78dd9af5355999427605a0c64b9d3262c18a6290782f8046e
QSI-2026-17976	file_excerpt	src/cbmpc/crypto/base_ecc_secp256k1.cpp (line 5)	872667182b513b2fb3be5898f64aee3035d69bc5401c5422a09fa4
QSI-2026-17976	file_excerpt	src/cbmpc/crypto/base_ecc_secp256k1.cpp (line 6)	080665ef1f83af114ec0d02cf611f582583d388fba9861259f38e4
QSI-2026-17976	file_excerpt	src/cbmpc/crypto/base_ecc_secp256k1.cpp (line 7)	3fef17948caa87b9d5b3b241d1f94b1459b96d31c44dc1188c4062
QSI-2026-17968	file_excerpt	include-internal/cbmpc/internal/crypto/base_ecc.h (line 17)	1acb65be89f9287ebf0f9fdd748084d46a04587d02e8e23bd77cb5
QSI-2026-17968	file_excerpt	include-internal/cbmpc/internal/crypto/base_ecc.h (line 177)	32e38a7fe938b9f819247a3f2b8f4009a857ae01cfb18dc6643580
QSI-2026-17968	file_excerpt	include-internal/cbmpc/internal/crypto/base_ecc.h (line 246)	d6d38a0587aa30e2f8e219bbeb332a262f5d6e28c8f16c55803bbb
QSI-2026-17968	file_excerpt	include/cbmpc/api/curve.h (line 9)	8bc94e0040057c98486af0d2761abfd6ed943aa9547cb545354de9
QSI-2026-17968	file_excerpt	include/cbmpc/api/curve.h (line 10)	0eb2996e7229d0e76b10f0da6cc1353d0ed4e76d9997664d08fa47
QSI-2026-17968	file_excerpt	src/cbmpc/api/curve_util.h (line 13)	4a75918a0824abc51d4df2f3b0053de2ad333c16fee4e66dc47eac
QSI-2026-17968	file_excerpt	src/cbmpc/api/curve_util.h (line 30)	ea0e22518060778a7a9df31ae979e7d72520b1fc3bebb5996fceb1
QSI-2026-17968	file_excerpt	src/cbmpc/c_api/util.h (line 79)	e7c477a077d0efbf921de86527e4f38cd37dec90e2fabbe063db58
QSI-2026-17968	file_excerpt	src/cbmpc/crypto/base_ecc.cpp (line 673)	59055bc4efcd046ef6d49e3274cfc060c68a3620ea7436b2d76a3d
QSI-2026-17968	file_excerpt	src/cbmpc/crypto/base_ecc.cpp (line 677)	8996735a795dea2a0988f9d89bf72c598a082466689a5c52c12992
QSI-2026-17975	file_excerpt	src/cbmpc/crypto/base_ecc.cpp (line 420)	bc97f1d43e02c8937d050b6ff40221cbbe0b44782536f3749da34f
QSI-2026-17975	file_excerpt	src/cbmpc/crypto/base_ecc.cpp (line 428)	7704d598e6d557afa1663d4d9e33459c337911a17c2ca8640e59bc
QSI-2026-17975	file_excerpt	src/cbmpc/crypto/base_eddsa.cpp (line 73)	098cb191d292ec1d0e482d879f64faec8854c3290ae06e8b92fb31
QSI-2026-17975	file_excerpt	src/cbmpc/crypto/base_eddsa.cpp (line 74)	6ac622113d6a0eee7bdfb0992c54cd1dfdeabf37880dd29b486199
QSI-2026-17975	file_excerpt	src/cbmpc/crypto/base_eddsa.cpp (line 75)	5456bbfafd04245e9627dce77292b49b426863b9ecd3f6de7dffa7

QSI-2026-17975	file_excerpt	src/cbmpc/protocol/schnorr_mp.cpp (line 169)	`dbde3ddb4baf2c21baf4a87a6914ed7f9e0289e5a9e6080e665bb0`
QSI-2026-17977	file_excerpt	src/cbmpc/crypto/base_rsa.cpp (line 96)	`db6acbfbb01b1b6b2b382dc3e96fd9dbe38bd0d17244c79529f41f`
QSI-2026-17977	file_excerpt	src/cbmpc/crypto/base_rsa.cpp (line 201)	`2a07b530bd9526bfbff8696f00367319e11578e9fbdb917f5d310f`
QSI-2026-17969	file_excerpt	include-internal/cbmpc/internal/crypto/base_ecc.h (line 299)	`28f82276a84909538a7777f2fddddb21be288af66f48428f791704`
QSI-2026-17969	file_excerpt	include-internal/cbmpc/internal/crypto/base_ecc.h (line 328)	`7743eba94a1a6606ace6bf98cf07e363ed6b5af001f037832fd5d2`
QSI-2026-17969	file_excerpt	src/cbmpc/crypto/base_ecc.cpp (line 373)	`a6d9f37f314044dd61e5a40ad96ef3ed821bef576af77319a04b13`
QSI-2026-17969	file_excerpt	src/cbmpc/crypto/base_ecc.cpp (line 485)	`890e2d1fab1145cadf730e5f70917a0ef8d98c0ed2c921e05febab`

Post-quantum assessment

	Key establishment (x = how long data must stay confidential; harvest now, decrypt later)	Signatures (x = how long signatures/ keys must stay trusted)
Data/key lifetime x	10	10
Migration time y	5	5
Assumed years to CRQC z	8 (early)	8
x + y − z	7 → migration would finish too late under this scenario	7 → migration would finish too late under this scenario

Planning assumptions: x for key establishment, x for signatures, y are the defaults of the risk profile “Crypto exchange, custodian or wallet”, not the client's figures; with the client's actual lifetimes the verdict can change.

Post-quantum maturity: Level 1 of 4 — post-quantum code present, not wired

- Present, not wired: ML-KEM — include-internal/cbmpc/internal/crypto/mlkem768.h
- Present, not wired: ML-KEM — src/cbmpc/crypto/mlkem768.cpp
- Classical only — key wrapping and data encryption at rest: ECDH (5 file(s))
- Classical only — threshold signing and MPC protocols: ECDSA, Ed25519, Paillier, Pedersen commitment, Threshold ECDSA (33 file(s))

Next step: Wire the existing post-quantum primitive into a critical path (key wrapping or the channel) behind a hybrid construction, and test interoperability.

Levels: 0 none; 1 present, not wired; 2 in use outside the critical paths; 3 hybrid in a critical path; 4 post-quantum by default in the critical paths (root of trust, key wrapping, channel key exchange). Judged from code and manifests.

What the quantum-vulnerable algorithms do

Role	Algorithms (files)	ID	First step
key wrapping and data encryption at rest	ECDH (5)	QSI-2026-17972	Wrap keys with ML-KEM or a hybrid KEM (X25519 + ML-KEM-768) and re-wrap the stored keys; data that may already have been copied needs its own assessment
threshold signing and MPC protocols	Paillier (15), Threshold ECDSA (13), Ed25519 (9), Pedersen commitment (4), ECDSA (3)	QSI-2026-17967, QSI-2026-17970, QSI-2026-17971, QSI-2026-17973, QSI-2026-17974	Track post-quantum threshold signatures (NIST IR 8214C) and keep the protocol layer ready to swap the signature scheme; record which keys and shares must stay valid for how long
transaction and message signing	ECDSA (1)	QSI-2026-17976	Follow each chain's post-quantum roadmap, avoid public-key reuse, and keep signers ready to add post-quantum signature schemes as chains adopt them

role not determined	ECDSA (6), Ed25519 (3), Schnorr (BIP-340) (2), RSA (1)	QSI-2026-17968, QSI-2026-17969, QSI-2026-17975, QSI-2026-17977	Classify each usage, record data lifetimes, and plan migration to ML-DSA (FIPS 204) or SLH-DSA (FIPS 205), in a hybrid/composite form where the ecosystem supports it; introduce an abstraction layer for crypto-agility

Roles are judged from file paths, function names and the code around each match; review confirms them. Root-of-trust keys and wrapped keys come first: they are hard to replace or can be recorded today.

z is a planning assumption chosen per risk profile, not a prediction. A cryptographically relevant quantum computer is not publicly known to exist today.

Quantum status	Count
weak classically	2
reduced margin (Grover), approved	6
Grover: acceptable to NIST, below ECCG/ANSSI guidance	5
post-quantum	2
vulnerable (Shor)	93

Detailed findings: QSI-2026-17972, QSI-2026-17967, QSI-2026-17970, QSI-2026-17971, QSI-2026-17973, QSI-2026-17974, QSI-2026-17976, QSI-2026-17968, QSI-2026-17975, QSI-2026-17977, QSI-2026-17969

PQC readiness questionnaire

No readiness questionnaire was completed for this project.

Quantum algorithms relevant to this inventory

Quantum algorithm	Effect	Inventoried algorithms (rows)	What it means for this audit
Shor's algorithm — factoring Q1: quantum computation offline, classical access to the victim	breaks	Paillier (15), RSA (3)	Breaks RSA at every key length: a longer modulus only raises the cost polynomially. Plan migration to ML-KEM (or a hybrid) for key establishment and ML-DSA / SLH-DSA for signatures; start with keys protecting data that must stay confidential for years (harvest now, decrypt later) and with long-lived signatures.

Shor's algorithm — discrete logarithms in finite fields Q1: quantum computation offline, classical access to the victim	breaks	BN254 (alt_bn128) (2), ElGamal (4)	Breaks finite-field Diffie–Hellman and DSA at every size. Move key establishment to ML-KEM (hybrid with X25519 or ECDH during the transition) and signatures to ML-DSA or SLH-DSA.
Shor's algorithm — elliptic-curve discrete logarithms Q1: quantum computation offline, classical access to the victim	breaks	BN254 (alt_bn128) (2), ECDH (5), ECDSA (25), Ed25519 (20), Pedersen commitment (4), Schnorr (BIP-340) (2), Threshold ECDSA (13)	Elliptic-curve keys are expected to fall before RSA keys of comparable classical strength. On blockchains, coins whose public key is already on chain (reused addresses, pay-to-public-key and Taproot outputs) are exposed first; plan the move to post-quantum signatures and avoid key reuse in the meantime.
Grover's algorithm — key search and preimages Q1: quantum computation offline, classical access to the victim	weakens (larger keys restore the margin)	AES-128 (1), AES-192 (1), AES-256 (1), BLAKE2 (1), HKDF (3), HMAC (1), RIPEMD-160 (1), SHA-1 (1), SHA-2 (2), SHA-3 (1)	Not a break. 256-bit keys (AES-256, ChaCha20) keep a comfortable margin; AES-128 meets NIST category 1, while some authorities ask for 256-bit keys in quantum-resistant contexts (see the AES-128 entry). Prefer 256-bit keys for long-lived data; 256-bit hashes need no change for preimage resistance.
Brassard–Høyer–Tapp — collision search Q1: quantum computation offline, classical access to the victim	weakens (larger keys restore the margin)	BLAKE2 (1), RIPEMD-160 (1), SHA-1 (1), SHA-2 (2), SHA-3 (1)	256-bit hashes (SHA-256, SHA3-256) remain adequate for collision resistance; 160-bit hashes are already weak classically (SHA-1 collisions are practical). Use 384/512-bit hashes where NIST categories 4–5 are required.
Quantum lattice sieving Q1: quantum computation offline, classical access to the victim	included in standard parameters	ML-KEM (2)	No change for ML-KEM or ML-DSA at the standard parameter sets. A 2024 claim of a polynomial-time quantum LWE algorithm was withdrawn after a bug was found (see claims).

Effects: breaks — replace the algorithm; weakens — larger keys or outputs restore the margin; included in standard parameters — no action at standard parameter sets; only with superposition queries — not applicable to ordinary deployments.

Limitations and assumptions

- This report presents automated and documented analysis results for the stated scope. It is not a legal opinion, a certification or an attestation of compliance with any standard.
- z is a planning assumption chosen per risk profile, not a prediction. A cryptographically relevant quantum computer is not publicly known to exist today.

Remediation plan

QSI-2026-17972 · P3 · 90 days

short-term risk reduction

Add ECDH usages at source code to the cryptographic inventory with an owner and a data-lifetime estimate; design for crypto-agility (algorithm identifiers, configurable providers).

Rationale	Migration cannot be planned without knowing where and why the algorithm is used.
Expected outcome	Every usage has an owner, a lifetime and a migration path.
Complexity	medium
Dependencies	Access to system owners.
Side effects	None (documentation and design work).
Tests before change	Confirm the inventory entry matches the deployed configuration.
Tests after change	Inventory review signed off by the system owner.
Closure criteria	Inventory entry with owner, lifetime and target algorithm exists.

QSI-2026-17967 · P3 · 90 days

short-term risk reduction

Add Paillier usages at source code to the cryptographic inventory with an owner and a data-lifetime estimate; design for crypto-agility (algorithm identifiers, configurable providers).

Rationale	Migration cannot be planned without knowing where and why the algorithm is used.
Expected outcome	Every usage has an owner, a lifetime and a migration path.
Complexity	medium
Dependencies	Access to system owners.
Side effects	None (documentation and design work).
Tests before change	Confirm the inventory entry matches the deployed configuration.
Tests after change	Inventory review signed off by the system owner.
Closure criteria	Inventory entry with owner, lifetime and target algorithm exists.

QSI-2026-17970 · P3 · 90 days

short-term risk reduction

Add Threshold ECDSA usages at source code to the cryptographic inventory with an owner and a data-lifetime estimate; design for crypto-agility (algorithm identifiers, configurable providers).

Rationale	Migration cannot be planned without knowing where and why the algorithm is used.
Expected outcome	Every usage has an owner, a lifetime and a migration path.
Complexity	medium
Dependencies	Access to system owners.
Side effects	None (documentation and design work).
Tests before change	Confirm the inventory entry matches the deployed configuration.
Tests after change	Inventory review signed off by the system owner.

Closure criteria	Inventory entry with owner, lifetime and target algorithm exists.

QSI-2026-17971 · P3 · 90 days

short-term risk reduction

Add Ed25519 usages at source code to the cryptographic inventory with an owner and a data-lifetime estimate; design for crypto-agility (algorithm identifiers, configurable providers).

Rationale	Migration cannot be planned without knowing where and why the algorithm is used.
Expected outcome	Every usage has an owner, a lifetime and a migration path.
Complexity	medium
Dependencies	Access to system owners.
Side effects	None (documentation and design work).
Tests before change	Confirm the inventory entry matches the deployed configuration.
Tests after change	Inventory review signed off by the system owner.
Closure criteria	Inventory entry with owner, lifetime and target algorithm exists.

QSI-2026-17973 · P3 · 90 days

short-term risk reduction

Add Pedersen commitment usages at source code to the cryptographic inventory with an owner and a data-lifetime estimate; design for crypto-agility (algorithm identifiers, configurable providers).

Rationale	Migration cannot be planned without knowing where and why the algorithm is used.
Expected outcome	Every usage has an owner, a lifetime and a migration path.
Complexity	medium
Dependencies	Access to system owners.
Side effects	None (documentation and design work).
Tests before change	Confirm the inventory entry matches the deployed configuration.
Tests after change	Inventory review signed off by the system owner.
Closure criteria	Inventory entry with owner, lifetime and target algorithm exists.

QSI-2026-17974 · P3 · 90 days

short-term risk reduction

Add ECDSA usages at source code to the cryptographic inventory with an owner and a data-lifetime estimate; design for crypto-agility (algorithm identifiers, configurable providers).

Rationale	Migration cannot be planned without knowing where and why the algorithm is used.
Expected outcome	Every usage has an owner, a lifetime and a migration path.
Complexity	medium
Dependencies	Access to system owners.
Side effects	None (documentation and design work).
Tests before change	Confirm the inventory entry matches the deployed configuration.
Tests after change	Inventory review signed off by the system owner.

Closure criteria	Inventory entry with owner, lifetime and target algorithm exists.

QSI-2026-17976 · P3 · 90 days

short-term risk reduction

Add ECDSA usages at source code to the cryptographic inventory with an owner and a data-lifetime estimate; design for crypto-agility (algorithm identifiers, configurable providers).

Rationale	Migration cannot be planned without knowing where and why the algorithm is used.
Expected outcome	Every usage has an owner, a lifetime and a migration path.
Complexity	medium
Dependencies	Access to system owners.
Side effects	None (documentation and design work).
Tests before change	Confirm the inventory entry matches the deployed configuration.
Tests after change	Inventory review signed off by the system owner.
Closure criteria	Inventory entry with owner, lifetime and target algorithm exists.

QSI-2026-17968 · P3 · 90 days

short-term risk reduction

Add ECDSA usages at source code to the cryptographic inventory with an owner and a data-lifetime estimate; design for crypto-agility (algorithm identifiers, configurable providers).

Rationale	Migration cannot be planned without knowing where and why the algorithm is used.
Expected outcome	Every usage has an owner, a lifetime and a migration path.
Complexity	medium
Dependencies	Access to system owners.
Side effects	None (documentation and design work).
Tests before change	Confirm the inventory entry matches the deployed configuration.
Tests after change	Inventory review signed off by the system owner.
Closure criteria	Inventory entry with owner, lifetime and target algorithm exists.

QSI-2026-17975 · P3 · 90 days

short-term risk reduction

Add Ed25519 usages at source code to the cryptographic inventory with an owner and a data-lifetime estimate; design for crypto-agility (algorithm identifiers, configurable providers).

Rationale	Migration cannot be planned without knowing where and why the algorithm is used.
Expected outcome	Every usage has an owner, a lifetime and a migration path.
Complexity	medium
Dependencies	Access to system owners.
Side effects	None (documentation and design work).
Tests before change	Confirm the inventory entry matches the deployed configuration.
Tests after change	Inventory review signed off by the system owner.

Closure criteria	Inventory entry with owner, lifetime and target algorithm exists.

QSI-2026-17977 · P3 · 90 days

short-term risk reduction

Add RSA usages at source code to the cryptographic inventory with an owner and a data-lifetime estimate; design for crypto-agility (algorithm identifiers, configurable providers).

Rationale	Migration cannot be planned without knowing where and why the algorithm is used.
Expected outcome	Every usage has an owner, a lifetime and a migration path.
Complexity	medium
Dependencies	Access to system owners.
Side effects	None (documentation and design work).
Tests before change	Confirm the inventory entry matches the deployed configuration.
Tests after change	Inventory review signed off by the system owner.
Closure criteria	Inventory entry with owner, lifetime and target algorithm exists.

QSI-2026-17969 · P3 · 90 days

short-term risk reduction

Add Schnorr (BIP-340) usages at source code to the cryptographic inventory with an owner and a data-lifetime estimate; design for crypto-agility (algorithm identifiers, configurable providers).

Rationale	Migration cannot be planned without knowing where and why the algorithm is used.
Expected outcome	Every usage has an owner, a lifetime and a migration path.
Complexity	medium
Dependencies	Access to system owners.
Side effects	None (documentation and design work).
Tests before change	Confirm the inventory entry matches the deployed configuration.
Tests after change	Inventory review signed off by the system owner.
Closure criteria	Inventory entry with owner, lifetime and target algorithm exists.

QSI-2026-17972 · P4 · 90 days

root-cause fix

Plan migration of ECDH to Hybrid key establishment with ML-KEM (FIPS 203), e.g. X25519MLKEM768 in TLS 1.3 or mlkem768x25519-sha256 in SSH (or a hybrid scheme) once supported by your libraries, protocols and counterparties.

Rationale	Removes dependence on a quantum-vulnerable public-key primitive.
Expected outcome	The asset uses a NIST-standardized post-quantum or hybrid algorithm.
Complexity	high
Dependencies	Library/protocol support (e.g. OpenSSL ≥ 3.5, HSM firmware), interoperability with peers.
Side effects	Larger keys/signatures, possible performance and compatibility impact.
Tests before change	Interoperability tests in a staging environment.
Tests after change	Verify the negotiated/used algorithm on the production asset.
Closure criteria	

	Re-audit shows Hybrid key establishment with ML-KEM (FIPS 203), e.g. X25519MLKEM768 in TLS 1.3 or mlkem768x25519-sha256 in SSH or a hybrid scheme in use.

QSI-2026-17967 · P4 · 90 days

root-cause fix

Plan migration of Paillier to No standardized post-quantum replacement. Plan threshold schemes over post-quantum signatures as they mature (NIST threshold call, IR 8214C), or protocols that avoid Paillier (oblivious-transfer based) (or a hybrid scheme) once supported by your libraries, protocols and counterparties.

Rationale	Removes dependence on a quantum-vulnerable public-key primitive.
Expected outcome	The asset uses a NIST-standardized post-quantum or hybrid algorithm.
Complexity	high
Dependencies	Library/protocol support (e.g. OpenSSL ≥ 3.5, HSM firmware), interoperability with peers.
Side effects	Larger keys/signatures, possible performance and compatibility impact.
Tests before change	Interoperability tests in a staging environment.
Tests after change	Verify the negotiated/used algorithm on the production asset.
Closure criteria	Re-audit shows No standardized post-quantum replacement. Plan threshold schemes over post-quantum signatures as they mature (NIST threshold call, IR 8214C), or protocols that avoid Paillier (oblivious-transfer based) or a hybrid scheme in use.

QSI-2026-17970 · P4 · 90 days

root-cause fix

Plan migration of Threshold ECDSA to The signature scheme is fixed by the blockchain or verifier. Track chain-level post-quantum proposals and threshold post-quantum signatures (NIST IR 8214C); keep key-share refresh and crypto-agility in the custody design (or a hybrid scheme) once supported by your libraries, protocols and counterparties.

Rationale	Removes dependence on a quantum-vulnerable public-key primitive.
Expected outcome	The asset uses a NIST-standardized post-quantum or hybrid algorithm.
Complexity	high
Dependencies	Library/protocol support (e.g. OpenSSL ≥ 3.5, HSM firmware), interoperability with peers.
Side effects	Larger keys/signatures, possible performance and compatibility impact.
Tests before change	Interoperability tests in a staging environment.
Tests after change	Verify the negotiated/used algorithm on the production asset.
Closure criteria	Re-audit shows The signature scheme is fixed by the blockchain or verifier. Track chain-level post-quantum proposals and threshold post-quantum signatures (NIST IR 8214C); keep key-share refresh and crypto-agility in the custody design or a hybrid scheme in use.

QSI-2026-17971 · P4 · 90 days root-cause fix

Plan migration of Ed25519 to ML-DSA (FIPS 204) or SLH-DSA (FIPS 205), in a hybrid/ composite form where the ecosystem supports it (or a hybrid scheme) once supported by your libraries, protocols and counterparties.

Rationale	Removes dependence on a quantum-vulnerable public-key primitive.
Expected outcome	The asset uses a NIST-standardized post-quantum or hybrid algorithm.
Complexity	high
Dependencies	Library/protocol support (e.g. OpenSSL ≥ 3.5, HSM firmware), interoperability with peers.
Side effects	Larger keys/signatures, possible performance and compatibility impact.
Tests before change	Interoperability tests in a staging environment.
Tests after change	Verify the negotiated/used algorithm on the production asset.
Closure criteria	Re-audit shows ML-DSA (FIPS 204) or SLH-DSA (FIPS 205), in a hybrid/ composite form where the ecosystem supports it or a hybrid scheme in use.

QSI-2026-17973 · P4 · 90 days root-cause fix

Plan migration of Pedersen commitment to (or a hybrid scheme) once supported by your libraries, protocols and counterparties.

Rationale	Removes dependence on a quantum-vulnerable public-key primitive.
Expected outcome	The asset uses a NIST-standardized post-quantum or hybrid algorithm.
Complexity	high
Dependencies	Library/protocol support (e.g. OpenSSL ≥ 3.5, HSM firmware), interoperability with peers.
Side effects	Larger keys/signatures, possible performance and compatibility impact.
Tests before change	Interoperability tests in a staging environment.
Tests after change	Verify the negotiated/used algorithm on the production asset.
Closure criteria	Re-audit shows or a hybrid scheme in use.

QSI-2026-17974 · P4 · 90 days root-cause fix

Plan migration of ECDSA to ML-DSA (FIPS 204) or SLH-DSA (FIPS 205), in a hybrid/ composite form where the ecosystem supports it (or a hybrid scheme) once supported by your libraries, protocols and counterparties.

Rationale	Removes dependence on a quantum-vulnerable public-key primitive.
Expected outcome	The asset uses a NIST-standardized post-quantum or hybrid algorithm.
Complexity	high
Dependencies	Library/protocol support (e.g. OpenSSL ≥ 3.5, HSM firmware), interoperability with peers.
Side effects	Larger keys/signatures, possible performance and compatibility impact.
Tests before change	Interoperability tests in a staging environment.
Tests after change	Verify the negotiated/used algorithm on the production asset.
Closure criteria	Re-audit shows ML-DSA (FIPS 204) or SLH-DSA (FIPS 205), in a hybrid/ composite form where the ecosystem supports it or a hybrid scheme in use.

QSI-2026-17976 · P4 · 90 days root-cause fix

Plan migration of ECDSA to ML-DSA (FIPS 204) or SLH-DSA (FIPS 205), in a hybrid/ composite form where the ecosystem supports it (or a hybrid scheme) once supported by your libraries, protocols and counterparties.

Rationale	Removes dependence on a quantum-vulnerable public-key primitive.
Expected outcome	The asset uses a NIST-standardized post-quantum or hybrid algorithm.
Complexity	high
Dependencies	Library/protocol support (e.g. OpenSSL ≥ 3.5, HSM firmware), interoperability with peers.
Side effects	Larger keys/signatures, possible performance and compatibility impact.
Tests before change	Interoperability tests in a staging environment.
Tests after change	Verify the negotiated/used algorithm on the production asset.
Closure criteria	Re-audit shows ML-DSA (FIPS 204) or SLH-DSA (FIPS 205), in a hybrid/ composite form where the ecosystem supports it or a hybrid scheme in use.

QSI-2026-17968 · P4 · 90 days root-cause fix

Plan migration of ECDSA to ML-DSA (FIPS 204) or SLH-DSA (FIPS 205), in a hybrid/ composite form where the ecosystem supports it (or a hybrid scheme) once supported by your libraries, protocols and counterparties.

Rationale	Removes dependence on a quantum-vulnerable public-key primitive.
Expected outcome	The asset uses a NIST-standardized post-quantum or hybrid algorithm.
Complexity	high
Dependencies	Library/protocol support (e.g. OpenSSL ≥ 3.5, HSM firmware), interoperability with peers.
Side effects	Larger keys/signatures, possible performance and compatibility impact.
Tests before change	Interoperability tests in a staging environment.
Tests after change	Verify the negotiated/used algorithm on the production asset.
Closure criteria	Re-audit shows ML-DSA (FIPS 204) or SLH-DSA (FIPS 205), in a hybrid/ composite form where the ecosystem supports it or a hybrid scheme in use.

QSI-2026-17975 · P4 · 90 days root-cause fix

Plan migration of Ed25519 to ML-DSA (FIPS 204) or SLH-DSA (FIPS 205), in a hybrid/ composite form where the ecosystem supports it (or a hybrid scheme) once supported by your libraries, protocols and counterparties.

Rationale	Removes dependence on a quantum-vulnerable public-key primitive.
Expected outcome	The asset uses a NIST-standardized post-quantum or hybrid algorithm.
Complexity	high
Dependencies	Library/protocol support (e.g. OpenSSL ≥ 3.5, HSM firmware), interoperability with peers.
Side effects	Larger keys/signatures, possible performance and compatibility impact.
Tests before change	Interoperability tests in a staging environment.
Tests after change	Verify the negotiated/used algorithm on the production asset.
Closure criteria	

	Re-audit shows ML-DSA (FIPS 204) or SLH-DSA (FIPS 205), in a hybrid/ composite form where the ecosystem supports it or a hybrid scheme in use.

QSI-2026-17977 · P4 · 90 days

root-cause fix

Plan migration of RSA to ML-DSA (FIPS 204) or SLH-DSA (FIPS 205), in a hybrid/ composite form where the ecosystem supports it (or a hybrid scheme) once supported by your libraries, protocols and counterparties.

Rationale	Removes dependence on a quantum-vulnerable public-key primitive.
Expected outcome	The asset uses a NIST-standardized post-quantum or hybrid algorithm.
Complexity	high
Dependencies	Library/protocol support (e.g. OpenSSL ≥ 3.5, HSM firmware), interoperability with peers.
Side effects	Larger keys/signatures, possible performance and compatibility impact.
Tests before change	Interoperability tests in a staging environment.
Tests after change	Verify the negotiated/used algorithm on the production asset.
Closure criteria	Re-audit shows ML-DSA (FIPS 204) or SLH-DSA (FIPS 205), in a hybrid/ composite form where the ecosystem supports it or a hybrid scheme in use.

QSI-2026-17969 · P4 · 90 days

root-cause fix

Plan migration of Schnorr (BIP-340) to (or a hybrid scheme) once supported by your libraries, protocols and counterparties.

Rationale	Removes dependence on a quantum-vulnerable public-key primitive.
Expected outcome	The asset uses a NIST-standardized post-quantum or hybrid algorithm.
Complexity	high
Dependencies	Library/protocol support (e.g. OpenSSL ≥ 3.5, HSM firmware), interoperability with peers.
Side effects	Larger keys/signatures, possible performance and compatibility impact.
Tests before change	Interoperability tests in a staging environment.
Tests after change	Verify the negotiated/used algorithm on the production asset.
Closure criteria	Re-audit shows or a hybrid scheme in use.

Priorities for 30, 60 and 90 days

30 days

Priority	ID	Action	Type
None			

60 days

Priority	ID	Action	Type
None			

90 days

Priority	ID	Action	Type
P3	QSI-2026-17972	Add ECDH usages at source code to the cryptographic inventory with an owner and a data-lifetime estimate; design for crypto-agility (algorithm identifiers, configurable providers).	short-term risk reduction
P3	QSI-2026-17967	Add Paillier usages at source code to the cryptographic inventory with an owner and a data-lifetime estimate; design for crypto-agility (algorithm identifiers, configurable providers).	short-term risk reduction
P3	QSI-2026-17970	Add Threshold ECDSA usages at source code to the cryptographic inventory with an owner and a data-lifetime estimate; design for crypto-agility (algorithm identifiers, configurable providers).	short-term risk reduction
P3	QSI-2026-17971	Add Ed25519 usages at source code to the cryptographic inventory with an owner and a data-lifetime estimate; design for crypto-agility (algorithm identifiers, configurable providers).	short-term risk reduction
P3	QSI-2026-17973	Add Pedersen commitment usages at source code to the cryptographic inventory with an owner and a data-lifetime estimate; design for crypto-agility (algorithm identifiers, configurable providers).	short-term risk reduction
P3	QSI-2026-17974	Add ECDSA usages at source code to the cryptographic inventory with an owner and a data-lifetime estimate; design for crypto-agility (algorithm identifiers, configurable providers).	short-term risk reduction
P3	QSI-2026-17976	Add ECDSA usages at source code to the cryptographic inventory with an owner and a data-lifetime estimate; design for crypto-agility (algorithm identifiers, configurable providers).	short-term risk reduction
P3	QSI-2026-17968	Add ECDSA usages at source code to the cryptographic inventory with an owner and a data-lifetime estimate; design for crypto-agility (algorithm identifiers, configurable providers).	short-term risk reduction
P3	QSI-2026-17975	Add Ed25519 usages at source code to the cryptographic inventory with an owner and a data-lifetime estimate; design for crypto-agility (algorithm identifiers, configurable providers).	short-term risk reduction
P3	QSI-2026-17977	Add RSA usages at source code to the cryptographic inventory with an owner and a data-lifetime estimate; design for crypto-agility (algorithm identifiers, configurable providers).	short-term risk reduction

P3	QSI-2026-17969	Add Schnorr (BIP-340) usages at source code to the cryptographic inventory with an owner and a data-lifetime estimate; design for crypto-agility (algorithm identifiers, configurable providers).	short-term risk reduction
P4	QSI-2026-17972	Plan migration of ECDH to Hybrid key establishment with ML-KEM (FIPS 203), e.g. X25519MLKEM768 in TLS 1.3 or mlkem768x25519-sha256 in SSH (or a hybrid scheme) once supported by your libraries, protocols and counterparties.	root-cause fix
P4	QSI-2026-17967	Plan migration of Paillier to No standardized post-quantum replacement. Plan threshold schemes over post-quantum signatures as they mature (NIST threshold call, IR 8214C), or protocols that avoid Paillier (oblivious-transfer based) (or a hybrid scheme) once supported by your libraries, protocols and counterparties.	root-cause fix
P4	QSI-2026-17970	Plan migration of Threshold ECDSA to The signature scheme is fixed by the blockchain or verifier. Track chain-level post-quantum proposals and threshold post-quantum signatures (NIST IR 8214C); keep key-share refresh and crypto-agility in the custody design (or a hybrid scheme) once supported by your libraries, protocols and counterparties.	root-cause fix
P4	QSI-2026-17971	Plan migration of Ed25519 to ML-DSA (FIPS 204) or SLH-DSA (FIPS 205), in a hybrid/composite form where the ecosystem supports it (or a hybrid scheme) once supported by your libraries, protocols and counterparties.	root-cause fix
P4	QSI-2026-17973	Plan migration of Pedersen commitment to (or a hybrid scheme) once supported by your libraries, protocols and counterparties.	root-cause fix
P4	QSI-2026-17974	Plan migration of ECDSA to ML-DSA (FIPS 204) or SLH-DSA (FIPS 205), in a hybrid/composite form where the ecosystem supports it (or a hybrid scheme) once supported by your libraries, protocols and counterparties.	root-cause fix
P4	QSI-2026-17976	Plan migration of ECDSA to ML-DSA (FIPS 204) or SLH-DSA (FIPS 205), in a hybrid/composite form where the ecosystem supports it (or a hybrid scheme) once supported by your libraries, protocols and counterparties.	root-cause fix
P4	QSI-2026-17968	Plan migration of ECDSA to ML-DSA (FIPS 204) or SLH-DSA (FIPS 205), in a hybrid/composite form where the ecosystem supports it (or a hybrid scheme) once supported by your libraries, protocols and counterparties.	root-cause fix
P4	QSI-2026-17975	Plan migration of Ed25519 to ML-DSA (FIPS 204) or SLH-DSA (FIPS 205), in a hybrid/composite form where the ecosystem supports it (or a hybrid scheme) once supported by your libraries, protocols and counterparties.	root-cause fix
P4	QSI-2026-17977	Plan migration of RSA to ML-DSA (FIPS 204) or SLH-DSA (FIPS 205), in a hybrid/composite form where the ecosystem supports it (or a hybrid scheme) once supported by your libraries, protocols and counterparties.	root-cause fix
P4	QSI-2026-17969	Plan migration of Schnorr (BIP-340) to (or a hybrid scheme) once supported by your libraries, protocols and counterparties.	root-cause fix

Verification after remediation

ID	Retest procedure
QSI-2026-17972	Re-run the inventory after refactoring.
QSI-2026-17967	Re-run the inventory after refactoring.
QSI-2026-17970	Re-run the inventory after refactoring.
QSI-2026-17971	Re-run the inventory after refactoring.
QSI-2026-17973	Re-run the inventory after refactoring.
QSI-2026-17974	Re-run the inventory after refactoring.
QSI-2026-17976	Re-run the inventory after refactoring.
QSI-2026-17968	Re-run the inventory after refactoring.
QSI-2026-17975	Re-run the inventory after refactoring.
QSI-2026-17977	Re-run the inventory after refactoring.
QSI-2026-17969	Re-run the inventory after refactoring.

Tools used

Tool	Version
blockchain	1.0.0
certificates	1.2.0
chain_map	1.0.0
configs	1.1.0
dependencies	1.3.0
inventory_document	1.1.0
solidity	1.3.0
source_code	1.4.0
tls_code	1.1.0
tls_live	1.0.0
qsi-engine	1.3.0
OSV.dev API	v1

Sources and normative documents

Reviewed: 2026-10-13

1. A. Becker, L. Ducas, N. Gama, T. Laarhoven — New directions in nearest neighbor searching with applications to lattice sieving (SODA 2016; IACR ePrint 2015/1128) — IACR ePrint. https://eprint.iacr.org/2015/1128 (peer-reviewed article: classical sieving in 2^{0.292n + o(n)})
2. A. Chailloux, J. Loyer — Lattice sieving via quantum random walks (ASIACRYPT 2021; IACR ePrint 2021/570) — IACR ePrint. https://eprint.iacr.org/2021/570 (peer-reviewed article: 2^{0.2570d + o(d)}, previously 2^{0.2653d + o(d)} (Laarhoven))
3. A. Chailloux, M. Naya-Plasencia, A. Schrottenloher — An Efficient Quantum Collision Search Algorithm and Implications on Symmetric Cryptography (ASIACRYPT 2017; IACR ePrint 2017/847) — IACR ePrint. https://eprint.iacr.org/2017/847 (peer-reviewed article: Õ(2^{2n/5}) time, O(n) qubits, Õ(2^{n/5}) classical memory)
4. C. Chevignard, P.-A. Fouque, A. Schrottenloher — Reducing the Number of Qubits in Quantum Discrete Logarithms on Elliptic Curves (IACR ePrint 2026/280) — IACR ePrint. https://eprint.iacr.org/2026/280 (revision of a EUROCRYPT 2026 paper: 3.12n + o(n) qubits; for n = 256, 1193 qubits and 22 runs of 2^38.98 Toffoli gates)
5. C. Gidney — How to factor 2048 bit RSA integers with less than a million noisy qubits (arXiv:2505.15917) — arXiv. https://arxiv.org/abs/2505.15917 (preprint (2025-05-21): < 1 million noisy qubits, < 1 week, 0.1% gate error, 1 µs surface-code cycle)
6. C. Gidney, M. Ekerå — How to factor 2048 bit RSA integers in 8 hours using 20 million noisy qubits (Quantum 5, 433) — Quantum. https://doi.org/10.22331/q-2021-04-15-433 (peer-reviewed article (2021): 10^-3 gate error, 1 µs cycle, 10 µs reaction time)
7. C. Zalka — Grover's quantum searching algorithm is optimal (Phys. Rev. A 60, 2746, 1999; arXiv:quant-ph/9711070) — APS. https://doi.org/10.1103/PhysRevA.60.2746 (peer-reviewed article: optimal for any success probability; parallel search gains no more than splitting the space)
8. CRYSTALS-Kyber — Algorithm Specifications and Supporting Documentation (round 3, 2021-08-04) — CRYSTALS team. https://pq-crystals.org/kyber/data/kyber-specification-round3-20210804.pdf (NIST round-3 submission: core-SVP cost 2^{0.292β} classical, 2^{0.265β} quantum; Kyber768 166 quantum bits)
9. Common Vulnerability Scoring System v3.1: Specification Document — FIRST. https://www.first.org/cvss/v3.1/specification-document (final)
10. D. J. Bernstein — Cost analysis of hash collisions: Will quantum computers make SHARCS obsolete? (2009) — cr.yp.to. https://cr.yp.to/hash/collisioncost-20090823.pdf (paper dated 2009-08-23)
11. D. Litinski — How to compute a 256-bit elliptic curve private key with only 50 million Toffoli gates (arXiv:2306.08585) — arXiv. https://arxiv.org/abs/2306.08585 (preprint (2023-06-14): 6000 modules × 1152 physical qubits, one key per 10 minutes under its architecture assumptions)
12. FIPS 203 — Module-Lattice-Based Key-Encapsulation Mechanism Standard (ML-KEM) — NIST. https://csrc.nist.gov/pubs/fips/203/final (final (August 2024))
13. FIPS 204 — Module-Lattice-Based Digital Signature Standard (ML-DSA) — NIST. https://csrc.nist.gov/pubs/fips/204/final (final (August 2024))
14. FIPS 205 — Stateless Hash-Based Digital Signature Standard (SLH-DSA) — NIST. https://csrc.nist.gov/pubs/fips/205/final (final (August 2024))
15. G. Brassard, P. Høyer, A. Tapp — Quantum Algorithm for the Collision Problem (LATIN '98; arXiv:quant-ph/9705002) — Springer / arXiv. https://arxiv.org/abs/quant-ph/9705002 (peer-reviewed article: collisions of r-to-one functions in O((N/r)^{1/3}) expected evaluations)
16. J. Proos, C. Zalka — Shor's discrete logarithm quantum algorithm for elliptic curves (Quantum Inf. Comput. 3(4), 2003; arXiv:quant-ph/0301141) — Quantum Information & Computation. https://doi.org/10.26421/QIC3.4-3 (peer-reviewed article)
17. L. K. Grover — A fast quantum mechanical algorithm for database search (STOC 1996) — ACM. https://doi.org/10.1145/237814.237866 (peer-reviewed article)
18. M. Amy et al. — Estimating the cost of generic quantum pre-image attacks on SHA-2 and SHA-3 (SAC 2016; arXiv:1603.09383) — Springer / arXiv. https://arxiv.org/abs/1603.09383 (peer-reviewed article: SHA-256 about 2^153.8 surface-code cycles on 2^12.6 logical qubits; SHA3-256 about 2^146.5 cycles on 2^20)
19. M. Cain et al. — Shor's algorithm is possible with as few as 10,000 reconfigurable atomic qubits (arXiv:2603.28627) — arXiv. https://arxiv.org/abs/2603.28627 (preprint (2026-03-30): P-256 in a few days with 26,000 physical neutral-atom qubits; RSA-2048 one to two orders of magnitude longer)
20. M. Ekerå, J. Gärtner — A high-level comparison of state-of-the-art quantum algorithms for breaking asymmetric cryptography (arXiv:2405.14381) — arXiv. https://arxiv.org/abs/2405.14381 (preprint (2024-05-23): Regev-style algorithms show no overall advantage yet for cryptographic RSA and finite-field sizes)

21. M. Mosca — Cybersecurity in an Era with Quantum Computers: Will We Be Ready? (IEEE Security & Privacy, 2018) — IEEE. https://doi.org/10.1109/MSP.2018.3761723 (peer-reviewed article; source of the x + y > z migration inequality)
22. M. Roetteler, M. Naehrig, K. Svore, K. Lauter — Quantum resource estimates for computing elliptic curve discrete logarithms (ASIACRYPT 2017) — IACR / arXiv. https://arxiv.org/abs/1706.06752 (peer-reviewed article: at most 9n + 2⌈log2 n⌉ + 10 qubits and 448 n^3 log2 n + 4090 n^3 Toffoli gates)
23. NIST IR 8547 — Transition to Post-Quantum Cryptography Standards — NIST. https://csrc.nist.gov/pubs/ir/8547/final (final (2026-10-27; the initial public draft of November 2024 is obsoleted). Tables 2 and 4: ECDSA, EdDSA and RSA signatures, finite-field and elliptic-curve DH and MQV, and RSA key establishment are deprecated after 2030 and disallowed after 2035 at every key size — the draft deprecated only the 112-bit level. A composite (hybrid) key establishment stays FIPS 140-validatable while one input comes from an approved scheme. Repeats the federal deadlines of OMB M-26-15: post-quantum key establishment by 2030-12-31 and signatures by 2031-12-31 for high value assets and high impact systems)
24. NIST — Post-Quantum Cryptography Standardization: Evaluation Criteria, Security (Call for Proposals, Section 4.A.5) — NIST. https://csrc.nist.gov/Projects/Post-Quantum-Cryptography/Post-Quantum-Cryptography-Standardization/Evaluation-Criteria/Security-(Evaluation-Criteria) (security categories: AES-128 key search 2^170/MAXDEPTH quantum gates, AES-192 2^233/MAXDEPTH, AES-256 2^298/MAXDEPTH; MAXDEPTH 2^40–2^96)
25. P. W. Shor — Polynomial-Time Algorithms for Prime Factorization and Discrete Logarithms on a Quantum Computer (SIAM J. Comput., 1997) — SIAM. https://doi.org/10.1137/S0097539795293172 (peer-reviewed article)
26. R. Babbush et al. — Securing Elliptic Curve Cryptocurrencies against Quantum Vulnerabilities: Resource Estimates and Mitigations (arXiv:2603.28846) — arXiv. https://arxiv.org/abs/2603.28846 (preprint (2026-03-30, v2 2026-04-15): 256-bit ECDLP with < 1200 logical qubits and < 90 M Toffoli gates (or < 1450 and < 70 M); < 500,000 physical qubits at 10^-3 error, minutes)
27. S. Jaques, M. Naehrig, M. Roetteler, F. Virdia — Implementing Grover oracles for quantum key search on AES and LowMC (EUROCRYPT 2020; arXiv:1910.01700) — Springer / arXiv. https://arxiv.org/abs/1910.01700 (peer-reviewed article: lower cost estimates for the AES key searches that define the NIST categories)

Appendices

A. Cryptographic inventory

Algorithm	Parameter	Quantum status	Classical status	Count	Locations	Examples
RIPEMD-160	RIPEMD-160	weak classically	legacy	1	1	src/cbmpc/crypto/base_hash.cpp:70
SHA-1	SHA-1	weak classically	deprecated	1	1	src/cbmpc/crypto/base_rsa_oaep.cpp:86
AES-192	AES-192	reduced margin (Grover), approved	acceptable	1	1	src/cbmpc/crypto/base.cpp:126
AES-256	AES-256	reduced margin (Grover), approved	acceptable	1	1	src/cbmpc/crypto/base.cpp:128
HKDF		reduced margin (Grover), approved	acceptable	3	3	include-internal/cbmpc/internal/crypto/base_hash.h:351; include-internal/cbmpc/internal/crypto/base_pki.h:57; src/cbmpc/crypto/base_hash.cpp:212
HMAC		reduced margin (Grover), approved	acceptable	1	1	src/cbmpc/crypto/base_hash.cpp:146
AES-128	AES-128	Grover: acceptable to NIST, below ECCG/ANSSI guidance	acceptable	1	1	src/cbmpc/crypto/base.cpp:124
BLAKE2		Grover: acceptable to NIST, below ECCG/ANSSI guidance	acceptable	1	1	src/cbmpc/crypto/base_hash.cpp:68
SHA-2		Grover: acceptable to NIST, below ECCG/ANSSI guidance	acceptable	2	2	include-internal/cbmpc/internal/zk/fischlin.h:49; src/cbmpc/crypto/base_hash.cpp:55
SHA-3		Grover: acceptable to NIST, below ECCG/ANSSI guidance	acceptable	1	1	src/cbmpc/crypto/base_hash.cpp:63

ML-KEM	ML-KEM-768	post-quantum	acceptable	2	2	include-internal/cbmpc/internal/crypto/mlkem768.h; src/cbmpc/crypto/mlkem768.cpp:8
BN254 (alt_bn128)		vulnerable (Shor)	acceptable	2	2	include-internal/cbmpc/internal/crypto/base_bn256.h; src/cbmpc/crypto/base_bn256.cpp
ECDH		vulnerable (Shor)	acceptable	5	5	include-internal/cbmpc/internal/protocol/pve_base.h:213; src/cbmpc/api/pve_base_pke.cpp:325; src/cbmpc/api/pve_batch_ac.cpp:308
ECDSA	secp256k1	vulnerable (Shor)	acceptable	10	10	include-internal/cbmpc/internal/crypto/base_ecc.h:17; include/cbmpc/api/curve.h:10; src/cbmpc/api/curve_util.h:13
ECDSA		vulnerable (Shor)	acceptable	14	14	include-internal/cbmpc/internal/protocol/ecdsa_2p.h; include-internal/cbmpc/internal/protocol/ecdsa_mp.h; include-internal/cbmpc/internal/protocol/hd_keyset_ecdsa_2p.h
ECDSA	P-256	vulnerable (Shor)	acceptable	1	1	include/cbmpc/api/curve.h:9
Ed25519		vulnerable (Shor)	acceptable	7	7	include-internal/cbmpc/internal/crypto/base_eddsa.h; include/cbmpc/api/eddsa_mp.h; include/cbmpc/api/hd_keyset_eddsa_2p.h
Ed25519	Ed25519	vulnerable (Shor)	acceptable	13	13	include-internal/cbmpc/internal/protocol/eddsa.h:6; include-internal/cbmpc/internal/protocol/hd_keyset_eddsa_2p.h:26; include/cbmpc/api/eddsa_2p.h:8
ElGamal		vulnerable (Shor)	deprecated	4	4	include-internal/cbmpc/internal/crypto/elgamal.h; include-internal/cbmpc/internal/zk/zk_elgamal_com.h; src/cbmpc/crypto/elgamal.cpp
Paillier		vulnerable (Shor)	acceptable	15	15	include-internal/cbmpc/internal/crypto/base_bn.h:46; include-internal/cbmpc/internal/crypto/base_paillier.h:8; include-internal/cbmpc/internal/protocol/ecdsa_2p.h:18
Pedersen commitment		vulnerable (Shor)	acceptable	4	4	include-internal/cbmpc/internal/zk/zk_pedersen.h:8; src/cbmpc/protocol/ecdsa_2p.cpp:28; src/cbmpc/zk/zk_paillier.cpp:537
RSA		vulnerable (Shor)	acceptable	3	3	include-internal/cbmpc/internal/crypto/base_rsa.h; src/cbmpc/crypto/base_rsa.cpp:96; src/cbmpc/crypto/base_rsa_oaep.cpp

Schnorr (BIP-340)	vulnerable (Shor)	acceptable	2	2	include-internal/cbmpc/internal/crypto/base_ecc.h:299; src/cbmpc/crypto/base_ecc.cpp:373
Threshold ECDSA	vulnerable (Shor)	acceptable	13	13	include-internal/cbmpc/internal/protocol/ecdsa_2p.h:10; include-internal/cbmpc/internal/protocol/ecdsa_mp.h:9; include-internal/cbmpc/internal/protocol/hd_keyset_ecdsa_2p.h:3

Long lists are grouped here; the full per-file list is in the JSON report, signed with the same key.

B. JSON

qsi.report/1 · SHA-256 2a966078eafc0c75aa33ede65be2e88b49931bcd3069f62145418b9799d8281d

C. Input files

File	Size	SHA-256	Redaction
include-internal/cbmpc/internal/core/convert.h	8184	a56e2e6c773cbb9de2df1dae1b5240c9162c788f2b59d596262f67e417fd9ef5	0
include-internal/cbmpc/internal/core/extended_uint.h	1264	8551e894af07214d5d4faf8fd32eb9c6d8fb5da19097bb2f5d5fcb323484aed0	0
include-internal/cbmpc/internal/core/log.h	2878	52ec905cb9fa56db485bb9ac1e0d5c82dfb63db54b3b4a7aba1120aba12efac9	0
include-internal/cbmpc/internal/core/strext.h	873	f245b9bb300b256ecb1b52bc1ae9f5685411a16ab67724cf60bf16bfe17a2053	0
include-internal/cbmpc/internal/core/utils.h	7111	b98488440036d38243111e9d5126426e71a0481921bf0ae35b099dd3af572413	0
include-internal/cbmpc/internal/crypto/base.h	5757	def0f4da84c6da78a3ec08c2a1dc2f00f71bf0fb4bf3d788ea9dfff923b7ba01	0
include-internal/cbmpc/internal/crypto/base_bn.h	8887	2ab03b1f64160824d980856f8bb4d91a3413b293c5ff6b897e6ddb825bdef696	0
include-internal/cbmpc/internal/crypto/base_bn256.h	4992	253d3c7e26e94204dad124a6e6450db90ae1dc3617c30d56c25d300b37bf0ff1	0
include-internal/cbmpc/internal/crypto/base_ec_core.h	18124	d675354dcb9d373c9e84a80ea4af72476caaa1c708a36ceed0330798a9c0a0e9	0
include-internal/cbmpc/internal/crypto/base_ecc.h	13930	4622c8393c4f4bf8d3abdc12789b328ec85e725874e01b02df1896b8c5b311d0	0
include-internal/cbmpc/internal/crypto/base_ecc_secp256k1.h	2905	4fd96cb7eca67bfa1627efa01a11f095c5467120c3fca5cda2cce50935884dc2	0
include-internal/cbmpc/internal/crypto/base_eddsa.h	2547	11b91f8dd6e32ed727a8838aae477b5198d73a0f46930c8fbf67fdfde33de3ac	0

include-internal/cbmpc/internal/crypto/base_hash.h	9641	4eea85e07fd6c13ffbc81910fa739f11f7b4b367607592fdfd203379b14caab0	0
include-internal/cbmpc/internal/crypto/base_mod.h	5488	9416b0b19f16e95b1a82029433dc8f2e606cfb21a5e9776f74f1b8b88a6ad2a9	0
include-internal/cbmpc/internal/crypto/base_paillier.h	7140	635074e16e9ac9d0941b425940da73aaa1cfcbf9d9bfc23dbcaa17220462cfb1	0
include-internal/cbmpc/internal/crypto/base_pki.h	7471	98b0c1f3a7cfed44bcf1f4326ca61c7f25f0f196b63c04c50349ca400cff8a83	0
include-internal/cbmpc/internal/crypto/base_rsa.h	4133	d57c2cbddf86fcabca1fece5f47377f3c6593e2bbe1fd0d609ce39f666925d18	0
include-internal/cbmpc/internal/crypto/commitment.h	5024	12acf4a73daffe317049c4adbf897cac2471d3b5399e8ff8a6338397d3763e8a	0
include-internal/cbmpc/internal/crypto/ec25519_core.h	1819	91af646c59ed5ed8b7adfb862229c2569f7f7f7e02b06cbfc322ad6de1cd758d	0
include-internal/cbmpc/internal/crypto/elgamal.h	3841	3e7e1dc52f7c63d54377c18ed4d65cb8e2b7bd01daaf085530e3431ba66b676c	0
include-internal/cbmpc/internal/crypto/lagrange.h	2296	98372b80b7f725bcc14ed22b542e2e4b0fb959393a8c5e0048af309b2d4d1546	0
include-internal/cbmpc/internal/crypto/mlkem768.h	701	f34c16ad0e3074f42661f769d8b68b6b72ef35c431db68982049d8f2816620bd	0
include-internal/cbmpc/internal/crypto/ro.h	4056	a2a83967f8151a94001dd3cb20c359a2946abb0bceb359df96cbf243e6467bb6	0
include-internal/cbmpc/internal/crypto/scope.h	1338	6ee20f03d2bc5e27c80255120ac9d21650e222971584093b821cb2989ce83669	0
include-internal/cbmpc/internal/crypto/secret_sharing.h	6159	183ec4af5557f2176b790d99316b7296041d40dab13c75e712bdd46f4bcb49f8	0
include-internal/cbmpc/internal/crypto/tdh2.h	4119	84dcbc72243ec5d7acbc9e44387a9ea28bfe25478d7dfed9b339463b65d0e4a6	0
include-internal/cbmpc/internal/protocol/agree_random.h	1227	6b3da20d98680a9f583ec4339f34444ad214ac84e1d96ed194a6bf7a29220153	0
include-internal/cbmpc/internal/protocol/committed_broadcast.h	2828	8248d3fd59ab317e917b1a8a7b45500e35e74c587392b028714f95d1912fb872	0
include-internal/cbmpc/internal/protocol/ec_dkg.h	4175	47f244abb153a3bcc5efec66471fb70d0b92d13188783d09bf07c823213ce03d	0
include-internal/cbmpc/internal/protocol/ecdsa_2p.h	4524	bb2d45c7091bcb2dbdc81e77b6712c519093577ceec7a937003e57228bd767bb	0
include-internal/cbmpc/internal/protocol/ecdsa_mp.h	4370	09e920ca00569b73af88dd9ac50b4e809d20e6ef6c57a8ada392a2a40e7ebf3f	0

include-internal/cbmpc/internal/protocol/eddsa.h	802	1bae54da49de50c02f780d2bd27bb548eadc22ad94e095c01ae16b7e3cd34270	0
include-internal/cbmpc/internal/protocol/hd_keyset_ecdsa_2p.h	1460	98cef577118dc981109e7eca78bf1f41d24967f84449bf597008d2c8a69c604c	0
include-internal/cbmpc/internal/protocol/hd_keyset_eddsa_2p.h	1401	0ec98767b365b0bcc4a52f1dbf47fb1096c0a580321abe70532ce3c0efacad91	0
include-internal/cbmpc/internal/protocol/hd_tree_bip32.h	1749	66bc9c67289298cc3d3bae9f1ba2a960aadcdc50e9069105fad3e1fae2edfcad	0
include-internal/cbmpc/internal/protocol/int_commitment.h	847	d64fd9bd118676bcd8f856a70de1bf1678fe9eeea3597f164ac180e67ca4780d	0
include-internal/cbmpc/internal/protocol/mpc_job.h	17919	a93a6744fe1693909d3e46a1f5976961df525f515c6b28f6c65e4094fbf14763	0
include-internal/cbmpc/internal/protocol/ot.h	8615	da042352cfa725c622efe54930f3019ff25ee9668e81cc0586b68c687e67a1e1	0
include-internal/cbmpc/internal/protocol/pve.h	1268	f3d48fad161594f0175ece90e99aa661df33257447229f54ae10ec09f1bf046f	0
include-internal/cbmpc/internal/protocol/pve_ac.h	4481	e6d60929413bf4fa70c899856329d5f096062b0f39fc3d0e74e92c58f94d9824	0
include-internal/cbmpc/internal/protocol/pve_base.h	9109	26dcc28fef1f2733ed7c10f2f9a389df73ecd8cc981358367c67b29d930ebfc1	0
include-internal/cbmpc/internal/protocol/pve_batch.h	2350	140959a47e0bb81fb502192fc4d3c56a4f69b4aae8cd1b642ca8a5dcd6789575	0
include-internal/cbmpc/internal/protocol/schnorr_2p.h	955	26b5a68de67cb25384741b84bf862f3c30ab0f505474cc0b0a5f8fc10b8eb71b	0
include-internal/cbmpc/internal/protocol/schnorr_mp.h	1636	25c8b2c1a79f70349ee2098eb56c8bb6f148598fccc91b214af185a17b0b0c1b	0
include-internal/cbmpc/internal/protocol/sid.h	2398	a13269fefc215f1f5dbddd924174ee1fed95db295d1cdc909c69c5c014bbd589	0
include-internal/cbmpc/internal/protocol/util.h	2083	21d08c60af4b75538821a8ec31f3cd8a50adc6c8753c206837f9f7bb558ea170	0
include-internal/cbmpc/internal/zk/fischlin.h	3695	792546bb45cf6ce43db2bd34723b18da117d1f635a97fe518d09ff02c8fb31b6	0
include-internal/cbmpc/internal/zk/small_primes.h	1046	2159754496de246e69d96310f1f9dacaec9df1f3c04c16385c4bce995ea2e83e	0
include-internal/cbmpc/internal/zk/zk_ec.h	2816	01853d5739fecf852b82e20193aad9faa1a4d38702e4e6dc202d54094b3728e3	0
include-internal/cbmpc/internal/zk/zk_elgamal_com.h	3006	90fc7c4c62e170e4fc2bf0dad335cbf556472bb70f30ae1d39ef37dbb55a5135	0

include-internal/cbmpc/internal/zk/zk_paillier.h	7613	5ad37919ff30625baf38930da6bea9aefe1fb3cddab2a02e52d9e42a6a0f2253	0
include-internal/cbmpc/internal/zk/zk_pedersen.h	4139	899fad68ffd0cc058ea9edabd9505a26a539d2d31e64f3345d976991216bc528	0
include-internal/cbmpc/internal/zk/zk_unknown_order.h	622	f632c986fe305b9253cd61b00bf6ca4e91ae2afd4228d910f7ac3219feb9e1ef	0
include-internal/cbmpc/internal/zk/zk_util.h	1721	5751b4ae4aa64f5fbe7af8802b7a489737f5f042d05873dcee21ca8fec55a69e	0
include/cbmpc/api/curve.h	305	2facde4582730feb655e92033395aada9402fe2c32f78e6ac475bd8324936cad	0
include/cbmpc/api/ecdsa_2p.h	3871	105375859252d5a634822b7af6726a4a80003591cc2c8bcefdb6bf72674a1542	0
include/cbmpc/api/ecdsa_mp.h	6405	ab364b34f5c08cdcc436596ba385938b4853fb25bbc630ef507be7fa21d46588	0
include/cbmpc/api/eddsa_2p.h	3468	16ec1fa4dcb7e197b2ec1edb4f5fee3330b9d4b5016221c0292ca5c9208445d3	0
include/cbmpc/api/eddsa_mp.h	6602	3ab97cfccc9ad4c9ed383358f267e68140e69926bbafa9d98fa10ea2c09d477c	0
include/cbmpc/api/hd_keyset_ecdsa_2p.h	1761	fc16145b6c7db1ebf924e06172dbc041aca2a8b7186a79755d7f2cc88fb36399	0
include/cbmpc/api/hd_keyset_eddsa_2p.h	1946	ae8c48d856ea67d1aed7044aa7ab0df1e682a6a0fd062f8c8114fcbc75ff8070	0
include/cbmpc/api/pve_base_pke.h	7256	9280cee649b4752fc92360b22e6ba7ba8e6a2f588cb3bba2a9280a4135f23c2e	0
include/cbmpc/api/pve_batch_ac.h	6780	3fbe4705e6454184aec00705496ef78bcea0307f975fad7d1d77f0493e57cf8a	0
include/cbmpc/api/pve_batch_single_recipient.h	3445	f98c566cdba6caf7b3d6da68af9a773ae7946dc8f11451af43d573610a54ba57	0
include/cbmpc/api/schnorr_2p.h	3929	5b151a5677a5496d763f4e8f678a78b6b570dd8196d16f7eecd30605da3c5dc1	0
include/cbmpc/api/schnorr_mp.h	7143	39b31ba9980a43fb1fc8ba8a220ef25492b147ae020b1d0e540fe42b2d6bb53b	0
include/cbmpc/api/tdh2.h	4229	4292de2890a66de4ec19bd642ebbb68c0653bfd9e97957dc1d0153dee033308a	0
include/cbmpc/c_api/access_structure.h	2766	e9d53711590e479dd37c19a6c4d82cd08c6e9c1438121edb270c0690a9e71b9e	0
include/cbmpc/c_api/cmem.h	1198	29624c2da9423a7572f131eb244e216c2fe7944dfe59319edb3458b733c56fb4	0
include/cbmpc/c_api/common.h	2499	94bc94a3e819a719afa35151029c8964fb157cd7eb2609d93f257cd975b86746	0
include/cbmpc/c_api/ecdsa_2p.h	4212	88ab538b235f8a78490328bc6bf2ce39657689eab758413d36fdf7b00841f476	0
include/cbmpc/c_api/ecdsa_mp.h	8348	08b76cba5186c15ccfc1c7b6e49c290a4d4ab7c0fda98f3fab66eb3271a9bbed	0

include/cbmpc/c_api/eddsa_2p.h	3582	751f5fe0b4c9bdf3245a51887076846a0e89b0d6fc0ccbebc64c8470c92114f9	0
include/cbmpc/c_api/eddsa_mp.h	8026	22e2811912998b1feb41b8ddb171695f639e00af18c8258ebebe5b1e7de48bb9	0
include/cbmpc/c_api/job.h	2853	b61893a3c68d4ff836d4ffc6ca21bfa2601cc1b8c5161389217505ccaeee8d16	0
include/cbmpc/c_api/pve_base_pke.h	9594	7a93b2954d8f05745ba82a3238fe482f2c87aa593b60bb3f07048151c557b80d	0
include/cbmpc/c_api/pve_batch_ac.h	5993	2468fbb957d0607ea714fe4a5aecb91f8d46871053485c81f9d2490637dffda5	0
include/cbmpc/c_api/pve_batch_single_recipient.h	3786	f5d0f75b826da34508313415d8ce966191e701ce3184b230ee5cb0a3c8a84f43	0
include/cbmpc/c_api/schnorr_2p.h	3659	078fc3e11670dae87921ecc42238204196314aca571f4b328a726d2ea725b9e4	0
include/cbmpc/c_api/schnorr_mp.h	8242	daa14190b82a6adbe781120039be8f5f5d873c55e50d583c26569512d8b06dd6	0
include/cbmpc/c_api/tdh2.h	5404	67aac4a7c9032fa87988d1fdc559ae3b18df5773c4fcd0b59303afb6e0464cf1	0
include/cbmpc/core/access_structure.h	2181	168f318f2676eca879dd6567bc22aad1390c9f0217ce916134ec04a1b8e2a318	0
include/cbmpc/core/access_structure_limits.h	109	f6eb33c9c3f3ab6886e672f6b71ae35e21fd9895433c5d0845ea6036e66f4567	0
include/cbmpc/core/bip32_path.h	383	f404682cee2ab3b94e54ab3a625d74c6c483779aed72389cd63407ad0d3bd954	0
include/cbmpc/core/buf.h	8626	3211ba3cefa7bb2dc584fc4854d146b9830afcaa7040b64f31e4de89875d8c06	0
include/cbmpc/core/buf128.h	3122	8e2bef19a7dcab978acb3c29a992e12072f764b53f449d97e2dc907d5027c35c	0
include/cbmpc/core/buf256.h	1780	5c99e90645842aa88fa75191c7e138fe458b4605ae4b06b112e125aed7ba69e2	0
include/cbmpc/core/error.h	2750	82b6b7a47256c7fab6f46e74313f97291a634811f28cb64dd1486d95628182da	0
include/cbmpc/core/job.h	2073	0c35a15cdae4d5f4450d93e5ec27af30cc5550bf9722da8f2d41016fd71fc85f	0
include/cbmpc/core/macros.h	946	da42b82206cd7ae447f0dbb023494ba8cc4a94f36977faccd8a82e2648d5c50b	0
include/cbmpc/core/precompiled.h	3021	45071365b97849cfe36fea65e1a63b25a09078189e33495006cc592f8c44561a	0
src/cbmpc/api/access_structure_util.h	9006	ceddfd95a56fef01a49c9f9be5d4d02f9fa6f94dc584bf1e911b0289fc1f4580	0
src/cbmpc/api/curve_util.h	1106	2b1ce8031d294bd7721265d8bd13469b0828e5511b10a43ef2ba9cb16f3dd4d6	0
src/cbmpc/api/ecdsa2pc.cpp	13715	2bd6f2c9780b68b323f33f000c019d99aa9ece77fc399fd69a4c418a5b247724	0
src/cbmpc/api/ecdsa_mp.cpp	23511	e8b790be6ff65035680333e944c16aa409fc39b9f3efde09f3e1a034b66fb069	0
src/cbmpc/api/eddsa2pc.cpp	9662	277a7491b190d4e1fbec7aac06aa60e357a4a72d374a5af0d9c8d323344ab2ad	0
src/cbmpc/api/eddsa_mp.cpp	23718	fdc84660705d7dd8168aca64fd9620da0a9f5bc0ae584beded77339b79502e0b	0

src/cbmpc/api/hd_keyset_ecdsa_2p.cpp	9399	46f38a66df82ed9cd573f6887e08a8dd6f32f96cd4fa3d9e0baaa8efa2c9b34a	0
src/cbmpc/api/hd_keyset_eddsa_2p.cpp	8196	db69a2795c6ad2b92dccdb42301e4d58701cfe694787171382580d1f6eac8a5c	0
src/cbmpc/api/hd_keyset_util.h	1102	80b15e70053540d811ad516f0a2c9d20577454365379a737793359870c44884e	0
src/cbmpc/api/job_util.h	2963	0eaf11ceb45fe2a8c36148f925434e2b9b4e55b053f16fac7c023f751d8928c2	0
src/cbmpc/api/mem_util.h	2091	fd6fb01ab217ab64ab6182fe01ee9f656381a6690848ab3f0b11c6506b7063d0	0
src/cbmpc/api/pve_base_pke.cpp	15533	5639e943156dbf5e142c178b07da2c4eb0a5d60bcfa0f61af1b18bc22b830937	0
src/cbmpc/api/pve_batch_ac.cpp	19720	8b8be49db0d9dabae40d79f31809585672d745b3ac0a66147f6bab96a2f7daa3	0
src/cbmpc/api/pve_batch_single_recipient.cpp	12533	c5572970684fdeff67948f2d3e40b6e2777a4fbe0737e70eb334ecaf7cc0e746	0
src/cbmpc/api/pve_internal.h	6257	47bce2585e9a7bf7b3a1939dc6f914f9f4a71a8e745a1dd372bc00ebab713754	0
src/cbmpc/api/schnorr2pc.cpp	10080	9495eab05f3110eaff559f33a89cea322a17fd6c873139300a9ff54b042eaaad	0
src/cbmpc/api/schnorr_mp.cpp	24257	bd909c04140c085cb023ee5fac58ee26b361234b6ce65f395fc0f37defe39bd0	0
src/cbmpc/api/tdh2.cpp	15729	a4ff1563e8b6429c4576c0430a6164510211b943d461362ee0ebd3a7186ae1c8	0
src/cbmpc/c_api/access_structure_adapter.h	4841	08d2877d3dd792e33afd088e767d5925d177be052c50f2023524c0bbf81ece68	0
src/cbmpc/c_api/common.cpp	1592	5280698eda4f9f4e66b6ae8560818f4c8dd2f4f9f7c13ce2957f583ffc70640f	0
src/cbmpc/c_api/ecdsa2pc.cpp	8935	350195de0a3b6dec093519c569d2fb7bb50de40ec80f81f750e6fe2e5cef5a77	0
src/cbmpc/c_api/ecdsa_mp.cpp	14657	ae5651ed5d7de9eea96f9e9b1c9b8f6ce4779bde23df3c7ad5835c584fe57986	0
src/cbmpc/c_api/eddsa2pc.cpp	7405	cac76cf191e1737f82300959bafe1b6d9a73723da0ac752c4fe573764ab576ad	0
src/cbmpc/c_api/eddsa_mp.cpp	14249	7393ff3f085a404140f443da26bae530000d8158963983a77a4eebe9402e9849	0
src/cbmpc/c_api/pve_base_pke.cpp	19582	c6e5ec7ce741d2c32c9895618ec807b02782e502401b759a79a7cd1030c1ba7e	0
src/cbmpc/c_api/pve_batch_ac.cpp	15057	86de96b4539a390203c7c25dd9f452ee31f6d22efe2445135d19fbfb356f9640	0
src/cbmpc/c_api/pve_batch_single_recipient.cpp	9558	c1bf050dfe843b0c9491835b2a4a67d5a87bc31e91b20167c76e18fccb15a40b	0
src/cbmpc/c_api/pve_internal.h	3922	67717ecc213db88a2ceeefeca34434d6ba44e7606d169118a384f4d0c70ae884	0
src/cbmpc/c_api/schnorr2pc.cpp	8125	0ddf4832e2ea31c50a5933a5f0d4b82c7fbbaa50e3de6f4b79f58ec4d8dfe6fc	0

src/cbmpc/c_api/schnorr_mp.cpp	15011	f1c40a8f09a77764fe725b393cdc7c0b4e5af68ec1373471d09a0e43b6105cb4	0
src/cbmpc/c_api/tdh2.cpp	12864	8a7813233276b5b2322215aff73847238307574f781aa9a331e8e619538f38ee	0
src/cbmpc/c_api/transport_adapter.h	3637	b40563601e342dad20c6d714eeb50b71e2a1e17fb3c55ea6e1b06781dd91d199	0
src/cbmpc/c_api/util.h	6137	54e197b005d5bf85a970ffd48c13fa55c1748b8e1a53e8b70cd4d2194e73d6a3	0
src/cbmpc/core/buf.cpp	19249	4f05b7b7f064a8df4fdbe8f73930690073f9bdf7fe644ad8df2fc95974436711	0
src/cbmpc/core/buf128.cpp	8097	ab4b91df60b609f7958c7c9927b1bfac57fef68079ae644be0070555c944d7d6	0
src/cbmpc/core/buf256.cpp	5718	bc92ef88c227313eb5c334e8315985ca4ddc23c0cd543e7bcf3778aa9d688878	0
src/cbmpc/core/convert.cpp	5831	e058331387e5a1467cbc044ad88e4717644b4893d4d251e1268798a4d8c75f05	0
src/cbmpc/core/error.cpp	5599	b32bfc0d066f34f00f5b5e319a04284d35b405ace58c487e0f2105293e024aeb	0
src/cbmpc/core/strext.cpp	3904	d760ebfff69eb90c43825f4c67cd57c619e447baa7219ee06a3f1f675b5874bb	0
src/cbmpc/crypto/base.cpp	8596	dd2af36fb426bc7b3b618d9972a4215e01577766256eac1ed92966b54e57af93	0
src/cbmpc/crypto/base_bn.cpp	21760	fbec856dfe302bc6c8dc4dfdaa52a0f0ee84287ef13634885cf34e1d03ade10e	0
src/cbmpc/crypto/base_bn256.cpp	38165	5aab4b8a2ae1328950c40a1589bee877ecb9468101b0fc7baecd773514e5fec3	0
src/cbmpc/crypto/base_ec_core.cpp	2539	16280192dd3f73e0969ff983499669d5327b215018dace8f4e37eb161e822c6a	0
src/cbmpc/crypto/base_ecc.cpp	35151	dd31645addc8cf00b027fc453868a4aec33a826a95a7acca172dd3af54ca97ec	0
src/cbmpc/crypto/base_ecc_secp256k1.cpp	15422	31cabe4ca85327316c07f9865c9efa3a81c98a630bc3276806d3dd96cf400c73	0
src/cbmpc/crypto/base_eddsa.cpp	8170	45697966a1eb28d114a3f26c52dbd3d97abef3ed0bd13a6da051f2825f70f99d	0
src/cbmpc/crypto/base_hash.cpp	12718	6797b8c75aaaf50070644024ab4df41ade4e6a676dc53cba207929a5e334af86	0
src/cbmpc/crypto/base_mod.cpp	16690	8390bd8433403219ac67b744ca8c1f04b919376f75b48e12aaebe1044a551738	0
src/cbmpc/crypto/base_paillier.cpp	11598	bc74a8ec5b010ffa69aaeabeb2edb7dd075972229f2997cb48b6bc38106de467	0
src/cbmpc/crypto/base_rsa.cpp	13948	ce1f7e2af4ab105d95931ebce00de933dc0718afbb555bea8cac329324b39cf4	0
src/cbmpc/crypto/base_rsa_oaep.cpp	7631	488a05f19bfe3be1bb45df021c887b46f88af1930dbe88f4412830a77a70cd19	0
src/cbmpc/crypto/drbg.cpp	2236	4e3fbc5382e267539b72d1556890ad8d3ffb15509db8ba4f6d3609f4a75b7708	0
src/cbmpc/crypto/ec25519_core.cpp	32300	fcf18843c539fff85668d46a094aa97b4ba6014fdb3005bbf08ce87804fa4d61	0
src/cbmpc/crypto/elgamal.cpp	4096	44e90812713ef86a0f2ef69a55d8fd53447a6aee718fe91410a73a3e27b0ab16	0

src/cbmpc/crypto/lagrange.cpp	6291	4ed9ad1c1a9f9a3597cd49fc2034d9b6c0986b8d92fb7b1109a87f2dda24772c	0
src/cbmpc/crypto/mlkem768.cpp	3026	4078550dd5d763189b297626094dc68bca380049f1f36a8b123a0a0272576792	0
src/cbmpc/crypto/ro.cpp	4612	b594d9dff0634336ee222e03972a16e871028b334c15cbd03b74de7bcc74bb41	0
src/cbmpc/crypto/secret_sharing.cpp	18838	aea152036abdf368422312bc67b533c9564db6645b423f87bcd7bb4a0fbcce26	0
src/cbmpc/crypto/tdh2.cpp	7393	09bb2ea74cb90fce2455dfdfb59a46d2602ec8ec22a88cc65f1006746eaa87db	0
src/cbmpc/protocol/agree_random.cpp	4095	fda790e3f41acc7561402f8dc85f21c20e40d9a0228ee0e8596c2135e1476175	0
src/cbmpc/protocol/ec_dkg.cpp	24991	3b23c2ec0047bc420818c27c59c8c134214d805ed9f9e835757aa7b5a07a1855	0
src/cbmpc/protocol/ecdsa_2p.cpp	24824	676da782f28e8371b19dd2737d91d08ac8fbf805bf4c91b0c4defe0f9116216c	0
src/cbmpc/protocol/ecdsa_mp.cpp	20263	6fd98e15fd272931e7ed76418a3833da33c3facd895e60d95453dd3acea59c0b	0
src/cbmpc/protocol/eddsa.cpp	982	e534d848e59ef7fad0a8156804d0b545e919aca37cc0995bee5482904f5e985e	0
src/cbmpc/protocol/hd_keyset_ecdsa_2p.cpp	6599	dc2f999c8ba5817ac88817a08aa3cdfbfb09d258bf16c2b11719990f9355b075	0
src/cbmpc/protocol/hd_keyset_eddsa_2p.cpp	5751	60b1f34c8280d8ca1979f5522553544df9015d0c6c3f8d0f46c9a4f411d1f5b7	0
src/cbmpc/protocol/hd_tree_bip32.cpp	1202	b477c98d2d5e834999eab5bc3bdb6d610d01137b3922ce40d2b33f296cfcd939	0
src/cbmpc/protocol/int_commitment.cpp	90896	28356c850e19c96fc65a8abb43a8191779f756cf424c07146d4ffde86e64afdd	0
src/cbmpc/protocol/mpc_job.cpp	1207	50346b5c5839ece7d5db342babcff1a124f3341a79ee0f4cc9f5da526af5fb09	0
src/cbmpc/protocol/ot.cpp	17534	6a1a3e82170609e3e7d4bf15b7d0fcdb22c2887d3f68b851ad9aabe7bb0800db	0
src/cbmpc/protocol/pve.cpp	4987	d4c53ffa9710407b9d016673f2de6eb5ce18e3458a6c803b11eb57880905286f	0
src/cbmpc/protocol/pve_ac.cpp	11348	de010bed8070f48c7adafbaf606cc0e4bb43243177c9c12448ecb3d9dc2ca536	0
src/cbmpc/protocol/pve_base.cpp	1661	4cf97abd43be32195eeb17a2e8ef41aec4bf40d7dac414bee458425764c25df3	0
src/cbmpc/protocol/pve_batch.cpp	7350	2bbf74000b73ade87272a6d048a4c894019a5338da4916084e26f510be5dd178	0
src/cbmpc/protocol/schnorr_2p.cpp	5348	a998fa463bf108155247586360a6e309dc8ec940ea10916c93a66334c0baab50	0
src/cbmpc/protocol/schnorr_mp.cpp	7312	b7aa492e64186b649ce0a19abc70e27afe5f7bcaaffc008bad3a6e0ee7d83af8	0
src/cbmpc/zk/fischlin.cpp	2071	b272d3a5cc641eeaab74baaf6d494958a0e56db0e205d28f301b9944b3d66c68	0

src/cbmpc/zk/small_primes.cpp	82305	508021bcc27b6bc7efe6481ce1f85407a02501c9a8a6c1628cd022fc59ec4630	0
src/cbmpc/zk/zk_ec.cpp	11090	864cc7b1616050ed50842d23b2c8d78c09ca253fcd811d08987091f4bf002614	0
src/cbmpc/zk/zk_elgamal_com.cpp	11105	ba7214e14d37fcb23c9334f0502c9ce9fb9627cce992fd676921d82c6f8377ec	0
src/cbmpc/zk/zk_paillier.cpp	23160	fd1dc137a76118088153562685210 63e54f833048b8fc42e616a59c7188e0ab0	0
src/cbmpc/zk/zk_pedersen.cpp	18743	968641640c623fc2cdfe6012b8686db394631006f90478bfc182820228662bc6	0
src/cbmpc/zk/zk_unknown_order.cpp	2674	bcde5bc6688e9e3f6bc022f2a4089d98f98a8d3b83f277ed00fbde0e1608fbd7	0