Notes while developing this app

Alexander Ahmann

Coding Approaches & Usage

In MainActivity.java, the following “pseudo-test harness” is given which activates panes

```
// Pseudo Test harness for different activities
Intent activity_database = new Intent(MainActivity.this, ActivityDB.class);
Intent activity_sms = new Intent(MainActivity.this, ActivitySMS.class);
//startActivity(activity_database);
startActivity(activity_sms);
// End pseudo test harness
```

In order to run a particular activity pane and have it override the activity_main, uncomment the startActivity(activity_database) or startActivity(activity_sms).

In order to get the inventory table populated with sample data, I did so dynamically through hardcoding Java in the database activity view’s TableLayout:

```
TableLayout tabintInventory = (TableLayout) findViewById(R.id.table_inventoryitems);

TableRow testRow = new TableRow(this);

TextView testRow_name = new TextView(this);
testRow_name.setText("test name");
testRow_name.setPadding(35, 35, 35, 35);
testRow.addView(testRow_name);

TextView testRow_cat = new TextView(this);
testRow_cat.setText("test cat");
testRow_cat.setPadding(35, 35, 35, 35);
testRow.addView(testRow_cat);

TextView testRow_qty = new TextView(this);
testRow_qty.setText("42");
testRow_qty.setPadding(35, 35, 35, 35);
testRow.addView(testRow_qty);

TextView testRow_date = new TextView(this);
testRow_date.setText("Sept. 1, 2011");
testRow_date.setPadding(35, 35, 35, 35);
testRow.addView(testRow_date);

Button testRow_removeItem = new Button(this);
testRow_removeItem.setText("Remove item");
testRow_removeItem.setPadding(35, 35, 35,35);
testRow.addView(testRow_removeItem);

tabintInventory.addView(testRow);
```

This is not really the result of good coding practices, so this application will need to be further refactored and heavily worked on in order to produce a more reliable prototype inventory app (the submission for the third project will most likely be a “beta” version of what I am working on, or at the “alpha” stage at the very least).

General Remarks

- I initially started this project with a minimum API version of 24, but had to upgrade the minimum API version to 30 (whilst still maintaining a target API version of 37) so that other API features would work.
- I did not log debug information into the Log console, I instead put text labels to show status (which may not be the best guideline for programming).
- I used a “TableLayout” to organize the database activity pane, and dynamically added rows. The layout seriously needs to be worked on, though.
- I was not quite sure how to implement SMS for this case, so I just included a sample “text message sender” activity pane that checks for permissions.
- When SMS_SEND permissions are not granted, the app does not persistently ask for permissions every time it is opened (I do not know why).