

# Week7 Support Vector Machines

## Overview

This week, we will be learning about support vector machine (SVM) algorithm.

SVM are considered by many to be the most powerful 'black box' learning algorithm, and by posing a cleverly-chosen optimization objective, one of the most widely used learning algorithms today.

- Compare to both logistic regression and neural networks, the Support Vector Machine sometimes gives a cleaner, and sometimes more powerful way of learning algorithms.

## Optimization objective

Alternative view of logistic regression:

Hypothesis:  $h_{\theta}(x) = \frac{1}{1+e^{-\theta^T x}}$


- if  $y = 1$ , we want  $h_{\theta} \approx 1, \theta^T x \gg 0$
- if  $y = 0$ , we want  $h_{\theta} \approx 0, \theta^T x \ll 0$

The cost function:


- $-(y \log h_{\theta}(x) + (1 - y) \log(1 - h_{\theta})) \Rightarrow -y \log \frac{1}{1+e^{-\theta^T x}} - (1 - y) \log \frac{1}{1+e^{-\theta^T x}}$

The graph below:

If  $y = 1$  (want  $\theta^T x \gg 0$ ):  
 $z = \theta^T x$



If  $y = 0$  (want  $\theta^T x \ll 0$ ):



Logistic regression:

$$\min_{\theta} \frac{1}{m} \left[ \sum_{i=1}^m -y \log \frac{1}{1+e^{-\theta^T x}} - (1-y) \log \frac{1}{1+e^{-\theta^T x}} \right] + \frac{\lambda}{2m} \sum_{j=1}^n \theta_j^2$$

Support vector machine hypothesis:

$$\min_{\theta} C \sum_{i=1}^m \left[ -y \text{cost}_1(\theta^T x^{(i)}) - (1-y) \text{cost}_0(\theta^T x^{(i)}) \right] + \frac{\lambda}{2m} \sum_{j=1}^n \theta_j^2$$

## Large Margin Classification

数据集中所有满足  $y^{(n)}(\mathbf{w}^T \mathbf{x}^{(n)} + b) = 1$  的样本点, 都称为**支持向量** (Support Vector)。

对于一个线性可分的数据集, 其分割超平面有很多个, 但是间隔最大的超平面是唯一的。图3.6给定了支持向量机的最大间隔分割超平面的示例, 其中轮廓线加粗的样本点为支持向量。






图 3.6 支持向量机示例

## Support Vector Machine

$$\rightarrow \min_{\theta} C \sum_{i=1}^m \left[ y^{(i)} \text{cost}_1(\theta^T x^{(i)}) + (1 - y^{(i)}) \text{cost}_0(\theta^T x^{(i)}) \right] + \frac{1}{2} \sum_{j=1}^n \theta_j^2$$



$\rightarrow$  If  $y = 1$ , we want  $\theta^T x \geq 1$  (not just  $\geq 0$ )

$$\theta^T x \geq 1$$

$\rightarrow$  If  $y = 0$ , we want  $\theta^T x \leq -1$  (not just  $< 0$ )

$$\theta^T x \leq -1$$

$$C = 100,000$$

And

## SVM Decision Boundary

$$\min_{\theta} C \sum_{i=1}^m \left[ y^{(i)} \text{cost}_1(\theta^T x^{(i)}) + (1 - y^{(i)}) \text{cost}_0(\theta^T x^{(i)}) \right] + \frac{1}{2} \sum_{j=1}^n \theta_j^2$$

Whenever  $y^{(i)} = 1$ :

$$\theta^T x^{(i)} \geq 1$$

$$\min_{\theta} C + \frac{1}{2} \sum_{j=1}^n \theta_j^2$$

$$\text{s.t. } \theta^T x^{(i)} \geq 1 \quad \text{if } y^{(i)} = 1$$

$$\theta^T x^{(i)} \leq -1 \quad \text{if } y^{(i)} = 0$$

Whenever  $y^{(i)} = 0$ :

$$\theta^T x^{(i)} \leq -1$$

Question:

Consider the following minimization problems:

$$1. \min_{\theta} \frac{1}{m} \left[ \sum_{i=1}^m y^{(i)} \text{cost}_1(\theta^T x^{(i)}) + (1 - y^{(i)}) \text{cost}_0(\theta^T x^{(i)}) \right] + \frac{\lambda}{2m} \sum_{j=1}^n \theta_j^2$$

$$2. \min_{\theta} C \left[ \sum_{i=1}^m y^{(i)} \text{cost}_1(\theta^T x^{(i)}) + (1 - y^{(i)}) \text{cost}_0(\theta^T x^{(i)}) \right] + \frac{1}{2} \sum_{j=1}^n \theta_j^2$$

These two optimization problems will give the same value of  $\theta$  (i.e., the same value of  $\theta$  gives the optimal solution to both problems) if:

- ☐  $C = \lambda$
- ☐  $C = -\lambda$
- ☒  $C = \frac{1}{\lambda}$
- ☐  $C = \frac{2}{\lambda}$

✓ Correct

## The mathematics behind large margin classification

---

$$\omega = (\sqrt{w'})^2$$

## SVM Decision Boundary

$$\min_{\theta} \frac{1}{2} \sum_{j=1}^n \theta_j^2 = \frac{1}{2} (\theta_1^2 + \theta_2^2) = \frac{1}{2} (\sqrt{\theta_1^2 + \theta_2^2})^2 = \frac{1}{2} \|\theta\|^2$$

$$\text{s.t. } \theta^T x^{(i)} \geq 1 \quad \text{if } y^{(i)} = 1$$

$$\rightarrow \theta^T x^{(i)} \leq -1 \quad \text{if } y^{(i)} = 0$$


Simplification:  $\theta_0 = 0$   $n=2$

$$= \|\theta\|$$

$$\begin{bmatrix} \theta_0 \\ \theta_1 \\ \theta_2 \end{bmatrix} \theta_0 = 0$$

$$\theta^T x^{(i)} = ?$$

$\uparrow \quad \uparrow$   
 $u^T v$



$$\theta^T x^{(i)} = p^{(i)} \cdot \|\theta\| \leftarrow$$

$$= \theta_1 x_1^{(i)} + \theta_2 x_2^{(i)} \leftarrow$$

Andrew Ng




## SVM Decision Boundary

$$\Rightarrow \min_{\theta} \frac{1}{2} \sum_{j=1}^n \theta_j^2 = \frac{1}{2} \|\theta\|^2 \leftarrow$$

$$\text{s.t. } \left. \begin{aligned} p^{(i)} \cdot \|\theta\| &\geq 1 & \text{if } y^{(i)} = 1 \\ p^{(i)} \cdot \|\theta\| &\leq -1 & \text{if } y^{(i)} = -1 \end{aligned} \right\} C \text{ vary large}$$

where  $p^{(i)}$  is the projection of  $x^{(i)}$  onto the vector  $\theta$ .

Simplification:  $\theta_0 = 0$




Andrew Ng

Notes: Same as **vector inner product**

## Kernels

## Non-linear Decision Boundary



Predict  $y = 1$  if

$$\rightarrow \theta_0 + \theta_1 \underline{x_1} + \theta_2 \underline{x_2} + \theta_3 \underline{x_1 x_2} + \theta_4 \underline{x_1^2} + \theta_5 \underline{x_2^2} + \dots \geq 0$$

$$h_\theta(x) = \begin{cases} 1 & \text{if } \theta_0 + \theta_1 x_1 + \dots \geq 0 \\ 0 & \text{otherwise} \end{cases}$$


$$\rightarrow \theta_0 + \theta_1 f_1 + \theta_2 f_2 + \theta_3 f_3 + \dots$$

$$f_1 = x_1, f_2 = x_2, f_3 = x_1 x_2, f_4 = x_1^2, f_5 = x_2^2, \dots$$

Is there a different / better choice of the features  $f_1, f_2, f_3, \dots$ ?

Andrew N

## Kernel



Given  $x$ , compute new feature depending on proximity to landmarks  $l^{(1)}, l^{(2)}, l^{(3)}$

Given  $x$ :

$$f_1 = \text{similarity}(x, l^{(1)}) = \exp\left(-\frac{\|x - l^{(1)}\|^2}{2\sigma^2}\right)$$

$$f_2 = \text{similarity}(x, l^{(2)}) = \exp\left(-\frac{\|x - l^{(2)}\|^2}{2\sigma^2}\right)$$

$$f_3 = \text{similarity}(x, l^{(3)}) = \exp(\dots)$$

$\uparrow$  kernel (Gaussian kernels)  $k(x, l^{(i)})$

$\|w\|$   
 $\uparrow$   
 $\|x - l^{(1)}\|^2$   
 $\uparrow$   
 $\|x - l^{(1)}\|^2$

It's Gaussian Kernel

## Kernels and Similarity

$$f_1 = \text{similarity}(x, \underline{l^{(1)}}) = \exp\left(-\frac{\|x - l^{(1)}\|^2}{2\sigma^2}\right)$$

If  $\underline{x} \approx \underline{l^{(1)}} :$

$$f_1 \approx \exp\left(-\frac{0^2}{2\sigma^2}\right) \approx 1$$

If  $\underline{x}$  is far from  $\underline{l^{(1)}} :$

$$f_1 = \exp\left(-\frac{(\text{large number})^2}{2\sigma^2}\right) \approx 0.$$

$l^{(1)} \rightarrow f_1$   
 $l^{(2)} \rightarrow f_2$   
 $l^{(3)} \rightarrow f_3$   
 $\uparrow \quad \quad \uparrow \times$

Andrew

### Example:







$\rightarrow l^{(1)} = \begin{bmatrix} 3 \\ 5 \end{bmatrix}$ 
 $f_1 = \exp\left(-\frac{\|x - l^{(1)}\|^2}{2\sigma^2}\right)$

$\rightarrow \sigma^2 = 1$


$x = \begin{bmatrix} 3 \\ 5 \end{bmatrix}$

$\sigma^2 = 0.5$

$\sigma^2 = 3$




Andrew



SO HOW DO WE CHOOSE THE LANDMARK?

### Choosing the landmarks




Given  $x$ :

$$f_i = \text{similarity}(x, l^{(i)}) = \exp\left(-\frac{\|x - l^{(i)}\|^2}{2\sigma^2}\right)$$

Predict  $y = 1$  if  $\theta_0 + \theta_1 f_1 + \theta_2 f_2 + \theta_3 f_3 \geq 0$

Where to get  $l^{(1)}, l^{(2)}, l^{(3)}, \dots$ ?





## SVM with Kernels

- Given  $(x^{(1)}, y^{(1)}), (x^{(2)}, y^{(2)}), \dots, (x^{(m)}, y^{(m)})$ ,
- choose  $l^{(1)} = x^{(1)}, l^{(2)} = x^{(2)}, \dots, l^{(m)} = x^{(m)}$ .

Given example  $x$ :

$$\begin{aligned} \rightarrow f_1 &= \text{similarity}(x, l^{(1)}) \\ \rightarrow f_2 &= \text{similarity}(x, l^{(2)}) \\ &\vdots \end{aligned}$$

$$f = \begin{bmatrix} f_0 \\ f_1 \\ f_2 \\ \vdots \\ f_m \end{bmatrix} \quad f_0 = 1$$

For training example  $(x^{(i)}, y^{(i)})$ :

$$\begin{aligned} f_1^{(i)} &= \text{sim}(x^{(i)}, l^{(1)}) \\ f_2^{(i)} &= \text{sim}(x^{(i)}, l^{(2)}) \\ &\vdots \\ f_i^{(i)} &= \text{sim}(x^{(i)}, l^{(i)}) = \exp(-\frac{0}{2x_i}) = 1 \\ &\vdots \\ f_m^{(i)} &= \text{sim}(x^{(i)}, l^{(m)}) \end{aligned}$$

$$x^{(i)} \in \mathbb{R}^{n+1} \quad (\text{or } \mathbb{R}^n)$$

$$f^{(i)} = \begin{bmatrix} f_0^{(i)} \\ f_1^{(i)} \\ f_2^{(i)} \\ \vdots \\ f_m^{(i)} \end{bmatrix} \quad f_0^{(i)} = 1$$

Andrew Ng

Hypothesis: Given  $x$ , compute features  $f \in \mathbb{R}^{m+1}$

$$\theta \in \mathbb{R}^{n+1}$$

$\rightarrow$  Predict "y=1" if  $\theta^T f \geq 0$

$$\theta_0 f_0 + \theta_1 f_1 + \dots + \theta_m f_m$$

Training:

$$\min_{\theta} C \sum_{i=1}^m y^{(i)} \text{cost}_1(\theta^T f^{(i)}) + (1 - y^{(i)}) \text{cost}_0(\theta^T f^{(i)}) + \frac{1}{2} \sum_{j=1}^m \theta_j^2$$


$$\begin{aligned} \rightarrow \sum_j \theta_j^2 &= \theta^T \theta \leftarrow \theta = \begin{bmatrix} \theta_1 \\ \vdots \\ \theta_m \end{bmatrix} \quad (\text{ignoring } \theta_0) \\ &\rightarrow \theta^T M \theta \leftarrow \| \theta \|^2 \quad M = 10,000 \end{aligned}$$

Parameters in SVM


$C (= \frac{1}{\lambda})$ .  $\rightarrow$  Large  $C$ : Lower bias, high variance. (small  $\lambda$ )  
 $\rightarrow$  Small  $C$ : Higher bias, low variance. (large  $\lambda$ )

$\sigma^2$  Large  $\sigma^2$ : Features  $f_i$  vary more smoothly.  
 $\rightarrow$  Higher bias, lower variance.

$$\exp\left(-\frac{\|x - x^{(i)}\|^2}{2\sigma^2}\right)$$



Small  $\sigma^2$ : Features  $f_i$  vary less smoothly.  
 Lower bias, higher variance.



Logistic regression or SVMs?

$n$  = number of features ( $x \in \mathbb{R}^{n+1}$ ),  $m$  = number of training examples

$\rightarrow$  If  $n$  is large (relative to  $m$ ): (e.g.  $n \geq m$ ,  $n = 10,000$ ,  $m = 10 \dots 1000$ )

$\rightarrow$  Use logistic regression, or SVM without a kernel ("linear kernel")


$\rightarrow$  If  $n$  is small,  $m$  is intermediate: ( $n = 1-1000$ ,  $m = 10-10,000$ )  $\leftarrow$

$\rightarrow$  Use SVM with Gaussian kernel

If  $n$  is small,  $m$  is large: ( $n = 1-1000$ ,  $m = 50,000+$ )


$\rightarrow$  Create/add more features, then use logistic regression or SVM without a kernel

$\rightarrow$  Neural network likely to work well for most of these settings, but may be slower to train.



Quiz: Support Vector Machines


1. Suppose you have trained an SVM classifier with a Gaussian kernel, and it learned the following decision boundary on the training set: 1 point




You suspect that the SVM is underfitting your dataset. Should you try increasing or decreasing  $C$ ? Increasing or decreasing  $\sigma^2$ ?



- ☐ It would be reasonable to try **decreasing**  $C$ . It would also be reasonable to try **increasing**  $\sigma^2$ .
- ☒ It would be reasonable to try **increasing**  $C$ . It would also be reasonable to try **decreasing**  $\sigma^2$ .
- ☐ It would be reasonable to try **increasing**  $C$ . It would also be reasonable to try **increasing**  $\sigma^2$ .
- ☐ It would be reasonable to try **decreasing**  $C$ . It would also be reasonable to try **decreasing**  $\sigma^2$ .
2. The formula for the Gaussian kernel is given by  $\text{similarity}(x, l^{(1)}) = \exp\left(-\frac{\|x - l^{(1)}\|^2}{2\sigma^2}\right)$ .

The figure below shows a plot of  $f_1 = \text{similarity}(x, l^{(1)})$  when  $\sigma^2 = 1$ .





Which of the following is a plot of  $f_1$  when  $\sigma^2 = 0.25$ ?










Figure 4.



3. The SVM solves

$$\min_{\theta} C \sum_{i=1}^m y^{(i)} \text{cost}_1(\theta^T x^{(i)}) + (1 - y^{(i)}) \text{cost}_0(\theta^T x^{(i)}) + \sum_{j=1}^n \theta_j^2$$

where the functions  $\text{cost}_0(z)$  and  $\text{cost}_1(z)$  look like this:



The first term in the objective is:

$$C \sum_{i=1}^m y^{(i)} \text{cost}_1(\theta^T x^{(i)}) + (1 - y^{(i)}) \text{cost}_0(\theta^T x^{(i)}).$$

This first term will be zero if two of the following four conditions hold true. Which are the two conditions that would guarantee that this term equals zero?

- ☒ For every example with  $y^{(i)} = 1$ , we have that  $\theta^T x^{(i)} \geq 1$ .
- ☐ For every example with  $y^{(i)} = 1$ , we have that  $\theta^T x^{(i)} \geq 0$ .
- ☒ For every example with  $y^{(i)} = 0$ , we have that  $\theta^T x^{(i)} \leq -1$ .
- ☐ For every example with  $y^{(i)} = 0$ , we have that  $\theta^T x^{(i)} \leq 0$ .

4. Suppose you have a dataset with  $n = 10$  features and  $m = 5000$  examples.

1 point

After training your logistic regression classifier with gradient descent, you find that it has underfit the training set and does not achieve the desired performance on the training or cross validation sets.

Which of the following might be promising steps to take? Check all that apply.

- ☐ Use an SVM with a linear kernel, without introducing new features.
- ☒ Use an SVM with a Gaussian Kernel.
- ☐ Increase the regularization parameter  $\lambda$ .
- ☒ Create / add new polynomial features.

5. Which of the following statements are true? Check all that apply.

1 point

- ☐ If the data are linearly separable, an SVM using a linear kernel will return the same parameters  $\theta$  regardless of the chosen value of  $C$  (i.e., the resulting value of  $\theta$  does not depend on  $C$ ).
- ☒ Suppose you have 2D input examples (ie,  $x^{(i)} \in \mathbb{R}^2$ ). The decision boundary of the SVM (with the linear kernel) is a straight line.
- ☐ If you are training multi-class SVMs with the one-vs-all method, it is not possible to use a kernel.
- ☒ The maximum value of the Gaussian kernel (i.e.,  $\text{sim}(x, l^{(1)})$ ) is 1.