



Swagger UI

/q/openapi

Explore

api API

1.0-SNAPSHOT

OAS 3.1

/q/openapi

Analysis Resource

GET

/analyses

Get All Analyses

Parameters

Try it out

No parameters

Responses

Code	Description	Links
200	OK Media type application/json Controls Accept header. Example Value Schema [{ "id": 0, "title": "string", "description": "string", "publicCode": "string", "createdAt": "2022-03-10T12:15:50" }]	

 No links |

POST

/analyses

Create Analysis

Parameters

Try it out

No parameters

Request body required

application/json

Example Value | Schema

```
{
  "title": "string",
  "description": "string"
}
```

Responses

Code	Description	Links
200	OK Media type application/json Controls Accept header. Example Value Schema <pre>{ "id": 0, "title": "string", "description": "string", "publicCode": "string", "createdAt": "2022-03-10T12:15:50" }</pre>	No links
400	Bad Request	No links

Question Resource

GET

/analyses/{analysisId}/questions

Get Questions By Analysis Id

Parameters

Try it out

Name	Description
analysisId required integer(int64) (path)	analysisId

Responses

Code	Description	Links
200	OK Media type application/json Controls Accept header. Example Value Schema <pre>[{ "id": 0, "analysisId": 0, "questionText": "string", "position": 0, "createdAt": "2022-03-10T12:15:50" }]</pre>	No links

POST

/analyses/{analysisId}/questions

Create Question

Try it out

Parameters

Name	Description
analysisId * required integer(\$int64) (path)	analysisId

Request body required

application/json

Example Value | Schema

```
{
  "questionText": "string",
  "position": 0
}
```

Responses

Code	Description	Links
200	OK Media type application/json Controls Accept header.	No links

Code	Description	Links
	Example Value Schema <pre>{ "id": 0, "analysisId": 0, "questionText": "string", "position": 0, "createdAt": "2022-03-10T12:15:50" }</pre>	
400	Bad Request	No links

GET

/analyses/{analysisId}/questions/{questionId}

Get Question By Analysis Id And Question Id

Parameters

Try it out

Name	Description
analysisId * required integer(\$int64) (path)	analysisId
questionId * required integer(\$int64) (path)	questionId

Responses

Code	Description	Links
200	OK Media type application/json Controls Accept header. Example Value Schema <pre>{ "id": 0, "analysisId": 0, "questionText": "string", "position": 0, "createdAt": "2022-03-10T12:15:50" }</pre>	No links

POST

/analyses/{analysisId}/questions/{questionId}/ai/conversation

Continue Conversation

⬆

Parameters

Try it out

Name	Description
analysisId * required integer(\$int64) (path)	analysisId
questionId * required integer(\$int64) (path)	questionId

Request body required

application/json

⌵

Example Value | Schema

```
{  "previousResponses": [    {      "questionId": 0,      "summary": "string"    }  ],  "messages": [    {      "sender": "string",      "messageText": "string"    }  ]}
```

Responses

Code	Description	Links
200	OK Media type application/json ⌵ Controls Accept header. Example Value Schema <pre>{ "state": "string", "messageText": "string"}</pre>	No links
400	Bad Request	No links

Analysis Session Resource

GET /analyses/{analysisId}/sessions Get Sessions By Analysis

Parameters

Try it out

Name	Description
analysisId * required integer(\$int64) (path)	analysisId

Responses

Code	Description	Links
200	OK Media type application/json Controls Accept header. Example Value Schema <pre>[{ "id": 0, "analysisId": 0, "respondent": "string", "completedAt": "2022-03-10T12:15:50" }]</pre>	No links

POST /analyses/{analysisId}/sessions Create Analysis Session

Parameters

Try it out

Name	Description
analysisId * required integer(\$int64) (path)	analysisId

Request body required

application/json

Example Value | Schema

```
{
  "respondent": "string"
}
```

Responses

Code	Description	Links
200	OK Media type application/json Controls Accept header. Example Value Schema <pre>{ "id": 0, "analysisId": 0, "respondent": "string", "completedAt": "2022-03-10T12:15:50" }</pre>	No links
400	Bad Request	No links

POST /analyses/{analysisId}/sessions/full Create Full Analysis Session

Parameters

Try it out

Name	Description
analysisId * required integer(\$int64) (path)	analysisId

Request body required

application/json

Example Value | Schema

```
{
  "respondent": "string",
  "responses": [
    {
      "questionId": 0,
      "messages": [
        {
          "sender": "string",

```

```
    "messageText": "string",
    "position": 0
  }
}
}
```

Responses

Code	Description	Links
200	OK	No links
	Media type application/json Controls Accept header. Example Value Schema <pre>{ "id": 0, "analysisId": 0, "respondent": "string", "completedAt": "2022-03-10T12:15:50" }</pre>	
400	Bad Request	No links

GET /analyses/{analysisId}/sessions/{sessionId} Get Session By Analysis Id And Session Id

Parameters

Try it out

Name	Description
analysisId * required integer(\$int64) (path)	analysisId
sessionId * required integer(\$int64) (path)	sessionId

Responses

Code	Description	Links
200	OK	No links

Code

Description

Links

Media type

application/json

Controls Accept header.

Example Value | Schema

```
{
  "id": 0,
  "analysisId": 0,
  "respondent": "string",
  "completedAt": "2022-03-10T12:15:50"
}
```

GET

/analyses/{analysisId}/sessions/{sessionId}/full

Get Full Analysis Session

^

Parameters

Try it out

Name

Description

analysisId * required

integer(\$int64)

(path)

analysisId

sessionId * required

integer(\$int64)

(path)

sessionId

Responses

Code

Description

Links

200

OK

No links

Media type

application/json

Controls Accept header.

Example Value | Schema

```
{
  "id": 0,
  "analysisId": 0,
  "respondent": "string",
  "completedAt": "2022-03-10T12:15:50",
  "responses": [
    {
      "id": 0,
      "questionId": 0,
      "questionText": "string",
      "messages": [
        {

```

Code	Description	Links
	<pre>"id": 0, "sender": "string", "messageText": "string", "position": 0, "createdAt": "2022-03-10T12:15:50" } } }</pre>	

Greeting Resource

GET

/hello

Hello

Parameters

Try it out

No parameters

Responses

Code	Description	Links
200	OK Media type text/plain Controls Accept header. Example Value Schema string	No links

Schemas

AiConversationMessageRequest ^ Collapse all object

```
sender string
messageText string
```

AiConversationRequest ^ Collapse all object

previousResponses ^ Collapse all array<object>

Items ^ Collapse all object

questionId integer int64

summary string

messages ^ Collapse all array<object>

Items ^ Collapse all object

sender string

messageText string

AiConversationResponse ^ Collapse all object

state string

messageText string

AiPreviousResponseRequest ^ Collapse all object

questionId integer int64

summary string

AnalysisResponse ^ Collapse all object

id integer int64

title string

description string

publicCode string

createdAt ^ Collapse all string date-time

Examples ^ Collapse all array

#0="2022-03-10T12:15:50"

AnalysisSessionResponse ^ Collapse all object

id integer int64

analysisId integer int64

respondent string

completedAt ^ Collapse all string date-time

Examples ^ Collapse all array

#0="2022-03-10T12:15:50"

CreateAnalysisRequest ^ Collapse all object

title string

description string

CreateAnalysisSessionRequest ^ Collapse all object

```
respondent string
```

CreateFullAnalysisSessionRequest ^ Collapse all object

```
respondent string
```

```
responses ^ Collapse all array<object>
```

```
Items ^ Collapse all object
```

```
questionId integer int64
```

```
messages ^ Collapse all array<object>
```

```
Items ^ Collapse all object
```

```
sender string
```

```
messageText string
```

```
position integer int32
```

CreateQuestionRequest ^ Collapse all object

```
questionText string
```

```
position integer int32
```

CreateQuestionResponseRequest ^ Collapse all object

```
questionId integer int64
```

```
messages ^ Collapse all array<object>
```

```
Items ^ Collapse all object
```

```
sender string
```

```
messageText string
```

```
position integer int32
```

CreateResponseMessageRequest ^ Collapse all object

```
sender string
```

```
messageText string
```

```
position integer int32
```

FullAnalysisSessionResponse ^ Collapse all object

```
id integer int64
```

```
analysisId integer int64
```

```
respondent string
```

```
completedAt ^ Collapse all string date-time
```

```
Examples ^ Collapse all array
```

```
#0="2022-03-10T12:15:50"
```

```
responses ^ Collapse all array<object>
```

```
Items ^ Collapse all object
```

```
id integer int64
```

```
questionId integer int64
questionText string
messages ^ Collapse all array<object>
  Items ^ Collapse all object
    id integer int64
    sender string
    messageText string
    position integer int32
    createdAt ^ Collapse all string date-time
    Examples ^ Collapse all array
      #0="2022-03-10T12:15:50"
```

LocalDateTime ^ Collapse all string date-time

Examples ^ Collapse all array

#0="2022-03-10T12:15:50"

QuestionResponse ^ Collapse all object

```
id integer int64
analysisId integer int64
questionText string
position integer int32
createdAt ^ Collapse all string date-time
Examples ^ Collapse all array
  #0="2022-03-10T12:15:50"
```

QuestionResponseFullResponse ^ Collapse all object

```
id integer int64
questionId integer int64
questionText string
messages ^ Collapse all array<object>
  Items ^ Collapse all object
    id integer int64
    sender string
    messageText string
    position integer int32
    createdAt ^ Collapse all string date-time
    Examples ^ Collapse all array
      #0="2022-03-10T12:15:50"
```

ResponseMessageResponse ^ Collapse all object

```
id integer int64
sender string
messageText string
position integer int32
createdAt ^ Collapse all string date-time
Examples ^ Collapse all array
#0="2022-03-10T12:15:50"
```