

Style for IFAC Conferences & Symposia: Use Title Case for Paper Title

Alessandra Elisa Sindi Morando^{*,**} Pedro Castillo^{**}
Roberto Sacile^{*} Enrico Zero^{*}

^{*} *University of Genoa, Genoa, Italy*
alessandra.elisa.sindi.morando@edu.unige.it, roberto.sacile@unige.it,
enrico.zero@dibris.unige.it

^{**} *Université de technologie de Compiègne, CNRS, Heudiasyc,*
Compiègne, France
alessandra-elisa-sindi.morando@utc.fr, pedro.castillo@hds.utc.fr

Abstract: ...

Keywords: ...

1. INTRODUCTION

Multi-agent systems (MASs) are nowadays used in a variety of applications from as they can perform complex tasks, which would otherwise impossible for a single robot. This is even more the case when considering heterogeneous fleet where the strenghts of one type of robot can compensate for the limitations of another. For example, to monitor a large area, multiple ground agents can move from one point to another being supervised from above by a drone with a wide field of view. To deepen the subject and understand both the potential tasks and challenges of MASs, the reader can refer to the work of Maldonado et al. (2024).

One of the fundamental cooperative tasks when working with multi-agents is formation control. This topic has been studied for years. For example, already Lee and Chong (2009) already proposed a decentralized control algorithm for a team of two-wheeled robots to achieve achieve a geometric pattern. However, formation control remains an hot challenging topic to this day. Tran et al. (2021) experimentally validated a robust distributed control based on negative imaginary systems consensus theory, using both ground robots and an air-ground fleet. In the work of Güler and İsa E. Yıldırım (2023), each agent computes its control action in a leader-follower manner using local extended Kalman filter's estimates to achieve a desired shape together with other wheeled robots and a drone. An optimal distributed formation control algorithm for double-integrator multi-agents has been presented and validated through simulations by Huang et al. (2023). Aditya and Werner (2023) defined the formation problem for a group of double-integrator agents as a discrete-time game whose solution is given by a state-dependent Riccati equation. A robust distributed consensus controller is presented by Restrepo et al. (2023) to address the rendezvous problem and applied in simulation to a swarm of drones. In the recent years, reinforcement learning has used in many areas including formation control. Wang et al. (2020) addressed multi-particle formation control by combining graph attention networks and multiple long short-term




Fig. 1. This paper proposes a formation control for a heterogeneous fleet to attain a desired shape despite obstacles.

memories to achieve the desired shape and avoid collisions respectively. A position and an orientation robust controllers based on reinforcement learning are proposed and validated through simulations by Zhong et al. (2025) for the formation of a term of quadrotors.

In this context is placed this work which proposes a novel formation control scheme for a team consisting of a quadcopter and two unicycles, as show in Fig. 1. When addressing the multi-agent formation, there are two main challenges to solve: achieving the desired shape and avoiding collisions. On one hand, for the first challenge, a distributed controller combining Feedback Linearization (FL) and an optimal linear controller based on Linear Matrix Inequalities (LMIs) is presented. LMIs are a powerful mathematical tool used in many applications among which also formation control. In the work of Trejo et al. (2023), an LMI is solved to design the controller and observer gains, guaranteeing stable formation flight for a group of quadcopters. Deshpande et al. (2011) propose a formation control with artificial fixed delays for multiple double-integrators and verify the asymptotic stability of the scheme by checking the solvability of an LMI. Semsar-Kazerooni and Khorasani (2009) present an LMI formulation of the LQR problem to guarantee stable state consensus with an optimal control effort in a multi-agent system. On the other end, to avoid collision avoidance, the chosen solution is Artificial Potential Field (APF). In analogy with a particle moving in an electrostatic or gravitational




Fig. 2. Air-ground heterogeneous fleet.

field, virtual repulsive force fields are simulated to ward off the robot from an obstacle. This approach has been widely used in formation control of ground vehicles, see for example the work of Yongshen et al. (2018). However, in more recent works, e.g. Han et al. (2024) and Piet et al. (2025), APFs are employed to navigate around obstacles and prevent collisions while attaining the desired shape.

This paper represents the continuation of the previous work by Morando et al. (2025), where a control architecture combining Feedback Linearization (FL), a robust LMI-based controller and APFs was proposed and validated through simulations for the formation of three unicycles. The successive developments sought to manage the challenge of a heterogeneous team (replacing a ground vehicle with a quadcopter) by adapting the methodology and then experimentally validating the new solution. The contributions of this work are: a) a controller involving FL, a LMI-based controller and APFs is presented for the stable formation of an air-ground fleet; b) the proposed controller has been validated through MATLAB Simulink simulations and a comprehensive set of experiments, including both static and dynamic obstacle scenarios. The remainder paper is structured as follows. In Section 2, the mathematical model used to describe the team is stated. The proposed formation controller is detailed in Section 3. The simulations and experiments results are reported and analyzed in Section 4 and in Section 5 respectively. Finally, conclusions are drawn in Section 6.

2. HETEROGENEOUS FLEET MODELING

3. FORMATION CONTROLLER

4. SIMULATIONS RESULTS

5. EXPERIMENTAL VALIDATION

6. CONCLUSION

...

REFERENCES

Aditya, P. and Werner, H. (2023). A distributed linear quadratic discrete-time game approach to formation

control with collision avoidance. In *2023 62nd IEEE Conference on Decision and Control (CDC)*, 1239–1244. doi:10.1109/CDC49753.2023.10384062.

Deshpande, P., Menon, P.P., Edwards, C., and Postlethwaite, I. (2011). Formation control of multi-agent systems with double integrator dynamics using delayed static output feedback. In *2011 50th IEEE Conference on Decision and Control and European Control Conference*, 3446–3451. doi:10.1109/CDC.2011.6161074.

Güler, S. and İsa E. Yıldırım (2023). A distributed relative localization approach for air-ground robot formations with onboard sensing. *Control Engineering Practice*, 135, 105492. doi: <https://doi.org/10.1016/j.conengprac.2023.105492>.

Han, L., Wang, Y., Yan, Z., Li, X., and Ren, Z. (2024). Event-triggered formation control with obstacle avoidance for multi-agent systems applied to multi-uav formation flying. *Control Engineering Practice*, 153, 106105. doi: <https://doi.org/10.1016/j.conengprac.2024.106105>.

Huang, F., Duan, M., Su, H., and Zhu, S. (2023). Distributed optimal formation control of second-order multiagent systems with obstacle avoidance. *IEEE Control Systems Letters*, 7, 2647–2652. doi: 10.1109/LCSYS.2023.3287950.

Lee, G. and Chong, N.Y. (2009). Decentralized formation control for small-scale robot teams with anonymity. *Mechatronics*, 19(1), 85–105. doi: <https://doi.org/10.1016/j.mechatronics.2008.06.005>.

Maldonado, D., Cruz, E., Abad Torres, J., Cruz, P.J., and Gamboa Benítez, S.d.P. (2024). Multi-agent systems: A survey about its components, framework and workflow. *IEEE Access*, 12, 80950–80975. doi: 10.1109/ACCESS.2024.3409051.

Morando, A.E.S., Bozzi, A., Zero, E., Sacile, R., and Castillo, P. (2025). Robust control architecture for fleet formation based on lmi and artificial potential fields. In *2025 20th Annual System of Systems Engineering Conference (SoSE)*, 1–6. doi: 10.1109/SoSE66311.2025.11083835.

Piet, B., Strub, G., Changey, S., and Petit, N. (2025). Control of an uav swarm in amorphous formation. In *2025 American Control Conference (ACC)*, 469–475. doi:10.23919/ACC63710.2025.11108054.

Restrepo, E., Loría, A., Sarras, I., and Marzat, J. (2023). Robust consensus of high-order systems under output constraints: Application to rendezvous of underactuated uavs. *IEEE Transactions on Automatic Control*, 68(1), 329–342. doi:10.1109/TAC.2022.3144107.

Semsar-Kazerooni, E. and Khorasani, K. (2009). An lmi approach to optimal consensus seeking in multi-agent systems. In *2009 American Control Conference*, 4519–4524. doi:10.1109/ACC.2009.5160268.

Tran, V.P., Garratt, M.A., and Petersen, I.R. (2021). Multi-vehicle formation control and obstacle avoidance using negative-imaginary systems theory. *IFAC Journal of Systems and Control*, 15, 100117. doi: <https://doi.org/10.1016/j.ifacsc.2020.100117>.

Trejo, J.A.V., Ponsart, J.C., Adam-Medina, M., Valencia-Palomo, G., and Theilliol, D. (2023). Distributed observer-based leader-following consensus control for lpv multi-agent systems: Application to multiple vtol-uavs formation control. In *2023 International Conference on*

- Unmanned Aircraft Systems (ICUAS)*, 1316–1323. doi:10.1109/ICUAS57906.2023.10156012.
- Wang, H., Qiu, T., Liu, Z., Pu, Z., and Yi, J. (2020). Multi-agent formation control with obstacles avoidance under restricted communication through graph reinforcement learning. *IFAC-PapersOnLine*, 53(2), 8150–8156. doi:<https://doi.org/10.1016/j.ifacol.2020.12.2300>. 21st IFAC World Congress.
- Yongshen, L., Xuerong, Y., Yajun, Y., and Shengdong, P. (2018). Formation control of ugvs based on artificial potential field. In *2018 37th Chinese Control Conference (CCC)*, 6830–6835. doi:10.23919/ChiCC.2018.8483701.
- Zhong, S., Tian, H., Xia, Y., and Liu, H. (2025). Quadrotor formation maneuver control via reinforcement learning. In *2025 44th Chinese Control Conference (CCC)*, 1–6. doi:10.23919/CCC64809.2025.11179569.