EuroMPI 2019
ETH Zurich

LEGaTO

www.legato-project.eu

Multilevel Checkpointing for MPI Applications

Konstantinos Parasyris
konstantinos.parasyris@bsc.es

Material

git clone -b tutorial https://github.com/leobago/fti
TUTORIAL

Motivation

- Fault tolerance is critical at extreme scale.
- More components, more failures.
- Multiple different types of failures (hard, soft, ect).
- Power limits might impact reliability.
- Current techniques will not scale.

C/R Idea


Execution Time
Get Checkpoint
Get Checkpoint
Get Checkpoint

C/R Idea


Execution Time
Failure
Get Checkpoint
Get Checkpoint
Get Checkpoint

C/R Idea


Execution Time
Store Checkpoint
store Checkpoint
store Checkpoint
Restart execution from Last Checkpoint
Execution Time

Checkpoint efficiency aspects



- Checkpoint overhead depends on:
  - Size of data to be stored.
  - Frequency of checkpoints.
    (Non Frequent checkpoints increase execution time on recovery).
  - File system:
    Storage close to the node (SSD) are faster but less reliable.

Checkpoint Scope

1) Application Level

- The developer indicates:
  - The data to be stored
  - When will the checkpoint take place

2) User Level

- Checkpoint entire user-application.

3) Kernel Level

- Checkpoint Entire System

Basic information about FTI

- Download at:
  http://www.github.com/leobago/fti
- Documentation at
  https://github.com/leobago/fti/wiki/Introduction
  (Library in C/C++ with Fortran bindings)
- More than 10000 lines of code
- Applications ported:
  - HACC
  - Nek5K
  - CESM (ice module)
  - LAMMPS
  - GYSELA 5D
  - SPECFEM3D
  - HYDRO
  - Other miniApps

Multilevel Checkpoint.

Level-1 (Local Storage) :
SSD, PCM, NVM. Fastest checkpoint level. Low reliability, transient failures

Level-2 (Partner Copy) :
Ckpt. Replication. Fast copy to neighbor node. tolerates multiple node failures (depending on location).

Level-3 (RS Encoding) :
Ckpt. Encoding. Slow for large checkpoints. Tolerates Multiple node failures (independent of location)

Level-4 (File System (PFS)) :
Classic Ckpt. Slowest of all levels. The most reliable. Power outage.

Multiple levels offer multiple:

- Resiliency levels
- Checkpoint overheads
- Checkpoint intervals
- Power consumption

Topology aware clustering



- Automatic process location recognition
- Intelligent clustering

- Enhanced reliability for node crashes
- Automatic repositioning after failure

Level 2 Recovery



Level 2 Recovery: Node can recover from the data stored into partner node.

If me and partner fail we cannot recover.

Level 3 Recovery



Level 3 Recovery: Node can recover using the Rs encoded files.

If more than the half nodes of the group fail I cannot recover

Checkpoint Methods (Normal)



User defines memory regions to be protected



Memory occupied by the memory.

Checkpoint file(s).

Non-Protected user variable

Protected user variable

Memory region not allocated by user.

Checkpoint Methods (Normal)



User requests a checkpoint.



Memory occupied by the memory.

Checkpoint file(s).

Non-Protected user variable

Protected user variable

Memory region not allocated by user.

Checkpoint Methods (Normal)



Memory occupied by the memory.

Checkpoint file(s).

Non-Protected user variable

Protected user variable

Memory region not allocated by user.

Checkpoint Methods (Incremental Checkpoint)



User defines memory regions to be protected



Memory occupied by the memory.

Checkpoint file(s).

Non-Protected user variable

Protected user variable

Memory region not allocated by user.

Checkpoint Methods (Incremental Checkpoint)





Memory occupied by the memory.

Non-Protected user variable

Protected user variable

Memory region not allocated by user.

Checkpoint file(s).

Checkpoint Methods (Incremental Checkpoint)





Memory occupied by the memory.

Checkpoint file(s).

Non-Protected user variable

Protected user variable

Memory region not allocated by user.

Checkpoint Methods (Incremental Checkpoint)





Memory occupied by the memory.



Checkpoint file(s).

Non-Protected user variable

Protected user variable

Memory region not allocated by user.

Checkpoint Methods (Incremental Checkpoint)



Memory occupied by the memory.

Checkpoint file(s).

Non-Protected user variable

Protected user variable

Memory region not allocated by user.

Checkpoint Methods (differential Checkpoint (dCP))



User defines memory regions to be protected



Memory occupied by the memory.

Checkpoint file(s).

Non-Protected user variable

Protected user variable

Memory region not allocated by user.

Checkpoint Methods (dCP)



Memory occupied by the memory.

Checkpoint file(s).

Non-Protected user variable

Protected user variable

Memory region not allocated by user.

In the dCP case on the first checkpoint all data are stored in the checkpoint

Checkpoint Methods (dCP)



Memory occupied by the memory.

Checkpoint file(s).

Non-Protected user variable

Protected user variable

Memory region not allocated by user.

Data that have changed in comparison to previous checkpoint

Checkpoint Methods (dCP)



Memory occupied by the memory.

Checkpoint file(s).

Non-Protected user variable

Protected user variable

Memory region not allocated by user.

Data that have changed in comparison with previous checkpoint

Store only the changed data to the checkpoint file. ----→ Reduces IO.

Asynchronous post-processing

Synchronous post-processing



Asynchronous post-processing



- FTI dedicated threads
- Asynchronous data transfer
- Reduced checkpoint overhead

How to use.

Functions:

- ***FTI_Init()***
- ***FTI_Protect()***
- ***FTI_Snapshot()***
- ***FTI_Finalize()***

Communicator:

- **FTI_COMM_WORLD**

```
int main(int argc, char **argv) {
    MPI_Init(&argc, &argv);
    FTI_Init("conf.fti", MPI_COMM_WORLD);
    double *grid;
    int i, steps=500, size=10000;
    initialize(grid);
    FTI_Protect(0, &i,1, FTI_INTG);
    FTI_Protect(1, grid, size,FTI_DFLT);
    for (i=0; i<steps; i++) {
        FTI_Snapshot();
        kernel1(grid);
        kernel2(grid);
        comms(FTI_COMM_WORLD);
    }
    FTI_Finalize();
    MPI_Finalize();
    return 0;
}
```

FTI_Init(...)

FTI_Init(confFile, communicator):

- Read/parse configuration file
- Recognizes whether is a restart or not
- Creates checkpoint directories
- Detect topology of the system
- Regenerates/moves data upon recovery
- Splits the communicator (optional)

FTI_Protect(...)

FTI_Protect(ID,pointer,size,type):

- Stores metadata of the protected variable
- FTI can predict size of checkpoints
- Useful for data compression/aggregation
- Can be reset during the execution
- User can create new FTI types
- Required in order to write/read ckpt. data

FTI_Snapshot()

FTI_Snapshot():

- Measures (global average) iteration length
- Exponential decay for global agreement
- Translates from minutes to iterations
- Test if it is time for a checkpoint
- It saves the checkpoint as requested
- It loads the checkpoint upon recovery
- Planning to integrate notifications

Beyond FTI_Snapshot

FTI_Checkpoint(ID, lvl):

- Takes a checkpoint with id ID and level lvl

FTI_Status():

- Returns the status (initial run or restart)

FTI_Recover():

- It recovers from last available checkpoint

Incremental Checkpoint

New Functions:

- **FTI_InitICP()**
- **FTI_AddVarICP()**
- **FTI_FinalizeICP()**

Communicator:

- **FTI_COMM_WORLD**

```
int main(int argc, char **argv) {
    MPI_Init(&argc, &argv);
    FTI_Init("conf.fti", MPI_COMM_WORLD);
    double *grid1 , *grid2;
    int i, steps=500, size=10000;
    initialize(grid);
    FTI_Protect(0, &i,1, FTI_INTG);
    FTI_Protect(1, grid1, size,FTI_DFLT);
    FTI_Protect(2, grid2, size,FTI_DFLT);
    for (i=0; i<steps; i++) {
        FTI_InitICP( i, (i +1)%4 +1 , 1 );
        FTI_AddVarICP(0);
        kernel1(grid);
        FTI_AddVarICP(1);
        kernel2(grid);
        FTI_AddVarICP(2);
        comms(FTI_COMM_WORLD);
        FTI_FinalizeICP();
    }
    FTI_Finalize();
    ....
}
```

Configuration file (1/3)

```
[basic]
# Set to 1 for having 1 FTI dedicated process per node
Head                                    =       1
# Number of processes per node (including FTI dedicated processes)
node_size                               =       2
# Path where local checkpoints will be stored
ckpt_dir                                = /path/to/local/storage/
# Path where global checkpoints will be stored
glbl_dir                                = /path/to/global/storage/
# Path where checkpoints metadata will be stored
meta_dir                                = /path/to/myhome/.fti/
# Checkpoint interval in minutes for level 1
ckpt_int                                = 1
# Checkpoint interval in minutes for level 2
ckpt_l2                                 = 2
# Checkpoint interval in minutes for level 3
ckpt_l3                                 = 4
# Checkpoint interval in minutes for level 4
ckpt_l4                                 = 8
```

Configuration file (2/3)

[basic]

 # Set to 0 to do L2 postprocessing asynchronously by the dedicated process
inline_l2 ***= 0***

 # Set to 0 to do L3 postprocessing asynchronously by the dedicated process
inline_l3 ***= 0***

 # Set to 0 to do L4 postprocessing asynchronously by the dedicated process
inline_l4 ***= 0***

 # Set to 1 to keep the last checkpoint after Finalize
keep_last_ckpt ***= 0***

 # Size of the group for RSencoding and Partnercopy ring
group_size ***= 4***

 # Set to 1 for verbose mode, 2 for moderate, 3 for silent
Verbosity ***= 1***

Configuration file (3/3)

```
[restart]
# This will be set to 1 automatically after FTI_Init

Failure                                 = 0

# This will be set to 1 automatically after FTI_Init
exec_id                                 = 20131120_150152

[advanced]
# Block size for communications
block_size                              = 1024

# MPI tag for FTI communications
mpi_tag                                 = 2612

# Set to 1 for local tests in one single node
local_test                              = 0
```

Scaling to ~10K processes

- CURIE supercomputer in France
- SSD on the compute nodes (16 cores)
- HYDRO scientific application
- Using 1 FTI dedicated process per node
- Checkpoint every ~6 minutes
- Weak scaling to almost 10k processes

Scaling to ~10K processes



Scaling to >32K processes

- MIRA supercomputer at ANL (BG\Q)
- Persistent memory compute nodes
- LAMMPS scientific application
- Lennard-Jones simulation of 1.3 billion atoms
- 512 nodes, 64 MPI processes per node (32,678pr.)
- Power monitoring during the entire run
- Checkpoint every ~5 minutes
- Less than 5% overhead on time to completion

Scaling to >32K processes

Synchronous Checkpoint

Without FTI – dedicated process

Head = 0

Execution: ~ 3000s



Scaling to >32K processes

Asynchronous Checkpoint

With FTI – dedicated process

Head = 1

Execution: ~ 2400s

Execution 10 minutes Faster



Features and Limitations

- ✔ FTI can predict time and size of next checkpoints
- ✔ Detailed knowledge of the datasets allows for:
  - ✔ Transparent data compression-verification
  - ✔ Transparent dedicated processes (Comm. Split)
  - ✔ Topology reconstruction upon restart
- ✔ Dynamic checkpoint interval adaptation

- ✗ FTI needs every rank in the given communicator to write a checkpoint file
- ✗ Application level checkpoint (code modification)
- ✗ Coordinated checkpoint, everybody restarts

Thank You!!!!