

# DPhil Thesis Draft



Alessandro Lodi  
Trinity College  
University of Oxford

A thesis submitted for the degree of  
*Doctor of Philosophy*

Michaelmas 2021



# Contents

|                                                                       |            |
|-----------------------------------------------------------------------|------------|
| <b>List of Figures</b>                                                | <b>vii</b> |
| <b>List of Abbreviations</b>                                          | <b>ix</b>  |
| <b>Abbreviations</b>                                                  | <b>xi</b>  |
| <b>1 Introduction</b>                                                 | <b>1</b>   |
| 1.1 Motivation . . . . .                                              | 1          |
| 1.2 Graphene . . . . .                                                | 1          |
| 1.2.1 crystal structure . . . . .                                     | 1          |
| 1.2.2 band dispersion . . . . .                                       | 3          |
| 1.2.3 thermal conductivity . . . . .                                  | 4          |
| 1.2.4 graphene as electrode material . . . . .                        | 5          |
| 1.2.5 Graphene Transistors . . . . .                                  | 5          |
| 1.3 Carbon-based Field Effect Transistor . . . . .                    | 8          |
| 1.4 Graphene Nanoribbons . . . . .                                    | 10         |
| 1.5 Delocalised $\pi$ -electron Systems . . . . .                     | 11         |
| <b>2 Foundations</b>                                                  | <b>13</b>  |
| 2.1 Charge Transport In Zero-Dimensional Objects . . . . .            | 13         |
| 2.2 Charge Transport in One-Dimensional Objects . . . . .             | 13         |
| 2.3 Thermoelectric Phenomena in Zero-Dimensional Structures . . . . . | 14         |
| 2.4 Density Functional Theory . . . . .                               | 14         |
| 2.5 Non-Equilibrium Green Function Theory . . . . .                   | 14         |
| <b>3 Instrumentations</b>                                             | <b>15</b>  |
| 3.1 Room Temperature DC Measurements . . . . .                        | 15         |
| 3.2 Dipstick DC Measurements . . . . .                                | 15         |
| 3.3 Cryogenic DC Measurements . . . . .                               | 15         |
| 3.4 Cryogenic AC Measurements . . . . .                               | 16         |
| 3.5 Thermoelectric Measurements . . . . .                             | 16         |

|          |                                                                        |           |
|----------|------------------------------------------------------------------------|-----------|
| <b>4</b> | <b>Fabrication</b>                                                     | <b>17</b> |
| 4.1      | General Fabrication Procedure . . . . .                                | 17        |
| 4.1.1    | Graphene Preparation and Wet Transferring . . . . .                    | 17        |
| 4.2      | Graphene Nanogaps . . . . .                                            | 18        |
| 4.3      | Chip Design . . . . .                                                  | 18        |
| 4.3.1    | 2T Design . . . . .                                                    | 18        |
| 4.3.2    | 3T Design . . . . .                                                    | 18        |
| 4.3.3    | Thermoelectric Device . . . . .                                        | 18        |
| 4.4      | Deposition Process and Related Phenomna . . . . .                      | 18        |
| <b>5</b> | <b>Room Temperature Graphene Nanoribbon Single-Electron Transistor</b> | <b>19</b> |
| 5.1      | Introduction . . . . .                                                 | 19        |
| 5.2      | Sample Preparation and Characterisation . . . . .                      | 19        |
| 5.3      | Electrical Transport Measurements . . . . .                            | 20        |
| 5.4      | Summary . . . . .                                                      | 20        |
| <b>6</b> | <b>Chemical Doping of the Bandgap for Cove Graphene Nanoribbons</b>    | <b>21</b> |
| 6.1      | Introduction . . . . .                                                 | 21        |
| 6.2      | Sample Preparation and Characterisation . . . . .                      | 21        |
| 6.3      | <i>Ab-initio</i> Experiments . . . . .                                 | 21        |
| 6.4      | Electrical Transport Measurements . . . . .                            | 22        |
| 6.5      | Summary . . . . .                                                      | 22        |
| <b>7</b> | <b>Thermocurrent Spectroscopy of cove Graphene Nanoribbons</b>         | <b>23</b> |
| 7.1      | Introduction . . . . .                                                 | 23        |
| 7.2      | Sample Preparation and Characterisation . . . . .                      | 23        |
| 7.3      | Electrical Transport Measurements . . . . .                            | 24        |
| 7.4      | Summary . . . . .                                                      | 24        |
| <b>8</b> | <b>Transport Spectroscopy of Biaryl-linked Dy–Tb Porphyrin</b>         | <b>25</b> |
| 8.1      | Introduction . . . . .                                                 | 25        |
| 8.2      | Sample Preparation and Characterisation . . . . .                      | 25        |
| 8.3      | Electrical Transport Measurements . . . . .                            | 26        |
| 8.4      | Summary . . . . .                                                      | 26        |
| <b>9</b> | <b>Conclusions and Outlook</b>                                         | <b>27</b> |
| 9.1      | Conclusions . . . . .                                                  | 27        |
| 9.2      | Outlook . . . . .                                                      | 27        |

## Appendices

|          |                                                           |           |
|----------|-----------------------------------------------------------|-----------|
| <b>A</b> | <b>Review of Cardiac Physiology and Electrophysiology</b> | <b>31</b> |
| A.1      | Anatomy . . . . .                                         | 31        |
| A.2      | Mechanical Cycle . . . . .                                | 34        |
| A.3      | Electrical Cycle . . . . .                                | 35        |
| A.4      | Cellular Electromechanical Coupling . . . . .             | 37        |
|          | <b>References</b>                                         | <b>39</b> |



## List of Figures





## List of Abbreviations

- 1-D, 2-D** . . . One- or two-dimensional, referring in this thesis to spatial dimensions in an image.
- Otter** . . . . . One of the finest of water mammals.
- Hedgehog** . . . Quite a nice prickly friend.



# Abbreviations

**CNT** carbon nanotube. 8

**MW** multi-walled. 8

**SW** single-walled. 8



# 1

## Introduction

### 1.1 Motivation

Motivation

### 1.2 Graphene

#### 1.2.1 crystal structure

Graphene has a hexagonal structure where the carbon atoms are hybridised  $sp^2$ , as detailed by the Pauling theory on chemical bonds. Based on the experimental evidence collected in the last 20 years, the model that seems to best describe the proprieties of graphene is the band-structure Wallace model, which dates back in 1947, and describes graphene as a semimetal with a linear dispersion of the electronic excitations. In the International Table of Crystallography, graphene is included in the symmorphic space group #191, with symmetry  $D_6^1h$  ( $P6/mmm$ ). The triangular lattice is obtained by considering two atoms per unit cell having the respective lattice vectors:

The carbon atoms in graphene form a two-dimensional hexagonal crystal with two atoms per unit cell, as shown in figure.

$$\mathbf{a}_1 = \frac{a}{2}(3, \sqrt{3}), \quad \mathbf{a}_2 = \frac{a}{2}(3, -\sqrt{3}), \quad (1.1)$$

with  $a \approx 1.42 \text{ \AA}$  be the carbon-carbon bond length. Each atom belonging to one sublattice, called sublattice A, has three first neighbours belonging to the other sublattice, called sublattice B. With respect to one atom chosen from sublattice A as origin, the position of these first three neighbours in real space are given by:

$$\boldsymbol{\delta}_1 = \frac{a}{2}(1, \sqrt{3}), \quad \boldsymbol{\delta}_2 = \frac{a}{2}(1, -\sqrt{3}), \quad \boldsymbol{\delta}_3 = -a(1, 0), \quad (1.2)$$

The reciprocal-lattice vectors are then given

$$\mathbf{b}_1 = \frac{2\pi}{3a}(1, \sqrt{3}), \quad \mathbf{b}_2 = \frac{2\pi}{3a}(1, -\sqrt{3}), \quad (1.3)$$

In order to define the vertices of the Brillouin zone one has to apply the Bragg condition:

$$2\mathbf{k} \cdot \mathbf{G} = 0 \quad (1.4)$$

where

$$\mathbf{G} = n\mathbf{b}_1 + m\mathbf{b}_2, \quad (1.5)$$

The first amongst these are:

$$\begin{array}{lll} n = \pm 1, & m = 0, & \mathbf{G} = \pm \mathbf{b}_1, \\ n = 0, & m = \pm 1, & \mathbf{G} = \pm \mathbf{b}_2, \\ n = \pm 1, & m = \pm 1, & \mathbf{G} = \pm(\mathbf{b}_1 + \mathbf{b}_2), \end{array}$$

and all these vectors have the same modulus  $|\mathbf{G}| = \frac{4\pi}{3a}$ . By applying Bragg's condition in the first of the three cases we get:

$$\sqrt{3}k_x + k_y = \mp \frac{4\pi}{3a}, \quad (1.6)$$

which gets satisfied by the points:

$$K \equiv \mp \frac{2\pi}{3a} \left( \frac{1}{\sqrt{3}}, 1 \right) \quad (1.7)$$

For the second case one gets:

$$\mp (\sqrt{3}k_x - k_y) = \frac{4\pi}{3a}, \quad (1.8)$$

which gives the points:

$$K' \equiv \pm \frac{2\pi}{3a} \left( \frac{1}{\sqrt{3}}, -1 \right) \quad (1.9)$$

The third and last case gives the point:

$$M \equiv \pm \left( 0, \pm \frac{2\pi}{3a} \right) \quad (1.10)$$

### 1.2.2 band dispersion

The electronic structure of graphene can be model with a tight-binding hamiltonian. Following the second quantization formalism ( $\hbar = 1$  units), the hamiltonian can be written as:

$$H = -t \sum_{\langle ij \rangle, \sigma} \left( a_{\sigma,i}^\dagger b_{\sigma,j} + \text{H.c.} \right) - t' \sum_{\langle\langle ij \rangle\rangle, \sigma} \left( a_{\sigma,i}^\dagger a_{\sigma,j} + b_{\sigma,i}^\dagger b_{\sigma,j} + \text{H.c.} \right), \quad (1.11)$$

The notation  $\langle ij \rangle$  means that the sum runs over pairs of electrons which are nearest neighbour; similarly, the notation  $\langle\langle ij \rangle\rangle$  specify a summation over the next nearest neighbours; the operators  $a_{i,\sigma}^\dagger$  ( $a_{i,\sigma}$ ) and  $b_{i,\sigma}^\dagger$  ( $b_{i,\sigma}$ ) creates (annihilates) an electron with spin  $\sigma$  ( $\sigma = \uparrow, \downarrow$ ) for atoms on sublattice A and B, respectively. The value of  $t$  which reproduces best experimental result is  $t \approx 2.8$  eV and quantify the nearest-neighbour hopping energy; similarly,  $t'$  denotes the next nearest-neighbour hopping energy. The dispersion energy computed from this model reads:

$$E_{\pm}(\mathbf{k}) = \epsilon_p - t' f(\mathbf{k}) \pm t \sqrt{3 + f(\mathbf{k})}, \quad (1.12)$$

with  $f(\mathbf{k})$  defined as:

$$f(\mathbf{k}) = 2 \cos(\sqrt{3}k_y a) + 4 \cos\left(\frac{\sqrt{3}}{2}k_y a\right) \cos\left(\frac{3}{2}k_x a\right). \quad (1.13)$$

Therefore, it is possible to identify an upper ( $\pi^*$ ) band associated with the plus sign and a lower ( $\pi$ ) band described by the minus sign; these are symmetric with respect to the single-particle zero energy. The experimental estimate reported for next nearest-neighbour hopping energy is  $t' \approx 0.1\text{eV}$  thus the asymmetry introduced is small. It is worthwhile to notice that the function  $3 + f(\mathbf{k})$

If the system is not doped, there is one electron per carbon atom, so two electrons per cell: it follows that the lower band is full and the upper band is empty the upper one is empty. The system is therefore a semi-metal. The peculiarities of the dispersion in graphene become apparent when analysing their trend near the point  $\mathbf{K}$  and  $\mathbf{K}'$ . By taking the positive components for the  $\mathbf{K}$  as define in Eq. 1.7 and expanding the Eq. 1.12 as  $\mathbf{k} = \mathbf{K} + \mathbf{q}$ , with  $|\mathbf{q}| \ll |\mathbf{K}|$ , one gets:

$$E_{\pm}(\mathbf{q}) = \epsilon_p \pm \frac{3at}{2}|\mathbf{q}| \quad (1.14)$$

which is linear in  $\mathbf{q}$ . For intrinsic graphene, at  $T = 0\text{K}$   $E_F = \epsilon_p$ . The Fermi velocity is defined by the usuale relation  $v_F = \frac{1}{\hbar} \left( \frac{dE}{d\mathbf{k}} \right)$ , and in graphene  $v_F \simeq 1 \times 10^6 \text{m s}^{-1}$ .

A difference arises in the density of the states, when we limit ourselves to consider those near the Fermi energy. In the case of a two-dimensional electron gas, it is constant. On the contrary for graphene, the density of states per unite cell is:

$$\rho(E) = \frac{2A_{\text{cell}}}{\pi} \frac{|E|}{v_F^2} \quad (1.15)$$

If the graphene is charge-neautral, the DOS has two Van Hove singularities at  $\omega_{\text{VH}} = \pm 1\text{eV}$  [1]. This behaviour is in stark constrat with the DOS of carbon nanotubes and clean graphene nanoribbons, as they show  $1/\sqrt{E}$  singularities due to the 1D nature, which imposes a quantization perpendicular to the ribbon or tube longitudinal direction.

### 1.2.3 thermal conductivity

Thermal Properties of graphene



### 1.2.4 graphene as electrode material

can be used as electrode material

### 1.2.5 Graphene Transistors

The first graphene field-effect transistor (GFET) was the one reported by the Manchester group in 2004 where a scotch-taped exfoliated flake of graphene was deposited on top of 300 nm of SiO<sub>2</sub> acting as a back-gate [2]. The resulting output characteristics displayed were characteristics of an ambipolar device, with linear relation between the current and the drain-source voltage, without any saturation regime reached for the charge carrier [3] (Fig. ??): this behaviour agrees with the semi-metal nature of graphene and indicates that transistor functionality was exclusively limited by inevitable contact resistances [4]. As for any transistor, the charge carriers can be varied by sweeping the gate voltage, which distinguishable branches of the gate-transfer characteristic; the charge neutrality point (Dirac point) is where they touch each other. Large positive gate voltages promote an electron accumulation in the channel (n-type channel), and large negative gate voltages lead to a p-type channel [5, 6].

Hysteresis between the forward and reverse sweeps have been reported depending on the sweeping rate and range [7], and attributed mainly to charge trapping in silanol groups (Si–OH), mediated and assisted by surface-bound H<sub>2</sub>O molecules [8]. Despite the usefulness for its proof-of-concept purposes, back-gate devices suffered from parasitic capacitances, making impossible further integration with other components. Alternatives geometries have since then been explored, in order to increase the carriers mobility, to decrease contact resistances and parasitic capacitances, and to avoid Schottky barriers formation between the graphene and the semiconductor. Top-gate devices have been the first to chronologically appear in the literature. Back then in 2007, Lemme and co workeres used a stack of SiO<sub>2</sub> (20 nm), Ti (10 nm), and Au (100 nm) as top gate for modulating the current inside a large-area graphene channel transistor obtained by the exfoliation method [9]. Whilst the gate characteristics exhibit a similar trend of the characteristics

|                                                                   | Direct Gap |      |      | Indirect Gap |        |          |
|-------------------------------------------------------------------|------------|------|------|--------------|--------|----------|
|                                                                   | InP        | Si   | Ge   | GaAs         | InAs   | Graphene |
| $a_{\text{lattice}}$ (Å)                                          | 5.87       | 5.43 | 5.65 | 5.65         | 6.06   | 2.46     |
| $E_g$ (eV)                                                        | 1.35       | 1.12 | 0.66 | 1.42         | 0.36   | 0        |
| $\mu$ (cm <sup>2</sup> V <sup>-1</sup> s <sup>-1</sup> ) at 300 K | 2800       | 1400 | 3900 | 4600         | 16,000 | 200,000  |
| $v_{\text{sat}}$ (10 <sup>7</sup> cm s <sup>-1</sup> )            | 2.2        | 1    | 0.6  | 2.2          | 4.0    | >5       |
| DOS ( $m^*/m_0$ )                                                 | 0.077      | 1.08 | 0.56 | 0.067        | 0.023  | 0        |
| $\epsilon_r$                                                      | 12.4       | 11.9 | 16.0 | 13.1         | 14.6   | 2.4      |
| $\kappa$ (W m <sup>-1</sup> K <sup>-1</sup> )                     | 68         | 150  | 60.2 | 46           | 27     | 5000     |

**Table 1.1:** Differences between the main semiconductors used in modern digital electronics and graphene.

(the top gate reduces the back-gate current modulation, lowering the drain current by one order of magnitude) and the hysteresis, weak current saturation at high drain-source bias have been reported [10]. This effect seem due to a partial charge pinning at the contacts at high back-gate voltages [11] and carrier drift velocity eventually saturating due to optical-phonon scattering [12]. Top-gated graphene MOSFET with CVD and epitaxial graphene have been also made [13, 14]; SiO<sub>2</sub>, Al<sub>2</sub>O<sub>3</sub>, and HfO<sub>2</sub> have been used as top-gate dielectric.

However, despite the improvements obtained with a top gate, most graphene MOSFETs with large-area (gapless) graphene channels show on-off switching ratios of less than 10 at room temperature [15], much too little for complex logic circuits.

In 2012, Mehr et al. proposed a vertical arrangement of emitter (E), base (B), and collector (C) (like in a vacuum triode) where the graphene plays the base role and electrons travel vertically rather than transversely as in a GFET (Fig. ??). When the device is in the ON state, the electrons tunnel with a Fowler-Nordheim tunnelling mechanism ( $I \propto (V_{\text{sd}}/d)^2 \exp\{-\alpha d/V_{\text{sd}}\}$ ) through the emitter-base

insulator (of thickness  $d$ ), the base electrode (graphene), and the base–collector insulator. Vertical FETs based on hBN–graphene [**britnell2012field**] and WeS<sub>2</sub>–graphene [16] heterostructures with ON/OFF ratios about  $10^4$  have been reported.

Solution methods have also been addressed, by which graphene is dropcasted on top of the wafer, and then spin-coated [17]. The main difficulties arise when attempting to quantify the structure and the quality of the deposited graphene, and not many methods can guarantee a good dispersion in organic solvents [**sun2011graphene**]. Simpler ways to obtain graphene oxide in solution have been reported [**van2016effect**], but once deposited, graphene oxide needs to be reduced for obtaining pure graphene – low mobility values (up to, at best,  $1000 \text{ cm}^2 \text{ V}^{-1} \text{ s}^{-1}$  [**cresti2008charge**]) caused by defects during the fabrication steps have discouraged further investigations along this direction.

Yet in spite of the very different physics and resulting DC electrical behavior, it has been shown that graphene FETs behave very much like their semiconductor counterparts when they are operated at high frequency, under alternating-current (AC) conditions. This comparison is made by measuring each system’s frequency response, its output signal strength when it is given a particular input signal: features such as ballistic transport, linear current-voltage characteristics, high transconductance, and very high ( $> 10^8 \text{ A cm}^{-2}$ ) sustainable currents are all ideal features for analog/RF applications, which do not need to be switched off [**meric2008rf**, 12].

The primary means of estimating frequency response is through the cutoff frequency: it is a fundamental property indicating how quickly a signal can travel from the gate to the drain of the device. The frequency response depends inversely on the length of the gate, and proportionally to the transconductance, which is loosely proportional to mobility. Thus, to make faster devices, we can either reduce the gate length or use higher mobility materials [15].

The first graphene MOSFET with a cutoff frequency  $f_T$  in the gigahertz range has been reported in late 2008 [**meric2008rf**]. In 2009, graphene MOSFETs with 350-nm gates and a cutoff frequency of 50 GHz have been presented

[lin2009development]; in early 2010, a graphene MOSFET with a 240-nm gate showing an  $f_T$  of 100 GHz has been reported [14], soon followed by a 144-nm gate graphene MOSFET with  $f_T \approx 300$  GHz later that year [liao2010high]. Finally, in 2012, a graphene MOSFET with a 40-nm-long gate showing 350-GHz  $f_T$  [wu2012state] and a 67-nm gate graphene MOSFET with an  $f_T$  of 427 GHz have been reported [cheng2012high]. Graphene RF MOSFETs have successfully been realized using exfoliated (e.g., [liao2010high] and [lin2009development]), epitaxial (e.g., [14] and [10]), and CVD ([wu2011high]) graphene.

Fig. ?? shows the cutoff frequency of the best graphene MOSFETs reported, together with the  $f_T$  performance of competing RF FET types. The record  $f_T$  data of the competing FETs are 688 GHz for a 40-nm GaAs mHEMT[kim2011f] and 644 GHz for a 30-nm InP HEMT [kim201030], 485 GHz for a 29-nm Si MOSFET [lee2007record], 152 GHz for a 100-nm GaAs pHEMT [nguyen1989characterization], and 153 GHz for a 100-nm carbon nanotube (CNT) MOSFET [steiner2012high]. Worthwhile to mention also the results obtained by Han et al. [han2014graphene] in 2014, when they implemented a high-performance three-stage graphene integrated circuit using Si fabrication steps and CVD graphene: the reported performance for  $f_T$  and  $f_{\max}$  were ranging from 8 to 10 GHz and from 8.5 to 13.5 GHz.

### 1.3 Carbon-based Field Effect Transistor

A great deal of attention from the scientific community has been dedicated – since the late 90s – to carbon nanotubes (CNTs) [18]. This crystalline form of carbon is a rolled up sheet of graphene and comes in two major flavours, namely single-walled (SW) and multi-walled (MW). With typical diameter ranging from 1 to 100 nm, these hollow cylindrical structures display an electronic band gap which depends on the chirality and the diameter of the nanotube [19].

The chiral vector is the direction along which the graphene sheet is rolled up and becomes the circumference of the nanotube: it must be a linear combination of the basis vectors with integers coefficients ( $m, n$ ). Based on the values of  $m$  and  $n$ , CNTs can be metallic ( $m = n$ ), quasi-metallic ( $m - n$  is a multiple of 3, with  $m \cdot n \neq 0$  and

| <i>Device type</i> | $I_{\text{on}}/I_{\text{off}}$ | $SS$<br>(mV/dec) | $g_{\text{mt}}$<br>( $\mu\text{S cm}^{-1}$ ) | $L_{\text{ch}}$<br>(nm) | $f_T$ [ $f_{\text{max}}$ ]<br>(GHz) | Ref. |
|--------------------|--------------------------------|------------------|----------------------------------------------|-------------------------|-------------------------------------|------|
| Bottom gate        | $10^4$                         | 94               | $\sim 40$                                    | 9                       | —                                   | [21] |
|                    | $10^5$                         | $\sim 85$        | 40                                           | 15                      | —                                   | [22] |
|                    | $10^5$                         | $\sim 85$        | 20                                           | 20                      | —                                   | [22] |
|                    | $10^5$                         | 60               | 20                                           | 200                     | —                                   | [23] |
|                    | $10^5$                         | $\sim 63$        | —                                            | 200                     | —                                   | [24] |
|                    | $10^4$                         | 80               | 50                                           | 240                     | —                                   | [25] |
|                    | —                              | —                | 143                                          | 800                     | [1]                                 | [26] |
|                    | $10^4$                         | —                | —                                            | 1,500                   | 1.5 – 3.0                           | [27] |
|                    | —                              | 70               | $12^\dagger$                                 | 2,000 <sup>1</sup>      | —                                   | [28] |
|                    | $10^8$                         | —                | —                                            | $< 10,000^1$            | —                                   | [29] |
|                    | —                              | —                | - 500                                        | —                       | 30                                  | [30] |
| Top gate           | $10^6$                         | —                | $20^2$                                       | 80                      | —                                   | [31] |
|                    | 2                              | —                | $\sim 50$                                    | 100                     | 25                                  | [32] |
|                    | 50                             | —                | 310                                          | 100                     | $\sim 70$ [80]                      | [33] |
|                    | —                              | —                | 0.3                                          | 210                     | —                                   | [34] |
|                    | $10^5$                         | —                | 33.5                                         | 85,000                  | —                                   | [35] |

**Table 1.2:** Figures of merit for a few CNFET reported in literature.  $S$ : subthreshold swing;  $g_m$ : intrinsic transconductances;  $L_{ch}$ : channel length;  $\mu$ : carriers mobility

<sup>†</sup>Normalized by the tube width.

<sup>1</sup> Referred to the gated length of a nanotube.

<sup>2</sup> For the n-type transistor, whereas 10  $\mu\text{S}$  were measured for the p-type.

| <i>Device type</i> | $I_{\text{on}}$<br>(A) | $I_{\text{off}}$<br>(A) | $I_{\text{on}}/I_{\text{off}}$ | $g_{\text{mt}}$<br>( $\mu\text{S}$ ) | $SS$<br>(mV/dec) |
|--------------------|------------------------|-------------------------|--------------------------------|--------------------------------------|------------------|
| Conventional       | $1.41 \times 10^{-5}$  | $4.06 \times 10^{-10}$  | $3.4 \times 10^4$              | 29                                   | 99.6             |
| Partial S/D-doped  | $1.50 \times 10^{-5}$  | $2.33 \times 10^{-8}$   | $6.4 \times 10^2$              | 63.6                                 | 93.1             |
| Schottky-Barrier   | $3.26 \times 10^{-6}$  | $2.31 \times 10^{-8}$   | $1.41 \times 10^2$             | 19.6                                 | 109.8            |
| Tunnel             | $5.53 \times 10^{-6}$  | $1.16 \times 10^{-8}$   | $4.76 \times 10^2$             | 13                                   | 107.9            |

**Table 1.3:** Comparative simulation for the four major type of CNFETs as reported in [36]. These results are obtained by setting  $V_{\text{sd}} = 0.5$  V.

$m \neq n$ ), and semiconducting for the majority of the remaining cases – exceptions due to the curvature (spin–orbit couplings) in small-diameter tubes are also known [20].

Detail here the carbon nanotube journey.

## 1.4 Graphene Nanoribbons

The scientific interest for graphene nanoribbons started in the physics community. Although this may appear irrelevant at the first glance, we will see that this actually had an impact over the last twenty years of progress in the field. The physics community was looking for a way to open a bandgap in graphene. As mentioned in Sec. 1.1, graphene is a semi-metal, therefore unsuitable for all those semiconducting applications where the conduction paths for the charge carriers are well defined.

The first class of methods for synthesising graphene nanoribbons are methods that involve cutting or producing rectangular shapes from the graphene lattice through macroscopic methods. For this reason, they are also known as *top-down* approaches. Although they have seen an improvements in recent years, common drawbacks for this class of methods are a random distribution in the widths, a non-atomical control of the edge structures, and non-negligible impurity concentrations left after the process.

Kim and co-workers synthesized GNRs by employing the electron-beam lithography and etching technique [37]. The widths of GNRs obtained by this technique were scattered over a broad range, and most of the edges were extremely rough. An 8 nm GNR FET showed a dramatically improved on/off ratio of about 160.

Nanocutting of graphene is another promising method of GNR synthesis. In 2008, Strachan et al. used thermally activated Fe nanoparticles as chemical scissors to cut graphene sheet along a specific crystallographic direction [37, 38]. Later, Ni and other catalysts were employed as well. The carbon-carbon bond breaking is driven by the combustion reaction  $\text{Ni} + \text{C}_{\text{graphene}} + 2\text{H}_2 \uparrow \longrightarrow \text{Ni/Fe} + \text{CH}_4 \uparrow$  catalysed by the nanoparticles, thus producing hydrocarbon compounds. One of the reason that have discouraged these synthetic way is the random width distribution obtained: this is likely to be a consequence of the change in direction when nanoparticles encounter defects or edges.

It will be interesting to discuss the  $E_g \propto 1/W$  relation as the model used for describing gnr is the particle in the box, but in the toy model (particle in a box) as a relation of the kind  $E_g \propto 1/W^2$ .

## 1.5 Delocalised $\pi$ -electron Systems

Porphyrin





# 2

## Foundations

### Contents

---

|            |                                                      |           |
|------------|------------------------------------------------------|-----------|
| <b>1.1</b> | <b>Motivation</b>                                    | <b>1</b>  |
| <b>1.2</b> | <b>Graphene</b>                                      | <b>1</b>  |
| 1.2.1      | crystal structure                                    | 1         |
| 1.2.2      | band dispersion                                      | 3         |
| 1.2.3      | thermal conductivity                                 | 4         |
| 1.2.4      | graphene as electrode material                       | 5         |
| 1.2.5      | Graphene Transistors                                 | 5         |
| <b>1.3</b> | <b>Carbon-based Field Effect Transistor</b>          | <b>8</b>  |
| <b>1.4</b> | <b>Graphene Nanoribbons</b>                          | <b>10</b> |
| <b>1.5</b> | <b>Delocalised <math>\pi</math>-electron Systems</b> | <b>11</b> |

---

## 2.1 Charge Transport In Zero-Dimensional Objects

quantum dots transport physics

## 2.2 Charge Transport in One-Dimensional Objects

nanowires transport physics

## 2.3 Thermoelectric Phenomena in Zero-Dimensional Structures

What are the necessary changes that one has to take into account when dealing also with other extensive variable such as a temperature gradient

## 2.4 Density Functional Theory

What are the relevant parameters/quantities that we are interested to calculate ab initio Why we opted for a pseudopotential such as SIESTA rather than others (quantum espresso). Explain why calculating the isolated gas phase all-electron electronic structure is legit for a qualitative see how the electron density is distributed over the system.

Remember also to emphasise the difference from stricly and non-stricly localised functions used for computing the electronic properties: when the functions are stricly localised they are zero outside a given radius from the atom they are associated with and so the radius is a key quality determined parameter for the basis set

## 2.5 Non-Equilibrium Green Function Theory

This section is needed to explain formally the results from transiesta and TB-trans calculations

# 3

## Instrumentations

### Contents

---

|     |                                                                   |    |
|-----|-------------------------------------------------------------------|----|
| 2.1 | Charge Transport In Zero-Dimensional Objects . . . . .            | 13 |
| 2.2 | Charge Transport in One-Dimensional Objects . . . . .             | 13 |
| 2.3 | Thermoelectric Phenomena in Zero-Dimensional Structures . . . . . | 14 |
| 2.4 | Density Functional Theory . . . . .                               | 14 |
| 2.5 | Non-Equilibrium Green Function Theory . . . . .                   | 14 |

---

### 3.1 Room Temperature DC Measurements

Describe here the probe station setup]

### 3.2 Dipstick DC Measurements

Describe here the dipstick used for both liquid N<sub>2</sub> and liquid He

### 3.3 Cryogenic DC Measurements

Describe here the delft box. Describe how the delft box modular structure enables to adapt two and multi-terminal DC measurements

## 3.4 Cryogenic AC Measurements

Describe here the delft box + lock-in setup and why it is so complicated to set it up

## 3.5 Thermoelectric Measurements

Describe here the setup used for the thermoelectric devices and why it needs a dedicated section Describe also here from a setup point of view which complications have raised during the setup (direct lines instead of dc lines, the need to use nano-D connectors and to design the a new pcb board).

# 4

## Fabrication

### Contents

---

|            |                                                   |           |
|------------|---------------------------------------------------|-----------|
| <b>3.1</b> | <b>Room Temperature DC Measurements . . . . .</b> | <b>15</b> |
| <b>3.2</b> | <b>Dipstick DC Measurements . . . . .</b>         | <b>15</b> |
| <b>3.3</b> | <b>Cryogenic DC Measurements . . . . .</b>        | <b>15</b> |
| <b>3.4</b> | <b>Cryogenic AC Measurements . . . . .</b>        | <b>16</b> |
| <b>3.5</b> | <b>Thermoelectric Measurements . . . . .</b>      | <b>16</b> |

---

## 4.1 General Fabrication Procedure

The steps are well known: chip preparation, e-beam, development, metal deposition and lift-off, graphene transfer old process, graphenea graphene

### 4.1.1 Graphene Preparation and Wet Transferring

Initially the graphene was transferred on top of the substrate through the wet transfer method. The graphene was supplied by Graphene ain 5 x 5 cm2 rectangles, with a PMMA front-layer and a back-layer of partially removed graphene. Before transfer, the back-layer had to be fully removed via etching, and the remaining stack appropriately sized for the substrates for this work. The graphene arrived in a vacuum-sealed pack, which had to be transported to the cleanroom before

being opened and the following preparation steps initiated. Figure 6.2 depicts the main stages involved in preparing the graphene for transfe

## 4.2 Graphene Nanogaps

Here three methods have been exploited: standard feedback electroburning, gate-dependent electroburning, and lithographic patterning of graphene nanogap

## 4.3 Chip Design

Here the designs for the different chips that have been used. Give a proper credit to Dr. Alex Gee for the fabrication of thermoelectric and the common gate ones.

### 4.3.1 2T Design

How convenient and 'quick' is the usage of a backgate device. List, as usual, pro and cons

### 4.3.2 3T Design

Why the need to use 3T over 2T

#### Local Gates from Waterloo

Give proper credit

#### Interconnected Drain and Gate

The one I made and also made with the help of Alex

### 4.3.3 Thermoelectric Device

Common and different features of the thermoelectric

## 4.4 Deposition Process and Related Phenomna

Why it has been important to try different deposition techniques How this has been qualitatevely addressed.

# 5

## Room Temperature Graphene Nanoribbon Single-Electron Transistor

### Contents

---

|            |                                                          |           |
|------------|----------------------------------------------------------|-----------|
| <b>4.1</b> | <b>General Fabrication Procedure . . . . .</b>           | <b>17</b> |
| 4.1.1      | Graphene Preparation and Wet Transferring . . . . .      | 17        |
| <b>4.2</b> | <b>Graphene Nanogaps . . . . .</b>                       | <b>18</b> |
| <b>4.3</b> | <b>Chip Design . . . . .</b>                             | <b>18</b> |
| 4.3.1      | 2T Design . . . . .                                      | 18        |
| 4.3.2      | 3T Design . . . . .                                      | 18        |
| 4.3.3      | Thermoelectric Device . . . . .                          | 18        |
| <b>4.4</b> | <b>Deposition Process and Related Phenomna . . . . .</b> | <b>18</b> |

---

### 5.1 Introduction

A brief intro why single-electron transistors with gnr are interesting A brief intro to what we are gonna do/measure in this chapter

### 5.2 Sample Preparation and Characterisation

How the sample it has been prepared (lot of crossreference with previous chapters)  
Explained why the scarcity of characterisation checks is intrinsically scarce in molecular electronics.

## 5.3 Electrical Transport Measurements

What type of experiments have been performed and which tricks have been used in triton to do so. What are the evolution in temperature of the zero-bias, low-bias and high bias conductance. Look at the dependence in temperature and explain possible interpretations: why it is not a Luttinger Liquid (the gnr has a bandgap) and what possible phonon modes are responsible at some point for desctructing the

## 5.4 Summary



# 6

## Chemical Doping of the Bandgap for Cove Graphene Nanoribbons

### Contents

---

|     |                                                   |    |
|-----|---------------------------------------------------|----|
| 5.1 | Introduction . . . . .                            | 19 |
| 5.2 | Sample Preparation and Characterisation . . . . . | 19 |
| 5.3 | Electrical Transport Measurements . . . . .       | 20 |
| 5.4 | Summary . . . . .                                 | 20 |

---

### 6.1 Introduction

A brief intro on how why it is important to study this

### 6.2 Sample Preparation and Characterisation

How the sample it has been prepared (lot of crossreference with previous chapters)  
Explained why the scarcity of characterisation checks i s intrinsically scarce in  
molecular electronics.

### 6.3 *Ab-initio* Experiments

What DFT and NEGF have been used and for what.

## 6.4 Electrical Transport Measurements

Explain how the calculations have initially suggested the comparison between the base case and the methoxy groups, as they have the largest bandgap distance.

## 6.5 Summary

# 7

## Thermocurrent Spectroscopy of covalent Graphene Nanoribbons

### Contents

---

|     |                                                   |    |
|-----|---------------------------------------------------|----|
| 6.1 | Introduction . . . . .                            | 21 |
| 6.2 | Sample Preparation and Characterisation . . . . . | 21 |
| 6.3 | <i>Ab-initio</i> Experiments . . . . .            | 21 |
| 6.4 | Electrical Transport Measurements . . . . .       | 22 |
| 6.5 | Summary . . . . .                                 | 22 |

---

### 7.1 Introduction

A brief intro on how why it is important to study this what has been done.

### 7.2 Sample Preparation and Characterisation

How the sample it has been prepared (lot of crossreference with previous chapters)

Explained why the scarcity of characterisation checks is intrinsically scarce in molecular electronics.

## 7.3 Electrical Transport Measurements

Explain how the calculations have initially suggested the comparison between the base case and the methoxy groups, as they have the largest bandgap distance.

## 7.4 Summary

# 8

## Transport Spectroscopy of Biaryl-linked Dy–Tb Porphyrin

### Contents

---

|            |                                                          |           |
|------------|----------------------------------------------------------|-----------|
| <b>7.1</b> | <b>Introduction . . . . .</b>                            | <b>23</b> |
| <b>7.2</b> | <b>Sample Preparation and Characterisation . . . . .</b> | <b>23</b> |
| <b>7.3</b> | <b>Electrical Transport Measurements . . . . .</b>       | <b>24</b> |
| <b>7.4</b> | <b>Summary . . . . .</b>                                 | <b>24</b> |

---

### 8.1 Introduction

A brief intro on how why it is important to study this

### 8.2 Sample Preparation and Characterisation

How the sample it has been prepared (lot of crossreference with previous chapters)

Explained why the scarcity of characterisation checks i s intrinsically scarce in  
molecular electronics.

## 8.3 Electrical Transport Measurements

Explain how the calculations have initially suggested the comparison between the base case and the methoxy groups, as they have the largest bandgap distance.

## 8.4 Summary

# 9

## Conclusions and Outlook

### Contents

---

|     |                                                   |    |
|-----|---------------------------------------------------|----|
| 8.1 | Introduction . . . . .                            | 25 |
| 8.2 | Sample Preparation and Characterisation . . . . . | 25 |
| 8.3 | Electrical Transport Measurements . . . . .       | 26 |
| 8.4 | Summary . . . . .                                 | 26 |

---

### 9.1 Conclusions

Here the final conclusions

### 9.2 Outlook





# Appendices



*Cor animalium, fundamentum est vitæ, princeps omnium, Microcosmi Sol, a quo omnis vegetatio dependet, vigor omnis & robur emanat.*

*The heart of animals is the foundation of their life, the sovereign of everything within them, the sun of their microcosm, that upon which all growth depends, from which all power proceeds.*

— William Harvey [39]



# Review of Cardiac Physiology and Electrophysiology

Appendices are just like chapters. Their sections and subsections get numbered and included in the table of contents; figures and equations and tables added up, etc. Lorem ipsum dolor sit amet, consectetur adipiscing elit. Sed et dui sem. Aliquam dictum et ante ut semper. Donec sollicitudin sed quam at aliquet. Sed maximus diam elementum justo auctor, eget volutpat elit eleifend. Curabitur hendrerit ligula in erat feugiat, at rutrum risus suscipit. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Integer risus nulla, facilisis eget lacinia a, pretium mattis metus. Vestibulum aliquam varius ligula nec consectetur. Maecenas ac ipsum odio. Cras ac elit consequat, eleifend ipsum sodales, euismod nunc. Nam vitae tempor enim, sit amet eleifend nisi. Etiam at erat vel neque consequat.

## A.1 Anatomy

Lorem ipsum dolor sit amet, consectetur adipiscing elit. Donec accumsan cursus neque. Pellentesque eget tempor turpis, quis malesuada dui. Proin egestas, sapien sit amet feugiat vulputate, nunc nibh mollis nunc, nec auctor turpis purus sed metus. Aenean consequat leo congue volutpat euismod. Vestibulum et vulputate

nisl, at ultrices ligula. Cras pulvinar lacinia ipsum at bibendum. In ac augue ut ante mollis molestie in a arcu.

Etiam vitae quam sollicitudin, luctus tortor eu, efficitur nunc. Vestibulum maximus, ante quis consequat sagittis, augue velit luctus odio, in scelerisque arcu magna id diam. Proin et mauris congue magna auctor pretium id sit amet felis. Maecenas sit amet lorem ipsum. Proin a risus diam. Integer tempus eget est condimentum faucibus. Suspendisse sem metus, consequat vel ante eget, porttitor maximus dui. Nunc dapibus tincidunt enim, non aliquam diam vehicula sed. Proin vel felis ut quam porta tempor. Vestibulum elit mi, dictum eget augue non, volutpat imperdiet eros. Praesent ac egestas neque, et vehicula felis.

Pellentesque malesuada volutpat justo, id eleifend leo pharetra at. Pellentesque feugiat rutrum lobortis. Curabitur hendrerit erat porta massa tincidunt rutrum. Donec tincidunt facilisis luctus. Aliquam dapibus sodales consectetur. Suspendisse lacinia, ipsum sit amet elementum fermentum, nulla urna mattis erat, eu porta metus ipsum vel purus. Fusce eget sem nisl. Pellentesque dapibus, urna vitae tristique aliquam, purus leo gravida nunc, id faucibus ipsum magna aliquet ligula. Lorem ipsum dolor sit amet, consectetur adipiscing elit. Proin sem lacus, rutrum eget efficitur sed, aliquam vel augue. Aliquam ut eros vitae sem cursus ultrices ut ornare urna. Nullam tempor porta enim, in pellentesque arcu commodo quis. Interdum et malesuada fames ac ante ipsum primis in faucibus. Curabitur maximus orci purus, ut molestie turpis pellentesque ut.

Donec lacinia tristique ultricies. Proin dignissim risus ut dolor pulvinar mollis. Proin ac turpis vitae nibh finibus ullamcorper viverra quis felis. Mauris pellentesque neque diam, id feugiat diam vestibulum vitae. In suscipit dui eu libero ultrices, et sagittis nunc blandit. Aliquam at aliquet ex. Nullam molestie pulvinar ex vitae interdum. Praesent purus nunc, gravida id est consectetur, convallis elementum nulla. Praesent ex dolor, maximus eu facilisis at, viverra eget nulla. Donec ullamcorper ante nisi. Sed volutpat diam eros. Nullam egestas neque non tortor aliquet, sed pretium velit tincidunt. Aenean condimentum, est ac vestibulum mattis, quam

augue congue augue, mattis ultrices nibh libero non ante. Lorem ipsum dolor sit amet, consectetur adipiscing elit.

Aenean volutpat eros tortor, non convallis sapien blandit et. Maecenas faucibus nulla a magna posuere commodo. Nullam laoreet ante a turpis laoreet malesuada. Phasellus in varius sem. Vestibulum sagittis nibh sed tincidunt blandit. Donec aliquam accumsan odio sit amet lacinia. Integer in tellus diam. Vivamus varius massa leo, vitae ullamcorper metus pulvinar sed. Maecenas nec lorem ornare, elementum est quis, gravida massa. Suspendisse volutpat odio ex, ac ultrices leo ultrices vel. Sed sed convallis ipsum. Pellentesque euismod a nulla sed rhoncus. Sed vehicula urna vitae mi aliquet, non sodales lacus ullamcorper. Duis mattis justo turpis, id tempus est tempus eu. Curabitur vitae hendrerit ligula.

Curabitur non pretium enim, in commodo ligula. Etiam commodo eget ligula a lacinia. Vestibulum laoreet ante tellus, vel congue sapien ornare in. Donec venenatis cursus velit vitae pulvinar. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Suspendisse in metus lectus. Pellentesque gravida dolor eget finibus imperdiet. Duis id molestie tortor. Mauris laoreet faucibus facilisis. Aliquam vitae dictum massa, sit amet dignissim lacus.

Fusce eleifend tellus id ex consequat maximus. Donec ultrices ex ut turpis ornare, non molestie mi placerat. Nulla sit amet auctor nunc, sit amet euismod elit. Phasellus risus tellus, condimentum a metus et, venenatis tristique urna. Cras mattis felis eget ipsum fermentum egestas. Ut augue odio, venenatis id convallis vel, congue quis augue. Maecenas sed maximus est, posuere aliquet tortor. Ut condimentum egestas nisi eu porttitor. Ut mi turpis, posuere id lorem vel, elementum tempor arcu.

Morbi nisl arcu, venenatis non metus ac, ullamcorper scelerisque justo. Nulla et accumsan lorem. Mauris aliquet dui sit amet libero aliquet, in ornare metus porttitor. Integer ultricies urna eu consequat ultrices. Maecenas a justo id purus ultricies posuere sed et quam. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Sed eleifend risus quis aliquet gravida. Nullam ac erat porta est bibendum dictum in a dolor. Nam eget turpis viverra, vulputate

lectus eget, mattis ligula. Nam at tellus eget dui lobortis sodales et ut augue. In vestibulum diam eget mi cursus, ut tincidunt nulla pellentesque.

Aliquam erat volutpat. Sed ultrices massa id ex mattis bibendum. Nunc augue magna, ornare at aliquet gravida, vehicula sed lorem. Quisque lobortis ipsum eu posuere eleifend. Duis bibendum cursus viverra. Nam venenatis elit leo, vitae feugiat quam aliquet sed. Cras velit est, tempus ac lorem sed, pharetra lobortis ipsum. Donec suscipit gravida interdum. Nunc non finibus est. Nullam turpis elit, tempus non ante.

## A.2 Mechanical Cycle

Lorem ipsum dolor sit amet, consectetur adipiscing elit. Aenean tellus est, suscipit sed facilisis quis, malesuada at ipsum. Nam tristique urna quis quam iaculis, et mattis orci pretium. Praesent euismod elit vel metus commodo ultrices. Vestibulum et tincidunt ex, in molestie ex. Donec ullamcorper sollicitudin accumsan. Etiam ac leo turpis. Duis a tortor felis. Nullam sollicitudin eu purus ac hendrerit. Nam hendrerit ligula libero, eget finibus orci bibendum a. Aenean ut ipsum magna.

Ut viverra, sapien sed accumsan blandit, nisi sem tempus tellus, at suscipit magna erat ornare nunc. Proin lacinia, nisi ut rutrum malesuada, nibh quam pellentesque nunc, sit amet consectetur purus felis ac tortor. Suspendisse lacinia ipsum eu sapien pellentesque mattis. Mauris ipsum nunc, placerat non diam vel, efficitur laoreet nunc. Sed lobortis, ipsum eget gravida facilisis, sem nulla viverra mi, in placerat eros sem viverra lacus. Aliquam porta aliquet diam vel commodo. Nulla facilisi. Duis erat libero, lobortis vel hendrerit vitae, sagittis id dui. Nulla pretium eros nec quam tincidunt, vel luctus mi aliquam. Integer imperdiet purus in est tristique venenatis. Ut pellentesque, nunc vitae iaculis ultricies, urna turpis dignissim risus, a laoreet felis magna nec erat.

Quisque sollicitudin faucibus ligula, et egestas nibh dictum sit amet. Proin eu mi a lectus congue pretium eu quis arcu. Suspendisse vehicula libero eu ipsum aliquam, vel elementum nibh mattis. Sed sed sapien vitae turpis tristique pulvinar a ut metus. Etiam semper gravida est, mollis gravida est porta ac. Proin eget tincidunt

erat. Maecenas ultrices erat eget purus ultricies, ut lacinia arcu dictum. Nam et nisi sit amet ex congue mattis vel eget lorem. Aliquam erat volutpat. Pellentesque porttitor nibh vitae elementum consectetur. Aenean et est lobortis, congue sapien non, ullamcorper sapien. Ut facilisis sem non dapibus vehicula.

Mauris euismod odio dolor, sit amet gravida mauris placerat et. Curabitur nec dolor non nibh molestie lobortis dignissim non ante. Nullam rutrum lobortis ultrices. Aenean ex erat, elementum sed maximus id, posuere id quam. Proin rutrum ex elit, pretium aliquam risus finibus at. Aenean egestas orci velit, sed aliquet sapien condimentum a. Duis consequat, arcu eu viverra venenatis, dolor lorem gravida lectus, non aliquet nisi sem at augue. Donec laoreet blandit luctus. Aenean vehicula nisl vel faucibus luctus. Sed ut semper velit, vitae laoreet magna. Sed at interdum magna.

Sed iaculis faucibus odio, eu aliquam purus efficitur vel. Cras at nulla ac enim congue varius ut et nulla. Integer blandit mattis augue.

### **A.3 Electrical Cycle**

Lorem ipsum dolor sit amet, consectetur adipiscing elit. In faucibus condimentum rhoncus. Ut dictum nisl id risus gravida lobortis. Sed vehicula mollis tellus ut varius. Fusce eget egestas dui, et commodo dui. Proin sollicitudin interdum tempus. Nullam in elit a enim fringilla bibendum. Vestibulum sodales pellentesque condimentum. Nulla facilisi. Nunc et dolor in nulla eleifend dictum at vel ligula. Aliquam ut velit non elit ullamcorper porta ac et ex. Fusce ornare magna non nunc vestibulum, eget molestie quam dictum. In interdum aliquam odio, in posuere tellus convallis quis. Curabitur non diam elit. Proin vulputate orci diam, a tincidunt ante luctus eu. Ut a viverra ligula. Curabitur pulvinar tempus tellus eget suscipit.

Aliquam posuere massa at ante dapibus congue. Curabitur ullamcorper tortor eget consectetur aliquet. Mauris tempor magna id mauris fringilla, a varius erat blandit. Nam eleifend ullamcorper placerat. Phasellus augue tortor, volutpat bibendum lorem nec, fringilla volutpat nisl. Mauris cursus urna metus, vel eleifend orci iaculis ut. Sed sit amet scelerisque massa, quis consequat dui. Donec

semper sem dui, ac placerat velit egestas vel. Nulla facilisi. Quisque tellus eros, sagittis malesuada augue ut, faucibus dictum nulla. Vestibulum non dapibus erat, ut consequat libero. Ut turpis mi, dapibus commodo libero lobortis, maximus vestibulum lectus. Vestibulum sit amet sapien dapibus, tincidunt leo in, suscipit arcu. Sed in erat bibendum, laoreet eros eu, pellentesque justo. Nulla sodales purus neque, eget maximus ipsum consequat at. Maecenas a nisl sagittis, tempus ipsum sed, dictum mauris.

Suspendisse posuere odio lacus, at auctor tortor vehicula sed. Phasellus suscipit ornare enim vitae placerat. Sed viverra purus vel sapien tempor, quis iaculis erat laoreet. Aenean vel nunc vestibulum, ornare nunc ac, mollis urna. Aenean ultrices felis ipsum, ac semper est ullamcorper in. Donec in justo varius, egestas tortor ut, venenatis augue. Duis mattis, ligula quis lacinia fringilla, tellus neque accumsan ipsum, vitae tempor metus elit vel nibh. Curabitur porttitor urna nec sapien tempor, et porttitor velit malesuada.

Suspendisse aliquam nisl quis placerat vulputate. Proin dapibus ipsum ac ante sagittis, volutpat auctor sem dapibus. Nam in facilisis odio. Integer ante mauris, eleifend et pulvinar in, venenatis quis ligula. Phasellus posuere sollicitudin tortor eget euismod. Maecenas mollis tortor eget justo vulputate sagittis. Etiam hendrerit massa quis ex molestie sodales. Quisque facilisis erat lacus, id convallis sem suscipit bibendum. Integer dui urna, pharetra sed porta sed, bibendum ut odio. Donec placerat at lectus egestas consequat. Sed id rhoncus est, vitae vulputate sapien. Fusce tempus quam lorem, id ornare turpis sodales sed. Integer aliquet urna eget condimentum consequat. Vestibulum quis dui vel ligula posuere luctus id nec turpis.

Nam vitae placerat lacus. Mauris scelerisque interdum volutpat. Nunc aliquet tristique enim, sit amet molestie felis ullamcorper vitae. Nullam sollicitudin orci orci, in condimentum tellus consectetur in. Nam id justo justo. Fusce eget finibus est. Proin id tortor nec quam cursus vehicula. Aliquam ultrices eros eros, a tincidunt elit eleifend auctor.

Nullam consectetur dapibus ligula sit amet efficitur. Nunc non posuere sapien. Vivamus dui nisl, aliquam id ipsum non, pulvinar ornare neque. Nunc rhoncus



pretium congue. Fusce id laoreet enim. Cras sed massa in eros bibendum auctor in nec sem. Nam commodo, velit id porta consequat, mi arcu gravida lorem, ut aliquam elit ante quis dui. Quisque in massa sed nibh blandit dictum.

Vestibulum molestie consectetur porttitor. Donec tincidunt vel orci at pharetra. Nullam id felis sit amet nulla tempus lacinia. Integer egestas ullamcorper massa, ut ultricies diam congue sit amet. Cras sit amet velit at nibh vehicula finibus a et lorem. Cras odio metus, venenatis ut ultrices non, ornare ac orci. Morbi et nulla dui. Mauris dictum molestie nibh, eu efficitur lorem accumsan quis.

## **A.4 Cellular Electromechanical Coupling**

Lorem ipsum dolor sit amet, consectetur adipiscing elit. Nullam vitae consectetur metus, ac maximus ex. Quisque vitae ex eu lectus ultricies consequat vel non lorem. Etiam odio ipsum, tempus ut lobortis in, molestie ac leo. Vivamus mollis feugiat bibendum. Vestibulum eget venenatis quam. Aenean faucibus, massa sed ullamcorper porta, arcu nunc iaculis velit, quis consectetur purus neque placerat nibh. Vestibulum elit nunc, dignissim vulputate venenatis et, sodales non massa. Proin leo ligula, vehicula eu aliquam varius, posuere a dolor. Donec iaculis auctor neque, sit amet gravida libero porta vel. Vivamus consequat elementum lacus, at bibendum mauris egestas nec. Fusce fermentum diam eu dolor ornare, vitae vestibulum leo interdum. Morbi luctus libero quis dictum laoreet. Etiam semper porta ante, vel ullamcorper enim sodales quis.

Nullam eu nisi faucibus, fermentum ex auctor, tempor arcu. Phasellus condimentum erat mi, condimentum malesuada ligula congue venenatis. Nullam gravida imperdiet urna quis cursus. Ut tempus nec purus eget posuere. Cras non nulla sit amet justo aliquet pellentesque nec sed eros. Nam aliquam nisl urna, in placerat magna gravida venenatis. Donec interdum vel magna ullamcorper molestie. Nunc felis neque, rhoncus fringilla faucibus sit amet, ultrices sed magna. Maecenas malesuada hendrerit diam in ultrices. Nam libero urna, volutpat ut auctor eget, interdum sed odio. Vestibulum suscipit mauris nec augue ornare, ut eleifend nulla gravida. Proin imperdiet, mauris quis consectetur porta, leo dui convallis leo,

id lobortis massa diam eu libero. Aenean hendrerit vel ante aliquam venenatis. Pellentesque bibendum pretium odio, ut sagittis lectus feugiat a. Donec porttitor vulputate lacus.

Nunc volutpat efficitur lacus in aliquet. Nullam non iaculis diam, at ultrices diam. Proin vehicula vulputate cursus. Morbi tempus sapien id urna lobortis interdum. Maecenas elementum sagittis elementum. Donec at sodales velit, a posuere tortor. Nulla id hendrerit tortor. Sed semper velit in magna sagittis pulvinar. Nulla nec arcu molestie, ultricies sapien sit amet, sollicitudin nisi. Donec nisi massa, suscipit ut dignissim quis, lacinia id leo.

Suspendisse ut mi metus. Morbi tincidunt ligula in porttitor consectetur. Integer eu urna urna. Suspendisse potenti. Mauris sit amet felis eu diam auctor ullamcorper. Morbi in porta nisi. Nam ante tortor, venenatis vitae tempor sed, sagittis vitae velit. In semper orci sit amet nisi ullamcorper varius. Aenean dignissim ultrices imperdiet. Maecenas lacinia enim id neque porttitor iaculis. Curabitur laoreet ante ut urna dignissim, id sollicitudin metus consectetur. Aenean massa ipsum, auctor vel ante vel, blandit dignissim libero. Fusce interdum ac magna et interdum.

*The first kind of intellectual and artistic personality  
belongs to the hedgehogs, the second to the foxes ...*

— Sir Isaiah Berlin [40]

## References

- [1] Cristina Bena and Steven A Kivelson. “Quasiparticle scattering and local density of states in graphite”. In: *Physical Review B* 72.12 (2005), p. 125432.
- [2] Kostya S Novoselov et al. “Electric field effect in atomically thin carbon films”. In: *science* 306.5696 (2004), pp. 666–669.
- [3] Yu-Ming Lin et al. “Operation of graphene transistors at gigahertz frequencies”. In: *Nano letters* 9.1 (2008), pp. 422–426.
- [4] SA Thiele, JA Schaefer, and Frank Schwierz. “Modeling of graphene metal-oxide-semiconductor field-effect transistors with gapless large-area graphene channels”. In: *Journal of Applied Physics* 107.9 (2010), p. 094505.
- [5] Phaedon Avouris. “Graphene: electronic and photonic properties and devices”. In: *Nano letters* 10.11 (2010), pp. 4285–4294.
- [6] A. H. Castro Neto et al. “The electronic properties of graphene”. In: *Rev. Mod. Phys.* 81.1 (Jan. 2009), pp. 109–162. URL: <http://link.aps.org/doi/10.1103/RevModPhys.81.109>.
- [7] Haomin Wang et al. “Hysteresis of electronic transport in graphene transistors”. In: *ACS nano* 4.12 (2010), pp. 7221–7228.
- [8] P Joshi et al. “Intrinsic doping and gate hysteresis in graphene field effect devices fabricated on SiO<sub>2</sub> substrates”. In: *Journal of Physics: Condensed Matter* 22.33 (2010), p. 334214.
- [9] Max C Lemme et al. “A graphene field-effect device”. In: *IEEE Electron Device Letters* 28.4 (2007), pp. 282–284.
- [10] JS Moon et al. “Epitaxial-graphene RF field-effect transistors on Si-face 6H-SiC substrates”. In: *IEEE Electron Device Letters* 30.6 (2009), pp. 650–652.
- [11] Antonio Di Bartolomeo et al. “Charge transfer and partial pinning at the contacts as the origin of a double dip in the transfer characteristics of graphene-based field-effect transistors”. In: *Nanotechnology* 22.27 (2011), p. 275702.
- [12] Inanc Meric et al. “Current saturation in zero-bandgap, top-gated graphene field-effect transistors”. In: *Nature nanotechnology* 3.11 (2008), p. 654.
- [13] Jakub Kedzierski et al. “Epitaxial graphene transistors on SiC substrates”. In: *IEEE Transactions on Electron Devices* 55.8 (2008), pp. 2078–2085.
- [14] Y-M Lin et al. “100-GHz transistors from wafer-scale epitaxial graphene”. In: *Science* 327.5966 (2010), pp. 662–662.
- [15] Frank Schwierz. “Graphene transistors”. In: *Nature nanotechnology* 5.7 (2010), p. 487.

- [16] Thanasis Georgiou et al. “Vertical field-effect transistor based on graphene–WS 2 heterostructures for flexible and transparent electronics”. In: *Nature nanotechnology* 8.2 (2013), p. 100.
- [17] Li-Hong Liu et al. “A simple and scalable route to wafer-size patterned graphene”. In: *Journal of materials chemistry* 20.24 (2010), pp. 5041–5046.
- [18] Mildred S Dresselhaus et al. “Carbon nanotubes”. In: *The physics of fullerene-based and fullerene-related materials*. Springer, 2000, pp. 331–379.
- [19] H-S Philip Wong and Deji Akinwande. *Carbon nanotube and graphene device physics*. Cambridge University Press, 2011.
- [20] Edward A Laird et al. “Quantum transport in carbon nanotubes”. In: *Reviews of Modern Physics* 87.3 (2015), p. 703.
- [21] Aaron D Franklin et al. “Sub-10 nm carbon nanotube transistor”. In: *Nano letters* 12.2 (2012), pp. 758–762.
- [22] Aaron D Franklin and Zhihong Chen. “Length scaling of carbon nanotube transistors”. In: *Nature nanotechnology* 5.12 (2010), p. 858.
- [23] Ralf Thomas Weitz et al. “High-performance carbon nanotube field effect transistors with a thin gate dielectric based on a self-assembled monolayer”. In: *Nano letters* 7.1 (2007), pp. 22–27.
- [24] Yu-Ming Lin et al. “High-performance carbon nanotube field-effect transistor with tunable polarities”. In: *IEEE Transactions on Nanotechnology* 4.5 (2005), pp. 481–489.
- [25] Ali Javey et al. “High-field quasiballistic transport in short carbon nanotubes”. In: *Physical Review Letters* 92.10 (2004), p. 106804.
- [26] N Chimot et al. “Gigahertz frequency flexible carbon nanotube transistors”. In: *Applied Physics Letters* 91.15 (2007), p. 153111.
- [27] Michael Schröter et al. “CNTFET-based RF electronics—State-of-the-art and future prospects”. In: *2016 IEEE 16th Topical Meeting on Silicon Monolithic Integrated Circuits in RF Systems (SiRF)*. IEEE. 2016, pp. 97–100.
- [28] Ali Javey et al. “High- $\kappa$  dielectrics for advanced carbon-nanotube transistors and logic gates”. In: *Nature materials* 1.4 (2002), p. 241.
- [29] Vladimir Derenskyi et al. “Carbon nanotube network ambipolar field-effect transistors with 108 on/off ratio”. In: *Advanced Materials* 26.34 (2014), pp. 5969–5975.
- [30] A Le Louarn et al. “Intrinsic current gain cutoff frequency of 30 GHz with carbon nanotube transistors”. In: *Applied physics letters* 90.23 (2007), p. 233108.
- [31] Ali Javey et al. “High performance n-type carbon nanotube field-effect transistors with chemically doped contacts”. In: *Nano letters* 5.2 (2005), pp. 345–348.
- [32] Yuchi Che et al. “T-gate aligned nanotube radio frequency transistors and circuits with superior performance”. In: *ACS nano* 7.5 (2013), pp. 4343–4350.
- [33] Yu Cao et al. “Radio frequency transistors using aligned semiconducting carbon nanotubes with current-gain cutoff frequency and maximum oscillation frequency simultaneously greater than 70 GHz”. In: *ACS nano* 10.7 (2016), pp. 6782–6790.

- [34] Fumiyuki Nihey et al. “A top-gate carbon-nanotube field-effect transistor with a titanium-dioxide insulator”. In: *Japanese journal of applied physics* 41.10A (2002), p. L1049.
- [35] Pak Heng Lau et al. “Fully printed, high performance carbon nanotube thin-film transistors on flexible substrates”. In: *Nano letters* 13.8 (2013), pp. 3864–3869.
- [36] Amandeep Singh, Mamta Khosla, and Balwinder Raj. “Comparative analysis of carbon nanotube field effect transistors”. In: *2015 IEEE 4th Global Conference on Consumer Electronics (GCCE)*. IEEE. 2015, pp. 552–555.
- [37] Liang Ma, Jinlan Wang, and Feng Ding. “Recent Progress and Challenges in Graphene Nanoribbon Synthesis”. In: *ChemPhysChem* 14.1 (2013), pp. 47–54.
- [38] Sujit S. Datta et al. “Crystallographic Etching of Few-Layer Graphene”. In: *Nano Letters* 8.7 (2008), pp. 1912–1915. URL: <http://arxiv.org/pdf/0806.3965v1.pdf>.
- [39] William Harvey. *Exercitatio Anatomica de Motu Cordis et Sanguinis in Animalibus*. Latin. 1st. Frankfurt: Sumptibus Guilielmi Fitzeri, 1628.
- [40] Isaiah Berlin. *The Hedgehog and the Fox: An Essay on Tolstoy’s View of History*. English. Ed. by Henry Hardy. 2nd. Princeton University Press, June 2013.