



UNIVERSITY OF TRENTO

Advanced Programming of Cryptographic Methods

Project Report

The Rust Unique Secure Talk (T.R.U.S.T)

Matteo Bordinon, Alessandro Perez, Christian Sassi

May 27, 2025

Contents

1	Introduction	2
1.1	Organization of the Report	2
1.2	Overview of the Protocol	3
1.2.1	Extended Triple Diffie-Hellman	3
1.2.2	Double Ratchet	3
2	Requirements	4
2.1	Functional Requirements	4
2.1.1	Server Functional Requirements	4
2.2	Security Requirements	5
3	Technical Details	6
3.1	Architecture	6
3.1.1	Establishment of a Secure Connection	7
3.1.2	User Registration	7
3.1.3	Adding a Friend	8
3.1.4	Sending Messages	8
3.2	Implementation	9
3.2.1	Key Generation for X3DH	9
3.2.2	Pre-Key Bundle Processing	10
3.2.3	Code Structure	13
3.2.4	Dependencies	13
4	Security Considerations	15
5	Known Limitations	16
6	Instruction for Installation and Execution	17

Chapter 1

Introduction

This report presents the design, implementation, and evaluation of **T.R.U.S.T.** (**T**he **R**ust **U**nique **S**ecure **T**alk), a terminal user interface (TUI)-based secure chat application developed in Rust. The primary objective of this project was to explore secure communication principles and implement a reliable end-to-end encryption system.

To achieve this purpose we combined different cryptographic primitives to create a key agreement protocol based on **X3DH** [2] and later encrypt each message with a new key given by the key management scheme: **Double Ratchet** [1] first introduced by Signal.

The combination of the two gives resilience to both practical and complete leak of the encryption key during the same or different sessions as we will see in later chapters 4. More over thanks to the choice of **Rust** we are sure of not having memory issues or data race conditions, also when a variable is out-of scope we are sure it is set to zero before deleting it.

1.1 Organization of the Report

This document is organized as follows: Introduction 1 provides an overview of the application's purpose and core functionalities; Requirements 2 defines both the functional and security requirements; Technical Details 3 outlines the system's architecture, the main implementation decisions, and the code structure; Security Considerations 4 discusses cryptographic measures and potential threats; Known Limitations 5 highlights current constraints and possible improvements; and finally, Instructions for Installation and Execution 6 guides readers through setting up and running the application.

1.2 Overview of the Protocol

The first step to achieve end-to-end encryption is to have a secure method of establishing a shared secret. There exists many algorithms mainly based on public key cryptography, we decided to implement **X3DH**, both for its security derived by the Diffie-Hellman algorithm and the use of signatures to prevent miss-bindings compared to the classical implementation of Diffie-Hellman.

1.2.1 Extended Triple Diffie-Hellman

X3DH establishes a shared secret key between two parties who mutually authenticate each other based on public keys. X3DH provides forward secrecy and cryptographic deniability.

This choice was also due to the fact that X3DH is designed for asynchronous settings where one user (“Bob”) is offline but has published some information to a server. Another user (“Alice”) wants to use that information to send encrypted data to Bob, and also establish a shared secret key for future communication.

Before exchanging keys with other users we first need to establish a secure connection between the user and the server so that the server can distribute the correct keys to whoever asks for them. This is done using X3DH between each user and the server we know that this process is secure because the public key of the server is hard-coded and a simple hash of the program ensures integrity.

Once a shared key is established the user can request for any key bundle containing all the necessary keys to start a chat with another user. Now the user can start the establishment of a shared secret with another user passing through the server. After the shared key is established the two parties will use the Double Ratchet to send and receive encrypted messages.

1.2.2 Double Ratchet

The parties derive new keys for every message using **Double Ratchet**, so that earlier keys cannot be calculated from later ones. The parties also send Diffie-Hellman public values attached to their messages. The results of Diffie-Hellman calculations are mixed into the derived keys so that later keys cannot be calculated from earlier ones. These properties give some protection to earlier or later encrypted messages in case of a compromise of a party’s keys.

Now that keys are derived we can send each of the messages encrypted using AES-GCM, an AEAD algorithm, which gives both CCA security and CI. Thanks to all of these algorithms we can have end-to-end encryption and ensure both confidentiality and integrity.

Chapter 2

Requirements

TRUST needs to follow a list of both **functional** requirements and **security** requirements, these properties are non negotiables, we implemented the application using these requirements as guidelines that helped us in choosing algorithms.

2.1 Functional Requirements

This section defines the functional requirements of the system, outlining the core features and expected behaviors necessary for its operation. For this project we can split them further into two sub sets **server functional requirements** and **client functional requirements**.

2.1.1 Server Functional Requirements

The server must fulfill the following functional requirements:

- **Manage user registration**
- **Distribute public keys of registered users**
- **Relay encrypted messages to their intended recipients**

The server cannot access the content of user messages; it can only identify the sender and recipient.

Client Functional Requirements

The client application, on the other hand, must meet the following requirements:

- Offer a user-friendly TUI
- Allow users to register in the system
- Enable users to add others to their contact list
- Support message exchange between users

This set of requirements should be enough to have a functional chat application, by adding the **security requirements** the application will also have: security of data in transit with end-to-end-encryption (E2EE).

2.2 Security Requirements

In addition to the functional requirements, we have established the following security requirements:

- **Server Authentication:** Clients must be able to verify the authenticity of the server.
- **Client-Server Confidentiality:** Clients must be able to establish a shared secret with the server.
- **End-to-End Confidentiality:** Clients must be able to establish a shared secret with other clients.
- **End-to-End Integrity:** Clients must use shared secrets to encrypt, decrypt, and verify the integrity of messages exchanged with both the server and other clients.
- **Forward Secrecy:** The compromise of a key must not affect the confidentiality of data exchanged previously.
- **Self Healing (Post Compromise Security):** even if an adversary temporarily compromises a user's device and obtains current session keys, future messages will remain secure as long as the device regains control and resumes proper ratcheting.

Chapter 3

Technical Details

This section provides an in-depth overview of the architecture, implementation, and key components of TRUST. It covers the cryptographic protocols used, system architecture, core libraries, and design decisions that ensure security and usability.

The application is built using Rust’s asynchronous runtime (`tokio`) and the framework for networking is `tokio-tungstenite`, while the user interface is implemented with `ratatui`. X3DH was implemented using primitives provided by the `dalek-cryptography` library, and AES-GCM using primitives provided by the `aes-gcm` library, ensuring end-to-end encryption for user messages.

3.1 Architecture

The application follows a client-server architecture with some modifications to enhance flexibility. By leveraging **WebSockets**, which provide bidirectional TCP communication, both the client and server can initiate requests. This approach simplifies development by enabling real-time message exchange without requiring traditional request-response cycles, making the system more efficient and responsive. To better understand the application’s functionality, we outline four key scenarios that define its core operations:

1. **Establishment of a Secure Connection:** The client and server perform a handshake to initiate a secure, encrypted communication channel.
2. **User Registration:** New users send their public keys and register with the server while ensuring their identity remains protected.
3. **Adding a Friend:** Users exchange public keys and establish a secure communication channel for encrypted messaging.

4. **Sending Messages:** Messages are encrypted, transmitted over WebSockets, and decrypted on the recipient's side, ensuring end-to-end security.

Each of these steps plays a crucial role in maintaining the privacy and integrity of user interactions. The following sections describe these scenarios in detail.

3.1.1 Establishment of a Secure Connection

The secure connection process begins with a standard **WebSocket handshake** (Figure 3.1) between the client and server. Once the bidirectional channel is established, the client transmits its **Pre-Key Bundle**, which the server processes to:

- Derive the shared key used to encrypt communications.
- Generate the **Server Initial Message (SIM)**, which is then sent back to the client.




Figure 3.1: WebSocket Handshake

Upon receiving the SIM, the client verifies the server's identity by comparing the known **server public identity key** with the one provided in the message. This prevents **Man-in-the-Middle (MitM) attacks**. If authentication is successful, the client processes the SIM and derives the shared key. From this point forward, all communication between the client and server will be encrypted.

3.1.2 User Registration

Once a secure connection with the server is established, the user can register by choosing a **username** and sending a **registration request** to the server. The server then verifies whether the chosen username is unique.

- If the username is **available**, the server sends a **confirmation response** to the client.




Figure 3.2: Secure connection establishment

- If the username is **already taken**, the server responds with a **"Conflict"** status code and the message **"User Already Exists"**, prompting the user to choose a different username.

Listing 3.1: Example of a Registration request

```

1 {
2   "action": "register",
3   "username": "xyz",
4   "bundle": "dGhpcyBpcyB0aGUgdXNlciBwcmVrZXkgYnVuZGxGluIGJ2U2NA
5   =="}

```

3.1.3 Adding a Friend

Once the user is registered in the system, they can add a new friend by submitting a **get user pre-key bundle request** to the server, specifying the username of the desired contact. The server then checks whether the requested user is registered in the application.

- If the user **exists**, the server responds with the requested user's **Pre-Key Bundle**.
- If the user **is not found**, the server returns a **"UserNotFound"** error response with status code 404.

3.1.4 Sending Messages

Upon receiving the requested user's **Pre-Key Bundle**, the user derives the **shared key** and generates the **initial message**. The user then sends a **send_message** request to the recipient, embedding the initial message in the **"text"** field. The request follows the JSON format below:

Listing 3.2: Initial Message Request Format

```

1 {
2   "action": "send_message",
3   "msg_type": "initial_message",
4   "to": "alice",
5   "from": "bob",
6   "text": "dGhpcyBpcyB0aGxNlciBpbml0aWFsIG1lc3NhZ2UgaW4gYmFzZTY
7   "timestamp": "2025-02-06T14:21:21+00:00"
8 }

```

The user who will receive the initial message will derive the shared key and then add the sender as a contact in their contacts list.

3.2 Implementation

This section will provide a comprehensive explanation of the implementation of each key component of the application. Each aspect of the application, from the underlying security mechanisms to the user-facing interface, is discussed in detail to give a clear understanding of the technical choices and how they come together to ensure a seamless and secure user experience.

3.2.1 Key Generation for X3DH

The function responsible for generating **Pre-Key Bundles** is `generate_prekey_bundle()`. This function creates the **Private Identity Key**, **Private Signed Pre-Key**, and their corresponding **Public Keys**. Additionally, it returns the **Pre-Key Bundle** along with the **private keys** required for secure communication.

To prevent **replay attacks**, **One-Time Pre-Keys (OTPKs)** are incorporated into the key generation process. For this purpose, a specialized function, `generate_prekey_bundle_with_otpk()`, is introduced. This function takes as input the number of **one-time pre-keys** to generate and returns a tuple containing:

- The **Pre-Key Bundle**,
- The **Private Identity Key**,
- The **Private Signed Pre-Key**,

- A vector of **private One-Time Pre-Keys**.

This approach ensures that each session can maintain **forward secrecy** while mitigating potential security risks such as **key reuse and replay attacks**.

3.2.2 Pre-Key Bundle Processing

The function responsible for processing **Pre-Key Bundles** is `process_prekey_bundle()`, which takes as input the received bundle and the receiver's **Private Identity Key**.

The function first verifies the signature contained in the bundle to ensure its authenticity. After validation, it performs the **X3DH (Extended Triple Diffie-Hellman) key agreement protocol** to derive the shared secret. This is done by passing the secret obtained from the three Diffie-Hellman exchanges through a **Key Derivation Function (KDF)** to generate the final 32-byte shared key.

Once the shared key is established, an **Initial Message (IM)** is generated, containing the following components:

- The receiver's **Public Identity Key**;
- The receiver's **Public Ephemeral Key**;
- The sender's **Public Signed Pre-Key hash** (extracted from the bundle);
- The sender's **Public One-Time Pre-Key (OTPK) hash**;
- **Associated Data**, which includes the Public Identity Keys of both the sender and receiver.

The function then returns the shared key and the initial message.

Initial Message Processing The functions responsible for processing the **Initial Message** are `process_server_initial_message()` and `process_initial_message()`. These two functions are equivalent, except that the former additionally verifies whether the **Server's Public Identity Key** provided as input matches the one included in the Initial Message.

Both functions take as input the received Initial Message, the receiver's **Private Identity Key**, **Private Signed Key**, and **Private One-Time Pre-Key (OTPK)**. They compute the three Diffie-Hellman (3DH) secrets and pass the resulting value through a **Key Derivation Function (KDF)** to derive the 32-byte shared key. Finally, they return the computed shared key.

AES Encryption The function responsible for AES encryption is `encrypt()`. This function takes as input the encryption key, the data to be encrypted, and the **Associated Data (AD)**.

First, it generates a nonce using the Cryptographically Secure Pseudo Random Number Generator (CSPRNG) provided by the `rand` crate in Rust (`OsRng`). Then, it constructs the payload and performs AES-GCM encryption. Finally, it concatenates the nonce, the associated data, and the ciphertext before returning the result as a **Base64-encoded string**.

AES Decryption The function responsible for AES decryption is `decrypt()`. It takes as input the decryption key, the cipher text to be decrypted, and the **Associated Data (AD)** and the **Nonce**.

This function checks for integrity and then performs the inverse operation of the encryption process if the message has not been tampered with. Finally, it returns the decrypted data as a **byte vector**.

Server

The server implementation is built on an asynchronous runtime provided by the `tokio` library in Rust. This library enables the server to perform non-blocking asynchronous operations, improving both flexibility and performance.

Each new connection is handled by a separate Tokio task, allowing the server to efficiently manage multiple concurrent connections. For each **Connection task**, two additional Tokio tasks are generated:

- the first task (`task_receiver`) continuously listen for incoming requests;
- the second task (`task_sender`) forwards messages to the client;

Task Receiver This task continuously listens for incoming requests on the WebSocket connection from the client. It exposes four API endpoints:

- **establish_connection**: Used to establish a secure connection between the client and the server. This API endpoint is handled by the function `handle_establish_connection()`, which first verifies whether the Pre-Key bundle is correctly formatted. If the verification is successful, the function calls `process_key_bundle()` to generate the shared secret; otherwise, it returns an error. Once the shared secret is derived, it is stored in a shared variable called `session`, allowing both tasks to access it. This endpoint is only accessible if no shared secret exists, meaning that a secure connection has not yet been established.

- **register**: Accessible once the secure connection is established, allowing the client to register within the application. This API endpoint is handled by the function `handle_registration_request()`, which first performs the necessary username validation (ensuring it is alphanumeric and not already in use). It then verifies whether the Pre-Key bundle is well-formed. If all checks pass, the user is registered in the system and it sends back a confirmation response.
- **get_user_bundle**: Accessible after the secure connection is established, enabling the client to retrieve a user's key bundle. This API endpoint is handled by the function `handle_get_bundle_request()`, which verifies whether the requested user is registered in the system. If the user exists, the function generates a response containing the corresponding key bundle; otherwise, it returns a **User Not Found** error.
- **send_message**: Available once the secure connection is established, allowing the client to exchange messages with other users. This API endpoint is handled directly by the task. It first checks whether the recipient is registered (and thus connected) to the system. If the recipient is online, the task forwards the message to the recipient's sender task, which then delivers it to the recipient's client.

All API requests received after the secure connection is established are decrypted upon arrival, and all responses are encrypted before being sent to the client.

Task Sender The Task Sender is responsible for message forwarding. It continuously listens on an `mpsc channel` for incoming messages. Upon receiving a message, it encrypts the content using the session key shared between the recipient client and the server, ensuring secure communication. Once the message is encrypted, it forwards the encrypted message to the recipient.

The content of messages is encrypted using the shared key between the two clients. The `send_message` request undergoes two layers of encryption: first, the message text is encrypted with the shared key between the clients, and then the entire request is encrypted using the shared key between the client and the server, ensuring end-to-end security.

Client & TUI

The client backend also utilizes `tokio` for asynchronous runtime. When a new client is created (i.e., when the TUI program is started), it attempts to establish a secure connection with the server. If successful, it spawns a Tokio listener task, which continuously listens for incoming responses or new messages.

To manage the correlation between requests and responses, we introduced a struct called `RequestWrapper`. This struct contains two fields: `request.uuid`, which uniquely identifies

the request, and `body`, which holds the actual request to be sent to the server. When the server responds, it includes the same `request_uuid` in the `ResponseWrapper`, allowing the client to match each response to its corresponding request.

Chat messages, on the other hand, are handled as regular `send_message` requests. When the client receives a message, it forwards it to a task running in the TUI binary, which listens for incoming messages on an `mpsc channel`. This task then invokes the appropriate handler to process the message and render it in the user interface.

3.2.3 Code Structure

The codebase is organized into five separate Cargo projects, each serving a distinct purpose:

- **Protocol:** A library that implements the cryptographic protocols used in the system, including X3DH and AES-GCM.
- **Common:** A shared library providing utility functions used by both the client and server.
- **Server:** Contains the server binary along with all necessary utility functions for server-side operations.
- **Client:** A library that facilitates client interactions with the server.
- **Tui:** Includes the TUI application binary, along with all files required for the user interface and front-end logic.

3.2.4 Dependencies

The implementation of **TRUST** application relies on several external Rust crates that provide critical functionalities such as asynchronous networking, cryptographic operations, and terminal user interface (TUI) rendering. All dependencies used in this project are well-known, actively maintained, and considered de facto standards in their respective domains, ensuring reliability, security, and long-term support. Below is an overview of the main dependencies.

Networking and Asynchronous Execution - `tokio (1.42.0)`: Provides the asynchronous runtime used throughout the application to handle concurrent tasks efficiently, enabling non-blocking communication between clients and the server. - `tokio-tungstenite (0.26.1)`: A WebSocket library that integrates with Tokio, allowing real-time, bidirectional communication over WebSockets. - `futures (0.3.31)` & `futures-util (0.3.31)`: Provide

abstractions for asynchronous programming, including streams and futures for handling asynchronous events. - **tokio-stream (0.1.17)**: Enhances stream handling within Tokio-based applications, making it easier to process asynchronous data flows.

Cryptography and Secure Communication - **aes (0.8.4) & aes-gcm (0.10.3)**: Provide authenticated encryption for securing messages using the AES-GCM encryption scheme. - **rand (0.8.5)**: A cryptographically secure random number generator, essential for generating nonces securely. - **ed25519-dalek (2.1.1)**: Implements the Ed25519 signature scheme, ensuring authentication and integrity of messages. - **x25519-dalek (2.0.1)**: Used for implementing the X3DH key exchange protocol, allowing secure key agreement between clients. - **curve25519-dalek (4.1.3)**: Provides elliptic curve operations, specifically for Diffie-Hellman key exchange and digital signatures. - **sha2 (0.10.8)**: Implements the SHA-2 family of cryptographic hash functions, ensuring data integrity and secure hashing of credentials. - **hkdf (0.12.4)**: Implements the HMAC-based Key Derivation Function (HKDF) used to derive cryptographic keys securely. - **zeroize (1.8.1)**: Ensures that sensitive cryptographic data is securely erased from memory when no longer needed.

Data Serialization and Parsing - **serde (1.0.216) & serde_json (1.0.137)**: Used for serializing and deserializing data exchanged between the client and server. - **base64 (0.22.1)**: Handles encoding and decoding of binary data, particularly for securely transmitting encrypted messages.

Terminal User Interface (TUI) - **ratatui (0.29.0)**: A Rust TUI library used to create the command-line interface for the chat application. - **crossterm (0.28.1)**: Provides cross-platform support for handling terminal input and output, including event handling and text rendering.

Utilities - **uuid (1.11.0)**: Used for generating unique request identifiers, allowing the system to match server responses with client requests. - **arrayref (0.3.9)**: Provides utilities for working with fixed-size arrays, useful in cryptographic operations.

These dependencies collectively enable our application to provide secure, efficient, and user-friendly encrypted messaging.

Chapter 4

Security Considerations

aaaaaaaaaaaaaaaaaaaa

Chapter 5

Known Limitations

aaaaaaaaaaaaaaaaaaaaa

Chapter 6

Instruction for Installation and Execution

aaaaaaaaaaaaaaaaaaaaa

Bibliography

- [1] Moxie Marlinspike and Trevor Perrin. “The Double Ratchet Algorithm”. In: (2016).
- [2] Moxie Marlinspike and Trevor Perrin. “The X3DH Key Agreement Protocol”. In: (2016).