

Package ‘RJDPprocessor’

February 14, 2025

Type Package

Title RJDPprocessor

Version 1.1.1

Author Alessandro Piovani

Maintainer Alessandro Piovani <alessandro.piovani@istat.it>,
<alessandro.piovani13@gmail.com>

Description The rjdverse libraries are the officially recommended R software for seasonal adjustment in the European Central Bank and Statistical System. The RJDPprocessor library integrates the rjdverse packages into a fully R-based production pipeline, ready to be used and easily extendable by methodologists. It offers the capability to manage the entire seasonal adjustment process: acquisition, processing, storage, automation, and not just seasonal adjustment of the data. Processing of multiple time series is possible by storing their specifications in JSON files, and interoperability with other JDemetra+ software is guaranteed because RJDPprocessor can read workspaces and is able to produce them as an output.

RJDPprocessor also provides functions to manage workspaces, such as splitting a workspace containing multiple time series into individual single-series workspaces, which are suitable for storing in databases with single time series records. Functions to merge workspaces are also available.

License EUPL

Encoding UTF-8

LazyData true

Imports RJDemetra (>= 0.2.5),
rjson (>= 0.2.21)

Suggests rjd3providers (>= 3.2.3),
readxl (>= 1.4.3),
roxygen2 (>= 7.2.3)

Roxygen list(markdown = TRUE)

RoxygenNote 7.2.3

Collate import_and_interface_definition.R
Data_reader_csv.R
Data_reader_csv_istat_format.R
Data_reader_ext_reg_tsplus.R
Data_reader_ext_reg_xlsx.R
Data_reader_ext_reg_csv.R
Data_reader_xlsx.R
Data_reader_list.R
Data_reader_xml.R

Data_reader_workspace.R
 Extended_tramoseats_spec.R
 JD_JSON.R
 JD_JSON_file_processor.R
 basic_spec.R
 utility_functions.R
 workspaces_manager.R
 report.R

R topics documented:

check_data	3
check_external_regressors	3
compare_sa_ts	4
compare_workspaces	5
convert_numeric_matrix_to_mts	6
create_diagnostic_report1	7
create_diagnostic_report2	8
Data_reader_csv	8
Data_reader_csv_istat_format	9
Data_reader_ext_reg_csv	9
Data_reader_ext_reg_tsplus	10
Data_reader_ext_reg_xlsx	11
Data_reader_list	11
Data_reader_workspace	12
Data_reader_xlsx	13
Data_reader_xml	13
from_full_to_reduced_JD_JSON_file	14
from_reduced_to_full_JD_JSON_file	15
get_r_model_from_j_model	15
get_single_ts_workspaces	16
JD_JSON_file_processor	17
JD_JSON_from_materialized_workspace	18
JD_JSON_from_virtual_workspace	20
JD_JSON_to_materialized_workspace	21
JD_JSON_to_virtual_workspace	22
merge_workspaces	23
produce_fully_R_workspace	24
read_data,Data_reader_csv-method	25
read_data,Data_reader_csv_istat_format-method	25
read_data,Data_reader_list-method	26
read_data,Data_reader_workspace-method	26
read_data,Data_reader_xlsx-method	27
read_data,Data_reader_xml-method	27
read_ext_reg_data,Data_reader_ext_reg_csv-method	28
read_ext_reg_data,Data_reader_ext_reg_tsplus-method	29
read_ext_reg_data,Data_reader_ext_reg_xlsx-method	30
read_ext_reg_info,Data_reader_ext_reg_csv-method	31
read_ext_reg_info,Data_reader_ext_reg_tsplus-method	31
read_ext_reg_info,Data_reader_ext_reg_xlsx-method	32
update_data	33

Index**34**

check_data	<i>Compare the data in a workspace with only one time series with given data</i>
------------	--

Description

This function compares the data in a workspace with only one time series with given raw data in array form

Usage

```
check_data(raw_data, ws_single_ts, raw_data_start = NA, raw_data_freq = NA)
```

Arguments

raw_data	Raw data to be compared with the ones in the workspace
ws_single_ts	The xml path of the workspace containing the data to be compared
raw_data_start	-optional- Default=NA, the starting date of the raw data in form "YYYY-MM-DD". If NA, the starting date is assumed to be the same as the workspace data
raw_data_freq	-optional- Default=NA, the frequency of the raw data (e.g. 12=monthly, 4=quarterly). If NA, the frequency is assumed to be the same as the workspace data

Value

Boolean: TRUE if data are the same, FALSE otherwise

Examples

```
require(RJDemetra)
original_directory <- getwd()
extdata_directory <- system.file("extdata", package = "RJDPProcessor")
setwd(extdata_directory)
single_workspaces_path <- "splitted_workspaces_to_merge"
single_ws<-load_workspace(paste0(single_workspaces_path,"\\VATPIC\\VATPIC.xml"))
result<-check_data(c(1,2,3), single_ws)
setwd(original_directory)
```

check_external_regressors	<i>Verify the external regressors used in a workspace</i>
---------------------------	---

Description

This function check whether the external regressors used in a workspace are up to date (i.e. they cover from the beginning to the end of the time series and have the same frequency). The workspace must contain a single time series.

Usage

```
check_external_regressors(ws_single_ts)
```

Arguments

`ws_single_ts` The xml path of the workspace containing the data to be checked

Value

Boolean: TRUE if ckeck is ok, FALSE if there are problems in the external regressors.

Examples

```
require(RJDemetra)
original_directory <- getwd()
extdata_directory <- system.file("extdata", package = "RJProcessor")
setwd(extdata_directory)
single_workspaces_path <- "splitted_workspaces_to_merge"
single_ws<-load_workspace(paste0(single_workspaces_path,"\\VATPIC\\VATPIC.xml"))
compute(single_ws)
result<- check_external_regressors(single_ws)
setwd(original_directory)
```

compare_sa_ts

Compare the same models contained in two workspaces

Description

This function compares the same models contained in two workspaces (old and new) plotting the respective sasonally adjusted series into a pdf file

Usage

```
compare_sa_ts(
  new_r_model = NA,
  new_model_workspace,
  old_model_workspace,
  materialized_ws_new = FALSE,
  materialized_ws_old = TRUE,
  java_processing_old_model = TRUE
)
```

Arguments

`new_r_model` -optional- an R model obtained via `RJDemetra::get_model(workspace)`. If != NA, this model is used as new model in the comparison. Default = NA, `new_model_workspace` is used as new model

`new_model_workspace` the workspace (relative/absolute) path of the .xml file or object used as new model in the comparison

`old_model_workspace`
the workspace (relative/absolute) path of the .xml file or object used as old model in the comparison

`materialized_ws_new`
-optional- Default=FALSE, boolean field stating whether the new workspace in the comparison is passed as a matherialized or a virtual workspace (i.e. R object)

`materialized_ws_old`
-optional- Default=TRUE, boolean field stating whether the new workspace in the comparison is passed as a matherialized or a virtual workspace (i.e. R object)

`java_processing_old_model`
-optional- Default=TRUE, use Java models for the internal processing of the old workspace (faster than R)

Value

a "comparisons.pdf" file containig the plots of the seasonally adjusted time series of both the new and old workspaces. Series with the same series_name are reported in the same plot

Examples

```
require(RJDemetra)
original_directory <- getwd()
extdata_directory <- system.file("extdata", package = "RJProcessor")
setwd(extdata_directory)
input_workspace_materialized <- "workspace_test/workspace.xml"
virtual_workspace <- load_workspace(input_workspace_materialized)
compute(virtual_workspace)
compare_sa_ts(new_model_workspace = virtual_workspace,
              old_model_workspace = input_workspace_materialized ,
              materialized_ws_new=FALSE, materialized_ws_old=TRUE,
              java_processing_old_model=FALSE)
setwd(original_directory)
```

compare_workspaces	<i>Compare two RJDemetra workspaces</i>
--------------------	---

Description

This function compares two RJDemetra workspaces, either provided as objects or file paths, and generates a report of the differences in the final seasonally adjusted series and likelihood BIC values.

Usage

```
compare_workspaces(
  workspace1,
  workspace2,
  output_file = "differences_report.txt"
)
```

Arguments

workspace1	Either an RJDemetra workspace object or a file path to a workspace.
output_file	Character string specifying the path of the output report file. Default is "differences_report.txt".
patworkspace2	Either an RJDemetra workspace object or a file path to a workspace.

Details

The function loads the workspaces if they are provided as file paths, computes the models, and extracts the seasonally adjusted series and likelihood BIC. It then compares these values and records any differences in the output file.

Differences are checked for the last 36 observations of the seasonally adjusted series and the likelihood BIC values.

Value

The function does not return a value but writes a report to the specified file.

```
convert_numeric_matrix_to_mts
```

Convert a numeric matrix to an mts object

Description

This function takes a numeric matrix with dates as row names and series names as column names, and converts it to an mts (multivariate time series) object. It is good for converting data read by data_readers and ext_reg_data_readers into mts that could be useful as input as usrdef.var for RJDemetra functions tramoseats() and X13()

Usage

```
convert_numeric_matrix_to_mts(data_matrix, freq = NULL)
```

Arguments

data_matrix	A numeric matrix where row names are dates in "YYYY-MM-DD" format, and column names are the names of the time series.
freq	-optional- The frequency of the time series. If not provided, the function will try to infer the frequency based on the difference between the first two dates.

Value

An mts object with the given time series data.

Examples

```
input_data_file_name <- system.file("extdata", "CSV-FAS/grezzi_trim_FAS.csv", package = "RJProcessor")
input_data_reader    <- Data_reader_csv(input_source = input_data_file_name)
data_matrix <- input_data_reader@read_data()

# Convert the matrix to an mts object
mts_object <- convert_numeric_matrix_to_mts(data_matrix)
print(mts_object)
```

```
create_diagnostic_report1
```

Create Diagnostic Report for Time Series Models

Description

This function generates a diagnostic report for time series models, including BIC, p-values from Ljung-Box tests, and normality test results. It organizes the output into categories: all series, series with Ljung-Box problems, series with normality issues, and a summary of problematic series.

Usage

```
create_diagnostic_report1(workspace, output_file = "report.txt")
```

Arguments

workspace	A workspace object containing the time series models.
output_file	A string specifying the output file path where the report will be saved (default is "report.txt").

Examples

```
require(RJDemetra)

original_directory <- getwd()
extdata_directory <- system.file("extdata", package = "RJProcessor")
setwd(extdata_directory)
ws_path <- "WorkspaceTUR-container/workspace-TUR.xml"

workspace <- load_workspace(file=ws_path)
create_diagnostic_report1(workspace, output_file = "report.out")
setwd(original_directory)
```

```
create_diagnostic_report2
```

Create another Diagnostic Report for Time Series Models

Description

This function generates a diagnostic report for time series models. It shows for every time series a complete view, including regression coefficients with their T-statistics as well as LB, LB2, Normality tests and BIC

Usage

```
create_diagnostic_report2(workspace, output_file = "series_info.txt")
```

Arguments

<code>workspace</code>	A workspace object containing the time series models.
<code>output_file</code>	A string specifying the output file path where the report will be saved (default is "report.txt").

Examples

```
require(RJDemetra)

original_directory <- getwd()
extdata_directory <- system.file("extdata", package = "RJDProcessor")
setwd(extdata_directory)
ws_path <- "WorkspaceTUR-container/workspace-TUR.xml"

workspace <- load_workspace(file=ws_path)
create_diagnostic_report2(workspace, output_file = "report.out")
setwd(original_directory)
```

```
Data_reader_csv
```

Constructor (R-like) of the Data_reader object

Description

This function creates a `Data_reader` object capable of reading data from CSV files and returning it using the `read_data()` function.

Usage

```
Data_reader_csv(input_source = NA, ...)
```

Arguments

<code>input_source</code>	A string with file name (also with path).
---------------------------	---

Value

The Data_reader_csv object

Examples

```
input_data_file_name <- system.file("extdata", "CSV-FAS/grezzi_trim_FAS.csv", package = "RJDPProcessor")
input_data_reader    <- Data_reader_csv(input_source = input_data_file_name)
input_data_reader@read_data()
```

Data_reader_csv_istat_format

Constructor (R-like) of the Data_reader object

Description

This function creates a Data_reader object capable of reading data from CSV files in ISTAT format and returning it using the read_data() function. The ISTAT format is a csv file with dates in format YYYYqMM as rownames and time_series names as colnames

Usage

```
Data_reader_csv_istat_format(input_source = NA, ...)
```

Arguments

input_source A string with file name (also with path).

Value

The Data_reader_csv_istat_format object

Examples

```
input_data_file_name <- system.file("extdata", "SITIC-TUR/grezziTUR.csv", package = "RJDPProcessor")
input_data_reader <- Data_reader_csv_istat_format(input_source = input_data_file_name)
#input_data_reader@read_data()
```

Data_reader_ext_reg_csv

Constructor (R-like) of the Data_reader object

Description

This function creates a Data_reader_ext_reg object capable of reading data from CSV external regressors files and returning it using the read_ext_reg_data() function.

Usage

```
Data_reader_ext_reg_csv(input_source, ...)
```

Arguments

`input_source` A string with the input: e.g. a file name (also with path) if the input is a file.

Value

The `Data_reader_ext_reg_csv` object

Examples

```
require(RJDemetra)
input_workspace_xml <- system.file("extdata", "WorkspaceTUR-container/workspace-TUR.xml",
                                   package = "RJProcessor")
input_data_file_name <- system.file("extdata", "CSV-TUR/grezzi_trim_TUR.csv", package = "RJProcessor")
regr_directory <- system.file("extdata", "CSV-TUR/regr", package = "RJProcessor")
ws <- load_workspace(file = input_workspace_xml)
compute(ws)
data_reader_ext_reg <- Data_reader_ext_reg_csv(regr_directory)
all_model_ext_vars_info <- data_reader_ext_reg@read_ext_reg_info(ws)
vars_matrix <- data_reader_ext_reg@read_ext_reg_data(all_model_ext_vars_info, "VATASC",
                                                    frequency=12)
```

`Data_reader_ext_reg_tsplus`

Constructor (R-like) of the Data_reader object

Description

This function creates a `Data_reader_ext_reg` object capable of reading data from TRAMO-SEATS+ external regressors files and returning it using the `read_ext_reg_data()` function.

Usage

```
Data_reader_ext_reg_tsplus(input_source, ...)
```

Arguments

`input_source` A string with the input: e.g. a file name (also with path) if the input is a file.

Value

The `Data_reader_ext_reg_tsplus` object

Examples

```
require(RJDemetra)
input_workspace_xml <- system.file("extdata", "WorkspaceTUR-container/workspace-TUR.xml",
                                   package = "RJProcessor")
input_data_file_name <- system.file("extdata", "SITIC-TUR/grezziTUR.csv", package = "RJProcessor")
regr_directory <- system.file("extdata", "SITIC-TUR/regr", package = "RJProcessor")
ws <- load_workspace(file = input_workspace_xml)
compute(ws)
data_reader_ext_reg <- Data_reader_ext_reg_tsplus(regr_directory)
```

```
all_model_ext_vars_info <- data_reader_ext_reg@read_ext_reg_info(ws)
vars_matrix             <- data_reader_ext_reg@read_ext_reg_data(all_model_ext_vars_info, "VATASC",
                                                                frequency=12)
```

Data_reader_ext_reg_xlsx

Constructor (R-like) of the Data_reader object

Description

This function creates a `Data_reader_ext_reg` object capable of reading data from XLSX external regressors files and returning it using the `read_ext_reg_data()` function.

Usage

```
Data_reader_ext_reg_xlsx(input_source, ...)
```

Arguments

`input_source` A string with the input: e.g. a file name (also with path) if the input is a file.

Value

The `Data_reader_ext_reg_tsplus` object

Examples

```
require(RJDemetra)
input_workspace_xlsx <- system.file("extdata", "WorkspaceTUR-container/workspace-TUR.xml",
                                   package = "RJDProcessor")
input_data_file_name <- system.file("extdata", "SITIC-TUR/grezziTUR.csv", package = "RJDProcessor")
regr_directory       <- system.file("extdata", "SITIC-TUR/regr", package = "RJDProcessor")
ws                   <- load_workspace(file = input_workspace_xlsx)
compute(ws)
data_reader_ext_reg  <- Data_reader_ext_reg_tsplus(regr_directory)
all_model_ext_vars_info <- data_reader_ext_reg@read_ext_reg_info(ws)
vars_matrix          <- data_reader_ext_reg@read_ext_reg_data(all_model_ext_vars_info, "VATASC",
                                                                frequency=12)
```

Data_reader_list

Constructor (R-like) of the Data_reader object

Description

This function creates a `Data_reader` object capable of reading data from a list and returning it using the `read_data()` function.

Usage

```
Data_reader_list(input_source = NA, ...)
```

Arguments

`input_source` A string with file name (also with path).

Value

The `Data_reader_csv` object

Examples

```
FATEXP_10_list <- list("series_name"="FATEXP_10", "dates"=c("2005-01-01", "2005-02-01", "2005-03-01"),
                      "values"=c(12, 15, 11.1))
C_DEFL_list   <- list("series_name"="C_DEFL",   "dates"=c("2001-01-01", "2001-02-01", "2001-03-01"),
                      "values"=c(99, 100, 99.1))
# ...
input_data_list <- list(FATEXP_10_list, C_DEFL_list) #add more time series if you want (here are 2)
input_data_reader <- Data_reader_list(input_source = input_data_list)
input_data_reader@read_data()
```

`Data_reader_workspace` *Constructor (R-like) of the Data_reader object*

Description

This function creates a `Data_reader` object capable of reading data from workspaces and returning them using the `read_data()` function.

Usage

```
Data_reader_workspace(input_source = NA, ...)
```

Arguments

`input_source` A string with workspace xml file name (also with path).

Value

The `Data_reader_workspace` object

Examples

```
input_data_file_name <- system.file("extdata", "WorkspaceTUR-container/workspace-TUR.xml", package = "RJDPProc")
input_data_reader    <- Data_reader_workspace(input_source = input_data_file_name)
mts <- input_data_reader@read_data()
```

Data_reader_xlsx	<i>Constructor (R-like) of the Data_reader object</i>
------------------	---

Description

This function creates a Data_reader object capable of reading data from XLSX files and returning it using the read_data() function.

Usage

```
Data_reader_xlsx(input_source = NA, ...)
```

Arguments

input_source A string with file name (also with path).

Value

The Data_reader_xlsx object

Examples

```
input_data_file_name <- system.file("extdata", "XLSX-TUR/grezzi_trim_TUR.xlsx", package = "RJProcessor")
input_data_reader <- Data_reader_xlsx(input_source = input_data_file_name)
input_data_reader@read_data()
```

Data_reader_xml	<i>Constructor (R-like) of the Data_reader object</i>
-----------------	---

Description

This function creates a Data_reader object capable of reading data from XLSX files and returning it using the read_data() function.

Usage

```
Data_reader_xml(input_source = NA, ...)
```

Arguments

input_source A string with file name (also with path).

Value

The Data_reader_xml object

Examples

```
input_data_file_name <- system.file("extdata", "Prod.xml", package = "RJProcessor")
# NOTE: absolute paths are better for this Data_reader
input_data_reader <- Data_reader_xml(input_source = input_data_file_name)
#input_data_reader@read_data() # for reading the data
```

```
from_full_to_reduced_JD_JSON_file
```

Print a JSON file with only the fields that differ from the basic spec

Description

This function prints a JSON string that contains only the fields of the JD_JSON object that differ from the ones of the basic specification (i.e. "RSA0", "RSA1", ...)

Usage

```
from_full_to_reduced_JD_JSON_file(  
  JD_JSON_file,  
  output_file_name = NA,  
  indent = TRUE,  
  basic_spec = NA  
)
```

Arguments

JD_JSON_file	The name of the file in which the JD_JSON will be saved
output_file_name	-optional- The name of the file (optionally with path) in which the JD_JSON will be saved. If NA, the name of the file will be paste0(JD_DJSON_file,"_reduced")
indent	-optional- Default TRUE. Print each field of the JSON in a different row
basic_spec	-optional- i.e. "RSA0", "RSA1", Default=NA. If NA, use the basic spec specified in the input JSON

Value

Void. A JSON file is saved on the filesystem

Examples

```
require(RJDemetra)
original_directory <- getwd()
extdata_directory <- system.file("extdata", package = "RJDProcessor")
JSON_file_name <- system.file("extdata", "specifications_example3_full.txt",  
                             package = "RJDProcessor")
setwd(extdata_directory)
from_full_to_reduced_JD_JSON_file(JSON_file_name, "specification_new_out2.txt")
setwd(original_directory)
```

```
from_reduced_to_full_JD_JSON_file
```

Print a JSON file with all the JD_JSON fields explicit

Description

This function prints a JSON string that contains all the fields of the JD_JSON object explicitly defined.

Usage

```
from_reduced_to_full_JD_JSON_file(  
  JD_JSON_file,  
  output_file_name = NA,  
  indent = TRUE  
)
```

Arguments

`JD_JSON_file` The name of the file in which the JD_JSON will be saved
`output_file_name` -optional- The name of the file (optionally with path) in which the JD_JSON will be saved. If NA, the name of the file will be paste0(JD_DJSON_file,"_full")
`indent` -optional- Default TRUE. Print each field of the JSON in a different row

Value

Void. A JSON file is saved on the filesystem with all the JD_JSON fields

Examples

```
original_directory <- getwd()  
extdata_directory <- system.file("extdata", package = "RJDPProcessor")  
JSON_file_name <- system.file("extdata", "specifications_example2.txt", package = "RJDPProcessor")  
setwd(extdata_directory)  
from_reduced_to_full_JD_JSON_file(JSON_file_name)  
setwd(original_directory)
```

```
get_r_model_from_j_model
```

Get an R list with model information from java model

Description

This function gets an R list with model information from java model

Usage

```
get_r_model_from_j_model(j_model)
```

Arguments

j_model a Java model obtained from RJDemetra

Value

a list containing all the models specifications

Examples

```
require(RJDemetra)
original_directory <- getwd()
extdata_directory <- system.file("extdata", package = "RJDPprocessor")
setwd(extdata_directory)
input_workspace <- "workspace_test/workspace.xml"
virtual_workspace <- load_workspace(input_workspace)
compute(virtual_workspace)
m <- get_jmodel(virtual_workspace)
r_model_list <- get_r_model_from_j_model(m)
setwd(original_directory)
```

```
get_single_ts_workspaces
```

Get a single workspace for each series in a workspace

Description

This function gets a single time series workspace for each time series SA model present in a given workspace

Usage

```
get_single_ts_workspaces(
  full_workspace,
  single_workspaces_path,
  compressed_ws = TRUE,
  clean_single_ws_directory = TRUE,
  from_TS_PLUS_plugin = TRUE
)
```

Arguments

full_workspace A workspace with multiple time series SA models

single_workspaces_path The path in which the single workspaces will be stored

compressed_ws -optional- Default=TRUE, compress the single workspaces that will be created

clean_single_ws_directory -optional- Default=TRUE, delete the original workspace after creating the single series ones

from_TS_PLUS_plugin -optional- Default=TRUE, the original workspace is created by the SA_ext_plugin. In that case some internal adjustments are needed and they could make the computation slower. There are no problems if this field is TRUE but the ws is created without SA_ext_plugin

Value

A set of materialized workspaces in `single_workspaces_path`, one workspace for each time series
 SA model contained in `full_workspace`

Examples

```
require(RJDemetra)
original_directory <- getwd()
extdata_directory <- system.file("extdata", package = "RJProcessor")
setwd(extdata_directory)
single_workspaces_path <- "splitted_workspaces"
full_workspace <- "WorkspaceTUR-container\\workspace-TUR.xml"
compressed_ws <- FALSE
get_single_ts_workspaces(full_workspace, single_workspaces_path,
  compressed_ws = compressed_ws )
setwd(original_directory)
```

JD_JSON_file_processor

Process a JD_JSON file

Description

This function processes a JSON file with JD_JSON fields and returns a virtual workspace

Usage

```
JD_JSON_file_processor(
  input_data_reader,
  ext_reg_data_reader,
  spec_file_name,
  output_workspace_dir = NA,
  series_to_proc_names = NA,
  java_processing = TRUE
)
```

Arguments

`input_data_reader`
 A specific Data_reader object (CSV, XLSX, ...) to read the input

`ext_reg_data_reader`
 A specific Data_reader_ext_reg object (CSV, XLSX, ...) to read the external
 regssors

`spec_file_name` Name of the file (with path, if desired) containing the JD_JSON to be processed
 (e.g. "specification_new.txt")

`output_workspace_dir`
 -optional- Name of the directory that will contain the output workspace. De-
 fault=NA stores the workspace in a directory called "output_workspace_container"

`series_to_proc_names`
 -optional- vector of names of time series to be processed (e.g. c('VATASA','VATPIA'))
 . Default=NA: all the series are processed

java_processing

-optional- Default=TRUE. Use only Java API (faster) for the internal computation

Value

a virtual workspace, already processed

Examples

```
require(RJDemetra)
original_directory <- getwd()
extdata_directory <- system.file("extdata", package = "RJDPProcessor")
setwd(extdata_directory)
spec_file_name <- "specifications_to_proc.txt"
input_workspace_directory <- "WorkspaceTUR-container/workspace-TUR.xml"
input_data_file_name <- "CSV-TUR/grezzi_trim_TUR.csv"
regr_directory <- "CSV-TUR/regr"
diff <- TRUE # Reduced JSON if diff=TRUE, Full JSON format otherwise

##### Operational flow #####

input_data_reader <- Data_reader_csv(input_source = input_data_file_name)
ext_reg_input_data_reader <- Data_reader_ext_reg_csv(regr_directory)
JD_JSON_from_materialized_workspace(input_workspace_directory,
  ext_reg_input_data_reader, JSON_file_name = spec_file_name,
  diff=TRUE, java_processing=FALSE)
series_to_proc_names <- NA #c("FATEXP_13", "C_DEFL") # NA to process all
virtual_workspace <- JD_JSON_file_processor(input_data_reader = input_data_reader,
  ext_reg_data_reader = ext_reg_input_data_reader,
  spec_file_name = spec_file_name,
  output_workspace_dir = "output_workspace_container",
  series_to_proc_names = series_to_proc_names,
  java_processing = FALSE)
# set java_processor=TRUE to speed-up the operations, but it does not work with
# workspaces readed by sa-ext plugin
m <- get_model(virtual_workspace) #get directly the R model (slower)
from_reduced_to_full_JD_JSON_file(spec_file_name)
compare_sa_ts(new_model_workspace = virtual_workspace,
  old_model_workspace = input_workspace_directory ,
  materialized_ws_new=FALSE, materialized_ws_old=TRUE,
  java_processing_old_model=FALSE)
setwd(original_directory)
```

JD_JSON_from_materialized_workspace

Turn model spec of a materialized workspace in JD_JSON

Description

This function represent model specifications contained into a materialized workspace in JD_JSON

Usage

```
JD_JSON_from_materialized_workspace(
  workspace,
  ext_reg_input_data_reader,
  regr_directory = NA,
  JSON_file_name = "JD_JSON_specification.txt",
  diff = TRUE,
  java_processing = FALSE
)
```

Arguments

<code>workspace</code>	Name of the workspace xml file (also with path).
<code>ext_reg_input_data_reader</code>	A <code>Data_reader_ext_reg</code> object, to read the external regressors in the desired format (csv, xlsx, tramoseats+, ...)
<code>regr_directory</code>	-optional- Name of the directory containing the sources (e.g. files) of the external regressors
<code>JSON_file_name</code>	-optional- Name of the JSON file to be created. If NA the file will be called "JD_JSON_specification.txt"
<code>diff</code>	-optional- if TRUE a reduced version of the JSON specification is produced; In the reduced version, fields with default values equals to the ones of the default specification (i.e. "RSA0", "RSA1", ...) are not reported Default=TRUE
<code>java_processing</code>	-optional- If TRUE, the function works internally with Java API (faster), otherwise it uses R API. Default=FALSE
<code>input_data_reader</code>	A <code>Data_Reader</code> object

Value

A JSON file saved on the filesystem

Examples

```
require(RJDemetra)

input_workspace <- system.file("extdata", "WorkspaceTUR-container/workspace-TUR.xml",
                               package = "RJProcessor")
input_data_file_name <- system.file("extdata", "CSV-TUR/grezzi_trim_TUR.csv",
                                    package = "RJProcessor")
regr_directory <- system.file("extdata", "CSV-TUR/regr", package = "RJProcessor")
diff <- TRUE # Reduced JSON if diff=TRUE, Full JSON format otherwise

input_data_reader <- Data_reader_csv(input_source = input_data_file_name)
ext_reg_input_data_reader <- Data_reader_ext_reg_csv(regr_directory)
JD_JSON_from_materialized_workspace(input_workspace, ext_reg_input_data_reader, JSON_file_name = "specificat
```

JD_JSON_from_virtual_workspace

Turn model spec of a virtual (R) workspace in JD_JSON

Description

This function represent model specifications contained into an R workspace in JD_JSON

Usage

```
JD_JSON_from_virtual_workspace(
  ws,
  ext_reg_input_data_reader,
  JSON_file_name = "JD_JSON_specification.txt",
  diff = TRUE,
  java_processing = TRUE
)
```

Arguments

ws	workspace R object.
ext_reg_input_data_reader	A Data_reader_ext_reg object, to read the external regressors in the desired format (csv, xlsx, tramoseats+, ...)
JSON_file_name	-optional- Name of the JSON file to be created. If NA the file will be called "JD_JSON_specification.txt"
diff	-optional- if TRUE a reduced version of the JSON specification is produced; In the reduced version, fields with default values equals to the ones of the default specification (i.e. "RSA0", "RSA1", ...) are not reported Default=TRUE
java_processing	-optional- If TRUE, the function works internally with Java API (faster), otherwise it uses R API. Default=TRUE
input_data_reader	A Data_Reader object
regr_directory	-optional- Name of the directory containing the sources (e.g. files) of the external regressors

Value

A JSON file saved on the filesystem

Examples

```
require(RJDemetra)

input_workspace_directory <- system.file("extdata", "WorkspaceTUR-container/workspace-TUR.xml",
                                         package = "RJProcessor")
input_data_file_name      <- system.file("extdata", "CSV-TUR/grezzi_trim_TUR.csv",
                                         package = "RJProcessor")
regr_directory            <- system.file("extdata", "CSV-TUR/regr", package = "RJProcessor")
```

```

diff <- TRUE # Reduced JSON if diff=TRUE, Full JSON format otherwise

input_data_reader      <- Data_reader_csv(input_source = input_data_file_name)
ext_reg_input_data_reader <- Data_reader_ext_reg_csv(regr_directory)

original_directory <- getwd()
extdata_directory <- system.file("extdata", package = "RJDProcessor")
setwd(extdata_directory)

ws <- load_workspace(file = input_workspace_directory)
JD_JSON_from_virtual_workspace(ws, ext_reg_input_data_reader, JSON_file_name = "specifications_new_out.txt",
setwd(original_directory)

```

JD_JSON_to_materialized_workspace

Turn a JD_JSON in a materialized workspace

Description

This function obtain a JD_JSON file from a workspace stored in the filesystem (in a directory). See test folder for examples

Usage

```

JD_JSON_to_materialized_workspace(
  workspace_dir = NA,
  JSON_file,
  input_data_reader,
  ext_reg_data_reader = NA,
  series_to_proc_names = NA
)

```

Arguments

workspace_dir -optional- the directory of the input workspace. Default = NA stores the workspace in a directory called "output_workspace_container"

JSON_file Name of the JSON file that will be produced (also with path).

input_data_reader
A Data_Reader object

ext_reg_data_reader
-optional- A Data_reader_ext_reg object, to produce the metadata of the external regressors (i.e. create the names of the csv rather than a xlsx files o other containers for external regressors) Default = NA, do not consider external regressors (discouraged)

series_to_proc_names
-optional- an array containing the name of the series to be included in the workspace among the ones present in the JD_JSON file e.g. c("VATASA", "VATAIA")

Value

void in R environment, a workspace materialized in the filesystem

Examples

```
require(RJDemetra)
input_JD_JSON      <- system.file("extdata", "specifications_example1.txt", package = "RJDPProcessor")
input_data_file_name <- system.file("extdata", "CSV-TUR/grezzi_trim_TUR.csv", package = "RJDPProcessor")
regr_directory      <- system.file("extdata", "CSV-TUR/regr", package = "RJDPProcessor")
input_data_reader    <- Data_reader_csv(input_source = input_data_file_name)
ext_reg_input_data_reader <- Data_reader_ext_reg_csv(regr_directory)
JD_JSON_to_materialized_workspace(workspace_dir="ws_out" ,input_JD_JSON, input_data_reader, ext_reg_input_data_reader)
```

JD_JSON_to_virtual_workspace

Turn a JD_JSON in a virtual workspace

Description

This function obtain a virtual workspace from a JD_JSON file. See test folder for examples

Usage

```
JD_JSON_to_virtual_workspace(
  JSON_file,
  input_data_reader,
  ext_reg_data_reader = NA,
  series_to_proc_names = NA
)
```

Arguments

JSON_file Name of the JSON file to turn in a workspace (also with path).

input_data_reader A `Data_Reader` object

ext_reg_data_reader -optional- A `Data_reader_ext_reg` object, to read the external regressors in the desired format (csv, xlsx, tramoseats+, ...) Default = NA, do not consider external regressors (discouraged)

series_to_proc_names -optional- an array containing the name of the series to be included in the workspace among the ones present in the JD_JSON file e.g. c("VATASA","VATAIA")

Value

A virtual workspace

Examples

```
require(RJDemetra)
input_JD_JSON      <- system.file("extdata", "specifications_example1.txt", package = "RJDPProcessor")
input_data_file_name <- system.file("extdata", "CSV-TUR/grezzi_trim_TUR.csv", package = "RJDPProcessor")
regr_directory      <- system.file("extdata", "CSV-TUR/regr", package = "RJDPProcessor")
input_data_reader    <- Data_reader_csv(input_source = input_data_file_name)
```

```
ext_reg_input_data_reader <- Data_reader_ext_reg_csv(regr_directory)
ws <- JD_JSON_to_virtual_workspace(input_JD_JSON, input_data_reader, ext_reg_input_data_reader, series_to_pr
```

merge_workspaces	<i>Merge many workspaces in one</i>
------------------	-------------------------------------

Description

This function gets merges many workspaces contained in a given folder into one workspace

Usage

```
merge_workspaces(
  source_workspaces_path,
  merged_ws_name = "merged_ws",
  merged_ws_dir = NA,
  compressed = TRUE,
  delete_originals = TRUE,
  silent = TRUE
)
```

Arguments

source_workspaces_path	The path in which to find all the workspcaes that will be merged
merged_ws_name	-optional- Default="merged_ws". The name of the workspace that will be created
merged_ws_dir	-optional- Default=NA, the path in which the merged workspace will be stored. If NA it will be stored in the current directory
compressed	-optional- Default=TRUE, workspaces to be merged are compressed
delete_originals	-optional- Default=TRUE, delete original workspaces after merging them
silent	-optional- Default=TRUE, do not print status bar and messages during the operations

Value

A virtual (R) and a marerialized workspace containing all the multiprocessings and time series SA models of the original workspaces

Examples

```
require(RJDemetra)
original_directory <- getwd()
extdata_directory <- system.file("extdata", package = "RJProcessor")
setwd(extdata_directory)
single_workspaces_path <- "splitted_workspaces_to_merge"
full_workspace_path <- "merged_ws_test"
compressed_ws <- FALSE
ws_merged <- merge_workspaces(source_workspaces_path=single_workspaces_path,
```

```
merged_ws_dir = full_workspace_path, compressed = TRUE,
delete_originals = FALSE, silent=TRUE)

setwd(original_directory)
```

```
produce_fully_R_workspace
```

Process a JD_JSON file

Description

This function processes a JSON file with JD_JSON fields and returns a virtual workspace

Usage

```
produce_fully_R_workspace(
  ext_reg_input_data_reader = NA,
  original_ws_xml,
  new_r_ws_folder
)
```

Arguments

```
ext_reg_input_data_reader
  A specific Data_reader_ext_reg object (CSV, XLSX, ...) to read the external
  regressors. Default=NA.

original_ws_xml
  xml file (also with path) of the workspace to be transformed into a fully R
  workspace

new_r_ws_folder
  Name of the directory that will contain the output, fully R, workspace.
```

Value

a virtual workspace, already processed

Examples

```
require(RJDemetra)
original_directory <- getwd()
extdata_directory <- system.file("extdata", package = "RJProcessor")
setwd(extdata_directory)
original_ws_xml <- "WorkspaceTUR-container/workspace-TUR.xml"
new_r_ws_folder <- "output_fully_R_ws"
regr_directory <- "SITIC-TUR/regr"
ext_reg_input_data_reader <- Data_reader_ext_reg_tsplus(regr_directory)
produce_fully_R_workspace(ext_reg_input_data_reader, original_ws_xml, new_r_ws_folder)

extdata_directory <- system.file("extdata", package = "RJProcessor")
setwd(extdata_directory)
original_ws_xml <- "WorkspaceFAS-standard-container//FAS.xml"
new_r_ws_folder <- "output_fully_R_ws"
```



```

regr_directory <- "CSV-FAS//regr"
ext_reg_input_data_reader <- Data_reader_ext_reg_csv(regr_directory)
produce_fully_R_workspace(ext_reg_input_data_reader, original_ws_xml, new_r_ws_folder)
setwd(original_directory)

```

read_data,Data_reader_csv-method

Get the data from a Data_reader_csv

Description

This function returns the data from the input_source of the object.

Usage

```

## S4 method for signature 'Data_reader_csv'
read_data(object, ...)

```

Value

data in form of numeric matrix, with rownames = dates (in string format, YYYY-MM-DD) and colnames = time series names (string)

Examples

```

input_data_file_name <- system.file("extdata", "CSV-FAS/grezzi_trim_FAS.csv", package = "RJDPProcessor")
input_data_reader <- Data_reader_csv(input_source = input_data_file_name)
input_data_reader@read_data()

```

read_data,Data_reader_csv_istat_format-method

Get the data from a Data_reader_csv_istat_format

Description

This function returns the data from the input_source of the object.

Usage

```

## S4 method for signature 'Data_reader_csv_istat_format'
read_data(object, ...)

```

Value

data in form of numeric matrix, with rownames = dates (in string format, YYYYqMM) and colnames = time series names (string)

Examples

```

input_data_file_name <- system.file("extdata", "SITIC-TUR/grezziTUR.csv", package = "RJDPProcessor")
input_data_reader <- Data_reader_csv_istat_format(input_source = input_data_file_name)
input_data_reader@read_data()

```

read_data,Data_reader_list-method

Get the data from a Data_reader_list

Description

This function returns the data from the input_source of the object.

Usage

```
## S4 method for signature 'Data_reader_list'
read_data(object, ...)
```

Value

data in form of numeric matrix, with rownames = dates (in string format, YYYY-MM-DD) and colnames = time series names (string)

Examples

```
FATEXP_10_list <- list("series_name"="FATEXP_10", "dates"=c("2005-01-01","2005-02-01","2005-03-01"),
                      "values"=c(12, 15, 11.1))
C_DEFL_list    <- list("series_name"="C_DEFL", "dates"=c("2001-01-01","2001-02-01","2001-03-01"),
                      "values"=c(99, 100, 99.1))
#...
input_data_list <- list(FATEXP_10_list, C_DEFL_list) #add more time series if you want (here are 2)
input_data_reader <- Data_reader_list(input_source = input_data_list)
input_data_reader@read_data()
```

read_data,Data_reader_workspace-method

Get the data from a Data_reader_workspace

Description

This function returns the data from the input_source of the object.

Usage

```
## S4 method for signature 'Data_reader_workspace'
read_data(object, ...)
```

Value

data in form of numeric matrix, with rownames = dates (in string format, YYYY-MM-DD) and colnames = time series names (string)

Examples

```
input_data_file_name <- system.file("extdata","WorkspaceTUR-container/workspace-TUR.xml", package = "RJDProc")
input_data_reader    <- Data_reader_workspace(input_source = input_data_file_name)
mts <- input_data_reader@read_data()
```

`read_data,Data_reader_xlsx-method`*Get the data from a Data_reader_csv*

Description

This function returns the data from the `input_source` of the object.

Usage

```
## S4 method for signature 'Data_reader_xlsx'  
read_data(object, ...)
```

Value

data in form of numeric matrix, with `rownames` = dates (in string format, YYYY-MM-DD) and `colnames` = time series names (string)

Examples

```
input_data_file_name <- system.file("extdata", "XLSX-TUR/grezzi_trim_TUR.xlsx", package = "RJDPProcessor")  
input_data_reader    <- Data_reader_xlsx(input_source = input_data_file_name)  
input_data_reader@read_data()
```

`read_data,Data_reader_xml-method`*Get the data from a Data_reader_xml*

Description

This function returns the data from the `input_source` of the object.

Usage

```
## S4 method for signature 'Data_reader_xml'  
read_data(object, ...)
```

Value

data in form of numeric matrix, with `rownames` = dates (in string format, YYYY-MM-DD) and `colnames` = time series names (string)

Examples

```
input_data_file_name <- system.file("extdata", "Prod.xml", package = "RJDPProcessor")  
# NOTE: absolute paths are better for this Data_reader  
input_data_reader    <- Data_reader_xml(input_source = input_data_file_name)  
#input_data_reader@read_data() # for reading the data
```


read_ext_reg_data, Data_reader_ext_reg_tsplus-method
Read external regressors data

Description

This function reads data from external regressors and returns it as a numeric matrix with variable names as colnames and YYYY-MM-DD dates as rownames

Usage

```
## S4 method for signature 'Data_reader_ext_reg_tsplus'
read_ext_reg_data(
  object,
  var_info = NULL,
  time_series_info = NULL,
  frequency = NA_integer_,
  ...
)
```

Arguments

var_info	A string with file name (also with path).
time_series_info	A string with time series name in workspace name (also with path).
frequency	i.e. 12 = monthly data, 4 = quarterly data

Value

a numeric matrix with variable names as colnames and YYYY-MM-DD dates as rownames

Examples

[illegible]

read_ext_reg_info,Data_reader_ext_reg_csv-method

Read information about external regressors from a workspace

Description

This function returns a list of information about external regressors used in the models contained in a workspaces

Usage

```
## S4 method for signature 'Data_reader_ext_reg_csv'
read_ext_reg_info(object, var_info_container, adjust_path = TRUE, ...)
```

Arguments

var_info_container
workspace xml file path

Value

list() of information about external regressors

Examples

```
require(RJDemetra)
input_workspace_xml <- system.file("extdata", "WorkspaceTUR-container/workspace-TUR.xml",
                                   package = "RJDProcessor")
input_data_file_name <- system.file("extdata", "CSV-TUR/grezzi_trim_TUR.csv", package = "RJDProcessor")
regr_directory <- system.file("extdata", "CSV-TUR/regr", package = "RJDProcessor")
ws <- load_workspace(file = input_workspace_xml)
compute(ws)
data_reader_ext_reg <- Data_reader_ext_reg_csv(regr_directory)
all_model_ext_vars_info <- data_reader_ext_reg@read_ext_reg_info(ws)
```

read_ext_reg_info,Data_reader_ext_reg_tsplus-method

Read information about external regressors from a workspace

Description

This function returns a list of information about external regressors used in the models contained in a workspaces

Usage

```
## S4 method for signature 'Data_reader_ext_reg_tsplus'
read_ext_reg_info(object, var_info_container, adjust_path = TRUE, ...)
```

Arguments

var_info_container
workspace xml file path

Value

list() of information about external regressors

Examples

```
require(RJDemetra)
input_workspace_xml <- system.file("extdata", "WorkspaceTUR-container/workspace-TUR.xml",
                                   package = "RJDPProcessor")
input_data_file_name <- system.file("extdata", "SITIC-TUR/grezziTUR.csv", package = "RJDPProcessor")
regr_directory <- system.file("extdata", "SITIC-TUR/regr", package = "RJDPProcessor")
ws <- load_workspace(file = input_workspace_xml)
compute(ws)
data_reader_ext_reg <- Data_reader_ext_reg_tsplus(regr_directory)
all_model_ext_vars_info <- data_reader_ext_reg@read_ext_reg_info(ws)
```

read_ext_reg_info, Data_reader_ext_reg_xlsx-method

Read information about external regressors from a workspace

Description

This function returns a list of information about external regressors used in the models contained in a workspaces

Usage

```
## S4 method for signature 'Data_reader_ext_reg_xlsx'
read_ext_reg_info(object, var_info_container, adjust_path = TRUE, ...)
```

Arguments

var_info_container
workspace xml file path

Value

list() of information about external regressors

Examples

```
require(RJDemetra)
input_workspace_xlsx <- system.file("extdata", "WorkspaceTUR-container/workspace-TUR.xml",
                                   package = "RJDPProcessor")
input_data_file_name <- system.file("extdata", "XLSX-TUR/grezzi_trim_TUR.xlsx", package = "RJDPProcessor")
regr_directory <- system.file("extdata", "XLSX-TUR/regr", package = "RJDPProcessor")
ws <- load_workspace(file = input_workspace_xlsx)
compute(ws)
```



```
data_reader_ext_reg      <- Data_reader_ext_reg_xlsx(regr_directory)
all_model_ext_vars_info <- data_reader_ext_reg@read_ext_reg_info(ws)
```

update_data	<i>Update the data of a workspace</i>
-------------	---------------------------------------

Description

This function update the data of a workspace's time series basing on the data read by a Data_reader object already initialized. The time series read by the Data_reader must have the same colnames as the time series names of the workspace to produce an update

Usage

```
update_data(workspace_xml_path, data_reader)
```

Arguments

workspace_xml_path	Path of the xml file of the workspace whose data have to be updated
data_reader	A Data_reader object already initialized with its input source

Examples

```
require(RJDemetra)
original_directory <- getwd()
extdata_directory <- system.file("extdata", package = "RJDPProcessor")
setwd(extdata_directory)
ws_xml_path <- "TUR_ws_test_container/merged_ws.xml"
dr <- RJDPProcessor::Data_reader_csv(input_source = "rawdata_TUR.csv")
# num_mat<-dr@read_data() # to check if the data are available
update_data(ws_xml_path, dr)
setwd(original_directory)
```

Index

check_data, [3](#)
check_external_regressors, [3](#)
compare_sa_ts, [4](#)
compare_workspaces, [5](#)
convert_numeric_matrix_to_mts, [6](#)
create_diagnostic_report1, [7](#)
create_diagnostic_report2, [8](#)

Data_reader_csv, [8](#)
Data_reader_csv_istat_format, [9](#)
Data_reader_ext_reg_csv, [9](#)
Data_reader_ext_reg_tsplus, [10](#)
Data_reader_ext_reg_xlsx, [11](#)
Data_reader_list, [11](#)
Data_reader_workspace, [12](#)
Data_reader_xlsx, [13](#)
Data_reader_xml, [13](#)

from_full_to_reduced_JD_JSON_file, [14](#)
from_reduced_to_full_JD_JSON_file, [15](#)

get_r_model_from_j_model, [15](#)
get_single_ts_workspaces, [16](#)

JD_JSON_file_processor, [17](#)
JD_JSON_from_materialized_workspace, [18](#)
JD_JSON_from_virtual_workspace, [20](#)
JD_JSON_to_materialized_workspace, [21](#)
JD_JSON_to_virtual_workspace, [22](#)

merge_workspaces, [23](#)

produce_fully_R_workspace, [24](#)

read_data, Data_reader_csv-method, [25](#)
read_data, Data_reader_csv_istat_format-method, [25](#)
read_data, Data_reader_list-method, [26](#)
read_data, Data_reader_workspace-method, [26](#)
read_data, Data_reader_xlsx-method, [27](#)
read_data, Data_reader_xml-method, [27](#)
read_ext_reg_data, Data_reader_ext_reg_csv-method, [28](#)
read_ext_reg_data, Data_reader_ext_reg_tsplus-method, [29](#)
read_ext_reg_data, Data_reader_ext_reg_xlsx-method, [30](#)
read_ext_reg_info, Data_reader_ext_reg_csv-method, [31](#)
read_ext_reg_info, Data_reader_ext_reg_tsplus-method, [31](#)
read_ext_reg_info, Data_reader_ext_reg_xlsx-method, [32](#)

update_data, [33](#)