Lista 6

Alessandro Silva - RA:236928

```
library(DBI)
library(RSQLite)
con <- dbConnect(RSQLite::SQLite(), "me315.sqlite")
```

Questão 1

```
select state, min(acres) as menor_area
from preserve
group by state
```

Table 1: 3 records

STATE	menor_area
AZ	380
MA	4
MT	121

Questão 2

```
select state, max(acres) maior_area
from preserve
where acres <= 10000
group by state
```

Table 2: 3 records

STATE	maior_area
AZ	1200
MA	830
MT	1130

Questão 3

```
select state, max(acres) maior_area
from preserve
where acres <= 10000
group by state
order by maior_area desc
```

Table 3: 3 records

STATE	maior_area
AZ	1200
MT	1130
MA	830

Questão 4

```
select state, max(acres) as maior_area
from preserve
group by state
having maior_area < 25000
```

Table 4: 2 records

STATE	maior_area
MA	830
MT	15000

Questão 5

```
select state, min(acres) as menor_area
from preserve
group by state
having menor_area < 100
```

Table 5: 1 records

STATE	menor_area
MA	4

Questão 6

```
select state, pname, max(acres) as maior_area
from preserve
where acres > 1000
group by state
having maior_area < 25000
```

Table 6: 1 records

STATE	PNAME	maior_area
MT	PINE BUTTE SWAMP	15000

Questão 7

```
select state, sum(acres) as tamanho_total
from preserve
group by state
having tamanho_total between 10000 and 50000
```

Table 7: 1 records

STATE	tamanho_total
MT	16931

Questão 8

```
select state, avg(acres) as qtd_media
from preserve
group by state
order by qtd_media desc
limit 1
```

Table 8: 1 records

STATE	qtd_media
AZ	12840

Questão 9

```
select dno, avg(salary) as salario_medio
from employee
group by dno
```

Table 9: 3 records

DNO	salario_medio
10	1200.000
20	4666.667
40	500.000

Questão 10

```
select dno, sum(salary) as total_salario, max(salary) as salario_maximo, min(salary) as sala
from employee
group by dno
```

Table 10: 3 records

DNO	total_salario	salario_maximo	salario_minimo
10	2400	2000	400
20	14000	9000	2000
40	500	500	500

Questão 11

```
select dno, count(*) as qtd_func
from employee
where not dno=40
group by dno
```

Table 11: 2 records

DNO	qtd_func
10	2
20	3

Questão 12

```
select dno, count(*) as qtd_func
from employee
group by dno
having qtd_func >2
```

Table 12: 1 records

DNO	qtd_func
20	3

Questão 13

```
select state, sum(acres)
from preserve
group by state

union all
select 'Total' as state, sum(acres) as 'sum(acres)'
from preserve
```

Table 13: 4 records

STATE	sum(acres)
AZ	51360
MA	1760
MT	16931
Total	70051

```
Sys.setenv(TZ = "America/Sao_Paulo")
Sys.time()
```

```
[1] "2026-09-29 00:46:06 -03"
```