

lista04

```
library(DBI)
library(RSQLite)

#conexão com SQL
con <- dbConnect(SQLite(), "me315.sqlite")
```

Questão 1

```
SELECT *
FROM PRESERVE
WHERE PNO IN (2,4,6,8,10);
```

Table 1: 3 records

PNO	PNAME	STATE	ACRES	FEE
2	PINE BUTTE SWAMP	MT	15000	0
6	PAPAGONIA-SONOITA CREEK	AZ	1200	3
10	HOFT FARM	MA	90	0

Questão 2

```
select*
from preserve
where pname not in ('DANCING PRAIRIE', 'MULESHOE RANCH', 'MCELWAIN-OLSEN', 'TATKON');
```

Table 2: Displaying records 1 - 10

PNO	PNAME	STATE	ACRES	FEE
5	HASSAYAMPA RIVER	AZ	660	3
40	SOUTH FORK MADISON	MT	121	0
9	DAVID H. SMITH	MA	830	0
11	MIACOMET MOORS	MA	4	0
12	MOUNT PLANTAIN	MA	730	0
1	COMERTOWN PRAIRIE	MT	1130	0
2	PINE BUTTE SWAMP	MT	15000	0
80	RAMSEY CANYON	AZ	380	3
10	HOFT FARM	MA	90	0
6	PAPAGONIA-SONOITA CREEK	AZ	1200	3

Questão 3

```
select*
from preserve
where pno between 3 and 10
```

Table 3: 6 records

PNO	PNAME	STATE	ACRES	FEE
3	DANCING PRAIRIE	MT	680	0
5	HASSAYAMPA RIVER	AZ	660	3
6	PAPAGONIA-SONOITA CREEK	AZ	1200	3
7	MULESHOE RANCH	AZ	49120	0
9	DAVID H. SMITH	MA	830	0
10	HOFT FARM	MA	90	0

Questão 4

```
select*
from preserve
where pno not between 3 and 10
```

Table 4: 8 records

PNO	PNAME	STATE	ACRES	FEE
40	SOUTH FORK MADISON	MT	121	0
14	MCELWAIN-OLSEN	MA	66	0
13	TATKON	MA	40	0
11	MIACOMET MOORS	MA	4	0
12	MOUNT PLANTAIN	MA	730	0
1	COMERTOWN PRAIRIE	MT	1130	0
2	PINE BUTTE SWAMP	MT	15000	0
80	RAMSEY CANYON	AZ	380	3

Questão 5

```
SELECT STATE, PNO, ACRES
FROM PRESERVE
WHERE STATE NOT IN ('MT', 'AZ')
      AND (ACRES < 50 OR ACRES > 800)
ORDER BY PNO DESC;
```

Table 5: 3 records

STATE	PNO	ACRES
MA	13	40
MA	11	4
MA	9	830

Questão 6

```
select pname
from preserve
where pname like 'D%'
```

Table 6: 2 records

PNAME
DANCING PRAIRIE
DAVID H. SMITH

Questão 7

```
select pname
from preserve
where pname like '%TOWN';
```

Table 7: 0 records

PNAME

Questão 8

```
select pname
from preserve
where pname like '%PRAIRIE'
```

Table 8: 2 records

PNAME
DANCING PRAIRIE
COMERTOWN PRAIRIE

Questão 9

```
select pname
from preserve
where pname like "%ING%"
```

Table 9: 1 records

PNAME
DANCING PRAIRIE

Questão 10

```
select pname
from preserve
where pname like '%E'
```

Table 10: 2 records

PNAME
DANCING PRAIRIE
COMERTOWN PRAIRIE

Questão 11

```
select pname
from preserve
where pname like "%ME%"
```

Table 11: 2 records

PNAME
MIACOMET MOORS
COMERTOWN PRAIRIE

Questão 12

```
SELECT PNAME
FROM PRESERVE
WHERE PNAME LIKE '%M%E%'
```

Table 12: 6 records

PNAME
HASSAYAMPA RIVER
MULESHOE RANCH
MCELWAIN-OLSEN
MIACOMET MOORS
COMERTOWN PRAIRIE
RAMSEY CANYON

Questão 13

```
select pname
from preserve
where pname like '_A%'
```

Table 13: 6 records

PNAME
HASSAYAMPA RIVER
DANCING PRAIRIE
TATKON
DAVID H. SMITH
RAMSEY CANYON
PAPAGONIA-SONOITA CREEK

Questão 14

```
SELECT PNAME
FROM PRESERVE
WHERE PNAME LIKE '% %'
```

Table 14: Displaying records 1 - 10

PNAME
HASSAYAMPA RIVER
DANCING PRAIRIE
MULESHOE RANCH
SOUTH FORK MADISON
DAVID H. SMITH
MIACOMET MOORS
MOUNT PLANTAIN
COMERTOWN PRAIRIE
PINE BUTTE SWAMP
RAMSEY CANYON

Questão 15

```
select pname
from preserve
where pname like '%FARM%' or '%SWAMP%' or '%PRAIRE%'
```

Table 15: 1 records

PNAME
HOFT FARM

Questão 16

```
select pname
from preserve
where pname like '%.%' or '%-%'
```

Table 16: 1 records

PNAME
DAVID H. SMITH

Questão 17

```
SELECT PNAME
FROM PRESERVE
WHERE PNAME LIKE '____R%PRAIRIE';
```

Table 17: 1 records

PNAME
COMERTOWN PRAIRIE

Questão 18

```
select *
from employee
where DNO between 10 and 40
```

Table 18: 6 records

ENO	ENAME	SALARY	DNO
1000	MOE	2000	20
2000	LARRY	2000	10
3000	CURLY	3000	20
4000	SHEMP	500	40
5000	JOE	400	10
6000	GEORGE	9000	20

Questão 19

```
select *  
from employee  
where DNO not between 10 and 40
```

Table 19: 0 records

ENO	ENAME	SALARY	DNO
-----	-------	--------	-----

Questão 20

```
select *  
from employee  
where salary between 500 and 2000
```

Table 20: 3 records

ENO	ENAME	SALARY	DNO
1000	MOE	2000	20
2000	LARRY	2000	10
4000	SHEMP	500	40

Questão 21

```
select *  
from employee  
where salary not between 500 and 2000
```

Table 21: 3 records

ENO	ENAME	SALARY	DNO
3000	CURLY	3000	20
5000	JOE	400	10
6000	GEORGE	9000	20

```
Sys.setenv(TZ = "America/Sao_Paulo")
Sys.time()
```

```
[1] "2026-09-03 08:44:31 -03"
```