

Formal verification of the 5G EAP-TLS authentication protocol using Proverif

2023

Alessandro Zanatta

University of Pisa

Reference paper (DOI): [10.1109/ACCESS.2020.2969474](https://doi.org/10.1109/ACCESS.2020.2969474)

Proverif

- Symbolic verification tool:

Proverif

- Symbolic verification tool:
 - Attacker \rightarrow Dolev-Yao;

Proverif

- Symbolic verification tool:
 - Attacker \rightarrow Dolev-Yao;
 - Messages \rightarrow terms;

Proverif

- Symbolic verification tool:
 - Attacker \rightarrow Dolev-Yao;
 - Messages \rightarrow terms;
 - Cryptographic primitives \rightarrow black-box;

Proverif

- Symbolic verification tool:
 - Attacker \rightarrow Dolev-Yao;
 - Messages \rightarrow terms;
 - Cryptographic primitives \rightarrow black-box;
 - **Perfect cryptography** assumption.

Proverif

- Symbolic verification tool:
 - Attacker \rightarrow Dolev-Yao;
 - Messages \rightarrow terms;
 - Cryptographic primitives \rightarrow black-box;
 - **Perfect cryptography** assumption. Suppose we have:
 - Two primitives: enc, dec;
 - Two terms: m, k ;
 - The following equality:

$$\text{dec}(\text{enc}(m, k), k) = m \quad (1)$$

Proverif

- Symbolic verification tool:
 - Attacker \rightarrow Dolev-Yao;
 - Messages \rightarrow terms;
 - Cryptographic primitives \rightarrow black-box;
 - **Perfect cryptography** assumption. Suppose we have:
 - Two primitives: enc, dec;
 - Two terms: m, k ;
 - The following equality:

$$\text{dec}(\text{enc}(m, k), k) = m \quad (1)$$

- can decrypt $\text{enc}(m, k) \iff k$ is known

Proverif

- Symbolic verification tool:
 - Attacker \rightarrow Dolev-Yao;
 - Messages \rightarrow terms;
 - Cryptographic primitives \rightarrow black-box;
 - **Perfect cryptography** assumption. Suppose we have:
 - Two primitives: enc, dec;
 - Two terms: m, k ;
 - The following equality:

$$\text{dec}(\text{enc}(m, k), k) = m \quad (1)$$

- can decrypt $\text{enc}(m, k) \iff k$ is known
- Based on **applied π -calculus**;

Applied π -calculus

Grammar of processes (P, Q):

Applied π -calculus

Grammar of processes (P, Q):

0 (* null process *)

Applied π -calculus

Grammar of processes (P, Q):

0	<i>(* null process *)</i>
<code>out(N, M); P</code>	<i>(* output to channel N the message M *)</i>
<code>in(N, M: T); P</code>	<i>(* input from channel N of message M *)</i>

Applied π -calculus

Grammar of processes (P, Q):

<code>0</code>	<i>(* null process *)</i>
<code>out(N, M); P</code>	<i>(* output to channel N the message M *)</i>
<code>in(N, M: T); P</code>	<i>(* input from channel N of message M *)</i>
<code>P Q</code>	<i>(* parallel composition *)</i>
<code>!P</code>	<i>(* infinite replication *)</i>

Applied π -calculus

Grammar of processes (P, Q):

<code>0</code>	<i>(* null process *)</i>
<code>out(N, M); P</code>	<i>(* output to channel N the message M *)</i>
<code>in(N, M: T); P</code>	<i>(* input from channel N of message M *)</i>
<code>P Q</code>	<i>(* parallel composition *)</i>
<code>!P</code>	<i>(* infinite replication *)</i>
<code>new a: T; P</code>	<i>(* fresh value of sort T *)</i>
<code>if M then P else Q</code>	<i>(* conditional *)</i>

Applied π -calculus

Grammar of processes (P, Q):

```

0                                (* null process *)
out(N, M); P                    (* output to channel N the message M *)
in(N, M: T); P                  (* input from channel N of message M *)
P | Q                          (* parallel composition *)
!P                              (* infinite replication *)
new a: T; P                     (* fresh value of sort T *)
if M then P else Q              (* conditional *)

```

Additionally:

```

event EventName(x);             (* add event to trace *)
query event(EventName(x)).      (* define a query on events *)

```

Applied π -calculus

Grammar of processes (P, Q):

```

0                                (* null process *)
out(N, M); P                    (* output to channel N the message M *)
in(N, M: T); P                  (* input from channel N of message M *)
P | Q                          (* parallel composition *)
!P                              (* infinite replication *)
new a: T; P                     (* fresh value of sort T *)
if M then P else Q             (* conditional *)

```

Additionally:

```

event EventName(x);            (* add event to trace *)
query event(EventName(x)).     (* define a query on events *)
let macroName = P.             (* create a process macro *)
let x = M in P else Q.         (* assignment and pattern matching *)

```


0	<i>(* null process *)</i>
out(N, M); P	<i>(* output to channel N the message M *)</i>
in(N, M: T); P	<i>(* input from channel N of message M *)</i>
P Q	<i>(* parallel composition *)</i>
!P	<i>(* infinite replication *)</i>
new a: T; P	<i>(* fresh value of sort T *)</i>
if M then P else Q	<i>(* conditional *)</i>

```
event EventName(x);      (* add event to trace *)
query event(EventName(x)). (* define a query on events *)
let macroName = P.       (* create a process macro *)
let x = M in P else Q.   (* assignment and pattern matching *)
phase t;                 (* execute a process in phase t *)
```

5G EAP-TLS protocol entities

Involved entities:

- User Equipment (UE):
 - Subscription Permanent Identifier (**SUPI**)
 - Public asymmetric key pk_{HN}

5G EAP-TLS protocol entities

Involved entities:

- User Equipment (UE):
 - Subscription Permanent Identifier (**SUPI**)
 - Public asymmetric key pk_{HN}
- Home Network (HN):
 - Authentication Server Function (**AUSF**)
 - Unified Data Management (**UDM**)

5G EAP-TLS protocol entities

Involved entities:

- User Equipment (UE):
 - Subscription Permanent Identifier (**SUPI**)
 - Public asymmetric key pk_{HN}
- Home Network (HN):
 - Authentication Server Function (**AUSF**)
 - Unified Data Management (**UDM**)
- Serving Network (SN):
 - Security Anchor Function (**SEAF**)

5G EAP-TLS protocol entities


Involved entities:

- User Equipment (UE):
 - Subscription Permanent Identifier (**SUPI**)
 - Public asymmetric key pk_{HN}
- Home Network (HN):
 - Authentication Server Function (**AUSF**)
 - Unified Data Management (**UDM**)
- Serving Network (SN):
 - Security Anchor Function (**SEAF**)


Assumptions:

- $HN \leftrightarrow SN$ communications are secure

5G EAP-TLS protocol execution I



5G EAP-TLS protocol execution II



Required security properties

Required security properties

- **Authentication properties:**

- A1. Both the home network and the subscriber should agree on the identity of each other after successful termination
- A2. Both the home network and the subscriber should agree on the pre-master key R_{prekey} after successful termination

Required security properties

- **Authentication properties:**

- A1. Both the home network and the subscriber should agree on the identity of each other after successful termination
- A2. Both the home network and the subscriber should agree on the pre-master key R_{prekey} after successful termination

- **Secrecy properties:**

- S1. The attacker cannot obtain the identity $SUPI$ of an honest subscriber
- S2. The attacker cannot obtain the pre-master key R_{prekey} of an honest subscriber
- S3. The attacker cannot obtain the session key $K_{session}$ of an honest subscriber

It's ***DEMO*** time!!

Broken properties


- **Authentication properties:**

- A1. Both the home network and the subscriber should agree on the identity of each other after successful termination
- A2. Both the home network and the subscriber should agree on the pre-master key R_{prekey} after successful termination


- **Secrecy properties:**

- S1. The attacker cannot obtain the identity $SUPI$ of an honest subscriber
- S2. The attacker cannot obtain the pre-master key R_{prekey} of an honest subscriber
- S3. The attacker cannot obtain the session key $K_{session}$ of an honest subscriber

Counterexample for property A1



Counterexample for property A2



Fixing the protocol

