

Network Analysis in ArangoDB

Alessandro d’Agostino, Mattia Ceccarelli, Riccardo Scheda

January 2020

Abstract

The project aim is to develop a simple python API that let the user interact with the open-source multi-model database ArangoDB to perform fast queries on multi-partite graphs, extract and visualize sub-network which can then be analyzed with powerful python libraries. The study also includes results on the computational efficiency of ArangoDB’s algorithms, in order to have an estimate of the API timing behaviours with large networks.

1 Introduction

ArangoDB [1] is a multi-model, open-source database with flexible data models for documents, graphs and key-values. It is being used in different fields: from semantic analysis to genome studies.

In the present work we employed the library `python-arango` [2] to import and export multi-partite network-like databases, that are defined as collections of documents (nodes) and collections of relationships between them (edges).

In particular, a document is a python dictionary with a mandatory `_id` key assigned to a unique value. What we call an “edge” is also a python dictionary, but with an `_id`, `_source` and `_target` voices, to specify not only the linked nodes, but also the direction of said link in the case of directed graphs.

Graph Object A Graph is the combination of at least one node collection and one or multiple edge collections, called edge definitions. With a Graph two main operations are available: visu-

alization and execution of queries.

The former is possible thanks to ArangoDB web interface, as shown in the figures below, which provide the user many options such as the starting node and the number of elements to load. By default, the starting node is random.

For the latter we relied on the powerful AQL, that is the query language implemented in arango. It is used to execute different kind of “search” through the graph, and select nodes and edges.

Why ArangoDB? ArangoDB resulted to be the NoQL engine with the most favorable compromise between memory usage and computation speed among others available alternatives. (CHIEDERE TABELLA CON LE PRESTAZIONI A NICO) ArangoDB offers a valid web interface where all the commands could be given intuitively and graph and queries’ results could be visualized in an organic way. Furthermore there are several ArangoDB Python interfaces available on line, which allowed us to tailor this powerful tool to our needs.

NetworkX Even though ArangoDB allows fast queries it is necessary the right tool to study the characteristics of a resulting subnet. For this purpose we decided to exploit mainly the Python library NetworkX [3] due to its huge availability of function and tools.

2 Pipeline

Now we describe a typical usage case and all the operations needed to extract a subgraph in ArangoDB. The first thing to do is to read the file in the right input format (typically `.gexf`) through the function `read_gexf`:

```
read_gexf(db,
          filename,
          nodes_collection_name='nodes',
          edges_collection_name='edges',
          graph_name='Net')
```

The function takes the information about nodes and edges from the `gexf` file and creates the correspondent collections on the ArangoDB engine. Then it returns two graphs: one python-arango type and one of networkx type.

Once the graph and the collections of nodes and edges are uploaded on Arango web interface we can proceed with further analysis. For instance, we can perform a graph traversal aimed to extract the first neighbours of a certain node.

In this case we can make use of python-arango, calling the function:

```
first_neighbours = traverse(db,
                             starting_node,
                             nodes_collection_name,
                             graph_name,
                             direction='outbound',
                             item_order='forward',
```

```
                             min_depth=0,
                             max_depth=1,
                             vertex_uniqueness='global')
```

Tuning the given parameters, any traversal could be performed. The output of this type of function is meant to be the resulting sub net saved as Python dictionaries containing vertex and the path crossed by the traverse.

Having the list of the first neighbours we can obtain the corresponding subnet just using the function `subgraph` given by Networkx:

```
Nx_Sub_Net =
    Nx_Net.subgraph([vertex['label']
                     for vertex in
                     first_neighbours['vertices']])
```

In this way we create the minimal subgraph containing only with the labels of nodes and the corresponding edges. To recover the whole information contained in the starting network we add all the attributes back to each node:

```
for node in Nx_Sub_Net:
    attr = pa.get_vertex(db,
                          {'label':node},
                          'Sym_Deas')
    nx.set_node_attributes(Nx_Sub_Net,
                           {node : attr})
```

The last thing to do is to import the subnet in ArangoDB, using the two specific functions `nx_to_arango` and `export_to_arango`, for this passage is better and easier to convert the data in the `node_link_data` format:

```
sub_net = nx.readwrite.node_link_data(Nx_Sub_Net)
sub_net = pa.nx_to_arango(sub_net, 'Sub_Net')
Sub_Net = pa.export_to_arango(db,
                               sub_net ,
```

```
'Sub_Net',
'Sub_Net_edges',
'Sub_Graph')
```

Now the resulting subnet is ready for every kind of analysis offered by NetworkX. This is a usefull procedure to extract articulated subnet even on big non-relational base. Managing a huge amount of information is in fact one of the weak points of a straight NetworkX build.

3 Timing

As already mentioned, one of the main focuses is to apply queries to very big networks. Therefore a study on how the time spent to perform a query scales with graph's dimension was necessary. Hence we chose two different queries to be performed on several graphs with similar characteristics but different dimensions.

The queries taken into consideration are the traversal that extract the second neighbours (`min_depth=0 max_depth=2`) and the first four shortest path between two random nodes .

We created random graphs with a number of nodes ranging from 100 to 10000, using the NetworkX function `fast_gnp_random_graph`. One important factor is the number of link: infact, a dense networks with such an high number of nodes is impossible to handle for a home computer. So, we chose to generate random graphs with $\rho = 0.075$, which come from the analysis of the real case we tested the algorithms on.

We runned the queries under study onto 30 different starting nodes, in order to obtain an average value and an idea of its deviation.

In results We performed a linear fitting on the sampled data and a quite linear relationship

emerged in each case, with an R^2 coefficient always ≥ 0.9 . From this analysis we can extrapolate the behaviour facing an arbitrary big network dimension [Express better this concept]

4 Results




Figure 1: *Timing trend of the extraction of the first 4 shortest paths between two random nodes. The mean is calculated for 30 different couples on the same graph.*




Figure 2: *Timing trend of the second neighbours extraction query. The mean is calculated for 30 different starting nodes on the same graph.*




Figure 3: *ArangoDB visualization tool: in this figure we show a random branch of SymptomsNet, a graph of symptoms and disease.*

5 Conclusions

We’ve produced an applicative to visualize and efficiently query a graph-like database with a simple yet resourceful programming language like python.

As shown in the results, the scaling of the ArangoDB query algorithm is linear for the two cases taken into consideration, k shortest path and neighborhood search. This is promising for future application in large dataset.

Problems The main problems lie in the level of control we can gather through python. Indeed, it seems to be impossible to load and save default queries. Moreover, we couldn’t manage to save graph visualization options, which could




Figure 4: *ArangoDB visualization tool: in this figure we show the network of first neighbours of emicrania (chronic headache).*

ease the accessibility.

Another issue, come from the slowness of the export to arango algorithm, but since it’s a *una tantum* operation, it isn’t a priority.

Future Ideas We will focus on preparing the applicative for the non-programmer user.

We think a Graphical User Interface (GUI) could greatly smoothen the user experience.

In the future we want to test the applicative with a much larger database than the one we had at disposal.

References

- [1] “Arangodb.” <https://www.arangodb.com/>. open-source multi-model database.
- [2] joowani, “python-arango.” <https://github.com/Joowani/python-arango>. Python driver for ArangoDB.
- [3] “Networkx.” <https://networkx.github.io/>. Python library for Complex Networks.