

Modal Logics with Composition on Finite Forests: Expressivity and Complexity

Bartosz Bednarczyk² Stéphane Demri¹ Raul Fervari³ **Alessio Mansutti¹**

LICS 2020

¹LSV, CNRS, E.N.S. Paris-Saclay

²TU Dresden & University of Wrocław

³FAMAF, Universidad Nacional de Córdoba & CONICET

Reasoning on resources, locally

'99 Logic of Bunched Implications (BI) [P. O'Hearn, D. Pym]

Resources composition: $\varphi \bullet \psi$:

 $\models \varphi \bullet \psi$ iff  can be split into  and  s.t.  $\models \varphi$ and  $\models \psi$.

Reasoning on resources, locally

'99 Logic of Bunched Implications (BI) [P. O'Hearn, D. Pym]

Resources composition: $\varphi \bullet \psi$:

 $\models \varphi \bullet \psi$ iff  can be split into  and  s.t.  $\models \varphi$ and  $\models \psi$.

Ambient Logic

$\varphi | \psi$

Verification of Concurrent Systems
specified in Ambient Calculus

Separation Logic

$\varphi * \psi$

Verification of programs
manipulating pointers

Reasoning on resources, locally

'99 Logic of Bunched Implications (BI) [P. O'Hearn, D. Pym]

Resources composition: $\varphi \bullet \psi$:

 $\models \varphi \bullet \psi$ iff  can be split into  and  s.t.  $\models \varphi$ and  $\models \psi$.

Ambient Logic

Separation Logic

Our goal:

Compare $|$ and $*$, in terms of
complexity and expressive power.

Verification of C
specified in A

$\varphi * \psi$

on of programs
relating pointers

Ambient Logic and Separation Logic

Ambient Logic


Model: *Information trees*

$T := 0$ empty tree

| $\mathbf{n}[T]$

| $T \mathbf{\parallel} T$ union of trees

e.g. $a[0] \mathbf{\parallel} b[b[0] \mathbf{\parallel} a[0]]$



Separation Logic

Ambient Logic and Separation Logic

Ambient Logic

Model: *Information trees*

$T := 0$ empty tree


| $n[T]$

+ congruence

| $T \parallel T$ union of trees

\equiv

e.g. $a[0] \parallel b[b[0] \parallel a[0]]$



Separation Logic

Ambient Logic and Separation Logic

Ambient Logic

Model: *Information trees*

$T := 0$ empty tree


| $n[T]$

+ congruence

| $T \mid T$ union of trees

\equiv

e.g. $a[0] \mid b[b[0] \mid a[0]]$



Chop operator:

$T \models \varphi \mid \psi$ iff there are T_1 and T_2 such that
 $T \equiv T_1 \mid T_2$, $T_1 \models \varphi$ and $T_2 \models \psi$.

Separation Logic

Ambient Logic and Separation Logic

Ambient Logic

Model: *Information trees*

$T := 0$ empty tree


| $\mathbf{n}[T]$

+ congruence

| $T \mid T$ union of trees

\equiv

e.g. $a[0] \mid b[b[0] \mid a[0]]$




Chop operator:

$T \models \varphi \mid \psi$ iff there are T_1 and T_2 such that
 $T \equiv T_1 \mid T_2$, $T_1 \models \varphi$ and $T_2 \models \psi$.

Separation Logic

Model: *Memory state* (s, h)

A heap $h \in \mathbb{H}$: finite functional graph



Ambient Logic and Separation Logic

Ambient Logic

Model: *Information trees*

$T := 0$ empty tree


$| \mathbf{n}[T]$

+ congruence

$| T \mid T$ union of trees

\equiv

e.g. $a[0] \mid b[b[0] \mid a[0]]$




Chop operator:

$T \models \varphi \mid \psi$ iff there are T_1 and T_2 such that
 $T \equiv T_1 \mid T_2$, $T_1 \models \varphi$ and $T_2 \models \psi$.

Separation Logic

Model: *Memory state* (s, h)

A heap $h \in \mathbb{H}$: finite functional graph



+ : union of heaps

Ambient Logic and Separation Logic

Ambient Logic

Model: *Information trees*

$T := 0$ empty tree


$| n[T]$

$| T \mid T$ union of trees

+ congruence

\equiv

e.g. $a[0] \mid b[b[0] \mid a[0]]$




Chop operator:

$T \models \varphi \mid \psi$ iff there are T_1 and T_2 such that
 $T \equiv T_1 \mid T_2$, $T_1 \models \varphi$ and $T_2 \models \psi$.

Separation Logic

Model: *Memory state* (s, h)

A heap $h \in \mathbb{H}$: finite functional graph



$+$: union of heaps

Star operator:

$(s, h) \models \varphi * \psi$ iff there are h_1 and h_2 such that
 $h = h_1 + h_2$, $(s, h_1) \models \varphi$ and $(s, h_2) \models \psi$.

Ambient Logic and Separation Logic

Ambient Logic

Model: *Information trees*

$T := 0$ empty tree


$| n[T]$

$| T \mid T$ union of trees

+ congruence

\equiv

e.g. $a[0] \mid b[b[0] \mid a[0]]$




Chop operator:

$T \models \varphi \mid \psi$ iff there are T_1 and T_2 such that
 $T \equiv T_1 \mid T_2$, $T_1 \models \varphi$ and $T_2 \models \psi$.

Separation Logic

Model: *Memory state* (s, h)

A heap $h \in \mathbb{H}$: finite functional graph



$+$: union of heaps

Star operator:

$(s, h) \models \varphi * \psi$ iff there are h_1 and h_2 such that
 $h = h_1 + h_2$, $(s, h_1) \models \varphi$ and $(s, h_2) \models \psi$.

Comparing composition operators: Chop vs. Star

We introduce,

- $\text{ML}(\parallel)$: Modal Logic (ML) extended with $\varphi \parallel \psi$ from Ambient Logic
- $\text{ML}(\ast)$

Comparing composition operators: Chop vs. Star

We introduce,

- $\text{ML}(\parallel)$: Modal Logic (ML) extended with $\varphi \parallel \psi$ from Ambient Logic
- $\text{ML}(*)$: ML extended with $\varphi * \psi$ from Separation Logic

Comparing composition operators: Chop vs. Star

We introduce,

- $\text{ML}(\parallel)$: Modal Logic (ML) extended with $\varphi \parallel \psi$ from Ambient Logic
- $\text{ML}(*)$: ML extended with $\varphi * \psi$ from Separation Logic

For $\text{ML}(\parallel)$ and $\text{ML}(*)$ interpreted on finite forests:

	$\text{ML}(\parallel)$	$\text{ML}(*)$
Expressive Power	Graded Modal Logic (GML)	$< \text{GML}$
Complexity (SAT)	AEXP_{POL} -complete	TOWER-complete

Comparing composition operators: Chop vs. Star

We introduce,

- $ML(\parallel)$: Modal Logic (ML) extended with $\varphi \parallel \psi$ from Ambient Logic
- $ML(*)$: ML extended with $\varphi * \psi$ from Separation Logic

For $ML(\parallel)$ and $ML(*)$ interpreted on finite forests:

	$ML(\parallel)$	$ML(*)$
Expressive Power	Graded Modal Logic (GML)	$< \text{GML}$
Complexity (SAT)	$AEXP_{POL}\text{-complete}$	TOWER-complete

 $AEXP_{TIME}$, with polynomially many alternations


Comparing composition operators: Chop vs. Star

We introduce,

- $\text{ML}(\parallel)$: Modal Logic (ML) extended with $\varphi \parallel \psi$ from Ambient Logic
- $\text{ML}(*)$: ML extended with $\varphi * \psi$ from Separation Logic

For $\text{ML}(\parallel)$ and $\text{ML}(*)$ interpreted on finite forests:

	$\text{ML}(\parallel)$	$\text{ML}(*)$
Expressive Power	Graded Modal Logic (GML)	$< \text{GML}$
Complexity (SAT)	AEXP_{POL} -complete	TOWER-complete

A diagram consisting of a horizontal sequence of 2's separated by dots, with a final 2 at the end. A curly brace is drawn under the first 2, and the word 'elem' is written below it. An orange arrow curves from the bottom of the brace upwards and to the left, pointing towards the 'TOWER-complete' text in the table above.

Comparing composition operators: Chop vs. Star

We introduce,

- $\text{ML}(\parallel)$: Modal Logic (ML) extended with $\varphi \parallel \psi$ from Ambient Logic
- $\text{ML}(*)$: ML extended with $\varphi * \psi$ from Separation Logic

For $\text{ML}(\parallel)$ and $\text{ML}(*)$ interpreted on finite forests:

	$\text{ML}(\parallel)$	$\text{ML}(*)$
Expressive Power	Graded Modal Logic (GML)	$< \text{GML}$
Complexity (SAT)	AEXP_{POL} -complete	TOWER-complete

Comparing composition operators: Chop vs. Star

We introduce,

- $\text{ML}(\parallel)$: Modal Logic (ML) extended with $\varphi \parallel \psi$ from Ambient Logic
- $\text{ML}(*)$: ML extended with $\varphi * \psi$ from Separation Logic

For $\text{ML}(\parallel)$ and $\text{ML}(*)$ interpreted on finite forests:


	$\text{ML}(\parallel)$	$\text{ML}(*)$
Expressive Power	Graded Modal Logic (GML)	$< \text{GML}$
Complexity (SAT)	AEXP_{POL} -complete	TOWER-complete

Results transfer to known fragments/extensions of Ambient Logic and Separation Logic.

ML(|) and ML(*): two ways to chop a tree

The models:

- Atomic propositions: p, q, \dots
- Kripke-style finite forest: (\mathfrak{M}, w)




Standard ML:

$$\varphi := p \mid \top \mid \varphi \wedge \psi \mid \neg \varphi \mid \Diamond \varphi$$

ML(|) and ML(*): two ways to chop a tree

The models:

- Atomic propositions: p, q, \dots
- Kripke-style finite forest: (\mathfrak{M}, w)



Standard ML:


$$\varphi := p \mid \top \mid \varphi \wedge \psi \mid \neg \varphi \mid \Diamond \varphi$$

$$\Diamond(\neg \text{green} \wedge \Diamond \text{blue})$$

ML(|) and ML(*): two ways to chop a tree

The models:

- Atomic propositions: p, q, \dots
- Kripke-style finite forest: (\mathfrak{M}, w)



Standard ML:

$$\varphi := p \mid \top \mid \varphi \wedge \psi \mid \neg \varphi \mid \Diamond \varphi$$

$$\text{ML}(\ast) = \text{ML} + \varphi \ast \psi$$

$\mathfrak{M}, w \models \varphi \ast \psi$ iff there are \mathfrak{M}_1 and \mathfrak{M}_2 , such that


- $\mathfrak{M} = \mathfrak{M}_1 + \mathfrak{M}_2$,
- $\mathfrak{M}_1, w \models \varphi$ and $\mathfrak{M}_2, w \models \psi$.

$\mathfrak{M} = \mathfrak{M}_1 + \mathfrak{M}_2$:

ML(|) and ML(*): two ways to chop a tree

The models:

- Atomic propositions: p, q, \dots
- Kripke-style finite forest: (\mathfrak{M}, w)



Standard ML:


$$\varphi := p \mid \top \mid \varphi \wedge \psi \mid \neg \varphi \mid \Diamond \varphi$$

$$\text{ML}(\ast) = \text{ML} + \varphi \ast \psi$$

$\mathfrak{M}, w \models \varphi \ast \psi$ iff there are \mathfrak{M}_1 and \mathfrak{M}_2 , such that

- $\mathfrak{M} = \mathfrak{M}_1 + \mathfrak{M}_2$,
- $\mathfrak{M}_1, w \models \varphi$ and $\mathfrak{M}_2, w \models \psi$.


$\mathfrak{M} = \mathfrak{M}_1 + \mathfrak{M}_2$:



ML(|) and ML(*): two ways to chop a tree

The models:

- Atomic propositions: p, q, \dots
- Kripke-style finite forest: (\mathfrak{M}, w)




Standard ML:

$$\varphi := p \mid \top \mid \varphi \wedge \psi \mid \neg \varphi \mid \Diamond \varphi$$

$$\text{ML}(\ast) = \text{ML} + \varphi \ast \psi$$

$\mathfrak{M}, w \models \varphi * \psi$ iff there are \mathfrak{M}_1 and \mathfrak{M}_2 , such that

- $\mathfrak{M} = \mathfrak{M}_1 + \mathfrak{M}_2$,
- $\mathfrak{M}_1, w \models \varphi$ and $\mathfrak{M}_2, w \models \psi$.


$$\mathfrak{M} = \mathfrak{M}_1 + \mathfrak{M}_2:$$


Arrows of \mathfrak{M} are arbitrarily split between \mathfrak{M}_1 and \mathfrak{M}_2 .

ML(\mid) and ML(\ast): two ways to chop a tree

The models:

- Atomic propositions: p, q, \dots
- Kripke-style finite forest: (\mathfrak{M}, w)



Standard ML:

$$\varphi := p \mid \top \mid \varphi \wedge \psi \mid \neg \varphi \mid \Diamond \varphi$$

$$\text{ML}(\mid) = \text{ML} + \varphi \mid \psi$$

$\mathfrak{M}, w \models \varphi \mid \psi$ iff there are \mathfrak{M}_1 and \mathfrak{M}_2 , such that


- $\mathfrak{M} = \mathfrak{M}_1 \mid_w \mathfrak{M}_2$,
- $\mathfrak{M}_1, w \models \varphi$ and $\mathfrak{M}_2, w \models \psi$.

$$\mathfrak{M} = \mathfrak{M}_1 \mid_w \mathfrak{M}_2:$$

ML(|) and ML(*): two ways to chop a tree

The models:

- Atomic propositions: p, q, \dots
- Kripke-style finite forest: (\mathfrak{M}, w)



Standard ML:


$$\varphi := p \mid \top \mid \varphi \wedge \psi \mid \neg \varphi \mid \Diamond \varphi$$

$$\text{ML}(|) = \text{ML} + \varphi | \psi$$

$\mathfrak{M}, w \models \varphi | \psi$ iff there are \mathfrak{M}_1 and \mathfrak{M}_2 , such that

- $\mathfrak{M} = \mathfrak{M}_1 \mid_w \mathfrak{M}_2$,
- $\mathfrak{M}_1, w \models \varphi$ and $\mathfrak{M}_2, w \models \psi$.


$\mathfrak{M} = \mathfrak{M}_1 \mid_w \mathfrak{M}_2$:



ML(|) and ML(*): two ways to chop a tree

The models:

- Atomic propositions: p, q, \dots
- Kripke-style finite forest: (\mathfrak{M}, w)



Standard ML:


$$\varphi := p \mid \top \mid \varphi \wedge \psi \mid \neg \varphi \mid \Diamond \varphi$$

$$\text{ML}(|) = \text{ML} + \varphi | \psi$$

$\mathfrak{M}, w \models \varphi | \psi$ iff there are \mathfrak{M}_1 and \mathfrak{M}_2 , such that

- $\mathfrak{M} = \mathfrak{M}_1 |_w \mathfrak{M}_2$,
- $\mathfrak{M}_1, w \models \varphi$ and $\mathfrak{M}_2, w \models \psi$.

$\mathfrak{M} = \mathfrak{M}_1 |_w \mathfrak{M}_2$:




Subtrees rooted in a children of w are preserved.

ML(\mid) and ML(\ast): two ways to chop a tree

The models:

- Atomic propositions: p, q, \dots
- Kripke-style finite forest: (\mathfrak{M}, w)



Standard ML:


$$\varphi := p \mid \top \mid \varphi \wedge \psi \mid \neg \varphi \mid \Diamond \varphi$$

$$\text{ML}(\mid) = \text{ML} + \varphi \mid \psi$$

$\mathfrak{M}, w \models \varphi \mid \psi$ iff there are \mathfrak{M}_1 and \mathfrak{M}_2 , such that

- $\mathfrak{M} = \mathfrak{M}_1 \mid_w \mathfrak{M}_2$,
- $\mathfrak{M}_1, w \models \varphi$ and $\mathfrak{M}_2, w \models \psi$.


$$\mathfrak{M} = \mathfrak{M}_1 \mid_w \mathfrak{M}_2:$$



ML(|) and ML(*): two ways to chop a tree

The models:

- Atomic propositions: p, q, \dots
- Kripke-style finite forest: (\mathfrak{M}, w)



Standard ML:


$$\varphi := p \mid \top \mid \varphi \wedge \psi \mid \neg \varphi \mid \Diamond \varphi$$

$$\text{ML}(|) = \text{ML} + \varphi | \psi$$

$\mathfrak{M}, w \models \varphi | \psi$ iff there are \mathfrak{M}_1 and \mathfrak{M}_2 , such that

- $\mathfrak{M} = \mathfrak{M}_1 |_w \mathfrak{M}_2$,
- $\mathfrak{M}_1, w \models \varphi$ and $\mathfrak{M}_2, w \models \psi$.

$$\mathfrak{M} = \mathfrak{M}_1 |_w \mathfrak{M}_2:$$



$ML(\perp)$ vs $ML(*)$: preliminary analysis

- Both $ML(\perp)$ and $ML(*)$ are captured by MSO on finite forests


\Rightarrow their SAT problem is in `TOWER`

ML(\sqcup) vs ML($*$): preliminary analysis

- Both ML(\sqcup) and ML($*$) are captured by MSO on finite forests

\Rightarrow their SAT problem is in TOWER

$(\Diamond\varphi) \sqcup (\Diamond\varphi) \sqcup \Diamond\varphi$




ML(\sqcup) vs ML($*$): preliminary analysis

- Both ML(\sqcup) and ML($*$) are captured by MSO on finite forests

\Rightarrow their SAT problem is in TOWER

$$(\Diamond\varphi) \sqcup (\Diamond\varphi) \sqcup \Diamond\varphi$$



ML(\sqcup) vs ML($*$): preliminary analysis


- Both ML(\sqcup) and ML($*$) are captured by MSO on finite forests

\Rightarrow their SAT problem is in TOWER

$$\Diamond_{\geq 3} \varphi \equiv (\Diamond \varphi) \sqcup (\Diamond \varphi) \sqcup \Diamond \varphi$$

Graded modal logic (GML): ML + $(\Diamond_{\geq k} \varphi)_{k \in \mathbb{N}}$

$\mathfrak{M}, w \models \Diamond_{\geq k} \varphi$ iff w has at least k children satisfying φ .



ML(\mid) is as expressive as GML

Show that GML is closed under the operator \mid :

Consider $\varphi_1 \mid \varphi_2$ such that φ_1 and φ_2 are in GML. Find γ in GML s.t. $\gamma \equiv \varphi_1 \mid \varphi_2$.

ML($|$) is as expressive as GML

Show that GML is closed under the operator $|$:

Consider $\varphi_1 | \varphi_2$ such that φ_1 and φ_2 are in GML. Find γ in GML s.t. $\gamma \equiv \varphi_1 | \varphi_2$.

Some ingredients:

$$(\Diamond_{\geq 3} \varphi \wedge \neg \Diamond_{\geq 7} \varphi) | \Diamond_{\geq 2} \varphi \equiv \Diamond_{\geq 3+2} \varphi$$

ML($|$) is as expressive as GML

Show that GML is closed under the operator $|$:

Consider $\varphi_1 | \varphi_2$ such that φ_1 and φ_2 are in GML. Find γ in GML s.t. $\gamma \equiv \varphi_1 | \varphi_2$.

Some ingredients:

$$(\Diamond_{\geq 3} \varphi \wedge \neg \Diamond_{\geq 7} \varphi) | \Diamond_{\geq 2} \varphi \equiv \Diamond_{\geq 3+2} \varphi$$

- **Idea:** we see $\Diamond_{\geq k} \varphi$ as the expression $x_\varphi \geq k$ of Presburger Arithmetic (PA)
- Translation in PA:

$$\underbrace{\exists y_\varphi \exists z_\varphi}_{\text{there are } \mathfrak{M}_1, \mathfrak{M}_2} \cdot \underbrace{x_\varphi = y_\varphi + z_\varphi}_{\mathfrak{M} = \mathfrak{M}_1 | \mathfrak{M}_2} \wedge \underbrace{y_\varphi \geq 3 \wedge \neg y_\varphi \geq 7}_{\mathfrak{M}_1, w \models \Diamond_{\geq 3} \varphi \wedge \neg \Diamond_{\geq 7} \varphi} \wedge \underbrace{z_\varphi \geq 2}_{\mathfrak{M}_2, w \models \Diamond_{\geq 2} \varphi}$$

ML($|$) is as expressive as GML

Show that GML is closed under the operator $|$:

Consider $\varphi_1 | \varphi_2$ such that φ_1 and φ_2 are in GML. Find γ in GML s.t. $\gamma \equiv \varphi_1 | \varphi_2$.

Some ingredients:

$$(\Diamond_{\geq 3} \varphi \wedge \neg \Diamond_{\geq 7} \varphi) | \Diamond_{\geq 2} \varphi \equiv \Diamond_{\geq 3+2} \varphi$$

- **Idea:** we see $\Diamond_{\geq k} \varphi$ as the expression $x_\varphi \geq k$ of Presburger Arithmetic (PA)

 number of children satisfying φ

- Translation in PA:

$$\underbrace{\exists \mathbf{y}_\varphi \exists \mathbf{z}_\varphi}_{\text{there are } \mathfrak{M}_1, \mathfrak{M}_2} \cdot \underbrace{\mathbf{x}_\varphi = \mathbf{y}_\varphi + \mathbf{z}_\varphi}_{\mathfrak{M} = \mathfrak{M}_1 | \mathfrak{M}_2} \wedge \underbrace{\mathbf{y}_\varphi \geq 3 \wedge \neg \mathbf{y}_\varphi \geq 7}_{\mathfrak{M}_1, w \models \Diamond_{\geq 3} \varphi \wedge \neg \Diamond_{\geq 7} \varphi} \wedge \underbrace{\mathbf{z}_\varphi \geq 2}_{\mathfrak{M}_2, w \models \Diamond_{\geq 2} \varphi}$$

ML($|$) is as expressive as GML

Show that GML is closed under the operator $|$:

Consider $\varphi_1 | \varphi_2$ such that φ_1 and φ_2 are in GML. Find γ in GML s.t. $\gamma \equiv \varphi_1 | \varphi_2$.

Some ingredients:

$$(\Diamond_{\geq 3} \varphi \wedge \neg \Diamond_{\geq 7} \varphi) | \Diamond_{\geq 2} \varphi \equiv \Diamond_{\geq 3+2} \varphi$$

- **Idea:** we see $\Diamond_{\geq k} \varphi$ as the expression $x_\varphi \geq k$ of Presburger Arithmetic (PA)

 number of children satisfying φ

- Translation in PA:

$$\underbrace{\exists y_\varphi \exists z_\varphi}_{\text{there are } \mathfrak{M}_1, \mathfrak{M}_2} \cdot \underbrace{x_\varphi = y_\varphi + z_\varphi}_{\mathfrak{M} = \mathfrak{M}_1 | \mathfrak{M}_2} \wedge \underbrace{y_\varphi \geq 3 \wedge \neg y_\varphi \geq 7}_{\mathfrak{M}_1, w \models \Diamond_{\geq 3} \varphi \wedge \neg \Diamond_{\geq 7} \varphi} \wedge \underbrace{z_\varphi \geq 2}_{\mathfrak{M}_2, w \models \Diamond_{\geq 2} \varphi} \equiv x_\varphi \geq 3 + 2$$

ML(\mid) is as expressive as GML

Show that GML is closed under the operator \mid :

Consider $\varphi_1 \mid \varphi_2$ such that φ_1 and φ_2 are in GML. Find γ in GML s.t. $\gamma \equiv \varphi_1 \mid \varphi_2$.

Some ingredients:

$$\Diamond_{\geq k_1} \varphi \mid \Diamond_{\geq k_2} \psi$$

If $\varphi \wedge \psi$ is satisfiable, then the value of x_φ could depend on the value of x_ψ .

ML(\mid) is as expressive as GML

Show that GML is closed under the operator \mid :

Consider $\varphi_1 \mid \varphi_2$ such that φ_1 and φ_2 are in GML. Find γ in GML s.t. $\gamma \equiv \varphi_1 \mid \varphi_2$.

Some ingredients:

$$\Diamond_{\geq k_1} \varphi \mid \Diamond_{\geq k_2} \psi$$

If $\varphi \wedge \psi$ is satisfiable, then the value of x_φ could depend on the value of x_ψ .

- **Idea:** manipulate the formula so that $\varphi = \psi$, or $\varphi \wedge \psi$ unsatisfiable
- **Cost:** one exponential blow-up

ML(\mid) is as expressive as GML

Show that GML is closed under the operator \mid :

Consider $\varphi_1 \mid \varphi_2$ such that φ_1 and φ_2 are in GML. Find γ in GML s.t. $\gamma \equiv \varphi_1 \mid \varphi_2$.

Some ingredients:

$$\Diamond_{\geq k_1} \varphi \mid \Diamond_{\geq k_2} \psi$$

If $\varphi \wedge \psi$ is satisfiable, then the value of x_φ could depend on the value of x_ψ .

- **Idea:** manipulate the formula so that $\varphi = \psi$, or $\varphi \wedge \psi$ unsatisfiable
- **Cost:** one exponential blow-up

From the translation: ML(\mid) has an exp-size small-model property.

SAT(ML(|)) is AExp_{POL}-complete

 AExpTIME, with polynomially many alternations

SAT(ML(|)) is in AExp_{POL}:

- See φ in ML(|) as a formula from MSO (on finite forests)
- Guess a finite forest (\mathfrak{M}, w) of size exponential in $|\varphi|$
- Check whether $\mathfrak{M}, w \models \varphi$

SAT(ML(\mathbb{I})) is $\mathbf{AExp_{POL}}$ -complete

 $\mathbf{AExpTIME}$, with polynomially many alternations

SAT(ML(\mathbb{I})) is in $\mathbf{AExp_{POL}}$:

- See φ in ML(\mathbb{I}) as a formula from MSO (on finite forests)
- Guess a finite forest (\mathfrak{M}, w) of size exponential in $|\varphi|$
- Check whether $\mathfrak{M}, w \models \varphi$

SAT(ML(\mathbb{I})) is $\mathbf{AExp_{POL}}$ -hard:

- Every formula of Team Logic can be translated to a ML(\mathbb{I}) formula of with modal depth 1
- Team Logic is $\mathbf{AExp_{POL}}$ -complete [Hannula et al., TOCL'18]

A closer look on $ML(*)$


$$(\Diamond\varphi) \mid (\Diamond\varphi) \Rightarrow \Diamond_{\geq 2}\varphi$$

A closer look on $ML(*)$

$$(\Diamond\Diamond_{=1}\bigcirc) \mid (\Diamond\Diamond_{=1}\bigcirc) \Rightarrow \Diamond_{\geq 2}\Diamond_{=1}\bigcirc$$


A closer look on $ML(*)$

$$(\diamond\diamond=1 \text{ } \textcircled{\text{blue}}) * (\diamond\diamond=1 \text{ } \textcircled{\text{blue}}) \Rightarrow \diamond \geq 2 \diamond=1 \text{ } \textcircled{\text{blue}}$$




A closer look on $ML(*)$

$$(\diamond\diamond=1 \text{ (blue circle)}) * (\diamond\diamond=1 \text{ (blue circle)}) \Rightarrow \diamond \geq 2 \diamond = 1 \text{ (blue circle)}$$




A closer look on $ML(*)$

$$(\diamond\diamond=1 \text{ (blue)}) * (\diamond\diamond=1 \text{ (blue)}) \Rightarrow \diamond \geq 2 \diamond=1 \text{ (blue)}$$



A closer look on $ML(*)$

$$(\diamond\diamond=1 \text{ (blue circle)}) * (\diamond\diamond=1 \text{ (blue circle)}) \Rightarrow \diamond \geq 2 \diamond=1 \text{ (blue circle)}$$



ML(*) is at most as expressive as GML

Show that GML is closed under the “operator” $(-) * \Box \perp$.

$\text{ML}(\ast)$ is at most as expressive as GML

Show that GML is closed under the “operator” $(-) \ast \Box \perp$.

Some ingredients:

We rely on g -bisimulation [see De Rijke,'00]

$\mathfrak{M}, w \approx_{m,k}^P \mathfrak{M}', w$ iff for every $\varphi \in \text{GML}[m, k, P]$ ($\mathfrak{M}, w \models \varphi$ iff $\mathfrak{M}', w' \models \varphi$)

(m maximal modal depth, k maximal coefficient for $\Diamond_{\geq k}$, P finite set of atomic propositions)


$ML(*)$ is at most as expressive as GML

Show that GML is closed under the “operator” $(-) * \Box \perp$.

Some ingredients:

↙ (modal depth, coefficient $\Diamond_{\geq k}$)

To show: there is a function $f: \mathbb{N}^2 \rightarrow \mathbb{N}$ such that




ML(*) is at most as expressive as GML

Show that GML is closed under the “operator” $(-) * \square \perp$.

Some ingredients:

To show: there is a function $f: \mathbb{N}^2 \rightarrow \mathbb{N}$ such that




ML(*) is at most as expressive as GML

Show that GML is closed under the “operator” $(-) * \Box \perp$.

Some ingredients:

To show: there is a function $f: \mathbb{N}^2 \rightarrow \mathbb{N}$ such that




$ML(*)$ is at most as expressive as GML

Show that GML is closed under the “operator” $(-) * \Box \perp$.

Some ingredients:

To show: there is a function $f: \mathbb{N}^2 \rightarrow \mathbb{N}$ such that




$ML(*)$ is at most as expressive as GML

Show that GML is closed under the “operator” $(-) * \Box \perp$.

Some ingredients:


To show: there is a function $f: \mathbb{N}^2 \rightarrow \mathbb{N}$ such that



f is a non-elementary function. Can we do better?

No: we can characterise worlds of “type k ” with a $ML(*)$ formula of size exponential in k

- Type k nodes used for Quantified ML (QML) [Bednarczyk, Demri, LICS'19]



A diagram illustrating the exponential growth of children for type k nodes. It shows a sequence of powers of 2: $2^2 \cdot \dots \cdot 2$. An orange curly brace underneath the first 2^2 is labeled with a subscript k . An orange arrow points from this brace up and to the left towards the text "Type k nodes" in the list above. The word "children" is written in orange to the right of the sequence.


$$2^2 \cdot \dots \cdot 2$$

children

f is a non-elementary function. Can we do better?

No: we can characterise worlds of “type k ” with a $ML(*)$ formula of size exponential in k


- Type k nodes used for Quantified ML (QML) [Bednarczyk, Demri, LICS'19]



f is a non-elementary function. Can we do better?

No: we can characterise worlds of “type k ” with a $ML(*)$ formula of size exponential in k


- Type k nodes used for Quantified ML (QML) [Bednarczyk, Demri, LICS'19]



f is a non-elementary function. Can we do better?

No: we can characterise worlds of “type k ” with a $ML(*)$ formula of size exponential in k

- Type k nodes used for Quantified ML (QML) [Bednarczyk, Demri, LICS'19]




- every child is of type 1
- every child encode a different number
- every number is encoded by a child

f is a non-elementary function. Can we do better?

No: we can characterise worlds of “type k ” with a $ML(*)$ formula of size exponential in k


- Type k nodes used for Quantified ML (QML) [Bednarczyk, Demri, LICS'19]



f is a non-elementary function. Can we do better?

No: we can characterise worlds of “type k ” with a $ML(*)$ formula of size exponential in k


- Type k nodes used for Quantified ML (QML) [Bednarczyk, Demri, LICS'19]



f is a non-elementary function. Can we do better?

No: we can characterise worlds of “type k ” with a $ML(*)$ formula of size exponential in k


- Type k nodes used for Quantified ML (QML) [Bednarczyk, Demri, LICS'19]



f is a non-elementary function. Can we do better?

No: we can characterise worlds of “type k ” with a $ML(*)$ formula of size exponential in k

- Type k nodes used for Quantified ML (QML) [Bednarczyk, Demri, LICS'19]



A node of type k , has $f(k)$ children, where $f(1) = 2$ and $f(k + 1) = 2^{f(k)}$

f is a non-elementary function. Can we do better?

No: we can characterise worlds of “type k ” with a $ML(*)$ formula of size exponential in k

- Type k nodes used for Quantified ML (QML) [Bednarczyk, Demri, LICS'19]



Issues:

- The operator $*$ is less powerful than the 2nd-order quantification of QML
- The operator $*$ breaks the encoding of numbers (if not handled correctly)

Tower-hardness of $SAT(ML(*))$:



- Uniform reduction from the k -NEXPTIME version of the tiling problem, for $k \geq 2$

Recap

	 <p>ML(I)</p>	 <p>ML(*)</p>
Expressive Power	GML	\leq GML
Complexity (SAT)	AEXP _{POL} -complete	TOWER-complete

There is more...



Recap

	 <p>ML(I)</p>	 <p>ML(*)</p>
Expressive Power	GML	< GML
Complexity (SAT)	AEXP _{POL} -complete	TOWER-complete

There is more...

$\Diamond_{=2}\Diamond_{=1}\top$ cannot be expressed in $ML(*)$ (proof via EF-games)

Recap



	 <p>ML(I)</p>	 <p>ML(*)</p>
Expressive Power	GML	< GML
Complexity (SAT)	AEXP _{POL} -complete	TOWER-complete

There is more...

SAT(ML(I)) shows that

- Quantifier-free Intensional fragment of Ambient Logic is AEXP_{POL}-complete
- Ambient Logic in [Calcagno et al., TLDI'03] is AEXP_{POL}-hard

Recap

	 ML(I)	 ML(*)
Expressive Power	GML	< GML
Complexity (SAT)	AEXP _{POL} -complete	TOWER-complete

There is more...

SAT(ML(*)) shows that $MSL(*, \Diamond^{-1})$ [Demri, Fervari, AIML'18] is TOWER-complete.

Thanks for your attention.

Modal Logics with Composition on Finite Forests: Expressivity and Complexity

Bartosz Bednarczyk, Stéphane Demri, Raul Fervari, **Alessio Mansutti**