

Modal Logics and Local Quantifiers: A Zoo in the Elementary Hierarchy

Raul Fervari¹, **Alessio Mansutti**²

¹ Universidad Nacional de Córdoba, Argentina

² University of Oxford, UK



Enriching logics with quantification

A way to dynamically update a model and reason on its complex behavior.

Enriching logics with quantification

A way to dynamically update a model and reason on its complex behavior.

	Satisfiability problem
SAT \rightarrow QBF	NP \rightarrow PSPACE

Enriching logics with quantification

A way to dynamically update a model and reason on its complex behavior.

	Satisfiability problem
SAT \rightarrow QBF	NP \rightarrow PSPACE
ML \rightarrow QML	PSPACE \rightarrow undecidable [Fine, PhD thesis '70]

Enriching logics with quantification

A way to dynamically update a model and reason on its complex behavior.

	Satisfiability problem
SAT \rightarrow QBF	NP \rightarrow PSPACE
ML \rightarrow QML	PSPACE \rightarrow undecidable [Fine, PhD thesis '70]
CTL \rightarrow QCTL	EXPTIME \rightarrow undecidable [Laroussinie and Markey, LMCS'14]

Enriching logics with quantification

A way to dynamically update a model and reason on its complex behavior.

	Satisfiability problem	
SAT \rightarrow QBF	NP \rightarrow PSPACE	
ML \rightarrow QML	PSPACE \rightarrow undecidable	[Fine, PhD thesis '70]
CTL \rightarrow QCTL	EXPTIME \rightarrow undecidable	[Laroussinie and Markey, LMCS'14]
LTL \rightarrow HyperLTL	PSPACE \rightarrow Σ_1^1	[Fortin et al., MFCS'21]

Enriching logics with quantification


A way to dynamically update a model and reason on its complex behavior.

	Satisfiability problem	
SAT \rightarrow QBF	NP \rightarrow PSPACE	
ML \rightarrow QML	PSPACE \rightarrow undecidable	[Fine, PhD thesis '70]
CTL \rightarrow QCTL	EXPTIME \rightarrow undecidable	[Laroussinie and Markey, LMCS'14]
LTL \rightarrow HyperLTL	PSPACE $\rightarrow \Sigma_1^1$	[Fortin et al., MFCS'21]

Modal logic and propositional quantifiers

Kripke structure*:

- Atomic propositions: p, q, \dots
- worlds and accessibility relation:



* In this work we consider **Kripke trees**


Quantified ML:

$$\varphi, \psi ::= p \mid \top \mid \varphi \wedge \psi \mid \neg \varphi \mid \Diamond \varphi \mid \exists p : \varphi$$

Modal logic and propositional quantifiers

Kripke structure*:

- Atomic propositions: p, q, \dots
- worlds and accessibility relation:



* In this work we consider **Kripke trees**

Quantified ML:


$$\varphi, \psi := p \mid \top \mid \varphi \wedge \psi \mid \neg \varphi \mid \Diamond \varphi \mid \exists p : \varphi$$

E.g. (standard ML): $\Diamond(\neg \text{green} \wedge \Diamond \text{blue})$

Modal logic and propositional quantifiers

Kripke structure*:

- Atomic propositions: p, q, \dots
- worlds and accessibility relation:



* In this work we consider **Kripke trees**

Quantified ML:

$$\varphi, \psi := p \mid \top \mid \varphi \wedge \psi \mid \neg\varphi \mid \Diamond\varphi \mid \exists p : \varphi$$

E.g. (standard ML): $\Diamond(\neg \text{green} \wedge \Diamond \text{blue})$


First-order semantics:

$\mathfrak{M}, w \models \exists p : \varphi \Leftrightarrow$ there is a world w'
such that $\mathfrak{M}[p \leftarrow \{w'\}], w \models \varphi$

Modal logic and propositional quantifiers

Kripke structure*:

- Atomic propositions: p, q, \dots
- worlds and accessibility relation:



* In this work we consider **Kripke trees**

Quantified ML:

$$\varphi, \psi := p \mid \top \mid \varphi \wedge \psi \mid \neg \varphi \mid \Diamond \varphi \mid \exists p : \varphi$$

E.g. (standard ML): $\Diamond(\neg \text{green} \wedge \Diamond \text{blue})$

First-order semantics:


$\mathfrak{M}, w \models \exists p : \varphi \Leftrightarrow$ there is a world w'
such that $\mathfrak{M}[p \leftarrow \{w'\}], w \models \varphi$

E.g.: $\exists r : \Diamond \Diamond (\text{orange} \wedge r) \wedge \Diamond \Diamond (\text{orange} \wedge \neg r)$

Modal logic and propositional quantifiers

Kripke structure*:

- Atomic propositions: p, q, \dots
- worlds and accessibility relation:



* In this work we consider **Kripke trees**

Quantified ML:

$$\varphi, \psi := p \mid \top \mid \varphi \wedge \psi \mid \neg \varphi \mid \Diamond \varphi \mid \exists p : \varphi$$

E.g. (standard ML): $\Diamond(\neg \text{green} \wedge \Diamond \text{blue})$

First-order semantics:

$\mathfrak{M}, w \models \exists p : \varphi \Leftrightarrow$ there is a world w'
such that $\mathfrak{M}[p \leftarrow \{w'\}], w \models \varphi$

E.g.: $\exists r : \Diamond \Diamond (\text{orange} \wedge r) \wedge \Diamond \Diamond (\text{orange} \wedge \neg r)$

Second-order semantics:

$\mathfrak{M}, w \models \exists p : \varphi \Leftrightarrow$ there is a set of worlds W
such that $\mathfrak{M}[p \leftarrow W], w \models \varphi$

QML is very concise!

Theorem (Bednarczyk and Demri, LICS'19)

$\underbrace{2^{2^{\dots^2}}}_{f(n)}$



On trees, the SAT problem of second-order quantified modal logic is TOWER-hard.

Proof technique: uniform translation from the $k\text{NEXPTIME}$ version of the tiling problem, for every $k \geq 1$. The translation is exponential in k .

QML is very concise!

Theorem (Bednarczyk and Demri, LICS'19)

$$\underbrace{2^{2^{\dots^2}}}_{f(n)}$$


On trees, the SAT problem of second-order quantified modal logic is TOWER-hard.

Proof technique: uniform translation from the $k\text{NEXPTIME}$ version of the tiling problem, for every $k \geq 1$. The translation is exponential in k .

Unpleasant result:

1. QML on trees subsumes Dependence logic, Team logic, Modal team logic, Ambient logic, Sabotage modal logic (on trees) ...
but decision procedures for QML are suboptimal for these logics
2. Difficult result to parametrize (e.g. because translation is exponential).

Question: what is the expressiveness of QML on trees?

QML is very concise!

Theorem (Bednarczyk and Demri, LICS'19)

$$\underbrace{2^{2^{\dots^2}}}_{f(n)}$$


On trees, the SAT problem of second-order quantified modal logic is TOWER-hard.

Goals of this paper:

- Give a complexity analysis of QML (for both FO and SO semantics) that is more parametric and hierarchical, instead of just TOWER
- Characterise the expressive power of QML.

but decision procedures for QML are suboptimal for these logics

2. Difficult result to parametrize (e.g. because translation is exponential).

Question: what is the expressiveness of QML on trees?

Depth of quantification as a parameter?

Local quantifier $\exists^k q$: binds q to worlds accessible in at most k steps.

$$\text{ML}(\exists^k) = \text{ML} + \exists^1 + \dots + \exists^k$$

$\text{ML}(\exists_{FO}^k)$: $\text{ML}(\exists^k)$ under FO semantics $\text{ML}(\exists_{SO}^k)$: $\text{ML}(\exists^k)$ under SO semantics

Depth of quantification as a parameter?

Local quantifier $\exists^k q$: binds q to worlds accessible in at most k steps.

$$\text{ML}(\exists^k) = \text{ML} + \exists^1 + \dots + \exists^k$$

$\text{ML}(\exists_{FO}^k)$: $\text{ML}(\exists^k)$ under FO semantics $\text{ML}(\exists_{SO}^k)$: $\text{ML}(\exists^k)$ under SO semantics

Theorem (M., Fervari, *available soon(ish)*)

The SAT problem of $\text{ML}(\exists_{FO}^2)$ is already TOWER-hard.

Depth of quantification as a parameter?

Local quantifier $\exists^k q$: binds q to worlds accessible in at most k steps.


$$\text{ML}(\exists^k) = \text{ML} + \exists^1 + \dots + \exists^k$$

$\text{ML}(\exists_{FO}^k)$: $\text{ML}(\exists^k)$ under FO semantics

$\text{ML}(\exists_{SO}^k)$: $\text{ML}(\exists^k)$ under SO semantics

Theorem (M., Fervari, *available soon(ish)*)

The SAT problem of $\text{ML}(\exists_{FO}^2)$ is already TOWER-hard.



Depth of quantification as a parameter?

Local quantifier $\exists^k q$: binds q to worlds accessible in at most k steps.


$$\text{ML}(\exists^k) = \text{ML} + \exists^1 + \dots + \exists^k$$

$\text{ML}(\exists_{FO}^k)$: $\text{ML}(\exists^k)$ under FO semantics

$\text{ML}(\exists_{SO}^k)$: $\text{ML}(\exists^k)$ under SO semantics

Theorem (M., Fervari, *available soon(ish)*)

The SAT problem of $\text{ML}(\exists_{FO}^2)$ is already TOWER-hard.



Depth of quantification as a parameter?

Local quantifier $\exists^k q$: binds q to worlds accessible in at most k steps.


$$\text{ML}(\exists^k) = \text{ML} + \exists^1 + \dots + \exists^k$$

$\text{ML}(\exists^k_{FO})$: $\text{ML}(\exists^k)$ under FO semantics

$\text{ML}(\exists^k_{SO})$: $\text{ML}(\exists^k)$ under SO semantics

Theorem (M., Fervari, *available soon(ish)*)

The SAT problem of $\text{ML}(\exists^2_{FO})$ is already TOWER-hard.



Depth of quantification as a parameter?

Local quantifier $\exists^k q$: binds q to worlds accessible in at most k steps.


$$\text{ML}(\exists^k) = \text{ML} + \exists^1 + \dots + \exists^k$$

$\text{ML}(\exists_{FO}^k)$: $\text{ML}(\exists^k)$ under FO semantics

$\text{ML}(\exists_{SO}^k)$: $\text{ML}(\exists^k)$ under SO semantics

Theorem (M., Fervari, *available soon(ish)*)

The SAT problem of $\text{ML}(\exists_{FO}^2)$ is already TOWER-hard.



Depth of quantification as a parameter?

Local quantifier $\exists^k q$: binds q to worlds accessible in at most k steps.


$$\text{ML}(\exists^k) = \text{ML} + \exists^1 + \dots + \exists^k$$

$\text{ML}(\exists_{FO}^k)$: $\text{ML}(\exists^k)$ under FO semantics

$\text{ML}(\exists_{SO}^k)$: $\text{ML}(\exists^k)$ under SO semantics

Theorem (M., Fervari, *available soon(ish)*)

The SAT problem of $\text{ML}(\exists_{FO}^2)$ is already TOWER-hard.



Depth of quantification as a parameter?

Local quantifier $\exists^k q$: binds q to worlds accessible in at most k steps.


$$\text{ML}(\exists^k) = \text{ML} + \exists^1 + \dots + \exists^k$$

$\text{ML}(\exists_{FO}^k)$: $\text{ML}(\exists^k)$ under FO semantics

$\text{ML}(\exists_{SO}^k)$: $\text{ML}(\exists^k)$ under SO semantics

Theorem (M., Fervari, *available soon(ish)*)

The SAT problem of $\text{ML}(\exists_{FO}^2)$ is already TOWER-hard.



Depth of quantification as a parameter?

Local quantifier $\exists^k q$: binds q to worlds accessible in at most k steps.


$$\text{ML}(\exists^k) = \text{ML} + \exists^1 + \dots + \exists^k$$

$\text{ML}(\exists^k_{FO})$: $\text{ML}(\exists^k)$ under FO semantics

$\text{ML}(\exists^k_{SO})$: $\text{ML}(\exists^k)$ under SO semantics

Theorem (M., Fervari, *available soon(ish)*)

The SAT problem of $\text{ML}(\exists^2_{FO})$ is already TOWER-hard.



Depth of quantification as a parameter?

Local quantifier $\exists^k q$: binds q to worlds accessible in at most k steps.


$$\text{ML}(\exists^k) = \text{ML} + \exists^1 + \dots + \exists^k$$

$\text{ML}(\exists^k_{FO})$: $\text{ML}(\exists^k)$ under FO semantics

$\text{ML}(\exists^k_{SO})$: $\text{ML}(\exists^k)$ under SO semantics

Theorem (M., Fervari, *available soon(ish)*)

The SAT problem of $\text{ML}(\exists^2_{FO})$ is already TOWER-hard.



Observation: it is not just the depth of quantification that makes the problem hard, but also the “depth of interaction” between quantifiers.

Depth of interaction via the round-bounded fragment

Syntactic fragment of $\text{ML}(\exists^k)$ (for both FO and SO) such that

$$\text{ML}(\exists^{j+2}) \xrightarrow{\diamond} \text{ML}(\exists^{j+1}) \qquad \text{ML}(\exists^1) \xrightarrow{\diamond} \text{ML}(\exists^k)$$

E.g.: if φ is round-bounded for $\text{ML}(\exists^3)$, then so is $\exists^3 p \diamond \exists^2 q \diamond \exists^1 r \diamond \exists^3 p : \varphi$.

Depth of interaction via the round-bounded fragment

Syntactic fragment of $\text{ML}(\exists^k)$ (for both FO and SO) such that

$$\text{ML}(\exists^{j+2}) \xrightarrow{\diamond} \text{ML}(\exists^{j+1}) \qquad \text{ML}(\exists^1) \xrightarrow{\diamond} \text{ML}(\exists^k)$$

E.g.: if φ is round-bounded for $\text{ML}(\exists^3)$, then so is $\exists^3 p \diamond \exists^2 q \diamond \exists^1 r \diamond \exists^3 p : \varphi$.

A hierarchy for QML: $\text{QML} = \bigcup_{k=1}^{\infty} (\text{round-bounded } \text{ML}(\exists^k))$

Depth of interaction via the round-bounded fragment

Syntactic fragment of $ML(\exists^k)$ (for both FO and SO) such that

$$ML(\exists^{j+2}) \xrightarrow{\diamond} ML(\exists^{j+1})$$

$$ML(\exists^1) \xrightarrow{\diamond} ML(\exists^k)$$

Theorem

The SAT problem of round-bounded $ML(\exists_{FO}^k)$ is $(k+1)\text{NEXP TIME}$ -complete. The SAT problem of $ML(\exists_{FO}^k)$ is $k\text{NEXP TIME}$ -complete for formulae of modal depth $\leq k$.

Depth of interaction via the round-bounded fragment

Syntactic fragment of $ML(\exists^k)$ (for both FO and SO) such that

$$ML(\exists^{j+2}) \xrightarrow{\diamond} ML(\exists^{j+1})$$

$$ML(\exists^1) \xrightarrow{\diamond} ML(\exists^k)$$

Theorem

The SAT problem of round-bounded $ML(\exists_{SO}^k)$ is $(k+1)AEXP_{POLY}$ -complete. The SAT problem of $ML(\exists_{SO}^k)$ is $kAEXP_{POLY}$ -complete for formulae of modal depth $\leq k$.

$kAEXP_{POLY}$: class of problems decidable with an alternating Turing machine running in $kEXPTIME$ and performing polynomially many alternations.

Examples:

- Team logic is $AEXP_{POLY}$ -complete
- Presburger arithmetic is $2AEXP_{POLY}$ -complete.

Depth of interaction via the round-bounded fragment

Syntactic fragment of $ML(\exists^k)$ (for both FO and SO) such that

$$ML(\exists^{j+2}) \xrightarrow{\diamond} ML(\exists^{j+1})$$

$$ML(\exists^1) \xrightarrow{\diamond} ML(\exists^k)$$

Theorem

The SAT problem of round-bounded $ML(\exists_{SO}^k)$ is $(k+1)AEXP_{POLY}$ -complete. The SAT problem of $ML(\exists_{SO}^k)$ is $kAEXP_{POLY}$ -complete for formulae of modal depth $\leq k$.

Corollary (1)

$ML(\exists_{FO}^1)$ and $ML(\exists_{SO}^1)$ are $2NEXP_{TIME}$ -comp. and $2AEXP_{POLY}$ -comp., respectively.

recall: $ML(\exists_{FO}^2)$ and $ML(\exists_{SO}^2)$ are TOWER-complete.

Depth of interaction via the round-bounded fragment

Syntactic fragment of $ML(\exists^k)$ (for both FO and SO) such that

$$ML(\exists^{j+2}) \xrightarrow{\diamond} ML(\exists^{j+1})$$

$$ML(\exists^1) \xrightarrow{\diamond} ML(\exists^k)$$

Theorem

The SAT problem of round-bounded $ML(\exists_{SO}^k)$ is $(k+1)AEXP_{POLY}$ -complete. The SAT problem of $ML(\exists_{SO}^k)$ is $kAEXP_{POLY}$ -complete for formulae of modal depth $\leq k$.

Corollary (2)

Quantified S5 [Fine, '70] is $AEXP_{POLY}$ -comp.; Hybrid logic on trees is TOWER-comp.

Depth of interaction via the round-bounded fragment

Syntactic fragment of $ML(\exists^k)$ (for both FO and SO) such that

$$ML(\exists^{j+2}) \xrightarrow{\Diamond} ML(\exists^{j+1})$$

$$ML(\exists^1) \xrightarrow{\Diamond} ML(\exists^k)$$

Theorem

The SAT problem of round-bounded $ML(\exists_{SO}^k)$ is $(k+1)AEXP_{POLY}$ -complete. The SAT problem of $ML(\exists_{SO}^k)$ is $kAEXP_{POLY}$ -complete for formulae of modal depth $\leq k$.

Corollary (3)

QML is as expressive as graded modal logic (under both FO and SO semantics).

graded modal logic = $ML + \Diamond_{\geq j}$

Upper bounds

Input: A formula φ from $\text{ML}(\exists_{SO}^k)$.

Output: A graded modal logic formula ψ equivalent to φ .

Upper bounds

Input: A formula φ from $\text{ML}(\exists_{SO}^k)$.

Output: A graded modal logic formula ψ equivalent to φ .

A quantifier-elimination procedure:

From $\exists p : \varphi_{\text{QF}}$ we want to produce an equivalent ψ_{QF} .

Upper bounds

Input: A formula φ from $\text{ML}(\exists_{SO}^k)$.

Output: A graded modal logic formula ψ equivalent to φ .

A relaxed quantifier-elimination procedure:

- Given $\exists^1 p : \varphi_{\text{GML}}$ we produce an equivalent ψ_{GML} .
- Given $\exists^k p : \varphi$ with φ in $\text{ML}(\exists_{SO}^{k-1})$ we obtain an equivalent formula in $\text{ML}(\exists_{SO}^{k-1})$.

Upper bounds

Input: A formula φ from $\text{ML}(\exists_{SO}^k)$.

Output: A graded modal logic formula ψ equivalent to φ .

A **relaxed** quantifier-elimination procedure:

- Given $\exists^1 p : \varphi_{\text{GML}}$ we produce an equivalent ψ_{GML} .
- Given $\exists^k p : \varphi$ with φ in $\text{ML}(\exists_{SO}^{k-1})$ we obtain an equivalent formula in $\text{ML}(\exists_{SO}^{k-1})$.

Complexity remarks:

- at each step, the formula becomes exponentially larger...
- for round-bounded formulae these explosions do not propagate between “rounds”.

Lower bounds

Proposition (Bednarczyk and Demri, LICS'19)

Let $k \geq 1$. There is a formula $\text{type}(k, n)$ of QML (second-order semantics) that is satisfied only by worlds with $t(k, n) \stackrel{\text{def}}{=} \underbrace{2^{2 \dots 2^n}}_k$ many children. It has size exponential in k .

Lower bounds

Proposition (Bednarczyk and Demri, LICS'19) **round-bounded ML**(\exists_{FO}^k)

Let $k \geq 1$. There is a formula $\text{type}(k, n)$ of ~~QML (second-order semantics)~~ that is satisfied only by worlds with $t(k, n) \stackrel{\text{def}}{=} \underbrace{2^{2 \dots 2^n}}_k$ many children. It has size exponential in k .

Lower bounds

Proposition (Bednarczyk and Demri, LICS'19) **round-bounded ML**(\exists_{FO}^k)

Let $k \geq 1$. There is a formula $\text{type}(k, n)$ of ~~QML (second-order semantics)~~ that is satisfied only by worlds with $t(k, n) \stackrel{\text{def}}{=} \underbrace{2^{2 \dots 2^n}}_k$ many children. It has size ~~exponential~~ in k . **polynomial**

Lower bounds

Proposition (Bednarczyk and Demri, LICS'19) **round-bounded ML**(\exists_{FO}^k)

Let $k \geq 1$. There is a formula $\text{type}(k, n)$ of ~~QML (second-order semantics)~~ that is satisfied only by worlds with ~~$t(k, n) \stackrel{\text{def}}{=} 2^{2 \dots 2^n}$~~ many children. It has size ~~exponential~~ in k .
 $t(k+1, n)$ $\underbrace{2^{2 \dots 2^n}}_k$ **polynomial**

Lower bounds

Proposition (Bednarczyk and Demri, LICS'19) **round-bounded ML** (\exists_{FO}^k)

Let $k \geq 1$. There is a formula $\text{type}(k, n)$ of ~~QML (second-order semantics)~~ that is satisfied only by worlds with ~~$t(k, n) \stackrel{\text{def}}{=} 2^{2 \dots 2^n}$~~ many children. It has size ~~exponential~~ in k .
 $t(k+1, n)$ $\underbrace{2^{2 \dots 2^n}}_k$ **polynomial**

Funny stuff: improvements are based on encoding ripple-carry adders as formulae and leverage a trick by Fisher and Rabin [SIAM-AMS'74] to compress the formula further.

Lower bounds (extra)

Encoding numbers in the Kripke structure: $\mathfrak{M}, w \models \text{type}(k, n)$ implies

- w has $t(k, n)$ children, all encoding a distinct number in $[0, t(k, n) - 1]$
- using its children as indices, w encodes a number $\mathbf{n}_k(w) \in [0, t(k + 1, n) - 1]$.

In a nutshell, this is done thanks to formulae that express

$$\mathbf{n}_j(x) < \mathbf{n}_j(y) \quad \text{and} \quad \mathbf{n}_j(x) + 1 = \mathbf{n}_j(y), \quad j \in [1, k].$$

Lower bounds (extra)

Encoding numbers in the Kripke structure: $\mathfrak{M}, w \models \text{type}(k, n)$ implies

- w has $t(k, n)$ children, all encoding a distinct number in $[0, t(k, n) - 1]$
- using its children as indices, w encodes a number $\mathbf{n}_k(w) \in [0, t(k + 1, n) - 1]$.

In a nutshell, this is done thanks to formulae that express

$$\mathbf{n}_j(x) < \mathbf{n}_j(y) \quad \text{and} \quad \mathbf{n}_j(x) + 1 = \mathbf{n}_j(y), \quad j \in [1, k].$$

Issue: $\mathbf{n}_{j+1}(x) < \mathbf{n}_{j+1}(y)$ and $\mathbf{n}_{j+1}(x) + 1 = \mathbf{n}_{j+1}(y)$ are defined using several times $\mathbf{n}_j(x) < \mathbf{n}_j(y)$ and $\mathbf{n}_j(x) + 1 = \mathbf{n}_j(y)$ and their negation (\Rightarrow exponential blowup in j)

Lower bounds (extra)

Solution:

- to subsume both $n_j(x) < n_j(y)$ and $n_j(x)+1 = n_j(y)$ with a **single formula**...
- ...whose negation can be expressed in terms of positive occurrences of itself

Lower bounds (extra)

Solution:

- to subsume both $n_j(x) < n_j(y)$ and $n_j(x)+1 = n_j(y)$ with a **single formula**...
- ...whose negation can be expressed in terms of positive occurrences of itself

Why is this enough? We can use the Fisher and Rabin trick!

$$\varphi(\mathbf{x}) \wedge \varphi(\mathbf{y}) \equiv \forall \mathbf{z} : (\mathbf{z} = \mathbf{x} \vee \mathbf{z} = \mathbf{y}) \Rightarrow \varphi(\mathbf{z})$$

(this trick can be extended to Boolean combinations of positive occurrences of φ)

Lower bounds (extra)

Solution **Ripple-carry adders!**

- $t_j(x, y, z, c)$ that holds whenever ...
- - $n_j(x) + n_j(y) = n_j(z)$ and
 - $n_j(c)$ is the sequence of carries obtained when performing $n_j(x) + n_j(y)$ in binary, on $t(j, n)$ many bits.

Why

$$\varphi(\mathbf{x}) \wedge \varphi(\mathbf{y}) \equiv \forall \mathbf{z} : (\mathbf{z} = \mathbf{x} \vee \mathbf{z} = \mathbf{y}) \Rightarrow \varphi(\mathbf{z})$$

(this trick can be extended to Boolean combinations of positive occurrences of φ)

Lower bounds (extra)

Solution **Ripple-carry adders!**

- $t_j(x, y, z, c)$ that holds whenever ...
- - $n_j(x) + n_j(y) = n_j(z)$ and
 - $n_j(c)$ is the sequence of carries obtained when performing $n_j(x) + n_j(y)$ in binary, on $t(j, n)$ many bits.

Why

$$n_j(x) < n_j(z) \equiv \exists y, c : +_j(x, y, z, c)$$

(this t

Lower bounds (extra)

Solution **Ripple-carry adders!**

- $t_j(x, y, z, c)$ that holds whenever ...
- - $n_j(x) + n_j(y) = n_j(z)$ and
 - $n_j(c)$ is the sequence of carries obtained when performing $n_j(x) + n_j(y)$ in binary, on $t(j, n)$ many bits.

Why

$$n_j(x) + 1 = n_j(z) \equiv \exists y, c : +_j(x, y, z, c) \wedge n_j(y) = 1$$

(this t

Lower bounds (extra)

Solution **Ripple-carry adders!**

- $+_j(x, y, z, c)$ that holds whenever
- - $\mathbf{n}_j(x) + \mathbf{n}_j(y) = \mathbf{n}_j(z)$ and
 - $\mathbf{n}_j(c)$ is the sequence of carries obtained when performing $\mathbf{n}_j(x) + \mathbf{n}_j(y)$ in binary, on $t(j, n)$ many bits.

Why

the negation of $+_j(x, y, z, c)$ can be expressed as

(this is

$(\exists w, d : +_j(x, y, w, d) \wedge (\mathbf{n}_j(w) \neq \mathbf{n}_j(z) \vee \mathbf{n}_j(d) \neq \mathbf{n}_j(c))) \vee (\text{overflow})$

Conclusion

In the paper:

- we introduce a hierarchy for QML formulae that depend on the “depth of interaction” of quantifiers
- we characterise the complexity of each level of the hierarchy, for both FO and SO
- we characterise the expressive power of QML.

Conclusion

In the paper:

- we introduce a hierarchy for QML formulae that depend on the “depth of interaction” of quantifiers
- we characterise the complexity of each level of the hierarchy, for both FO and SO
- we characterise the expressive power of QML.

This allows us to connect QML with other logics, w.r.t. the right level of the hierarchy.

One exception: Ambient logic is $\text{AEXP}_{\text{POLY}}$ -comp., but $\text{ML}(\exists^1_{\text{SO}})$ is $2\text{AEXP}_{\text{POLY}}$ -comp.