

# Operads, Equivariance, and Pseudo-Commutativity

Alex Corner | Nick Gurski

Sheffield Hallam University | Case Western Reserve University



Slides: [alex-corner.github.io/slides/corner-pssl110.pdf](https://alex-corner.github.io/slides/corner-pssl110.pdf)

# Operads

## Data

$$n \in \mathbb{N} = \{0, 1, 2, \dots\}$$

- sets  $P(n)$  - thought of as ' $n$ -ary operations'
- functions - 'composition' or 'multiplication'

$$\mu^P: P(n) \times P(k_1) \times \dots \times P(k_n) \rightarrow P(k_1 + \dots + k_n)$$

- identity element  $e \in P(1)$

# Operads

## Data

$$n \in \mathbb{N} = \{0, 1, 2, \dots\}$$

- sets  $P(n)$  - thought of as ' $n$ -ary operations'
- functions - 'composition' or 'multiplication'

$$\mu^P: P(n) \times P(k_1) \times \dots \times P(k_n) \rightarrow P(k_1 + \dots + k_n)$$

- identity element  $e \in P(1)$

## Axioms


- multiplication:

$$\begin{aligned} \mu(\mu(p; q_1, \dots, q_n); r_{11}, \dots, r_{1k_1}, \dots, r_{n1}, \dots, r_{nk_n}) \\ = \\ \mu(p; \mu(q_1; r_{11}, \dots, r_{1k_1}), \dots, \mu(q_n; r_{n1}, \dots, r_{nk_n})) \end{aligned}$$


- identity:

$$\mu(p; e, \dots, e) = p = \mu(e; p)$$


## Composition Axiom



## Composition Axiom



## Composition Axiom



## Operads

### Data

$$n \in \mathbb{N} = \{0, 1, 2, \dots\}$$

- sets  $P(n)$  - thought of as ' $n$ -ary operations'
- functions - 'composition' or 'multiplication'

$$\mu^P: P(n) \times P(k_1) \times \dots \times P(k_n) \rightarrow P(k_1 + \dots + k_n)$$

- identity element  $e \in P(1)$

### Axioms

- multiplication:

$$\begin{aligned} \mu(\mu(p; q_1, \dots, q_n); r_{11}, \dots, r_{1k_1}, \dots, r_{n1}, \dots, r_{nk_n}) \\ = \\ \mu(p; \mu(q_1; r_{11}, \dots, r_{1k_1}), \dots, \mu(q_n; r_{n1}, \dots, r_{nk_n})) \end{aligned}$$

- identity:

$$\mu(p; e, \dots, e) = p = \mu(e; p)$$

## Operads - Symmetric Actions

### Idea

- elements of  $P(n)$  are  $n$ -ary operations:



## Operads

### Data

$$n \in \mathbb{N} = \{0, 1, 2, \dots\}$$

- sets  $P(n)$  - thought of as ' $n$ -ary operations'
- functions - 'composition' or 'multiplication'

$$\mu^P: P(n) \times P(k_1) \times \dots \times P(k_n) \rightarrow P(k_1 + \dots + k_n)$$

- identity element  $e \in P(1)$

### Axioms

- multiplication:

$$\begin{aligned} \mu(\mu(p; q_1, \dots, q_n); r_{11}, \dots, r_{1k_1}, \dots, r_{n1}, \dots, r_{nk_n}) \\ = \\ \mu(p; \mu(q_1; r_{11}, \dots, r_{1k_1}), \dots, \mu(q_n; r_{n1}, \dots, r_{nk_n})) \end{aligned}$$


- identity:

$$\mu(p; e, \dots, e) = p = \mu(e; p)$$

## Operads - Symmetric Actions

### Idea

- elements of  $P(n)$  are  $n$ -ary operations:



### Symmetric Operads

- for each  $n \in \mathbb{N}$ , an action:

$$P(n) \times \Sigma_n \rightarrow P(n)$$

- satisfying:

$$\mu(p \cdot g; q_1, \dots, q_n) = \mu(p; q_{g^{-1}(1)}, \dots, q_{g^{-1}(n)}) \cdot \delta(g)$$

$$\mu(p; q_1 \cdot g_1, \dots, q_n \cdot g_n) = \mu(p; q_1, \dots, q_n) \cdot \beta(g_1, \dots, g_n)$$



## Operads

### Data

$$n \in \mathbb{N} = \{0, 1, 2, \dots\}$$

- sets  $P(n)$  - thought of as ' $n$ -ary operations'
- functions - 'composition' or 'multiplication'

$$\mu^P: P(n) \times P(k_1) \times \dots \times P(k_n) \rightarrow P(k_1 + \dots + k_n)$$

- identity element  $e \in P(1)$

### Axioms

- multiplication:

$$\begin{aligned} \mu(\mu(p; q_1, \dots, q_n); r_{11}, \dots, r_{1k_1}, \dots, r_{n1}, \dots, r_{nk_n}) \\ = \\ \mu(p; \mu(q_1; r_{11}, \dots, r_{1k_1}), \dots, \mu(q_n; r_{n1}, \dots, r_{nk_n})) \end{aligned}$$


- identity:

$$\mu(p; e, \dots, e) = p = \mu(e; p)$$

## Operads - Symmetric Actions

### Idea

- elements of  $P(n)$  are  $n$ -ary operations:



### Symmetric Operads

- for each  $n \in \mathbb{N}$ , an action:

$$P(n) \times \Sigma_n \rightarrow P(n)$$

- satisfying:

$$\mu(p \cdot g; q_1, \dots, q_n) = \mu(p; q_{g^{-1}(1)}, \dots, q_{g^{-1}(n)}) \cdot \delta(g)$$

$$\mu(p; q_1 \cdot g_1, \dots, q_n \cdot g_n) = \mu(p; q_1, \dots, q_n) \cdot \beta(g_1, \dots, g_n)$$

### Plain Operads

- for each  $n \in \mathbb{N}$ , a trivial action:

$$P(n) \times 1 \rightarrow P(n)$$

## Operads - Symmetry Groups


### Symmetry Groups

- sets:  $P(n) = \Sigma_n$

## Operads - Symmetric Actions

### Idea

- elements of  $P(n)$  are  $n$ -ary operations:



### Symmetric Operads

- for each  $n \in \mathbb{N}$ , an action:

$$P(n) \times \Sigma_n \rightarrow P(n)$$

- satisfying:

$$\mu(p \cdot g; q_1, \dots, q_n) = \mu(p; q_{g^{-1}(1)}, \dots, q_{g^{-1}(n)}) \cdot \delta(g)$$

$$\mu(p; q_1 \cdot g_1, \dots, q_n \cdot g_n) = \mu(p; q_1, \dots, q_n) \cdot \beta(g_1, \dots, g_n)$$

### Plain Operads

- for each  $n \in \mathbb{N}$ , a trivial action:

$$P(n) \times 1 \rightarrow P(n)$$

## Operads - Symmetry Groups

### Symmetry Groups

- sets:  $P(n) = \Sigma_n$
- composition:


$\Sigma_3$



## Operads - Symmetric Actions

### Idea

- elements of  $P(n)$  are  $n$ -ary operations:



### Symmetric Operads

- for each  $n \in \mathbb{N}$ , an action:

$$P(n) \times \Sigma_n \rightarrow P(n)$$

- satisfying:

$$\mu(p \cdot g; q_1, \dots, q_n) = \mu(p; q_{g^{-1}(1)}, \dots, q_{g^{-1}(n)}) \cdot \delta(g)$$

$$\mu(p; q_1 \cdot g_1, \dots, q_n \cdot g_n) = \mu(p; q_1, \dots, q_n) \cdot \beta(g_1, \dots, g_n)$$

### Plain Operads

- for each  $n \in \mathbb{N}$ , a trivial action:

$$P(n) \times 1 \rightarrow P(n)$$

## Operads - Symmetry Groups

### Symmetry Groups

- sets:  $P(n) = \Sigma_n$
- composition:




$\Sigma_6$

## Operads - Symmetric Actions

### Idea

- elements of  $P(n)$  are  $n$ -ary operations:



### Symmetric Operads

- for each  $n \in \mathbb{N}$ , an action:

$$P(n) \times \Sigma_n \rightarrow P(n)$$

- satisfying:

$$\mu(p \cdot g; q_1, \dots, q_n) = \mu(p; q_{g^{-1}(1)}, \dots, q_{g^{-1}(n)}) \cdot \delta(g)$$

$$\mu(p; q_1 \cdot g_1, \dots, q_n \cdot g_n) = \mu(p; q_1, \dots, q_n) \cdot \beta(g_1, \dots, g_n)$$

### Plain Operads


- for each  $n \in \mathbb{N}$ , a trivial action:

$$P(n) \times 1 \rightarrow P(n)$$

## Operads - Symmetry Groups

### Symmetry Groups


- sets:  $P(n) = \Sigma_n$
- composition:



## Operads - Symmetric Actions

### Idea

- elements of  $P(n)$  are  $n$ -ary operations:



### Symmetric Operads

- for each  $n \in \mathbb{N}$ , an action:

$$P(n) \times \Sigma_n \rightarrow P(n)$$

- satisfying:

$$\mu(p \cdot g; q_1, \dots, q_n) = \mu(p; q_{g^{-1}(1)}, \dots, q_{g^{-1}(n)}) \cdot \delta(g)$$

$$\mu(p; q_1 \cdot g_1, \dots, q_n \cdot g_n) = \mu(p; q_1, \dots, q_n) \cdot \beta(g_1, \dots, g_n)$$

### Plain Operads


- for each  $n \in \mathbb{N}$ , a trivial action:

$$P(n) \times 1 \rightarrow P(n)$$

## Operads - Symmetry Groups

### Symmetry Groups

- sets:  $P(n) = \Sigma_n$
- composition:



### Block Sum

$$\beta(p_1, \dots, p_n) = \mu(e_n; p_1, \dots, p_n)$$

### Extension

$$\delta(p) = \mu(p; e_{k_1}, \dots, e_{k_n})$$

## Operads - Symmetric Actions

### Idea

- elements of  $P(n)$  are  $n$ -ary operations:



### Symmetric Operads

- for each  $n \in \mathbb{N}$ , an action:

$$P(n) \times \Sigma_n \rightarrow P(n)$$

- satisfying:

$$\mu(p \cdot g; q_1, \dots, q_n) = \mu(p; q_{g^{-1}(1)}, \dots, q_{g^{-1}(n)}) \cdot \delta(g)$$

$$\mu(p; q_1 \cdot g_1, \dots, q_n \cdot g_n) = \mu(p; q_1, \dots, q_n) \cdot \beta(g_1, \dots, g_n)$$

### Plain Operads


- for each  $n \in \mathbb{N}$ , a trivial action:

$$P(n) \times 1 \rightarrow P(n)$$

## Operads - Symmetry Groups

### Symmetry Groups

- sets:  $P(n) = \Sigma_n$
- composition:



Block Sum

$$\beta(p_1, \dots, p_n) = \mu(e_n; p_1, \dots, p_n)$$

Extension

$$\delta(p) = \mu(p; e_{k_1}, \dots, e_{k_n})$$

## Action Operads

Data


$$n \in \mathbb{N} = \{0, 1, 2, \dots\}$$

- **groups**  $\Lambda(n)$
- plain operad structure  $(\mu, e)$
- group homomorphisms  $\pi_n: \Lambda(n) \rightarrow \Sigma_n$

## Operads - Symmetry Groups

### Symmetry Groups

- sets:  $P(n) = \Sigma_n$
- composition:



Block Sum

$$\beta(p_1, \dots, p_n) = \mu(e_n; p_1, \dots, p_n)$$

Extension

$$\delta(p) = \mu(p; e_{k_1}, \dots, e_{k_n})$$

## Action Operads

Data

$$n \in \mathbb{N} = \{0, 1, 2, \dots\}$$

- **groups**  $\Lambda(n)$
- plain operad structure  $(\mu, e)$
- group homomorphisms  $\pi_n: \Lambda(n) \rightarrow \Sigma_n$

Equivariance Axiom


$$\begin{aligned} \mu(g'; h'_1, \dots, h'_n) \cdot \mu(g; h_1, \dots, h_n) \\ = \\ \mu(g' \cdot g; h'_{g(1)} \cdot h_1, \dots, h'_{g(n)} \cdot h_n) \end{aligned}$$



## Operads - Symmetry Groups

### Symmetry Groups

- sets:  $P(n) = \Sigma_n$
- composition:



Block Sum

$$\beta(p_1, \dots, p_n) = \mu(e_n; p_1, \dots, p_n)$$

Extension

$$\delta(p) = \mu(p; e_{k_1}, \dots, e_{k_n})$$

## Action Operads

Data

$$n \in \mathbb{N} = \{0, 1, 2, \dots\}$$

- **groups**  $\Lambda(n)$
- plain operad structure  $(\mu, e)$
- group homomorphisms  $\pi_n: \Lambda(n) \rightarrow \Sigma_n$

Equivariance Axiom

$$\begin{aligned} \mu(g'; h'_1, \dots, h'_n) \cdot \mu(g; h_1, \dots, h_n) \\ = \\ \mu(g' \cdot g; h'_{g(1)} \cdot h_1, \dots, h'_{g(n)} \cdot h_n) \end{aligned}$$

Symmetric Groups

- $\Lambda(n) = \Sigma_n$
- operad structure:  $\beta$  and  $\delta$ ,  $e_1 = (1) \in \Sigma_1$
- $\pi_n$  is the identity
- equivariance follows from symmetric equivariance

## Action Operads - Examples

### Examples

- $\Sigma$ :  $\Sigma_n$ , symmetric groups
- $T$ : 1, trivial groups
- $B$ :  $B_n$ , braid groups
- $RB$ :  $RB_n$ , ribbon braid groups
- $J$ :  $J_n$ , cactus groups

## Action Operads

### Data

$$n \in \mathbb{N} = \{0, 1, 2, \dots\}$$

- **groups**  $\Lambda(n)$
- plain operad structure  $(\mu, e)$
- group homomorphisms  $\pi_n: \Lambda(n) \rightarrow \Sigma_n$

### Equivariance Axiom

$$\begin{aligned} \mu(g'; h'_1, \dots, h'_n) \cdot \mu(g; h_1, \dots, h_n) \\ = \\ \mu(g' \cdot g; h'_{g(1)} \cdot h_1, \dots, h'_{g(n)} \cdot h_n) \end{aligned}$$

### Symmetric Groups

- $\Lambda(n) = \Sigma_n$
- operad structure:  $\beta$  and  $\delta$ ,  $e_1 = (1) \in \Sigma_1$
- $\pi_n$  is the identity
- equivariance follows from symmetric equivariance

## Action Operads - Examples

### Examples

- $\Sigma$ :  $\Sigma_n$ , symmetric groups
- $T$ : 1, trivial groups
- $B$ :  $B_n$ , braid groups
- $RB$ :  $RB_n$ , ribbon braid groups
- $J$ :  $J_n$ , cactus groups



## Action Operads

### Data

$$n \in \mathbb{N} = \{0, 1, 2, \dots\}$$

- **groups**  $\Lambda(n)$
- plain operad structure  $(\mu, e)$
- group homomorphisms  $\pi_n: \Lambda(n) \rightarrow \Sigma_n$

### Equivariance Axiom

$$\begin{aligned} \mu(g'; h'_1, \dots, h'_n) \cdot \mu(g; h_1, \dots, h_n) \\ = \\ \mu(g' \cdot g; h'_{g(1)} \cdot h_1, \dots, h'_{g(n)} \cdot h_n) \end{aligned}$$

### Symmetric Groups

- $\Lambda(n) = \Sigma_n$
- operad structure:  $\beta$  and  $\delta$ ,  $e_1 = (1) \in \Sigma_1$
- $\pi_n$  is the identity
- equivariance follows from symmetric equivariance

## Action Operads - Examples

### Examples

- $\Sigma$ :  $\Sigma_n$ , symmetric groups
  - $T$ : 1, trivial groups
  - $B$ :  $B_n$ , braid groups
  - $RB$ :  $RB_n$ , ribbon braid groups
  - $J$ :  $J_n$ , cactus groups
- Fiedorowicz/Salvatore
- Wahl/Zhang
- Henriques-Kamnitzer



## Action Operads

### Data

$$n \in \mathbb{N} = \{0, 1, 2, \dots\}$$

- **groups**  $\Lambda(n)$
- plain operad structure  $(\mu, e)$
- group homomorphisms  $\pi_n: \Lambda(n) \rightarrow \Sigma_n$

### Equivariance Axiom

$$\begin{aligned} \mu(g'; h'_1, \dots, h'_n) \cdot \mu(g; h_1, \dots, h_n) \\ = \\ \mu(g' \cdot g; h'_{g(1)} \cdot h_1, \dots, h'_{g(n)} \cdot h_n) \end{aligned}$$

### Symmetric Groups

- $\Lambda(n) = \Sigma_n$
- operad structure:  $\beta$  and  $\delta$ ,  $e_1 = (1) \in \Sigma_1$
- $\pi_n$  is the identity
- equivariance follows from symmetric equivariance

## Action Operads - Examples

### Examples

- $\Sigma$ :  $\Sigma_n$ , symmetric groups
- $T$ : 1, trivial groups
- $B$ :  $B_n$ , braid groups Fiedorowicz/Salvatore
- $RB$ :  $RB_n$ , ribbon braid groups Wahl/Zhang
- $J$ :  $J_n$ , cactus groups Henriques-Kamnitzer



### Non-Examples

- $A$ :  $A_n$ , alternating groups
- $H$ :  $H_n$ , hyperoctahedral groups
- $C$ :  $C_n$ , cyclic groups
- $R$ :  $C_2$ ,  $\pi_n$  order-reversing Fiedorowicz-Loday
- Most skew-simplicial groups, despite similarities.

## Action Operads

### Data

$$n \in \mathbb{N} = \{0, 1, 2, \dots\}$$

- **groups**  $\Lambda(n)$
- plain operad structure  $(\mu, e)$
- group homomorphisms  $\pi_n: \Lambda(n) \rightarrow \Sigma_n$

### Equivariance Axiom

$$\begin{aligned} \mu(g'; h'_1, \dots, h'_n) \cdot \mu(g; h_1, \dots, h_n) \\ = \\ \mu(g' \cdot g; h'_{g(1)} \cdot h_1, \dots, h'_{g(n)} \cdot h_n) \end{aligned}$$

### Symmetric Groups

- $\Lambda(n) = \Sigma_n$
- operad structure:  $\beta$  and  $\delta$ ,  $e_1 = (1) \in \Sigma_1$
- $\pi_n$  is the identity
- equivariance follows from symmetric equivariance

## Action Operads - Examples

### Examples

- $\Sigma$ :  $\Sigma_n$ , symmetric groups
- $T$ : 1, trivial groups
- $B$ :  $B_n$ , braid groups Fiedorowicz/Salvatore
- $RB$ :  $RB_n$ , ribbon braid groups Wahl/Zhang
- $J$ :  $J_n$ , cactus groups Henriques-Kamnitzer



### Non-Examples

- $A$ :  $A_n$ , alternating groups
- $H$ :  $H_n$ , hyperoctahedral groups
- $C$ :  $C_n$ , cyclic groups
- $R$ :  $C_2, \pi_n$  order-reversing Fiedorowicz-Loday
- Most skew-simplicial groups, despite similarities.

## $\Lambda$ -Operads

### Data

- an action operad  $\Lambda$
- an operad  $P$
- actions  $P(n) \times \Lambda(n) \rightarrow P(n)$
- satisfying:

## Action Operads - Examples

### Examples

- $\Sigma$ :  $\Sigma_n$ , symmetric groups
- $T$ : 1, trivial groups
- $B$ :  $B_n$ , braid groups Fiedorowicz/Salvatore
- $RB$ :  $RB_n$ , ribbon braid groups Wahl/Zhang
- $J$ :  $J_n$ , cactus groups Henriques-Kamnitzer



### Non-Examples

- $A$ :  $A_n$ , alternating groups
- $H$ :  $H_n$ , hyperoctahedral groups
- $C$ :  $C_n$ , cyclic groups
- $R$ :  $C_2$ ,  $\pi_n$  order-reversing Fiedorowicz-Loday
- Most skew-simplicial groups, despite similarities.

## $\Lambda$ -Operads

### Data

- an action operad  $\Lambda$
- an operad  $P$
- actions  $P(n) \times \Lambda(n) \rightarrow P(n)$
- satisfying:

$$\mu^P(p \cdot g; q_1, \dots, q_n) = \mu^P(p; q_{g^{-1}(1)}, \dots, q_{g^{-1}(n)}) \cdot \delta^\Lambda(g)$$

$$\mu^P(p; q_1 \cdot g_1, \dots, q_n \cdot g_n) = \mu^P(p; q_1, \dots, q_n) \cdot \beta^\Lambda(g_1, \dots, g_n)$$

## Action Operads - Examples

### Examples

- $\Sigma$ :  $\Sigma_n$ , symmetric groups
- $T$ : 1, trivial groups
- $B$ :  $B_n$ , braid groups Fiedorowicz/Salvatore
- $RB$ :  $RB_n$ , ribbon braid groups Wahl/Zhang
- $J$ :  $J_n$ , cactus groups Henriques-Kamnitzer



### Non-Examples

- $A$ :  $A_n$ , alternating groups
- $H$ :  $H_n$ , hyperoctahedral groups
- $C$ :  $C_n$ , cyclic groups
- $R$ :  $C_2$ ,  $\pi_n$  order-reversing Fiedorowicz-Loday
- Most skew-simplicial groups, despite similarities.

## $\Lambda$ -Operads

### Data

- an action operad  $\Lambda$
- an operad  $P$
- actions  $P(n) \times \Lambda(n) \rightarrow P(n)$
- satisfying:

$$\mu^P(p \cdot g; q_1, \dots, q_n) = \mu^P(p; q_{g^{-1}(1)}, \dots, q_{g^{-1}(n)}) \cdot \delta^\Lambda(g)$$

$$\mu^P(p; q_1 \cdot g_1, \dots, q_n \cdot g_n) = \mu^P(p; q_1, \dots, q_n) \cdot \beta^\Lambda(g_1, \dots, g_n)$$

### Monads

- each  $\Lambda$ -operad  $P$  induces a monad  $\underline{P}$  on **Set**:

$$\underline{P}(X) = \coprod_{n \in \mathbb{N}} (P(n) \times_{\Lambda_n} X^n)$$



## Action Operads - Examples

### Examples

- $\Sigma$ :  $\Sigma_n$ , symmetric groups
- $T$ : 1, trivial groups
- $B$ :  $B_n$ , braid groups Fiedorowicz/Salvatore
- $RB$ :  $RB_n$ , ribbon braid groups Wahl/Zhang
- $J$ :  $J_n$ , cactus groups Henriques-Kamnitzer



### Non-Examples

- $A$ :  $A_n$ , alternating groups
- $H$ :  $H_n$ , hyperoctahedral groups
- $C$ :  $C_n$ , cyclic groups
- $R$ :  $C_2$ ,  $\pi_n$  order-reversing Fiedorowicz-Loday
- Most skew-simplicial groups, despite similarities.

## $\Lambda$ -Operads

### Data

- an action operad  $\Lambda$
- an operad  $P$
- actions  $P(n) \times \Lambda(n) \rightarrow P(n)$
- satisfying:

$$\mu^P(p \cdot g; q_1, \dots, q_n) = \mu^P(p; q_{g^{-1}(1)}, \dots, q_{g^{-1}(n)}) \cdot \delta^\Lambda(g)$$

$$\mu^P(p; q_1 \cdot g_1, \dots, q_n \cdot g_n) = \mu^P(p; q_1, \dots, q_n) \cdot \beta^\Lambda(g_1, \dots, g_n)$$

### Monads

- each  $\Lambda$ -operad  $P$  induces a monad  $\underline{P}$  on **Set**:

$$\underline{P}(X) = \coprod_{n \in \mathbb{N}} (P(n) \times_{\Lambda_n} X^n)$$

- each  $P(n) \times_{\Lambda_n} X^n$  is a coequalizer:

$$(p \cdot g; x_1, \dots, x_n) \sim (p; x_{g^{-1}(1)}, \dots, x_{g^{-1}(n)})$$

## Action Operads - Examples

### Examples

- $\Sigma$ :  $\Sigma_n$ , symmetric groups
- $T$ : 1, trivial groups
- $B$ :  $B_n$ , braid groups Fiedorowicz/Salvatore
- $RB$ :  $RB_n$ , ribbon braid groups Wahl/Zhang
- $J$ :  $J_n$ , cactus groups Henriques-Kamnitzer



### Non-Examples

- $A$ :  $A_n$ , alternating groups
- $H$ :  $H_n$ , hyperoctahedral groups
- $C$ :  $C_n$ , cyclic groups
- $R$ :  $C_2$ ,  $\pi_n$  order-reversing Fiedorowicz-Loday
- Most skew-simplicial groups, despite similarities.

## $\Lambda$ -Operads

### Data

- an action operad  $\Lambda$
- an operad  $P$
- actions  $P(n) \times \Lambda(n) \rightarrow P(n)$
- satisfying:

$$\mu^P(p \cdot g; q_1, \dots, q_n) = \mu^P(p; q_{g^{-1}(1)}, \dots, q_{g^{-1}(n)}) \cdot \delta^\Lambda(g)$$

$$\mu^P(p; q_1 \cdot g_1, \dots, q_n \cdot g_n) = \mu^P(p; q_1, \dots, q_n) \cdot \beta^\Lambda(g_1, \dots, g_n)$$

### Monads

- each  $\Lambda$ -operad  $P$  induces a monad  $\underline{P}$  on **Set**:

$$\underline{P}(X) = \coprod_{n \in \mathbb{N}} (P(n) \times_{\Lambda_n} X^n)$$

- each  $P(n) \times_{\Lambda_n} X^n$  is a coequalizer:

$$(p \cdot g; x_1, \dots, x_n) \sim (p; x_{g^{-1}(1)}, \dots, x_{g^{-1}(n)})$$

- we investigate  $\Lambda$ -operads in **Cat**: 2-monads

## Commutative Monads

- $T: \mathcal{C} \rightarrow \mathcal{C}$  a monad
- a **strength** is a natural transformation + axioms

$$t_{X,Y}: X \otimes TY \rightarrow T(X \otimes Y)$$

- a **costrength** is a natural transformation + axioms

$$t_{X,Y}^*: TX \otimes Y \rightarrow T(X \otimes Y)$$

## $\Lambda$ -Operads

### Data

- an action operad  $\Lambda$
- an operad  $P$
- actions  $P(n) \times \Lambda(n) \rightarrow P(n)$
- satisfying:

$$\mu^P(p \cdot g; q_1, \dots, q_n) = \mu^P(p; q_{g^{-1}(1)}, \dots, q_{g^{-1}(n)}) \cdot \delta^\Lambda(g)$$

$$\mu^P(p; q_1 \cdot g_1, \dots, q_n \cdot g_n) = \mu^P(p; q_1, \dots, q_n) \cdot \beta^\Lambda(g_1, \dots, g_n)$$

### Monads

- each  $\Lambda$ -operad  $P$  induces a monad  $\underline{P}$  on **Set**:

$$\underline{P}(X) = \coprod_{n \in \mathbb{N}} (P(n) \times_{\Lambda_n} X^n)$$

- each  $P(n) \times_{\Lambda_n} X^n$  is a coequalizer:

$$(p \cdot g; x_1, \dots, x_n) \sim (p; x_{g^{-1}(1)}, \dots, x_{g^{-1}(n)})$$

- we investigate  $\Lambda$ -operads in **Cat**: 2-monads

## Commutative Monads

- $T: \mathcal{C} \rightarrow \mathcal{C}$  a monad
- a **strength** is a natural transformation + axioms

equivalent when  
 $\mathcal{C}$  sym. mon. cat

$$t_{X,Y}: X \otimes TY \rightarrow T(X \otimes Y)$$

- a **costrength** is a natural transformation + axioms

$$t_{X,Y}^*: TX \otimes Y \rightarrow T(X \otimes Y)$$

## $\Lambda$ -Operads

### Data

- an action operad  $\Lambda$
- an operad  $P$
- actions  $P(n) \times \Lambda(n) \rightarrow P(n)$
- satisfying:

$$\mu^P(p \cdot g; q_1, \dots, q_n) = \mu^P(p; q_{g^{-1}(1)}, \dots, q_{g^{-1}(n)}) \cdot \delta^\Lambda(g)$$

$$\mu^P(p; q_1 \cdot g_1, \dots, q_n \cdot g_n) = \mu^P(p; q_1, \dots, q_n) \cdot \beta^\Lambda(g_1, \dots, g_n)$$

### Monads

- each  $\Lambda$ -operad  $P$  induces a monad  $\underline{P}$  on **Set**:

$$\underline{P}(X) = \coprod_{n \in \mathbb{N}} (P(n) \times_{\Lambda_n} X^n)$$


- each  $P(n) \times_{\Lambda_n} X^n$  is a coequalizer:

$$(p \cdot g; x_1, \dots, x_n) \sim (p; x_{g^{-1}(1)}, \dots, x_{g^{-1}(n)})$$

- we investigate  $\Lambda$ -operads in **Cat**: 2-monads

## Commutative Monads

- $T: \mathcal{C} \rightarrow \mathcal{C}$  a monad
- a **strength** is a natural transformation + axioms  
 equivalent when  $\mathcal{C}$  sym. mon. cat  $t_{X,Y}: X \otimes TY \rightarrow T(X \otimes Y)$
- a **costrength** is a natural transformation + axioms  
 $t_{X,Y}^*: TX \otimes Y \rightarrow T(X \otimes Y)$
- $T$  is **commutative** if this commutes:



## $\Lambda$ -Operads

### Data

- an action operad  $\Lambda$
- an operad  $P$
- actions  $P(n) \times \Lambda(n) \rightarrow P(n)$
- satisfying:

$$\mu^P(p \cdot g; q_1, \dots, q_n) = \mu^P(p; q_{g^{-1}(1)}, \dots, q_{g^{-1}(n)}) \cdot \delta^\Lambda(g)$$

$$\mu^P(p; q_1 \cdot g_1, \dots, q_n \cdot g_n) = \mu^P(p; q_1, \dots, q_n) \cdot \beta^\Lambda(g_1, \dots, g_n)$$

### Monads

- each  $\Lambda$ -operad  $P$  induces a monad  $\underline{P}$  on **Set**:

$$\underline{P}(X) = \coprod_{n \in \mathbb{N}} (P(n) \times_{\Lambda_n} X^n)$$


- each  $P(n) \times_{\Lambda_n} X^n$  is a coequalizer:

$$(p \cdot g; x_1, \dots, x_n) \sim (p; x_{g^{-1}(1)}, \dots, x_{g^{-1}(n)})$$

- we investigate  $\Lambda$ -operads in **Cat**: 2-monads

## Commutative Monads

- $T: \mathcal{C} \rightarrow \mathcal{C}$  a monad
- a **strength** is a natural transformation + axioms
- **equivalent when**  
 $\mathcal{C}$  sym. mon. cat  $t_{X,Y}: X \otimes TY \rightarrow T(X \otimes Y)$
- a **costrength** is a natural transformation + axioms  
 $t_{X,Y}^*: TX \otimes Y \rightarrow T(X \otimes Y)$
- $T$  is **commutative** if this commutes:



Kock, A.

- $T$  commutative  $\Rightarrow T\text{-Alg}$  is sym. mon. closed
- allows us to 'tensor' algebras for  $T$

## $\Lambda$ -Operads

### Data

- an action operad  $\Lambda$
- an operad  $P$
- actions  $P(n) \times \Lambda(n) \rightarrow P(n)$
- satisfying:

$$\mu^P(p \cdot g; q_1, \dots, q_n) = \mu^P(p; q_{g^{-1}(1)}, \dots, q_{g^{-1}(n)}) \cdot \delta^\Lambda(g)$$

$$\mu^P(p; q_1 \cdot g_1, \dots, q_n \cdot g_n) = \mu^P(p; q_1, \dots, q_n) \cdot \beta^\Lambda(g_1, \dots, g_n)$$

### Monads

- each  $\Lambda$ -operad  $P$  induces a monad  $\underline{P}$  on **Set**:

$$\underline{P}(X) = \coprod_{n \in \mathbb{N}} (P(n) \times_{\Lambda_n} X^n)$$


- each  $P(n) \times_{\Lambda_n} X^n$  is a coequalizer:

$$(p \cdot g; x_1, \dots, x_n) \sim (p; x_{g^{-1}(1)}, \dots, x_{g^{-1}(n)})$$

- we investigate  $\Lambda$ -operads in **Cat**: 2-monads

## Commutative Monads


- $T: \mathcal{C} \rightarrow \mathcal{C}$  a monad
- a **strength** is a natural transformation + axioms  
equivalent when  $\mathcal{C}$  sym. mon. cat  $t_{X,Y}: X \otimes TY \rightarrow T(X \otimes Y)$
- a **costrength** is a natural transformation + axioms  
 $t_{X,Y}^*: TX \otimes Y \rightarrow T(X \otimes Y)$
- $T$  is **commutative** if this commutes:



- $T$  commutative  $\Rightarrow T\text{-Alg}$  is sym. mon. closed
- allows us to 'tensor' algebras for  $T$


## Pseudo-Commutative 2-Monads

- $T: \mathcal{C} \rightarrow \mathcal{C}$  a 2-monad
- equipped with strength and costrength (2d, strict)
- equipped with invertible modification:



## Commutative Monads


- $T: \mathcal{C} \rightarrow \mathcal{C}$  a monad
- a **strength** is a natural transformation + axioms
- equivalent when  $\mathcal{C}$  sym. mon. cat  $t_{X,Y}: X \otimes TY \rightarrow T(X \otimes Y)$
- a **costrength** is a natural transformation + axioms  $t_{X,Y}^*: TX \otimes Y \rightarrow T(X \otimes Y)$
- $T$  is **commutative** if this commutes:



- $T$  commutative  $\Rightarrow T\text{-Alg}$  is sym. mon. closed
- allows us to 'tensor' algebras for  $T$

## Pseudo-Commutative 2-Monads

- $T: \mathcal{C} \rightarrow \mathcal{C}$  a 2-monad
- equipped with strength and costrength (2d, strict)
- equipped with invertible modification:



- $T$  is **pseudo-commutative** if



## Commutative Monads

- $T: \mathcal{C} \rightarrow \mathcal{C}$  a monad
- a **strength** is a natural transformation + axioms


equivalent when  
 $\mathcal{C}$  sym. mon. cat

$$t_{X,Y}: X \otimes TY \rightarrow T(X \otimes Y)$$

- a **costrength** is a natural transformation + axioms

$$t_{X,Y}^*: TX \otimes Y \rightarrow T(X \otimes Y)$$

- $T$  is **commutative** if this commutes:




Kock, A.

- $T$  commutative  $\Rightarrow T\text{-Alg}$  is sym. mon. closed
- allows us to 'tensor' algebras for  $T$

## Pseudo-Commutative 2-Monads

- $T: \mathcal{C} \rightarrow \mathcal{C}$  a 2-monad
- equipped with strength and costrength (2d, strict)
- equipped with invertible modification:



Hyland-Power

- $T$  is **pseudo-commutative** if

lots of axioms

## Commutative Monads

- $T: \mathcal{C} \rightarrow \mathcal{C}$  a monad
- a **strength** is a natural transformation + axioms


equivalent when  
 $\mathcal{C}$  sym. mon. cat

$$t_{X,Y}: X \otimes TY \rightarrow T(X \otimes Y)$$

- a **costrength** is a natural transformation + axioms

$$t_{X,Y}^*: TX \otimes Y \rightarrow T(X \otimes Y)$$

- $T$  is **commutative** if this commutes:




Kock, A.

- $T$  commutative  $\Rightarrow T\text{-Alg}$  is sym. mon. closed
- allows us to 'tensor' algebras for  $T$

## Pseudo-Commutative 2-Monads

- $T: \mathcal{C} \rightarrow \mathcal{C}$  a 2-monad
- equipped with strength and costrength (2d, strict)
- equipped with invertible modification:

Hyland-Power



- $T$  is **pseudo-commutative** if

lots of axioms


- $T$  ps-commutative  $\Rightarrow T\text{-Alg}_{ps}$  is pseudo-closed
- allows us to 'tensor' strict algebras for  $T$

## Pseudo-Commutative $\wedge$ -Operads

- can characterise  $\wedge$ -operads with ps-commutativity

## Pseudo-Commutative 2-Monads

- $T: \mathcal{C} \rightarrow \mathcal{C}$  a 2-monad
- equipped with strength and costrength (2d, strict)
- equipped with invertible modification:



- $T$  is **pseudo-commutative** if

lots of axioms


- $T$  ps-commutative  $\Rightarrow T\text{-}\mathbf{Alg}_{ps}$  is pseudo-closed
- allows us to ‘tensor’ strict algebras for  $T$

## Pseudo-Commutative $\wedge$ -Operads

- can characterise  $\wedge$ -operads with ps-commutativity
- requires elements  $t_{m,n} \in \wedge(mn)$  with  $\pi(t_{m,n}) = \tau_{m,n}$

## Pseudo-Commutative 2-Monads

- $T: \mathcal{C} \rightarrow \mathcal{C}$  a 2-monad
- equipped with strength and costrength (2d, strict)
- equipped with invertible modification:



- $T$  is **pseudo-commutative** if

lots of axioms

- $T$  ps-commutative  $\Rightarrow T\text{-}\mathbf{Alg}_{ps}$  is pseudo-closed
- allows us to ‘tensor’ strict algebras for  $T$


## Pseudo-Commutative $\wedge$ -Operads

- can characterise  $\wedge$ -operads with ps-commutativity
- requires elements  $t_{m,n} \in \wedge(mn)$  with  $\pi(t_{m,n}) = \tau_{m,n}$
- $\tau_{5,3}$  is pictured below



## Pseudo-Commutative 2-Monads

- $T: \mathcal{C} \rightarrow \mathcal{C}$  a 2-monad
- equipped with strength and costrength (2d, strict)
- equipped with invertible modification:




- $T$  is **pseudo-commutative** if

lots of axioms

- $T$  ps-commutative  $\Rightarrow T\text{-}\mathbf{Alg}_{ps}$  is pseudo-closed
- allows us to 'tensor' strict algebras for  $T$


## Pseudo-Commutative $\Lambda$ -Operads

- can characterise  $\Lambda$ -operads with ps-commutativity
- requires elements  $t_{m,n} \in \Lambda(mn)$  with  $\pi(t_{m,n}) = \tau_{m,n}$
- $\tau_{5,3}$  is pictured below



## Pseudo-Commutative 2-Monads

- $T: \mathcal{C} \rightarrow \mathcal{C}$  a 2-monad
- equipped with strength and costrength (2d, strict)
- equipped with invertible modification:




- $T$  is **pseudo-commutative** if

lots of axioms

- $T$  ps-commutative  $\Rightarrow T\text{-}\mathbf{Alg}_{ps}$  is pseudo-closed
- allows us to ‘tensor’ strict algebras for  $T$


## Pseudo-Commutative $\Lambda$ -Operads

- can characterise  $\Lambda$ -operads with ps-commutativity
- requires elements  $t_{m,n} \in \Lambda(mn)$  with  $\pi(t_{m,n}) = \tau_{m,n}$
- $\tau_{5,3}$  is pictured below



## Pseudo-Commutative 2-Monads

- $T: \mathcal{C} \rightarrow \mathcal{C}$  a 2-monad
- equipped with strength and costrength (2d, strict)
- equipped with invertible modification:




- $T$  is **pseudo-commutative** if

lots of axioms

- $T$  ps-commutative  $\Rightarrow T\text{-}\mathbf{Alg}_{ps}$  is pseudo-closed
- allows us to ‘tensor’ strict algebras for  $T$


## Pseudo-Commutative $\Lambda$ -Operads

- can characterise  $\Lambda$ -operads with ps-commutativity
- requires elements  $t_{m,n} \in \Lambda(mn)$  with  $\pi(t_{m,n}) = \tau_{m,n}$
- $\tau_{5,3}$  is pictured below



## Pseudo-Commutative 2-Monads

- $T: \mathcal{C} \rightarrow \mathcal{C}$  a 2-monad
- equipped with strength and costrength (2d, strict)
- equipped with invertible modification:



- $T$  is **pseudo-commutative** if


lots of axioms

- $T$  ps-commutative  $\Rightarrow T\text{-}\mathbf{Alg}_{ps}$  is pseudo-closed
- allows us to ‘tensor’ strict algebras for  $T$




## Pseudo-Commutative $\Lambda$ -Operads

- can characterise  $\Lambda$ -operads with ps-commutativity
- requires elements  $t_{m,n} \in \Lambda(mn)$  with  $\pi(t_{m,n}) = \tau_{m,n}$
- $\tau_{5,3}$  is pictured below



## Pseudo-Commutative 2-Monads

- $T: \mathcal{C} \rightarrow \mathcal{C}$  a 2-monad
- equipped with strength and costrength (2d, strict)
- equipped with invertible modification:




- $T$  is **pseudo-commutative** if

lots of axioms

- $T$  ps-commutative  $\Rightarrow T\text{-}\mathbf{Alg}_{ps}$  is pseudo-closed
- allows us to ‘tensor’ strict algebras for  $T$

## Pseudo-Commutative $\Lambda$ -Operads

- can characterise  $\Lambda$ -operads with ps-commutativity
- requires elements  $t_{m,n} \in \Lambda(mn)$  with  $\pi(t_{m,n}) = \tau_{m,n}$
- $\tau_{5,3}$  is pictured below




- these permutations correspond to matrix transpose

$$\begin{bmatrix} (x_1, y_1) & (x_1, y_2) & (x_1, y_3) \\ (x_2, y_1) & (x_2, y_2) & (x_2, y_3) \\ (x_3, y_1) & (x_3, y_2) & (x_3, y_3) \\ (x_4, y_1) & (x_4, y_2) & (x_4, y_3) \\ (x_5, y_1) & (x_5, y_2) & (x_5, y_3) \end{bmatrix}^T = \begin{bmatrix} (x_1, y_1) & (x_2, y_1) & (x_3, y_1) & (x_4, y_1) & (x_5, y_1) \\ (x_1, y_2) & (x_2, y_2) & (x_3, y_2) & (x_4, y_2) & (x_5, y_2) \\ (x_1, y_3) & (x_2, y_3) & (x_3, y_3) & (x_4, y_3) & (x_5, y_3) \end{bmatrix}$$

## Pseudo-Commutative 2-Monads

- $T: \mathcal{C} \rightarrow \mathcal{C}$  a 2-monad
- equipped with strength and costrength (2d, strict)
- equipped with invertible modification:




- $T$  is **pseudo-commutative** if

lots of axioms

- $T$  ps-commutative  $\Rightarrow T\text{-}\mathbf{Alg}_{ps}$  is pseudo-closed
- allows us to ‘tensor’ strict algebras for  $T$

## Pseudo-Commutative $\Lambda$ -Operads

- can characterise  $\Lambda$ -operads with ps-commutativity
- requires elements  $t_{m,n} \in \Lambda(mn)$  with  $\pi(t_{m,n}) = \tau_{m,n}$
- $\tau_{5,3}$  is pictured below




- these permutations correspond to matrix transpose

$$\begin{bmatrix} (x_1, y_1) & (x_1, y_2) & (x_1, y_3) \\ (x_2, y_1) & (x_2, y_2) & (x_2, y_3) \\ (x_3, y_1) & (x_3, y_2) & (x_3, y_3) \\ (x_4, y_1) & (x_4, y_2) & (x_4, y_3) \\ (x_5, y_1) & (x_5, y_2) & (x_5, y_3) \end{bmatrix}^T = \begin{bmatrix} (x_1, y_1) & (x_2, y_1) & (x_3, y_1) & (x_4, y_1) & (x_5, y_1) \\ (x_1, y_2) & (x_2, y_2) & (x_3, y_2) & (x_4, y_2) & (x_5, y_2) \\ (x_1, y_3) & (x_2, y_3) & (x_3, y_3) & (x_4, y_3) & (x_5, y_3) \end{bmatrix}$$

- a  $\Lambda$ -operad with these elements is ps-commutative if

## Pseudo-Commutative 2-Monads

- $T: \mathcal{C} \rightarrow \mathcal{C}$  a 2-monad
- equipped with strength and costrength (2d, strict)
- equipped with invertible modification:




- $T$  is **pseudo-commutative** if

lots of axioms

- $T$  ps-commutative  $\Rightarrow T\text{-}\mathbf{Alg}_{ps}$  is pseudo-closed
- allows us to ‘tensor’ strict algebras for  $T$

## Pseudo-Commutative $\Lambda$ -Operads

- can characterise  $\Lambda$ -operads with ps-commutativity
- requires elements  $t_{m,n} \in \Lambda(mn)$  with  $\pi(t_{m,n}) = \tau_{m,n}$
- $\tau_{5,3}$  is pictured below



- these permutations correspond to matrix transpose

$$\begin{bmatrix} (x_1, y_1) & (x_1, y_2) & (x_1, y_3) \\ (x_2, y_1) & (x_2, y_2) & (x_2, y_3) \\ (x_3, y_1) & (x_3, y_2) & (x_3, y_3) \\ (x_4, y_1) & (x_4, y_2) & (x_4, y_3) \\ (x_5, y_1) & (x_5, y_2) & (x_5, y_3) \end{bmatrix}^T = \begin{bmatrix} (x_1, y_1) & (x_2, y_1) & (x_3, y_1) & (x_4, y_1) & (x_5, y_1) \\ (x_1, y_2) & (x_2, y_2) & (x_3, y_2) & (x_4, y_2) & (x_5, y_2) \\ (x_1, y_3) & (x_2, y_3) & (x_3, y_3) & (x_4, y_3) & (x_5, y_3) \end{bmatrix}$$


- a  $\Lambda$ -operad with these elements is ps-commutative if

lots of axioms

- then the corresponding 2-monad is ps-commutative

## Pseudo-Commutative 2-Monads

- $T: \mathcal{C} \rightarrow \mathcal{C}$  a 2-monad
- equipped with strength and costrength (2d, strict)
- equipped with invertible modification:




- $T$  is **pseudo-commutative** if

lots of axioms

- $T$  ps-commutative  $\Rightarrow T\text{-}\mathbf{Alg}_{ps}$  is pseudo-closed
- allows us to 'tensor' strict algebras for  $T$

## Pseudo-Commutative $\Lambda$ -Operads

- can characterise  $\Lambda$ -operads with ps-commutativity
- requires elements  $t_{m,n} \in \Lambda(mn)$  with  $\pi(t_{m,n}) = \tau_{m,n}$
- $\tau_{5,3}$  is pictured below



- these permutations correspond to matrix transpose

$$\begin{bmatrix} (x_1, y_1) & (x_1, y_2) & (x_1, y_3) \\ (x_2, y_1) & (x_2, y_2) & (x_2, y_3) \\ (x_3, y_1) & (x_3, y_2) & (x_3, y_3) \\ (x_4, y_1) & (x_4, y_2) & (x_4, y_3) \\ (x_5, y_1) & (x_5, y_2) & (x_5, y_3) \end{bmatrix}^T = \begin{bmatrix} (x_1, y_1) & (x_2, y_1) & (x_3, y_1) & (x_4, y_1) & (x_5, y_1) \\ (x_1, y_2) & (x_2, y_2) & (x_3, y_2) & (x_4, y_2) & (x_5, y_2) \\ (x_1, y_3) & (x_2, y_3) & (x_3, y_3) & (x_4, y_3) & (x_5, y_3) \end{bmatrix}$$

- a  $\Lambda$ -operad with these elements is ps-commutative if

lots of axioms

- then the corresponding 2-monad is ps-commutative

## Examples/Non-Examples

### Examples

Guillou–May–Merling–Osorno

- $\Sigma$ : symmetric strict monoidal categories
- $B$ : braided strict monoidal categories

C–G

### Non-Examples

- $J$ : cactus/coboundary strict monoidal categories

C–G

- 
- [arXiv:1508.04050](#) – Operads, tensor products, and the categorical Borel construction
  - [arXiv:1312.5910](#) – Operads with general groups of equivariance, and some 2-categorical aspects of operads in **Cat**