

Quantum++

v1.2

Generated by Doxygen 1.8.14

Contents

1	Quantum++	1
2	Namespace Index	3
2.1	Namespace List	3
3	Hierarchical Index	5
3.1	Class Hierarchy	5
4	Class Index	9
4.1	Class List	9
5	File Index	13
5.1	File List	13
6	Namespace Documentation	15
6.1	qpp Namespace Reference	15
6.1.1	Detailed Description	28
6.1.2	Typedef Documentation	28
6.1.2.1	bigint	28
6.1.2.2	bra	29
6.1.2.3	cmat	29
6.1.2.4	cplx	29
6.1.2.5	dmat	29
6.1.2.6	dyn_col_vect	29
6.1.2.7	dyn_mat	30
6.1.2.8	dyn_row_vect	30

6.1.2.9	idx	30
6.1.2.10	ket	30
6.1.2.11	to_void	31
6.1.3	Function Documentation	31
6.1.3.1	absm()	31
6.1.3.2	abssq() [1/3]	31
6.1.3.3	abssq() [2/3]	32
6.1.3.4	abssq() [3/3]	32
6.1.3.5	adjoint()	32
6.1.3.6	anticomm()	33
6.1.3.7	apply() [1/5]	33
6.1.3.8	apply() [2/5]	34
6.1.3.9	apply() [3/5]	34
6.1.3.10	apply() [4/5]	35
6.1.3.11	apply() [5/5]	35
6.1.3.12	applyCTRL() [1/2]	36
6.1.3.13	applyCTRL() [2/2]	37
6.1.3.14	applyQFT()	37
6.1.3.15	applyTFQ()	38
6.1.3.16	avg()	38
6.1.3.17	bloch2rho()	39
6.1.3.18	choi2kraus()	39
6.1.3.19	choi2super()	40
6.1.3.20	comm()	40
6.1.3.21	complement()	41
6.1.3.22	compperm()	41
6.1.3.23	concurrence()	41
6.1.3.24	conjugate()	42
6.1.3.25	contfrac2x()	42
6.1.3.26	convergents() [1/2]	43

6.1.3.27	convergents() [2/2]	43
6.1.3.28	cor()	44
6.1.3.29	cosm()	44
6.1.3.30	cov()	44
6.1.3.31	cwise()	45
6.1.3.32	det()	45
6.1.3.33	dirsum() [1/4]	46
6.1.3.34	dirsum() [2/4]	46
6.1.3.35	dirsum() [3/4]	47
6.1.3.36	dirsum() [4/4]	47
6.1.3.37	dirsumpow()	47
6.1.3.38	disp() [1/5]	48
6.1.3.39	disp() [2/5]	48
6.1.3.40	disp() [3/5]	49
6.1.3.41	disp() [4/5]	49
6.1.3.42	disp() [5/5]	50
6.1.3.43	egcd()	50
6.1.3.44	eig()	51
6.1.3.45	entanglement() [1/2]	51
6.1.3.46	entanglement() [2/2]	52
6.1.3.47	entropy() [1/2]	52
6.1.3.48	entropy() [2/2]	53
6.1.3.49	evals()	53
6.1.3.50	evecs()	53
6.1.3.51	expm()	54
6.1.3.52	factors()	54
6.1.3.53	funm()	55
6.1.3.54	gcd() [1/2]	55
6.1.3.55	gcd() [2/2]	56
6.1.3.56	gconcurrency()	56

6.1.3.57	<code>grams()</code> [1/3]	57
6.1.3.58	<code>grams()</code> [2/3]	57
6.1.3.59	<code>grams()</code> [3/3]	57
6.1.3.60	<code>hash_eigen()</code>	58
6.1.3.61	<code>heig()</code>	58
6.1.3.62	<code>hevals()</code>	59
6.1.3.63	<code>hevects()</code>	59
6.1.3.64	<code>inverse()</code>	60
6.1.3.65	<code>invperm()</code>	60
6.1.3.66	<code>ip()</code> [1/2]	60
6.1.3.67	<code>ip()</code> [2/2]	61
6.1.3.68	<code>isprime()</code>	61
6.1.3.69	<code>kraus2choi()</code>	62
6.1.3.70	<code>kraus2super()</code>	62
6.1.3.71	<code>kron()</code> [1/4]	63
6.1.3.72	<code>kron()</code> [2/4]	63
6.1.3.73	<code>kron()</code> [3/4]	64
6.1.3.74	<code>kron()</code> [4/4]	64
6.1.3.75	<code>kronpow()</code>	64
6.1.3.76	<code>lcm()</code> [1/2]	65
6.1.3.77	<code>lcm()</code> [2/2]	65
6.1.3.78	<code>load()</code>	66
6.1.3.79	<code>loadMATLAB()</code> [1/2]	66
6.1.3.80	<code>loadMATLAB()</code> [2/2]	67
6.1.3.81	<code>logdet()</code>	68
6.1.3.82	<code>logm()</code>	68
6.1.3.83	<code>lognegativity()</code> [1/2]	69
6.1.3.84	<code>lognegativity()</code> [2/2]	69
6.1.3.85	<code>marginalX()</code>	69
6.1.3.86	<code>marginalY()</code>	71

6.1.3.87	<code>measure()</code> [1/9]	71
6.1.3.88	<code>measure()</code> [2/9]	72
6.1.3.89	<code>measure()</code> [3/9]	72
6.1.3.90	<code>measure()</code> [4/9]	72
6.1.3.91	<code>measure()</code> [5/9]	73
6.1.3.92	<code>measure()</code> [6/9]	74
6.1.3.93	<code>measure()</code> [7/9]	74
6.1.3.94	<code>measure()</code> [8/9]	75
6.1.3.95	<code>measure()</code> [9/9]	76
6.1.3.96	<code>measure_seq()</code> [1/2]	76
6.1.3.97	<code>measure_seq()</code> [2/2]	77
6.1.3.98	<code>mket()</code> [1/2]	77
6.1.3.99	<code>mket()</code> [2/2]	78
6.1.3.100	<code>modinv()</code>	78
6.1.3.101	<code>modmul()</code>	79
6.1.3.102	<code>modpow()</code>	79
6.1.3.103	<code>mprj()</code> [1/2]	80
6.1.3.104	<code>mprj()</code> [2/2]	81
6.1.3.105	<code>multiidx2n()</code>	81
6.1.3.106	<code>n2multiidx()</code>	82
6.1.3.107	<code>negativity()</code> [1/2]	82
6.1.3.108	<code>negativity()</code> [2/2]	82
6.1.3.109	<code>norm()</code>	83
6.1.3.110	<code>normalize()</code>	83
6.1.3.111	<code>omega()</code>	84
6.1.3.112	<code>operator""_i()</code>	84
6.1.3.113	<code>powm()</code>	84
6.1.3.114	<code>prj()</code>	85
6.1.3.115	<code>prod()</code> [1/3]	85
6.1.3.116	<code>prod()</code> [2/3]	86

6.1.3.117 <code>prod()</code> [3/3]	86
6.1.3.118 <code>ptrace()</code> [1/2]	86
6.1.3.119 <code>ptrace()</code> [2/2]	87
6.1.3.120 <code>ptrace1()</code> [1/2]	87
6.1.3.121 <code>ptrace1()</code> [2/2]	88
6.1.3.122 <code>ptrace2()</code> [1/2]	88
6.1.3.123 <code>ptrace2()</code> [2/2]	89
6.1.3.124 <code>ptranspose()</code> [1/2]	89
6.1.3.125 <code>ptranspose()</code> [2/2]	90
6.1.3.126 <code>QFT()</code>	90
6.1.3.127 <code>qmutualinfo()</code> [1/2]	91
6.1.3.128 <code>qmutualinfo()</code> [2/2]	91
6.1.3.129 <code>rand()</code> [1/5]	92
6.1.3.130 <code>rand()</code> [2/5]	92
6.1.3.131 <code>rand()</code> [3/5]	93
6.1.3.132 <code>rand()</code> [4/5]	93
6.1.3.133 <code>rand()</code> [5/5]	94
6.1.3.134 <code>randH()</code>	94
6.1.3.135 <code>randidx()</code>	95
6.1.3.136 <code>randket()</code>	95
6.1.3.137 <code>randkraus()</code>	95
6.1.3.138 <code>randn()</code> [1/4]	96
6.1.3.139 <code>randn()</code> [2/4]	96
6.1.3.140 <code>randn()</code> [3/4]	97
6.1.3.141 <code>randn()</code> [4/4]	97
6.1.3.142 <code>randperm()</code>	98
6.1.3.143 <code>randprime()</code>	98
6.1.3.144 <code>randprob()</code>	99
6.1.3.145 <code>randrho()</code>	99
6.1.3.146 <code>randU()</code>	99

6.1.3.147 randV()	100
6.1.3.148 renyi() [1/2]	100
6.1.3.149 renyi() [2/2]	101
6.1.3.150 reshape()	101
6.1.3.151 rho2bloch()	102
6.1.3.152 rho2pure()	102
6.1.3.153 save()	103
6.1.3.154 saveMATLAB() [1/2]	103
6.1.3.155 saveMATLAB() [2/2]	104
6.1.3.156 schatten()	104
6.1.3.157 schmidtA() [1/2]	105
6.1.3.158 schmidtA() [2/2]	105
6.1.3.159 schmidtB() [1/2]	105
6.1.3.160 schmidtB() [2/2]	106
6.1.3.161 schmidtcoeffs() [1/2]	106
6.1.3.162 schmidtcoeffs() [2/2]	107
6.1.3.163 schmidtprobs() [1/2]	107
6.1.3.164 schmidtprobs() [2/2]	108
6.1.3.165 sigma()	108
6.1.3.166 sinm()	109
6.1.3.167 spectralpowm()	109
6.1.3.168 sqrtm()	110
6.1.3.169 sum() [1/3]	110
6.1.3.170 sum() [2/3]	110
6.1.3.171 sum() [3/3]	111
6.1.3.172 super2choi()	111
6.1.3.173 svals()	112
6.1.3.174 svd()	112
6.1.3.175 svdU()	112
6.1.3.176 svdV()	113

6.1.3.177	syspermute() [1/2]	113
6.1.3.178	syspermute() [2/2]	114
6.1.3.179	TFQ()	114
6.1.3.180	trace()	115
6.1.3.181	transpose()	115
6.1.3.182	tsallis() [1/2]	115
6.1.3.183	tsallis() [2/2]	116
6.1.3.184	uniform()	116
6.1.3.185	var()	117
6.1.3.186	x2contfrac()	117
6.1.4	Variable Documentation	118
6.1.4.1	chop	118
6.1.4.2	ee	118
6.1.4.3	infty	118
6.1.4.4	maxn	118
6.1.4.5	pi	118
6.2	qpp::exception Namespace Reference	118
6.2.1	Detailed Description	120
6.3	qpp::experimental Namespace Reference	120
6.3.1	Detailed Description	120
6.4	qpp::internal Namespace Reference	120
6.4.1	Detailed Description	122
6.4.2	Function Documentation	122
6.4.2.1	check_cvector()	122
6.4.2.2	check_dims()	122
6.4.2.3	check_dims_match_cvect()	122
6.4.2.4	check_dims_match_mat()	122
6.4.2.5	check_dims_match_rvect()	123
6.4.2.6	check_eq_dims()	123
6.4.2.7	check_matching_sizes()	123

6.4.2.8	<code>check_no_duplicates()</code>	123
6.4.2.9	<code>check_nonzero_size()</code>	123
6.4.2.10	<code>check_perm()</code>	123
6.4.2.11	<code>check_qubit_cvector()</code>	124
6.4.2.12	<code>check_qubit_matrix()</code>	124
6.4.2.13	<code>check_qubit_rvector()</code>	124
6.4.2.14	<code>check_qubit_vector()</code>	124
6.4.2.15	<code>check_rvector()</code>	124
6.4.2.16	<code>check_square_mat()</code>	124
6.4.2.17	<code>check_subsys_match_dims()</code>	125
6.4.2.18	<code>check_vector()</code>	125
6.4.2.19	<code>dirsum2()</code>	125
6.4.2.20	<code>get_dim_subsys()</code>	125
6.4.2.21	<code>get_num_subsys()</code>	125
6.4.2.22	<code>hash_combine()</code>	125
6.4.2.23	<code>kron2()</code>	126
6.4.2.24	<code>multiidx2n()</code>	126
6.4.2.25	<code>n2multiidx()</code>	126
6.4.2.26	<code>variadic_vector_emplace()</code> ^[1/2]	126
6.4.2.27	<code>variadic_vector_emplace()</code> ^[2/2]	126
6.5	<code>qpp::literals</code> Namespace Reference	127
6.5.1	Function Documentation	127
6.5.1.1	<code>operator""_bra()</code>	127
6.5.1.2	<code>operator""_i()</code>	127
6.5.1.3	<code>operator""_ket()</code>	128
6.5.1.4	<code>operator""_prj()</code>	128

7	Class Documentation	131
7.1	qpp::Bit_circuit Class Reference	131
7.1.1	Detailed Description	133
7.1.2	Constructor & Destructor Documentation	133
7.1.2.1	Bit_circuit()	133
7.1.3	Member Function Documentation	133
7.1.3.1	CNOT()	133
7.1.3.2	Dynamic_bitset()	134
7.1.3.3	FRED()	134
7.1.3.4	NOT()	134
7.1.3.5	reset()	135
7.1.3.6	SWAP()	135
7.1.3.7	TOF()	135
7.1.3.8	X()	136
7.1.4	Member Data Documentation	136
7.1.4.1	gate_count	136
7.2	qpp::Codes Class Reference	136
7.2.1	Detailed Description	137
7.2.2	Member Enumeration Documentation	137
7.2.2.1	Type	138
7.2.3	Constructor & Destructor Documentation	138
7.2.3.1	Codes()	138
7.2.3.2	~Codes()	138
7.2.4	Member Function Documentation	138
7.2.4.1	codeword()	138
7.2.5	Friends And Related Function Documentation	139
7.2.5.1	internal::Singleton< const Codes >	139
7.3	qpp::exception::CustomException Class Reference	139
7.3.1	Detailed Description	140
7.3.2	Constructor & Destructor Documentation	140

7.3.2.1	CustomException()	141
7.3.3	Member Function Documentation	141
7.3.3.1	type_description()	141
7.3.4	Member Data Documentation	141
7.3.4.1	what_	141
7.4	qpp::exception::DimsInvalid Class Reference	142
7.4.1	Detailed Description	143
7.4.2	Member Function Documentation	143
7.4.2.1	Exception()	143
7.4.2.2	type_description()	143
7.5	qpp::exception::DimsMismatchCvector Class Reference	144
7.5.1	Detailed Description	145
7.5.2	Member Function Documentation	145
7.5.2.1	Exception()	145
7.5.2.2	type_description()	145
7.6	qpp::exception::DimsMismatchMatrix Class Reference	146
7.6.1	Detailed Description	147
7.6.2	Member Function Documentation	147
7.6.2.1	Exception()	147
7.6.2.2	type_description()	147
7.7	qpp::exception::DimsMismatchRvector Class Reference	148
7.7.1	Detailed Description	149
7.7.2	Member Function Documentation	149
7.7.2.1	Exception()	149
7.7.2.2	type_description()	149
7.8	qpp::exception::DimsMismatchVector Class Reference	150
7.8.1	Detailed Description	151
7.8.2	Member Function Documentation	151
7.8.2.1	Exception()	151
7.8.2.2	type_description()	151

7.9	qpp::exception::DimsNotEqual Class Reference	152
7.9.1	Detailed Description	153
7.9.2	Member Function Documentation	153
7.9.2.1	Exception()	153
7.9.2.2	type_description()	153
7.10	qpp::internal::Display_Impl_Struct Reference	154
7.10.1	Member Function Documentation	154
7.10.1.1	display_impl_()	154
7.11	qpp::exception::Duplicates Class Reference	155
7.11.1	Detailed Description	156
7.11.2	Member Function Documentation	156
7.11.2.1	Exception()	156
7.11.2.2	type_description()	156
7.12	qpp::Dynamic_bitset Class Reference	157
7.12.1	Detailed Description	159
7.12.2	Member Typedef Documentation	159
7.12.2.1	storage_type	159
7.12.2.2	value_type	159
7.12.3	Constructor & Destructor Documentation	159
7.12.3.1	Dynamic_bitset()	159
7.12.3.2	~Dynamic_bitset()	160
7.12.4	Member Function Documentation	160
7.12.4.1	all()	160
7.12.4.2	any()	160
7.12.4.3	count()	160
7.12.4.4	data()	161
7.12.4.5	display()	161
7.12.4.6	flip() [1/2]	161
7.12.4.7	flip() [2/2]	162
7.12.4.8	get()	162

7.12.4.9	<code>index_()</code>	162
7.12.4.10	<code>none()</code>	163
7.12.4.11	<code>offset_()</code>	163
7.12.4.12	<code>operator!=()</code>	163
7.12.4.13	<code>operator-()</code>	164
7.12.4.14	<code>operator==()</code>	164
7.12.4.15	<code>rand()</code> [1/2]	164
7.12.4.16	<code>rand()</code> [2/2]	165
7.12.4.17	<code>reset()</code> [1/2]	165
7.12.4.18	<code>reset()</code> [2/2]	165
7.12.4.19	<code>set()</code> [1/2]	166
7.12.4.20	<code>set()</code> [2/2]	166
7.12.4.21	<code>size()</code>	166
7.12.4.22	<code>storage_size()</code>	166
7.12.4.23	<code>to_string()</code>	167
7.12.5	Member Data Documentation	167
7.12.5.1	<code>N_</code>	167
7.12.5.2	<code>storage_size_</code>	167
7.12.5.3	<code>v_</code>	168
7.13	<code>qpp::internal::EqualEigen</code> Class Reference	168
7.13.1	Detailed Description	168
7.13.2	Member Function Documentation	168
7.13.2.1	<code>operator()()</code>	168
7.14	<code>qpp::exception::Exception</code> Class Reference	169
7.14.1	Detailed Description	170
7.14.2	Constructor & Destructor Documentation	171
7.14.2.1	<code>Exception()</code>	171
7.14.3	Member Function Documentation	171
7.14.3.1	<code>type_description()</code>	171
7.14.3.2	<code>what()</code>	172

7.14.4	Member Data Documentation	172
7.14.4.1	msg_	172
7.14.4.2	where_	172
7.15	qpp::Bit_circuit::Gate_count Struct Reference	172
7.15.1	Member Data Documentation	172
7.15.1.1	CNOT	173
7.15.1.2	FRED	173
7.15.1.3	NOT	173
7.15.1.4	SWAP	173
7.15.1.5	TOF	173
7.15.1.6	X	173
7.16	qpp::Gates Class Reference	174
7.16.1	Detailed Description	176
7.16.2	Constructor & Destructor Documentation	176
7.16.2.1	Gates()	176
7.16.2.2	~Gates()	176
7.16.3	Member Function Documentation	177
7.16.3.1	CTRL()	177
7.16.3.2	expandout() [1/3]	177
7.16.3.3	expandout() [2/3]	178
7.16.3.4	expandout() [3/3]	179
7.16.3.5	Fd()	179
7.16.3.6	get_name()	180
7.16.3.7	Id()	180
7.16.3.8	MODMUL()	180
7.16.3.9	Rn()	181
7.16.3.10	RX()	181
7.16.3.11	RY()	182
7.16.3.12	RZ()	182
7.16.3.13	SWAPd()	182

7.16.3.14	Xd()	184
7.16.3.15	Zd()	184
7.16.4	Friends And Related Function Documentation	185
7.16.4.1	internal::Singleton< const Gates >	185
7.16.5	Member Data Documentation	185
7.16.5.1	CNOT	185
7.16.5.2	CNOTba	185
7.16.5.3	CZ	185
7.16.5.4	FRED	185
7.16.5.5	H	186
7.16.5.6	Id2	186
7.16.5.7	S	186
7.16.5.8	SWAP	186
7.16.5.9	T	186
7.16.5.10	TOF	186
7.16.5.11	X	187
7.16.5.12	Y	187
7.16.5.13	Z	187
7.17	qpp::QCircuit::GateStep Struct Reference	187
7.17.1	Detailed Description	188
7.17.2	Constructor & Destructor Documentation	188
7.17.2.1	GateStep() [1/2]	188
7.17.2.2	GateStep() [2/2]	188
7.17.3	Member Data Documentation	189
7.17.3.1	ctrl_	189
7.17.3.2	gate_hash_	189
7.17.3.3	gate_type_	189
7.17.3.4	name_	189
7.17.3.5	target_	190
7.18	qpp::internal::HashEigen Class Reference	190

7.18.1 Detailed Description	190
7.18.2 Member Function Documentation	190
7.18.2.1 operator()	190
7.19 qpp::IDisplay Class Reference	191
7.19.1 Detailed Description	192
7.19.2 Constructor & Destructor Documentation	192
7.19.2.1 IDisplay() [1/3]	192
7.19.2.2 IDisplay() [2/3]	192
7.19.2.3 IDisplay() [3/3]	192
7.19.2.4 ~IDisplay()	192
7.19.3 Member Function Documentation	193
7.19.3.1 display()	193
7.19.3.2 operator=() [1/2]	193
7.19.3.3 operator=() [2/2]	193
7.19.4 Friends And Related Function Documentation	193
7.19.4.1 operator<<	193
7.20 qpp::IJSON Class Reference	194
7.20.1 Detailed Description	194
7.20.2 Constructor & Destructor Documentation	195
7.20.2.1 IJSON() [1/3]	195
7.20.2.2 IJSON() [2/3]	195
7.20.2.3 IJSON() [3/3]	195
7.20.2.4 ~IJSON()	195
7.20.3 Member Function Documentation	195
7.20.3.1 operator=() [1/2]	195
7.20.3.2 operator=() [2/2]	196
7.20.3.3 to_JSON()	196
7.21 qpp::Init Class Reference	196
7.21.1 Detailed Description	197
7.21.2 Constructor & Destructor Documentation	197

7.21.2.1	Init()	197
7.21.2.2	~Init()	198
7.21.3	Friends And Related Function Documentation	198
7.21.3.1	internal::Singleton< const Init >	198
7.22	qpp::exception::InvalidIterator Class Reference	198
7.22.1	Detailed Description	199
7.22.2	Member Function Documentation	199
7.22.2.1	Exception()	199
7.22.2.2	type_description()	200
7.23	qpp::internal::IOManipEigen Class Reference	200
7.23.1	Constructor & Destructor Documentation	201
7.23.1.1	IOManipEigen() [1/2]	201
7.23.1.2	IOManipEigen() [2/2]	202
7.23.2	Member Function Documentation	202
7.23.2.1	display()	202
7.23.3	Member Data Documentation	202
7.23.3.1	A_	202
7.23.3.2	chop_	202
7.24	qpp::internal::IOManipPointer< PointerType > Class Template Reference	203
7.24.1	Constructor & Destructor Documentation	204
7.24.1.1	IOManipPointer() [1/2]	204
7.24.1.2	IOManipPointer() [2/2]	204
7.24.2	Member Function Documentation	204
7.24.2.1	display()	204
7.24.2.2	operator=()	205
7.24.3	Member Data Documentation	205
7.24.3.1	end_	205
7.24.3.2	N_	205
7.24.3.3	p_	205
7.24.3.4	separator_	205

7.24.3.5	<code>start_</code>	205
7.25	<code>qpp::internal::IOManipRange< InputIterator ></code> Class Template Reference	206
7.25.1	Constructor & Destructor Documentation	207
7.25.1.1	<code>IOManipRange()</code> [1/2]	207
7.25.1.2	<code>IOManipRange()</code> [2/2]	207
7.25.2	Member Function Documentation	207
7.25.2.1	<code>display()</code>	207
7.25.2.2	<code>operator=()</code>	208
7.25.3	Member Data Documentation	208
7.25.3.1	<code>end_</code>	208
7.25.3.2	<code>first_</code>	208
7.25.3.3	<code>last_</code>	208
7.25.3.4	<code>separator_</code>	208
7.25.3.5	<code>start_</code>	208
7.26	<code>qpp::is_complex< T ></code> Struct Template Reference	209
7.26.1	Detailed Description	209
7.27	<code>qpp::is_complex< std::complex< T > ></code> Struct Template Reference	210
7.27.1	Detailed Description	210
7.28	<code>qpp::is_iterable< T, typename ></code> Struct Template Reference	211
7.28.1	Detailed Description	211
7.29	<code>qpp::is_iterable< T, to_void< decltype(std::declval< T >().begin()), decltype(std::declval< T >().end()), decltype(*(std::declval< T >().begin()))> ></code> Struct Template Reference	212
7.29.1	Detailed Description	213
7.30	<code>qpp::is_matrix_expression< Derived ></code> Struct Template Reference	213
7.30.1	Detailed Description	213
7.31	<code>qpp::QCircuit::iterator</code> Class Reference	214
7.31.1	Detailed Description	215
7.31.2	Member Typedef Documentation	215
7.31.2.1	<code>difference_type</code>	215
7.31.2.2	<code>iterator_category</code>	215
7.31.2.3	<code>pointer</code>	216

7.31.2.4	reference	216
7.31.2.5	value_type	216
7.31.3	Constructor & Destructor Documentation	216
7.31.3.1	iterator() [1/2]	216
7.31.3.2	iterator() [2/2]	216
7.31.4	Member Function Documentation	216
7.31.4.1	operator!==(())	216
7.31.4.2	operator*()	217
7.31.4.3	operator++() [1/2]	217
7.31.4.4	operator++() [2/2]	217
7.31.4.5	operator=()	218
7.31.4.6	operator==(())	218
7.31.4.7	set_begin_()	218
7.31.4.8	set_end_()	218
7.31.5	Member Data Documentation	219
7.31.5.1	elem_	219
7.31.5.2	qc_	219
7.32	qpp::make_void< Ts > Struct Template Reference	219
7.32.1	Detailed Description	219
7.32.2	Member Typedef Documentation	220
7.32.2.1	type	220
7.33	qpp::exception::MatrixMismatchSubsys Class Reference	220
7.33.1	Detailed Description	221
7.33.2	Member Function Documentation	221
7.33.2.1	Exception()	221
7.33.2.2	type_description()	222
7.34	qpp::exception::MatrixNotCvector Class Reference	222
7.34.1	Detailed Description	223
7.34.2	Member Function Documentation	223
7.34.2.1	Exception()	223

7.34.2.2	<code>type_description()</code>	224
7.35	<code>qpp::exception::MatrixNotRvector</code> Class Reference	224
7.35.1	Detailed Description	225
7.35.2	Member Function Documentation	225
7.35.2.1	<code>Exception()</code>	225
7.35.2.2	<code>type_description()</code>	226
7.36	<code>qpp::exception::MatrixNotSquare</code> Class Reference	226
7.36.1	Detailed Description	227
7.36.2	Member Function Documentation	227
7.36.2.1	<code>Exception()</code>	227
7.36.2.2	<code>type_description()</code>	228
7.37	<code>qpp::exception::MatrixNotSquareNorCvector</code> Class Reference	228
7.37.1	Detailed Description	229
7.37.2	Member Function Documentation	229
7.37.2.1	<code>Exception()</code>	229
7.37.2.2	<code>type_description()</code>	230
7.38	<code>qpp::exception::MatrixNotSquareNorRvector</code> Class Reference	230
7.38.1	Detailed Description	231
7.38.2	Member Function Documentation	231
7.38.2.1	<code>Exception()</code>	231
7.38.2.2	<code>type_description()</code>	232
7.39	<code>qpp::exception::MatrixNotSquareNorVector</code> Class Reference	232
7.39.1	Detailed Description	233
7.39.2	Member Function Documentation	233
7.39.2.1	<code>Exception()</code>	233
7.39.2.2	<code>type_description()</code>	234
7.40	<code>qpp::exception::MatrixNotVector</code> Class Reference	234
7.40.1	Detailed Description	235
7.40.2	Member Function Documentation	235
7.40.2.1	<code>Exception()</code>	235

7.40.2.2	type_description()	236
7.41	qpp::QCircuit::MeasureStep Struct Reference	236
7.41.1	Detailed Description	237
7.41.2	Constructor & Destructor Documentation	237
7.41.2.1	MeasureStep() [1/2]	237
7.41.2.2	MeasureStep() [2/2]	237
7.41.3	Member Data Documentation	238
7.41.3.1	c_reg_	238
7.41.3.2	mats_hash_	238
7.41.3.3	measurement_type_	238
7.41.3.4	name_	238
7.41.3.5	target_	238
7.42	qpp::exception::NoCodeword Class Reference	239
7.42.1	Detailed Description	240
7.42.2	Member Function Documentation	240
7.42.2.1	Exception()	240
7.42.2.2	type_description()	240
7.43	qpp::NoiseBase< T > Class Template Reference	241
7.43.1	Detailed Description	242
7.43.2	Member Typedef Documentation	242
7.43.2.1	noise_type	242
7.43.3	Constructor & Destructor Documentation	243
7.43.3.1	NoiseBase() [1/2]	243
7.43.3.2	NoiseBase() [2/2]	243
7.43.3.3	~NoiseBase()	244
7.43.4	Member Function Documentation	244
7.43.4.1	compute_probs_()	244
7.43.4.2	compute_state_()	244
7.43.4.3	get_d()	245
7.43.4.4	get_Ks()	245

7.43.4.5	get_last_idx()	245
7.43.4.6	get_last_K()	245
7.43.4.7	get_last_p()	246
7.43.4.8	get_probs()	246
7.43.4.9	operator() [1/3]	246
7.43.4.10	operator() [2/3]	246
7.43.4.11	operator() [3/3]	247
7.43.5	Member Data Documentation	247
7.43.5.1	d_	247
7.43.5.2	generated_	248
7.43.5.3	i_	248
7.43.5.4	Ks_	248
7.43.5.5	probs_	248
7.44	qpp::NoiseType Class Reference	248
7.44.1	Detailed Description	249
7.45	qpp::exception::NotBipartite Class Reference	249
7.45.1	Detailed Description	250
7.45.2	Member Function Documentation	250
7.45.2.1	Exception()	250
7.45.2.2	type_description()	251
7.46	qpp::exception::NotImplemented Class Reference	251
7.46.1	Detailed Description	252
7.46.2	Member Function Documentation	252
7.46.2.1	Exception()	252
7.46.2.2	type_description()	253
7.47	qpp::exception::NotQubitCvector Class Reference	253
7.47.1	Detailed Description	254
7.47.2	Member Function Documentation	254
7.47.2.1	Exception()	254
7.47.2.2	type_description()	255

7.48	qpp::exception::NotQubitMatrix Class Reference	255
7.48.1	Detailed Description	256
7.48.2	Member Function Documentation	256
7.48.2.1	Exception()	256
7.48.2.2	type_description()	257
7.49	qpp::exception::NotQubitRvector Class Reference	257
7.49.1	Detailed Description	258
7.49.2	Member Function Documentation	258
7.49.2.1	Exception()	258
7.49.2.2	type_description()	259
7.50	qpp::exception::NotQubitSubsys Class Reference	259
7.50.1	Detailed Description	260
7.50.2	Member Function Documentation	260
7.50.2.1	Exception()	260
7.50.2.2	type_description()	261
7.51	qpp::exception::NotQubitVector Class Reference	261
7.51.1	Detailed Description	262
7.51.2	Member Function Documentation	262
7.51.2.1	Exception()	262
7.51.2.2	type_description()	263
7.52	qpp::exception::OutOfRange Class Reference	263
7.52.1	Detailed Description	264
7.52.2	Member Function Documentation	264
7.52.2.1	Exception()	264
7.52.2.2	type_description()	265
7.53	qpp::exception::PermInvalid Class Reference	265
7.53.1	Detailed Description	266
7.53.2	Member Function Documentation	266
7.53.2.1	Exception()	266
7.53.2.2	type_description()	267

7.54	qpp::exception::PermMismatchDims Class Reference	267
7.54.1	Detailed Description	268
7.54.2	Member Function Documentation	268
7.54.2.1	Exception()	268
7.54.2.2	type_description()	269
7.55	qpp::QCCircuit Class Reference	269
7.55.1	Detailed Description	274
7.55.2	Member Typedef Documentation	274
7.55.2.1	const_iterator	274
7.55.3	Member Enumeration Documentation	274
7.55.3.1	GateType	274
7.55.3.2	MeasureType	275
7.55.3.3	StepType	275
7.55.4	Constructor & Destructor Documentation	275
7.55.4.1	QCCircuit()	275
7.55.4.2	~QCCircuit()	276
7.55.5	Member Function Documentation	276
7.55.5.1	add_hash_()	276
7.55.5.2	begin() [1/2]	276
7.55.5.3	begin() [2/2]	277
7.55.5.4	cbegin()	277
7.55.5.5	cCTRL() [1/4]	277
7.55.5.6	cCTRL() [2/4]	278
7.55.5.7	cCTRL() [3/4]	278
7.55.5.8	cCTRL() [4/4]	278
7.55.5.9	cCTRL_custom()	279
7.55.5.10	cend()	279
7.55.5.11	CTRL() [1/4]	280
7.55.5.12	CTRL() [2/4]	280
7.55.5.13	CTRL() [3/4]	281

7.55.5.14 CTRL() [4/4]	281
7.55.5.15 CTRL_custom()	282
7.55.5.16 display()	282
7.55.5.17 end() [1/2]	283
7.55.5.18 end() [2/2]	283
7.55.5.19 gate() [1/3]	283
7.55.5.20 gate() [2/3]	283
7.55.5.21 gate() [3/3]	284
7.55.5.22 gate_custom()	284
7.55.5.23 gate_fan() [1/3]	285
7.55.5.24 gate_fan() [2/3]	285
7.55.5.25 gate_fan() [3/3]	286
7.55.5.26 get_cmat_hash_tbl_()	286
7.55.5.27 get_d()	286
7.55.5.28 get_gate_count() [1/2]	287
7.55.5.29 get_gate_count() [2/2]	287
7.55.5.30 get_gate_depth() [1/2]	287
7.55.5.31 get_gate_depth() [2/2]	287
7.55.5.32 get_gates_()	288
7.55.5.33 get_measured() [1/2]	288
7.55.5.34 get_measured() [2/2]	288
7.55.5.35 get_measurement_count() [1/2]	289
7.55.5.36 get_measurement_count() [2/2]	289
7.55.5.37 get_measurements_()	289
7.55.5.38 get_name()	289
7.55.5.39 get_nc()	290
7.55.5.40 get_non_measured()	290
7.55.5.41 get_nop_count()	290
7.55.5.42 get_nq()	290
7.55.5.43 get_step_count()	291

7.55.5.44	measureV() [1/2]	291
7.55.5.45	measureV() [2/2]	291
7.55.5.46	measureZ()	292
7.55.5.47	nop()	292
7.55.5.48	QFT() [1/3]	292
7.55.5.49	QFT() [2/3]	293
7.55.5.50	QFT() [3/3]	293
7.55.5.51	TFQ() [1/3]	294
7.55.5.52	TFQ() [2/3]	294
7.55.5.53	TFQ() [3/3]	294
7.55.5.54	to_JSON()	295
7.55.6	Friends And Related Function Documentation	295
7.55.6.1	operator<< [1/4]	295
7.55.6.2	operator<< [2/4]	296
7.55.6.3	operator<< [3/4]	296
7.55.6.4	operator<< [4/4]	296
7.55.6.5	QEngine	297
7.55.7	Member Data Documentation	297
7.55.7.1	cmat_hash_tbl_	297
7.55.7.2	count_	297
7.55.7.3	d_	297
7.55.7.4	depth_	297
7.55.7.5	gates_	298
7.55.7.6	measured_	298
7.55.7.7	measurement_count_	298
7.55.7.8	measurements_	298
7.55.7.9	name_	298
7.55.7.10	nc_	298
7.55.7.11	nq_	299
7.55.7.12	step_types_	299

7.56	qpp::QEngine Class Reference	299
7.56.1	Detailed Description	301
7.56.2	Constructor & Destructor Documentation	301
7.56.2.1	QEngine() [1/3]	302
7.56.2.2	QEngine() [2/3]	302
7.56.2.3	QEngine() [3/3]	302
7.56.2.4	~QEngine()	302
7.56.3	Member Function Documentation	303
7.56.3.1	display()	303
7.56.3.2	execute() [1/2]	303
7.56.3.3	execute() [2/2]	303
7.56.3.4	get_circuit()	304
7.56.3.5	get_dit()	304
7.56.3.6	get_dits()	304
7.56.3.7	get_measured() [1/2]	305
7.56.3.8	get_measured() [2/2]	305
7.56.3.9	get_non_measured()	305
7.56.3.10	get_probs()	306
7.56.3.11	get_psi()	306
7.56.3.12	get_relative_pos_()	306
7.56.3.13	operator=()	307
7.56.3.14	reset()	307
7.56.3.15	set_dit()	307
7.56.3.16	set_measured_()	307
7.56.3.17	set_psi()	308
7.56.3.18	to_JSON()	308
7.56.4	Member Data Documentation	309
7.56.4.1	dits_	309
7.56.4.2	probs_	309
7.56.4.3	psi_	309

7.56.4.4	qc_	309
7.56.4.5	subsys_	309
7.57	qpp::QNoisyEngine< NoiseModel > Class Template Reference	310
7.57.1	Detailed Description	311
7.57.2	Constructor & Destructor Documentation	311
7.57.2.1	QNoisyEngine()	311
7.57.3	Member Function Documentation	312
7.57.3.1	execute() [1/2]	312
7.57.3.2	execute() [2/2]	312
7.57.3.3	get_noise_results()	312
7.57.4	Member Data Documentation	313
7.57.4.1	noise_	313
7.57.4.2	noise_results_	313
7.58	qpp::QubitAmplitudeDampingNoise Class Reference	313
7.58.1	Detailed Description	314
7.58.2	Constructor & Destructor Documentation	314
7.58.2.1	QubitAmplitudeDampingNoise()	314
7.59	qpp::QubitBitFlipNoise Class Reference	315
7.59.1	Detailed Description	316
7.59.2	Constructor & Destructor Documentation	316
7.59.2.1	QubitBitFlipNoise()	316
7.60	qpp::QubitBitPhaseFlipNoise Class Reference	316
7.60.1	Detailed Description	317
7.60.2	Constructor & Destructor Documentation	317
7.60.2.1	QubitBitPhaseFlipNoise()	317
7.61	qpp::QubitDepolarizingNoise Class Reference	318
7.61.1	Detailed Description	319
7.61.2	Constructor & Destructor Documentation	319
7.61.2.1	QubitDepolarizingNoise()	319
7.62	qpp::QubitPhaseDampingNoise Class Reference	319

7.62.1 Detailed Description	320
7.62.2 Constructor & Destructor Documentation	320
7.62.2.1 QubitPhaseDampingNoise()	320
7.63 qpp::QubitPhaseFlipNoise Class Reference	321
7.63.1 Detailed Description	322
7.63.2 Constructor & Destructor Documentation	322
7.63.2.1 QubitPhaseFlipNoise()	322
7.64 qpp::exception::QuditAlreadyMeasured Class Reference	322
7.64.1 Detailed Description	323
7.64.2 Member Function Documentation	323
7.64.2.1 Exception()	323
7.64.2.2 type_description()	324
7.65 qpp::QuditDepolarizingNoise Class Reference	324
7.65.1 Detailed Description	325
7.65.2 Constructor & Destructor Documentation	325
7.65.2.1 QuditDepolarizingNoise()	325
7.65.3 Member Function Documentation	326
7.65.3.1 fill_Ks_()	326
7.65.3.2 fill_probs_()	326
7.66 qpp::RandomDevices Class Reference	327
7.66.1 Detailed Description	328
7.66.2 Constructor & Destructor Documentation	328
7.66.2.1 RandomDevices()	328
7.66.2.2 ~RandomDevices()	329
7.66.3 Member Function Documentation	329
7.66.3.1 get_prng()	329
7.66.3.2 load()	329
7.66.3.3 save()	329
7.66.4 Friends And Related Function Documentation	330
7.66.4.1 internal::Singleton< RandomDevices >	330

7.66.5	Member Data Documentation	330
7.66.5.1	prng_	330
7.66.5.2	rd_	330
7.67	qpp::internal::Singleton< T > Class Template Reference	330
7.67.1	Detailed Description	331
7.67.2	Constructor & Destructor Documentation	331
7.67.2.1	Singleton() [1/2]	332
7.67.2.2	Singleton() [2/2]	332
7.67.2.3	~Singleton()	332
7.67.3	Member Function Documentation	332
7.67.3.1	get_instance()	332
7.67.3.2	get_thread_local_instance()	332
7.67.3.3	operator=()	332
7.68	qpp::exception::SizeMismatch Class Reference	333
7.68.1	Detailed Description	334
7.68.2	Member Function Documentation	334
7.68.2.1	Exception()	334
7.68.2.2	type_description()	334
7.69	qpp::NoiseType::StateDependent Class Reference	335
7.69.1	Detailed Description	335
7.70	qpp::NoiseType::StateIndependent Class Reference	335
7.70.1	Detailed Description	335
7.71	qpp::States Class Reference	335
7.71.1	Detailed Description	337
7.71.2	Constructor & Destructor Documentation	338
7.71.2.1	States()	338
7.71.2.2	~States()	338
7.71.3	Member Function Documentation	338
7.71.3.1	jn()	338
7.71.3.2	mes()	338

7.71.3.3	minus()	339
7.71.3.4	one()	339
7.71.3.5	plus()	340
7.71.3.6	zero()	340
7.71.4	Friends And Related Function Documentation	340
7.71.4.1	internal::Singleton< const States >	340
7.71.5	Member Data Documentation	340
7.71.5.1	b00	341
7.71.5.2	b01	341
7.71.5.3	b10	341
7.71.5.4	b11	341
7.71.5.5	GHZ	341
7.71.5.6	pb00	341
7.71.5.7	pb01	342
7.71.5.8	pb10	342
7.71.5.9	pb11	342
7.71.5.10	pGHZ	342
7.71.5.11	pW	342
7.71.5.12	px0	342
7.71.5.13	px1	343
7.71.5.14	py0	343
7.71.5.15	py1	343
7.71.5.16	pz0	343
7.71.5.17	pz1	343
7.71.5.18	W	343
7.71.5.19	x0	344
7.71.5.20	x1	344
7.71.5.21	y0	344
7.71.5.22	y1	344
7.71.5.23	z0	344

7.71.5.24 z1	344
7.72 qpp::exception::SubsysMismatchDims Class Reference	345
7.72.1 Detailed Description	346
7.72.2 Member Function Documentation	346
7.72.2.1 Exception()	346
7.72.2.2 type_description()	346
7.73 qpp::Timer< T, CLOCK_T > Class Template Reference	347
7.73.1 Detailed Description	348
7.73.2 Constructor & Destructor Documentation	348
7.73.2.1 Timer() [1/3]	348
7.73.2.2 Timer() [2/3]	349
7.73.2.3 Timer() [3/3]	349
7.73.2.4 ~Timer()	349
7.73.3 Member Function Documentation	349
7.73.3.1 display()	349
7.73.3.2 get_duration()	350
7.73.3.3 operator=() [1/2]	350
7.73.3.4 operator=() [2/2]	350
7.73.3.5 tic()	351
7.73.3.6 tics()	351
7.73.3.7 toc()	351
7.73.4 Member Data Documentation	351
7.73.4.1 end_	351
7.73.4.2 start_	352
7.74 qpp::exception::TypeMismatch Class Reference	352
7.74.1 Detailed Description	353
7.74.2 Member Function Documentation	353
7.74.2.1 Exception()	353
7.74.2.2 type_description()	354
7.75 qpp::exception::UndefinedType Class Reference	354

7.75.1 Detailed Description	355
7.75.2 Member Function Documentation	355
7.75.2.1 Exception()	355
7.75.2.2 type_description()	356
7.76 qpp::exception::Unknown Class Reference	356
7.76.1 Detailed Description	357
7.76.2 Member Function Documentation	357
7.76.2.1 Exception()	357
7.76.2.2 type_description()	358
7.77 qpp::QCircuit::iterator::value_type_ Class Reference	358
7.77.1 Detailed Description	359
7.77.2 Constructor & Destructor Documentation	359
7.77.2.1 value_type_() [1/2]	359
7.77.2.2 value_type_() [2/2]	360
7.77.3 Member Function Documentation	360
7.77.3.1 display()	360
7.77.3.2 operator=()	360
7.77.4 Member Data Documentation	360
7.77.4.1 gates_ip_	361
7.77.4.2 ip_	361
7.77.4.3 measurements_ip_	361
7.77.4.4 type_	361
7.77.4.5 value_type_qc_	361
7.78 qpp::exception::ZeroSize Class Reference	362
7.78.1 Detailed Description	363
7.78.2 Member Function Documentation	363
7.78.2.1 Exception()	363
7.78.2.2 type_description()	363

8	File Documentation	365
8.1	classes/circuits/circuits.h File Reference	365
8.1.1	Detailed Description	366
8.2	classes/circuits/engines.h File Reference	366
8.2.1	Detailed Description	366
8.3	classes/codes.h File Reference	367
8.3.1	Detailed Description	367
8.4	classes/exception.h File Reference	367
8.4.1	Detailed Description	369
8.5	classes/gates.h File Reference	369
8.5.1	Detailed Description	370
8.6	classes/ideisplay.h File Reference	370
8.6.1	Detailed Description	371
8.7	classes/init.h File Reference	371
8.7.1	Detailed Description	371
8.8	classes/noise.h File Reference	372
8.8.1	Detailed Description	372
8.9	classes/random_devices.h File Reference	373
8.9.1	Detailed Description	373
8.10	classes/reversible.h File Reference	373
8.10.1	Detailed Description	374
8.11	classes/states.h File Reference	374
8.11.1	Detailed Description	375
8.12	classes/timer.h File Reference	375
8.12.1	Detailed Description	375
8.13	constants.h File Reference	376
8.13.1	Detailed Description	377
8.14	entanglement.h File Reference	377
8.14.1	Detailed Description	378
8.15	entropies.h File Reference	378

8.15.1 Detailed Description	379
8.16 experimental/experimental.h File Reference	380
8.16.1 Detailed Description	380
8.17 functions.h File Reference	380
8.17.1 Detailed Description	385
8.18 input_output.h File Reference	385
8.18.1 Detailed Description	386
8.19 instruments.h File Reference	386
8.19.1 Detailed Description	387
8.20 internal/classes/iomanip.h File Reference	387
8.20.1 Detailed Description	388
8.21 internal/classes/singleton.h File Reference	388
8.21.1 Detailed Description	389
8.22 internal/util.h File Reference	389
8.22.1 Detailed Description	390
8.23 MATLAB/matlab.h File Reference	391
8.23.1 Detailed Description	391
8.24 number_theory.h File Reference	391
8.24.1 Detailed Description	393
8.25 operations.h File Reference	393
8.25.1 Detailed Description	395
8.26 qpp.h File Reference	395
8.26.1 Detailed Description	397
8.26.2 Macro Definition Documentation	397
8.26.2.1 QPP_UNUSED_	397
8.27 random.h File Reference	397
8.27.1 Detailed Description	399
8.28 statistics.h File Reference	399
8.28.1 Detailed Description	400
8.29 traits.h File Reference	400
8.29.1 Detailed Description	401
8.30 types.h File Reference	401
8.30.1 Detailed Description	402
8.31 /Users/vlad/qpp/README.md File Reference	402

Chapter 1

Quantum++

Version 1.2 - 10 February 2019

Build status:

Chat (questions/issues)

About

Quantum++ is a modern C++11 general purpose quantum computing library, composed solely of template header files. Quantum++ is written in standard C++11 and has very low external dependencies, using only the [Eigen 3](#) linear algebra header-only template library and, if available, the [OpenMP](#) multi-processing library.

Quantum++ is not restricted to qubit systems or specific quantum information processing tasks, being capable of simulating arbitrary quantum processes. The main design factors taken in consideration were the ease of use, high portability, and high performance. The library's simulation capabilities are only restricted by the amount of available physical memory. On a typical machine (Intel i5 8Gb RAM) Quantum++ can successfully simulate the evolution of 25 qubits in a pure state or of 12 qubits in a mixed state reasonably fast.

To report any bugs or ask for additional features/enhancements, please [submit an issue](#) with an appropriate label.

If you are interesting in contributing to this project, feel free to contact me. Alternatively, create a custom branch, add your contribution, then finally create a pull request. If I accept the pull request, I will merge your custom branch with the latest development branch. The latter will eventually be merged into a future release version. To contribute, you need to have a solid knowledge of C++ (preferably C++11), including templates and the standard library, a basic knowledge of quantum computing and linear algebra, and working experience with [Eigen 3](#).

For additional [Eigen 3](#) documentation see <http://eigen.tuxfamily.org/dox/>. For a simple [Eigen 3](#) quick ASCII reference see <http://eigen.tuxfamily.org/dox/AsciiQuickReference.txt>.

Copyright (c) 2013 - 2019 Vlad Gheorghiu, vgheorgh AT gmail DOT com.

License

[Quantum++](#) is distributed under the MIT license. Please see the [LICENSE](#) file for more details.

Installation instructions and further documentation

Please see the installation guide <https://github.com/vsoftco/qpp/blob/master/INSTALL.md> "INSTALL.md" and the comprehensive [Wiki](#) for further documentation and detailed examples.

The official API documentation is available in PDF and HTML formats in the [doc](#) folder.

Chapter 2

Namespace Index

2.1 Namespace List

Here is a list of all namespaces with brief descriptions:

qpp	Quantum++ main namespace	15
qpp::exception	Quantum++ exception hierarchy namespace	118
qpp::experimental	Experimental/test functions/classes, do not use or modify	120
qpp::internal	Internal utility functions, do not use them directly or modify them	120
qpp::literals	127

Chapter 3

Hierarchical Index

3.1 Class Hierarchy

This inheritance list is sorted roughly, but not completely, alphabetically:

qpp::internal::Display_Impl_	154
qpp::internal::IOManipEigen	200
qpp::internal::EqualEigen	168
std::exception	
qpp::exception::Exception	169
qpp::exception::CustomException	139
qpp::exception::DimsInvalid	142
qpp::exception::DimsMismatchCvector	144
qpp::exception::DimsMismatchMatrix	146
qpp::exception::DimsMismatchRvector	148
qpp::exception::DimsMismatchVector	150
qpp::exception::DimsNotEqual	152
qpp::exception::Duplicates	155
qpp::exception::InvalidIterator	198
qpp::exception::MatrixMismatchSubsys	220
qpp::exception::MatrixNotCvector	222
qpp::exception::MatrixNotRvector	224
qpp::exception::MatrixNotSquare	226
qpp::exception::MatrixNotSquareNorCvector	228
qpp::exception::MatrixNotSquareNorRvector	230
qpp::exception::MatrixNotSquareNorVector	232
qpp::exception::MatrixNotVector	234
qpp::exception::NoCodeword	239
qpp::exception::NotBipartite	249
qpp::exception::NotImplemented	251
qpp::exception::NotQubitCvector	253
qpp::exception::NotQubitMatrix	255
qpp::exception::NotQubitRvector	257
qpp::exception::NotQubitSubsys	259
qpp::exception::NotQubitVector	261
qpp::exception::OutOfRange	263
qpp::exception::PermInvalid	265
qpp::exception::PermMismatchDims	267
qpp::exception::QuditAlreadyMeasured	322
qpp::exception::SizeMismatch	333

qpp::exception::SubsysMismatchDims	345
qpp::exception::TypeMismatch	352
qpp::exception::UndefinedType	354
qpp::exception::Unknown	356
qpp::exception::ZeroSize	362
false_type	
qpp::is_complex< T >	209
qpp::is_iterable< T, typename >	211
qpp::Bit_circuit::Gate_count	172
qpp::QCircuit::GateStep	187
qpp::internal::HashEigen	190
qpp::IDisplay	191
qpp::Dynamic_bitset	157
qpp::Bit_circuit	131
qpp::internal::IOManipEigen	200
qpp::internal::IOManipPointer< PointerType >	203
qpp::internal::IOManipRange< InputIterator >	206
qpp::QCircuit	269
qpp::QCircuit::iterator::value_type_	358
qpp::QEngine	299
qpp::QNoisyEngine< NoiseModel >	310
qpp::Timer< T, CLOCK_T >	347
qpp::IJSON	194
qpp::QCircuit	269
qpp::QEngine	299
is_base_of	
qpp::is_matrix_expression< Derived >	213
qpp::QCircuit::iterator	214
qpp::make_void< Ts >	219
qpp::QCircuit::MeasureStep	236
qpp::NoiseBase< T >	241
qpp::NoiseBase< NoiseType::StateDependent >	241
qpp::QubitAmplitudeDampingNoise	313
qpp::QubitPhaseDampingNoise	319
qpp::NoiseBase< NoiseType::StateIndependent >	241
qpp::QubitBitFlipNoise	315
qpp::QubitBitPhaseFlipNoise	316
qpp::QubitDepolarizingNoise	318
qpp::QubitPhaseFlipNoise	321
qpp::QuditDepolarizingNoise	324
qpp::NoiseType	248
qpp::internal::Singleton< T >	330
qpp::internal::Singleton< const Codes >	330
qpp::Codes	136
qpp::internal::Singleton< const Gates >	330
qpp::Gates	174
qpp::internal::Singleton< const Init >	330
qpp::Init	196
qpp::internal::Singleton< const States >	330
qpp::States	335
qpp::internal::Singleton< RandomDevices >	330
qpp::RandomDevices	327
qpp::NoiseType::StateDependent	335
qpp::NoiseType::StateIndependent	335
true_type	

qpp::is_complex< std::complex< T > >	210
qpp::is_iterable< T, to_void< decltype(std::declval< T >().begin()), decltype(std::declval< T >().end()), decltype(*(std::declval< T >().begin()))> >	212

Chapter 4

Class Index

4.1 Class List

Here are the classes, structs, unions and interfaces with brief descriptions:

qpp::Bit_circuit	Classical reversible circuit simulator	131
qpp::Codes	Const Singleton class that defines quantum error correcting codes	136
qpp::exception::CustomException	Custom exception	139
qpp::exception::DimsInvalid	Invalid dimension(s) exception	142
qpp::exception::DimsMismatchCvector	Dimension(s) mismatch column vector size exception	144
qpp::exception::DimsMismatchMatrix	Dimension(s) mismatch matrix size exception	146
qpp::exception::DimsMismatchRvector	Dimension(s) mismatch row vector size exception	148
qpp::exception::DimsMismatchVector	Dimension(s) mismatch vector size exception	150
qpp::exception::DimsNotEqual	Dimensions not equal exception	152
qpp::internal::Display_Impl_		154
qpp::exception::Duplicates	System (e.g. std::vector) has duplicates exception	155
qpp::Dynamic_bitset	Dynamic bitset class, allows the specification of the number of bits at runtime (unlike std::bitset<N>)	157
qpp::internal::EqualEigen	Functor for comparing Eigen expressions for equality	168
qpp::exception::Exception	Base class for generating Quantum++ custom exceptions	169
qpp::Bit_circuit::Gate_count		172
qpp::Gates	Const Singleton class that implements most commonly used gates	174
qpp::QCircuit::GateStep	One step consisting only of gates/operators in the circuit	187
qpp::internal::HashEigen	Functor for hashing Eigen expressions	190

qpp::IDisplay	Abstract class (interface) that mandates the definition of virtual <code>std::ostream& display(std::ostream& os) const</code>	191
qpp::IJSON	Abstract class (interface) that mandates the definition of very basic JSON serialization support	194
qpp::Init	Const Singleton class that performs additional initializations/cleanups	196
qpp::exception::InvalidIterator	Invalid iterator	198
qpp::internal::IOManipEigen		200
qpp::internal::IOManipPointer< PointerType >		203
qpp::internal::IOManipRange< InputIterator >		206
qpp::is_complex< T >	Checks whether the type is a complex type	209
qpp::is_complex< std::complex< T > >	Checks whether the type is a complex number type, specialization for complex types	210
qpp::is_iterable< T, typename >	Checks whether <i>T</i> is compatible with an STL-like iterable container	211
qpp::is_iterable< T, to_void< decltype(std::declval< T >().begin()), decltype(std::declval< T >().end()), decltype(*(std::declval< T >().begin())) >>	Checks whether <i>T</i> is compatible with an STL-like iterable container, specialization for STL-like iterable containers	212
qpp::is_matrix_expression< Derived >	Checks whether the type is an Eigen matrix expression	213
qpp::QCircuit::iterator	Quantum circuit bound-checking (safe) iterator	214
qpp::make_void< Ts >	Helper for qpp::to_void<> alias template	219
qpp::exception::MatrixMismatchSubsys	Matrix mismatch subsystems exception	220
qpp::exception::MatrixNotCvector	Matrix is not a column vector exception	222
qpp::exception::MatrixNotRvector	Matrix is not a row vector exception	224
qpp::exception::MatrixNotSquare	Matrix is not square exception	226
qpp::exception::MatrixNotSquareNorCvector	Matrix is not square nor column vector exception	228
qpp::exception::MatrixNotSquareNorRvector	Matrix is not square nor row vector exception	230
qpp::exception::MatrixNotSquareNorVector	Matrix is not square nor vector exception	232
qpp::exception::MatrixNotVector	Matrix is not a vector exception	234
qpp::QCircuit::MeasureStep	One step consisting only of measurements in the circuit	236
qpp::exception::NoCodeword	Codeword does not exist exception	239
qpp::NoiseBase< T >	Base class for all noise models, derive your particular noise model	241
qpp::NoiseType	Contains template tags used to specify the noise type	248
qpp::exception::NotBipartite	Not bi-partite exception	249
qpp::exception::NotImplemented	Code not yet implemented	251
qpp::exception::NotQubitCvector	Column vector is not 2 x 1 exception	253

qpp::exception::NotQubitMatrix	
Matrix is not 2 x 2 exception	255
qpp::exception::NotQubitRvector	
Row vector is not 1 x 2 exception	257
qpp::exception::NotQubitSubsys	
Subsystems are not qubits exception	259
qpp::exception::NotQubitVector	
Vector is not 2 x 1 nor 1 x 2 exception	261
qpp::exception::OutOfRange	
Argument out of range exception	263
qpp::exception::PermInvalid	
Invalid permutation exception	265
qpp::exception::PermMismatchDims	
Permutation mismatch dimensions exception	267
qpp::QCCircuit	
Quantum circuit class	269
qpp::QEngine	
Quantum circuit engine, executes qpp::QCCircuit	299
qpp::QNoisyEngine< NoiseModel >	
Noisy quantum circuit engine, executes qpp::QCCircuit	310
qpp::QubitAmplitudeDampingNoise	
Qubit amplitude damping noise, as described in Nielsen and Chuang	313
qpp::QubitBitFlipNoise	
Qubit bit flip noise	315
qpp::QubitBitPhaseFlipNoise	
Qubit bit-phase flip (dephasing) noise	316
qpp::QubitDepolarizingNoise	
Qubit depolarizing noise	318
qpp::QubitPhaseDampingNoise	
Qubit phase damping noise, as described in Nielsen and Chuang	319
qpp::QubitPhaseFlipNoise	
Qubit phase flip (dephasing) noise	321
qpp::exception::QuditAlreadyMeasured	
Qudit was already measured exception	322
qpp::QuditDepolarizingNoise	
Qudit depolarizing noise	324
qpp::RandomDevices	
Singleton class that manages the source of randomness in the library	327
qpp::internal::Singleton< T >	
Singleton policy class, used internally to implement the singleton pattern via CRTP (Curiously recurring template pattern)	330
qpp::exception::SizeMismatch	
Size mismatch exception	333
qpp::NoiseType::StateDependent	
Template tag, used whenever the noise is state-dependent	335
qpp::NoiseType::StateIndependent	
Template tag, used whenever the noise is state-independent	335
qpp::States	
Const Singleton class that implements most commonly used states	335
qpp::exception::SubsysMismatchDims	
Subsystems mismatch dimensions exception	345
qpp::Timer< T, CLOCK_T >	
Chronometer	347
qpp::exception::TypeMismatch	
Type mismatch exception	352
qpp::exception::UndefinedType	
Not defined for this type exception	354

qpp::exception::Unknown	
Unknown exception	356
qpp::QCircuit::iterator::value_type_	
Value type class for qpp::QCircuit::iterator	358
qpp::exception::ZeroSize	
Object has zero size exception	362

Chapter 5

File Index

5.1 File List

Here is a list of all files with brief descriptions:

constants.h	
Constants	376
entanglement.h	
Entanglement functions	377
entropies.h	
Entropy functions	378
functions.h	
Generic quantum computing functions	380
input_output.h	
Input/output functions	385
instruments.h	
Measurement functions	386
number_theory.h	
Number theory functions	391
operations.h	
Quantum operation functions	393
qpp.h	
Quantum++ main header file, includes all other necessary headers	395
random.h	
Randomness-related functions	397
statistics.h	
Statistics functions	399
traits.h	
Type traits	400
types.h	
Type aliases	401
classes/ codes.h	
Quantum error correcting codes	367
classes/ exception.h	
Exceptions	367
classes/ gates.h	
Quantum gates	369
classes/ display.h	
Display interface via the non-virtual interface (NVI) and very basic JSON serialization support interface	370

classes/ init.h	
Initialization	371
classes/ noise.h	
Noise models	372
classes/ random_devices.h	
Random devices	373
classes/ reversible.h	
Support for classical reversible circuits	373
classes/ states.h	
Quantum states	374
classes/ timer.h	
Timing	375
classes/circuits/ circuits.h	
Qudit quantum circuits	365
classes/circuits/ engines.h	
Qudit quantum engines	366
experimental/ experimental.h	
Experimental/test functions/classes	380
internal/ util.h	
Internal utility functions	389
internal/classes/ iomanip.h	
Input/output manipulators	387
internal/classes/ singleton.h	
Singleton pattern via CRTP	388
MATLAB/ matlab.h	
Input/output interfacing with MATLAB	391

Chapter 6

Namespace Documentation

6.1 qpp Namespace Reference

Quantum++ main namespace.

Namespaces

- [exception](#)
Quantum++ exception hierarchy namespace.
- [experimental](#)
Experimental/test functions/classes, do not use or modify.
- [internal](#)
Internal utility functions, do not use them directly or modify them.
- [literals](#)

Classes

- class [Bit_circuit](#)
Classical reversible circuit simulator.
- class [Codes](#)
const Singleton class that defines quantum error correcting codes
- class [Dynamic_bitset](#)
Dynamic bitset class, allows the specification of the number of bits at runtime (unlike `std::bitset<N>`)
- class [Gates](#)
const Singleton class that implements most commonly used gates
- class [IDisplay](#)
Abstract class (interface) that mandates the definition of virtual `std::ostream& display(std::ostream& os) const`.
- class [IJSON](#)
Abstract class (interface) that mandates the definition of very basic JSON serialization support.
- class [Init](#)
const Singleton class that performs additional initializations/cleanups
- struct [is_complex](#)
Checks whether the type is a complex type.
- struct [is_complex< std::complex< T > >](#)

- Checks whether the type is a complex number type, specialization for complex types.*
- struct [is_iterable](#)
 - Checks whether T is compatible with an STL-like iterable container.*
- struct [is_iterable< T, to_void< decltype\(std::declval< T >\(\).begin\(\)\), decltype\(std::declval< T >\(\).end\(\)\), decltype\(*\(std::declval< T >\(\).begin\(\)\)\)>](#)
 - Checks whether T is compatible with an STL-like iterable container, specialization for STL-like iterable containers.*
- struct [is_matrix_expression](#)
 - Checks whether the type is an Eigen matrix expression.*
- struct [make_void](#)
 - Helper for [qpp::to_void<>](#) alias template.*
- class [NoiseBase](#)
 - Base class for all noise models, derive your particular noise model.*
- class [NoiseType](#)
 - Contains template tags used to specify the noise type.*
- class [QCircuit](#)
 - Quantum circuit class.*
- class [QEngine](#)
 - Quantum circuit engine, executes [qpp::QCircuit](#).*
- class [QNoisyEngine](#)
 - Noisy quantum circuit engine, executes [qpp::QCircuit](#).*
- class [QubitAmplitudeDampingNoise](#)
 - Qubit amplitude damping noise, as described in Nielsen and Chuang.*
- class [QubitBitFlipNoise](#)
 - Qubit bit flip noise.*
- class [QubitBitPhaseFlipNoise](#)
 - Qubit bit-phase flip (dephasing) noise.*
- class [QubitDepolarizingNoise](#)
 - Qubit depolarizing noise.*
- class [QubitPhaseDampingNoise](#)
 - Qubit phase damping noise, as described in Nielsen and Chuang.*
- class [QubitPhaseFlipNoise](#)
 - Qubit phase flip (dephasing) noise.*
- class [QuditDepolarizingNoise](#)
 - Qudit depolarizing noise.*
- class [RandomDevices](#)
 - Singleton class that manages the source of randomness in the library.*
- class [States](#)
 - const Singleton class that implements most commonly used states*
- class [Timer](#)
 - Chronometer.*

Typedefs

- template<typename... Ts>
 - using [to_void](#) = typename [make_void< Ts... >::type](#)
 - Alias template that implements the proposal for [void_t](#).*
- using [idx](#) = std::size_t
 - Non-negative integer index, make sure you use an unsigned type.*
- using [bigint](#) = long long int
 - Big integer.*
- using [cplx](#) = std::complex< double >

- *Complex number in double precision.*
- using `ket` = `Eigen::VectorXcd`
Complex (double precision) dynamic Eigen column vector.
- using `bra` = `Eigen::RowVectorXcd`
Complex (double precision) dynamic Eigen row vector.
- using `cmat` = `Eigen::MatrixXcd`
Complex (double precision) dynamic Eigen matrix.
- using `dmat` = `Eigen::MatrixXd`
Real (double precision) dynamic Eigen matrix.
- template<typename Scalar >
using `dyn_mat` = `Eigen::Matrix< Scalar, Eigen::Dynamic, Eigen::Dynamic >`
Dynamic Eigen matrix over the field specified by Scalar.
- template<typename Scalar >
using `dyn_col_vect` = `Eigen::Matrix< Scalar, Eigen::Dynamic, 1 >`
Dynamic Eigen column vector over the field specified by Scalar.
- template<typename Scalar >
using `dyn_row_vect` = `Eigen::Matrix< Scalar, 1, Eigen::Dynamic >`
Dynamic Eigen row vector over the field specified by Scalar.

Functions

- constexpr `cplx operator"" _i` (long double x) noexcept
User-defined literal for complex $i = \sqrt{-1}$ (real overload)
- `cplx omega` (idx D)
D-th root of unity.
- template<typename Derived >
`dyn_col_vect< double > schmidtcoeffs` (const `Eigen::MatrixBase< Derived >` &A, const `std::vector< idx >` &dims)
Schmidt coefficients of the bi-partite pure state A.
- template<typename Derived >
`dyn_col_vect< double > schmidtcoeffs` (const `Eigen::MatrixBase< Derived >` &A, `idx d=2`)
Schmidt coefficients of the bi-partite pure state A.
- template<typename Derived >
`cmat schmidtA` (const `Eigen::MatrixBase< Derived >` &A, const `std::vector< idx >` &dims)
Schmidt basis on Alice side.
- template<typename Derived >
`cmat schmidtA` (const `Eigen::MatrixBase< Derived >` &A, `idx d=2`)
Schmidt basis on Alice side.
- template<typename Derived >
`cmat schmidtB` (const `Eigen::MatrixBase< Derived >` &A, const `std::vector< idx >` &dims)
Schmidt basis on Bob side.
- template<typename Derived >
`cmat schmidtB` (const `Eigen::MatrixBase< Derived >` &A, `idx d=2`)
Schmidt basis on Bob side.
- template<typename Derived >
`std::vector< double > schmidtprobs` (const `Eigen::MatrixBase< Derived >` &A, const `std::vector< idx >` &dims)
Schmidt probabilities of the bi-partite pure state A.
- template<typename Derived >
`std::vector< double > schmidtprobs` (const `Eigen::MatrixBase< Derived >` &A, `idx d=2`)
Schmidt probabilities of the bi-partite pure state A.

- `template<typename Derived >`
`double entanglement (const Eigen::MatrixBase< Derived > &A, const std::vector< idx > &dims)`
Entanglement of the bi-partite pure state A.
- `template<typename Derived >`
`double entanglement (const Eigen::MatrixBase< Derived > &A, idx d=2)`
Entanglement of the bi-partite pure state A.
- `template<typename Derived >`
`double gconcurrence (const Eigen::MatrixBase< Derived > &A)`
G-concurrence of the bi-partite pure state A.
- `template<typename Derived >`
`double negativity (const Eigen::MatrixBase< Derived > &A, const std::vector< idx > &dims)`
Negativity of the bi-partite mixed state A.
- `template<typename Derived >`
`double negativity (const Eigen::MatrixBase< Derived > &A, idx d=2)`
Negativity of the bi-partite mixed state A.
- `template<typename Derived >`
`double lognegativity (const Eigen::MatrixBase< Derived > &A, const std::vector< idx > &dims)`
Logarithmic negativity of the bi-partite mixed state A.
- `template<typename Derived >`
`double lognegativity (const Eigen::MatrixBase< Derived > &A, idx d=2)`
Logarithmic negativity of the bi-partite mixed state A.
- `template<typename Derived >`
`double concurrence (const Eigen::MatrixBase< Derived > &A)`
Wootters concurrence of the bi-partite qubit mixed state A.
- `template<typename Derived >`
`double entropy (const Eigen::MatrixBase< Derived > &A)`
von-Neumann entropy of the density matrix A
- `double entropy (const std::vector< double > &prob)`
Shannon entropy of the probability distribution prob.
- `template<typename Derived >`
`double renyi (const Eigen::MatrixBase< Derived > &A, double alpha)`
Renyi- α entropy of the density matrix A, for $\alpha \geq 0$.
- `double renyi (const std::vector< double > &prob, double alpha)`
Renyi- α entropy of the probability distribution prob, for $\alpha \geq 0$.
- `template<typename Derived >`
`double tsallis (const Eigen::MatrixBase< Derived > &A, double q)`
Tsallis- q entropy of the density matrix A, for $q \geq 0$.
- `double tsallis (const std::vector< double > &prob, double q)`
Tsallis- q entropy of the probability distribution prob, for $q \geq 0$.
- `template<typename Derived >`
`double qmutualinfo (const Eigen::MatrixBase< Derived > &A, const std::vector< idx > &subsysA, const std::vector< idx > &subsysB, const std::vector< idx > &dims)`
Quantum mutual information between 2 subsystems of a composite system.
- `template<typename Derived >`
`double qmutualinfo (const Eigen::MatrixBase< Derived > &A, const std::vector< idx > &subsysA, const std::vector< idx > &subsysB, idx d=2)`
Quantum mutual information between 2 subsystems of a composite system.
- `template<typename Derived >`
`dyn_mat< typename Derived::Scalar > transpose (const Eigen::MatrixBase< Derived > &A)`
Transpose.
- `template<typename Derived >`
`dyn_mat< typename Derived::Scalar > conjugate (const Eigen::MatrixBase< Derived > &A)`
Complex conjugate.

- `template<typename Derived >`
`dyn_mat< typename Derived::Scalar > adjoint` (const Eigen::MatrixBase< Derived > &A)
Adjoint.
- `template<typename Derived >`
`dyn_mat< typename Derived::Scalar > inverse` (const Eigen::MatrixBase< Derived > &A)
Inverse.
- `template<typename Derived >`
`Derived::Scalar trace` (const Eigen::MatrixBase< Derived > &A)
Trace.
- `template<typename Derived >`
`Derived::Scalar det` (const Eigen::MatrixBase< Derived > &A)
Determinant.
- `template<typename Derived >`
`Derived::Scalar logdet` (const Eigen::MatrixBase< Derived > &A)
Logarithm of the determinant.
- `template<typename Derived >`
`Derived::Scalar sum` (const Eigen::MatrixBase< Derived > &A)
Element-wise sum of A.
- `template<typename Derived >`
`Derived::Scalar prod` (const Eigen::MatrixBase< Derived > &A)
Element-wise product of A.
- `template<typename Derived >`
`double norm` (const Eigen::MatrixBase< Derived > &A)
Frobenius norm.
- `template<typename Derived >`
`dyn_mat< typename Derived::Scalar > normalize` (const Eigen::MatrixBase< Derived > &A)
Normalizes state vector (column or row vector) or density matrix.
- `template<typename Derived >`
`std::pair< dyn_col_vect< cplx >, cmat > eig` (const Eigen::MatrixBase< Derived > &A)
Full eigen decomposition.
- `template<typename Derived >`
`dyn_col_vect< cplx > evals` (const Eigen::MatrixBase< Derived > &A)
Eigenvalues.
- `template<typename Derived >`
`cmat evecs` (const Eigen::MatrixBase< Derived > &A)
Eigenvectors.
- `template<typename Derived >`
`std::pair< dyn_col_vect< double >, cmat > heig` (const Eigen::MatrixBase< Derived > &A)
Full eigen decomposition of Hermitian expression.
- `template<typename Derived >`
`dyn_col_vect< double > hevals` (const Eigen::MatrixBase< Derived > &A)
Hermitian eigenvalues.
- `template<typename Derived >`
`cmat hevects` (const Eigen::MatrixBase< Derived > &A)
Eigenvectors of Hermitian matrix.
- `template<typename Derived >`
`std::tuple< cmat, dyn_col_vect< double >, cmat > svd` (const Eigen::MatrixBase< Derived > &A)
Full singular value decomposition.
- `template<typename Derived >`
`dyn_col_vect< double > svals` (const Eigen::MatrixBase< Derived > &A)
Singular values.
- `template<typename Derived >`
`cmat svdU` (const Eigen::MatrixBase< Derived > &A)

- Left singular vectors.*

 - `template<typename Derived >`
`cmat svdV` (const Eigen::MatrixBase< Derived > &A)
- Right singular vectors.*

 - `template<typename Derived >`
`cmat funm` (const Eigen::MatrixBase< Derived > &A, `cplx`(*f)(const `cplx` &))
- Functional calculus $f(A)$*

 - `template<typename Derived >`
`cmat sqrtm` (const Eigen::MatrixBase< Derived > &A)
- Matrix square root.*

 - `template<typename Derived >`
`cmat absm` (const Eigen::MatrixBase< Derived > &A)
- Matrix absolute value.*

 - `template<typename Derived >`
`cmat expm` (const Eigen::MatrixBase< Derived > &A)
- Matrix exponential.*

 - `template<typename Derived >`
`cmat logm` (const Eigen::MatrixBase< Derived > &A)
- Matrix logarithm.*

 - `template<typename Derived >`
`cmat sinm` (const Eigen::MatrixBase< Derived > &A)
- Matrix sin.*

 - `template<typename Derived >`
`cmat cosm` (const Eigen::MatrixBase< Derived > &A)
- Matrix cos.*

 - `template<typename Derived >`
`cmat spectralpowm` (const Eigen::MatrixBase< Derived > &A, const `cplx` z)
- Matrix power.*

 - `template<typename Derived >`
`dyn_mat< typename Derived::Scalar > powm` (const Eigen::MatrixBase< Derived > &A, `idx` n)
- Fast matrix power based on the SQUARE-AND-MULTIPLY algorithm.*

 - `template<typename Derived >`
`double Schatten` (const Eigen::MatrixBase< Derived > &A, double p)
- Schatten matrix norm.*

 - `template<typename OutputScalar , typename Derived >`
`dyn_mat< OutputScalar > cwise` (const Eigen::MatrixBase< Derived > &A, OutputScalar(*f)(const type-name Derived::Scalar &))
- Functor.*

 - `template<typename T >`
`dyn_mat< typename T::Scalar > kron` (const T &head)
- Kronecker product.*

 - `template<typename T , typename... Args>`
`dyn_mat< typename T::Scalar > kron` (const T &head, const Args &... tail)
- Kronecker product.*

 - `template<typename Derived >`
`dyn_mat< typename Derived::Scalar > kron` (const std::vector< Derived > &As)
- Kronecker product.*

 - `template<typename Derived >`
`dyn_mat< typename Derived::Scalar > kron` (const std::initializer_list< Derived > &As)
- Kronecker product.*

 - `template<typename Derived >`
`dyn_mat< typename Derived::Scalar > kronpow` (const Eigen::MatrixBase< Derived > &A, `idx` n)
- Kronecker power.*

- `template<typename T >`
`dyn_mat< typename T::Scalar > dirsum (const T &head)`
Direct sum.
- `template<typename T , typename... Args>`
`dyn_mat< typename T::Scalar > dirsum (const T &head, const Args &... tail)`
Direct sum.
- `template<typename Derived >`
`dyn_mat< typename Derived::Scalar > dirsum (const std::vector< Derived > &As)`
Direct sum.
- `template<typename Derived >`
`dyn_mat< typename Derived::Scalar > dirsum (const std::initializer_list< Derived > &As)`
Direct sum.
- `template<typename Derived >`
`dyn_mat< typename Derived::Scalar > dirsumpow (const Eigen::MatrixBase< Derived > &A, idx n)`
Direct sum power.
- `template<typename Derived >`
`dyn_mat< typename Derived::Scalar > reshape (const Eigen::MatrixBase< Derived > &A, idx rows, idx cols)`
Reshape.
- `template<typename Derived1 , typename Derived2 >`
`dyn_mat< typename Derived1::Scalar > comm (const Eigen::MatrixBase< Derived1 > &A, const Eigen::MatrixBase< Derived2 > &B)`
Commutator.
- `template<typename Derived1 , typename Derived2 >`
`dyn_mat< typename Derived1::Scalar > anticomm (const Eigen::MatrixBase< Derived1 > &A, const Eigen::MatrixBase< Derived2 > &B)`
Anti-commutator.
- `template<typename Derived >`
`dyn_mat< typename Derived::Scalar > prj (const Eigen::MatrixBase< Derived > &A)`
Projector.
- `template<typename Derived >`
`dyn_mat< typename Derived::Scalar > grams (const std::vector< Derived > &As)`
Gram-Schmidt orthogonalization.
- `template<typename Derived >`
`dyn_mat< typename Derived::Scalar > grams (const std::initializer_list< Derived > &As)`
Gram-Schmidt orthogonalization.
- `template<typename Derived >`
`dyn_mat< typename Derived::Scalar > grams (const Eigen::MatrixBase< Derived > &A)`
Gram-Schmidt orthogonalization.
- `std::vector< idx > n2multiidx (idx n, const std::vector< idx > &dims)`
Non-negative integer index to multi-index.
- `idx multiidx2n (const std::vector< idx > &midx, const std::vector< idx > &dims)`
Multi-index to non-negative integer index.
- `ket mket (const std::vector< idx > &mask, const std::vector< idx > &dims)`
Multi-partite qudit ket.
- `ket mket (const std::vector< idx > &mask, idx d=2)`
Multi-partite qudit ket.
- `cmat mprj (const std::vector< idx > &mask, const std::vector< idx > &dims)`
Projector onto multi-partite qudit ket.
- `cmat mprj (const std::vector< idx > &mask, idx d=2)`
Projector onto multi-partite qudit ket.
- `template<typename InputIterator >`
`std::vector< double > abssq (InputIterator first, InputIterator last)`

Computes the absolute values squared of an STL-like range of complex numbers.

- `template<typename Container >`
`std::vector< double > abssq (const Container &c, typename std::enable_if< is_iterable< Container >::value >::type * = nullptr)`

Computes the absolute values squared of an STL-like container.

- `template<typename Derived >`
`std::vector< double > abssq (const Eigen::MatrixBase< Derived > &A)`

Computes the absolute values squared of an Eigen expression.

- `template<typename InputIterator >`
`std::iterator_traits< InputIterator >::value_type sum (InputIterator first, InputIterator last)`

Element-wise sum of an STL-like range.

- `template<typename Container >`
`Container::value_type sum (const Container &c, typename std::enable_if< is_iterable< Container >::value >::type * = nullptr)`

Element-wise sum of the elements of an STL-like container.

- `template<typename InputIterator >`
`std::iterator_traits< InputIterator >::value_type prod (InputIterator first, InputIterator last)`

Element-wise product of an STL-like range.

- `template<typename Container >`
`Container::value_type prod (const Container &c, typename std::enable_if< is_iterable< Container >::value >::type * = nullptr)`

Element-wise product of the elements of an STL-like container.

- `template<typename Derived >`
`dyn_col_vect< typename Derived::Scalar > rho2pure (const Eigen::MatrixBase< Derived > &A)`

Finds the pure state representation of a matrix proportional to a projector onto a pure state.

- `std::vector< idx > complement (std::vector< idx > subsys, idx n)`

Constructs the complement of a subsystem vector.

- `template<typename Derived >`
`std::vector< double > rho2bloch (const Eigen::MatrixBase< Derived > &A)`

Computes the 3-dimensional real Bloch vector corresponding to the qubit density matrix A.

- `cmat bloch2rho (const std::vector< double > &r)`

Computes the density matrix corresponding to the 3-dimensional real Bloch vector r.

- `template<typename Derived >`
`std::size_t hash_eigen (const Eigen::MatrixBase< Derived > &A, std::size_t seed=0)`

Computes the hash of an Eigen matrix/vector/expression.

- `template<typename Derived >`
`internal::IOManipEigen disp (const Eigen::MatrixBase< Derived > &A, double chop=qpp::chop)`

Eigen expression ostream manipulator.

- `internal::IOManipEigen disp (cplx z, double chop=qpp::chop)`

Complex number ostream manipulator.

- `template<typename InputIterator >`
`internal::IOManipRange< InputIterator > disp (InputIterator first, InputIterator last, const std::string &separator, const std::string &start="[" , const std::string &end="]")`

Range ostream manipulator.

- `template<typename Container >`
`internal::IOManipRange< typename Container::const_iterator > disp (const Container &c, const std::string &separator, const std::string &start="[" , const std::string &end="]", typename std::enable_if< is_iterable< Container >::value >::type * = nullptr)`

Standard container ostream manipulator. The container must support std::begin(), std::end() and forward iteration.

- `template<typename PointerType >`
`internal::IOManipPointer< PointerType > disp (const PointerType *p, idx N, const std::string &separator, const std::string &start="[" , const std::string &end="]")`

C-style pointer ostream manipulator.

- `template<typename Derived >`
`void save (const Eigen::MatrixBase< Derived > &A, const std::string &fname)`
Saves Eigen expression to a binary file (internal format) in double precision.
- `template<typename Derived >`
`dyn_mat< typename Derived::Scalar > load (const std::string &fname)`
Loads Eigen matrix from a binary file (internal format) in double precision.
- `template<typename Derived >`
`dyn_col_vect< typename Derived::Scalar > ip (const Eigen::MatrixBase< Derived > &phi, const Eigen::MatrixBase< Derived > &psi, const std::vector< idx > &subsys, const std::vector< idx > &dims)`
Generalized inner product.
- `template<typename Derived >`
`dyn_col_vect< typename Derived::Scalar > ip (const Eigen::MatrixBase< Derived > &phi, const Eigen::MatrixBase< Derived > &psi, const std::vector< idx > &subsys, idx d=2)`
Generalized inner product.
- `template<typename Derived >`
`std::tuple< idx, std::vector< double >, std::vector< cmat > > measure (const Eigen::MatrixBase< Derived > &A, const std::vector< cmat > &Ks)`
Measures the state vector or density operator A using the set of Kraus operators Ks.
- `template<typename Derived >`
`std::tuple< idx, std::vector< double >, std::vector< cmat > > measure (const Eigen::MatrixBase< Derived > &A, const std::initializer_list< cmat > &Ks)`
Measures the state vector or density matrix A using the set of Kraus operators Ks.
- `template<typename Derived >`
`std::tuple< idx, std::vector< double >, std::vector< cmat > > measure (const Eigen::MatrixBase< Derived > &A, const cmat &U)`
Measures the state vector or density matrix A in the orthonormal basis specified by the unitary matrix U.
- `template<typename Derived >`
`std::tuple< idx, std::vector< double >, std::vector< cmat > > measure (const Eigen::MatrixBase< Derived > &A, const std::vector< cmat > &Ks, const std::vector< idx > &target, const std::vector< idx > &dims)`
Measures the part subsys of the multi-partite state vector or density matrix A using the set of Kraus operators Ks.
- `template<typename Derived >`
`std::tuple< idx, std::vector< double >, std::vector< cmat > > measure (const Eigen::MatrixBase< Derived > &A, const std::initializer_list< cmat > &Ks, const std::vector< idx > &target, const std::vector< idx > &dims)`
Measures the part target of the multi-partite state vector or density matrix A using the set of Kraus operators Ks.
- `template<typename Derived >`
`std::tuple< idx, std::vector< double >, std::vector< cmat > > measure (const Eigen::MatrixBase< Derived > &A, const std::vector< cmat > &Ks, const std::vector< idx > &target, idx d=2)`
Measures the part target of the multi-partite state vector or density matrix A using the set of Kraus operators Ks.
- `template<typename Derived >`
`std::tuple< idx, std::vector< double >, std::vector< cmat > > measure (const Eigen::MatrixBase< Derived > &A, const std::initializer_list< cmat > &Ks, const std::vector< idx > &target, idx d=2)`
Measures the part target of the multi-partite state vector or density matrix A using the set of Kraus operators Ks.
- `template<typename Derived >`
`std::tuple< idx, std::vector< double >, std::vector< cmat > > measure (const Eigen::MatrixBase< Derived > &A, const cmat &V, const std::vector< idx > &target, const std::vector< idx > &dims)`
Measures the part target of the multi-partite state vector or density matrix A in the orthonormal basis or rank-1 projectors specified by the columns of the matrix V.
- `template<typename Derived >`
`std::tuple< idx, std::vector< double >, std::vector< cmat > > measure (const Eigen::MatrixBase< Derived > &A, const cmat &V, const std::vector< idx > &target, idx d=2)`
Measures the part target of the multi-partite state vector or density matrix A in the orthonormal basis or rank-1 projectors specified by the columns of the matrix V.

- `template<typename Derived >`
`std::tuple< std::vector< idx >, double, cmat > measure_seq` (const Eigen::MatrixBase< Derived > &A,
`std::vector< idx > target, std::vector< idx > dims)`
Sequentially measures the part target of the multi-partite state vector or density matrix A in the computational basis.
- `template<typename Derived >`
`std::tuple< std::vector< idx >, double, cmat > measure_seq` (const Eigen::MatrixBase< Derived > &A,
`std::vector< idx > target, idx d=2)`
Sequentially measures the part target of the multi-partite state vector or density matrix A in the computational basis.
- `template<typename Derived >`
`std::enable_if< std::is_same< typename Derived::Scalar, cplx >::value, dyn_mat< cplx > >::type`
`loadMATLAB` (const std::string &mat_file, const std::string &var_name)
Loads a complex Eigen dynamic matrix from a MATLAB .mat file,.
- `template<typename Derived >`
`std::enable_if<!std::is_same< typename Derived::Scalar, cplx >::value, dyn_mat< typename Derived::Scalar > >::type`
`loadMATLAB` (const std::string &mat_file, const std::string &var_name)
Loads a non-complex Eigen dynamic matrix from a MATLAB .mat file,.
- `template<typename Derived >`
`std::enable_if< std::is_same< typename Derived::Scalar, cplx >::value >::type saveMATLAB` (const
Eigen::MatrixBase< Derived > &A, const std::string &mat_file, const std::string &var_name, const std::string &mode)
Saves a complex Eigen dynamic matrix to a MATLAB .mat file,.
- `template<typename Derived >`
`std::enable_if< !std::is_same< typename Derived::Scalar, cplx >::value >::type saveMATLAB` (const
Eigen::MatrixBase< Derived > &A, const std::string &mat_file, const std::string &var_name, const std::string &mode)
Saves a non-complex Eigen dynamic matrix to a MATLAB .mat file,.
- `std::vector< int > x2contfrac` (double x, idx N, idx cut=1e5)
Simple continued fraction expansion.
- `double contfrac2x` (const std::vector< int > &cf, idx N=idx(-1))
Real representation of a simple continued fraction.
- `bigint gcd` (bigint a, bigint b)
Greatest common divisor of two integers.
- `bigint gcd` (const std::vector< bigint > &as)
Greatest common divisor of a list of integers.
- `bigint lcm` (bigint a, bigint b)
Least common multiple of two integers.
- `bigint lcm` (const std::vector< bigint > &as)
Least common multiple of a list of integers.
- `std::vector< idx > invperm` (const std::vector< idx > &perm)
Inverse permutation.
- `std::vector< idx > compperm` (const std::vector< idx > &perm, const std::vector< idx > &sigma)
Compose permutations.
- `std::vector< bigint > factors` (bigint a)
Prime factor decomposition.
- `bigint modmul` (bigint a, bigint b, bigint p)
Modular multiplication without overflow.
- `bigint modpow` (bigint a, bigint n, bigint p)
Fast integer power modulo p based on the SQUARE-AND-MULTIPLY algorithm.
- `std::tuple< bigint, bigint, bigint > egcd` (bigint a, bigint b)
Extended greatest common divisor of two integers.
- `bigint modinv` (bigint a, bigint p)
Modular inverse of a mod p.

- `bool isprime (bigint p, idx k=80)`
Primality test based on the Miller-Rabin's algorithm.
- `bigint randprime (bigint a, bigint b, idx N=1000)`
Generates a random big prime uniformly distributed in the interval [a, b].
- `std::vector< std::pair< int, int > > convergents (const std::vector< int > &cf)`
Convergents.
- `std::vector< std::pair< int, int > > convergents (double x, idx N)`
Convergents.
- `template<typename Derived1 , typename Derived2 >`
`dyn_mat< typename Derived1::Scalar > applyCTRL (const Eigen::MatrixBase< Derived1 > &state, const Eigen::MatrixBase< Derived2 > &A, const std::vector< idx > &ctrl, const std::vector< idx > &target, const std::vector< idx > &dims)`
Applies the controlled-gate A to the part target of the multi-partite state vector or density matrix state.
- `template<typename Derived1 , typename Derived2 >`
`dyn_mat< typename Derived1::Scalar > applyCTRL (const Eigen::MatrixBase< Derived1 > &state, const Eigen::MatrixBase< Derived2 > &A, const std::vector< idx > &ctrl, const std::vector< idx > &target, idx d=2)`
Applies the controlled-gate A to the part target of the multi-partite state vector or density matrix state.
- `template<typename Derived1 , typename Derived2 >`
`dyn_mat< typename Derived1::Scalar > apply (const Eigen::MatrixBase< Derived1 > &state, const Eigen::MatrixBase< Derived2 > &A, const std::vector< idx > &target, const std::vector< idx > &dims)`
Applies the gate A to the part target of the multi-partite state vector or density matrix state.
- `template<typename Derived1 , typename Derived2 >`
`dyn_mat< typename Derived1::Scalar > apply (const Eigen::MatrixBase< Derived1 > &state, const Eigen::MatrixBase< Derived2 > &A, const std::vector< idx > &target, idx d=2)`
Applies the gate A to the part target of the multi-partite state vector or density matrix state.
- `template<typename Derived >`
`cmat apply (const Eigen::MatrixBase< Derived > &A, const std::vector< cmat > &Ks)`
Applies the channel specified by the set of Kraus operators Ks to the density matrix A.
- `template<typename Derived >`
`cmat apply (const Eigen::MatrixBase< Derived > &A, const std::vector< cmat > &Ks, const std::vector< idx > &target, const std::vector< idx > &dims)`
Applies the channel specified by the set of Kraus operators Ks to the part target of the multi-partite density matrix A.
- `template<typename Derived >`
`cmat apply (const Eigen::MatrixBase< Derived > &A, const std::vector< cmat > &Ks, const std::vector< idx > &target, idx d=2)`
Applies the channel specified by the set of Kraus operators Ks to the part target of the multi-partite density matrix A.
- `cmat kraus2super (const std::vector< cmat > &Ks)`
Superoperator matrix.
- `cmat kraus2choi (const std::vector< cmat > &Ks)`
Choi matrix.
- `std::vector< cmat > choi2kraus (const cmat &A)`
Orthogonal Kraus operators from Choi matrix.
- `cmat choi2super (const cmat &A)`
Converts Choi matrix to superoperator matrix.
- `cmat super2choi (const cmat &A)`
Converts superoperator matrix to Choi matrix.
- `template<typename Derived >`
`dyn_mat< typename Derived::Scalar > ptrace1 (const Eigen::MatrixBase< Derived > &A, const std::vector< idx > &dims)`
Partial trace.
- `template<typename Derived >`
`dyn_mat< typename Derived::Scalar > ptrace1 (const Eigen::MatrixBase< Derived > &A, idx d=2)`

Partial trace.

- `template<typename Derived >`
`dyn_mat< typename Derived::Scalar > ptrace2 (const Eigen::MatrixBase< Derived > &A, const std::vector< idx > &dims)`

Partial trace.

- `template<typename Derived >`
`dyn_mat< typename Derived::Scalar > ptrace2 (const Eigen::MatrixBase< Derived > &A, idx d=2)`

Partial trace.

- `template<typename Derived >`
`dyn_mat< typename Derived::Scalar > ptrace (const Eigen::MatrixBase< Derived > &A, const std::vector< idx > &target, const std::vector< idx > &dims)`

Partial trace.

- `template<typename Derived >`
`dyn_mat< typename Derived::Scalar > ptrace (const Eigen::MatrixBase< Derived > &A, const std::vector< idx > &target, idx d=2)`

Partial trace.

- `template<typename Derived >`
`dyn_mat< typename Derived::Scalar > ptranspose (const Eigen::MatrixBase< Derived > &A, const std::vector< idx > &target, const std::vector< idx > &dims)`

Partial transpose.

- `template<typename Derived >`
`dyn_mat< typename Derived::Scalar > ptranspose (const Eigen::MatrixBase< Derived > &A, const std::vector< idx > &target, idx d=2)`

Partial transpose.

- `template<typename Derived >`
`dyn_mat< typename Derived::Scalar > syspermute (const Eigen::MatrixBase< Derived > &A, const std::vector< idx > &perm, const std::vector< idx > &dims)`

Subsystem permutation.

- `template<typename Derived >`
`dyn_mat< typename Derived::Scalar > syspermute (const Eigen::MatrixBase< Derived > &A, const std::vector< idx > &perm, idx d=2)`

Subsystem permutation.

- `template<typename Derived >`
`dyn_mat< typename Derived::Scalar > applyQFT (const Eigen::MatrixBase< Derived > &A, const std::vector< idx > &target, idx d=2, bool swap=true)`

Applies the qudit quantum Fourier transform to the part target of the multi-partite state vector or density matrix A.

- `template<typename Derived >`
`dyn_mat< typename Derived::Scalar > applyTFQ (const Eigen::MatrixBase< Derived > &A, const std::vector< idx > &target, idx d=2, bool swap=true)`

Applies the inverse (adjoint) qudit quantum Fourier transform to the part target of the multi-partite state vector or density matrix A.

- `template<typename Derived >`
`dyn_col_vect< typename Derived::Scalar > TFQ (const Eigen::MatrixBase< Derived > &A, idx d=2, bool swap=true)`

Inverse (adjoint) qudit quantum Fourier transform.

- `template<typename Derived >`
`dyn_col_vect< typename Derived::Scalar > QFT (const Eigen::MatrixBase< Derived > &A, idx d=2, bool swap=true)`

Qudit quantum Fourier transform.

- `double rand (double a, double b)`

Generates a random real number uniformly distributed in the interval [a, b)

- `bigint rand (bigint a, bigint b)`

Generates a random big integer uniformly distributed in the interval [a, b].

- `idx randidx (idx a=std::numeric_limits< idx >::min(), idx b=std::numeric_limits< idx >::max())`

- Generates a random index (idx) uniformly distributed in the interval [a, b].*

 - `template<typename Derived >`
 Derived `rand` (`idx` rows QPP_UNUSED_, `idx` cols QPP_UNUSED_, double `a` QPP_UNUSED_=0, double `b` QPP_UNUSED_=1)
Generates a random matrix with entries uniformly distributed in the interval [a, b]
- `template<>`
`dmat rand` (`idx` rows, `idx` cols, double `a`, double `b`)
Generates a random real matrix with entries uniformly distributed in the interval [a, b], specialization for double matrices (`qpp::dmat`)
- `template<>`
`cmat rand` (`idx` rows, `idx` cols, double `a`, double `b`)
Generates a random complex matrix with entries (both real and imaginary) uniformly distributed in the interval [a, b], specialization for complex matrices (`qpp::cmat`)
- `template<typename Derived >`
 Derived `randn` (`idx` rows QPP_UNUSED_, `idx` cols QPP_UNUSED_, double `mean` QPP_UNUSED_=0, double `sigma` QPP_UNUSED_=1)
Generates a random matrix with entries normally distributed in $N(\text{mean}, \text{sigma})$
- `template<>`
`dmat randn` (`idx` rows, `idx` cols, double `mean`, double `sigma`)
Generates a random real matrix with entries normally distributed in $N(\text{mean}, \text{sigma})$, specialization for double matrices (`qpp::dmat`)
- `template<>`
`cmat randn` (`idx` rows, `idx` cols, double `mean`, double `sigma`)
Generates a random complex matrix with entries (both real and imaginary) normally distributed in $N(\text{mean}, \text{sigma})$, specialization for complex matrices (`qpp::cmat`)
- double `randn` (double `mean`=0, double `sigma`=1)
Generates a random real number (double) normally distributed in $N(\text{mean}, \text{sigma})$
- `cmat randU` (`idx` D=2)
Generates a random unitary matrix.
- `cmat randV` (`idx` Din, `idx` Dout)
Generates a random isometry matrix.
- `std::vector< cmat > randkraus` (`idx` N, `idx` D=2)
Generates a set of random Kraus operators.
- `cmat randH` (`idx` D=2)
Generates a random Hermitian matrix.
- `ket randket` (`idx` D=2)
Generates a random normalized ket (pure state vector)
- `cmat randrho` (`idx` D=2)
Generates a random density matrix.
- `std::vector< idx > randperm` (`idx` N)
Generates a random uniformly distributed permutation.
- `std::vector< double > randprob` (`idx` N)
Generates a random probability vector uniformly distributed over the probability simplex.
- `std::vector< double > uniform` (`idx` N)
Uniform probability distribution vector.
- `std::vector< double > marginalX` (const `dmat` &probXY)
Marginal distribution.
- `std::vector< double > marginalY` (const `dmat` &probXY)
Marginal distribution.
- `template<typename Container >`
 double `avg` (const `std::vector< double >` &prob, const Container &X, `typename std::enable_if< is_iterable< Container >::value >::type` *=`nullptr`)
Average.

- `template<typename Container >`
`double cov (const dmat &probXY, const Container &X, const Container &Y, typename std::enable_if<`
`is_iterable< Container >::value >::type * = nullptr)`
Covariance.
- `template<typename Container >`
`double var (const std::vector< double > &prob, const Container &X, typename std::enable_if< is_iterable<`
`Container >::value >::type * = nullptr)`
Variance.
- `template<typename Container >`
`double sigma (const std::vector< double > &prob, const Container &X, typename std::enable_if<`
`is_iterable< Container >::value >::type * = nullptr)`
Standard deviation.
- `template<typename Container >`
`double cor (const dmat &probXY, const Container &X, const Container &Y, typename std::enable_if<`
`is_iterable< Container >::value >::type * = nullptr)`
Correlation.

Variables

- `constexpr double chop = 1e-10`
Used in `qpp::disp()` for setting to zero numbers that have their absolute value smaller than `qpp::chop`.
- `constexpr idx maxn = 64`
Maximum number of allowed qubits/qudits (subsystems)
- `constexpr double pi = 3.141592653589793238462643383279502884`
 π
- `constexpr double ee = 2.718281828459045235360287471352662497`
Base of natural logarithm, e .
- `constexpr double infy = std::numeric_limits<double>::max()`
Used to denote infinity in double precision.

6.1.1 Detailed Description

Quantum++ main namespace.

6.1.2 Typedef Documentation

6.1.2.1 bigint

```
using qpp::bigint = typedef long long int
```

Big integer.

6.1.2.2 bra

```
using qpp::bra = typedef Eigen::RowVectorXcd
```

Complex (double precision) dynamic Eigen row vector.

6.1.2.3 cmat

```
using qpp::cmat = typedef Eigen::MatrixXcd
```

Complex (double precision) dynamic Eigen matrix.

6.1.2.4 cplx

```
using qpp::cplx = typedef std::complex<double>
```

Complex number in double precision.

6.1.2.5 dmat

```
using qpp::dmat = typedef Eigen::MatrixXd
```

Real (double precision) dynamic Eigen matrix.

6.1.2.6 dyn_col_vect

```
template<typename Scalar >  
using qpp::dyn_col_vect = typedef Eigen::Matrix<Scalar, Eigen::Dynamic, 1>
```

Dynamic Eigen column vector over the field specified by *Scalar*.

Example:

```
// type of colvect is Eigen::Matrix<float, Eigen::Dynamic, 1>  
dyn_col_vect<float> colvect(2);
```

6.1.2.7 dyn_mat

```
template<typename Scalar >  
using qpp::dyn_mat = typedef Eigen::Matrix<Scalar, Eigen::Dynamic, Eigen::Dynamic>
```

Dynamic Eigen matrix over the field specified by *Scalar*.

Example:

```
// type of mat is Eigen::Matrix<float, Eigen::Dynamic, Eigen::Dynamic>  
dyn_mat<float> mat(2, 3);
```

6.1.2.8 dyn_row_vect

```
template<typename Scalar >  
using qpp::dyn_row_vect = typedef Eigen::Matrix<Scalar, 1, Eigen::Dynamic>
```

Dynamic Eigen row vector over the field specified by *Scalar*.

Example:

```
// type of rowvect is Eigen::Matrix<float, 1, Eigen::Dynamic>  
dyn_row_vect<float> rowvect(3);
```

6.1.2.9 idx

```
using qpp::idx = typedef std::size_t
```

Non-negative integer index, make sure you use an unsigned type.

6.1.2.10 ket

```
using qpp::ket = typedef Eigen::VectorXcd
```

Complex (double precision) dynamic Eigen column vector.

6.1.2.11 to_void

```
template<typename... Ts>
using qpp::to_void = typedef typename make_void<Ts...>::type
```

Alias template that implements the proposal for void_t.

See also

<http://www.open-std.org/jtc1/sc22/wg21/docs/papers/2014/n3911>

6.1.3 Function Documentation

6.1.3.1 absm()

```
template<typename Derived >
cmat qpp::absm (
    const Eigen::MatrixBase< Derived > & A )
```

Matrix absolute value.

Parameters

<i>A</i>	Eigen expression
----------	------------------

Returns

Matrix absolute value of *A*

6.1.3.2 abssq() [1/3]

```
template<typename InputIterator >
std::vector<double> qpp::abssq (
    InputIterator first,
    InputIterator last )
```

Computes the absolute values squared of an STL-like range of complex numbers.

Parameters

<i>first</i>	Iterator to the first element of the range
<i>last</i>	Iterator to the last element of the range

Returns

Real vector consisting of the range absolute values squared

6.1.3.3 abssq() [2/3]

```
template<typename Container >
std::vector<double> qpp::abssq (
    const Container & c,
    typename std::enable_if< is\_iterable< Container >::value >::type * = nullptr )
```

Computes the absolute values squared of an STL-like container.

Parameters

<i>c</i>	STL-like container
----------	--------------------

Returns

Real vector consisting of the container's absolute values squared

6.1.3.4 abssq() [3/3]

```
template<typename Derived >
std::vector<double> qpp::abssq (
    const Eigen::MatrixBase< Derived > & A )
```

Computes the absolute values squared of an Eigen expression.

Parameters

<i>A</i>	Eigen expression
----------	------------------

Returns

Real vector consisting of the absolute values squared

6.1.3.5 adjoint()

```
template<typename Derived >
dyn\_mat<typename Derived::Scalar> qpp::adjoint (
    const Eigen::MatrixBase< Derived > & A )
```

Adjoint.

Parameters

<i>A</i>	Eigen expression
----------	------------------

Returns

Adjoint (Hermitian conjugate) of *A*, as a dynamic matrix over the same scalar field as *A*

6.1.3.6 anticomm()

```
template<typename Derived1 , typename Derived2 >
dyn_mat<typename Derived1::Scalar> qpp::anticomm (
    const Eigen::MatrixBase< Derived1 > & A,
    const Eigen::MatrixBase< Derived2 > & B )
```

Anti-commutator.

See also

[qpp::comm\(\)](#)

Anti-commutator $\{A, B\} = AB + BA$. Both *A* and *B* must be Eigen expressions over the same scalar field.

Parameters

<i>A</i>	Eigen expression
<i>B</i>	Eigen expression

Returns

Anti-commutator $AB + BA$, as a dynamic matrix over the same scalar field as *A*

6.1.3.7 apply() [1/5]

```
template<typename Derived1 , typename Derived2 >
dyn_mat<typename Derived1::Scalar> qpp::apply (
    const Eigen::MatrixBase< Derived1 > & state,
    const Eigen::MatrixBase< Derived2 > & A,
    const std::vector< idx > & target,
    const std::vector< idx > & dims )
```

Applies the gate *A* to the part *target* of the multi-partite state vector or density matrix *state*.

Note

The dimension of the gate *A* must match the dimension of *target*

Parameters

<i>state</i>	Eigen expression
<i>A</i>	Eigen expression
<i>target</i>	Subsystem indexes where the gate <i>A</i> is applied
<i>dims</i>	Dimensions of the multi-partite system

Returns

Gate *A* applied to the part *target* of *state*

6.1.3.8 `apply()` [2/5]

```
template<typename Derived1 , typename Derived2 >
dyn_mat<typename Derived1::Scalar> qpp::apply (
    const Eigen::MatrixBase< Derived1 > & state,
    const Eigen::MatrixBase< Derived2 > & A,
    const std::vector< idx > & target,
    idx d = 2 )
```

Applies the gate *A* to the part *target* of the multi-partite state vector or density matrix *state*.

Note

The dimension of the gate *A* must match the dimension of *target*

Parameters

<i>state</i>	Eigen expression
<i>A</i>	Eigen expression
<i>target</i>	Subsystem indexes where the gate <i>A</i> is applied
<i>d</i>	Subsystem dimensions

Returns

Gate *A* applied to the part *target* of *state*

6.1.3.9 `apply()` [3/5]

```
template<typename Derived >
cmat qpp::apply (
    const Eigen::MatrixBase< Derived > & A,
    const std::vector< cmat > & Ks )
```

Applies the channel specified by the set of Kraus operators *Ks* to the density matrix *A*.

Parameters

<i>A</i>	Eigen expression
<i>Ks</i>	Set of Kraus operators

Returns

Output density matrix after the action of the channel

6.1.3.10 `apply()` [4/5]

```
template<typename Derived >
cmat qpp::apply (
    const Eigen::MatrixBase< Derived > & A,
    const std::vector< cmat > & Ks,
    const std::vector< idx > & target,
    const std::vector< idx > & dims )
```

Applies the channel specified by the set of Kraus operators *Ks* to the part *target* of the multi-partite density matrix *A*.

Parameters

<i>A</i>	Eigen expression
<i>Ks</i>	Set of Kraus operators
<i>target</i>	Subsystem indexes where the Kraus operators <i>Ks</i> are applied
<i>dims</i>	Dimensions of the multi-partite system

Returns

Output density matrix after the action of the channel

6.1.3.11 `apply()` [5/5]

```
template<typename Derived >
cmat qpp::apply (
    const Eigen::MatrixBase< Derived > & A,
    const std::vector< cmat > & Ks,
    const std::vector< idx > & target,
    idx d = 2 )
```

Applies the channel specified by the set of Kraus operators *Ks* to the part *target* of the multi-partite density matrix *A*.

Parameters

<i>A</i>	Eigen expression
<i>Ks</i>	Set of Kraus operators
<i>target</i>	Subsystem indexes where the Kraus operators <i>Ks</i> are applied
<i>d</i>	Subsystem dimensions

Returns

Output density matrix after the action of the channel

6.1.3.12 `applyCTRL()` [1/2]

```
template<typename Derived1 , typename Derived2 >
dyn_mat<typename Derived1::Scalar> qpp::applyCTRL (
    const Eigen::MatrixBase< Derived1 > & state,
    const Eigen::MatrixBase< Derived2 > & A,
    const std::vector< idx > & ctrl,
    const std::vector< idx > & target,
    const std::vector< idx > & dims )
```

Applies the controlled-gate *A* to the part *target* of the multi-partite state vector or density matrix *state*.

See also

[qpp::Gates::CTRL\(\)](#)

Note

The dimension of the gate *A* must match the dimension of *target*. Also, all control subsystems in *ctrl* must have the same dimension.

Parameters

<i>state</i>	Eigen expression
<i>A</i>	Eigen expression
<i>ctrl</i>	Control subsystem indexes
<i>target</i>	Subsystem indexes where the gate <i>A</i> is applied
<i>dims</i>	Dimensions of the multi-partite system

Returns

CTRL-A gate applied to the part *target* of *state*

6.1.3.13 `applyCTRL()` [2/2]

```
template<typename Derived1 , typename Derived2 >
dyn_mat<typename Derived1::Scalar> qpp::applyCTRL (
    const Eigen::MatrixBase< Derived1 > & state,
    const Eigen::MatrixBase< Derived2 > & A,
    const std::vector< idx > & ctrl,
    const std::vector< idx > & target,
    idx d = 2 )
```

Applies the controlled-gate *A* to the part *target* of the multi-partite state vector or density matrix *state*.

See also

[qpp::Gates::CTRL\(\)](#)

Note

The dimension of the gate *A* must match the dimension of *target*

Parameters

<i>state</i>	Eigen expression
<i>A</i>	Eigen expression
<i>ctrl</i>	Control subsystem indexes
<i>target</i>	Subsystem indexes where the gate <i>A</i> is applied
<i>d</i>	Subsystem dimensions

Returns

CTRL-A gate applied to the part *target* of *state*

6.1.3.14 `applyQFT()`

```
template<typename Derived >
dyn_mat<typename Derived::Scalar> qpp::applyQFT (
    const Eigen::MatrixBase< Derived > & A,
    const std::vector< idx > & target,
    idx d = 2,
    bool swap = true )
```

Applies the qudit quantum Fourier transform to the part *target* of the multi-partite state vector or density matrix *A*.

Parameters

<i>A</i>	Eigen expression
<i>target</i>	Subsystem indexes where the QFT is applied
<i>d</i>	Subsystem dimensions
<i>swap</i>	Swaps the qubits/qudits at the end (true by default)

Returns

Qudit Quantum Fourier transform applied to the part *target* of *A*

6.1.3.15 applyTFQ()

```
template<typename Derived >
dyn_mat<typename Derived::Scalar> qpp::applyTFQ (
    const Eigen::MatrixBase< Derived > & A,
    const std::vector< idx > & target,
    idx d = 2,
    bool swap = true )
```

Applies the inverse (adjoint) qudit quantum Fourier transform to the part *target* of the multi-partite state vector or density matrix *A*.

Parameters

<i>A</i>	Eigen expression
<i>target</i>	Subsystem indexes where the TFQ is applied
<i>d</i>	Subsystem dimensions
<i>swap</i>	Swaps the qubits/qudits at the end (true by default)

Returns

Inverse (adjoint) qudit Quantum Fourier transform applied to the part *target* of *A*

6.1.3.16 avg()

```
template<typename Container >
double qpp::avg (
    const std::vector< double > & prob,
    const Container & X,
    typename std::enable_if< is_iterable< Container >::value >::type * = nullptr )
```

Average.

Parameters

<i>prob</i>	Real probability vector representing the probability distribution of <i>X</i>
<i>X</i>	Real random variable values represented by an STL-like container

Returns

Average of *X*

6.1.3.17 `bloch2rho()`

```
cmat qpp::bloch2rho (
    const std::vector< double > & r ) [inline]
```

Computes the density matrix corresponding to the 3-dimensional real Bloch vector r .

See also

[qpp::rho2bloch\(\)](#)

Parameters

r	3-dimensional real vector
-----	---------------------------

Returns

Qubit density matrix

6.1.3.18 `choi2kraus()`

```
std::vector<cmat> qpp::choi2kraus (
    const cmat & A ) [inline]
```

Orthogonal Kraus operators from Choi matrix.

See also

[qpp::kraus2choi\(\)](#)

Extracts a set of orthogonal (under Hilbert-Schmidt operator norm) Kraus operators from the Choi matrix A

Note

The Kraus operators satisfy $Tr(K_i^\dagger K_j) = \delta_{ij}$ for all $i \neq j$

Parameters

A	Choi matrix
-----	-------------

Returns

Set of orthogonal Kraus operators

6.1.3.19 `choi2super()`

```
cmat qpp::choi2super (
    const cmat & A ) [inline]
```

Converts Choi matrix to superoperator matrix.

See also

[qpp::super2choi\(\)](#)

Parameters

<i>A</i>	Choi matrix
----------	-------------

Returns

Superoperator matrix

6.1.3.20 `comm()`

```
template<typename Derived1 , typename Derived2 >
dyn_mat<typename Derived1::Scalar> qpp::comm (
    const Eigen::MatrixBase< Derived1 > & A,
    const Eigen::MatrixBase< Derived2 > & B )
```

Commutator.

See also

[qpp::anticomm\(\)](#)

Commutator $[A, B] = AB - BA$. Both A and B must be Eigen expressions over the same scalar field.

Parameters

<i>A</i>	Eigen expression
<i>B</i>	Eigen expression

Returns

Commutator $AB - BA$, as a dynamic matrix over the same scalar field as A

6.1.3.21 complement()

```
std::vector<idx> qpp::complement (
    std::vector< idx > subsys,
    idx n ) [inline]
```

Constructs the complement of a subsystem vector.

Parameters

<i>subsys</i>	Subsystem vector
<i>n</i>	Total number of systems

Returns

Complement of *subsys* with respect to the set $\{0, 1, \dots, n - 1\}$

6.1.3.22 compperm()

```
std::vector<idx> qpp::compperm (
    const std::vector< idx > & perm,
    const std::vector< idx > & sigma ) [inline]
```

Compose permutations.

Parameters

<i>perm</i>	Permutation
<i>sigma</i>	Permutation

Returns

Composition of the permutations $perm \circ sigma = perm(sigma)$

6.1.3.23 concurrence()

```
template<typename Derived >
double qpp::concurrence (
    const Eigen::MatrixBase< Derived > & A )
```

Wootters concurrence of the bi-partite qubit mixed state *A*.

Parameters

<i>A</i>	Eigen expression
----------	------------------

Returns

Wootters concurrence

6.1.3.24 conjugate()

```
template<typename Derived >
dyn_mat<typename Derived::Scalar> qpp::conjugate (
    const Eigen::MatrixBase< Derived > & A )
```

Complex conjugate.

Parameters

<i>A</i>	Eigen expression
----------	------------------

Returns

Complex conjugate of *A*, as a dynamic matrix over the same scalar field as *A*

6.1.3.25 contfrac2x()

```
double qpp::contfrac2x (
    const std::vector< int > & cf,
    idx N = idx(-1) ) [inline]
```

Real representation of a simple continued fraction.

See also

[qpp::x2contfrac\(\)](#)

Note

If *N* is greater than the size of *cf* (by default it is), then all terms in *cf* are considered.

Parameters

<i>cf</i>	Integer vector containing the simple continued fraction expansion
<i>N</i>	Number of terms considered in the continued fraction expansion.

Returns

Real representation of the simple continued fraction

6.1.3.26 `convergents()` [1/2]

```
std::vector<std::pair<int, int> > qpp::convergents (
    const std::vector< int > & cf ) [inline]
```

Convergents.

See also

[qpp::contfrac2x\(\)](#) and [qpp::x2contfrac\(\)](#)

Parameters

<i>cf</i>	Continued fraction
-----------	--------------------

Returns

Vector of convergents pairs (a_k, b_k) that approximate the number represented by the continued fraction

6.1.3.27 `convergents()` [2/2]

```
std::vector<std::pair<int, int> > qpp::convergents (
    double x,
    idx N ) [inline]
```

Convergents.

See also

[qpp::contfrac2x\(\)](#) and [qpp::x2contfrac\(\)](#)

Note

In the continued fraction expansion of x has less terms than N , then the series of convergents is truncated to the number of terms in the continued fraction expansion of x .

Parameters

x	Real number
N	Number of convergents.

Returns

Vector of convergents pairs (a_k, b_k) that approximate the number x

6.1.3.28 cor()

```
template<typename Container >
double qpp::cor (
    const dmat & probXY,
    const Container & X,
    const Container & Y,
    typename std::enable_if< is_iterable< Container >::value >::type * = nullptr )
```

Correlation.

Parameters

<i>probXY</i>	Real matrix representing the joint probability distribution of <i>X</i> and <i>Y</i> in lexicographical order (<i>X</i> labels the rows, <i>Y</i> labels the columns)
<i>X</i>	Real random variable values represented by an STL-like container
<i>Y</i>	Real random variable values represented by an STL-like container

Returns

Correlation of *X* and *Y*

6.1.3.29 cosm()

```
template<typename Derived >
dmat qpp::cosm (
    const Eigen::MatrixBase< Derived > & A )
```

Matrix cos.

Parameters

<i>A</i>	Eigen expression
----------	------------------

Returns

Matrix cosine of *A*

6.1.3.30 cov()

```
template<typename Container >
double qpp::cov (
    const dmat & probXY,
    const Container & X,
    const Container & Y,
    typename std::enable_if< is_iterable< Container >::value >::type * = nullptr )
```

Covariance.

Parameters

<i>probXY</i>	Real matrix representing the joint probability distribution of <i>X</i> and <i>Y</i> in lexicographical order (<i>X</i> labels the rows, <i>Y</i> labels the columns)
<i>X</i>	Real random variable values represented by an STL-like container
<i>Y</i>	Real random variable values represented by an STL-like container

Returns

Covariance of *X* and *Y*

6.1.3.31 `cwise()`

```
template<typename OutputScalar , typename Derived >
dyn_mat<OutputScalar> qpp::cwise (
    const Eigen::MatrixBase< Derived > & A,
    OutputScalar(*) (const typename Derived::Scalar &) f )
```

Functor.

Parameters

<i>A</i>	Eigen expression
<i>f</i>	Pointer-to-function from scalars of <i>A</i> to <i>OutputScalar</i>

Returns

Component-wise $f(A)$, as a dynamic matrix over the *OutputScalar* scalar field

6.1.3.32 `det()`

```
template<typename Derived >
Derived::Scalar qpp::det (
    const Eigen::MatrixBase< Derived > & A )
```

Determinant.

Parameters

<i>A</i>	Eigen expression
----------	------------------

Returns

Determinant of *A*, as a scalar over the same scalar field as *A*. Returns $\pm\infty$ when the determinant overflows/underflows.

6.1.3.33 `dirsum()` [1/4]

```
template<typename T >
dyn_mat<typename T::Scalar> qpp::dirsum (
    const T & head )
```

Direct sum.

See also

[qpp::dirsumpow\(\)](#)

Used to stop the recursion for the variadic template version of [qpp::dirsum\(\)](#)

Parameters

<i>head</i>	Eigen expression
-------------	------------------

Returns

Its argument *head*

6.1.3.34 `dirsum()` [2/4]

```
template<typename T , typename... Args>
dyn_mat<typename T::Scalar> qpp::dirsum (
    const T & head,
    const Args &... tail )
```

Direct sum.

See also

[qpp::dirsumpow\(\)](#)

Parameters

<i>head</i>	Eigen expression
<i>tail</i>	Variadic Eigen expression (zero or more parameters)

Returns

Direct sum of all input parameters, evaluated from left to right, as a dynamic matrix over the same scalar field as its arguments

6.1.3.35 `dirsum()` [3/4]

```
template<typename Derived >
dyn_mat<typename Derived::Scalar> qpp::dirsum (
    const std::vector< Derived > & As )
```

Direct sum.

See also

[qpp::dirsumpow\(\)](#)

Parameters

<i>As</i>	std::vector of Eigen expressions
-----------	----------------------------------

Returns

Direct sum of all elements in *As*, evaluated from left to right, as a dynamic matrix over the same scalar field as its arguments

6.1.3.36 `dirsum()` [4/4]

```
template<typename Derived >
dyn_mat<typename Derived::Scalar> qpp::dirsum (
    const std::initializer_list< Derived > & As )
```

Direct sum.

See also

[qpp::dirsumpow\(\)](#)

Parameters

<i>As</i>	std::initializer_list of Eigen expressions, such as { <i>A1</i> , <i>A2</i> , ... , <i>Ak</i> }
-----------	-------------------------------------------------------------------------------------------------

Returns

Direct sum of all elements in *As*, evaluated from left to right, as a dynamic matrix over the same scalar field as its arguments

6.1.3.37 `dirsumpow()`

```
template<typename Derived >
dyn_mat<typename Derived::Scalar> qpp::dirsumpow (
```

```
const Eigen::MatrixBase< Derived > & A,
idx n )
```

Direct sum power.

See also

[qpp::dirsum\(\)](#)

Parameters

A	Eigen expression
n	Non-negative integer

Returns

Direct sum of A with itself n times $A^{\oplus n}$, as a dynamic matrix over the same scalar field as A

6.1.3.38 `disp()` [1/5]

```
template<typename Derived >
internal::IOManipEigen qpp::disp (
    const Eigen::MatrixBase< Derived > & A,
    double chop = qpp::chop )
```

Eigen expression ostream manipulator.

Parameters

A	Eigen expression
$chop$	Set to zero the elements smaller in absolute value than $chop$

Returns

Instance of [qpp::internal::IOManipEigen](#)

6.1.3.39 `disp()` [2/5]

```
internal::IOManipEigen qpp::disp (
    cplx z,
    double chop = qpp::chop ) [inline]
```

Complex number ostream manipulator.

Parameters

<i>z</i>	Complex number (or any other type implicitly cast-able to <code>std::complex<double></code>)
<i>chop</i>	Set to zero the elements smaller in absolute value than <i>chop</i>

Returns

Instance of [qpp::internal::IOManipEigen](#)

6.1.3.40 `disp()` [3/5]

```
template<typename InputIterator >
internal::IOManipRange<InputIterator> qpp::disp (
    InputIterator first,
    InputIterator last,
    const std::string & separator,
    const std::string & start = "[",
    const std::string & end = "]" )
```

Range ostream manipulator.

Parameters

<i>first</i>	Iterator to the first element of the range
<i>last</i>	Iterator to the last element of the range
<i>separator</i>	Separator
<i>start</i>	Left marking
<i>end</i>	Right marking

Returns

Instance of [qpp::internal::IOManipRange](#)

6.1.3.41 `disp()` [4/5]

```
template<typename Container >
internal::IOManipRange<typename Container::const_iterator> qpp::disp (
    const Container & c,
    const std::string & separator,
    const std::string & start = "[",
    const std::string & end = "]",
    typename std::enable_if< is_iterable< Container >::value >::type * = nullptr )
```

Standard container ostream manipulator. The container must support `std::begin()`, `std::end()` and forward iteration.

Parameters

<i>c</i>	Container
<i>separator</i>	Separator
<i>start</i>	Left marking
<i>end</i>	Right marking

Returns

Instance of [qpp::internal::IOManipRange](#)

6.1.3.42 `disp()` [5/5]

```
template<typename PointerType >
internal::IOManipPointer<PointerType> qpp::disp (
    const PointerType * p,
    idx N,
    const std::string & separator,
    const std::string & start = "[",
    const std::string & end = "]" )
```

C-style pointer ostream manipulator.

Parameters

<i>p</i>	Pointer to the first element
<i>N</i>	Number of elements to be displayed
<i>separator</i>	Separator
<i>start</i>	Left marking
<i>end</i>	Right marking

Returns

Instance of [qpp::internal::IOManipPointer](#)

6.1.3.43 `egcd()`

```
std::tuple<bigint, bigint, bigint> qpp::egcd (
    bigint a,
    bigint b ) [inline]
```

Extended greatest common divisor of two integers.

See also

[qpp::gcd\(\)](#)

Parameters

<i>a</i>	Integer
<i>b</i>	Integer

Returns

Tuple of: 1. Integer m , 2. Integer n , and 3. Non-negative integer $\gcd(a, b)$ such that $ma + nb = \gcd(a, b)$

6.1.3.44 eig()

```
template<typename Derived >
std::pair<dyn_col_vect<cplx>, cmat> qpp::eig (
    const Eigen::MatrixBase< Derived > & A )
```

Full eigen decomposition.

See also

[qpp::heig\(\)](#)

Parameters

<i>A</i>	Eigen expression
----------	------------------

Returns

Pair of: 1. Eigenvalues of A , as a complex dynamic column vector, and 2. Eigenvectors of A , as columns of a complex dynamic matrix

6.1.3.45 entanglement() [1/2]

```
template<typename Derived >
double qpp::entanglement (
    const Eigen::MatrixBase< Derived > & A,
    const std::vector< idx > & dims )
```

Entanglement of the bi-partite pure state A .

Defined as the von-Neumann entropy of the reduced density matrix of one of the subsystems

See also

[qpp::entropy\(\)](#)

Parameters

<i>A</i>	Eigen expression
<i>dims</i>	Dimensions of the bi-partite system

Returns

Entanglement, with the logarithm in base 2

6.1.3.46 entanglement() [2/2]

```
template<typename Derived >
double qpp::entanglement (
    const Eigen::MatrixBase< Derived > & A,
    idx d = 2 )
```

Entanglement of the bi-partite pure state *A*.

Defined as the von-Neumann entropy of the reduced density matrix of one of the subsystems

See also

[qpp::entropy\(\)](#)

Parameters

<i>A</i>	Eigen expression
<i>d</i>	Subsystem dimensions

Returns

Entanglement, with the logarithm in base 2

6.1.3.47 entropy() [1/2]

```
template<typename Derived >
double qpp::entropy (
    const Eigen::MatrixBase< Derived > & A )
```

von-Neumann entropy of the density matrix *A*

Parameters

<i>A</i>	Eigen expression
----------	------------------

Returns

von-Neumann entropy, with the logarithm in base 2

6.1.3.48 entropy() [2/2]

```
double qpp::entropy (
    const std::vector< double > & prob ) [inline]
```

Shannon entropy of the probability distribution *prob*.

Parameters

<i>prob</i>	Real probability vector
-------------	-------------------------

Returns

Shannon entropy, with the logarithm in base 2

6.1.3.49 evals()

```
template<typename Derived >
dyn_col_vect<cplx> qpp::evals (
    const Eigen::MatrixBase< Derived > & A )
```

Eigenvalues.

See also

[qpp::hevals\(\)](#)

Parameters

<i>A</i>	Eigen expression
----------	------------------

Returns

Eigenvalues of *A*, as a complex dynamic column vector

6.1.3.50 evects()

```
template<typename Derived >
cmat qpp::evects (
    const Eigen::MatrixBase< Derived > & A )
```

Eigenvectors.

See also

[qpp::hevects\(\)](#)

Parameters

A	Eigen expression
-----	------------------

Returns

Eigenvectors of A , as columns of a complex dynamic matrix

6.1.3.51 `expm()`

```
template<typename Derived >
cmat qpp::expm (
    const Eigen::MatrixBase< Derived > & A )
```

Matrix exponential.

Parameters

A	Eigen expression
-----	------------------

Returns

Matrix exponential of A

6.1.3.52 `factors()`

```
std::vector<bigint> qpp::factors (
    bigint a ) [inline]
```

Prime factor decomposition.

Note

Runs in $\mathcal{O}(\sqrt{n})$ time complexity

Parameters

a	Integer different from 0, 1 or -1
-----	-----------------------------------

Returns

Integer vector containing the factors

6.1.3.53 funm()

```
template<typename Derived >
cmat qpp::funm (
    const Eigen::MatrixBase< Derived > & A,
    cplx (*) (const cplx &) f )
```

Functional calculus $f(A)$

Parameters

A	Eigen expression
f	Pointer-to-function from complex to complex

Returns

$f(A)$

6.1.3.54 gcd() [1/2]

```
bigint qpp::gcd (
    bigint a,
    bigint b ) [inline]
```

Greatest common divisor of two integers.

See also

[`qpp::lcm\(\)`](#)

Parameters

a	Integer
b	Integer

Returns

Greatest common divisor of a and b

6.1.3.55 gcd() [2/2]

```
bigint qpp::gcd (
    const std::vector< bigint > & as ) [inline]
```

Greatest common divisor of a list of integers.

See also

[qpp::lcm\(\)](#)

Parameters

<i>as</i>	List of integers
-----------	------------------

Returns

Greatest common divisor of all numbers in *as*

6.1.3.56 gconcurrence()

```
template<typename Derived >
double qpp::gconcurrence (
    const Eigen::MatrixBase< Derived > & A )
```

G-concurrence of the bi-partite pure state *A*.

Note

Both local dimensions must be equal

Uses [qpp::logdet\(\)](#) to avoid overflows

See also

[qpp::logdet\(\)](#)

Parameters

<i>A</i>	Eigen expression
----------	------------------

Returns

G-concurrence

6.1.3.57 `grams()` [1/3]

```
template<typename Derived >
dyn_mat<typename Derived::Scalar> qpp::grams (
    const std::vector< Derived > & As )
```

Gram-Schmidt orthogonalization.

Parameters

As	std::vector of Eigen expressions as column vectors
-----------	----------------------------------------------------

Returns

Gram-Schmidt vectors of *As* as columns of a dynamic matrix over the same scalar field as its arguments

6.1.3.58 `grams()` [2/3]

```
template<typename Derived >
dyn_mat<typename Derived::Scalar> qpp::grams (
    const std::initializer_list< Derived > & As )
```

Gram-Schmidt orthogonalization.

Parameters

As	std::initializer_list of Eigen expressions as column vectors
-----------	--------------------------------------------------------------

Returns

Gram-Schmidt vectors of *As* as columns of a dynamic matrix over the same scalar field as its arguments

6.1.3.59 `grams()` [3/3]

```
template<typename Derived >
dyn_mat<typename Derived::Scalar> qpp::grams (
    const Eigen::MatrixBase< Derived > & A )
```

Gram-Schmidt orthogonalization.

Parameters

A	Eigen expression, the input vectors are the columns of <i>A</i>
----------	-----------------------------------------------------------------

Returns

Gram-Schmidt vectors of the columns of A , as columns of a dynamic matrix over the same scalar field as A

6.1.3.60 hash_eigen()

```
template<typename Derived >
std::size_t qpp::hash_eigen (
    const Eigen::MatrixBase< Derived > & A,
    std::size_t seed = 0 )
```

Computes the hash of an Eigen matrix/vector/expression.

Note

Code taken from [boost::hash_combine\(\)](#), see https://www.boost.org/doc/libs/1_69_0/doc/html/hash/reference.html#boost.hash_combine

Parameters

A	Eigen expression
<i>seed</i>	Seed, 0 by default

Returns

Hash of its argument

6.1.3.61 heig()

```
template<typename Derived >
std::pair<dyn_col_vect<double>, cmat> qpp::heig (
    const Eigen::MatrixBase< Derived > & A )
```

Full eigen decomposition of Hermitian expression.

See also

[qpp::eig\(\)](#)

Parameters

A	Eigen expression
-----	------------------

Returns

Pair of: 1. Eigenvalues of A , as a real dynamic column vector, and 2. Eigenvectors of A , as columns of a complex dynamic matrix

6.1.3.62 hevals()

```
template<typename Derived >
dyn_col_vect<double> qpp::hevals (
    const Eigen::MatrixBase< Derived > & A )
```

Hermitian eigenvalues.

See also

[qpp::evals\(\)](#)

Parameters

A	Eigen expression
-----	------------------

Returns

Eigenvalues of Hermitian A , as a real dynamic column vector

6.1.3.63 hevects()

```
template<typename Derived >
cmat qpp::hevects (
    const Eigen::MatrixBase< Derived > & A )
```

Eigenvectors of Hermitian matrix.

See also

[qpp::evects\(\)](#)

Parameters

A	Eigen expression
-----	------------------

Returns

Eigenvectors of Hermitian matrix A , as columns of a complex matrix

6.1.3.64 `inverse()`

```
template<typename Derived >
dyn_mat<typename Derived::Scalar> qpp::inverse (
    const Eigen::MatrixBase< Derived > & A )
```

Inverse.

Parameters

<i>A</i>	Eigen expression
----------	------------------

Returns

Inverse of *A*, as a dynamic matrix over the same scalar field as *A*

6.1.3.65 `invperm()`

```
std::vector<idx> qpp::invperm (
    const std::vector< idx > & perm ) [inline]
```

Inverse permutation.

Parameters

<i>perm</i>	Permutation
-------------	-------------

Returns

Inverse of the permutation *perm*

6.1.3.66 `ip()` [1/2]

```
template<typename Derived >
dyn_col_vect<typename Derived::Scalar> qpp::ip (
    const Eigen::MatrixBase< Derived > & phi,
    const Eigen::MatrixBase< Derived > & psi,
    const std::vector< idx > & subsys,
    const std::vector< idx > & dims )
```

Generalized inner product.

Parameters

<i>phi</i>	Column vector Eigen expression
<i>psi</i>	Column vector Eigen expression
<i>subsys</i>	Subsystem indexes over which <i>phi</i> is defined
<i>dims</i>	Dimensions of the multi-partite system

Returns

Inner product $\langle \phi_{\text{subsys}} | \psi \rangle$, as a scalar or column vector over the remaining Hilbert space

6.1.3.67 ip() [2/2]

```
template<typename Derived >
dyn_col_vect<typename Derived::Scalar> qpp::ip (
    const Eigen::MatrixBase< Derived > & phi,
    const Eigen::MatrixBase< Derived > & psi,
    const std::vector< idx > & subsys,
    idx d = 2 )
```

Generalized inner product.

Parameters

<i>phi</i>	Column vector Eigen expression
<i>psi</i>	Column vector Eigen expression
<i>subsys</i>	Subsystem indexes over which <i>phi</i> is defined
<i>d</i>	Subsystem dimensions

Returns

Inner product $\langle \phi_{\text{subsys}} | \psi \rangle$, as a scalar or column vector over the remaining Hilbert space

6.1.3.68 isprime()

```
bool qpp::isprime (
    bigint p,
    idx k = 80 ) [inline]
```

Primality test based on the Miller-Rabin's algorithm.

Parameters

<i>p</i>	Integer different from 0, 1 or -1
<i>k</i>	Number of iterations. The probability of a false positive is 2^{-k} .

Returns

True if the number is (most-likely) prime, false otherwise

6.1.3.69 kraus2choi()

```
cmat qpp::kraus2choi (
    const std::vector< cmat > & Ks ) [inline]
```

Choi matrix.

See also

[qpp::choi2kraus\(\)](#)

Constructs the Choi matrix of the channel specified by the set of Kraus operators K_s in the standard operator basis $\{|i\rangle\langle j|\}$ ordered in lexicographical order, i.e. $|0\rangle\langle 0|$, $|0\rangle\langle 1|$ etc.

Note

The superoperator matrix S and the Choi matrix C are related by $S_{ab,mn} = C_{ma,nb}$

Parameters

K_s	Set of Kraus operators
-------	------------------------

Returns

Choi matrix

6.1.3.70 kraus2super()

```
cmat qpp::kraus2super (
    const std::vector< cmat > & Ks ) [inline]
```

Superoperator matrix.

Constructs the superoperator matrix of the channel specified by the set of Kraus operators K_s in the standard operator basis $\{|i\rangle\langle j|\}$ ordered in lexicographical order, i.e. $|0\rangle\langle 0|$, $|0\rangle\langle 1|$ etc.

Parameters

K_s	Set of Kraus operators
-------	------------------------

Returns

Superoperator matrix

6.1.3.71 `kron()` [1/4]

```
template<typename T >
dyn_mat<typename T::Scalar> qpp::kron (
    const T & head )
```

Kronecker product.

See also

[qpp::kronpow\(\)](#)

Used to stop the recursion for the variadic template version of [qpp::kron\(\)](#)

Parameters

<i>head</i>	Eigen expression
-------------	------------------

Returns

Its argument *head*

6.1.3.72 `kron()` [2/4]

```
template<typename T , typename... Args>
dyn_mat<typename T::Scalar> qpp::kron (
    const T & head,
    const Args &... tail )
```

Kronecker product.

See also

[qpp::kronpow\(\)](#)

Parameters

<i>head</i>	Eigen expression
<i>tail</i>	Variadic Eigen expression (zero or more parameters)

Returns

Kronecker product of all input parameters, evaluated from left to right, as a dynamic matrix over the same scalar field as its arguments

6.1.3.73 `kron()` [3/4]

```
template<typename Derived >
dyn_mat<typename Derived::Scalar> qpp::kron (
    const std::vector< Derived > & As )
```

Kronecker product.

See also

[qpp::kronpow\(\)](#)

Parameters

As	std::vector of Eigen expressions
-----------	----------------------------------

Returns

Kronecker product of all elements in *As*, evaluated from left to right, as a dynamic matrix over the same scalar field as its arguments

6.1.3.74 `kron()` [4/4]

```
template<typename Derived >
dyn_mat<typename Derived::Scalar> qpp::kron (
    const std::initializer_list< Derived > & As )
```

Kronecker product.

See also

[qpp::kronpow\(\)](#)

Parameters

As	std::initializer_list of Eigen expressions, such as { <i>A1</i> , <i>A2</i> , ... , <i>Ak</i> }
-----------	-------------------------------------------------------------------------------------------------

Returns

Kronecker product of all elements in *As*, evaluated from left to right, as a dynamic matrix over the same scalar field as its arguments

6.1.3.75 `kronpow()`

```
template<typename Derived >
dyn_mat<typename Derived::Scalar> qpp::kronpow (
```

```
const Eigen::MatrixBase< Derived > & A,
idx n )
```

Kronecker power.

See also

[qpp::kron\(\)](#)

Parameters

A	Eigen expression
n	Non-negative integer

Returns

Kronecker product of A with itself n times $A^{\otimes n}$, as a dynamic matrix over the same scalar field as A

6.1.3.76 lcm() [1/2]

```
bigint qpp::lcm (
    bigint a,
    bigint b ) [inline]
```

Least common multiple of two integers.

See also

[qpp::gcd\(\)](#)

Parameters

a	Integer
b	Integer

Returns

Least common multiple of a and b

6.1.3.77 lcm() [2/2]

```
bigint qpp::lcm (
    const std::vector< bigint > & as ) [inline]
```

Least common multiple of a list of integers.

See also

[qpp::gcd\(\)](#)

Parameters

<i>as</i>	List of integers
-----------	------------------

Returns

Least common multiple of all numbers in *as*

6.1.3.78 load()

```
template<typename Derived >
dyn_mat<typename Derived::Scalar> qpp::load (
    const std::string & fname )
```

Loads Eigen matrix from a binary file (internal format) in double precision.

See also

[qpp::save\(\)](#)

The template parameter cannot be automatically deduced and must be explicitly provided, depending on the scalar field of the matrix that is being loaded.

Example:

```
// loads a previously saved Eigen dynamic complex matrix from "input.bin"
cmat mat = load<cmat>("input.bin");
```

Parameters

<i>fname</i>	Output file name
--------------	------------------

6.1.3.79 loadMATLAB() [1/2]

```
template<typename Derived >
std::enable_if<std::is_same<typename Derived::Scalar, cplx>::value, dyn_mat<cplx> >::type
qpp::loadMATLAB (
    const std::string & mat_file,
    const std::string & var_name )
```

Loads a complex Eigen dynamic matrix from a MATLAB .mat file,.

See also

[qpp::saveMATLAB\(\)](#)

The template parameter cannot be automatically deduced and must be explicitly provided

Example:

```
// loads a previously saved Eigen ket
// from the MATLAB file "input.mat"
ket psi = loadMATLAB<ket>("input.mat");
```

Template Parameters

<i>Derived</i>	Complex Eigen type
----------------	--------------------

Parameters

<i>mat_file</i>	MATALB .mat file
<i>var_name</i>	Variable name in the .mat file representing the matrix to be loaded

Returns

Eigen dynamic matrix

6.1.3.80 loadMATLAB() [2/2]

```
template<typename Derived >
std::enable_if<!std::is_same<typename Derived::Scalar, cplx>::value, dyn_mat<typename Derived↵
::Scalar> >::type qpp::loadMATLAB (
    const std::string & mat_file,
    const std::string & var_name )
```

Loads a non-complex Eigen dynamic matrix from a MATLAB .mat file,.

See also

[qpp::saveMATLAB\(\)](#)

The template parameter cannot be automatically deduced and must be explicitly provided

Example:

```
// loads a previously saved Eigen dynamic double matrix
// from the MATLAB file "input.mat"
dmat mat = loadMATLAB<dmat>("input.mat");
```

Template Parameters

<i>Derived</i>	Non-complex Eigen type
----------------	------------------------

Parameters

<i>mat_file</i>	MATALB .mat file
<i>var_name</i>	Variable name in the .mat file representing the matrix to be loaded

Returns

Eigen dynamic matrix

6.1.3.81 `logdet()`

```
template<typename Derived >
Derived::Scalar qpp::logdet (
    const Eigen::MatrixBase< Derived > & A )
```

Logarithm of the determinant.

Useful when the determinant overflows/underflows

Parameters

<i>A</i>	Eigen expression
----------	------------------

Returns

Logarithm of the determinant of *A*, as a scalar over the same scalar field as *A*

6.1.3.82 `logm()`

```
template<typename Derived >
cmat qpp::logm (
    const Eigen::MatrixBase< Derived > & A )
```

Matrix logarithm.

Parameters

<i>A</i>	Eigen expression
----------	------------------

Returns

Matrix logarithm of A

6.1.3.83 lognegativity() [1/2]

```
template<typename Derived >
double qpp::lognegativity (
    const Eigen::MatrixBase< Derived > & A,
    const std::vector< idx > & dims )
```

Logarithmic negativity of the bi-partite mixed state A .

Parameters

A	Eigen expression
$dims$	Dimensions of the bi-partite system

Returns

Logarithmic negativity, with the logarithm in base 2

6.1.3.84 lognegativity() [2/2]

```
template<typename Derived >
double qpp::lognegativity (
    const Eigen::MatrixBase< Derived > & A,
    idx d = 2 )
```

Logarithmic negativity of the bi-partite mixed state A .

Parameters

A	Eigen expression
d	Subsystem dimensions

Returns

Logarithmic negativity, with the logarithm in base 2

6.1.3.85 marginalX()

```
std::vector<double> qpp::marginalX (
    const dmat & probXY ) [inline]
```

Marginal distribution.

Parameters

<i>probXY</i>	Real matrix representing the joint probability distribution of X and Y in lexicographical order (X labels the rows, Y labels the columns)
---------------	----------------------------------------------------------------------------------------------------------------------------------------------------

Returns

Real vector consisting of the marginal distribution of X

6.1.3.86 marginalY()

```
std::vector<double> qpp::marginalY (
    const dmat & probXY ) [inline]
```

Marginal distribution.

Parameters

<i>probXY</i>	Real matrix representing the joint probability distribution of X and Y in lexicographical order (X labels the rows, Y labels the columns)
---------------	----------------------------------------------------------------------------------------------------------------------------------------------------

Returns

Real vector consisting of the marginal distribution of Y

6.1.3.87 measure() [1/9]

```
template<typename Derived >
std::tuple<idx, std::vector<double>, std::vector<cmat> > qpp::measure (
    const Eigen::MatrixBase< Derived > & A,
    const std::vector< cmat > & Ks )
```

Measures the state vector or density operator A using the set of Kraus operators Ks .

Parameters

A	Eigen expression
Ks	Set of Kraus operators

Returns

Tuple of: 1. Result of the measurement, 2. Vector of outcome probabilities, and 3. Vector of post-measurement normalized states

6.1.3.88 `measure()` [2/9]

```
template<typename Derived >
std::tuple<idx, std::vector<double>, std::vector<cmat> > qpp::measure (
    const Eigen::MatrixBase< Derived > & A,
    const std::initializer_list< cmat > & Ks )
```

Measures the state vector or density matrix A using the set of Kraus operators Ks .

Parameters

A	Eigen expression
Ks	Set of Kraus operators

Returns

Tuple of: 1. Result of the measurement, 2. Vector of outcome probabilities, and 3. Vector of post-measurement normalized states

6.1.3.89 `measure()` [3/9]

```
template<typename Derived >
std::tuple<idx, std::vector<double>, std::vector<cmat> > qpp::measure (
    const Eigen::MatrixBase< Derived > & A,
    const cmat & U )
```

Measures the state vector or density matrix A in the orthonormal basis specified by the unitary matrix U .

Parameters

A	Eigen expression
U	Unitary matrix whose columns represent the measurement basis vectors

Returns

Tuple of: 1. Result of the measurement, 2. Vector of outcome probabilities, and 3. Vector of post-measurement normalized states

6.1.3.90 `measure()` [4/9]

```
template<typename Derived >
std::tuple<idx, std::vector<double>, std::vector<cmat> > qpp::measure (
    const Eigen::MatrixBase< Derived > & A,
    const std::vector< cmat > & Ks,
    const std::vector< idx > & target,
    const std::vector< idx > & dims )
```

Measures the part *subsys* of the multi-partite state vector or density matrix A using the set of Kraus operators Ks .

See also

[qpp::measure_seq\(\)](#)

Note

The dimension of all *Ks* must match the dimension of *target*. The measurement is destructive, i.e. the measured subsystems are traced away.

Parameters

<i>A</i>	Eigen expression
<i>Ks</i>	Set of Kraus operators
<i>target</i>	Subsystem indexes that are measured
<i>dims</i>	Dimensions of the multi-partite system

Returns

Tuple of: 1. Result of the measurement, 2. Vector of outcome probabilities, and 3. Vector of post-measurement normalized states

6.1.3.91 `measure()` [5/9]

```
template<typename Derived >
std::tuple<idx, std::vector<double>, std::vector<cmat> > qpp::measure (
    const Eigen::MatrixBase< Derived > & A,
    const std::initializer_list< cmat > & Ks,
    const std::vector< idx > & target,
    const std::vector< idx > & dims )
```

Measures the part *target* of the multi-partite state vector or density matrix *A* using the set of Kraus operators *Ks*.

See also

[qpp::measure_seq\(\)](#)

Note

The dimension of all *Ks* must match the dimension of *target*. The measurement is destructive, i.e. the measured subsystems are traced away.

Parameters

<i>A</i>	Eigen expression
<i>Ks</i>	Set of Kraus operators
<i>target</i>	Subsystem indexes that are measured
<i>dims</i>	Dimensions of the multi-partite system

Returns

Tuple of: 1. Result of the measurement, 2. Vector of outcome probabilities, and 3. Vector of post-measurement normalized states

6.1.3.92 measure() [6/9]

```
template<typename Derived >
std::tuple<idx, std::vector<double>, std::vector<cmat> > qpp::measure (
    const Eigen::MatrixBase< Derived > & A,
    const std::vector< cmat > & Ks,
    const std::vector< idx > & target,
    idx d = 2 )
```

Measures the part *target* of the multi-partite state vector or density matrix *A* using the set of Kraus operators *Ks*.

See also

[qpp::measure_seq\(\)](#)

Note

The dimension of all *Ks* must match the dimension of *target*. The measurement is destructive, i.e. the measured subsystems are traced away.

Parameters

<i>A</i>	Eigen expression
<i>Ks</i>	Set of Kraus operators
<i>target</i>	Subsystem indexes that are measured
<i>d</i>	Subsystem dimensions

Returns

Tuple of: 1. Result of the measurement, 2. Vector of outcome probabilities, and 3. Vector of post-measurement normalized states

6.1.3.93 measure() [7/9]

```
template<typename Derived >
std::tuple<idx, std::vector<double>, std::vector<cmat> > qpp::measure (
    const Eigen::MatrixBase< Derived > & A,
    const std::initializer_list< cmat > & Ks,
    const std::vector< idx > & target,
    idx d = 2 )
```

Measures the part *target* of the multi-partite state vector or density matrix *A* using the set of Kraus operators *Ks*.

See also

[qpp::measure_seq\(\)](#)

Note

The dimension of all *Ks* must match the dimension of *target*. The measurement is destructive, i.e. the measured subsystems are traced away.

Parameters

<i>A</i>	Eigen expression
<i>Ks</i>	Set of Kraus operators
<i>target</i>	Subsystem indexes that are measured
<i>d</i>	Subsystem dimensions

Returns

Tuple of: 1. Result of the measurement, 2. Vector of outcome probabilities, and 3. Vector of post-measurement normalized states

6.1.3.94 `measure()` [8/9]

```
template<typename Derived >
std::tuple<idx, std::vector<double>, std::vector<cmat> > qpp::measure (
    const Eigen::MatrixBase< Derived > & A,
    const cmat & V,
    const std::vector< idx > & target,
    const std::vector< idx > & dims )
```

Measures the part *target* of the multi-partite state vector or density matrix *A* in the orthonormal basis or rank-1 projectors specified by the columns of the matrix *V*.

See also

[qpp::measure_seq\(\)](#)

Note

The dimension of *V* must match the dimension of *target*. The measurement is destructive, i.e. the measured subsystems are traced away.

Parameters

<i>A</i>	Eigen expression
<i>V</i>	Matrix whose columns represent the measurement basis vectors or the bra parts of the rank-1 projectors
<i>target</i>	Subsystem indexes that are measured
<i>dims</i>	Dimensions of the multi-partite system

Returns

Tuple of: 1. Result of the measurement, 2. Vector of outcome probabilities, and 3. Vector of post-measurement normalized states

6.1.3.95 `measure()` [9/9]

```
template<typename Derived >
std::tuple<idx, std::vector<double>, std::vector<cmat> > qpp::measure (
    const Eigen::MatrixBase< Derived > & A,
    const cmat & V,
    const std::vector< idx > & target,
    idx d = 2 )
```

Measures the part *target* of the multi-partite state vector or density matrix *A* in the orthonormal basis or rank-1 projectors specified by the columns of the matrix *V*.

See also

[qpp::measure_seq\(\)](#)

Note

The dimension of *V* must match the dimension of *target*. The measurement is destructive, i.e. the measured subsystems are traced away.

Parameters

<i>A</i>	Eigen expression
<i>V</i>	Matrix whose columns represent the measurement basis vectors or the bra parts of the rank-1 projectors
<i>target</i>	Subsystem indexes that are measured
<i>d</i>	Subsystem dimensions

Returns

Tuple of: 1. Result of the measurement, 2. Vector of outcome probabilities, and 3. Vector of post-measurement normalized states

6.1.3.96 `measure_seq()` [1/2]

```
template<typename Derived >
std::tuple<std::vector<idx>, double, cmat> qpp::measure_seq (
    const Eigen::MatrixBase< Derived > & A,
    std::vector< idx > target,
    std::vector< idx > dims )
```

Sequentially measures the part *target* of the multi-partite state vector or density matrix *A* in the computational basis.

See also

[qpp::measure\(\)](#)

Parameters

<i>A</i>	Eigen expression
<i>target</i>	Subsystem indexes that are measured
<i>dims</i>	Dimensions of the multi-partite system

Returns

Tuple of: 1. Vector of outcome results of the measurement (ordered in increasing order with respect to *target*, i.e. first measurement result corresponds to the subsystem with the smallest index), 2. Outcome probability, and 3. Post-measurement normalized state

6.1.3.97 `measure_seq()` [2/2]

```
template<typename Derived >
std::tuple<std::vector<idx>, double, cmat> qpp::measure_seq (
    const Eigen::MatrixBase< Derived > & A,
    std::vector< idx > target,
    idx d = 2 )
```

Sequentially measures the part *target* of the multi-partite state vector or density matrix *A* in the computational basis.

See also

[qpp::measure\(\)](#)

Parameters

<i>A</i>	Eigen expression
<i>target</i>	Subsystem indexes that are measured
<i>d</i>	Subsystem dimensions

Returns

Tuple of: 1. Vector of outcome results of the measurement (ordered in increasing order with respect to *target*, i.e. first measurement result corresponds to the subsystem with the smallest index), 2. Outcome probability, and 3. Post-measurement normalized state

6.1.3.98 `mket()` [1/2]

```
ket qpp::mket (
    const std::vector< idx > & mask,
    const std::vector< idx > & dims ) [inline]
```

Multi-partite qudit ket.

See also

[qpp::operator "" _ket\(\)](#)

Constructs the multi-partite qudit ket $|\text{mask}\rangle$, where *mask* is a `std::vector` of non-negative integers. Each element in *mask* has to be smaller than the corresponding element in *dims*.

Parameters

<i>mask</i>	<code>std::vector</code> of non-negative integers
<i>dims</i>	Dimensions of the multi-partite system

Returns

Multi-partite qudit state vector, as a complex dynamic column vector

6.1.3.99 `mket()` [2/2]

```
ket qpp::mket (
    const std::vector< idx > & mask,
    idx d = 2 ) [inline]
```

Multi-partite qudit ket.

See also

[qpp::operator "" _ket\(\)](#)

Constructs the multi-partite qudit ket $|\text{mask}\rangle$, all subsystem having equal dimension *d*. *mask* is a `std::vector` of non-negative integers, and each element in *mask* has to be strictly smaller than *d*.

Parameters

<i>mask</i>	<code>std::vector</code> of non-negative integers
<i>d</i>	Subsystem dimensions

Returns

Multi-partite qudit state vector, as a complex dynamic column vector

6.1.3.100 `modinv()`

```
bigint qpp::modinv (
    bigint a,
    bigint p ) [inline]
```

Modular inverse of a mod p .

See also

[qpp::egcd\(\)](#)

Note

a and p must be co-prime

Parameters

a	Non-negative integer
p	Non-negative integer

Returns

Modular inverse $a^{-1} \bmod p$

6.1.3.101 modmul()

```
bigint qpp::modmul (
    bigint a,
    bigint b,
    bigint p ) [inline]
```

Modular multiplication without overflow.

Computes $ab \bmod p$ without overflow

Parameters

a	Integer
b	Integer
p	Positive integer

Returns

$ab \bmod p$ avoiding overflow

6.1.3.102 modpow()

```
bigint qpp::modpow (
    bigint a,
```

```

    bigint n,
    bigint p ) [inline]

```

Fast integer power modulo p based on the SQUARE-AND-MULTIPLY algorithm.

Note

Uses `qpp::modmul()` that avoids overflows

Computes $a^n \bmod p$

Parameters

a	Non-negative integer
n	Non-negative integer
p	Strictly positive integer

Returns

$a^n \bmod p$

6.1.3.103 `mprj()` [1/2]

```

cmat qpp::mprj (
    const std::vector< idx > & mask,
    const std::vector< idx > & dims ) [inline]

```

Projector onto multi-partite qudit ket.

See also

`qpp::operator "" _prj()`

Constructs the projector onto the multi-partite qudit ket $|\text{mask}\rangle$, where *mask* is a `std::vector` of non-negative integers. Each element in *mask* has to be smaller than the corresponding element in *dims*.

Parameters

<i>mask</i>	<code>std::vector</code> of non-negative integers
<i>dims</i>	Dimensions of the multi-partite system

Returns

Projector onto multi-partite qudit state vector, as a complex dynamic matrix

6.1.3.104 `mprj()` [2/2]

```

cmat qpp::mprj (
    const std::vector< idx > & mask,
    idx d = 2 ) [inline]

```

Projector onto multi-partite qudit ket.

See also

[qpp::operator "" _prj\(\)](#)

Constructs the projector onto the multi-partite qudit ket $|\text{mask}\rangle$, all subsystem having equal dimension d . *mask* is a `std::vector` of non-negative integers, and each element in *mask* has to be strictly smaller than d .

Parameters

<i>mask</i>	std::vector of non-negative integers
<i>d</i>	Subsystem dimensions

Returns

Projector onto multi-partite qudit state vector, as a complex dynamic matrix

6.1.3.105 `multiidx2n()`

```

idx qpp::multiidx2n (
    const std::vector< idx > & midx,
    const std::vector< idx > & dims ) [inline]

```

Multi-index to non-negative integer index.

See also

[qpp::n2multiidx\(\)](#)

Uses standard lexicographical order, i.e. 00...0, 00...1 etc.

Parameters

<i>midx</i>	Multi-index
<i>dims</i>	Dimensions of the multi-partite system

Returns

Non-negative integer index

6.1.3.106 `n2multiidx()`

```
std::vector<idx> qpp::n2multiidx (
    idx n,
    const std::vector< idx > & dims ) [inline]
```

Non-negative integer index to multi-index.

See also

[qpp::multiidx2n\(\)](#)

Uses standard lexicographical order, i.e. 00...0, 00...1 etc.

Parameters

<i>n</i>	Non-negative integer index
<i>dims</i>	Dimensions of the multi-partite system

Returns

Multi-index of the same size as *dims*

6.1.3.107 `negativity()` [1/2]

```
template<typename Derived >
double qpp::negativity (
    const Eigen::MatrixBase< Derived > & A,
    const std::vector< idx > & dims )
```

Negativity of the bi-partite mixed state *A*.

Parameters

<i>A</i>	Eigen expression
<i>dims</i>	Dimensions of the bi-partite system

Returns

Negativity

6.1.3.108 `negativity()` [2/2]

```
template<typename Derived >
double qpp::negativity (
```



```
const Eigen::MatrixBase< Derived > & A,
idx d = 2 )
```

Negativity of the bi-partite mixed state A .

Parameters

A	Eigen expression
d	Subsystem dimensions

Returns

Negativity

6.1.3.109 norm()

```
template<typename Derived >
double qpp::norm (
    const Eigen::MatrixBase< Derived > & A )
```

Frobenius norm.

Parameters

A	Eigen expression
-----	------------------

Returns

Frobenius norm of A

6.1.3.110 normalize()

```
template<typename Derived >
dyn_mat<typename Derived::Scalar> qpp::normalize (
    const Eigen::MatrixBase< Derived > & A )
```

Normalizes state vector (column or row vector) or density matrix.

Parameters

A	Eigen expression
-----	------------------

Returns

Normalized state vector or density matrix

6.1.3.111 omega()

```
cplx qpp::omega (
    idx D ) [inline]
```

D-th root of unity.

Parameters

<i>D</i>	Non-negative integer
----------	----------------------

Returns

D-th root of unity $\exp(2\pi i/D)$

6.1.3.112 operator""_i()

```
constexpr cplx qpp::operator"" _i (
    long double x ) [inline], [noexcept]
```

User-defined literal for complex $i = \sqrt{-1}$ (real overload)

Example:

```
cplx z = 4.5_i; // type of z is std::complex<double>
```

6.1.3.113 powm()

```
template<typename Derived >
dyn_mat<typename Derived::Scalar> qpp::powm (
    const Eigen::MatrixBase< Derived > & A,
    idx n )
```

Fast matrix power based on the SQUARE-AND-MULTIPLY algorithm.

See also

[qpp::spectralpowm\(\)](#)

Explicitly multiplies the matrix A with itself n times. By convention $A^0 = I$.

Parameters

A	Eigen expression
n	Non-negative integer

Returns

Matrix power A^n , as a dynamic matrix over the same scalar field as A

6.1.3.114 prj()

```
template<typename Derived >
dyn_mat<typename Derived::Scalar> qpp::prj (
    const Eigen::MatrixBase< Derived > & A )
```

Projector.

Normalized projector onto state vector

Parameters

A	Eigen expression
-----	------------------

Returns

Projector onto the state vector A , or the matrix *Zero* if A has norm zero, as a dynamic matrix over the same scalar field as A

6.1.3.115 prod() [1/3]

```
template<typename Derived >
Derived::Scalar qpp::prod (
    const Eigen::MatrixBase< Derived > & A )
```

Element-wise product of A .

Parameters

A	Eigen expression
-----	------------------

Returns

Element-wise product of A , as a scalar over the same scalar field as A

6.1.3.116 prod() [2/3]

```
template<typename InputIterator >
std::iterator_traits<InputIterator>::value_type qpp::prod (
    InputIterator first,
    InputIterator last )
```

Element-wise product of an STL-like range.

Parameters

<i>first</i>	Iterator to the first element of the range
<i>last</i>	Iterator to the last element of the range

Returns

Element-wise product of the range, as a scalar over the same scalar field as the range

6.1.3.117 prod() [3/3]

```
template<typename Container >
Container::value_type qpp::prod (
    const Container & c,
    typename std::enable_if< is\_iterable< Container >::value >::type * = nullptr )
```

Element-wise product of the elements of an STL-like container.

Parameters

<i>c</i>	STL-like container
----------	--------------------

Returns

Element-wise product of the elements of the container, as a scalar over the same scalar field as the container

6.1.3.118 ptrace() [1/2]

```
template<typename Derived >
dyn\_mat<typename Derived::Scalar> qpp::ptrace (
    const Eigen::MatrixBase< Derived > & A,
    const std::vector< idx > & target,
    const std::vector< idx > & dims )
```

Partial trace.

See also

[qpp::ptrace1\(\)](#), [qpp::ptrace2\(\)](#)

Partial trace of the multi-partite state vector or density matrix over the list *target* of subsystems

Parameters

<i>A</i>	Eigen expression
<i>target</i>	Subsystem indexes
<i>dims</i>	Dimensions of the multi-partite system

Returns

Partial trace $Tr_{subsys}(\cdot)$ over the subsystems *target* in a multi-partite system, as a dynamic matrix over the same scalar field as *A*

6.1.3.119 ptrace() [2/2]

```
template<typename Derived >
dyn_mat<typename Derived::Scalar> qpp::ptrace (
    const Eigen::MatrixBase< Derived > & A,
    const std::vector< idx > & target,
    idx d = 2 )
```

Partial trace.

See also

[qpp::ptrace1\(\)](#), [qpp::ptrace2\(\)](#)

Partial trace of the multi-partite state vector or density matrix over the list *target* of subsystems

Parameters

<i>A</i>	Eigen expression
<i>target</i>	Subsystem indexes
<i>d</i>	Subsystem dimensions

Returns

Partial trace $Tr_{subsys}(\cdot)$ over the subsystems *target* in a multi-partite system, as a dynamic matrix over the same scalar field as *A*

6.1.3.120 ptrace1() [1/2]

```
template<typename Derived >
dyn_mat<typename Derived::Scalar> qpp::ptrace1 (
    const Eigen::MatrixBase< Derived > & A,
    const std::vector< idx > & dims )
```

Partial trace.

See also

[qpp::ptrace2\(\)](#)

Partial trace over the first subsystem of bi-partite state vector or density matrix

Parameters

A	Eigen expression
$dims$	Dimensions of the bi-partite system

Returns

Partial trace $Tr_A(\cdot)$ over the first subsystem A in a bi-partite system $A \otimes B$, as a dynamic matrix over the same scalar field as A

6.1.3.121 `ptrace1()` [2/2]

```
template<typename Derived >
dyn_mat<typename Derived::Scalar> qpp::ptrace1 (
    const Eigen::MatrixBase< Derived > & A,
    idx d = 2 )
```

Partial trace.

See also

[qpp::ptrace2\(\)](#)

Partial trace over the first subsystem of bi-partite state vector or density matrix

Parameters

A	Eigen expression
d	Subsystem dimensions

Returns

Partial trace $Tr_A(\cdot)$ over the first subsystem A in a bi-partite system $A \otimes B$, as a dynamic matrix over the same scalar field as A

6.1.3.122 `ptrace2()` [1/2]

```
template<typename Derived >
dyn_mat<typename Derived::Scalar> qpp::ptrace2 (
    const Eigen::MatrixBase< Derived > & A,
    const std::vector< idx > & dims )
```

Partial trace.

See also

[qpp::ptrace1\(\)](#)

Partial trace over the second subsystem of bi-partite state vector or density matrix

Parameters

A	Eigen expression
$dims$	Dimensions of the bi-partite system

Returns

Partial trace $Tr_B(\cdot)$ over the second subsystem B in a bi-partite system $A \otimes B$, as a dynamic matrix over the same scalar field as A

6.1.3.123 ptrace2() [2/2]

```
template<typename Derived >
dyn_mat<typename Derived::Scalar> qpp::ptrace2 (
    const Eigen::MatrixBase< Derived > & A,
    idx d = 2 )
```

Partial trace.

See also

[qpp::ptrace1\(\)](#)

Partial trace over the second subsystem of bi-partite state vector or density matrix

Parameters

A	Eigen expression
d	Subsystem dimensions

Returns

Partial trace $Tr_B(\cdot)$ over the second subsystem B in a bi-partite system $A \otimes B$, as a dynamic matrix over the same scalar field as A

6.1.3.124 ptranspose() [1/2]

```
template<typename Derived >
dyn_mat<typename Derived::Scalar> qpp::ptranspose (
```

```
const Eigen::MatrixBase< Derived > & A,
const std::vector< idx > & target,
const std::vector< idx > & dims )
```

Partial transpose.

Partial transpose of the multi-partite state vector or density matrix over the list *target* of subsystems

Parameters

<i>A</i>	Eigen expression
<i>target</i>	Subsystem indexes
<i>dims</i>	Dimensions of the multi-partite system

Returns

Partial transpose $(\cdot)^{T_{\text{subsys}}}$ over the subsystems *target* in a multi-partite system, as a dynamic matrix over the same scalar field as *A*

6.1.3.125 ptranspose() [2/2]

```
template<typename Derived >
dyn_mat<typename Derived::Scalar> qpp::pttranspose (
    const Eigen::MatrixBase< Derived > & A,
    const std::vector< idx > & target,
    idx d = 2 )
```

Partial transpose.

Partial transpose of the multi-partite state vector or density matrix over the list *target* of subsystems

Parameters

<i>A</i>	Eigen expression
<i>target</i>	Subsystem indexes
<i>d</i>	Subsystem dimensions

Returns

Partial transpose $(\cdot)^{T_{\text{subsys}}}$ over the subsystems *target* in a multi-partite system, as a dynamic matrix over the same scalar field as *A*

6.1.3.126 QFT()

```
template<typename Derived >
dyn_col_vect<typename Derived::Scalar> qpp::QFT (
```



```
const Eigen::MatrixBase< Derived > & A,
    idx d = 2,
    bool swap = true )
```

Qudit quantum Fourier transform.

Parameters

<i>A</i>	Eigen expression
<i>d</i>	Subsystem dimensions
<i>swap</i>	Swaps the qubits/qudits at the end (true by default)

Returns

Qudit quantum Fourier transform applied on *A*

6.1.3.127 qmutualinfo() [1/2]

```
template<typename Derived >
double qpp::qmutualinfo (
    const Eigen::MatrixBase< Derived > & A,
    const std::vector< idx > & subsysA,
    const std::vector< idx > & subsysB,
    const std::vector< idx > & dims )
```

Quantum mutual information between 2 subsystems of a composite system.

Parameters

<i>A</i>	Eigen expression
<i>subsysA</i>	Indexes of the first subsystem
<i>subsysB</i>	Indexes of the second subsystem
<i>dims</i>	Dimensions of the multi-partite system

Returns

Mutual information between the 2 subsystems

6.1.3.128 qmutualinfo() [2/2]

```
template<typename Derived >
double qpp::qmutualinfo (
    const Eigen::MatrixBase< Derived > & A,
    const std::vector< idx > & subsysA,
    const std::vector< idx > & subsysB,
    idx d = 2 )
```

Quantum mutual information between 2 subsystems of a composite system.

Parameters

<i>A</i>	Eigen expression
<i>subsysA</i>	Indexes of the first subsystem
<i>subsysB</i>	Indexes of the second subsystem
<i>d</i>	Subsystem dimensions

Returns

Mutual information between the 2 subsystems

6.1.3.129 rand() [1/5]

```
double qpp::rand (
    double a,
    double b ) [inline]
```

Generates a random real number uniformly distributed in the interval [a, b)

Parameters

<i>a</i>	Beginning of the interval, belongs to it
<i>b</i>	End of the interval, does not belong to it

Returns

Random real number (double) uniformly distributed in the interval [a, b)

6.1.3.130 rand() [2/5]

```
bigint qpp::rand (
    bigint a,
    bigint b ) [inline]
```

Generates a random big integer uniformly distributed in the interval [a, b].

Note

To avoid ambiguity with double [qpp::rand\(double, double\)](#) cast at least one of the arguments to [qpp::bigint](#)

Parameters

<i>a</i>	Beginning of the interval, belongs to it
<i>b</i>	End of the interval, belongs to it

Returns

Random big integer uniformly distributed in the interval [a, b]

6.1.3.131 rand() [3/5]

```
template<typename Derived >
Derived qpp::rand (
    idx rows QPP_UNUSED_,
    idx cols QPP_UNUSED_,
    double a QPP_UNUSED_ = 0,
    double b QPP_UNUSED_ = 1 )
```

Generates a random matrix with entries uniformly distributed in the interval [a, b)

If complex, then both real and imaginary parts are uniformly distributed in [a, b)

This is the generic version that always throws `qpp::Exception::Type::UNDEFINED_TYPE`. It is specialized only for `qpp::dmat` and `qpp::cmat`

6.1.3.132 rand() [4/5]

```
template<>
dmat qpp::rand (
    idx rows ,
    idx cols ,
    double a ,
    double b ) [inline]
```

Generates a random real matrix with entries uniformly distributed in the interval [a, b), specialization for double matrices (`qpp::dmat`)

The template parameter cannot be automatically deduced and must be explicitly provided

Example:

```
// generates a 3 x 3 random Eigen::MatrixXd,
// with entries uniformly distributed in [-1,1)
dmat mat = rand<dmat>(3, 3, -1, 1);
```

Parameters

<i>rows</i>	Number of rows of the random generated matrix
<i>cols</i>	Number of columns of the random generated matrix
<i>a</i>	Beginning of the interval, belongs to it
<i>b</i>	End of the interval, does not belong to it

Returns

Random real matrix

6.1.3.133 rand() [5/5]

```
template<>
cmat qpp::rand (
    idx rows ,
    idx cols ,
    double a ,
    double b ) [inline]
```

Generates a random complex matrix with entries (both real and imaginary) uniformly distributed in the interval [a, b), specialization for complex matrices (`qpp::cmat`)

The template parameter cannot be automatically deduced and must be explicitly provided

Example:

```
// generates a 3 x 3 random Eigen::MatrixXcd,
// with entries (both real and imaginary) uniformly distributed in [-1,1)
cmat mat = rand<cmat>(3, 3, -1, 1);
```

Parameters

<i>rows</i>	Number of rows of the random generated matrix
<i>cols</i>	Number of columns of the random generated matrix
<i>a</i>	Beginning of the interval, belongs to it
<i>b</i>	End of the interval, does not belong to it

Returns

Random complex matrix

6.1.3.134 randH()

```
cmat qpp::randH (
    idx D = 2 ) [inline]
```

Generates a random Hermitian matrix.

Parameters

<i>D</i>	Dimension of the Hilbert space
----------	--------------------------------

Returns

Random Hermitian matrix

6.1.3.135 randidx()

```
idx qpp::randidx (
    idx a = std::numeric_limits<idx>::min(),
    idx b = std::numeric_limits<idx>::max() ) [inline]
```

Generates a random index (idx) uniformly distributed in the interval [a, b].

Parameters

<i>a</i>	Beginning of the interval, belongs to it
<i>b</i>	End of the interval, belongs to it

Returns

Random index (idx) uniformly distributed in the interval [a, b]

6.1.3.136 randket()

```
ket qpp::randket (
    idx D = 2 ) [inline]
```

Generates a random normalized ket (pure state vector)

Parameters

<i>D</i>	Dimension of the Hilbert space
----------	--------------------------------

Returns

Random normalized ket

6.1.3.137 randkraus()

```
std::vector<cmat> qpp::randkraus (
    idx N,
    idx D = 2 ) [inline]
```

Generates a set of random Kraus operators.

Note

The set of Kraus operators satisfy the closure condition $\sum_i K_i^\dagger K_i = I$

Parameters

N	Number of Kraus operators
D	Dimension of the Hilbert space

Returns

Set of N Kraus operators satisfying the closure condition

6.1.3.138 randn() [1/4]

```
template<typename Derived >
Derived qpp::randn (
    idx rows QPP_UNUSED_,
    idx cols QPP_UNUSED_,
    double mean QPP_UNUSED_ = 0,
    double sigma QPP_UNUSED_ = 1 )
```

Generates a random matrix with entries normally distributed in N(mean, sigma)

If complex, then both real and imaginary parts are normally distributed in N(mean, sigma)

This is the generic version that always throws `qpp::Exception::Type::UNDEFINED_TYPE`. It is specialized only for `qpp::dmat` and `qpp::cmat`

6.1.3.139 randn() [2/4]

```
template<>
dmat qpp::randn (
    idx rows ,
    idx cols ,
    double mean ,
    double sigma ) [inline]
```

Generates a random real matrix with entries normally distributed in N(mean, sigma), specialization for double matrices (`qpp::dmat`)

The template parameter cannot be automatically deduced and must be explicitly provided

Example:

```
// generates a 3 x 3 random Eigen::MatrixXd,
// with entries normally distributed in N(0,2)
dmat mat = randn<dmat>(3, 3, 0, 2);
```

Parameters

<i>rows</i>	Number of rows of the random generated matrix
<i>cols</i>	Number of columns of the random generated matrix
<i>mean</i>	Mean
<i>sigma</i>	Standard deviation

Returns

Random real matrix

6.1.3.140 randn() [3/4]

```
template<>
cmat qpp::randn (
    idx rows ,
    idx cols ,
    double mean ,
    double sigma ) [inline]
```

Generates a random complex matrix with entries (both real and imaginary) normally distributed in $N(\text{mean}, \text{sigma})$, specialization for complex matrices ([qpp::cmat](#))

The template parameter cannot be automatically deduced and must be explicitly provided

Example:

```
// generates a 3 x 3 random Eigen::MatrixXcd,
// with entries (both real and imaginary) normally distributed in N(0,2)
cmat mat = randn<cmat>(3, 3, 0, 2);
```

Parameters

<i>rows</i>	Number of rows of the random generated matrix
<i>cols</i>	Number of columns of the random generated matrix
<i>mean</i>	Mean
<i>sigma</i>	Standard deviation

Returns

Random complex matrix

6.1.3.141 randn() [4/4]

```
double qpp::randn (
    double mean = 0,
    double sigma = 1 ) [inline]
```

Generates a random real number (double) normally distributed in $N(\text{mean}, \text{sigma})$

Parameters

<i>mean</i>	Mean
<i>sigma</i>	Standard deviation

Returns

Random real number normally distributed in $N(\text{mean}, \text{sigma})$

6.1.3.142 randperm()

```
std::vector<idx> qpp::randperm (
    idx N ) [inline]
```

Generates a random uniformly distributed permutation.

Uses Knuth shuffle method (as implemented by `std::shuffle`), so that all permutations are equally probable

Parameters

<i>N</i>	Size of the permutation
----------	-------------------------

Returns

Random permutation of size *N*

6.1.3.143 randprime()

```
bigint qpp::randprime (
    bigint a,
    bigint b,
    idx N = 1000 ) [inline]
```

Generates a random big prime uniformly distributed in the interval $[a, b]$.

Parameters

<i>a</i>	Beginning of the interval, belongs to it
<i>b</i>	End of the interval, belongs to it
<i>N</i>	Maximum number of candidates

Returns

Random big integer uniformly distributed in the interval [a, b]

6.1.3.144 randprob()

```
std::vector<double> qpp::randprob (
    idx N ) [inline]
```

Generates a random probability vector uniformly distributed over the probability simplex.

Parameters

<i>N</i>	Size of the probability vector
----------	--------------------------------

Returns

Random probability vector

6.1.3.145 randrho()

```
cmat qpp::randrho (
    idx D = 2 ) [inline]
```

Generates a random density matrix.

Parameters

<i>D</i>	Dimension of the Hilbert space
----------	--------------------------------

Returns

Random density matrix

6.1.3.146 randU()

```
cmat qpp::randU (
    idx D = 2 ) [inline]
```

Generates a random unitary matrix.

Parameters

<i>D</i>	Dimension of the Hilbert space
----------	--------------------------------

Returns

Random unitary

6.1.3.147 randV()

```
cmat qpp::randV (
    idx Din,
    idx Dout ) [inline]
```

Generates a random isometry matrix.

Parameters

<i>Din</i>	Size of the input Hilbert space
<i>Dout</i>	Size of the output Hilbert space

Returns

Random isometry matrix

6.1.3.148 renyi() [1/2]

```
template<typename Derived >
double qpp::renyi (
    const Eigen::MatrixBase< Derived > & A,
    double alpha )
```

Renyi- α entropy of the density matrix A , for $\alpha \geq 0$.

Note

When $\alpha \rightarrow 1$ the Renyi entropy converges to the von-Neumann entropy, with the logarithm in base 2

Parameters

<i>A</i>	Eigen expression
<i>alpha</i>	Non-negative real number, use qpp::infy for $\alpha = \infty$

Returns

Renyi- α entropy, with the logarithm in base 2

6.1.3.149 `renyi()` [2/2]

```
double qpp::renyi (
    const std::vector< double > & prob,
    double alpha ) [inline]
```

Renyi- α entropy of the probability distribution *prob*, for $\alpha \geq 0$.

Note

When $\alpha \rightarrow 1$ the Renyi entropy converges to the Shannon entropy, with the logarithm in base 2

Parameters

<i>prob</i>	Real probability vector
<i>alpha</i>	Non-negative real number, use <code>qpp::infy</code> for $\alpha = \infty$

Returns

Renyi- α entropy, with the logarithm in base 2

6.1.3.150 `reshape()`

```
template<typename Derived >
dyn_mat<typename Derived::Scalar> qpp::reshape (
    const Eigen::MatrixBase< Derived > & A,
    idx rows,
    idx cols )
```

Reshape.

Uses column-major order when reshaping (same as MATLAB)

Parameters

<i>A</i>	Eigen expression
<i>rows</i>	Number of rows of the reshaped matrix
<i>cols</i>	Number of columns of the reshaped matrix

Returns

Reshaped matrix with *rows* rows and *cols* columns, as a dynamic matrix over the same scalar field as *A*

6.1.3.151 rho2bloch()

```
template<typename Derived >
std::vector<double> qpp::rho2bloch (
    const Eigen::MatrixBase< Derived > & A )
```

Computes the 3-dimensional real Bloch vector corresponding to the qubit density matrix *A*.

See also

[qpp::bloch2rho\(\)](#)

Note

It is implicitly assumed that the density matrix is Hermitian

Parameters

<i>A</i>	Eigen expression
----------	------------------

Returns

3-dimensional Bloch vector

6.1.3.152 rho2pure()

```
template<typename Derived >
dyn_col_vect<typename Derived::Scalar> qpp::rho2pure (
    const Eigen::MatrixBase< Derived > & A )
```

Finds the pure state representation of a matrix proportional to a projector onto a pure state.

Note

No purity check is done, the input state *A* must have rank one, otherwise the function returns the first non-zero eigenvector of *A*

Parameters

<i>A</i>	Eigen expression, assumed to be proportional to a projector onto a pure state, i.e. <i>A</i> is assumed to have rank one
----------	--------------------------------------------------------------------------------------------------------------------------

Returns

The unique non-zero eigenvector of A (up to a phase), as a dynamic column vector over the same scalar field as A

6.1.3.153 `save()`

```
template<typename Derived >
void qpp::save (
    const Eigen::MatrixBase< Derived > & A,
    const std::string & fname )
```

Saves Eigen expression to a binary file (internal format) in double precision.

See also

[qpp::load\(\)](#)

Parameters

A	Eigen expression
<i>fname</i>	Output file name

6.1.3.154 `saveMATLAB()` [1/2]

```
template<typename Derived >
std::enable_if< std::is_same<typename Derived::Scalar, cplx>::value>::type qpp::saveMATLAB (
    const Eigen::MatrixBase< Derived > & A,
    const std::string & mat_file,
    const std::string & var_name,
    const std::string & mode )
```

Saves a complex Eigen dynamic matrix to a MATLAB .mat file,.

See also

[qpp::loadMATLAB\(\)](#)

Template Parameters

<i>Complex</i>	Eigen type
----------------	------------

Parameters

A	Eigen expression over the complex field
-----	-----------------------------------------

Parameters

<i>mat_file</i>	MATALB .mat file
<i>var_name</i>	Variable name in the .mat file representing the matrix to be saved
<i>mode</i>	Saving mode (append, overwrite etc.), see MATLAB <i>matOpen()</i> documentation for details

6.1.3.155 `saveMATLAB()` [2/2]

```
template<typename Derived >
std::enable_if< !std::is_same<typename Derived::Scalar, cplx>::value>::type qpp::saveMATLAB (
    const Eigen::MatrixBase< Derived > & A,
    const std::string & mat_file,
    const std::string & var_name,
    const std::string & mode )
```

Saves a non-complex Eigen dynamic matrix to a MATLAB .mat file,.

See also

[qpp::loadMATLAB\(\)](#)

Template Parameters

<i>Npn-complex</i>	Eigen type
--------------------	------------

Parameters

<i>A</i>	Non-complex Eigen expression
<i>mat_file</i>	MATALB .mat file
<i>var_name</i>	Variable name in the .mat file representing the matrix to be saved
<i>mode</i>	Saving mode (append, overwrite etc.), see MATLAB <i>matOpen()</i> documentation for details

6.1.3.156 `schatten()`

```
template<typename Derived >
double qpp::schatten (
    const Eigen::MatrixBase< Derived > & A,
    double p )
```

Schatten matrix norm.

Parameters

<i>A</i>	Eigen expression
<i>p</i>	Real number, greater or equal to 1, use qpp::infy for $p = \infty$

Returns

Schatten- p matrix norm of A

6.1.3.157 schmidtA() [1/2]

```
template<typename Derived >
cmat qpp::schmidtA (
    const Eigen::MatrixBase< Derived > & A,
    const std::vector< idx > & dims )
```

Schmidt basis on Alice side.

Parameters

A	Eigen expression
$dims$	Dimensions of the bi-partite system

Returns

Unitary matrix U whose columns represent the Schmidt basis vectors on Alice side.

6.1.3.158 schmidtA() [2/2]

```
template<typename Derived >
cmat qpp::schmidtA (
    const Eigen::MatrixBase< Derived > & A,
    idx d = 2 )
```

Schmidt basis on Alice side.

Parameters

A	Eigen expression
d	Subsystem dimensions

Returns

Unitary matrix U whose columns represent the Schmidt basis vectors on Alice side.

6.1.3.159 schmidtB() [1/2]

```
template<typename Derived >
cmat qpp::schmidtB (
```

```
const Eigen::MatrixBase< Derived > & A,
const std::vector< idx > & dims )
```

Schmidt basis on Bob side.

Parameters

<i>A</i>	Eigen expression
<i>dims</i>	Dimensions of the bi-partite system

Returns

Unitary matrix V whose columns represent the Schmidt basis vectors on Bob side.

6.1.3.160 `schmidtB()` [2/2]

```
template<typename Derived >
cmat qpp::schmidtB (
    const Eigen::MatrixBase< Derived > & A,
    idx d = 2 )
```

Schmidt basis on Bob side.

Parameters

<i>A</i>	Eigen expression
<i>d</i>	Subsystem dimensions

Returns

Unitary matrix V whose columns represent the Schmidt basis vectors on Bob side.

6.1.3.161 `schmidtcoeffs()` [1/2]

```
template<typename Derived >
dyn_col_vect<double> qpp::schmidtcoeffs (
    const Eigen::MatrixBase< Derived > & A,
    const std::vector< idx > & dims )
```

Schmidt coefficients of the bi-partite pure state A .

Note

The sum of the squares of the Schmidt coefficients equals 1

See also

[qpp::schmidtprobs\(\)](#)

Parameters

<i>A</i>	Eigen expression
<i>dims</i>	Dimensions of the bi-partite system

Returns

Schmidt coefficients of *A*, ordered in decreasing order, as a real dynamic column vector

6.1.3.162 `schmidtcoeffs()` [2/2]

```
template<typename Derived >
dyn_col_vect<double> qpp::schmidtcoeffs (
    const Eigen::MatrixBase< Derived > & A,
    idx d = 2 )
```

Schmidt coefficients of the bi-partite pure state *A*.

Note

The sum of the squares of the Schmidt coefficients equals 1

See also

[qpp::schmidtprobs\(\)](#)

Parameters

<i>A</i>	Eigen expression
<i>d</i>	Subsystem dimensions

Returns

Schmidt coefficients of *A*, ordered in decreasing order, as a real dynamic column vector

6.1.3.163 `schmidtprobs()` [1/2]

```
template<typename Derived >
std::vector<double> qpp::schmidtprobs (
    const Eigen::MatrixBase< Derived > & A,
    const std::vector< idx > & dims )
```

Schmidt probabilities of the bi-partite pure state *A*.

Defined as the squares of the Schmidt coefficients. The sum of the Schmidt probabilities equals 1.

See also

[qpp::schmidtcoeffs\(\)](#)

Parameters

<i>A</i>	Eigen expression
<i>dims</i>	Dimensions of the bi-partite system

Returns

Real vector consisting of the Schmidt probabilities of *A*, ordered in decreasing order

6.1.3.164 `schmidtprobs()` [2/2]

```
template<typename Derived >
std::vector<double> qpp::schmidtprobs (
    const Eigen::MatrixBase< Derived > & A,
    idx d = 2 )
```

Schmidt probabilities of the bi-partite pure state *A*.

Defined as the squares of the Schmidt coefficients. The sum of the Schmidt probabilities equals 1.

See also

[qpp::schmidtcoeffs\(\)](#)

Parameters

<i>A</i>	Eigen expression
<i>d</i>	Subsystem dimensions

Returns

Real vector consisting of the Schmidt probabilities of *A*, ordered in decreasing order

6.1.3.165 `sigma()`

```
template<typename Container >
double qpp::sigma (
    const std::vector< double > & prob,
    const Container & X,
    typename std::enable_if< is_iterable< Container >::value >::type * = nullptr )
```

Standard deviation.

Parameters

<i>prob</i>	Real probability vector representing the probability distribution of X
X	Real random variable values represented by an STL-like container

Returns

Standard deviation of X

6.1.3.166 `sinm()`

```
template<typename Derived >
cmat qpp::sinm (
    const Eigen::MatrixBase< Derived > & A )
```

Matrix sin.

Parameters

A	Eigen expression
-----	------------------

Returns

Matrix sine of A

6.1.3.167 `spectralpowm()`

```
template<typename Derived >
cmat qpp::spectralpowm (
    const Eigen::MatrixBase< Derived > & A,
    const cplx z )
```

Matrix power.

See also

[`qpp::powm\(\)`](#)

Uses the spectral decomposition of A to compute the matrix power. By convention $A^0 = I$.

Parameters

A	Eigen expression
z	Complex number

Returns

Matrix power A^z

6.1.3.168 sqrtm()

```
template<typename Derived >
cmat qpp::sqrtm (
    const Eigen::MatrixBase< Derived > & A )
```

Matrix square root.

Parameters

A	Eigen expression
-----	------------------

Returns

Matrix square root of A

6.1.3.169 sum() [1/3]

```
template<typename Derived >
Derived::Scalar qpp::sum (
    const Eigen::MatrixBase< Derived > & A )
```

Element-wise sum of A .

Parameters

A	Eigen expression
-----	------------------

Returns

Element-wise sum of A , as a scalar over the same scalar field as A

6.1.3.170 sum() [2/3]

```
template<typename InputIterator >
std::iterator_traits<InputIterator>::value_type qpp::sum (
    InputIterator first,
    InputIterator last )
```

Element-wise sum of an STL-like range.

Parameters

<i>first</i>	Iterator to the first element of the range
<i>last</i>	Iterator to the last element of the range

Returns

Element-wise sum of the range, as a scalar over the same scalar field as the range

6.1.3.171 `sum()` [3/3]

```
template<typename Container >
Container::value_type qpp::sum (
    const Container & c,
    typename std::enable_if< is\_iterable< Container >::value >::type * = nullptr )
```

Element-wise sum of the elements of an STL-like container.

Parameters

<i>c</i>	STL-like container
----------	--------------------

Returns

Element-wise sum of the elements of the container, as a scalar over the same scalar field as the container

6.1.3.172 `super2choi()`

```
cmat qpp::super2choi (
    const cmat & A ) [inline]
```

Converts superoperator matrix to Choi matrix.

See also

[qpp::choi2super\(\)](#)

Parameters

<i>A</i>	Superoperator matrix
----------	----------------------

Returns

Choi matrix

6.1.3.173 svals()

```
template<typename Derived >
dyn_col_vect<double> qpp::svals (
    const Eigen::MatrixBase< Derived > & A )
```

Singular values.

Parameters

<i>A</i>	Eigen expression
----------	------------------

Returns

Singular values of *A*, ordered in decreasing order, as a real dynamic column vector

6.1.3.174 svd()

```
template<typename Derived >
std::tuple<cmat, dyn_col_vect<double>, cmat> qpp::svd (
    const Eigen::MatrixBase< Derived > & A )
```

Full singular value decomposition.

Parameters

<i>A</i>	Eigen expression
----------	------------------

Returns

Tuple of: 1. Left singular vectors of *A*, as columns of a complex dynamic matrix, 2. Singular values of *A*, ordered in decreasing order, as a real dynamic column vector, and 3. Right singular vectors of *A*, as columns of a complex dynamic matrix

6.1.3.175 svdU()

```
template<typename Derived >
cmat qpp::svdU (
    const Eigen::MatrixBase< Derived > & A )
```

Left singular vectors.

Parameters

<i>A</i>	Eigen expression
----------	------------------

Returns

Complex dynamic matrix, whose columns are the left singular vectors of *A*

6.1.3.176 svdV()

```
template<typename Derived >
cmat qpp::svdV (
    const Eigen::MatrixBase< Derived > & A )
```

Right singular vectors.

Parameters

<i>A</i>	Eigen expression
----------	------------------

Returns

Complex dynamic matrix, whose columns are the right singular vectors of *A*

6.1.3.177 syspermute() [1/2]

```
template<typename Derived >
dyn_mat<typename Derived::Scalar> qpp::syspermute (
    const Eigen::MatrixBase< Derived > & A,
    const std::vector< idx > & perm,
    const std::vector< idx > & dims )
```

Subsystem permutation.

Permutes the subsystems of a state vector or density matrix. The qubit *perm*[*i*] is permuted to the location *i*.

Parameters

<i>A</i>	Eigen expression
<i>perm</i>	Permutation
<i>dims</i>	Dimensions of the multi-partite system

Returns

Permuted system, as a dynamic matrix over the same scalar field as A

6.1.3.178 syspermute() [2/2]

```
template<typename Derived >
dyn_mat<typename Derived::Scalar> qpp::syspermute (
    const Eigen::MatrixBase< Derived > & A,
    const std::vector< idx > & perm,
    idx d = 2 )
```

Subsystem permutation.

Permutes the subsystems of a state vector or density matrix. The qubit $perm[i]$ is permuted to the location i .

Parameters

A	Eigen expression
$perm$	Permutation
d	Subsystem dimensions

Returns

Permuted system, as a dynamic matrix over the same scalar field as A

6.1.3.179 TFQ()

```
template<typename Derived >
dyn_col_vect<typename Derived::Scalar> qpp::TFQ (
    const Eigen::MatrixBase< Derived > & A,
    idx d = 2,
    bool swap = true )
```

Inverse (adjoint) qudit quantum Fourier transform.

Parameters

A	Eigen expression
d	Subsystem dimensions
$swap$	Swaps the qubits/qudits at the end (true by default)

Returns

Inverse (adjoint) qudit quantum Fourier transform applied on A

6.1.3.180 trace()

```
template<typename Derived >
Derived::Scalar qpp::trace (
    const Eigen::MatrixBase< Derived > & A )
```

Trace.

Parameters

<i>A</i>	Eigen expression
----------	------------------

Returns

Trace of *A*, as a scalar over the same scalar field as *A*

6.1.3.181 transpose()

```
template<typename Derived >
dyn_mat<typename Derived::Scalar> qpp::transpose (
    const Eigen::MatrixBase< Derived > & A )
```

Transpose.

Parameters

<i>A</i>	Eigen expression
----------	------------------

Returns

Transpose of *A*, as a dynamic matrix over the same scalar field as *A*

6.1.3.182 tsallis() [1/2]

```
template<typename Derived >
double qpp::tsallis (
    const Eigen::MatrixBase< Derived > & A,
    double q )
```

Tsallis- *q* entropy of the density matrix *A*, for $q \geq 0$.

Note

When $q \rightarrow 1$ the Tsallis entropy converges to the von-Neumann entropy, with the logarithm in base *e*

Parameters

A	Eigen expression
q	Non-negative real number

Returns

Tsallis- q entropy

6.1.3.183 tsallis() [2/2]

```
double qpp::tsallis (
    const std::vector< double > & prob,
    double q ) [inline]
```

Tsallis- q entropy of the probability distribution $prob$, for $q \geq 0$.

Note

When $q \rightarrow 1$ the Tsallis entropy converges to the Shannon entropy, with the logarithm in base e

Parameters

$prob$	Real probability vector
q	Non-negative real number

Returns

Tsallis- q entropy

6.1.3.184 uniform()

```
std::vector<double> qpp::uniform (
    idx N ) [inline]
```

Uniform probability distribution vector.

Parameters

N	Size of the alphabet
-----	----------------------

Returns

Real vector consisting of a uniform distribution of size N

6.1.3.185 var()

```
template<typename Container >
double qpp::var (
    const std::vector< double > & prob,
    const Container & X,
    typename std::enable_if< is\_iterable< Container >::value >::type * = nullptr )
```

Variance.

Parameters

<i>prob</i>	Real probability vector representing the probability distribution of X
X	Real random variable values represented by an STL-like container

Returns

Variance of X

6.1.3.186 x2contfrac()

```
std::vector<int> qpp::x2contfrac (
    double x,
    idx N,
    idx cut = 1e5 ) [inline]
```

Simple continued fraction expansion.

See also

[qpp::contfrac2x\(\)](#)

Parameters

x	Real number
N	Maximum number of terms in the expansion
<i>cut</i>	Stop the expansion when the next term is greater than <i>cut</i>

Returns

Integer vector containing the simple continued fraction expansion of x . If there are M less than N terms in the expansion, a shorter vector with M components is returned.

6.1.4 Variable Documentation

6.1.4.1 chop

```
constexpr double qpp::chop = 1e-10
```

Used in [qpp::disp\(\)](#) for setting to zero numbers that have their absolute value smaller than [qpp::chop](#).

6.1.4.2 ee

```
constexpr double qpp::ee = 2.718281828459045235360287471352662497
```

Base of natural logarithm, e .

6.1.4.3 infty

```
constexpr double qpp::infty = std::numeric_limits<double>::max()
```

Used to denote infinity in double precision.

6.1.4.4 maxn

```
constexpr idx qpp::maxn = 64
```

Maximum number of allowed qubits/qudits (subsystems)

Used internally to allocate arrays on the stack (for performance reasons):

6.1.4.5 pi

```
constexpr double qpp::pi = 3.141592653589793238462643383279502884
```

π

6.2 qpp::exception Namespace Reference

Quantum++ exception hierarchy namespace.

Classes

- class [CustomException](#)
Custom exception.
- class [DimsInvalid](#)
Invalid dimension(s) exception.
- class [DimsMismatchCvector](#)
Dimension(s) mismatch column vector size exception.
- class [DimsMismatchMatrix](#)
Dimension(s) mismatch matrix size exception.
- class [DimsMismatchRvector](#)
Dimension(s) mismatch row vector size exception.
- class [DimsMismatchVector](#)
Dimension(s) mismatch vector size exception.
- class [DimsNotEqual](#)
Dimensions not equal exception.
- class [Duplicates](#)
System (e.g. std::vector) has duplicates exception.
- class [Exception](#)
Base class for generating Quantum++ custom exceptions.
- class [InvalidIterator](#)
Invalid iterator.
- class [MatrixMismatchSubsys](#)
Matrix mismatch subsystems exception.
- class [MatrixNotCvector](#)
Matrix is not a column vector exception.
- class [MatrixNotRvector](#)
Matrix is not a row vector exception.
- class [MatrixNotSquare](#)
Matrix is not square exception.
- class [MatrixNotSquareNorCvector](#)
Matrix is not square nor column vector exception.
- class [MatrixNotSquareNorRvector](#)
Matrix is not square nor row vector exception.
- class [MatrixNotSquareNorVector](#)
Matrix is not square nor vector exception.
- class [MatrixNotVector](#)
Matrix is not a vector exception.
- class [NoCodeword](#)
Codeword does not exist exception.
- class [NotBipartite](#)
Not bi-partite exception.
- class [NotImplemented](#)
Code not yet implemented.
- class [NotQubitCvector](#)
Column vector is not 2 x 1 exception.
- class [NotQubitMatrix](#)
Matrix is not 2 x 2 exception.
- class [NotQubitRvector](#)
Row vector is not 1 x 2 exception.
- class [NotQubitSubsys](#)

- Subsystems are not qubits exception.*

 - class [NotQubitVector](#)

Vector is not 2 x 1 nor 1 x 2 exception.
 - class [OutOfRange](#)

Argument out of range exception.
 - class [PermInvalid](#)

Invalid permutation exception.
 - class [PermMismatchDims](#)

Permutation mismatch dimensions exception.
 - class [QuditAlreadyMeasured](#)

Qudit was already measured exception.
 - class [SizeMismatch](#)

Size mismatch exception.
 - class [SubsysMismatchDims](#)

Subsystems mismatch dimensions exception.
 - class [TypeMismatch](#)

Type mismatch exception.
 - class [UndefinedType](#)

Not defined for this type exception.
 - class [Unknown](#)

[Unknown](#) exception.
 - class [ZeroSize](#)

Object has zero size exception.

6.2.1 Detailed Description

Quantum++ exception hierarchy namespace.

6.3 qpp::experimental Namespace Reference

Experimental/test functions/classes, do not use or modify.

6.3.1 Detailed Description

Experimental/test functions/classes, do not use or modify.

6.4 qpp::internal Namespace Reference

Internal utility functions, do not use them directly or modify them.

Classes

- struct [Display_Impl_](#)
- class [EqualEigen](#)
Functor for comparing Eigen expressions for equality.
- class [HashEigen](#)
Functor for hashing Eigen expressions.
- class [IOManipEigen](#)
- class [IOManipPointer](#)
- class [IOManipRange](#)
- class [Singleton](#)
Singleton policy class, used internally to implement the singleton pattern via CRTP (Curiously recurring template pattern)

Functions

- template<class T >
void [hash_combine](#) (std::size_t &seed, const T &v)
- void [n2multiidx](#) (idx n, idx numdims, const idx *const dims, idx *result) noexcept
- idx [multiidx2n](#) (const idx *const midx, idx numdims, const idx *const dims) noexcept
- template<typename Derived >
bool [check_square_mat](#) (const Eigen::MatrixBase< Derived > &A)
- template<typename Derived >
bool [check_vector](#) (const Eigen::MatrixBase< Derived > &A)
- template<typename Derived >
bool [check_rvector](#) (const Eigen::MatrixBase< Derived > &A)
- template<typename Derived >
bool [check_cvector](#) (const Eigen::MatrixBase< Derived > &A)
- template<typename T >
bool [check_nonzero_size](#) (const T &x) noexcept
- template<typename T1 , typename T2 >
bool [check_matching_sizes](#) (const T1 &lhs, const T2 &rhs) noexcept
- bool [check_dims](#) (const std::vector< idx > &dims)
- template<typename Derived >
bool [check_dims_match_mat](#) (const std::vector< idx > &dims, const Eigen::MatrixBase< Derived > &A)
- template<typename Derived >
bool [check_dims_match_cvect](#) (const std::vector< idx > &dims, const Eigen::MatrixBase< Derived > &A)
- template<typename Derived >
bool [check_dims_match_rvect](#) (const std::vector< idx > &dims, const Eigen::MatrixBase< Derived > &A)
- bool [check_eq_dims](#) (const std::vector< idx > &dims, idx dim) noexcept
- bool [check_no_duplicates](#) (std::vector< idx > v)
- bool [check_subsys_match_dims](#) (const std::vector< idx > &subsys, const std::vector< idx > &dims)
- template<typename Derived >
bool [check_qubit_matrix](#) (const Eigen::MatrixBase< Derived > &A) noexcept
- template<typename Derived >
bool [check_qubit_cvector](#) (const Eigen::MatrixBase< Derived > &A) noexcept
- template<typename Derived >
bool [check_qubit_rvector](#) (const Eigen::MatrixBase< Derived > &A) noexcept
- template<typename Derived >
bool [check_qubit_vector](#) (const Eigen::MatrixBase< Derived > &A) noexcept
- bool [check_perm](#) (const std::vector< idx > &perm)
- template<typename Derived1 , typename Derived2 >
[dyn_mat](#)< typename Derived1::Scalar > [kron2](#) (const Eigen::MatrixBase< Derived1 > &A, const Eigen::MatrixBase< Derived2 > &B)

- `template<typename Derived1 , typename Derived2 >`
`dyn_mat< typename Derived1::Scalar > dirsum2 (const Eigen::MatrixBase< Derived1 > &A, const Eigen::MatrixBase< Derived2 > &B)`
- `template<typename T >`
`void variadic_vector_emplace (std::vector< T > &)`
- `template<typename T , typename First , typename... Args>`
`void variadic_vector_emplace (std::vector< T > &v, First &&first, Args &&... args)`
- `idx get_num_subsys (idx D, idx d)`
- `idx get_dim_subsys (idx sz, idx N)`

6.4.1 Detailed Description

Internal utility functions, do not use them directly or modify them.

6.4.2 Function Documentation

6.4.2.1 check_cvector()

```
template<typename Derived >
bool qpp::internal::check_cvector (
    const Eigen::MatrixBase< Derived > & A )
```

6.4.2.2 check_dims()

```
bool qpp::internal::check_dims (
    const std::vector< idx > & dims ) [inline]
```

6.4.2.3 check_dims_match_cvect()

```
template<typename Derived >
bool qpp::internal::check_dims_match_cvect (
    const std::vector< idx > & dims,
    const Eigen::MatrixBase< Derived > & A )
```

6.4.2.4 check_dims_match_mat()

```
template<typename Derived >
bool qpp::internal::check_dims_match_mat (
    const std::vector< idx > & dims,
    const Eigen::MatrixBase< Derived > & A )
```


6.4.2.5 check_dims_match_rvect()

```
template<typename Derived >
bool qpp::internal::check_dims_match_rvect (
    const std::vector< idx > & dims,
    const Eigen::MatrixBase< Derived > & A )
```

6.4.2.6 check_eq_dims()

```
bool qpp::internal::check_eq_dims (
    const std::vector< idx > & dims,
    idx dim ) [inline], [noexcept]
```

6.4.2.7 check_matching_sizes()

```
template<typename T1 , typename T2 >
bool qpp::internal::check_matching_sizes (
    const T1 & lhs,
    const T2 & rhs ) [noexcept]
```

6.4.2.8 check_no_duplicates()

```
bool qpp::internal::check_no_duplicates (
    std::vector< idx > v ) [inline]
```

6.4.2.9 check_nonzero_size()

```
template<typename T >
bool qpp::internal::check_nonzero_size (
    const T & x ) [noexcept]
```

6.4.2.10 check_perm()

```
bool qpp::internal::check_perm (
    const std::vector< idx > & perm ) [inline]
```

6.4.2.11 check_qubit_cvector()

```
template<typename Derived >
bool qpp::internal::check_qubit_cvector (
    const Eigen::MatrixBase< Derived > & A ) [noexcept]
```

6.4.2.12 check_qubit_matrix()

```
template<typename Derived >
bool qpp::internal::check_qubit_matrix (
    const Eigen::MatrixBase< Derived > & A ) [noexcept]
```

6.4.2.13 check_qubit_rvector()

```
template<typename Derived >
bool qpp::internal::check_qubit_rvector (
    const Eigen::MatrixBase< Derived > & A ) [noexcept]
```

6.4.2.14 check_qubit_vector()

```
template<typename Derived >
bool qpp::internal::check_qubit_vector (
    const Eigen::MatrixBase< Derived > & A ) [noexcept]
```

6.4.2.15 check_rvector()

```
template<typename Derived >
bool qpp::internal::check_rvector (
    const Eigen::MatrixBase< Derived > & A )
```

6.4.2.16 check_square_mat()

```
template<typename Derived >
bool qpp::internal::check_square_mat (
    const Eigen::MatrixBase< Derived > & A )
```

6.4.2.17 check_subsys_match_dims()

```
bool qpp::internal::check_subsys_match_dims (
    const std::vector< idx > & subsys,
    const std::vector< idx > & dims ) [inline]
```

6.4.2.18 check_vector()

```
template<typename Derived >
bool qpp::internal::check_vector (
    const Eigen::MatrixBase< Derived > & A )
```

6.4.2.19 dirsum2()

```
template<typename Derived1 , typename Derived2 >
dyn_mat<typename Derived1::Scalar> qpp::internal::dirsum2 (
    const Eigen::MatrixBase< Derived1 > & A,
    const Eigen::MatrixBase< Derived2 > & B )
```

6.4.2.20 get_dim_subsys()

```
idx qpp::internal::get_dim_subsys (
    idx sz,
    idx N ) [inline]
```

6.4.2.21 get_num_subsys()

```
idx qpp::internal::get_num_subsys (
    idx D,
    idx d ) [inline]
```

6.4.2.22 hash_combine()

```
template<class T >
void qpp::internal::hash_combine (
    std::size_t & seed,
    const T & v )
```

6.4.2.23 kron2()

```
template<typename Derived1 , typename Derived2 >
dyn_mat<typename Derived1::Scalar> qpp::internal::kron2 (
    const Eigen::MatrixBase< Derived1 > & A,
    const Eigen::MatrixBase< Derived2 > & B )
```

6.4.2.24 multiidx2n()

```
idx qpp::internal::multiidx2n (
    const idx *const midx,
    idx numdims,
    const idx *const dims ) [inline], [noexcept]
```

6.4.2.25 n2multiidx()

```
void qpp::internal::n2multiidx (
    idx n,
    idx numdims,
    const idx *const dims,
    idx * result ) [inline], [noexcept]
```

6.4.2.26 variadic_vector_emplace() [1/2]

```
template<typename T >
void qpp::internal::variadic_vector_emplace (
    std::vector< T > & )
```

6.4.2.27 variadic_vector_emplace() [2/2]

```
template<typename T , typename First , typename... Args>
void qpp::internal::variadic_vector_emplace (
    std::vector< T > & v,
    First && first,
    Args &&... args )
```

6.5 qpp::literals Namespace Reference

Functions

- constexpr `cplx operator"" _i` (unsigned long long int x) noexcept
User-defined literal for complex $i = \sqrt{-1}$ (integer overload)
- template<char... Bits>
`ket operator"" _ket` ()
Multi-partite qubit ket user-defined literal.
- template<char... Bits>
`bra operator"" _bra` ()
Multi-partite qubit bra user-defined literal.
- template<char... Bits>
`cmat operator"" _prj` ()
Multi-partite qubit projector user-defined literal.

6.5.1 Function Documentation

6.5.1.1 `operator"" _bra()`

```
template<char... Bits>
bra qpp::literals::operator"" _bra ( )
```

Multi-partite qubit bra user-defined literal.

See also

`qpp::mket()` and `qpp::adjoint()`

Constructs the multi-partite qubit bra $\langle \text{Bits} |$

Template Parameters

<i>Bits</i>	String of binary numbers representing the qubit bra
-------------	-----------------------------------------------------

Returns

Multi-partite qubit bra, as a complex dynamic row vector

6.5.1.2 `operator"" _i()`

```
constexpr cplx qpp::literals::operator"" _i (
    unsigned long long int x ) [inline], [noexcept]
```

User-defined literal for complex $i = \sqrt{-1}$ (integer overload)

Example:

```
cplx z = 4_i; // type of z is std::complex<double>
```

6.5.1.3 operator"" _ket()

```
template<char... Bits>
ket qpp::literals::operator"" _ket ( )
```

Multi-partite qubit ket user-defined literal.

See also

[qpp::mket\(\)](#)

Constructs the multi-partite qubit ket $|\text{Bits}\rangle$

Template Parameters

<i>Bits</i>	String of binary numbers representing the qubit ket
-------------	-----------------------------------------------------

Returns

Multi-partite qubit ket, as a complex dynamic column vector

6.5.1.4 operator"" _prj()

```
template<char... Bits>
cmat qpp::literals::operator"" _prj ( )
```

Multi-partite qubit projector user-defined literal.

See also

[qpp::mprj\(\)](#)

Constructs the multi-partite qubit projector $|\text{Bits}\rangle\langle\text{Bits}|$ (in the computational basis)

Template Parameters

<i>Bits</i>	String of binary numbers representing the qubit state to project on
-------------	---------------------------------------------------------------------

Returns

Multi-partite qubit projector, as a complex dynamic matrix

Chapter 7


Class Documentation

7.1 qpp::Bit_circuit Class Reference


Classical reversible circuit simulator.

```
#include <classes/reversible.h>
```

Inheritance diagram for qpp::Bit_circuit:



Collaboration diagram for `qpp::Bit_circuit`:



Classes

- struct [Gate_count](#)

Public Member Functions

- [Bit_circuit](#) (const [Dynamic_bitset](#) &dynamic_bitset)
Conversion constructor, used to initialize a `qpp::Bit_circuit` with a `qpp::Dynamic_bitset`.
- [Bit_circuit](#) & [X](#) (idx pos)
Bit flip.
- [Bit_circuit](#) & [NOT](#) (idx pos)
Bit flip.
- [Bit_circuit](#) & [CNOT](#) (const std::vector< idx > &pos)
Controlled-NOT.
- [Bit_circuit](#) & [TOF](#) (const std::vector< idx > &pos)
Toffoli gate.
- [Bit_circuit](#) & [SWAP](#) (const std::vector< idx > &pos)
Swap bits.
- [Bit_circuit](#) & [FRED](#) (const std::vector< idx > &pos)
Fredkin gate (Controlled-SWAP)
- [Bit_circuit](#) & [reset](#) () noexcept
Reset the circuit all zero, clear all gates.
- [Dynamic_bitset](#) (idx N)
Inherited constructor.

Public Attributes

- struct [qpp::Bit_circuit::Gate_count](#) `gate_count`
Gate counters.

Additional Inherited Members

7.1.1 Detailed Description

Classical reversible circuit simulator.

7.1.2 Constructor & Destructor Documentation

7.1.2.1 Bit_circuit()

```
qpp::Bit_circuit::Bit_circuit (
    const Dynamic\_bitset & dynamic_bitset ) [inline], [explicit]
```

Conversion constructor, used to initialize a [qpp::Bit_circuit](#) with a [qpp::Dynamic_bitset](#).

Parameters

<i>dynamic_bitset</i>	Dynamic bitset
-----------------------	----------------

7.1.3 Member Function Documentation

7.1.3.1 CNOT()

```
Bit\_circuit& qpp::Bit_circuit::CNOT (
    const std::vector< idx > & pos ) [inline]
```

Controlled-NOT.

Parameters

<i>pos</i>	Bit position in the circuit
------------	-----------------------------

Returns

Reference to the current instance

7.1.3.2 Dynamic_bitset()

```
qpp::Dynamic_bitset::Dynamic_bitset [inline], [explicit]
```

Inherited constructor.

7.1.3.3 FRED()

```
Bit_circuit& qpp::Bit_circuit::FRED (
    const std::vector< idx > & pos ) [inline]
```

Fredkin gate (Controlled-SWAP)

Parameters

<i>pos</i>	Bit positions in the circuit, in the order control-target-target
------------	------------------------------------------------------------------

Returns

Reference to the current instance

7.1.3.4 NOT()

```
Bit_circuit& qpp::Bit_circuit::NOT (
    idx pos ) [inline]
```

Bit flip.

See also

[qpp::Bit_circuit::X\(\)](#)

Parameters

<i>pos</i>	Bit position in the circuit
------------	-----------------------------

Returns

Reference to the current instance

7.1.3.5 reset()

```
Bit_circuit& qpp::Bit_circuit::reset ( ) [inline], [noexcept]
```

Reset the circuit all zero, clear all gates.

Returns

Reference to the current instance

7.1.3.6 SWAP()

```
Bit_circuit& qpp::Bit_circuit::SWAP (
    const std::vector< idx > & pos ) [inline]
```

Swap bits.

Parameters

<i>pos</i>	Bit positions in the circuit
------------	------------------------------

Returns

Reference to the current instance

7.1.3.7 TOF()

```
Bit_circuit& qpp::Bit_circuit::TOF (
    const std::vector< idx > & pos ) [inline]
```

Toffoli gate.

Parameters

<i>pos</i>	Bit positions in the circuit, in the order control-control-target
------------	-------------------------------------------------------------------

Returns

Reference to the current instance

7.1.3.8 X()

```
Bit_circuit& qpp::Bit_circuit::X (
    idx pos ) [inline]
```

Bit flip.

See also

[qpp::Bit_circuit::NOT\(\)](#)

Parameters

<i>pos</i>	Bit position in the circuit
------------	-----------------------------

Returns

Reference to the current instance

7.1.4 Member Data Documentation

7.1.4.1 gate_count

```
struct qpp::Bit_circuit::Gate_count qpp::Bit_circuit::gate_count
```

Gate counters.

The documentation for this class was generated from the following file:


- [classes/reversible.h](#)

7.2 qpp::Codes Class Reference


const Singleton class that defines quantum error correcting codes

```
#include <classes/codes.h>
```

Inheritance diagram for qpp::Codes:



Collaboration diagram for qpp::Codes:



Public Types

- enum `Type` { `Type::FIVE_QUBIT` = 1, `Type::SEVEN_QUBIT_STEANE`, `Type::NINE_QUBIT_SHOR` }
Code types, add more codes here if needed.

Public Member Functions

- `ket codeword` (`Type` type, `idx` i) const
Returns the codeword of the specified code type.

Private Member Functions

- `Codes` ()
Default constructor.
- `~Codes` ()=default
Default destructor.

Friends

- class `internal::Singleton< const Codes >`

Additional Inherited Members

7.2.1 Detailed Description

const Singleton class that defines quantum error correcting codes

7.2.2 Member Enumeration Documentation

7.2.2.1 Type

```
enum qpp::Codes::Type [strong]
```

Code types, add more codes here if needed.

See also

[qpp::Codes::codeword\(\)](#)

Enumerator

FIVE_QUBIT	[[5,1,3]] qubit code
SEVEN_QUBIT_STEANE	[[7,1,3]] Steane qubit code
NINE_QUBIT_SHOR	[[9,1,3]] Shor qubit code

7.2.3 Constructor & Destructor Documentation

7.2.3.1 Codes()

```
qpp::Codes::Codes ( ) [inline], [private]
```

Default constructor.

7.2.3.2 ~Codes()

```
qpp::Codes::~~Codes ( ) [private], [default]
```

Default destructor.

7.2.4 Member Function Documentation

7.2.4.1 codeword()

```
ket qpp::Codes::codeword (
    Type type,
    idx i ) const [inline]
```

Returns the codeword of the specified code type.

See also

[qpp::Codes::Type](#)

Parameters

<i>type</i>	Code type
<i>i</i>	Codeword index

Returns

i-th codeword of the code *type*

7.2.5 Friends And Related Function Documentation

7.2.5.1 internal::Singleton< const Codes >

```
friend class internal::Singleton< const Codes > [friend]
```

The documentation for this class was generated from the following file:


- [classes/codes.h](#)

7.3 qpp::exception::CustomException Class Reference


Custom exception.

```
#include <classes/exception.h>
```

Inheritance diagram for qpp::exception::CustomException:



Collaboration diagram for `qpp::exception::CustomException`:



Public Member Functions

- [CustomException](#) (const std::string &where, const std::string &[what](#))

Private Member Functions

- std::string [type_description](#) () const override
[Exception](#) type description.

Private Attributes

- std::string [what_](#) {}

7.3.1 Detailed Description

Custom exception.

Custom exception, the user must provide a custom message

7.3.2 Constructor & Destructor Documentation

7.3.2.1 CustomException()

```
qpp::exception::CustomException::CustomException (
    const std::string & where,
    const std::string & what ) [inline]
```

7.3.3 Member Function Documentation

7.3.3.1 type_description()

```
std::string qpp::exception::CustomException::type_description( ) const [inline], [override],
[private], [virtual]
```

[Exception](#) type description.

Returns

[Exception](#) type description

Implements [qpp::exception::Exception](#).

7.3.4 Member Data Documentation

7.3.4.1 what_

```
std::string qpp::exception::CustomException::what_ {} [private]
```

The documentation for this class was generated from the following file:


- [classes/exception.h](#)

7.4 qpp::exception::DimsInvalid Class Reference


Invalid dimension(s) exception.

```
#include <classes/exception.h>
```

Inheritance diagram for qpp::exception::DimsInvalid:



Collaboration diagram for qpp::exception::DimsInvalid:



Public Member Functions

- `std::string type_description ()` const override
Exception type description.
- `Exception (const std::string &where)`
Constructs an exception.

7.4.1 Detailed Description

Invalid dimension(s) exception.

`std::vector<idx>` of dimensions has zero size or contains zeros

7.4.2 Member Function Documentation

7.4.2.1 Exception()

```
qpp::exception::Exception::Exception [inline], [explicit]
```

Constructs an exception.

Parameters

<i>where</i>	Text representing where the exception occurred
--------------	------------------------------------------------

7.4.2.2 type_description()

```
std::string qpp::exception::DimsInvalid::type_description ( ) const [inline], [override],  
[virtual]
```

[Exception](#) type description.

Returns

[Exception](#) type description

Implements [qpp::exception::Exception](#).

The documentation for this class was generated from the following file:


- [classes/exception.h](#)

7.5 qpp::exception::DimsMismatchCvector Class Reference


Dimension(s) mismatch column vector size exception.

```
#include <classes/exception.h>
```

Inheritance diagram for qpp::exception::DimsMismatchCvector:



Collaboration diagram for qpp::exception::DimsMismatchCvector:



Public Member Functions

- `std::string type_description ()` const override
Exception type description.
- `Exception (const std::string &where)`
Constructs an exception.

7.5.1 Detailed Description

Dimension(s) mismatch column vector size exception.

Product of the elements of `std::vector<idx>` of dimensions is not equal to the number of elements of the Eigen::↵ Matrix (assumed to be a column vector)

7.5.2 Member Function Documentation

7.5.2.1 Exception()

```
qpp::exception::Exception::Exception [inline], [explicit]
```

Constructs an exception.

Parameters

<i>where</i>	Text representing where the exception occurred
--------------	------------------------------------------------

7.5.2.2 type_description()

```
std::string qpp::exception::DimsMismatchCvector::type_description ( ) const [inline], [override], [virtual]
```

[Exception](#) type description.

Returns

[Exception](#) type description

Implements [qpp::exception::Exception](#).

The documentation for this class was generated from the following file:


- `classes/exception.h`

7.6 qpp::exception::DimsMismatchMatrix Class Reference


Dimension(s) mismatch matrix size exception.

```
#include <classes/exception.h>
```

Inheritance diagram for qpp::exception::DimsMismatchMatrix:



Collaboration diagram for qpp::exception::DimsMismatchMatrix:



Public Member Functions

- `std::string type_description ()` const override
Exception type description.
- `Exception (const std::string &where)`
Constructs an exception.

7.6.1 Detailed Description

Dimension(s) mismatch matrix size exception.

Product of the elements of `std::vector<idx>` of dimensions is not equal to the number of rows of the `Eigen::Matrix` (assumed to be a square matrix)

7.6.2 Member Function Documentation

7.6.2.1 Exception()

```
qpp::exception::Exception::Exception [inline], [explicit]
```

Constructs an exception.

Parameters

<i>where</i>	Text representing where the exception occurred
--------------	------------------------------------------------

7.6.2.2 type_description()

```
std::string qpp::exception::DimsMismatchMatrix::type_description ( ) const [inline], [override], [virtual]
```

`Exception` type description.

Returns

`Exception` type description

Implements `qpp::exception::Exception`.

The documentation for this class was generated from the following file:


- `classes/exception.h`

7.7 qpp::exception::DimsMismatchRvector Class Reference


Dimension(s) mismatch row vector size exception.

```
#include <classes/exception.h>
```

Inheritance diagram for qpp::exception::DimsMismatchRvector:



Collaboration diagram for qpp::exception::DimsMismatchRvector:



Public Member Functions

- `std::string type_description ()` const override
Exception type description.
- `Exception (const std::string &where)`
Constructs an exception.

7.7.1 Detailed Description

Dimension(s) mismatch row vector size exception.

Product of the elements of `std::vector<idx>` of dimensions is not equal to the number of elements of the Eigen::↵ Matrix (assumed to be a row vector)

7.7.2 Member Function Documentation

7.7.2.1 Exception()

```
qpp::exception::Exception::Exception [inline], [explicit]
```

Constructs an exception.

Parameters

<i>where</i>	Text representing where the exception occurred
--------------	------------------------------------------------

7.7.2.2 type_description()

```
std::string qpp::exception::DimsMismatchRvector::type_description ( ) const [inline], [override], [virtual]
```

[Exception](#) type description.

Returns

[Exception](#) type description

Implements [qpp::exception::Exception](#).

The documentation for this class was generated from the following file:


- `classes/exception.h`

7.8 qpp::exception::DimsMismatchVector Class Reference


Dimension(s) mismatch vector size exception.

```
#include <classes/exception.h>
```

Inheritance diagram for qpp::exception::DimsMismatchVector:



Collaboration diagram for qpp::exception::DimsMismatchVector:



Public Member Functions

- `std::string type_description ()` const override
Exception type description.
- `Exception (const std::string &where)`
Constructs an exception.

7.8.1 Detailed Description

Dimension(s) mismatch vector size exception.

Product of the elements of `std::vector<idx>` of dimensions is not equal to the number of elements of the Eigen::↵ Matrix (assumed to be a row/column vector)

7.8.2 Member Function Documentation

7.8.2.1 Exception()

```
qpp::exception::Exception::Exception [inline], [explicit]
```

Constructs an exception.

Parameters

<i>where</i>	Text representing where the exception occurred
--------------	------------------------------------------------

7.8.2.2 type_description()

```
std::string qpp::exception::DimsMismatchVector::type_description ( ) const [inline], [override], [virtual]
```

[Exception](#) type description.

Returns

[Exception](#) type description

Implements [qpp::exception::Exception](#).

The documentation for this class was generated from the following file:


- `classes/exception.h`

7.9 qpp::exception::DimsNotEqual Class Reference


Dimensions not equal exception.

```
#include <classes/exception.h>
```

Inheritance diagram for qpp::exception::DimsNotEqual:



Collaboration diagram for qpp::exception::DimsNotEqual:



Public Member Functions

- `std::string type_description ()` const override
Exception type description.
- `Exception (const std::string &where)`
Constructs an exception.

7.9.1 Detailed Description

Dimensions not equal exception.

Local/global dimensions are not equal

7.9.2 Member Function Documentation

7.9.2.1 Exception()

```
qpp::exception::Exception::Exception [inline], [explicit]
```

Constructs an exception.

Parameters

<i>where</i>	Text representing where the exception occurred
--------------	------------------------------------------------

7.9.2.2 type_description()

```
std::string qpp::exception::DimsNotEqual::type_description ( ) const [inline], [override],  
[virtual]
```

[Exception](#) type description.

Returns

[Exception](#) type description

Implements [qpp::exception::Exception](#).


The documentation for this class was generated from the following file:

- `classes/exception.h`

7.10 qpp::internal::Display_Impl_ Struct Reference

```
#include <internal/util.h>
```

Inheritance diagram for qpp::internal::Display_Impl_:



Public Member Functions

- `template<typename T >`
`std::ostream & display_impl_ (const T &A, std::ostream &os, double chop=qpp::chop) const`

7.10.1 Member Function Documentation

7.10.1.1 display_impl_()

```
template<typename T >
std::ostream& qpp::internal::Display_Impl_::display_impl_ (
    const T & A,
    std::ostream & os,
    double chop = qpp::chop ) const [inline]
```

The documentation for this struct was generated from the following file:


- `internal/util.h`

7.11 qpp::exception::Duplicates Class Reference


System (e.g. `std::vector`) has duplicates exception.

```
#include <classes/exception.h>
```

Inheritance diagram for `qpp::exception::Duplicates`:



Collaboration diagram for `qpp::exception::Duplicates`:



Public Member Functions

- `std::string type_description ()` const override
Exception type description.
- `Exception (const std::string &where)`
Constructs an exception.

7.11.1 Detailed Description

System (e.g. `std::vector`) has duplicates exception.

7.11.2 Member Function Documentation

7.11.2.1 Exception()

```
qpp::exception::Exception::Exception [inline], [explicit]
```

Constructs an exception.

Parameters

<i>where</i>	Text representing where the exception occurred
--------------	------------------------------------------------

7.11.2.2 type_description()

```
std::string qpp::exception::Duplicates::type_description ( ) const [inline], [override],  
[virtual]
```

`Exception` type description.

Returns

`Exception` type description

Implements `qpp::exception::Exception`.

The documentation for this class was generated from the following file:


- `classes/exception.h`

7.12 qpp::Dynamic_bitset Class Reference


Dynamic bitset class, allows the specification of the number of bits at runtime (unlike `std::bitset<N>`)

```
#include <classes/reversible.h>
```

Inheritance diagram for `qpp::Dynamic_bitset`:



Collaboration diagram for `qpp::Dynamic_bitset`:



Public Types

- using `value_type` = unsigned int
Type of the storage elements.
- using `storage_type` = `std::vector<value_type>`
Type of the storage.

Public Member Functions

- [Dynamic_bitset](#) ([idx](#) N)
Constructor, initializes all bits to false (zero)
- virtual [~Dynamic_bitset](#) ()=default
Default virtual destructor.
- const [storage_type](#) & [data](#) () const
Raw storage space of the bitset.
- [idx](#) [size](#) () const noexcept
Number of bits stored in the bitset.
- [idx](#) [storage_size](#) () const noexcept
Size of the underlying storage space (in units of value_type, unsigned int by default)
- [idx](#) [count](#) () const noexcept
Number of bits set to one in the bitset (Hamming weight)
- bool [get](#) ([idx](#) pos) const noexcept
The value of the bit at position pos.
- bool [none](#) () const noexcept
Checks whether none of the bits are set.
- bool [all](#) () const noexcept
Checks whether all bits are set.
- bool [any](#) () const noexcept
Checks whether any bit is set.
- [Dynamic_bitset](#) & [set](#) ([idx](#) pos, bool value=true)
Sets the bit at position pos.
- [Dynamic_bitset](#) & [set](#) () noexcept
Set all bits to true.
- [Dynamic_bitset](#) & [rand](#) ([idx](#) pos, double p=0.5)
Sets the bit at position pos according to a Bernoulli(p) distribution.
- [Dynamic_bitset](#) & [rand](#) (double p=0.5)
Sets all bits according to a Bernoulli(p) distribution.
- [Dynamic_bitset](#) & [reset](#) ([idx](#) pos)
Sets the bit at position pos to false.
- [Dynamic_bitset](#) & [reset](#) () noexcept
Sets all bits to false.
- [Dynamic_bitset](#) & [flip](#) ([idx](#) pos)
Flips the bit at position pos.
- [Dynamic_bitset](#) & [flip](#) () noexcept
Flips all bits.
- bool [operator==](#) (const [Dynamic_bitset](#) &rhs) const noexcept
Equality operator.
- bool [operator!=](#) (const [Dynamic_bitset](#) &rhs) const noexcept
Inequality operator.
- [idx](#) [operator-](#) (const [Dynamic_bitset](#) &rhs) const noexcept
Number of places the two bitsets differ (Hamming distance)
- template<class CharT = char, class Traits = std::char_traits<CharT>, class Allocator = std::allocator<CharT>>
std::basic_string< CharT, Traits, Allocator > [to_string](#) (CharT zero=CharT('0'), CharT one=CharT('1')) const
String representation.

Protected Member Functions

- `idx index_ (idx pos) const`
Index of the pos bit in the storage space.
- `idx offset_ (idx pos) const`
Offset of the pos bit in the storage space relative to its index.

Protected Attributes

- `idx storage_size_`
Storage size.
- `idx N_`
Number of bits.
- `std::vector< value_type > v_`
Storage space.

Private Member Functions

- `std::ostream & display (std::ostream &os) const` override
qpp::IDisplay::display() override, displays the bitset bit by bit

7.12.1 Detailed Description

Dynamic bitset class, allows the specification of the number of bits at runtime (unlike `std::bitset<N>`)

7.12.2 Member Typedef Documentation

7.12.2.1 storage_type

```
using qpp::Dynamic_bitset::storage_type = std::vector<value_type>
```

Type of the storage.

7.12.2.2 value_type

```
using qpp::Dynamic_bitset::value_type = unsigned int
```

Type of the storage elements.

7.12.3 Constructor & Destructor Documentation

7.12.3.1 Dynamic_bitset()

```
qpp::Dynamic_bitset::Dynamic_bitset (
    idx N ) [inline], [explicit]
```

Constructor, initializes all bits to false (zero)

Parameters

<i>N</i>	Number of bits in the bitset
----------	------------------------------

7.12.3.2 ~Dynamic_bitset()

```
virtual qpp::Dynamic_bitset::~~Dynamic_bitset ( ) [virtual], [default]
```

Default virtual destructor.

7.12.4 Member Function Documentation

7.12.4.1 all()

```
bool qpp::Dynamic_bitset::all ( ) const [inline], [noexcept]
```

Checks whether all bits are set.

Returns

True if all of the bits are set

7.12.4.2 any()

```
bool qpp::Dynamic_bitset::any ( ) const [inline], [noexcept]
```

Checks whether any bit is set.

Returns

True if any of the bits is set

7.12.4.3 count()

```
idx qpp::Dynamic_bitset::count ( ) const [inline], [noexcept]
```

Number of bits set to one in the bitset (Hamming weight)

Returns

Hamming weight

7.12.4.4 data()

```
const storage_type& qpp::Dynamic_bitset::data ( ) const [inline]
```

Raw storage space of the bitset.

Returns

Const reference to the underlying storage space

7.12.4.5 display()

```
std::ostream& qpp::Dynamic_bitset::display (
    std::ostream & os ) const [inline], [override], [private], [virtual]
```

[qpp::IDisplay::display\(\)](#) override, displays the bitset bit by bit

Parameters

<i>os</i>	Output stream passed by reference
-----------	-----------------------------------

Returns

Reference to the output stream

Implements [qpp::IDisplay](#).

7.12.4.6 flip() [1/2]

```
Dynamic_bitset& qpp::Dynamic_bitset::flip (
    idx pos ) [inline]
```

Flips the bit at position *pos*.

Parameters

<i>pos</i>	Position in the bitset
------------	------------------------

Returns

Reference to the current instance

7.12.4.7 flip() [2/2]

```
Dynamic_bitset& qpp::Dynamic_bitset::flip ( ) [inline], [noexcept]
```

Flips all bits.

Returns

Reference to the current instance

7.12.4.8 get()

```
bool qpp::Dynamic_bitset::get (
    idx pos ) const [inline], [noexcept]
```

The value of the bit at position *pos*.

Parameters

<i>pos</i>	Position in the bitset
------------	------------------------

Returns

The value of the bit at position *pos*

7.12.4.9 index_()

```
idx qpp::Dynamic_bitset::index_ (
    idx pos ) const [inline], [protected]
```

Index of the *pos* bit in the storage space.

Parameters

<i>pos</i>	Bit location
------------	--------------

Returns

Index of the *pos* bit in the storage space

7.12.4.10 none()

```
bool qpp::Dynamic_bitset::none ( ) const [inline], [noexcept]
```

Checks whether none of the bits are set.

Returns

True if none of the bits are set

7.12.4.11 offset_()

```
idx qpp::Dynamic_bitset::offset_ (
    idx pos ) const [inline], [protected]
```

Offset of the *pos* bit in the storage space relative to its index.

Parameters

<i>pos</i>	Bit location
------------	--------------

Returns

Offset of the *pos* bit in the storage space relative to its index

7.12.4.12 operator!=(())

```
bool qpp::Dynamic_bitset::operator!= (
    const Dynamic_bitset & rhs ) const [inline], [noexcept]
```

Inequality operator.

Parameters

<i>rhs</i>	Dynamic_bitset against which the inequality is being tested
------------	-----------------------------------------------------------------------------

Returns

True if the bitsets are not equal (bit by bit), false otherwise

7.12.4.13 operator-()

```
idx qpp::Dynamic_bitset::operator- (
    const Dynamic_bitset & rhs ) const [inline], [noexcept]
```

Number of places the two bitsets differ (Hamming distance)

Parameters

<i>rhs</i>	Dynamic_bitset against which the the Hamming distance is computed
------------	-----------------------------------------------------------------------------------

Returns

Hamming distance

7.12.4.14 operator==()

```
bool qpp::Dynamic_bitset::operator== (
    const Dynamic_bitset & rhs ) const [inline], [noexcept]
```

Equality operator.

Parameters

<i>rhs</i>	Dynamic_bitset against which the equality is being tested
------------	---------------------------------------------------------------------------

Returns

True if the bitsets are equal (bit by bit), false otherwise

7.12.4.15 rand() [1/2]

```
Dynamic_bitset& qpp::Dynamic_bitset::rand (
    idx pos,
    double p = 0.5 ) [inline]
```

Sets the bit at position *pos* according to a Bernoulli(*p*) distribution.

Parameters

<i>pos</i>	Position in the bitset
<i>p</i>	Probability

Returns

Reference to the current instance

7.12.4.16 rand() [2/2]

```
Dynamic_bitset& qpp::Dynamic_bitset::rand (
    double p = 0.5 ) [inline]
```

Sets all bits according to a Bernoulli(*p*) distribution.

Parameters

<i>p</i>	Probability
----------	-------------

Returns

Reference to the current instance

7.12.4.17 reset() [1/2]

```
Dynamic_bitset& qpp::Dynamic_bitset::reset (
    idx pos ) [inline]
```

Sets the bit at position *pos* to false.

Parameters

<i>pos</i>	Position in the bitset
------------	------------------------

Returns

Reference to the current instance

7.12.4.18 reset() [2/2]

```
Dynamic_bitset& qpp::Dynamic_bitset::reset ( ) [inline], [noexcept]
```

Sets all bits to false.

Returns

Reference to the current instance

7.12.4.19 `set()` [1/2]

```
Dynamic_bitset& qpp::Dynamic_bitset::set (
    idx pos,
    bool value = true ) [inline]
```

Sets the bit at position *pos*.

Parameters

<i>pos</i>	Position in the bitset
<i>value</i>	Bit value

Returns

Reference to the current instance

7.12.4.20 `set()` [2/2]

```
Dynamic_bitset& qpp::Dynamic_bitset::set ( ) [inline], [noexcept]
```

Set all bits to true.

Returns

Reference to the current instance

7.12.4.21 `size()`

```
idx qpp::Dynamic_bitset::size ( ) const [inline], [noexcept]
```

Number of bits stored in the bitset.

Returns

Number of bits stored in the bitset

7.12.4.22 `storage_size()`

```
idx qpp::Dynamic_bitset::storage_size ( ) const [inline], [noexcept]
```

Size of the underlying storage space (in units of `value_type`, unsigned int by default)

Returns

Size of the underlying storage space

7.12.4.23 to_string()

```
template<class CharT = char, class Traits = std::char_traits<CharT>, class Allocator = std::allocator<CharT>>
std::basic_string<CharT, Traits, Allocator> qpp::Dynamic_bitset::to_string (
    CharT zero = CharT('0'),
    CharT one = CharT('1') ) const [inline]
```

String representation.

Template Parameters

<i>CharT</i>	String character type
<i>Traits</i>	String traits
<i>Allocator</i>	String Allocator

Parameters

<i>zero</i>	Character representing the zero
<i>one</i>	Character representing the one

Returns

The bitset as a string

7.12.5 Member Data Documentation

7.12.5.1 N_

`idx` qpp::Dynamic_bitset::N_ [protected]

Number of bits.

7.12.5.2 storage_size_

`idx` qpp::Dynamic_bitset::storage_size_ [protected]

Storage size.

7.12.5.3 v_

```
std::vector<value_type> qpp::Dynamic_bitset::v_ [protected]
```

Storage space.

The documentation for this class was generated from the following file:

- [classes/reversible.h](#)

7.13 qpp::internal::EqualEigen Class Reference

Functor for comparing Eigen expressions for equality.

```
#include <functions.h>
```

Public Member Functions

- `template<typename Derived >`
`bool operator\(\) (const Eigen::MatrixBase< Derived > &A, const Eigen::MatrixBase< Derived > &B) const`

7.13.1 Detailed Description

Functor for comparing Eigen expressions for equality.

Note

Works without assertion fails even if the dimensions of the arguments are different (in which case simply returns false)

7.13.2 Member Function Documentation

7.13.2.1 `operator()()`

```
template<typename Derived >
bool qpp::internal::EqualEigen::operator() (
    const Eigen::MatrixBase< Derived > & A,
    const Eigen::MatrixBase< Derived > & B ) const [inline]
```

The documentation for this class was generated from the following file:


- [functions.h](#)

7.14 qpp::exception::Exception Class Reference


Base class for generating Quantum++ custom exceptions.

```
#include <classes/exception.h>
```

Inheritance diagram for qpp::exception::Exception:



Collaboration diagram for `qpp::exception::Exception`:



Public Member Functions

- [Exception](#) (const std::string &where)
Constructs an exception.
- virtual const char * [what](#) () const noexcept override
Overrides std::exception::what()
- virtual std::string [type_description](#) () const =0
Exception type description.

Private Attributes

- std::string [where_](#)
- std::string [msg_](#)

7.14.1 Detailed Description

Base class for generating Quantum++ custom exceptions.

Derive from this class if more exceptions are needed, making sure to override [qpp::exception::Exception::type_description\(\)](#) in the derived class and to inherit the constructor [qpp::exception::Exception::Exception\(\)](#). Preferably keep your newly defined exception classes in the namespace [qpp::exception](#).

Example:


```

namespace qpp
{
namespace exception
{
    class ZeroSize : public Exception
    {
    public:
        std::string type_description() const override
        {
            return "Object has zero size";
        }

        // inherit the base class' qpp::exception::Exception constructor
        using Exception::Exception;
    };
} // namespace exception
} // namespace qpp

```

7.14.2 Constructor & Destructor Documentation

7.14.2.1 Exception()

```

qpp::exception::Exception::Exception (
    const std::string & where ) [inline], [explicit]

```

Constructs an exception.

Parameters

<i>where</i>	Text representing where the exception occurred
--------------	------------------------------------------------

7.14.3 Member Function Documentation

7.14.3.1 type_description()

```

std::string qpp::exception::Exception::type_description ( ) const [inline], [pure virtual]

```

[Exception](#) type description.

Returns

[Exception](#) type description

Implemented in [qpp::exception::InvalidIterator](#), [qpp::exception::NotImplemented](#), [qpp::exception::CustomException](#), [qpp::exception::Duplicates](#), [qpp::exception::QuditAlreadyMeasured](#), [qpp::exception::UndefinedType](#), [qpp::exception::SizeMismatch](#), [qpp::exception::TypeMismatch](#), [qpp::exception::OutOfRange](#), [qpp::exception::NoCodeword](#), [qpp::exception::NotBipartite](#), [qpp::exception::NotQubitSubsys](#), [qpp::exception::NotQubitVector](#), [qpp::exception::NotQubitRvector](#), [qpp::exception::NotQubitCvector](#), [qpp::exception::NotQubitMatrix](#), [qpp::exception::PermMismatchDims](#), [qpp::exception::PermInvalid](#), [qpp::exception::SubsysMismatchD](#), [qpp::exception::DimsMismatchVector](#), [qpp::exception::DimsMismatchRvector](#), [qpp::exception::DimsMismatchCvector](#), [qpp::exception::DimsMismatchMatrix](#), [qpp::exception::DimsNotEqual](#), [qpp::exception::DimsInvalid](#), [qpp::exception::MatrixMismatchSu](#), [qpp::exception::MatrixNotSquareNorVector](#), [qpp::exception::MatrixNotSquareNorRvector](#), [qpp::exception::MatrixNotSquareNorCvector](#), [qpp::exception::MatrixNotVector](#), [qpp::exception::MatrixNotRvector](#), [qpp::exception::MatrixNotCvector](#), [qpp::exception::MatrixNotSqua](#), [qpp::exception::ZeroSize](#), and [qpp::exception::Unknown](#).

7.14.3.2 what()

```
virtual const char* qpp::exception::Exception::what ( ) const [inline], [override], [virtual],  
[noexcept]
```

Overrides `std::exception::what()`

Returns

[Exception](#) description

7.14.4 Member Data Documentation

7.14.4.1 msg_

```
std::string qpp::exception::Exception::msg_ [mutable], [private]
```

7.14.4.2 where_

```
std::string qpp::exception::Exception::where_ [private]
```

The documentation for this class was generated from the following file:

- [classes/exception.h](#)

7.15 qpp::Bit_circuit::Gate_count Struct Reference

```
#include <classes/reversible.h>
```

Public Attributes

- [idx NOT](#) = 0
- [idx & X](#) = NOT
- [idx CNOT](#) = 0
- [idx SWAP](#) = 0
- [idx FRED](#) = 0
- [idx TOF](#) = 0

7.15.1 Member Data Documentation

7.15.1.1 CNOT

```
idx qpp::Bit_circuit::Gate_count::CNOT = 0
```

7.15.1.2 FRED

```
idx qpp::Bit_circuit::Gate_count::FRED = 0
```

7.15.1.3 NOT

```
idx qpp::Bit_circuit::Gate_count::NOT = 0
```

7.15.1.4 SWAP

```
idx qpp::Bit_circuit::Gate_count::SWAP = 0
```

7.15.1.5 TOF

```
idx qpp::Bit_circuit::Gate_count::TOF = 0
```

7.15.1.6 X

```
idx& qpp::Bit_circuit::Gate_count::X = NOT
```

The documentation for this struct was generated from the following file:


- [classes/reversible.h](#)

7.16 qpp::Gates Class Reference


const Singleton class that implements most commonly used gates

```
#include <classes/gates.h>
```

Inheritance diagram for qpp::Gates:



Collaboration diagram for qpp::Gates:



Public Member Functions

- **cmat Rn** (double theta, const std::vector< double > &n) const
Qubit rotation of theta about the 3-dimensional real (unit) vector n.
- **cmat RX** (double theta) const
Qubit rotation of theta about the X axis.
- **cmat RY** (double theta) const
Qubit rotation of theta about the Y axis.
- **cmat RZ** (double theta) const
Qubit rotation of theta about the Z axis.
- **cmat Zd** (idx D=2) const
Generalized Z gate for qudits.

- `cmat SWAPd (idx D=2) const`
SWAP gate for qudits.
- `cmat Fd (idx D=2) const`
Quantum Fourier transform gate for qudits.
- `cmat MODMUL (idx a, idx N, idx n) const`
Modular multiplication gate for qubits Implements $|x\rangle \rightarrow |ax \bmod N\rangle$.
- `cmat Xd (idx D=2) const`
Generalized X gate for qudits.
- `template<typename Derived = Eigen::MatrixXcd>`
`Derived Id (idx D=2) const`
Identity gate.
- `template<typename Derived >`
`dyn_mat< typename Derived::Scalar > CTRL (const Eigen::MatrixBase< Derived > &A, const std::vector< idx > &ctrl, const std::vector< idx > &target, idx n, idx d=2) const`
Generates the multi-partite multiple-controlled-A gate in matrix form.
- `template<typename Derived >`
`dyn_mat< typename Derived::Scalar > expandout (const Eigen::MatrixBase< Derived > &A, idx pos, const std::vector< idx > &dims) const`
Expands out.
- `template<typename Derived >`
`dyn_mat< typename Derived::Scalar > expandout (const Eigen::MatrixBase< Derived > &A, idx pos, const std::initializer_list< idx > &dims) const`
Expands out.
- `template<typename Derived >`
`dyn_mat< typename Derived::Scalar > expandout (const Eigen::MatrixBase< Derived > &A, idx pos, idx n, idx d=2) const`
Expands out.
- `std::string get_name (const cmat &U) const`
Get the name of the most common qubit gates.

Public Attributes

- `cmat Id2 {cmat::Identity(2, 2)}`
Identity gate.
- `cmat H {cmat::Zero(2, 2)}`
Hadamard gate.
- `cmat X {cmat::Zero(2, 2)}`
Pauli Sigma-X gate.
- `cmat Y {cmat::Zero(2, 2)}`
Pauli Sigma-Y gate.
- `cmat Z {cmat::Zero(2, 2)}`
Pauli Sigma-Z gate.
- `cmat S {cmat::Zero(2, 2)}`
S gate.
- `cmat T {cmat::Zero(2, 2)}`
T gate.
- `cmat CNOT {cmat::Identity(4, 4)}`
Controlled-NOT control target gate.
- `cmat CZ {cmat::Identity(4, 4)}`
Controlled-Phase gate.
- `cmat CNOTba {cmat::Zero(4, 4)}`

Controlled-NOT target->control gate.

- [cmat SWAP](#) {cmat::Identity(4, 4)}

SWAP gate.

- [cmat TOF](#) {cmat::Identity(8, 8)}

Toffoli gate.

- [cmat FRED](#) {cmat::Identity(8, 8)}

Fredkin gate.

Private Member Functions

- [Gates](#) ()

Initializes the gates.

- [~Gates](#) ()=default

Default destructor.

Friends

- class [internal::Singleton< const Gates >](#)

Additional Inherited Members

7.16.1 Detailed Description

const Singleton class that implements most commonly used gates

7.16.2 Constructor & Destructor Documentation

7.16.2.1 Gates()

```
qpp::Gates::Gates ( ) [inline], [private]
```

Initializes the gates.

7.16.2.2 ~Gates()

```
qpp::Gates::~Gates ( ) [private], [default]
```

Default destructor.

7.16.3 Member Function Documentation

7.16.3.1 CTRL()

```
template<typename Derived >
dyn_mat<typename Derived::Scalar> qpp::Gates::CTRL (
    const Eigen::MatrixBase< Derived > & A,
    const std::vector< idx > & ctrl,
    const std::vector< idx > & target,
    idx n,
    idx d = 2 ) const [inline]
```

Generates the multi-partite multiple-controlled-*A* gate in matrix form.

See also

[qpp::applyCTRL\(\)](#)

Note

The dimension of the gate *A* must match the dimension of *target*

Parameters

<i>A</i>	Eigen expression
<i>ctrl</i>	Control subsystem indexes
<i>target</i>	Subsystem indexes where the gate <i>A</i> is applied
<i>n</i>	Total number of subsystems
<i>d</i>	Subsystem dimensions

Returns

CTRL-*A* gate, as a matrix over the same scalar field as *A*

7.16.3.2 expandout() [1/3]

```
template<typename Derived >
dyn_mat<typename Derived::Scalar> qpp::Gates::expandout (
    const Eigen::MatrixBase< Derived > & A,
    idx pos,
    const std::vector< idx > & dims ) const [inline]
```

Expands out.

See also

[qpp::kron\(\)](#)

Expands out *A* as a matrix in a multi-partite system. Faster than using [qpp::kron\(I, I, ..., I, A, I, ..., I\)](#).

Parameters

<i>A</i>	Eigen expression
<i>pos</i>	Position
<i>dims</i>	Dimensions of the multi-partite system

Returns

Tensor product $I \otimes \dots \otimes I \otimes A \otimes I \otimes \dots \otimes I$, with A on position pos , as a dynamic matrix over the same scalar field as A

7.16.3.3 `expandout()` [2/3]

```
template<typename Derived >
dyn_mat<typename Derived::Scalar> qpp::Gates::expandout (
    const Eigen::MatrixBase< Derived > & A,
    idx pos,
    const std::initializer_list< idx > & dims ) const [inline]
```

Expands out.

See also

[qpp::kron\(\)](#)

Expands out A as a matrix in a multi-partite system. Faster than using [qpp::kron\(I, I, ..., I, A, I, ..., I\)](#).

Note

The `std::initializer_list` overload exists because otherwise, in the degenerate case when *dims* has only one element, the one element list is implicitly converted to the element's underlying type, i.e. [qpp::idx](#), which has the net effect of picking the wrong (non-vector) `qpp::expandout()` overload

Parameters

<i>A</i>	Eigen expression
<i>pos</i>	Position
<i>dims</i>	Dimensions of the multi-partite system

Returns

Tensor product $I \otimes \dots \otimes I \otimes A \otimes I \otimes \dots \otimes I$, with A on position pos , as a dynamic matrix over the same scalar field as A

7.16.3.4 expandout() [3/3]

```
template<typename Derived >
dyn_mat<typename Derived::Scalar> qpp::Gates::expandout (
    const Eigen::MatrixBase< Derived > & A,
    idx pos,
    idx n,
    idx d = 2 ) const [inline]
```

Expands out.

See also

[qpp::kron\(\)](#)

Expands out A as a matrix in a multi-partite system. Faster than using [qpp::kron\(I, I, ..., I, A, I, ..., I\)](#).

Parameters

A	Eigen expression
pos	Position
n	Number of subsystems
d	Subsystem dimensions

Returns

Tensor product $I \otimes \dots \otimes I \otimes A \otimes I \otimes \dots \otimes I$, with A on position pos , as a dynamic matrix over the same scalar field as A

7.16.3.5 Fd()

```
cmat qpp::Gates::Fd (
    idx D = 2 ) const [inline]
```

Quantum Fourier transform gate for qudits.

Note

Defined as $F = \sum_{j,k=0}^{D-1} \exp(2\pi i j k / D) |j\rangle \langle k|$

Parameters

D	Dimension of the Hilbert space
-----	--------------------------------

Returns

Fourier transform gate for qudits

7.16.3.6 get_name()

```
std::string qpp::Gates::get_name (
    const cmat & U ) const [inline]
```

Get the name of the most common qubit gates.

Note

Assumes that the gate U is represented by a square matrix. If not, returns the empty string

Parameters

U	Complex matrix representing the quantum gate
-----	----------------------------------------------

Returns

The name of the gate (if any), otherwise the empty string

7.16.3.7 Id()

```
template<typename Derived = Eigen::MatrixXcd>
Derived qpp::Gates::Id (
    idx D = 2 ) const [inline]
```

Identity gate.

Note

Can change the return type from complex matrix (default) by explicitly specifying the template parameter

Parameters

D	Dimension of the Hilbert space
-----	--------------------------------

Returns

Identity gate on a Hilbert space of dimension D

7.16.3.8 MODMUL()

```
cmat qpp::Gates::MODMUL (
    idx a,
```

```

    idx N,
    idx n ) const [inline]

```

Modular multiplication gate for qubits Implements $|x\rangle \longrightarrow |ax \bmod N\rangle$.

Note

For the gate to be unitary, a and N should be co-prime. The function does not check co-primality in release versions!

The number of qubits required to implement the gate should satisfy $n \geq \lceil \log_2(N) \rceil$

Parameters

a	Positive integer less than N
N	Positive integer
n	Number of qubits required for implementing the gate

Returns

Modular multiplication gate

7.16.3.9 Rn()

```

cmat qpp::Gates::Rn (
    double theta,
    const std::vector< double > & n ) const [inline]

```

Qubit rotation of θ about the 3-dimensional real (unit) vector n .

Parameters

θ	Rotation angle
n	3-dimensional real (unit) vector

Returns

Rotation gate

7.16.3.10 RX()

```

cmat qpp::Gates::RX (
    double theta ) const [inline]

```

Qubit rotation of θ about the X axis.

Parameters

<i>theta</i>	Rotation angle
--------------	----------------

Returns

Rotation gate

7.16.3.11 RY()

```
cmat qpp::Gates::RY (
    double theta ) const [inline]
```

Qubit rotation of *theta* about the Y axis.

Parameters

<i>theta</i>	Rotation angle
--------------	----------------

Returns

Rotation gate

7.16.3.12 RZ()

```
cmat qpp::Gates::RZ (
    double theta ) const [inline]
```

Qubit rotation of *theta* about the Z axis.

Parameters

<i>theta</i>	Rotation angle
--------------	----------------

Returns

Rotation gate

7.16.3.13 SWAPd()

```
cmat qpp::Gates::SWAPd (
    idx D = 2 ) const [inline]
```

SWAP gate for qudits.

Parameters

D	Dimension of the Hilbert space
-----	--------------------------------

Returns

SWAP gate for qudits

7.16.3.14 Xd()

```
cmat qpp::Gates::Xd (
    idx D = 2 ) const [inline]
```

Generalized X gate for qudits.

Note

Defined as $X = \sum_{j=0}^{D-1} |j \oplus 1\rangle\langle j|$, i.e. raising operator $X|j\rangle = |j \oplus 1\rangle$

Parameters

D	Dimension of the Hilbert space
-----	--------------------------------

Returns

Generalized X gate for qudits

7.16.3.15 Zd()

```
cmat qpp::Gates::Zd (
    idx D = 2 ) const [inline]
```

Generalized Z gate for qudits.

Note

Defined as $Z = \sum_{j=0}^{D-1} \exp(2\pi i j/D) |j\rangle\langle j|$

Parameters

D	Dimension of the Hilbert space
-----	--------------------------------

Returns

Generalized Z gate for qudits

7.16.4 Friends And Related Function Documentation

7.16.4.1 internal::Singleton< const Gates >

```
friend class internal::Singleton< const Gates > [friend]
```

7.16.5 Member Data Documentation

7.16.5.1 CNOT

```
cmat qpp::Gates::CNOT {cmat::Identity(4, 4)}
```

Controlled-NOT control target gate.

7.16.5.2 CNOTba

```
cmat qpp::Gates::CNOTba {cmat::Zero(4, 4)}
```

Controlled-NOT target->control gate.

7.16.5.3 CZ

```
cmat qpp::Gates::CZ {cmat::Identity(4, 4)}
```

Controlled-Phase gate.

7.16.5.4 FRED

```
cmat qpp::Gates::FRED {cmat::Identity(8, 8)}
```

Fredkin gate.

7.16.5.5 H

```
cmat qpp::Gates::H {cmat::Zero(2, 2)}
```

Hadamard gate.

7.16.5.6 Id2

```
cmat qpp::Gates::Id2 {cmat::Identity(2, 2)}
```

Identity gate.

7.16.5.7 S

```
cmat qpp::Gates::S {cmat::Zero(2, 2)}
```

S gate.

7.16.5.8 SWAP

```
cmat qpp::Gates::SWAP {cmat::Identity(4, 4)}
```

SWAP gate.

7.16.5.9 T

```
cmat qpp::Gates::T {cmat::Zero(2, 2)}
```

T gate.

7.16.5.10 TOF

```
cmat qpp::Gates::TOF {cmat::Identity(8, 8)}
```

Toffoli gate.

7.16.5.11 X

```
cmat qpp::Gates::X {cmat::Zero(2, 2)}
```

Pauli Sigma-X gate.

7.16.5.12 Y

```
cmat qpp::Gates::Y {cmat::Zero(2, 2)}
```

Pauli Sigma-Y gate.

7.16.5.13 Z

```
cmat qpp::Gates::Z {cmat::Zero(2, 2)}
```

Pauli Sigma-Z gate.

The documentation for this class was generated from the following file:


- [classes/gates.h](#)

7.17 qpp::QCircuit::GateStep Struct Reference

One step consisting only of gates/operators in the circuit.

```
#include <classes/circuits/circuits.h>
```

Collaboration diagram for qpp::QCircuit::GateStep:



Public Member Functions

- `GateStep()`=default
Default constructor.
- `GateStep(GateType gate_type, std::size_t gate_hash, const std::vector< idx > &ctrl, const std::vector< idx > &target, std::string name="")`
Constructs a gate step instance.

Public Attributes

- `GateType gate_type_ = GateType::NONE`
gate type
- `std::size_t gate_hash_`
gate hash
- `std::vector< idx > ctrl_`
control
- `std::vector< idx > target_`
target where the gate is applied
- `std::string name_`
custom name of the step

7.17.1 Detailed Description

One step consisting only of gates/operators in the circuit.

7.17.2 Constructor & Destructor Documentation

7.17.2.1 GateStep() [1/2]

```
qpp::QCircuit::GateStep::GateStep ( ) [default]
```

Default constructor.

7.17.2.2 GateStep() [2/2]

```
qpp::QCircuit::GateStep::GateStep (
    GateType gate_type,
    std::size_t gate_hash,
    const std::vector< idx > & ctrl,
    const std::vector< idx > & target,
    std::string name = "" ) [inline], [explicit]
```

Constructs a gate step instance.

Parameters

<i>gate_type</i>	Gate type
<i>gate_hash</i>	Hash of the quantum gate
<i>ctrl</i>	Control qudit indexes
<i>target</i>	Target qudit indexes
<i>name</i>	Optional gate name

7.17.3 Member Data Documentation

7.17.3.1 ctrl_

```
std::vector<idx> qpp::QCircuit::GateStep::ctrl_
```

control

7.17.3.2 gate_hash_

```
std::size_t qpp::QCircuit::GateStep::gate_hash_
```

gate hash

7.17.3.3 gate_type_

```
GateType qpp::QCircuit::GateStep::gate_type_ = GateType::NONE
```

gate type

7.17.3.4 name_

```
std::string qpp::QCircuit::GateStep::name_
```

custom name of the step

7.17.3.5 target_

```
std::vector<idx> qpp::QCircuit::GateStep::target_
```

target where the gate is applied

The documentation for this struct was generated from the following file:

- [classes/circuits/circuits.h](#)

7.18 qpp::internal::HashEigen Class Reference

Functor for hashing Eigen expressions.

```
#include <functions.h>
```

Public Member Functions

- `template<typename Derived >`
`std::size_t operator\(\) (const Eigen::MatrixBase< Derived > &A) const`

7.18.1 Detailed Description

Functor for hashing Eigen expressions.

7.18.2 Member Function Documentation

7.18.2.1 operator>()

```
template<typename Derived >
std::size_t qpp::internal::HashEigen::operator() (
    const Eigen::MatrixBase< Derived > & A ) const [inline]
```

The documentation for this class was generated from the following file:


- [functions.h](#)

7.19 qpp::IDisplay Class Reference

Abstract class (interface) that mandates the definition of virtual `std::ostream& display(std::ostream& os) const`.

```
#include <classes/ideisplay.h>
```

Inheritance diagram for qpp::IDisplay:



Public Member Functions

- `IDisplay()`=default
Default constructor.
- `IDisplay(const IDisplay &)=default`
Default copy constructor.
- `IDisplay(IDisplay &&)=default`
Default move constructor.
- `IDisplay & operator=(const IDisplay &)=default`
Default copy assignment operator.
- `IDisplay & operator=(IDisplay &&)=default`
Default move assignment operator.
- `virtual ~IDisplay()`=default
Default virtual destructor.

Private Member Functions

- `virtual std::ostream & display(std::ostream &os) const =0`
Must be overridden by all derived classes.

Friends

- `std::ostream & operator<< (std::ostream &os, const IDisplay &rhs)`
Overloads the extraction operator.

7.19.1 Detailed Description

Abstract class (interface) that mandates the definition of virtual `std::ostream& display(std::ostream& os) const`.

This class defines friend inline `std::ostream& operator<< (std::ostream& os, const qpp::IDisplay& rhs)`. The latter delegates the work to the pure private virtual function `qpp::IDisplay::display()` which has to be overridden by all derived classes.

7.19.2 Constructor & Destructor Documentation

7.19.2.1 IDisplay() [1/3]

```
qpp::IDisplay::IDisplay ( ) [default]
```

Default constructor.

7.19.2.2 IDisplay() [2/3]

```
qpp::IDisplay::IDisplay (
    const IDisplay & ) [default]
```

Default copy constructor.

7.19.2.3 IDisplay() [3/3]

```
qpp::IDisplay::IDisplay (
    IDisplay && ) [default]
```

Default move constructor.

7.19.2.4 ~IDisplay()

```
virtual qpp::IDisplay::~IDisplay ( ) [virtual], [default]
```

Default virtual destructor.

7.19.3 Member Function Documentation

7.19.3.1 display()

```
virtual std::ostream& qpp::IDisplay::display (
    std::ostream & os ) const [private], [pure virtual]
```

Must be overridden by all derived classes.

The actual stream extraction processing is performed by the overridden member function in the derived class. This function is automatically invoked by friend inline `std::ostream& operator<<(std::ostream& os, const IDisplay& rhs)`.

Implemented in [qpp::QCircuit](#), [qpp::QEngine](#), [qpp::QCircuit::iterator::value_type_](#), [qpp::Dynamic_bitset](#), [qpp::internal::IOManipEigen](#), [qpp::Timer< T, CLOCK_T >](#), [qpp::internal::IOManipPointer< PointerType >](#), and [qpp::internal::IOManipRange< InputIterator >](#).

7.19.3.2 operator=() [1/2]

```
IDisplay& qpp::IDisplay::operator= (
    const IDisplay & ) [default]
```

Default copy assignment operator.

7.19.3.3 operator=() [2/2]

```
IDisplay& qpp::IDisplay::operator= (
    IDisplay && ) [default]
```

Default move assignment operator.

7.19.4 Friends And Related Function Documentation

7.19.4.1 operator<<

```
std::ostream& operator<< (
    std::ostream & os,
    const IDisplay & rhs ) [friend]
```

Overloads the extraction operator.

Delegates the work to the virtual function [qpp::IDisplay::display\(\)](#)

The documentation for this class was generated from the following file:


- [classes/ideisplay.h](#)

7.20 qpp::IJSON Class Reference

Abstract class (interface) that mandates the definition of very basic JSON serialization support.

```
#include <classes/ideisplay.h>
```

Inheritance diagram for qpp::IJSON:



Public Member Functions

- [IJSON](#) ()=default
Default constructor.
- [IJSON](#) (const [IJSON](#) &)=default
Default copy constructor.
- [IJSON](#) ([IJSON](#) &&)=default
Default move constructor.
- [IJSON](#) & [operator=](#) (const [IJSON](#) &)=default
Default copy assignment operator.
- [IJSON](#) & [operator=](#) ([IJSON](#) &&)=default
Default move assignment operator.
- virtual [~IJSON](#) ()=default
Default virtual destructor.
- virtual std::string [to_JSON](#) (bool enclosed_in_curly_brackets=true) const =0
JSON representation of the derived instance, must be overridden by all derived classes.

7.20.1 Detailed Description

Abstract class (interface) that mandates the definition of very basic JSON serialization support.

7.20.2 Constructor & Destructor Documentation

7.20.2.1 IJSON() [1/3]

```
qpp::IJSON::IJSON ( ) [default]
```

Default constructor.

7.20.2.2 IJSON() [2/3]

```
qpp::IJSON::IJSON (
    const IJSON & ) [default]
```

Default copy constructor.

7.20.2.3 IJSON() [3/3]

```
qpp::IJSON::IJSON (
    IJSON && ) [default]
```

Default move constructor.

7.20.2.4 ~IJSON()

```
virtual qpp::IJSON::~IJSON ( ) [virtual], [default]
```

Default virtual destructor.

7.20.3 Member Function Documentation

7.20.3.1 operator=() [1/2]

```
IJSON& qpp::IJSON::operator= (
    const IJSON & ) [default]
```

Default copy assignment operator.

7.20.3.2 operator=() [2/2]

```
IJSON& qpp::IJSON::operator= (
    IJSON && ) [default]
```

Default move assignment operator.

7.20.3.3 to_JSON()

```
virtual std::string qpp::IJSON::to_JSON (
    bool enclosed_in_curly_brackets = true ) const [pure virtual]
```

JSON representation of the derived instance, must be overridden by all derived classes.

Parameters

<i>enclosed_in_curly_brackets</i>	If true, encloses the result in curly brackets
-----------------------------------	------------------------------------------------

Implemented in [qpp::QCircuit](#), and [qpp::QEngine](#).

The documentation for this class was generated from the following file:


- [classes/ideplay.h](#)

7.21 qpp::Init Class Reference


const Singleton class that performs additional initializations/cleanups

```
#include <classes/init.h>
```

Inheritance diagram for qpp::Init:



Collaboration diagram for qpp::Init:



Private Member Functions

- `Init()`
Additional initializations.
- `~Init()`
Cleanups.

Friends

- class `internal::Singleton< const Init >`

Additional Inherited Members

7.21.1 Detailed Description

const Singleton class that performs additional initializations/cleanups

7.21.2 Constructor & Destructor Documentation

7.21.2.1 Init()

```
qpp::Init::Init ( ) [inline], [private]
```

Additional initializations.

7.21.2.2 ~Init()

```
qpp::Init::~~Init ( ) [inline], [private]
```

Cleanups.

7.21.3 Friends And Related Function Documentation

7.21.3.1 internal::Singleton< const Init >

```
friend class internal::Singleton< const Init > [friend]
```

The documentation for this class was generated from the following file:


- [classes/init.h](#)

7.22 qpp::exception::InvalidIterator Class Reference


Invalid iterator.

```
#include <classes/exception.h>
```

Inheritance diagram for qpp::exception::InvalidIterator:



Collaboration diagram for qpp::exception::InvalidIterator:



Public Member Functions

- `std::string type_description ()` const override
[Exception](#) type description.
- `Exception (const std::string &where)`
Constructs an exception.

7.22.1 Detailed Description

Invalid iterator.

7.22.2 Member Function Documentation

7.22.2.1 `Exception()`

```
qpp::exception::Exception::Exception [inline], [explicit]
```

Constructs an exception.

Parameters

<i>where</i>	Text representing where the exception occurred
--------------	------------------------------------------------

7.22.2.2 `type_description()`

```
std::string qpp::exception::InvalidIterator::type_description ( ) const [inline], [override],  
[virtual]
```

[Exception](#) type description.

Returns

[Exception](#) type description

Implements [qpp::exception::Exception](#).


The documentation for this class was generated from the following file:

- [classes/exception.h](#)


7.23 `qpp::internal::IOManipEigen` Class Reference

```
#include <internal/classes/iomanip.h>
```

Inheritance diagram for `qpp::internal::IOManipEigen`:



Collaboration diagram for qpp::internal::IOManipEigen:



Public Member Functions

- `template<typename Derived >`
`IOManipEigen` (`const Eigen::MatrixBase< Derived > &A`, `double chop=qpp::chop`)
- `IOManipEigen` (`const cplx z`, `double chop=qpp::chop`)

Private Member Functions

- `std::ostream & display` (`std::ostream &os`) `const` override
Must be overridden by all derived classes.

Private Attributes

- `cmat A_`
- `double chop_`

7.23.1 Constructor & Destructor Documentation

7.23.1.1 IOManipEigen() [1/2]

```

template<typename Derived >
qpp::internal::IOManipEigen::IOManipEigen (
    const Eigen::MatrixBase< Derived > & A,
    double chop = qpp::chop ) [inline], [explicit]
  
```

7.23.1.2 IManipEigen() [2/2]

```
qpp::internal::IManipEigen::IManipEigen (
    const cplx z,
    double chop = qpp::chop ) [inline], [explicit]
```

7.23.2 Member Function Documentation

7.23.2.1 display()

```
std::ostream& qpp::internal::IManipEigen::display (
    std::ostream & os ) const [inline], [override], [private], [virtual]
```

Must be overridden by all derived classes.

The actual stream extraction processing is performed by the overridden member function in the derived class. This function is automatically invoked by friend inline `std::ostream& operator<<(std::ostream& os, const IDisplay& rhs)`.

Implements [qpp::IDisplay](#).

7.23.3 Member Data Documentation

7.23.3.1 A_

```
cmat qpp::internal::IManipEigen::A_ [private]
```

7.23.3.2 chop_

```
double qpp::internal::IManipEigen::chop_ [private]
```


The documentation for this class was generated from the following file:

- [internal/classes/iomanip.h](#)


7.24 qpp::internal::IOManipPointer< PointerType > Class Template Reference

```
#include <internal/classes/iomanip.h>
```

Inheritance diagram for qpp::internal::IOManipPointer< PointerType >:



Collaboration diagram for qpp::internal::IOManipPointer< PointerType >:



Public Member Functions

- [IOManipPointer](#) (const PointerType *p, [idx](#) N, const std::string &separator, const std::string &start="[" , const std::string &end="]")
- [IOManipPointer](#) (const [IOManipPointer](#) &)=default
- [IOManipPointer](#) & [operator=](#) (const [IOManipPointer](#) &)=default

Private Member Functions

- `std::ostream & display (std::ostream &os)` const override

Must be overridden by all derived classes.

Private Attributes

- `const PointerType * p_`
- `idx N_`
- `std::string separator_`
- `std::string start_`
- `std::string end_`

7.24.1 Constructor & Destructor Documentation

7.24.1.1 IManipPointer() [1/2]

```
template<typename PointerType>
qpp::internal::IManipPointer< PointerType >::IManipPointer (
    const PointerType * p,
    idx N,
    const std::string & separator,
    const std::string & start = "[",
    const std::string & end = "]" ) [inline], [explicit]
```

7.24.1.2 IManipPointer() [2/2]

```
template<typename PointerType>
qpp::internal::IManipPointer< PointerType >::IManipPointer (
    const IManipPointer< PointerType > & ) [default]
```

7.24.2 Member Function Documentation

7.24.2.1 display()

```
template<typename PointerType>
std::ostream& qpp::internal::IManipPointer< PointerType >::display (
    std::ostream & os ) const [inline], [override], [private], [virtual]
```

Must be overridden by all derived classes.

The actual stream extraction processing is performed by the overridden member function in the derived class. This function is automatically invoked by friend inline `std::ostream& operator<<(std::ostream& os, const IDisplay& rhs)`.

Implements `qpp::IDisplay`.

7.24.2.2 operator=()

```
template<typename PointerType>
IManipPointer& qpp::internal::IManipPointer< PointerType >::operator= (
    const IManipPointer< PointerType > & ) [default]
```

7.24.3 Member Data Documentation

7.24.3.1 end_

```
template<typename PointerType>
std::string qpp::internal::IManipPointer< PointerType >::end_ [private]
```

7.24.3.2 N_

```
template<typename PointerType>
idx qpp::internal::IManipPointer< PointerType >::N_ [private]
```

7.24.3.3 p_

```
template<typename PointerType>
const PointerType* qpp::internal::IManipPointer< PointerType >::p_ [private]
```

7.24.3.4 separator_

```
template<typename PointerType>
std::string qpp::internal::IManipPointer< PointerType >::separator_ [private]
```

7.24.3.5 start_

```
template<typename PointerType>
std::string qpp::internal::IManipPointer< PointerType >::start_ [private]
```


The documentation for this class was generated from the following file:

- [internal/classes/iomanip.h](#)


7.25 qpp::internal::IOManipRange< InputIterator > Class Template Reference

```
#include <internal/classes/iomanip.h>
```

Inheritance diagram for qpp::internal::IOManipRange< InputIterator >:



Collaboration diagram for qpp::internal::IOManipRange< InputIterator >:



Public Member Functions

- [IOManipRange](#) (InputIterator first, InputIterator last, const std::string &separator, const std::string &start="[", const std::string &end="]")
- [IOManipRange](#) (const [IOManipRange](#) &)=default
- [IOManipRange](#) & [operator=](#) (const [IOManipRange](#) &)=default

Private Member Functions

- `std::ostream & display (std::ostream &os)` const override
Must be overridden by all derived classes.

Private Attributes

- InputIterator `first_`
- InputIterator `last_`
- `std::string` `separator_`
- `std::string` `start_`
- `std::string` `end_`

7.25.1 Constructor & Destructor Documentation

7.25.1.1 IOManipRange() [1/2]

```
template<typename InputIterator>
qpp::internal::IOManipRange< InputIterator >::IOManipRange (
    InputIterator first,
    InputIterator last,
    const std::string & separator,
    const std::string & start = "[",
    const std::string & end = "]" ) [inline], [explicit]
```

7.25.1.2 IOManipRange() [2/2]

```
template<typename InputIterator>
qpp::internal::IOManipRange< InputIterator >::IOManipRange (
    const IOManipRange< InputIterator > & ) [default]
```

7.25.2 Member Function Documentation

7.25.2.1 display()

```
template<typename InputIterator>
std::ostream& qpp::internal::IOManipRange< InputIterator >::display (
    std::ostream & os ) const [inline], [override], [private], [virtual]
```

Must be overridden by all derived classes.

The actual stream extraction processing is performed by the overridden member function in the derived class. This function is automatically invoked by friend inline `std::ostream& operator<<(std::ostream& os, const IDisplay& rhs)`.

Implements `qpp::IDisplay`.

7.25.2.2 operator=()

```
template<typename InputIterator>
IOManipRange& qpp::internal::IOManipRange< InputIterator >::operator= (
    const IOManipRange< InputIterator > & ) [default]
```

7.25.3 Member Data Documentation

7.25.3.1 end_

```
template<typename InputIterator>
std::string qpp::internal::IOManipRange< InputIterator >::end_ [private]
```

7.25.3.2 first_

```
template<typename InputIterator>
InputIterator qpp::internal::IOManipRange< InputIterator >::first_ [private]
```

7.25.3.3 last_

```
template<typename InputIterator>
InputIterator qpp::internal::IOManipRange< InputIterator >::last_ [private]
```

7.25.3.4 separator_

```
template<typename InputIterator>
std::string qpp::internal::IOManipRange< InputIterator >::separator_ [private]
```

7.25.3.5 start_

```
template<typename InputIterator>
std::string qpp::internal::IOManipRange< InputIterator >::start_ [private]
```

The documentation for this class was generated from the following file:


- [internal/classes/iomanip.h](#)

7.26 qpp::is_complex< T > Struct Template Reference


Checks whether the type is a complex type.

```
#include <traits.h>
```

Inheritance diagram for qpp::is_complex< T >:



Collaboration diagram for qpp::is_complex< T >:



7.26.1 Detailed Description

```
template<typename T>  
struct qpp::is_complex< T >
```

Checks whether the type is a complex type.

Provides the constant member *value* which is equal to *true*, if the type is a complex type, i.e. *std::complex< T >*

The documentation for this struct was generated from the following file:


- [traits.h](#)

7.27 qpp::is_complex< std::complex< T > > Struct Template Reference


Checks whether the type is a complex number type, specialization for complex types.

```
#include <traits.h>
```

Inheritance diagram for qpp::is_complex< std::complex< T > >:



Collaboration diagram for qpp::is_complex< std::complex< T > >:



7.27.1 Detailed Description

```
template<typename T>
struct qpp::is_complex< std::complex< T > >
```

Checks whether the type is a complex number type, specialization for complex types.

The documentation for this struct was generated from the following file:


- [traits.h](#)

7.28 qpp::is_iterable< T, typename > Struct Template Reference


Checks whether *T* is compatible with an STL-like iterable container.

```
#include <traits.h>
```

Inheritance diagram for qpp::is_iterable< T, typename >:



Collaboration diagram for qpp::is_iterable< T, typename >:



7.28.1 Detailed Description

```
template<typename T, typename = void>  
struct qpp::is_iterable< T, typename >
```

Checks whether *T* is compatible with an STL-like iterable container.

Provides the constant member *value* which is equal to *true*, if *T* is compatible with an iterable container, i.e. provides at least *begin()* and *end()* member functions and allows de-referencing. Otherwise, *value* is equal to *false*.

The documentation for this struct was generated from the following file:


- [traits.h](#)

7.29 `qpp::is_iterable< T, to_void< decltype(std::declval< T >().begin()), decltype(std::declval< T >().end()), decltype(*(std::declval< T >().begin()))> >` Struct Template Reference


Checks whether *T* is compatible with an STL-like iterable container, specialization for STL-like iterable containers.

```
#include <traits.h>
```

Inheritance diagram for `qpp::is_iterable< T, to_void< decltype(std::declval< T >().begin()), decltype(std::declval< T >().end()), decltype(*(std::declval< T >().begin()))> >`:



Collaboration diagram for `qpp::is_iterable< T, to_void< decltype(std::declval< T >().begin()), decltype(std::declval< T >().end()), decltype(*(std::declval< T >().begin()))> >`:



7.29.1 Detailed Description

```
template<typename T>
struct qpp::is_iterable< T, to_void< decltype(std::declval< T >().begin()), decltype(std::declval< T >().end()), decltype(*(std::declval< T >().begin()))> >
```

Checks whether *T* is compatible with an STL-like iterable container, specialization for STL-like iterable containers.

The documentation for this struct was generated from the following file:


- [traits.h](#)

7.30 qpp::is_matrix_expression< Derived > Struct Template Reference


Checks whether the type is an Eigen matrix expression.

```
#include <traits.h>
```

Inheritance diagram for qpp::is_matrix_expression< Derived >:



Collaboration diagram for qpp::is_matrix_expression< Derived >:



7.30.1 Detailed Description

```
template<typename Derived>
struct qpp::is_matrix_expression< Derived >
```

Checks whether the type is an Eigen matrix expression.

Provides the constant member *value* which is equal to *true*, if the type is an Eigen matrix expression of type *Eigen::MatrixBase< Derived >*. Otherwise, *value* is equal to *false*.

The documentation for this struct was generated from the following file:

- [traits.h](#)

- bool `operator==` (const `iterator` &rhs) const
Equality operator.
- bool `operator!=` (const `iterator` &rhs) const
Inequality operator.
- const `value_type_ & operator*` () const
Safe de-referencing operator.
- void `set_begin_` (const `QCircuit` *qc)
Sets the iterator to std::begin(this)
- void `set_end_` (const `QCircuit` *qc)
Sets the iterator to std::end(this)

Private Attributes

- const `QCircuit` * `qc_` {nullptr}
< non-owning pointer to the parent const quantum circuit
- `value_type_ elem_` {nullptr}

7.31.1 Detailed Description

Quantum circuit bound-checking (safe) iterator.

Note

The iterator is a `const_iterator` by default

7.31.2 Member Typedef Documentation

7.31.2.1 difference_type

```
using qpp::QCircuit::iterator::difference_type = long long
```

iterator trait

7.31.2.2 iterator_category

```
using qpp::QCircuit::iterator::iterator_category = std::forward_iterator_tag
```

iterator trait

7.31.2.3 pointer

```
using qpp::QCircuit::iterator::pointer = const value_type*
```

iterator trait

7.31.2.4 reference

```
using qpp::QCircuit::iterator::reference = const value_type&
```

iterator trait

7.31.2.5 value_type

```
using qpp::QCircuit::iterator::value_type = value_type_
```

iterator trait

7.31.3 Constructor & Destructor Documentation

7.31.3.1 iterator() [1/2]

```
qpp::QCircuit::iterator::iterator ( ) [default]
```

Default constructor.

7.31.3.2 iterator() [2/2]

```
qpp::QCircuit::iterator::iterator (
    const iterator & ) [default]
```

Default copy constructor.

7.31.4 Member Function Documentation

7.31.4.1 operator!=(())

```
bool qpp::QCircuit::iterator::operator!= (
    iterator rhs ) const [inline]
```

Inequality operator.

Parameters

<i>rhs</i>	Iterator against which the inequality is being tested
------------	-------------------------------------------------------

Returns

True if the iterators are not equal (bit by bit), false otherwise

7.31.4.2 operator*()

```
const value_type_& qpp::QCircuit::iterator::operator* ( ) const [inline]
```

Safe de-referencing operator.

Returns

Constant reference to the iterator element

7.31.4.3 operator++() [1/2]

```
iterator& qpp::QCircuit::iterator::operator++ ( ) [inline]
```

Prefix increment operator.

Returns

Reference to the current instance

7.31.4.4 operator++() [2/2]

```
iterator qpp::QCircuit::iterator::operator++ (
    int ) [inline]
```

Postfix increment operator.

Returns

Copy of the current instance before the increment

7.31.4.5 operator=()

```
iterator& qpp::QCircuit::iterator::operator= (
    const iterator & ) [default]
```

Default copy assignment operator.

Returns

Reference to the current instance

7.31.4.6 operator==()

```
bool qpp::QCircuit::iterator::operator== (
    const iterator & rhs ) const [inline]
```

Equality operator.

Parameters

<i>rhs</i>	Iterator against which the equality is being tested
------------	-----------------------------------------------------

Returns

True if the iterators are equal, false otherwise

7.31.4.7 set_begin_()

```
void qpp::QCircuit::iterator::set_begin_ (
    const QCircuit * qc ) [inline]
```

Sets the iterator to std::begin(this)

Parameters

<i>qc</i>	Pointer to constant quantum circuit
-----------	-------------------------------------

7.31.4.8 set_end_()

```
void qpp::QCircuit::iterator::set_end_ (
    const QCircuit * qc ) [inline]
```

Sets the iterator to std::begin(this)

Parameters

<i>qc</i>	Pointer to constant quantum circuit
-----------	-------------------------------------

7.31.5 Member Data Documentation

7.31.5.1 elem_

```
value_type_ qpp::QCircuit::iterator::elem_ {nullptr} [private]
```

7.31.5.2 qc_

```
const QCircuit* qpp::QCircuit::iterator::qc_ {nullptr} [private]
```

< non-owning pointer to the parent const quantum circuit

The documentation for this class was generated from the following file:

- classes/circuits/[circuits.h](#)

7.32 qpp::make_void< Ts > Struct Template Reference

Helper for [qpp::to_void<>](#) alias template.

```
#include <traits.h>
```

Public Types

- typedef void [type](#)

7.32.1 Detailed Description

```
template<typename... Ts>
struct qpp::make_void< Ts >
```

Helper for [qpp::to_void<>](#) alias template.

See also

[qpp::to_void<>](#)

7.32.2 Member Typedef Documentation

7.32.2.1 type

```
template<typename... Ts>
typedef void qpp::make\_void< Ts >::type
```

The documentation for this struct was generated from the following file:


- [traits.h](#)

7.33 `qpp::exception::MatrixMismatchSubsys` Class Reference


Matrix mismatch subsystems exception.

```
#include <classes/exception.h>
```

Inheritance diagram for `qpp::exception::MatrixMismatchSubsys`:



Collaboration diagram for qpp::exception::MatrixMismatchSubsys:



Public Member Functions

- `std::string type_description ()` const override
Exception type description.
- `Exception (const std::string &where)`
Constructs an exception.

7.33.1 Detailed Description

Matrix mismatch subsystems exception.

Matrix size mismatch subsystem sizes (e.g. in `qpp::apply()`)

7.33.2 Member Function Documentation

7.33.2.1 Exception()

```
qpp::exception::Exception::Exception [inline], [explicit]
```

Constructs an exception.

Parameters

<i>where</i>	Text representing where the exception occurred
--------------	------------------------------------------------

7.33.2.2 type_description()

```
std::string qpp::exception::MatrixMismatchSubsys::type_description ( ) const [inline], [override], [virtual]
```

Exception type description.

Returns

Exception type description

Implements [qpp::exception::Exception](#).

The documentation for this class was generated from the following file:


- [classes/exception.h](#)

7.34 qpp::exception::MatrixNotCvector Class Reference


Matrix is not a column vector exception.

```
#include <classes/exception.h>
```

Inheritance diagram for `qpp::exception::MatrixNotCvector`:



Collaboration diagram for qpp::exception::MatrixNotCvector:



Public Member Functions

- `std::string type_description ()` const override
Exception type description.
- `Exception (const std::string &where)`
Constructs an exception.

7.34.1 Detailed Description

Matrix is not a column vector exception.

Eigen::Matrix is not a column vector

7.34.2 Member Function Documentation

7.34.2.1 Exception()

```
qpp::exception::Exception::Exception [inline], [explicit]
```

Constructs an exception.

Parameters

<i>where</i>	Text representing where the exception occurred
--------------	------------------------------------------------

7.34.2.2 type_description()

```
std::string qpp::exception::MatrixNotCvector::type_description ( ) const [inline], [override], [virtual]
```

[Exception](#) type description.

Returns

[Exception](#) type description

Implements [qpp::exception::Exception](#).

The documentation for this class was generated from the following file:


- [classes/exception.h](#)

7.35 qpp::exception::MatrixNotRvector Class Reference


Matrix is not a row vector exception.

```
#include <classes/exception.h>
```

Inheritance diagram for qpp::exception::MatrixNotRvector:



Collaboration diagram for qpp::exception::MatrixNotRvector:



Public Member Functions

- `std::string type_description ()` const override
Exception type description.
- `Exception (const std::string &where)`
Constructs an exception.

7.35.1 Detailed Description

Matrix is not a row vector exception.

Eigen::Matrix is not a row vector

7.35.2 Member Function Documentation

7.35.2.1 Exception()

```
qpp::exception::Exception::Exception [inline], [explicit]
```

Constructs an exception.

Parameters

<i>where</i>	Text representing where the exception occurred
--------------	------------------------------------------------

7.35.2.2 `type_description()`

```
std::string qpp::exception::MatrixNotRvector::type_description ( ) const [inline], [override],
[virtual]
```

[Exception](#) type description.

Returns

[Exception](#) type description

Implements [qpp::exception::Exception](#).

The documentation for this class was generated from the following file:


- [classes/exception.h](#)

7.36 `qpp::exception::MatrixNotSquare` Class Reference


Matrix is not square exception.

```
#include <classes/exception.h>
```

Inheritance diagram for `qpp::exception::MatrixNotSquare`:



Collaboration diagram for qpp::exception::MatrixNotSquare:



Public Member Functions

- `std::string type_description ()` const override
Exception type description.
- `Exception (const std::string &where)`
Constructs an exception.

7.36.1 Detailed Description

Matrix is not square exception.

Eigen::Matrix is not a square matrix

7.36.2 Member Function Documentation

7.36.2.1 Exception()

```
qpp::exception::Exception::Exception [inline], [explicit]
```

Constructs an exception.

Parameters

<i>where</i>	Text representing where the exception occurred
--------------	------------------------------------------------

7.36.2.2 type_description()

```
std::string qpp::exception::MatrixNotSquare::type_description ( ) const [inline], [override],  
[virtual]
```

[Exception](#) type description.

Returns

[Exception](#) type description

Implements [qpp::exception::Exception](#).

The documentation for this class was generated from the following file:


- [classes/exception.h](#)

7.37 qpp::exception::MatrixNotSquareNorCvector Class Reference


Matrix is not square nor column vector exception.

```
#include <classes/exception.h>
```

Inheritance diagram for qpp::exception::MatrixNotSquareNorCvector:



Collaboration diagram for qpp::exception::MatrixNotSquareNorCvector:



Public Member Functions

- `std::string type_description ()` const override
Exception type description.
- `Exception (const std::string &where)`
Constructs an exception.

7.37.1 Detailed Description

Matrix is not square nor column vector exception.

Eigen::Matrix is not a square matrix nor a column vector

7.37.2 Member Function Documentation

7.37.2.1 Exception()

```
qpp::exception::Exception::Exception [inline], [explicit]
```

Constructs an exception.

Parameters

<i>where</i>	Text representing where the exception occurred
--------------	------------------------------------------------

7.37.2.2 type_description()

```
std::string qpp::exception::MatrixNotSquareNorCvector::type_description ( ) const [inline],  
[override], [virtual]
```

[Exception](#) type description.

Returns

[Exception](#) type description

Implements [qpp::exception::Exception](#).

The documentation for this class was generated from the following file:


- [classes/exception.h](#)

7.38 qpp::exception::MatrixNotSquareNorRvector Class Reference


Matrix is not square nor row vector exception.

```
#include <classes/exception.h>
```

Inheritance diagram for qpp::exception::MatrixNotSquareNorRvector:



Collaboration diagram for qpp::exception::MatrixNotSquareNorRvector:



Public Member Functions

- `std::string type_description ()` const override
Exception type description.
- `Exception (const std::string &where)`
Constructs an exception.

7.38.1 Detailed Description

Matrix is not square nor row vector exception.

Eigen::Matrix is not a square matrix nor a row vector

7.38.2 Member Function Documentation

7.38.2.1 Exception()

```
qpp::exception::Exception::Exception [inline], [explicit]
```

Constructs an exception.

Parameters

<i>where</i>	Text representing where the exception occurred
--------------	------------------------------------------------

7.38.2.2 `type_description()`

```
std::string qpp::exception::MatrixNotSquareNorRvector::type_description ( ) const [inline],
[override], [virtual]
```

[Exception](#) type description.

Returns

[Exception](#) type description

Implements [qpp::exception::Exception](#).

The documentation for this class was generated from the following file:


- [classes/exception.h](#)

7.39 `qpp::exception::MatrixNotSquareNorVector` Class Reference


Matrix is not square nor vector exception.

```
#include <classes/exception.h>
```

Inheritance diagram for `qpp::exception::MatrixNotSquareNorVector`:



Collaboration diagram for qpp::exception::MatrixNotSquareNorVector:



Public Member Functions

- `std::string type_description ()` const override
Exception type description.
- `Exception (const std::string &where)`
Constructs an exception.

7.39.1 Detailed Description

Matrix is not square nor vector exception.

Eigen::Matrix is not a square matrix nor a row/column vector

7.39.2 Member Function Documentation

7.39.2.1 Exception()

```
qpp::exception::Exception::Exception [inline], [explicit]
```

Constructs an exception.

Parameters

<i>where</i>	Text representing where the exception occurred
--------------	------------------------------------------------

7.39.2.2 type_description()

```
std::string qpp::exception::MatrixNotSquareNorVector::type_description ( ) const [inline],  
[override], [virtual]
```

Exception type description.

Returns

Exception type description

Implements [qpp::exception::Exception](#).

The documentation for this class was generated from the following file:


- [classes/exception.h](#)

7.40 qpp::exception::MatrixNotVector Class Reference


Matrix is not a vector exception.

```
#include <classes/exception.h>
```

Inheritance diagram for qpp::exception::MatrixNotVector:



Collaboration diagram for qpp::exception::MatrixNotVector:



Public Member Functions

- `std::string type_description ()` const override
Exception type description.
- `Exception (const std::string &where)`
Constructs an exception.

7.40.1 Detailed Description

Matrix is not a vector exception.

Eigen::Matrix is not a row or column vector

7.40.2 Member Function Documentation

7.40.2.1 Exception()

```
qpp::exception::Exception::Exception [inline], [explicit]
```

Constructs an exception.

Parameters

<i>where</i>	Text representing where the exception occurred
--------------	------------------------------------------------

7.40.2.2 `type_description()`

```
std::string qpp::exception::MatrixNotVector::type_description ( ) const [inline], [override],
[virtual]
```

[Exception](#) type description.

Returns

[Exception](#) type description

Implements [qpp::exception::Exception](#).

The documentation for this class was generated from the following file:


- [classes/exception.h](#)

7.41 `qpp::QCircuit::MeasureStep` Struct Reference

One step consisting only of measurements in the circuit.

```
#include <classes/circuits/circuits.h>
```

Collaboration diagram for `qpp::QCircuit::MeasureStep`:



Public Member Functions

- [MeasureStep](#) ()=default
Default constructor.
- [MeasureStep](#) ([MeasureType](#) measurement_type, const std::vector< std::size_t > &mats_hash, const std::vector< [idx](#) > &target, [idx](#) c_reg, std::string name="")
Constructs a measurement step instance.

Public Attributes

- [MeasureType](#) measurement_type_ = [MeasureType::NONE](#)
measurement type
- std::vector< std::size_t > mats_hash_
- std::vector< [idx](#) > target_
target where the measurement is applied
- [idx](#) c_reg_ {}
- std::string name_
custom name of the step

7.41.1 Detailed Description

One step consisting only of measurements in the circuit.

7.41.2 Constructor & Destructor Documentation

7.41.2.1 MeasureStep() [1/2]

```
qpp::QCircuit::MeasureStep::MeasureStep ( ) [default]
```

Default constructor.

7.41.2.2 MeasureStep() [2/2]

```
qpp::QCircuit::MeasureStep::MeasureStep (
    MeasureType measurement_type,
    const std::vector< std::size_t > & mats_hash,
    const std::vector< idx > & target,
    idx c_reg,
    std::string name = "" ) [inline], [explicit]
```

Constructs a measurement step instance.

Parameters

<i>measurement_type</i>	Measurement type
<i>mats_hash</i>	Vector of hashes of the measurement matrix/matrices
<i>target</i>	Target qudit indexes
<i>c_reg</i>	Classical register where the value of the measurement is stored
<i>name</i>	Optional gate name

7.41.3 Member Data Documentation

7.41.3.1 c_reg_

```
idx qpp::QCircuit::MeasureStep::c_reg_ {}
```

index of the classical register where the measurement result is being stored

7.41.3.2 mats_hash_

```
std::vector<std::size_t> qpp::QCircuit::MeasureStep::mats_hash_
```

hashes of measurement matrix/matrices

7.41.3.3 measurement_type_

```
MeasureType qpp::QCircuit::MeasureStep::measurement_type_ = MeasureType::NONE
```

measurement type

7.41.3.4 name_

```
std::string qpp::QCircuit::MeasureStep::name_
```

custom name of the step

7.41.3.5 target_

```
std::vector<idx> qpp::QCircuit::MeasureStep::target_
```

target where the measurement is applied

The documentation for this struct was generated from the following file:


- [classes/circuits/circuits.h](#)

7.42 qpp::exception::NoCodeword Class Reference


Codeword does not exist exception.

```
#include <classes/exception.h>
```

Inheritance diagram for qpp::exception::NoCodeword:



Collaboration diagram for qpp::exception::NoCodeword:



Public Member Functions

- `std::string type_description ()` const override
[Exception](#) type description.
- `Exception (const std::string &where)`
Constructs an exception.

7.42.1 Detailed Description

Codeword does not exist exception.

Codeword does not exist, thrown when calling `qpp::Codes::codeword\(\)` with an invalid index

7.42.2 Member Function Documentation

7.42.2.1 [Exception\(\)](#)

```
qpp::exception::Exception::Exception [inline], [explicit]
```

Constructs an exception.

Parameters

<i>where</i>	Text representing where the exception occurred
--------------	------------------------------------------------

7.42.2.2 [type_description\(\)](#)

```
std::string qpp::exception::NoCodeword::type_description ( ) const [inline], [override],  
[virtual]
```

[Exception](#) type description.

Returns

[Exception](#) type description

Implements `qpp::exception::Exception`.

The documentation for this class was generated from the following file:


- `classes/exception.h`

7.43 qpp::NoiseBase< T > Class Template Reference

Base class for all noise models, derive your particular noise model.

```
#include <classes/noise.h>
```

Collaboration diagram for qpp::NoiseBase< T >:



Public Types

- using `noise_type` = T

Public Member Functions

- `template<typename U = noise_type>`
`NoiseBase` (const std::vector< `cmat` > &Ks, typename std::enable_if< std::is_same< `NoiseType::StateDependent`, U >::value >::type != nullptr)
Constructs a noise instance for StateDependent noise type.
- `template<typename U = noise_type>`
`NoiseBase` (const std::vector< `cmat` > &Ks, const std::vector< `double` > &probs, typename std::enable_if< std::is_same< `NoiseType::StateIndependent`, U >::value >::type != nullptr)
Constructs a noise instance for StateIndependent noise type.
- `virtual ~NoiseBase ()=default`
Default virtual destructor.
- `idx get_d () const noexcept`
Qudit dimension.
- `std::vector< cmat > get_Ks () const`
Vector of noise operators.
- `std::vector< double > get_probs () const`
Vector of probabilities corresponding to each noise operator.
- `idx get_last_idx () const`
Index of the last occurring noise element.
- `double get_last_p () const`
Probability of the last occurring noise element.
- `cmat get_last_K () const`
Last occurring noise element.

- virtual `cmat operator()` (const `cmat` &state) const
Function invocation operator, applies the underlying noise model on the state vector or density matrix state.
- virtual `cmat operator()` (const `cmat` &state, `idx` target) const
Function invocation operator, applies the underlying noise model on qudit target of the multi-partite state vector or density matrix state.
- virtual `cmat operator()` (const `cmat` &state, const std::vector< `idx` > &target) const
Function invocation operator, applies the underlying correlated noise model on qudits specified by target of the multi-partite state vector or density matrix state.

Protected Member Functions

- void `compute_probs_` (const `cmat` &state, const std::vector< `idx` > &target) const
Compute probability outcomes for StateDependent noise type, otherwise returns without performing any operation (no-op)
- `cmat compute_state_` (const `cmat` &state, const std::vector< `idx` > &target) const
Compute the resulting state after the noise was applied.

Protected Attributes

- const std::vector< `cmat` > `Ks_`
Kraus operators.
- std::vector< double > `probs_`
probabilities
- `idx d_` {}
qudit dimension
- `idx i_` {}
index of the last occurring noise element
- bool `generated_` {false}
invoked, or if the noise is state-independent

7.43.1 Detailed Description

```
template<class T>
class qpp::NoiseBase< T >
```

Base class for all noise models, derive your particular noise model.

7.43.2 Member Typedef Documentation

7.43.2.1 noise_type

```
template<class T>
using qpp::NoiseBase< T >::noise_type = T
```


7.43.3 Constructor & Destructor Documentation

7.43.3.1 NoiseBase() [1/2]

```
template<class T>
template<typename U = noise_type>
qpp::NoiseBase< T >::NoiseBase (
    const std::vector< cmat > & Ks,
    typename std::enable_if< std::is_same< NoiseType::StateDependent, U >::value >↵
::type * = nullptr ) [inline], [explicit]
```

Constructs a noise instance for StateDependent noise type.

Note

SFINAEd-out for StateIndependent noise

Parameters

<i>Ks</i>	Vector of noise (Kraus) operators that specify the noise
-----------	----------------------------------------------------------

7.43.3.2 NoiseBase() [2/2]

```
template<class T>
template<typename U = noise_type>
qpp::NoiseBase< T >::NoiseBase (
    const std::vector< cmat > & Ks,
    const std::vector< double > & probs,
    typename std::enable_if< std::is_same< NoiseType::StateIndependent, U >::value
>::type * = nullptr ) [inline], [explicit]
```

Constructs a noise instance for StateIndependent noise type.

Note

SFINAEd-out for StateDependent noise

Parameters

<i>Ks</i>	Vector of noise (Kraus) operators that specify the noise
<i>probs</i>	Vector of probabilities corresponding to each Kraus operator

7.43.3.3 `~NoiseBase()`

```
template<class T>
virtual qpp::NoiseBase< T >::~~NoiseBase ( ) [virtual], [default]
```

Default virtual destructor.

7.43.4 Member Function Documentation

7.43.4.1 `compute_probs_()`

```
template<class T>
void qpp::NoiseBase< T >::compute_probs_ (
    const cmat & state,
    const std::vector< idx > & target ) const [inline], [protected]
```

Compute probability outcomes for StateDependent noise type, otherwise returns without performing any operation (no-op)

Parameters

<i>state</i>	State vector or density matrix
<i>target</i>	Qudit indexes where the noise is applied

7.43.4.2 `compute_state_()`

```
template<class T>
cmat qpp::NoiseBase< T >::compute_state_ (
    const cmat & state,
    const std::vector< idx > & target ) const [inline], [protected]
```

Compute the resulting state after the noise was applied.

Parameters

<i>state</i>	State vector or density matrix
<i>target</i>	Qudit indexes where the noise is applied

Returns

Resulting state after the noise was applied

7.43.4.3 get_d()

```
template<class T>
idx qpp::NoiseBase< T >::get_d ( ) const [inline], [noexcept]
```

Qudit dimension.

Returns

Qudit dimension

7.43.4.4 get_Ks()

```
template<class T>
std::vector<cmat> qpp::NoiseBase< T >::get_Ks ( ) const [inline]
```

Vector of noise operators.

Returns

Vector of noise operators

7.43.4.5 get_last_idx()

```
template<class T>
idx qpp::NoiseBase< T >::get_last_idx ( ) const [inline]
```

Index of the last occurring noise element.

Returns

Index of the last occurring noise element

7.43.4.6 get_last_K()

```
template<class T>
cmat qpp::NoiseBase< T >::get_last_K ( ) const [inline]
```

Last occurring noise element.

Returns

Last occurring noise element

7.43.4.7 `get_last_p()`

```
template<class T>
double qpp::NoiseBase< T >::get_last_p ( ) const [inline]
```

Probability of the last occurring noise element.

Returns

Probability of the last occurring noise element

7.43.4.8 `get_probs()`

```
template<class T>
std::vector<double> qpp::NoiseBase< T >::get_probs ( ) const [inline]
```

Vector of probabilities corresponding to each noise operator.

Returns

Probability vector

7.43.4.9 `operator>()` [1/3]

```
template<class T>
virtual cmat qpp::NoiseBase< T >::operator() (
    const cmat & state ) const [inline], [virtual]
```

Function invocation operator, applies the underlying noise model on the state vector or density matrix *state*.

Parameters

<i>state</i>	State vector or density matrix
--------------	--------------------------------

Returns

Resulting state vector or density matrix

7.43.4.10 `operator>()` [2/3]

```
template<class T>
virtual cmat qpp::NoiseBase< T >::operator() (
```

```
const cmat & state,
idx target ) const [inline], [virtual]
```

Function invocation operator, applies the underlying noise model on qudit *target* of the multi-partite state vector or density matrix *state*.

Parameters

<i>state</i>	Multi-partite state vector or density matrix
<i>target</i>	Qudit index where the noise is applied

Returns

Resulting state vector or density matrix

7.43.4.11 operator() [3/3]

```
template<class T>
virtual cmat qpp::NoiseBase< T >::operator() (
    const cmat & state,
    const std::vector< idx > & target ) const [inline], [virtual]
```

Function invocation operator, applies the underlying correlated noise model on qudits specified by *target* of the multi-partite state vector or density matrix *state*.

Parameters

<i>state</i>	Multi-partite state vector or density matrix
<i>target</i>	Qudit indexes where the correlated noise is applied

Returns

Resulting state vector or density matrix

7.43.5 Member Data Documentation

7.43.5.1 d_

```
template<class T>
idx qpp::NoiseBase< T >::d_ {} [mutable], [protected]
```

qudit dimension

7.43.5.2 generated_

```
template<class T>
bool qpp::NoiseBase< T >::generated_ {false} [mutable], [protected]
```

invoked, or if the noise is state-independent

set to true after `compute_state_()` is

7.43.5.3 i_

```
template<class T>
idx qpp::NoiseBase< T >::i_ {} [mutable], [protected]
```

index of the last occurring noise element

7.43.5.4 Ks_

```
template<class T>
const std::vector<cmat> qpp::NoiseBase< T >::Ks_ [protected]
```

Kraus operators.

7.43.5.5 probs_

```
template<class T>
std::vector<double> qpp::NoiseBase< T >::probs_ [mutable], [protected]
```

probabilities

The documentation for this class was generated from the following file:

- [classes/noise.h](#)

7.44 qpp::NoiseType Class Reference

Contains template tags used to specify the noise type.

```
#include <classes/noise.h>
```

Classes

- class [StateDependent](#)
Template tag, used whenever the noise is state-dependent.
- class [StateIndependent](#)
Template tag, used whenever the noise is state-independent.

7.44.1 Detailed Description

Contains template tags used to specify the noise type.

The documentation for this class was generated from the following file:


- [classes/noise.h](#)

7.45 qpp::exception::NotBipartite Class Reference


Not bi-partite exception.

```
#include <classes/exception.h>
```

Inheritance diagram for qpp::exception::NotBipartite:



Collaboration diagram for `qpp::exception::NotBipartite`:



Public Member Functions

- `std::string` [type_description](#) () const override
Exception type description.
- [Exception](#) (const `std::string` &where)
Constructs an exception.

7.45.1 Detailed Description

Not bi-partite exception.

`std::vector<idx>` of dimensions has size different from 2

7.45.2 Member Function Documentation

7.45.2.1 Exception()

```
qpp::exception::Exception::Exception [inline], [explicit]
```

Constructs an exception.

Parameters

<i>where</i>	Text representing where the exception occurred
--------------	------------------------------------------------

7.45.2.2 type_description()

```
std::string qpp::exception::NotBipartite::type_description ( ) const [inline], [override],  
[virtual]
```

Exception type description.

Returns

Exception type description

Implements [qpp::exception::Exception](#).

The documentation for this class was generated from the following file:


- [classes/exception.h](#)

7.46 qpp::exception::NotImplemented Class Reference


Code not yet implemented.

```
#include <classes/exception.h>
```

Inheritance diagram for qpp::exception::NotImplemented:



Collaboration diagram for qpp::exception::NotImplemented:



Public Member Functions

- `std::string type_description ()` const override
[Exception](#) type description.
- `Exception (const std::string &where)`
Constructs an exception.

7.46.1 Detailed Description

Code not yet implemented.

7.46.2 Member Function Documentation

7.46.2.1 `Exception()`

```
qpp::exception::Exception::Exception [inline], [explicit]
```

Constructs an exception.

Parameters

<i>where</i>	Text representing where the exception occurred
--------------	------------------------------------------------

7.46.2.2 type_description()

```
std::string qpp::exception::NotImplemented::type_description ( ) const [inline], [override],  
[virtual]
```

Exception type description.

Returns

Exception type description

Implements [qpp::exception::Exception](#).

The documentation for this class was generated from the following file:


- [classes/exception.h](#)

7.47 qpp::exception::NotQubitCvector Class Reference


Column vector is not 2 x 1 exception.

```
#include <classes/exception.h>
```

Inheritance diagram for qpp::exception::NotQubitCvector:



Collaboration diagram for `qpp::exception::NotQubitCvector`:



Public Member Functions

- `std::string type_description ()` const override
Exception type description.
- `Exception (const std::string &where)`
Constructs an exception.

7.47.1 Detailed Description

Column vector is not 2 x 1 exception.

Eigen::Matrix is not 2 x 1

7.47.2 Member Function Documentation

7.47.2.1 Exception()

```
qpp::exception::Exception::Exception [inline], [explicit]
```

Constructs an exception.

Parameters

<i>where</i>	Text representing where the exception occurred
--------------	------------------------------------------------

7.47.2.2 type_description()

```
std::string qpp::exception::NotQubitCvector::type_description ( ) const [inline], [override],
[virtual]
```

Exception type description.

Returns

Exception type description

Implements [qpp::exception::Exception](#).

The documentation for this class was generated from the following file:


- [classes/exception.h](#)

7.48 qpp::exception::NotQubitMatrix Class Reference


Matrix is not 2 x 2 exception.

```
#include <classes/exception.h>
```

Inheritance diagram for qpp::exception::NotQubitMatrix:



Collaboration diagram for `qpp::exception::NotQubitMatrix`:



Public Member Functions

- `std::string type_description ()` const override
Exception type description.
- `Exception (const std::string &where)`
Constructs an exception.

7.48.1 Detailed Description

Matrix is not 2 x 2 exception.

Eigen::Matrix is not 2 x 2

7.48.2 Member Function Documentation

7.48.2.1 Exception()

```
qpp::exception::Exception::Exception [inline], [explicit]
```

Constructs an exception.

Parameters

<i>where</i>	Text representing where the exception occurred
--------------	------------------------------------------------

7.48.2.2 type_description()

```
std::string qpp::exception::NotQubitMatrix::type_description ( ) const [inline], [override],
[virtual]
```

Exception type description.

Returns

Exception type description

Implements [qpp::exception::Exception](#).

The documentation for this class was generated from the following file:


- [classes/exception.h](#)

7.49 qpp::exception::NotQubitRvector Class Reference


Row vector is not 1 x 2 exception.

```
#include <classes/exception.h>
```

Inheritance diagram for qpp::exception::NotQubitRvector:



Collaboration diagram for `qpp::exception::NotQubitRvector`:



Public Member Functions

- `std::string` [type_description](#) () const override
Exception type description.
- [Exception](#) (const `std::string` &where)
Constructs an exception.

7.49.1 Detailed Description

Row vector is not 1 x 2 exception.

Eigen::Matrix is not 1 x 2

7.49.2 Member Function Documentation

7.49.2.1 Exception()

```
qpp::exception::Exception::Exception [inline], [explicit]
```

Constructs an exception.

Parameters

<i>where</i>	Text representing where the exception occurred
--------------	------------------------------------------------

7.49.2.2 type_description()

```
std::string qpp::exception::NotQubitRvector::type_description ( ) const [inline], [override], [virtual]
```

Exception type description.

Returns

Exception type description

Implements [qpp::exception::Exception](#).

The documentation for this class was generated from the following file:


- [classes/exception.h](#)

7.50 qpp::exception::NotQubitSubsys Class Reference


Subsystems are not qubits exception.

```
#include <classes/exception.h>
```

Inheritance diagram for qpp::exception::NotQubitSubsys:



Collaboration diagram for qpp::exception::NotQubitSubsys:



Public Member Functions

- `std::string type_description ()` const override
[Exception](#) type description.
- `Exception (const std::string &where)`
Constructs an exception.

7.50.1 Detailed Description

Subsystems are not qubits exception.

Subsystems are not 2-dimensional (qubits)

7.50.2 Member Function Documentation

7.50.2.1 `Exception()`

```
qpp::exception::Exception::Exception [inline], [explicit]
```

Constructs an exception.

Parameters

<i>where</i>	Text representing where the exception occurred
--------------	------------------------------------------------

7.50.2.2 type_description()

```
std::string qpp::exception::NotQubitSubsys::type_description ( ) const [inline], [override],
[virtual]
```

Exception type description.

Returns

Exception type description

Implements [qpp::exception::Exception](#).

The documentation for this class was generated from the following file:


- [classes/exception.h](#)

7.51 qpp::exception::NotQubitVector Class Reference


Vector is not 2 x 1 nor 1 x 2 exception.

```
#include <classes/exception.h>
```

Inheritance diagram for qpp::exception::NotQubitVector:



Collaboration diagram for `qpp::exception::NotQubitVector`:



Public Member Functions

- `std::string type_description ()` const override
Exception type description.
- `Exception (const std::string &where)`
Constructs an exception.

7.51.1 Detailed Description

Vector is not 2 x 1 nor 1 x 2 exception.

Eigen::Matrix is not 2 x 1 nor 1 x 2

7.51.2 Member Function Documentation

7.51.2.1 Exception()

```
qpp::exception::Exception::Exception [inline], [explicit]
```

Constructs an exception.

Parameters

<i>where</i>	Text representing where the exception occurred
--------------	------------------------------------------------

7.51.2.2 type_description()

```
std::string qpp::exception::NotQubitVector::type_description ( ) const [inline], [override],
[virtual]
```

Exception type description.

Returns

Exception type description

Implements [qpp::exception::Exception](#).

The documentation for this class was generated from the following file:


- [classes/exception.h](#)

7.52 qpp::exception::OutOfRange Class Reference


Argument out of range exception.

```
#include <classes/exception.h>
```

Inheritance diagram for [qpp::exception::OutOfRange](#):



Collaboration diagram for `qpp::exception::OutOfRange`:



Public Member Functions

- `std::string` [type_description](#) () const override
Exception type description.
- [Exception](#) (const `std::string` &where)
Constructs an exception.

7.52.1 Detailed Description

Argument out of range exception.

Argument out of range

7.52.2 Member Function Documentation

7.52.2.1 Exception()

```
qpp::exception::Exception::Exception [inline], [explicit]
```

Constructs an exception.

Parameters

<i>where</i>	Text representing where the exception occurred
--------------	------------------------------------------------

7.52.2.2 type_description()

```
std::string qpp::exception::OutOfRange::type_description ( ) const [inline], [override],
[virtual]
```

Exception type description.

Returns

Exception type description

Implements [qpp::exception::Exception](#).

The documentation for this class was generated from the following file:


- [classes/exception.h](#)

7.53 qpp::exception::PerInvalid Class Reference


Invalid permutation exception.

```
#include <classes/exception.h>
```

Inheritance diagram for qpp::exception::PerInvalid:



Collaboration diagram for `qpp::exception::PermInvalid`:



Public Member Functions

- `std::string` [type_description](#) () const override
Exception type description.
- [Exception](#) (const `std::string` &where)
Constructs an exception.

7.53.1 Detailed Description

Invalid permutation exception.

`std::vector<idx>` does not represent a valid permutation

7.53.2 Member Function Documentation

7.53.2.1 Exception()

```
qpp::exception::Exception::Exception [inline], [explicit]
```

Constructs an exception.

Parameters

<i>where</i>	Text representing where the exception occurred
--------------	------------------------------------------------

7.53.2.2 type_description()

```
std::string qpp::exception::PermInvalid::type_description ( ) const [inline], [override],
[virtual]
```

Exception type description.

Returns

Exception type description

Implements [qpp::exception::Exception](#).

The documentation for this class was generated from the following file:


- [classes/exception.h](#)

7.54 qpp::exception::PermMismatchDims Class Reference


Permutation mismatch dimensions exception.

```
#include <classes/exception.h>
```

Inheritance diagram for qpp::exception::PermMismatchDims:



Collaboration diagram for `qpp::exception::PermMismatchDims`:



Public Member Functions

- `std::string type_description ()` const override
Exception type description.
- `Exception (const std::string &where)`
Constructs an exception.

7.54.1 Detailed Description

Permutation mismatch dimensions exception.

Size of the `std::vector<idx>` representing the permutation is different from the size of the `std::vector<idx>` of dimensions

7.54.2 Member Function Documentation

7.54.2.1 Exception()

```
qpp::exception::Exception::Exception [inline], [explicit]
```

Constructs an exception.

Parameters

<i>where</i>	Text representing where the exception occurred
--------------	------------------------------------------------

7.54.2.2 type_description()

```
std::string qpp::exception::PermMismatchDims::type_description ( ) const [inline], [override],  
[virtual]
```

[Exception](#) type description.

Returns

[Exception](#) type description

Implements [qpp::exception::Exception](#).

The documentation for this class was generated from the following file:


- [classes/exception.h](#)

7.55 qpp::QCircuit Class Reference


Quantum circuit class.

```
#include <classes/circuits/circuits.h>
```

Inheritance diagram for qpp::QCircuit:



Collaboration diagram for `qpp::QCircuit`:



Classes

- struct [GateStep](#)
One step consisting only of gates/operators in the circuit.
- class [iterator](#)
Quantum circuit bound-checking (safe) iterator.
- struct [MeasureStep](#)
One step consisting only of measurements in the circuit.

Public Types

- enum [GateType](#) {
`GateType::NONE`, `GateType::SINGLE`, `GateType::TWO`, `GateType::THREE`,
`GateType::CUSTOM`, `GateType::FAN`, `GateType::SINGLE_CTRL_SINGLE_TARGET`, `GateType::SINGLE_CTRL_MULTIPLE_TARGET`,
`GateType::MULTIPLE_CTRL_SINGLE_TARGET`, `GateType::MULTIPLE_CTRL_MULTIPLE_TARGET`,
`GateType::CUSTOM_CTRL`, `GateType::SINGLE_cCTRL_SINGLE_TARGET`,
`GateType::SINGLE_cCTRL_MULTIPLE_TARGET`, `GateType::MULTIPLE_cCTRL_SINGLE_TARGET`,
`GateType::MULTIPLE_cCTRL_MULTIPLE_TARGET`, `GateType::CUSTOM_cCTRL` }
Type of gate being executed in a gate step.
- enum [MeasureType](#) { `MeasureType::NONE`, `MeasureType::MEASURE_Z`, `MeasureType::MEASURE_V`, `MeasureType::MEASURE_V_MANY` }
Type of measurement being executed in a measurement step.
- enum [StepType](#) { `StepType::NONE`, `StepType::GATE`, `StepType::MEASUREMENT`, `StepType::NOP` }
Types of each step in the quantum circuit.
- using `const_iterator = iterator`
both iterators are `const_iterators`

Public Member Functions

- [iterator begin \(\)](#)
Iterator to the first element.
- [const_iterator begin \(\)](#) const noexcept
Constant iterator to the first element.
- [const_iterator cbegin \(\)](#) const noexcept

- Constant iterator to the first element.*

 - `iterator end ()`
- Iterator to the next to the last element.*

 - `const_iterator end ()` const noexcept
- Constant iterator to the next to the last element.*

 - `const_iterator cend ()` const noexcept
- Constant iterator to the next to the last element.*

 - `QCircuit (idx nq, idx nc=0, idx d=2, std::string name="")`
- Constructs a quantum circuit.*

 - `virtual ~QCircuit ()=default`
- Default virtual destructor.*

 - `idx get_nq ()` const noexcept
- Total number of qudits in the circuit.*

 - `idx get_nc ()` const noexcept
- Total number of classical dits in the circuit.*

 - `idx get_d ()` const noexcept
- Dimension of the comprising qudits.*

 - `std::string get_name ()` const
- Quantum circuit name.*

 - `idx get_measured (idx i)` const
- Check whether qudit i was already measured.*

 - `std::vector< idx > get_measured ()` const
- Vector of already measured qudit indexes.*

 - `std::vector< idx > get_non_measured ()` const
- Vector of non-measured qudit indexes.*

 - `idx get_gate_count ()` const noexcept
- Quantum circuit total gate count.*

 - `idx get_gate_count (const std::string &name)` const
- Quantum circuit gate count.*

 - `idx get_gate_depth ()` const
- Quantum circuit total gate depth.*

 - `idx get_gate_depth (const std::string &name QPP_UNUSED_)` const
- Quantum circuit gate depth.*

 - `idx get_measurement_count ()` const noexcept
- Quantum circuit total measurement count.*

 - `idx get_measurement_count (const std::string &name)` const
- Quantum circuit measurement count.*

 - `idx get_step_count ()` const noexcept
- Quantum circuit total steps count, i.e. the sum of gate count and measurement count.*

 - `idx get_nop_count ()` const
- No-op count.*

 - `QCircuit & gate (const cmat &U, idx i, std::string name="")`
- Applies the single qudit gate U on single qudit i.*

 - `QCircuit & gate (const cmat &U, idx i, idx j, std::string name="")`
- Applies the two qudit gate U on qudits i and j.*

 - `QCircuit & gate (const cmat &U, idx i, idx j, idx k, std::string name="")`
- Applies the three qudit gate U on qudits i, j and k.*

 - `QCircuit & gate_fan (const cmat &U, const std::vector< idx > &target, std::string name="")`
- Applies the single qudit gate U on every qudit listed in target.*

 - `QCircuit & gate_fan (const cmat &U, const std::initializer_list< idx > &target, std::string name="")`
- Applies the single qudit gate U on every qudit listed in target.*

- **QCircuit** & **gate_fan** (const **cmat** &U, std::string name="")
Applies the single qudit gate U on every remaining non-measured qudit.
- **QCircuit** & **gate_custom** (const **cmat** &U, const std::vector< **idx** > &target, std::string name="")
Jointly applies the custom multiple qudit gate U on the qudit indexes specified by target.
- **QCircuit** & **QFT** (const std::vector< **idx** > &target, bool swap=true)
Applies the quantum Fourier transform (as a series of gates) on the qudit indexes specified by target.
- **QCircuit** & **QFT** (const std::initializer_list< **idx** > &target, bool swap=true)
Applies the quantum Fourier transform (as a series of gates) on the qudit indexes specified by target.
- **QCircuit** & **QFT** (bool swap=true)
Applies the quantum Fourier transform (as a series of gates) on all of remaining non-measured qudits.
- **QCircuit** & **TFQ** (const std::vector< **idx** > &target, bool swap QPP_UNUSED_=true)
Applies the inverse quantum Fourier transform (as a series of gates) on the qudit indexes specified by target.
- **QCircuit** & **TFQ** (const std::initializer_list< **idx** > &target, bool swap=true)
Applies the inverse quantum Fourier transform (as a series of gates) on the qudit indexes specified by target.
- **QCircuit** & **TFQ** (bool swap=true)
Applies the inverse quantum Fourier transform (as a series of gates) on all of remaining non-measured qudits.
- **QCircuit** & **CTRL** (const **cmat** &U, **idx** ctrl, **idx** target, std::string name="")
Applies the single qudit controlled gate U with control qudit ctrl and target qudit target.
- **QCircuit** & **CTRL** (const **cmat** &U, **idx** ctrl, const std::vector< **idx** > &target, std::string name="")
Applies the single qudit controlled gate U with control qudit ctrl on every qudit listed in target.
- **QCircuit** & **CTRL** (const **cmat** &U, const std::vector< **idx** > &ctrl, **idx** target, std::string name="")
Applies the single qudit controlled gate U with multiple control qudits listed in ctrl on the target qudit target.
- **QCircuit** & **CTRL** (const **cmat** &U, const std::vector< **idx** > &ctrl, const std::vector< **idx** > &target, std::string name="")
Applies the single qudit controlled gate U with multiple control qudits listed in ctrl on every qudit listed in target.
- **QCircuit** & **CTRL_custom** (const **cmat** &U, const std::vector< **idx** > &ctrl, const std::vector< **idx** > &target, std::string name="")
Jointly applies the custom multiple-qudit controlled gate U with multiple control qudits listed in ctrl on the qudit indexes specified by target.
- **QCircuit** & **cCTRL** (const **cmat** &U, **idx** ctrl_dit, **idx** target, std::string name="")
Applies the single qubit controlled gate U with classical control dit ctrl and target qudit target.
- **QCircuit** & **cCTRL** (const **cmat** &U, **idx** ctrl_dit, const std::vector< **idx** > &target, std::string name="")
Applies the single qudit controlled gate U with classical control dit ctrl on every qudit listed in target.
- **QCircuit** & **cCTRL** (const **cmat** &U, const std::vector< **idx** > &ctrl_dits, **idx** target, std::string name="")
Applies the single qudit controlled gate U with multiple classical control dits listed in ctrl on the target qudit target.
- **QCircuit** & **cCTRL** (const **cmat** &U, const std::vector< **idx** > &ctrl_dits, const std::vector< **idx** > &target, std::string name="")
Applies the single qudit controlled gate U with multiple classical control dits listed in ctrl on every qudit listed in target.
- **QCircuit** & **cCTRL_custom** (const **cmat** &U, const std::vector< **idx** > &ctrl_dits, const std::vector< **idx** > &target, std::string name="")
Jointly applies the custom multiple-qudit controlled gate U with multiple classical control dits listed in ctrl on the qudit indexes specified by target.
- **QCircuit** & **measureZ** (**idx** target, **idx** c_reg, std::string name="")
Measurement of single qudit in the computational basis (Z-basis)
- **QCircuit** & **measureV** (const **cmat** &V, **idx** target, **idx** c_reg, std::string name="")
Measurement of single qudit in the orthonormal basis or rank-1 projectors specified by the columns of matrix V.
- **QCircuit** & **measureV** (const **cmat** &V, const std::vector< **idx** > &target, **idx** c_reg, std::string name="")
Joint measurement of multiple qudits in the orthonormal basis or rank-1 projectors specified by the columns of matrix V.
- **QCircuit** & **nop** ()
No operation (no-op)
- std::string **to_JSON** (bool enclosed_in_curly_brackets=true) const override
qpp::JSON::to_JSON() override

Private Member Functions

- void `add_hash_` (const `cmat` &U, std::size_t hashU)
Adds matrix to the hash table.
- const std::vector< `MeasureStep` > & `get_measurements_` () const noexcept
Vector of `qpp::QCircuit::MeasureStep`.
- const std::vector< `GateStep` > & `get_gates_` () const noexcept
Vector of `qpp::QCircuit::GateStep`.
- const std::unordered_map< std::size_t, `cmat` > & `get_cmat_hash_tbl_` () const noexcept
Hash table with the matrices used in the circuit.
- std::ostream & `display` (std::ostream &os) const override
`qpp::IDisplay::display()` override

Private Attributes

- const `idx` `nq_`
number of qudits
- const `idx` `nc_`
number of classical "dits"
- const `idx` `d_`
qudit dimension
- std::string `name_`
optional circuit name
- std::vector< bool > `measured_`
keeps track of the measured qudits
- std::unordered_map< std::size_t, `cmat` > `cmat_hash_tbl_` {}
- std::unordered_map< std::string, `idx` > `count_` {}
keeps track of the gate counts
- std::unordered_map< std::string, `idx` > `depth_` {}
keeps track of the gate depths
- std::unordered_map< std::string, `idx` > `measurement_count_` {}
keeps track of the measurement counts
- std::vector< `GateStep` > `gates_` {}
gates
- std::vector< `MeasureStep` > `measurements_` {}
measurements
- std::vector< `StepType` > `step_types_` {}
type of each step

Friends

- class `QEngine`
- std::ostream & `operator<<` (std::ostream &os, const `GateType` &gate_type)
Extraction operator overload for `qpp::QCircuit::GateType` enum class.
- std::ostream & `operator<<` (std::ostream &os, const `GateStep` &gate_step)
Extraction operator overload for `qpp::QCircuit::GateStep` class.
- std::ostream & `operator<<` (std::ostream &os, const `MeasureType` &measure_type)
Extraction operator overload for `qpp::QCircuit::MeasureType` enum class.
- std::ostream & `operator<<` (std::ostream &os, const `MeasureStep` &measure_step)
Extraction operator overload for `qpp::QCircuit::MeasureStep` class.

7.55.1 Detailed Description

Quantum circuit class.

See also

[qpp::QEngine](#)

7.55.2 Member Typedef Documentation

7.55.2.1 `const_iterator`

```
using qpp::QCircuit::const_iterator = iterator
```

both iterators are `const_iterators`

7.55.3 Member Enumeration Documentation

7.55.3.1 `GateType`

```
enum qpp::QCircuit::GateType [strong]
```

Type of gate being executed in a gate step.

Enumerator

NONE	represents no gate
SINGLE	unitary gate on a single qudit
TWO	unitary gate on 2 qudits
THREE	unitary gate on 3 qudits
CUSTOM	custom gate on multiple qudits
FAN	same unitary gate on multiple qudits
SINGLE_CTRL_SINGLE_TARGET	controlled 1 qudit unitary gate with one control and one target
SINGLE_CTRL_MULTIPLE_TARGET	controlled 1 qudit unitary gate with one control and multiple targets
MULTIPLE_CTRL_SINGLE_TARGET	controlled 1 qudit unitary gate with multiple controls and single target
MULTIPLE_CTRL_MULTIPLE_TARGET	controlled 1 qudit unitary gate with multiple controls and multiple targets
CUSTOM_CTRL	custom controlled gate with multiple controls and multiple targets
SINGLE_cCTRL_SINGLE_TARGET	controlled 1 qudit unitary gate with one classical control and one target
SINGLE_cCTRL_MULTIPLE_TARGET	controlled 1 qudit unitary gate with one classical control and multiple targets
MULTIPLE_cCTRL_SINGLE_TARGET	controlled 1 qudit unitary gate with multiple classical controls and single target
MULTIPLE_cCTRL_MULTIPLE_TARGET	controlled 1 qudit unitary gate with multiple classical controls and multiple targets
CUSTOM_cCTRL	custom controlled gate with multiple classical controls and multiple targets

7.55.3.2 MeasureType

```
enum qpp::QCircuit::MeasureType [strong]
```

Type of measurement being executed in a measurement step.

Enumerator

NONE	represents no measurement
MEASURE_Z	Z measurement of single qudit.
MEASURE_V	measurement of single qudit in the orthonormal basis or rank-1 projectors specified by the columns of matrix V
MEASURE_V_MANY	measurement of multiple qudits in the orthonormal basis or rank-1 projectors specified by the columns of matrix V

7.55.3.3 StepType

```
enum qpp::QCircuit::StepType [strong]
```

Types of each step in the quantum circuit.

Enumerator

NONE	represents no step
GATE	quantum gate(s)
MEASUREMENT	measurement
NOP	no-op

7.55.4 Constructor & Destructor Documentation

7.55.4.1 QCircuit()

```
qpp::QCircuit::QCircuit (
    idx nq,
    idx nc = 0,
    idx d = 2,
    std::string name = "" ) [inline], [explicit]
```

Constructs a quantum circuit.

Note

The measurement results can only be stored in the classical dits of which number is specified by *nc*

Parameters

<i>nq</i>	Number of qbits
<i>nc</i>	Number of classical dits
<i>d</i>	Subsystem dimensions (optional, default is qubit, i.e. $d = 2$)
<i>name</i>	Circuit name (optional)

7.55.4.2 `~QCircuit()`

```
virtual qpp::QCircuit::~~QCircuit ( ) [virtual], [default]
```

Default virtual destructor.

7.55.5 Member Function Documentation

7.55.5.1 `add_hash_()`

```
void qpp::QCircuit::add_hash_ (
    const cmat & U,
    std::size_t hashU ) [inline], [private]
```

Adds matrix to the hash table.

Note

Throws if a hash collision is detected., i.e., if two different matrices have the same hash

Parameters

<i>U</i>	Complex matrix
<i>hashU</i>	Hash value of U

7.55.5.2 `begin()` [1/2]

```
iterator qpp::QCircuit::begin ( ) [inline]
```

Iterator to the first element.

Returns

Iterator to the first element

7.55.5.3 `begin()` [2/2]

```
const_iterator qpp::QCircuit::begin ( ) const [inline], [noexcept]
```

Constant iterator to the first element.

Returns

Constant iterator to the first element

7.55.5.4 `cbegin()`

```
const_iterator qpp::QCircuit::cbegin ( ) const [inline], [noexcept]
```

Constant iterator to the first element.

Returns

Constant iterator to the first element

7.55.5.5 `cCTRL()` [1/4]

```
QCircuit& qpp::QCircuit::cCTRL (
    const cmat & U,
    idx ctrl_dit,
    idx target,
    std::string name = "" ) [inline]
```

Applies the single qubit controlled gate *U* with classical control dit *ctrl* and target qudit *target*.

Parameters

<i>U</i>	Single qudit quantum gate
<i>ctrl_dit</i>	Classical control dit index
<i>target</i>	Target qudit index
<i>name</i>	Optional gate name

Returns

Reference to the current instance

7.55.5.6 cCTRL() [2/4]

```
QCircuit& qpp::QCircuit::cCTRL (
    const cmat & U,
    idx ctrl_dit,
    const std::vector< idx > & target,
    std::string name = "" ) [inline]
```

Applies the single qudit controlled gate U with classical control dit $ctrl$ on every qudit listed in $target$.

Parameters

U	Single qudit quantum gate
$ctrl_dit$	Classical control dit index
$target$	Target qudit indexes; the gate U is applied on every one of them depending on the values of the classical control dits
$name$	Optional gate name

Returns

Reference to the current instance

7.55.5.7 cCTRL() [3/4]

```
QCircuit& qpp::QCircuit::cCTRL (
    const cmat & U,
    const std::vector< idx > & ctrl_dits,
    idx target,
    std::string name = "" ) [inline]
```

Applies the single qudit controlled gate U with multiple classical control dits listed in $ctrl$ on the target qudit $target$.

Parameters

U	Single qudit quantum gate
$ctrl_dits$	Classical control dits indexes
$target$	Target qudit index
$name$	Optional gate name

Returns

Reference to the current instance

7.55.5.8 cCTRL() [4/4]

```
QCircuit& qpp::QCircuit::cCTRL (
    const cmat & U,
```

```
const std::vector< idx > & ctrl_dits,
const std::vector< idx > & target,
std::string name = "" ) [inline]
```

Applies the single qudit controlled gate U with multiple classical control dits listed in *ctrl* on every qudit listed in *target*.

Parameters

<i>U</i>	Single qudit quantum gate
<i>ctrl_dits</i>	Classical control dits indexes
<i>target</i>	Target qudit indexes; the gate U is applied on every one of them depending on the values of the classical control dits
<i>name</i>	Optional gate name

Returns

Reference to the current instance

7.55.5.9 cCTRL_custom()

```
QCircuit& qpp::QCircuit::cCTRL_custom (
    const cmat & U,
    const std::vector< idx > & ctrl_dits,
    const std::vector< idx > & target,
    std::string name = "" ) [inline]
```

Jointly applies the custom multiple-qudit controlled gate U with multiple classical control dits listed in *ctrl* on the qudit indexes specified by *target*.

Parameters

<i>U</i>	Multiple-qudit quantum gate
<i>ctrl_dits</i>	Classical control dits indexes
<i>target</i>	Target qudit indexes where the gate U is applied depending on the values of the classical control dits
<i>name</i>	Optional gate name

Returns

Reference to the current instance

7.55.5.10 cend()

```
const_iterator qpp::QCircuit::cend ( ) const [inline], [noexcept]
```

Constant iterator to the next to the last element.

Returns

Constant iterator to the next to the last element

7.55.5.11 CTRL() [1/4]

```
QCircuit& qpp::QCircuit::CTRL (
    const cmat & U,
    idx ctrl,
    idx target,
    std::string name = "" ) [inline]
```

Applies the single qudit controlled gate U with control qudit $ctrl$ and target qudit $target$.

Parameters

U	Single qudit quantum gate
$ctrl$	Control qudit index
$target$	Target qudit index
$name$	Optional gate name

Returns

Reference to the current instance

7.55.5.12 CTRL() [2/4]

```
QCircuit& qpp::QCircuit::CTRL (
    const cmat & U,
    idx ctrl,
    const std::vector< idx > & target,
    std::string name = "" ) [inline]
```

Applies the single qudit controlled gate U with control qudit $ctrl$ on every qudit listed in $target$.

Parameters

U	Single qudit quantum gate
$ctrl$	Control qudit index
$target$	Target qudit indexes; the gate U is applied on every one of them depending on the values of the control qudits
$name$	Optional gate name

Returns

Reference to the current instance

7.55.5.13 CTRL() [3/4]

```
QCircuit& qpp::QCircuit::CTRL (
    const cmat & U,
    const std::vector< idx > & ctrl,
    idx target,
    std::string name = "" ) [inline]
```

Applies the single qudit controlled gate U with multiple control qudits listed in *ctrl* on the target qudit *target*.

Parameters

<i>U</i>	Single qudit quantum gate
<i>ctrl</i>	Control qudit indexes
<i>target</i>	Target qudit index
<i>name</i>	Optional gate name

Returns

Reference to the current instance

7.55.5.14 CTRL() [4/4]

```
QCircuit& qpp::QCircuit::CTRL (
    const cmat & U,
    const std::vector< idx > & ctrl,
    const std::vector< idx > & target,
    std::string name = "" ) [inline]
```

Applies the single qudit controlled gate U with multiple control qudits listed in *ctrl* on every qudit listed in *target*.

Parameters

<i>U</i>	Single qudit quantum gate
<i>ctrl</i>	Control qudit indexes
<i>target</i>	Target qudit indexes; the gate U is applied on every one of them depending on the values of the control qudits
<i>name</i>	Optional gate name

Returns

Reference to the current instance

7.55.5.15 CTRL_custom()

```
QCircuit& qpp::QCircuit::CTRL_custom (
    const cmat & U,
    const std::vector< idx > & ctrl,
    const std::vector< idx > & target,
    std::string name = "" ) [inline]
```

Jointly applies the custom multiple-qudit controlled gate U with multiple control qudits listed in *ctrl* on the qudit indexes specified by *target*.

Parameters

<i>U</i>	Multiple-qudit quantum gate
<i>ctrl</i>	Control qudit indexes
<i>target</i>	Target qudit indexes where the gate U is applied depending on the values of the control qudits
<i>name</i>	Optional gate name

Returns

Reference to the current instance

7.55.5.16 display()

```
std::ostream& qpp::QCircuit::display (
    std::ostream & os ) const [inline], [override], [private], [virtual]
```

[qpp::IDisplay::display\(\)](#) override

Writes to the output stream a textual representation of the quantum circuit

Parameters

<i>os</i>	Output stream passed by reference
-----------	-----------------------------------

Returns

Reference to the output stream

Implements [qpp::IDisplay](#).

7.55.5.17 `end()` [1/2]

```
iterator qpp::QCircuit::end ( ) [inline]
```

Iterator to the next to the last element.

Returns

Iterator to the next to the last element

7.55.5.18 `end()` [2/2]

```
const_iterator qpp::QCircuit::end ( ) const [inline], [noexcept]
```

Constant iterator to the next to the last element.

Returns

Constant iterator to the next to the last element

7.55.5.19 `gate()` [1/3]

```
QCircuit& qpp::QCircuit::gate (
    const cmat & U,
    idx i,
    std::string name = "" ) [inline]
```

Applies the single qudit gate U on single qudit i .

Parameters

U	Single qudit quantum gate
i	Qudit index
$name$	Optional gate name

Returns

Reference to the current instance

7.55.5.20 `gate()` [2/3]

```
QCircuit& qpp::QCircuit::gate (
    const cmat & U,
```

```

    idx i,
    idx j,
    std::string name = "" ) [inline]

```

Applies the two qudit gate U on qudits i and j .

Parameters

U	Two qudit quantum gate
i	Qudit index
j	Qudit index
$name$	Optional gate name

Returns

Reference to the current instance

7.55.5.21 gate() [3/3]

```

QCircuit& qpp::QCircuit::gate (
    const cmat & U,
    idx i,
    idx j,
    idx k,
    std::string name = "" ) [inline]

```

Applies the three qudit gate U on qudits i , j and k .

Parameters

U	Three qudit quantum gate
i	Qudit index
j	Qudit index
k	Qudit index
$name$	Optional gate name

Returns

Reference to the current instance

7.55.5.22 gate_custom()

```

QCircuit& qpp::QCircuit::gate_custom (
    const cmat & U,
    const std::vector< idx > & target,
    std::string name = "" ) [inline]

```

Jointly applies the custom multiple qudit gate U on the qudit indexes specified by $target$.

Parameters

<i>U</i>	Multiple qudit quantum gate
<i>target</i>	Subsystem indexes where the gate <i>U</i> is applied
<i>name</i>	Optional gate name

Returns

Reference to the current instance

7.55.5.23 gate_fan() [1/3]

```
QCircuit& qpp::QCircuit::gate_fan (  
    const cmat & U,  
    const std::vector< idx > & target,  
    std::string name = "" ) [inline]
```

Applies the single qudit gate *U* on every qudit listed in *target*.

Parameters

<i>U</i>	Single qudit quantum gate
<i>target</i>	Target qudit indexes; the gate <i>U</i> is applied on every one of them
<i>name</i>	Optional gate name

Returns

Reference to the current instance

7.55.5.24 gate_fan() [2/3]

```
QCircuit& qpp::QCircuit::gate_fan (  
    const cmat & U,  
    const std::initializer_list< idx > & target,  
    std::string name = "" ) [inline]
```

Applies the single qudit gate *U* on every qudit listed in *target*.

Parameters

<i>U</i>	Single qudit quantum gate
<i>target</i>	Target qudit indexes; the gate <i>U</i> is applied on every one of them
<i>name</i>	Optional gate name

Returns

Reference to the current instance

7.55.5.25 gate_fan() [3/3]

```
QCircuit& qpp::QCircuit::gate_fan (
    const cmat & U,
    std::string name = "" ) [inline]
```

Applies the single qudit gate U on every remaining non-measured qudit.

Parameters

U	Single qudit quantum gate
<i>name</i>	Optional gate name

Returns

Reference to the current instance

7.55.5.26 get_cmat_hash_tbl()

```
const std::unordered_map<std::size_t, cmat>& qpp::QCircuit::get_cmat_hash_tbl_ ( ) const
[inline], [private], [noexcept]
```

Hash table with the matrices used in the circuit.

Returns

Hash table with the matrices used in the circuit

7.55.5.27 get_d()

```
idx qpp::QCircuit::get_d ( ) const [inline], [noexcept]
```

Dimension of the comprising qudits.

Returns

Qudit dimension

7.55.5.28 `get_gate_count()` [1/2]

```
idx qpp::QCircuit::get_gate_count ( ) const [inline], [noexcept]
```

Quantum circuit total gate count.

Returns

Total gate count

7.55.5.29 `get_gate_count()` [2/2]

```
idx qpp::QCircuit::get_gate_count (
    const std::string & name ) const [inline]
```

Quantum circuit gate count.

Parameters

<i>name</i>	Gate name
-------------	-----------

Returns

Gate count

7.55.5.30 `get_gate_depth()` [1/2]

```
idx qpp::QCircuit::get_gate_depth ( ) const [inline]
```

Quantum circuit total gate depth.

Returns

Total gate depth

7.55.5.31 `get_gate_depth()` [2/2]

```
idx qpp::QCircuit::get_gate_depth (
    const std::string &name QPP_UNUSED_ ) const [inline]
```

Quantum circuit gate depth.

Parameters

<i>name</i>	Gate name
-------------	-----------

Returns

Gate depth

7.55.5.32 `get_gates_()`

```
const std::vector<GateStep>& qpp::QCircuit::get_gates_ ( ) const [inline], [private], [noexcept]
```

Vector of [qpp::QCircuit::GateStep](#).

Returns

Vector of [qpp::QCircuit::GateStep](#)

7.55.5.33 `get_measured()` [1/2]

```
idx qpp::QCircuit::get_measured (
    idx i ) const [inline]
```

Check whether qudit *i* was already measured.

Parameters

<i>i</i>	Qudit index
----------	-------------

Returns

True if qudit *i* was already measured, false otherwise

7.55.5.34 `get_measured()` [2/2]

```
std::vector<idx> qpp::QCircuit::get_measured ( ) const [inline]
```

Vector of already measured qudit indexes.

Returns

Vector of already measured qudit indexes

7.55.5.35 `get_measurement_count()` [1/2]

```
idx qpp::QCircuit::get_measurement_count ( ) const [inline], [noexcept]
```

Quantum circuit total measurement count.

Returns

Total measurement count

7.55.5.36 `get_measurement_count()` [2/2]

```
idx qpp::QCircuit::get_measurement_count (
    const std::string & name ) const [inline]
```

Quantum circuit measurement count.

Parameters

<i>name</i>	Measurement name
-------------	------------------

Returns

Measurement count

7.55.5.37 `get_measurements_()`

```
const std::vector<MeasureStep>& qpp::QCircuit::get_measurements_ ( ) const [inline], [private],
[noexcept]
```

Vector of [qpp::QCircuit::MeasureStep](#).

Returns

Vector of [qpp::QCircuit::MeasureStep](#)

7.55.5.38 `get_name()`

```
std::string qpp::QCircuit::get_name ( ) const [inline]
```

Quantum circuit name.

Returns

Quantum circuit name

7.55.5.39 get_nc()

```
idx qpp::QCircuit::get_nc ( ) const [inline], [noexcept]
```

Total number of classical dits in the circuit.

Returns

Total number of classical dits

7.55.5.40 get_non_measured()

```
std::vector<idx> qpp::QCircuit::get_non_measured ( ) const [inline]
```

Vector of non-measured qudit indexes.

Returns

Vector of non-measured qudit indexes

7.55.5.41 get_nop_count()

```
idx qpp::QCircuit::get_nop_count ( ) const [inline]
```

No-op count.

Returns

No-op count

7.55.5.42 get_nq()

```
idx qpp::QCircuit::get_nq ( ) const [inline], [noexcept]
```

Total number of qudits in the circuit.

Returns

Total number of qudits

7.55.5.43 `get_step_count()`

```
idx qpp::QCircuit::get_step_count ( ) const [inline], [noexcept]
```

Quantum circuit total steps count, i.e. the sum of gate count and measurement count.

Returns

Total (gates + measurements) count

7.55.5.44 `measureV()` [1/2]

```
QCircuit& qpp::QCircuit::measureV (
    const cmat & V,
    idx target,
    idx c_reg,
    std::string name = "" ) [inline]
```

Measurement of single qudit in the orthonormal basis or rank-1 projectors specified by the columns of matrix *V*.

Parameters

<i>V</i>	Orthonormal basis or rank-1 projectors specified by the columns of matrix <i>V</i>
<i>target</i>	Qudit index
<i>c_reg</i>	Classical register where the value of the measurement is stored
<i>name</i>	Optional measurement name

Returns

Reference to the current instance

7.55.5.45 `measureV()` [2/2]

```
QCircuit& qpp::QCircuit::measureV (
    const cmat & V,
    const std::vector< idx > & target,
    idx c_reg,
    std::string name = "" ) [inline]
```

Joint measurement of multiple qudits in the orthonormal basis or rank-1 projectors specified by the columns of matrix *V*.

Parameters

<i>V</i>	Orthonormal basis or rank-1 projectors specified by the columns of matrix <i>V</i>
<i>target</i>	Target qudit indexes that are jointly measured
<i>c_reg</i>	Classical register where the value of the measurement is stored
<i>name</i>	Optional measurement name

Returns

Reference to the current instance

7.55.5.46 measureZ()

```
QCircuit& qpp::QCircuit::measureZ (
    idx target,
    idx c_reg,
    std::string name = "" ) [inline]
```

Measurement of single qudit in the computational basis (Z-basis)

Parameters

<i>target</i>	Qudit index
<i>c_reg</i>	Classical register where the value of the measurement is being stored
<i>name</i>	Optional measurement name, default is "Measure Z"

Returns

Reference to the current instance

7.55.5.47 nop()

```
QCircuit& qpp::QCircuit::nop ( ) [inline]
```

No operation (no-op)

Note

If the underlying step is executed on a noisy engine, then noise acts before it

Returns

Reference to the current instance

7.55.5.48 QFT() [1/3]

```
QCircuit& qpp::QCircuit::QFT (
    const std::vector< idx > & target,
    bool swap = true ) [inline]
```

Applies the quantum Fourier transform (as a series of gates) on the qudit indexes specified by *target*.

Parameters

<i>target</i>	Subsystem indexes where the quantum Fourier transform is applied
<i>swap</i>	Swaps the qubits at the end (true by default)

Returns

Reference to the current instance

7.55.5.49 QFT() [2/3]

```
QCircuit& qpp::QCircuit::QFT (
    const std::initializer_list< idx > & target,
    bool swap = true ) [inline]
```

Applies the quantum Fourier transform (as a series of gates) on the qudit indexes specified by *target*.

Parameters

<i>target</i>	Subsystem indexes where the quantum Fourier transform is applied
<i>swap</i>	Swaps the qubits at the end (true by default)

Returns

Reference to the current instance

7.55.5.50 QFT() [3/3]

```
QCircuit& qpp::QCircuit::QFT (
    bool swap = true ) [inline]
```

Applies the quantum Fourier transform (as a series of gates) on all of remaining non-measured qudits.

Parameters

<i>swap</i>	Swaps the qubits at the end (true by default)
-------------	-----------------------------------------------

Returns

Reference to the current instance

7.55.5.51 TFQ() [1/3]

```
QCircuit& qpp::QCircuit::TFQ (
    const std::vector< idx > & target,
    bool swap QPP_UNUSED_ = true ) [inline]
```

Applies the inverse quantum Fourier transform (as a series of gates) on the qudit indexes specified by *target*.

Parameters

<i>target</i>	Subsystem indexes where the inverse quantum Fourier transform is applied
<i>swap</i>	Swaps the qubits at the end (true by default)

Returns

Reference to the current instance

7.55.5.52 TFQ() [2/3]

```
QCircuit& qpp::QCircuit::TFQ (
    const std::initializer_list< idx > & target,
    bool swap = true ) [inline]
```

Applies the inverse quantum Fourier transform (as a series of gates) on the qudit indexes specified by *target*.

Parameters

<i>target</i>	Subsystem indexes where the inverse quantum Fourier transform is applied
<i>swap</i>	Swaps the qubits at the end (true by default)

Returns

Reference to the current instance

7.55.5.53 TFQ() [3/3]

```
QCircuit& qpp::QCircuit::TFQ (
    bool swap = true ) [inline]
```

Applies the inverse quantum Fourier transform (as a series of gates) on all of remaining non-measured qudits.

Parameters

<i>swap</i>	Swaps the qubits at the end (true by default)
-------------	-----------------------------------------------

Returns

Reference to the current instance

7.55.5.54 to_JSON()

```
std::string qpp::QCircuit::to_JSON (
    bool enclosed_in_curly_brackets = true ) const [inline], [override], [virtual]
```

qpp::IJSON::to_JSON() override

Displays the quantum circuit in JSON format

Parameters

<i>enclosed_in_curly_brackets</i>	If true, encloses the result in curly brackets
-----------------------------------	------------------------------------------------

Returns

String containing the JSON representation of the quantum circuit

Implements [qpp::IJSON](#).

7.55.6 Friends And Related Function Documentation**7.55.6.1 operator<< [1/4]**

```
std::ostream& operator<< (
    std::ostream & os,
    const GateType & gate_type ) [friend]
```

Extraction operator overload for [qpp::QCircuit::GateType](#) enum class.

Parameters

<i>os</i>	Output stream
<i>gate_type</i>	qpp::QCircuit::GateType enum class

Returns

Output stream

7.55.6.2 `operator<<` [2/4]

```
std::ostream& operator<< (  
    std::ostream & os,  
    const GateStep & gate_step ) [friend]
```

Extraction operator overload for [qpp::QCircuit::GateStep](#) class.

Parameters

<i>os</i>	Output stream
<i>gate_step</i>	qpp::QCircuit::GateStep class

Returns

Output stream

7.55.6.3 `operator<<` [3/4]

```
std::ostream& operator<< (  
    std::ostream & os,  
    const MeasureType & measure_type ) [friend]
```

Extraction operator overload for [qpp::QCircuit::MeasureType](#) enum class.

Parameters

<i>os</i>	Output stream
<i>measure_type</i>	qpp::QCircuit::MeasureType enum class

Returns

Output stream

7.55.6.4 `operator<<` [4/4]

```
std::ostream& operator<< (  
    std::ostream & os,  
    const MeasureStep & measure_step ) [friend]
```

Extraction operator overload for [qpp::QCircuit::MeasureStep](#) class.

Parameters

<i>os</i>	Output stream
<i>measure_step</i>	qpp::QCircuit::MeasureStep enum class

Returns

Output stream

7.55.6.5 QEngine

```
friend class QEngine [friend]
```

7.55.7 Member Data Documentation

7.55.7.1 cmat_hash_tbl_

```
std::unordered_map<std::size_t, cmat> qpp::QCircuit::cmat_hash_tbl_ {} [private]
```

hash table with the matrices used in the circuit, with [Key = idx, Value = cmat]

7.55.7.2 count_

```
std::unordered_map<std::string, idx> qpp::QCircuit::count_ {} [private]
```

keeps track of the gate counts

7.55.7.3 d_

```
const idx qpp::QCircuit::d_ [private]
```

qudit dimension

7.55.7.4 depth_

```
std::unordered_map<std::string, idx> qpp::QCircuit::depth_ {} [private]
```

keeps track of the gate depths

7.55.7.5 gates_

```
std::vector<GateStep> qpp::QCircuit::gates_ {} [private]
```

gates

7.55.7.6 measured_

```
std::vector<bool> qpp::QCircuit::measured_ [private]
```

keeps track of the measured qudits

7.55.7.7 measurement_count_

```
std::unordered_map<std::string, idx> qpp::QCircuit::measurement_count_ {} [private]
```

keeps track of the measurement counts

7.55.7.8 measurements_

```
std::vector<MeasureStep> qpp::QCircuit::measurements_ {} [private]
```

measurements

7.55.7.9 name_

```
std::string qpp::QCircuit::name_ [private]
```

optional circuit name

7.55.7.10 nc_

```
const idx qpp::QCircuit::nc_ [private]
```

number of classical "dits"

7.55.7.11 nq_

```
const idx qpp::QCircuit::nq_ [private]
```

number of qudits

7.55.7.12 step_types_

```
std::vector<StepType> qpp::QCircuit::step_types_ {} [private]
```

type of each step

The documentation for this class was generated from the following file:


- [classes/circuits/circuits.h](#)

7.56 qpp::QEngine Class Reference

Quantum circuit engine, executes [qpp::QCircuit](#).

```
#include <classes/circuits/engines.h>
```

Inheritance diagram for qpp::QEngine:



Executes one step in the quantum circuit.

- virtual void [execute](#) (const [QCircuit::iterator](#) &it)

Executes one step in the quantum circuit.

- std::string [to_JSON](#) (bool enclosed_in_curly_brackets=true) const override
qpp::IJSON::to_JSON() override

Protected Member Functions

- void [set_measured_](#) (idx i)

Marks qudit i as measured then re-label accordingly the remaining non-measured qudits.

- std::vector< [idx](#) > [get_relative_pos_](#) (std::vector< [idx](#) > v)

Giving a vector V of non-measured qudits, get their relative position with respect to the measured qudits.

Protected Attributes

- const [QCircuit](#) * [qc_](#)

pointer to constant quantum circuit

- [ket psi_](#)

state vector

- std::vector< [idx](#) > [dits_](#)

classical dits

- std::vector< double > [probs_](#)

measurement probabilities

- std::vector< [idx](#) > [subsys_](#)

relabel them after measurements

Private Member Functions

- std::ostream & [display](#) (std::ostream &os) const override

qpp::IDisplay::display() override

7.56.1 Detailed Description

Quantum circuit engine, executes [qpp::QCircuit](#).

See also

[qpp::QCircuit](#)

7.56.2 Constructor & Destructor Documentation

7.56.2.1 QEngine() [1/3]

```
qpp::QEngine::QEngine (
    const QCircuit & qc ) [inline], [explicit]
```

Constructs a quantum engine out of a quantum circuit.

Note

The quantum circuit must be an lvalue

See also

[qpp::QEngine\(QCircuit&&\)](#)

Note

The initial underlying quantum state is set to $|0\rangle^{\otimes n}$

Parameters

<i>qc</i>	Quantum circuit
-----------	-----------------

7.56.2.2 QEngine() [2/3]

```
qpp::QEngine::QEngine (
    const QEngine & ) [default]
```

Default copy constructor.

7.56.2.3 QEngine() [3/3]

```
qpp::QEngine::QEngine (
    QCircuit && ) [delete]
```

Disables rvalue [QCircuit](#).

7.56.2.4 ~QEngine()

```
virtual qpp::QEngine::~QEngine ( ) [virtual], [default]
```

Default virtual destructor.

7.56.3 Member Function Documentation

7.56.3.1 display()

```
std::ostream& qpp::QEngine::display (
    std::ostream & os ) const [inline], [override], [private], [virtual]
```

[qpp::IDisplay::display\(\)](#) override

Writes to the output stream a textual representation of the state of the engine

Parameters

<i>os</i>	Output stream passed by reference
-----------	-----------------------------------

Returns

Reference to the output stream

Implements [qpp::IDisplay](#).

7.56.3.2 execute() [1/2]

```
virtual void qpp::QEngine::execute (
    const QCircuit::iterator::value_type & elem ) [inline], [virtual]
```

Executes one step in the quantum circuit.

Parameters

<i>elem</i>	Step to be executed
-------------	---------------------

Reimplemented in [qpp::QNoisyEngine< NoiseModel >](#).

7.56.3.3 execute() [2/2]

```
virtual void qpp::QEngine::execute (
    const QCircuit::iterator & it ) [inline], [virtual]
```

Executes one step in the quantum circuit.

Parameters

<i>it</i>	Iterator to the step to be executed
-----------	-------------------------------------

Reimplemented in [qpp::QNoisyEngine< NoiseModel >](#).

7.56.3.4 get_circuit()

```
const QCircuit& qpp::QEngine::get_circuit ( ) const [inline], [noexcept]
```

Quantum circuit.

Returns

Underlying quantum circuit

7.56.3.5 get_dit()

```
idx qpp::QEngine::get_dit (
    idx i ) const [inline]
```

Value of the classical dit at position *i*.

Parameters

<i>i</i>	Classical dit index
----------	---------------------

Returns

Value of the classical dit at position *i*

7.56.3.6 get_dits()

```
std::vector<idx> qpp::QEngine::get_dits ( ) const [inline]
```

Vector with the values of the underlying classical dits.

Returns

Vector of underlying classical dits

7.56.3.7 get_measured() [1/2]

```
bool qpp::QEngine::get_measured (
    idx i ) const [inline]
```

Check whether qudit i was already measured.

Parameters

i	Qudit index
-----	-------------

Returns

True if qudit i was already measured, false otherwise

7.56.3.8 get_measured() [2/2]

```
std::vector<idx> qpp::QEngine::get_measured ( ) const [inline]
```

Vector of already measured qudit indexes.

Returns

Vector of already measured qudit indexes

7.56.3.9 get_non_measured()

```
std::vector<idx> qpp::QEngine::get_non_measured ( ) const [inline]
```

Vector of non-measured qudit indexes.

Returns

Vector of non-measured qudit indexes

7.56.3.10 get_probs()

```
std::vector<double> qpp::QEngine::get_probs ( ) const [inline]
```

Vector of underlying measurement outcome probabilities.

Those should be interpreted as conditional probabilities based on the temporal order of the measurements, i.e. if we measure qubit 0, then measure qubit 1, and finally qubit 2, the resulting vector of outcome probabilities probs[2] should be interpreted as the conditional probability of qubit 2 having the outcome it had given that qubit 1 and qubit 0 had their given outcomes, respectively. As an example, if we measure the qubit 0 followed by the qubit 1 of a maximally entangled state $(|00\rangle + |11\rangle)/\sqrt{2}$, then the vector of outcome probabilities will be [0.5, 1].

Note

The probability vector has the same length as the vector of classical dits. If the measurement result is stored at the index *c_reg*, then the outcome probability is automatically stored at the same index *c_reg* in the probability vector.

Returns

Vector of underlying measurement outcome probabilities

7.56.3.11 get_psi()

```
ket qpp::QEngine::get_psi ( ) const [inline]
```

Underlying quantum state.

Returns

Underlying quantum state

7.56.3.12 get_relative_pos_()

```
std::vector<idx> qpp::QEngine::get_relative_pos_ (
    std::vector< idx > v ) [inline], [protected]
```

Giving a vector *V* of non-measured qudits, get their relative position with respect to the measured qudits.

Parameters

<i>v</i>	
----------	--

Returns

Vector of qudit indexes

7.56.3.13 operator=()

```
QEngine& qpp::QEngine::operator= (
    const QEngine & ) [default]
```

Default copy assignment operator.

Returns

Reference to the current instance

7.56.3.14 reset()

```
void qpp::QEngine::reset ( ) [inline]
```

Resets the engine.

Re-initializes everything to zero and sets the initial state to $|0\rangle^{\otimes n}$

7.56.3.15 set_dit()

```
QEngine& qpp::QEngine::set_dit (
    idx i,
    idx value ) [inline]
```

Sets the classical dit at position i .

Parameters

i	Classical dit index
$value$	Classical dit value

Returns

Reference to the current instance

7.56.3.16 set_measured_()

```
void qpp::QEngine::set_measured_ (
    idx i ) [inline], [protected]
```

Marks qudit i as measured then re-label accordingly the remaining non-measured qudits.

Parameters

i	Qudit index
-----	-------------

7.56.3.17 set_psi()

```
QEngine& qpp::QEngine::set_psi (
    const ket & psi ) [inline]
```

Sets the underlying quantum state to ψ .

Note

The order is lexicographical with respect to the remaining non-measured qudits

Parameters

ψ	State vector
--------	--------------

Returns

Reference to the current instance

7.56.3.18 to_JSON()

```
std::string qpp::QEngine::to_JSON (
    bool enclosed_in_curly_brackets = true ) const [inline], [override], [virtual]
```

qpp::IJSON::to_JSON() override

Displays the state of the engine in JSON format

Parameters

<i>enclosed_in_curly_brackets</i>	If true, encloses the result in curly brackets
-----------------------------------	------------------------------------------------

Returns

String containing the JSON representation of the state of the engine

Implements [qpp::IJSON](#).

7.56.4 Member Data Documentation

7.56.4.1 dits_

`std::vector<idx> qpp::QEngine::dits_ [protected]`

classical dits

7.56.4.2 probs_

`std::vector<double> qpp::QEngine::probs_ [protected]`

measurement probabilities

7.56.4.3 psi_

`ket qpp::QEngine::psi_ [protected]`

state vector

7.56.4.4 qc_

`const QCircuit* qpp::QEngine::qc_ [protected]`

pointer to constant quantum circuit

7.56.4.5 subsys_

`std::vector<idx> qpp::QEngine::subsys_ [protected]`

relabel them after measurements

keeps track of the measured subsystems,

The documentation for this class was generated from the following file:


- `classes/circuits/engines.h`

7.57 qpp::QNoisyEngine< NoiseModel > Class Template Reference


Noisy quantum circuit engine, executes [qpp::QCircuit](#).

```
#include <classes/circuits/engines.h>
```

Inheritance diagram for `qpp::QNoisyEngine< NoiseModel >`:



Collaboration diagram for `qpp::QNoisyEngine< NoiseModel >`:



Public Member Functions

- [QNoisyEngine](#) (const [QCircuit](#) &qc, const NoiseModel &noise)
Constructs a noisy quantum engine out of a quantum circuit.
- void [execute](#) (const [QCircuit::iterator::value_type](#) &elem) override
Executes one step in the quantum circuit.
- void [execute](#) (const [QCircuit::iterator](#) &it) override
Executes one step in the noisy quantum circuit.
- `std::vector< std::vector< idx > > get_noise_results ()` const
Vector of noise results obtained before every step in the circuit.

Private Attributes

- const NoiseModel [noise_](#)
quantum noise model
- std::vector< std::vector< [idx](#) > > [noise_results_](#)
noise results

Additional Inherited Members

7.57.1 Detailed Description

```
template<typename NoiseModel>
class qpp::QNoisyEngine< NoiseModel >
```

Noisy quantum circuit engine, executes [qpp::QCircuit](#).

See also

[qpp::QCircuit](#), [qpp::NoiseBase](#)

Assumes an uncorrelated noise model that is applied to each non-measured qubit before every step in the logical circuit

Template Parameters

<i>NoiseModel</i>	Quantum noise model, should be derived from qpp::NoiseBase
-------------------	----------------------------------------------------------------------------

7.57.2 Constructor & Destructor Documentation

7.57.2.1 QNoisyEngine()

```
template<typename NoiseModel >
qpp::QNoisyEngine< NoiseModel >::QNoisyEngine (
    const QCircuit & qc,
    const NoiseModel & noise ) [inline], [explicit]
```

Constructs a noisy quantum engine out of a quantum circuit.

Parameters

<i>qc</i>	Quantum circuit
<i>noise</i>	Quantum noise model

7.57.3 Member Function Documentation

7.57.3.1 `execute()` [1/2]

```
template<typename NoiseModel >
void qpp::QNoisyEngine< NoiseModel >::execute (
    const QCircuit::iterator::value_type & elem ) [inline], [override], [virtual]
```

Executes one step in the quantum circuit.

Parameters

<i>elem</i>	Step to be executed
-------------	---------------------

Reimplemented from [qpp::QEngine](#).

7.57.3.2 `execute()` [2/2]

```
template<typename NoiseModel >
void qpp::QNoisyEngine< NoiseModel >::execute (
    const QCircuit::iterator & it ) [inline], [override], [virtual]
```

Executes one step in the noisy quantum circuit.

Parameters

<i>it</i>	Iterator to the step to be executed
-----------	-------------------------------------

Reimplemented from [qpp::QEngine](#).

7.57.3.3 `get_noise_results()`

```
template<typename NoiseModel >
std::vector<std::vector<idx> > qpp::QNoisyEngine< NoiseModel >::get_noise_results ( ) const
[inline]
```

Vector of noise results obtained before every step in the circuit.

The first vector contains the noise measurement results obtained before applying the first step in the circuit, and so on, ordered by non-measured qudits. That is, the first element in the vector corresponding to noise obtained before a given step in the circuit represents the noise result obtained on the first non-measured qudit etc.

Returns

Vector of noise results

7.57.4 Member Data Documentation

7.57.4.1 noise_

```
template<typename NoiseModel >
const NoiseModel qpp::QNoisyEngine< NoiseModel >::noise_ [private]
```

quantum noise model

7.57.4.2 noise_results_

```
template<typename NoiseModel >
std::vector<std::vector<idx> > qpp::QNoisyEngine< NoiseModel >::noise_results_ [private]
```

noise results

The documentation for this class was generated from the following file:


- [classes/circuits/engines.h](#)

7.58 qpp::QubitAmplitudeDampingNoise Class Reference


Qubit amplitude damping noise, as described in Nielsen and Chuang.

```
#include <classes/noise.h>
```

Inheritance diagram for qpp::QubitAmplitudeDampingNoise:



Collaboration diagram for `qpp::QubitAmplitudeDampingNoise`:



Public Member Functions

- [QubitAmplitudeDampingNoise](#) (double gamma)
Qubit amplitude damping noise constructor.

Additional Inherited Members

7.58.1 Detailed Description

Qubit amplitude damping noise, as described in Nielsen and Chuang.

7.58.2 Constructor & Destructor Documentation

7.58.2.1 QubitAmplitudeDampingNoise()

```
qpp::QubitAmplitudeDampingNoise::QubitAmplitudeDampingNoise (
    double gamma ) [inline], [explicit]
```

Qubit amplitude damping noise constructor.

Parameters

<i>gamma</i>	Amplitude damping coefficient
--------------	-------------------------------

The documentation for this class was generated from the following file:


- [classes/noise.h](#)

7.59 qpp::QubitBitFlipNoise Class Reference


Qubit bit flip noise.

```
#include <classes/noise.h>
```

Inheritance diagram for qpp::QubitBitFlipNoise:



Collaboration diagram for qpp::QubitBitFlipNoise:



Public Member Functions

- [QubitBitFlipNoise](#) (double p)
Qubit bit flip noise constructor.

Additional Inherited Members

7.59.1 Detailed Description

Qubit bit flip noise.

7.59.2 Constructor & Destructor Documentation

7.59.2.1 QubitBitFlipNoise()

```
qpp::QubitBitFlipNoise::QubitBitFlipNoise (
    double p ) [inline], [explicit]
```

Qubit bit flip noise constructor.

Parameters

p	Noise probability
-----	-------------------

The documentation for this class was generated from the following file:


- [classes/noise.h](#)

7.60 qpp::QubitBitPhaseFlipNoise Class Reference


Qubit bit-phase flip (dephasing) noise.

```
#include <classes/noise.h>
```

Inheritance diagram for qpp::QubitBitPhaseFlipNoise:



Collaboration diagram for qpp::QubitBitPhaseFlipNoise:



Public Member Functions

- [QubitBitPhaseFlipNoise](#) (double p)
Qubit bit-phase flip noise constructor.

Additional Inherited Members

7.60.1 Detailed Description

Qubit bit-phase flip (dephasing) noise.

7.60.2 Constructor & Destructor Documentation

7.60.2.1 QubitBitPhaseFlipNoise()

```
qpp::QubitBitPhaseFlipNoise::QubitBitPhaseFlipNoise (
    double p ) [inline], [explicit]
```

Qubit bit-phase flip noise constructor.

Parameters

p	Noise probability
-----	-------------------

The documentation for this class was generated from the following file:


- [classes/noise.h](#)

7.61 qpp::QubitDepolarizingNoise Class Reference


Qubit depolarizing noise.

```
#include <classes/noise.h>
```

Inheritance diagram for qpp::QubitDepolarizingNoise:



Collaboration diagram for qpp::QubitDepolarizingNoise:



Public Member Functions

- [QubitDepolarizingNoise](#) (double p)
Qubit depolarizing noise constructor.

Additional Inherited Members

7.61.1 Detailed Description

Qubit depolarizing noise.

7.61.2 Constructor & Destructor Documentation

7.61.2.1 QubitDepolarizingNoise()

```
qpp::QubitDepolarizingNoise::QubitDepolarizingNoise (
    double p ) [inline], [explicit]
```

Qubit depolarizing noise constructor.

Parameters

p	Noise probability
-----	-------------------

The documentation for this class was generated from the following file:


- [classes/noise.h](#)

7.62 qpp::QubitPhaseDampingNoise Class Reference


Qubit phase damping noise, as described in Nielsen and Chuang.

```
#include <classes/noise.h>
```

Inheritance diagram for qpp::QubitPhaseDampingNoise:



Collaboration diagram for `qpp::QubitPhaseDampingNoise`:



Public Member Functions

- [QubitPhaseDampingNoise](#) (double lambda)
Qubit phase damping noise constructor.

Additional Inherited Members

7.62.1 Detailed Description

Qubit phase damping noise, as described in Nielsen and Chuang.

7.62.2 Constructor & Destructor Documentation

7.62.2.1 QubitPhaseDampingNoise()

```
qpp::QubitPhaseDampingNoise::QubitPhaseDampingNoise (
    double lambda ) [inline], [explicit]
```

Qubit phase damping noise constructor.

Parameters

<i>lambda</i>	Phase damping coefficient
---------------	---------------------------

The documentation for this class was generated from the following file:


- [classes/noise.h](#)

7.63 qpp::QubitPhaseFlipNoise Class Reference


Qubit phase flip (dephasing) noise.

```
#include <classes/noise.h>
```

Inheritance diagram for qpp::QubitPhaseFlipNoise:



Collaboration diagram for qpp::QubitPhaseFlipNoise:



Public Member Functions

- [QubitPhaseFlipNoise](#) (double p)
Qubit phase flip (dephasing) noise constructor.

Additional Inherited Members

7.63.1 Detailed Description

Qubit phase flip (dephasing) noise.

7.63.2 Constructor & Destructor Documentation

7.63.2.1 QubitPhaseFlipNoise()

```
qpp::QubitPhaseFlipNoise::QubitPhaseFlipNoise (
    double p ) [inline], [explicit]
```

Qubit phase flip (dephasing) noise constructor.

Parameters

p	Noise probability
-----	-------------------

The documentation for this class was generated from the following file:


- [classes/noise.h](#)

7.64 qpp::exception::QuditAlreadyMeasured Class Reference


Qudit was already measured exception.

```
#include <classes/exception.h>
```

Inheritance diagram for qpp::exception::QuditAlreadyMeasured:



Collaboration diagram for qpp::exception::QuditAlreadyMeasured:



Public Member Functions

- `std::string type_description ()` const override
Exception type description.
- `Exception (const std::string &where)`
Constructs an exception.

7.64.1 Detailed Description

Qudit was already measured exception.

The qudit was already measured and cannot be measured again

7.64.2 Member Function Documentation

7.64.2.1 Exception()

```
qpp::exception::Exception::Exception [inline], [explicit]
```

Constructs an exception.

Parameters

<i>where</i>	Text representing where the exception occurred
--------------	------------------------------------------------

7.64.2.2 `type_description()`

```
std::string qpp::exception::QuditAlreadyMeasured::type_description ( ) const [inline], [override],
[virtual]
```

[Exception](#) type description.

Returns

[Exception](#) type description

Implements [qpp::exception::Exception](#).

The documentation for this class was generated from the following file:


- [classes/exception.h](#)

7.65 `qpp::QuditDepolarizingNoise` Class Reference


Qudit depolarizing noise.

```
#include <classes/noise.h>
```

Inheritance diagram for `qpp::QuditDepolarizingNoise`:



Collaboration diagram for qpp::QuditDepolarizingNoise:



Public Member Functions

- [QuditDepolarizingNoise](#) (double p, [idx](#) d)
Qudit depolarizing noise constructor.

Private Member Functions

- std::vector< [cmat](#) > [fill_Ks_](#) ([idx](#) d) const
Fills the Kraus operator vector.
- std::vector< double > [fill_probs_](#) (double p, [idx](#) d) const
Fills the probability vector.

Additional Inherited Members

7.65.1 Detailed Description

Qudit depolarizing noise.

7.65.2 Constructor & Destructor Documentation

7.65.2.1 QuditDepolarizingNoise()

```

qpp::QuditDepolarizingNoise::QuditDepolarizingNoise (
    double p,
    idx d ) [inline], [explicit]
  
```

Qudit depolarizing noise constructor.

Parameters

p	Noise probability
d	Qudit dimension

7.65.3 Member Function Documentation

7.65.3.1 fill_Ks_()

```
std::vector<cmat> qpp::QuditDepolarizingNoise::fill_Ks_ (
    idx d ) const [inline], [private]
```

Fills the Kraus operator vector.

Parameters

d	Qudit dimension
-----	-----------------

Returns

Vector of Kraus operators representing the depolarizing noise

7.65.3.2 fill_probs_()

```
std::vector<double> qpp::QuditDepolarizingNoise::fill_probs_ (
    double p,
    idx d ) const [inline], [private]
```

Fills the probability vector.

Parameters

p	Probability
d	Qudit dimension

Returns

Probability vector

The documentation for this class was generated from the following file:


- [classes/noise.h](#)

7.66 qpp::RandomDevices Class Reference


Singleton class that manages the source of randomness in the library.

```
#include <classes/random_devices.h>
```

Inheritance diagram for qpp::RandomDevices:



Collaboration diagram for qpp::RandomDevices:



Public Member Functions

- `std::mt19937 & get_prng ()`
Returns a reference to the internal PRNG object.
- `std::istream & load (std::istream &is)`
Loads the state of the PRNG from an input stream.
- `std::ostream & save (std::ostream &os) const`
Saves the state of the PRNG to an output stream.

Private Member Functions

- [RandomDevices](#) ()
Initializes and seeds the random number generators.
- [~RandomDevices](#) ()=default
Default destructor.

Private Attributes

- `std::random_device` [rd_](#)
used to seed `std::mt19937` `prng_`
- `std::mt19937` [prng_](#)
Mersenne twister random number generator.

Friends

- class [internal::Singleton](#)< [RandomDevices](#) >

Additional Inherited Members

7.66.1 Detailed Description

Singleton class that manages the source of randomness in the library.

Consists of a wrapper around an `std::mt19937` Mersenne twister random number generator engine and an `std::random_device` engine. The latter is used to seed the Mersenne twister.

Warning

This class DOES NOT seed the standard C number generator used by `Eigen::Matrix::Random()`, since it is not thread safe. Do not use `Eigen::Matrix::Random()` or functions that depend on the C style random number engine, but use [qpp::rand\(\)](#) instead!

7.66.2 Constructor & Destructor Documentation

7.66.2.1 RandomDevices()

```
qpp::RandomDevices::RandomDevices ( ) [inline], [private]
```

Initializes and seeds the random number generators.

7.66.2.2 ~RandomDevices()

```
qpp::RandomDevices::~~RandomDevices ( ) [private], [default]
```

Default destructor.

7.66.3 Member Function Documentation

7.66.3.1 get_prng()

```
std::mt19937& qpp::RandomDevices::get_prng ( ) [inline]
```

Returns a reference to the internal PRNG object.

Returns

Reference to the internal PRNG object

7.66.3.2 load()

```
std::istream& qpp::RandomDevices::load (
    std::istream & is ) [inline]
```

Loads the state of the PRNG from an input stream.

Parameters

<i>is</i>	Input stream
-----------	--------------

Returns

The input stream

7.66.3.3 save()

```
std::ostream& qpp::RandomDevices::save (
    std::ostream & os ) const [inline]
```

Saves the state of the PRNG to an output stream.

Parameters

<code>os</code>	Output stream
-----------------	---------------

Returns

The output stream

7.66.4 Friends And Related Function Documentation

7.66.4.1 `internal::Singleton< RandomDevices >`

```
friend class internal::Singleton< RandomDevices > [friend]
```

7.66.5 Member Data Documentation

7.66.5.1 `prng_`

```
std::mt19937 qpp::RandomDevices::prng_ [private]
```

Mersenne twister random number generator.

7.66.5.2 `rd_`

```
std::random_device qpp::RandomDevices::rd_ [private]
```

used to seed `std::mt19937 prng_`

The documentation for this class was generated from the following file:

- `classes/random_devices.h`

7.67 `qpp::internal::Singleton< T >` Class Template Reference

`Singleton` policy class, used internally to implement the singleton pattern via CRTP (Curiously recurring template pattern)

```
#include <internal/classes/singleton.h>
```


Static Public Member Functions

- static `T & get_instance ()` noexcept(std::is_nothrow_constructible< T >::value)
- static `T & get_thread_local_instance ()` noexcept(std::is_nothrow_constructible< T >::value)

Protected Member Functions

- `Singleton ()` noexcept=default
- `Singleton (const Singleton &)=delete`
- `Singleton & operator= (const Singleton &)=delete`
- virtual `~Singleton ()=default`

7.67.1 Detailed Description

```
template<typename T>
class qpp::internal::Singleton< T >
```

`Singleton` policy class, used internally to implement the singleton pattern via CRTP (Curiously recurring template pattern)

To implement a singleton, derive your class from `qpp::internal::Singleton`, make `qpp::internal::Singleton` a friend of your class, then declare the constructor and destructor of your class as private. To get an instance, use the static member function `qpp::internal::Singleton::get_instance()` (`qpp::internal::Singleton::get_thread_local_instance()`), which returns a reference (thread_local reference) to your newly created singleton (thread-safe in C++11).

Example:

```
class MySingleton: public qpp::internal::Singleton<MySingleton>
{
    friend class qpp::internal::Singleton<MySingleton>;
public:
    // Declare all public members here
private:
    MySingleton()
    {
        // Implement the constructor here
    }
    ~MySingleton()
    {
        // Implement the destructor here
    }
};

MySingleton& mySingleton = MySingleton::get_instance(); // Get an instance
thread_local MySingleton& tls = MySingleton::get_thread_local_instance();
// Get a thread_local instance
```

See also

Code of `qpp::Codes`, `qpp::Gates`, `qpp::Init`, `qpp::RandomDevices`, `qpp::States` or `qpp.h` for real world examples of usage.

7.67.2 Constructor & Destructor Documentation

7.67.2.1 Singleton() [1/2]

```
template<typename T>
qpp::internal::Singleton< T >::Singleton ( ) [protected], [default], [noexcept]
```

7.67.2.2 Singleton() [2/2]

```
template<typename T>
qpp::internal::Singleton< T >::Singleton (
    const Singleton< T > & ) [protected], [delete]
```

7.67.2.3 ~Singleton()

```
template<typename T>
virtual qpp::internal::Singleton< T >::~~Singleton ( ) [protected], [virtual], [default]
```

7.67.3 Member Function Documentation

7.67.3.1 get_instance()

```
template<typename T>
static T& qpp::internal::Singleton< T >::get_instance ( ) [inline], [static], [noexcept]
```

7.67.3.2 get_thread_local_instance()

```
template<typename T>
static T& qpp::internal::Singleton< T >::get_thread_local_instance ( ) [inline], [static],
[noexcept]
```

7.67.3.3 operator=()

```
template<typename T>
Singleton& qpp::internal::Singleton< T >::operator= (
    const Singleton< T > & ) [protected], [delete]
```

The documentation for this class was generated from the following file:


- [internal/classes/singleton.h](#)

7.68 qpp::exception::SizeMismatch Class Reference


Size mismatch exception.

```
#include <classes/exception.h>
```

Inheritance diagram for qpp::exception::SizeMismatch:



Collaboration diagram for qpp::exception::SizeMismatch:



Public Member Functions

- `std::string type_description ()` const override
[Exception](#) type description.
- `Exception (const std::string &where)`
Constructs an exception.

7.68.1 Detailed Description

Size mismatch exception.

Sizes do not match

7.68.2 Member Function Documentation

7.68.2.1 [Exception\(\)](#)

```
qpp::exception::Exception::Exception [inline], [explicit]
```

Constructs an exception.

Parameters

<i>where</i>	Text representing where the exception occurred
--------------	------------------------------------------------

7.68.2.2 [type_description\(\)](#)

```
std::string qpp::exception::SizeMismatch::type_description ( ) const [inline], [override],  
[virtual]
```

[Exception](#) type description.

Returns

[Exception](#) type description

Implements [qpp::exception::Exception](#).

The documentation for this class was generated from the following file:

- `classes/exception.h`

7.69 qpp::NoiseType::StateDependent Class Reference

Template tag, used whenever the noise is state-dependent.

```
#include <classes/noise.h>
```

7.69.1 Detailed Description

Template tag, used whenever the noise is state-dependent.

The documentation for this class was generated from the following file:

- [classes/noise.h](#)

7.70 qpp::NoiseType::StateIndependent Class Reference

Template tag, used whenever the noise is state-independent.

```
#include <classes/noise.h>
```

7.70.1 Detailed Description

Template tag, used whenever the noise is state-independent.

The documentation for this class was generated from the following file:


- [classes/noise.h](#)

7.71 qpp::States Class Reference


const Singleton class that implements most commonly used states

```
#include <classes/states.h>
```

Inheritance diagram for qpp::States:



Collaboration diagram for qpp::States:



Public Member Functions

- `ket mes (idx d=2) const`
Maximally entangled state of 2 qudits.
- `ket zero (idx n, idx d=2) const`
Zero state of n qudits.
- `ket one (idx n, idx d=2) const`
One state of n qudits.
- `ket jn (idx j, idx n, idx d=2) const`
 $|j\rangle^{\otimes n}$ state of n qudits
- `ket plus (idx n) const`
Plus state of n qubits.
- `ket minus (idx n) const`
Minus state of n qubits.

Public Attributes

- `ket x0 {ket::Zero(2)}`
Pauli Sigma-X 0-eigenstate $|+\rangle$
- `ket x1 {ket::Zero(2)}`
Pauli Sigma-X 1-eigenstate $|-\rangle$
- `ket y0 {ket::Zero(2)}`
Pauli Sigma-Y 0-eigenstate $|y+\rangle$
- `ket y1 {ket::Zero(2)}`
Pauli Sigma-Y 1-eigenstate $|y-\rangle$
- `ket z0 {ket::Zero(2)}`
Pauli Sigma-Z 0-eigenstate $|0\rangle$
- `ket z1 {ket::Zero(2)}`
Pauli Sigma-Z 1-eigenstate $|1\rangle$
- `cmat px0 {cmat::Zero(2, 2)}`
Projector onto the Pauli Sigma-X 0-eigenstate $|+\rangle\langle +|$.
- `cmat px1 {cmat::Zero(2, 2)}`
Projector onto the Pauli Sigma-X 1-eigenstate $|-\rangle\langle -|$.

- [cmat py0](#) {cmat::Zero(2, 2)}
Projector onto the Pauli Sigma-Y 0-eigenstate $|y+\rangle\langle y+|$.
- [cmat py1](#) {cmat::Zero(2, 2)}
Projector onto the Pauli Sigma-Y 1-eigenstate $|y-\rangle\langle y-|$.
- [cmat pz0](#) {cmat::Zero(2, 2)}
Projector onto the Pauli Sigma-Z 0-eigenstate $|0\rangle\langle 0|$.
- [cmat pz1](#) {cmat::Zero(2, 2)}
Projector onto the Pauli Sigma-Z 1-eigenstate $|1\rangle\langle 1|$.
- [ket b00](#) {ket::Zero(4)}
Bell-00 state, as described in Nielsen and Chuang.
- [ket b01](#) {ket::Zero(4)}
Bell-01 state, as described in Nielsen and Chuang.
- [ket b10](#) {ket::Zero(4)}
Bell-10 state, as described in Nielsen and Chuang.
- [ket b11](#) {ket::Zero(4)}
Bell-11 state, as described in Nielsen and Chuang.
- [cmat pb00](#) {cmat::Zero(4, 4)}
Projector onto the Bell-00 state.
- [cmat pb01](#) {cmat::Zero(4, 4)}
Projector onto the Bell-01 state.
- [cmat pb10](#) {cmat::Zero(4, 4)}
Projector onto the Bell-10 state.
- [cmat pb11](#) {cmat::Zero(4, 4)}
Projector onto the Bell-11 state.
- [ket GHZ](#) {ket::Zero(8)}
GHZ state.
- [ket W](#) {ket::Zero(8)}
W state.
- [cmat pGHZ](#) {cmat::Zero(8, 8)}
Projector onto the GHZ state.
- [cmat pW](#) {cmat::Zero(8, 8)}
Projector onto the W state.

Private Member Functions

- [States](#) ()
- [~States](#) ()=default
Default destructor.

Friends

- class [internal::Singleton](#)< const [States](#) >

Additional Inherited Members

7.71.1 Detailed Description

const Singleton class that implements most commonly used states

7.71.2 Constructor & Destructor Documentation

7.71.2.1 States()

```
qpp::States::States ( ) [inline], [private]
```

Initialize the states

7.71.2.2 ~States()

```
qpp::States::~~States ( ) [private], [default]
```

Default destructor.

7.71.3 Member Function Documentation

7.71.3.1 jn()

```
ket qpp::States::jn (
    idx j,
    idx n,
    idx d = 2 ) const [inline]
```

$|j\rangle^{\otimes n}$ state of n qudits

Parameters

j	Non-negative integer
n	Non-negative integer
d	Subsystem dimensions

Returns

$|j\rangle^{\otimes n}$ state of n qudits

7.71.3.2 mes()

```
ket qpp::States::mes (
    idx d = 2 ) const [inline]
```

Maximally entangled state of 2 qudits.

Parameters

d	Subsystem dimensions
-----	----------------------

Returns

Maximally entangled state $\frac{1}{\sqrt{d}} \sum_{j=0}^{d-1} |jj\rangle$ of 2 qudits

7.71.3.3 minus()

```
ket qpp::States::minus (
    idx n ) const [inline]
```

Minus state of n qubits.

Parameters

n	Non-negative integer
-----	----------------------

Returns

Minus state $|-\rangle^{\otimes n}$ of n qubits

7.71.3.4 one()

```
ket qpp::States::one (
    idx n,
    idx d = 2 ) const [inline]
```

One state of n qudits.

Parameters

n	Non-negative integer
d	Subsystem dimensions

Returns

One state $|1\rangle^{\otimes n}$ of n qudits

7.71.3.5 plus()

```
ket qpp::States::plus (
    idx n ) const [inline]
```

Plus state of n qubits.

Parameters

n	Non-negative integer
-----	----------------------

Returns

Plus state $|+\rangle^{\otimes n}$ of n qubits

7.71.3.6 zero()

```
ket qpp::States::zero (
    idx n,
    idx d = 2 ) const [inline]
```

Zero state of n qudits.

Parameters

n	Non-negative integer
d	Subsystem dimensions

Returns

Zero state $|0\rangle^{\otimes n}$ of n qudits

7.71.4 Friends And Related Function Documentation

7.71.4.1 internal::Singleton< const States >

```
friend class internal::Singleton< const States > [friend]
```

7.71.5 Member Data Documentation

7.71.5.1 b00

```
ket qpp::States::b00 {ket::Zero(4)}
```

Bell-00 state, as described in Nielsen and Chuang.

7.71.5.2 b01

```
ket qpp::States::b01 {ket::Zero(4)}
```

Bell-01 state, as described in Nielsen and Chuang.

7.71.5.3 b10

```
ket qpp::States::b10 {ket::Zero(4)}
```

Bell-10 state, as described in Nielsen and Chuang.

7.71.5.4 b11

```
ket qpp::States::b11 {ket::Zero(4)}
```

Bell-11 state, as described in Nielsen and Chuang.

7.71.5.5 GHZ

```
ket qpp::States::GHZ {ket::Zero(8)}
```

GHZ state.

7.71.5.6 pb00

```
cmat qpp::States::pb00 {cmat::Zero(4, 4)}
```

Projector onto the Bell-00 state.

7.71.5.7 pb01

```
cmat qpp::States::pb01 {cmat::Zero(4, 4)}
```

Projector onto the Bell-01 state.

7.71.5.8 pb10

```
cmat qpp::States::pb10 {cmat::Zero(4, 4)}
```

Projector onto the Bell-10 state.

7.71.5.9 pb11

```
cmat qpp::States::pb11 {cmat::Zero(4, 4)}
```

Projector onto the Bell-11 state.

7.71.5.10 pGHZ

```
cmat qpp::States::pGHZ {cmat::Zero(8, 8)}
```

Projector onto the GHZ state.

7.71.5.11 pW

```
cmat qpp::States::pW {cmat::Zero(8, 8)}
```

Projector onto the W state.

7.71.5.12 px0

```
cmat qpp::States::px0 {cmat::Zero(2, 2)}
```

Projector onto the Pauli Sigma-X 0-eigenstate $|+\rangle\langle+|$.

7.71.5.13 px1

```
cmat qpp::States::px1 {cmat::Zero(2, 2)}
```

Projector onto the Pauli Sigma-X 1-eigenstate $|-\rangle\langle-|$.

7.71.5.14 py0

```
cmat qpp::States::py0 {cmat::Zero(2, 2)}
```

Projector onto the Pauli Sigma-Y 0-eigenstate $|y+\rangle\langle y+|$.

7.71.5.15 py1

```
cmat qpp::States::py1 {cmat::Zero(2, 2)}
```

Projector onto the Pauli Sigma-Y 1-eigenstate $|y-\rangle\langle y-|$.

7.71.5.16 pz0

```
cmat qpp::States::pz0 {cmat::Zero(2, 2)}
```

Projector onto the Pauli Sigma-Z 0-eigenstate $|0\rangle\langle 0|$.

7.71.5.17 pz1

```
cmat qpp::States::pz1 {cmat::Zero(2, 2)}
```

Projector onto the Pauli Sigma-Z 1-eigenstate $|1\rangle\langle 1|$.

7.71.5.18 W

```
ket qpp::States::W {ket::Zero(8)}
```

W state.

7.71.5.19 x0

```
ket qpp::States::x0 {ket::Zero(2)}
```

Pauli Sigma-X 0-eigenstate $|+\rangle$

7.71.5.20 x1

```
ket qpp::States::x1 {ket::Zero(2)}
```

Pauli Sigma-X 1-eigenstate $|-\rangle$

7.71.5.21 y0

```
ket qpp::States::y0 {ket::Zero(2)}
```

Pauli Sigma-Y 0-eigenstate $|y+\rangle$

7.71.5.22 y1

```
ket qpp::States::y1 {ket::Zero(2)}
```

Pauli Sigma-Y 1-eigenstate $|y-\rangle$

7.71.5.23 z0

```
ket qpp::States::z0 {ket::Zero(2)}
```

Pauli Sigma-Z 0-eigenstate $|0\rangle$

7.71.5.24 z1

```
ket qpp::States::z1 {ket::Zero(2)}
```

Pauli Sigma-Z 1-eigenstate $|1\rangle$

The documentation for this class was generated from the following file:


- [classes/states.h](#)

7.72 qpp::exception::SubsysMismatchDims Class Reference


Subsystems mismatch dimensions exception.

```
#include <classes/exception.h>
```

Inheritance diagram for qpp::exception::SubsysMismatchDims:



Collaboration diagram for qpp::exception::SubsysMismatchDims:



Public Member Functions

- `std::string type_description ()` const override
Exception type description.
- `Exception (const std::string &where)`
Constructs an exception.

7.72.1 Detailed Description

Subsystems mismatch dimensions exception.

`std::vector<idx>` of subsystem labels has duplicates, or has entries that are larger than the size of the `std::vector<idx>` of dimensions

7.72.2 Member Function Documentation

7.72.2.1 Exception()

```
qpp::exception::Exception::Exception [inline], [explicit]
```

Constructs an exception.

Parameters

<i>where</i>	Text representing where the exception occurred
--------------	------------------------------------------------

7.72.2.2 type_description()

```
std::string qpp::exception::SubsysMismatchDims::type_description ( ) const [inline], [override], [virtual]
```

[Exception](#) type description.

Returns

[Exception](#) type description

Implements [qpp::exception::Exception](#).

The documentation for this class was generated from the following file:


- [classes/exception.h](#)

7.73 qpp::Timer< T, CLOCK_T > Class Template Reference


Chronometer.

```
#include <classes/timer.h>
```

Inheritance diagram for qpp::Timer< T, CLOCK_T >:



Collaboration diagram for qpp::Timer< T, CLOCK_T >:



Public Member Functions

- `Timer ()` noexcept
Constructs an instance with the current time as the starting point.
- `void tic ()` noexcept
Resets the chronometer.
- `const Timer & toc ()` noexcept
Stops the chronometer.
- `double tics ()` const noexcept
Time passed in the duration specified by T.
- `template<typename U = T>`
 `U get_duration ()` const noexcept
Duration specified by U.
- `Timer (const Timer &)=default`

- *Default copy constructor.*
- [Timer](#) ([Timer](#) &&)=default
- *Default move constructor.*
- [Timer](#) & [operator=](#) (const [Timer](#) &)=default
- *Default copy assignment operator.*
- [Timer](#) & [operator=](#) ([Timer](#) &&)=default
- *Default move assignment operator.*
- virtual [~Timer](#) ()=default
- *Default virtual destructor.*

Protected Attributes

- [CLOCK_T::time_point](#) [start_](#)
- [CLOCK_T::time_point](#) [end_](#)

Private Member Functions

- [std::ostream](#) & [display](#) ([std::ostream](#) &os) const override
[qpp::IDisplay::display\(\)](#) override

7.73.1 Detailed Description

```
template<typename T = std::chrono::duration<double>, typename CLOCK_T = std::chrono::steady_clock>
class qpp::Timer< T, CLOCK_T >
```

Chronometer.

Template Parameters

T	Tics duration, default is <code>std::chrono::duration<double, 1></code> , i.e. seconds in double precision
CLOCK_T	Clock's type, default is <code>std::chrono::steady_clock</code> , not affected by wall clock changes during runtime

7.73.2 Constructor & Destructor Documentation

7.73.2.1 [Timer\(\)](#) [1/3]

```
template<typename T = std::chrono::duration<double>, typename CLOCK_T = std::chrono::steady_clock>
qpp::Timer< T, CLOCK_T >::Timer ( ) [inline], [noexcept]
```

Constructs an instance with the current time as the starting point.

7.73.2.2 Timer() [2/3]

```
template<typename T = std::chrono::duration<double>, typename CLOCK_T = std::chrono::steady↵
_clock>
qpp::Timer< T, CLOCK_T >::Timer (
    const Timer< T, CLOCK_T > & ) [default]
```

Default copy constructor.

7.73.2.3 Timer() [3/3]

```
template<typename T = std::chrono::duration<double>, typename CLOCK_T = std::chrono::steady↵
_clock>
qpp::Timer< T, CLOCK_T >::Timer (
    Timer< T, CLOCK_T > && ) [default]
```

Default move constructor.

7.73.2.4 ~Timer()

```
template<typename T = std::chrono::duration<double>, typename CLOCK_T = std::chrono::steady↵
_clock>
virtual qpp::Timer< T, CLOCK_T >::~~Timer ( ) [virtual], [default]
```

Default virtual destructor.

7.73.3 Member Function Documentation

7.73.3.1 display()

```
template<typename T = std::chrono::duration<double>, typename CLOCK_T = std::chrono::steady↵
_clock>
std::ostream& qpp::Timer< T, CLOCK_T >::display (
    std::ostream & os ) const [inline], [override], [private], [virtual]
```

[qpp::IDisplay::display\(\)](#) override

Writes to the output stream the number of tics (specified by T) that passed between the instantiation/reset and invocation of [qpp::Timer::toc\(\)](#).

Parameters

<i>os</i>	Output stream passed by reference
-----------	-----------------------------------

Returns

Reference to the output stream

Implements [qpp::IDisplay](#).

7.73.3.2 get_duration()

```
template<typename T = std::chrono::duration<double>, typename CLOCK_T = std::chrono::steady_clock>
template<typename U = T>
U qpp::Timer< T, CLOCK_T >::get_duration ( ) const [inline], [noexcept]
```

Duration specified by U.

Template Parameters

<i>U</i>	Duration, default is T, which defaults to std::chrono::duration<double, 1>, i.e. seconds in double precision
----------	--------------------------------------------------------------------------------------------------------------

Returns

Duration that passed between the instantiation/reset and invocation of [qpp::Timer::toc\(\)](#)

7.73.3.3 operator=() [1/2]

```
template<typename T = std::chrono::duration<double>, typename CLOCK_T = std::chrono::steady_clock>
Timer& qpp::Timer< T, CLOCK_T >::operator= (
    const Timer< T, CLOCK_T > & ) [default]
```

Default copy assignment operator.

7.73.3.4 operator=() [2/2]

```
template<typename T = std::chrono::duration<double>, typename CLOCK_T = std::chrono::steady_clock>
Timer& qpp::Timer< T, CLOCK_T >::operator= (
    Timer< T, CLOCK_T > && ) [default]
```

Default move assignment operator.

7.73.3.5 `tic()`

```
template<typename T = std::chrono::duration<double>, typename CLOCK_T = std::chrono::steady↵
_clock>
void qpp::Timer< T, CLOCK_T >::tic ( ) [inline], [noexcept]
```

Resets the chronometer.

Resets the starting/ending point to the current time

7.73.3.6 `tics()`

```
template<typename T = std::chrono::duration<double>, typename CLOCK_T = std::chrono::steady↵
_clock>
double qpp::Timer< T, CLOCK_T >::tics ( ) const [inline], [noexcept]
```

Time passed in the duration specified by T.

Returns

Number of tics (specified by T) that passed between the instantiation/reset and invocation of `qpp::Timer::toc()`

7.73.3.7 `toc()`

```
template<typename T = std::chrono::duration<double>, typename CLOCK_T = std::chrono::steady↵
_clock>
const Timer& qpp::Timer< T, CLOCK_T >::toc ( ) [inline], [noexcept]
```

Stops the chronometer.

Set the current time as the ending point

Returns

Reference to the current instance

7.73.4 Member Data Documentation

7.73.4.1 `end_`

```
template<typename T = std::chrono::duration<double>, typename CLOCK_T = std::chrono::steady↵
_clock>
CLOCK_T::time_point qpp::Timer< T, CLOCK_T >::end_ [protected]
```

7.73.4.2 start_

```
template<typename T = std::chrono::duration<double>, typename CLOCK_T = std::chrono::steady_clock>
_Clock>
CLOCK_T::time_point qpp::Timer< T, CLOCK_T >::start_ [protected]
```

The documentation for this class was generated from the following file:


- [classes/timer.h](#)

7.74 qpp::exception::TypeMismatch Class Reference


Type mismatch exception.

```
#include <classes/exception.h>
```

Inheritance diagram for qpp::exception::TypeMismatch:



Collaboration diagram for qpp::exception::TypeMismatch:



Public Member Functions

- `std::string type_description ()` const override
Exception type description.
- `Exception (const std::string &where)`
Constructs an exception.

7.74.1 Detailed Description

Type mismatch exception.

Scalar types do not match

7.74.2 Member Function Documentation

7.74.2.1 Exception()

```
qpp::exception::Exception::Exception [inline], [explicit]
```

Constructs an exception.

Parameters

<i>where</i>	Text representing where the exception occurred
--------------	------------------------------------------------

7.74.2.2 `type_description()`

```
std::string qpp::exception::TypeMismatch::type_description ( ) const [inline], [override],  
[virtual]
```

[Exception](#) type description.

Returns

[Exception](#) type description

Implements [qpp::exception::Exception](#).

The documentation for this class was generated from the following file:


- [classes/exception.h](#)

7.75 `qpp::exception::UndefinedType` Class Reference


Not defined for this type exception.

```
#include <classes/exception.h>
```

Inheritance diagram for `qpp::exception::UndefinedType`:



Collaboration diagram for qpp::exception::UndefinedType:



Public Member Functions

- `std::string type_description ()` const override
Exception type description.
- `Exception (const std::string &where)`
Constructs an exception.

7.75.1 Detailed Description

Not defined for this type exception.

Templated specialization is not defined for this type

7.75.2 Member Function Documentation

7.75.2.1 Exception()

```
qpp::exception::Exception::Exception [inline], [explicit]
```

Constructs an exception.

Parameters

<i>where</i>	Text representing where the exception occurred
--------------	------------------------------------------------

7.75.2.2 `type_description()`

```
std::string qpp::exception::UndefinedType::type_description ( ) const [inline], [override],  
[virtual]
```

[Exception](#) type description.

Returns

[Exception](#) type description

Implements [qpp::exception::Exception](#).

The documentation for this class was generated from the following file:


- [classes/exception.h](#)

7.76 `qpp::exception::Unknown` Class Reference


[Unknown](#) exception.

```
#include <classes/exception.h>
```

Inheritance diagram for `qpp::exception::Unknown`:



Collaboration diagram for qpp::exception::Unknown:



Public Member Functions

- `std::string type_description ()` const override
Exception type description.
- `Exception (const std::string &where)`
Constructs an exception.

7.76.1 Detailed Description

`Unknown` exception.

Thrown when no other exception is suitable (not recommended, it is better to define another suitable exception type)

7.76.2 Member Function Documentation

7.76.2.1 Exception()

```
qpp::exception::Exception::Exception [inline], [explicit]
```

Constructs an exception.

Parameters

<i>where</i>	Text representing where the exception occurred
--------------	------------------------------------------------

7.76.2.2 `type_description()`

```
std::string qpp::exception::Unknown::type_description ( ) const [inline], [override], [virtual]
```

[Exception](#) type description.

Returns

[Exception](#) type description

Implements [qpp::exception::Exception](#).


The documentation for this class was generated from the following file:

- [classes/exception.h](#)


7.77 `qpp::QCircuit::iterator::value_type_` Class Reference

Value type class for [qpp::QCircuit::iterator](#).

Inheritance diagram for `qpp::QCircuit::iterator::value_type_`:



Collaboration diagram for `qpp::QCircuit::iterator::value_type_`:



Public Member Functions

- [value_type_](#) (const [QCircuit](#) *[value_type_qc](#))
Default [value_type_](#) constructor.
- [value_type_](#) (const [value_type_](#) &)=default
Default copy constructor.
- [value_type_](#) & [operator=](#) (const [value_type_](#) &)=default
Default copy assignment operator.

Public Attributes

- const [QCircuit](#) * [value_type_qc_](#)
< non-owning pointer to the grand-parent const quantum circuit
- [StepType](#) [type_](#) {[StepType::NONE](#)}
step type
- [idx](#) [ip_](#) {static_cast<[idx](#)>(-1)}
instruction pointer
- std::vector< [GateStep](#) >::const_iterator [gates_ip_](#) {}
gates instruction pointer
- std::vector< [MeasureStep](#) >::const_iterator [measurements_ip_](#) {}
measurements instruction pointer

Private Member Functions

- std::ostream & [display](#) (std::ostream &os) const override
[qpp::IDisplay::display\(\)](#) override

7.77.1 Detailed Description

Value type class for [qpp::QCircuit::iterator](#).

7.77.2 Constructor & Destructor Documentation

7.77.2.1 [value_type_\(\)](#) [1/2]

```
qpp::QCircuit::iterator::value_type_::value_type_ (
    const QCircuit * value\_type\_qc ) [inline], [explicit]
```

Default [value_type_](#) constructor.

Parameters

value_type_qc	Pointer to constant quantum circuit
-------------------------------	-------------------------------------

7.77.2.2 `value_type_()` [2/2]

```
qpp::QCircuit::iterator::value_type_::value_type_ (
    const value_type_ & ) [default]
```

Default copy constructor.

7.77.3 Member Function Documentation

7.77.3.1 `display()`

```
std::ostream& qpp::QCircuit::iterator::value_type_::display (
    std::ostream & os ) const [inline], [override], [private], [virtual]
```

[qpp::IDisplay::display\(\)](#) override

Writes to the output stream the textual representation of the iterator de-referenced element

Parameters

<code>os</code>	Output stream passed by reference
-----------------	-----------------------------------

Returns

Reference to the output stream

Implements [qpp::IDisplay](#).

7.77.3.2 `operator=()`

```
value_type_& qpp::QCircuit::iterator::value_type_::operator= (
    const value_type_ & ) [default]
```

Default copy assignment operator.

Returns

Reference to the current instance

7.77.4 Member Data Documentation

7.77.4.1 gates_ip_

```
std::vector<GateStep>::const_iterator qpp::QCircuit::iterator::value_type_::gates_ip_ {}
```

gates instruction pointer

7.77.4.2 ip_

```
idx qpp::QCircuit::iterator::value_type_::ip_ {static_cast<idx>(-1)}
```

instruction pointer

7.77.4.3 measurements_ip_

```
std::vector<MeasureStep>::const_iterator qpp::QCircuit::iterator::value_type_::measurements_ip_ {}
```

measurements instruction pointer

7.77.4.4 type_

```
StepType qpp::QCircuit::iterator::value_type_::type_ {StepType::NONE}
```

step type

7.77.4.5 value_type_qc_

```
const QCircuit* qpp::QCircuit::iterator::value_type_::value_type_qc_
```

< non-owning pointer to the grand-parent const quantum circuit

The documentation for this class was generated from the following file:


- [classes/circuits/circuits.h](#)

7.78 qpp::exception::ZeroSize Class Reference


Object has zero size exception.

```
#include <classes/exception.h>
```

Inheritance diagram for qpp::exception::ZeroSize:



Collaboration diagram for qpp::exception::ZeroSize:



Public Member Functions

- `std::string type_description ()` const override
Exception type description.
- `Exception (const std::string &where)`
Constructs an exception.

7.78.1 Detailed Description

Object has zero size exception.

Zero sized object, e.g. empty `Eigen::Matrix` or `std::vector` with no elements

7.78.2 Member Function Documentation

7.78.2.1 Exception()

```
qpp::exception::Exception::Exception [inline], [explicit]
```

Constructs an exception.

Parameters

<i>where</i>	Text representing where the exception occurred
--------------	------------------------------------------------

7.78.2.2 type_description()

```
std::string qpp::exception::ZeroSize::type_description ( ) const [inline], [override], [virtual]
```

[Exception](#) type description.

Returns

[Exception](#) type description

Implements [qpp::exception::Exception](#).

The documentation for this class was generated from the following file:

- `classes/exception.h`


Chapter 8

File Documentation

8.1 classes/circuits/circuits.h File Reference

Qudit quantum circuits.

This graph shows which files directly or indirectly include this file:



Classes

- class [qpp::QCircuit](#)
Quantum circuit class.
- struct [qpp::QCircuit::GateStep](#)
One step consisting only of gates/operators in the circuit.
- struct [qpp::QCircuit::MeasureStep](#)
One step consisting only of measurements in the circuit.
- class [qpp::QCircuit::iterator](#)
Quantum circuit bound-checking (safe) iterator.
- class [qpp::QCircuit::iterator::value_type_](#)
Value type class for [qpp::QCircuit::iterator](#).

Namespaces

- [qpp](#)

Quantum++ main namespace.


8.1.1 Detailed Description

Qudit quantum circuits.

8.2 classes/circuits/engines.h File Reference

Qudit quantum engines.

This graph shows which files directly or indirectly include this file:



Classes

- class [qpp::QEngine](#)
Quantum circuit engine, executes [qpp::QCircuit](#).
- class [qpp::QNoisyEngine< NoiseModel >](#)
Noisy quantum circuit engine, executes [qpp::QCircuit](#).

Namespaces

- [qpp](#)

Quantum++ main namespace.


8.2.1 Detailed Description

Qudit quantum engines.

8.3 classes/codes.h File Reference

Quantum error correcting codes.

This graph shows which files directly or indirectly include this file:



Classes

- class [qpp::Codes](#)
const Singleton class that defines quantum error correcting codes

Namespaces

- [qpp](#)
Quantum++ main namespace.


8.3.1 Detailed Description

Quantum error correcting codes.

8.4 classes/exception.h File Reference

Exceptions.

This graph shows which files directly or indirectly include this file:



Classes

- class [qpp::exception::Exception](#)
Base class for generating Quantum++ custom exceptions.
- class [qpp::exception::Unknown](#)
Unknown exception.
- class [qpp::exception::ZeroSize](#)
Object has zero size exception.
- class [qpp::exception::MatrixNotSquare](#)
Matrix is not square exception.
- class [qpp::exception::MatrixNotCvector](#)
Matrix is not a column vector exception.
- class [qpp::exception::MatrixNotRvector](#)
Matrix is not a row vector exception.
- class [qpp::exception::MatrixNotVector](#)
Matrix is not a vector exception.
- class [qpp::exception::MatrixNotSquareNorCvector](#)
Matrix is not square nor column vector exception.
- class [qpp::exception::MatrixNotSquareNorRvector](#)
Matrix is not square nor row vector exception.
- class [qpp::exception::MatrixNotSquareNorVector](#)
Matrix is not square nor vector exception.
- class [qpp::exception::MatrixMismatchSubsys](#)
Matrix mismatch subsystems exception.
- class [qpp::exception::DimsInvalid](#)
Invalid dimension(s) exception.
- class [qpp::exception::DimsNotEqual](#)
Dimensions not equal exception.
- class [qpp::exception::DimsMismatchMatrix](#)
Dimension(s) mismatch matrix size exception.
- class [qpp::exception::DimsMismatchCvector](#)
Dimension(s) mismatch column vector size exception.
- class [qpp::exception::DimsMismatchRvector](#)
Dimension(s) mismatch row vector size exception.
- class [qpp::exception::DimsMismatchVector](#)
Dimension(s) mismatch vector size exception.
- class [qpp::exception::SubsysMismatchDims](#)
Subsystems mismatch dimensions exception.
- class [qpp::exception::PermInvalid](#)
Invalid permutation exception.
- class [qpp::exception::PermMismatchDims](#)
Permutation mismatch dimensions exception.
- class [qpp::exception::NotQubitMatrix](#)
Matrix is not 2 x 2 exception.
- class [qpp::exception::NotQubitCvector](#)
Column vector is not 2 x 1 exception.
- class [qpp::exception::NotQubitRvector](#)
Row vector is not 1 x 2 exception.
- class [qpp::exception::NotQubitVector](#)
Vector is not 2 x 1 nor 1 x 2 exception.
- class [qpp::exception::NotQubitSubsys](#)

- Subsystems are not qubits exception.*
- class [qpp::exception::NotBipartite](#)
Not bi-partite exception.
- class [qpp::exception::NoCodeword](#)
Codeword does not exist exception.
- class [qpp::exception::OutOfRange](#)
Argument out of range exception.
- class [qpp::exception::TypeMismatch](#)
Type mismatch exception.
- class [qpp::exception::SizeMismatch](#)
Size mismatch exception.
- class [qpp::exception::UndefinedType](#)
Not defined for this type exception.
- class [qpp::exception::QuditAlreadyMeasured](#)
Qudit was already measured exception.
- class [qpp::exception::Duplicates](#)
System (e.g. std::vector) has duplicates exception.
- class [qpp::exception::CustomException](#)
Custom exception.
- class [qpp::exception::NotImplemented](#)
Code not yet implemented.
- class [qpp::exception::InvalidIterator](#)
Invalid iterator.

Namespaces

- [qpp](#)
Quantum++ main namespace.
- [qpp::exception](#)
Quantum++ exception hierarchy namespace.


8.4.1 Detailed Description

Exceptions.

8.5 classes/gates.h File Reference

Quantum gates.

This graph shows which files directly or indirectly include this file:



Classes

- class [qpp::Gates](#)
const Singleton class that implements most commonly used gates

Namespaces

- [qpp](#)
Quantum++ main namespace.


8.5.1 Detailed Description

Quantum gates.

8.6 classes/ideisplay.h File Reference

Display interface via the non-virtual interface (NVI) and very basic JSON serialization support interface.

This graph shows which files directly or indirectly include this file:



Classes

- class [qpp::IDisplay](#)
Abstract class (interface) that mandates the definition of virtual `std::ostream& display(std::ostream& os) const`.
- class [qpp::IJSON](#)
Abstract class (interface) that mandates the definition of very basic JSON serialization support.

Namespaces

- [qpp](#)
Quantum++ main namespace.


8.6.1 Detailed Description

Display interface via the non-virtual interface (NVI) and very basic JSON serialization support interface.

8.7 classes/init.h File Reference

Initialization.

This graph shows which files directly or indirectly include this file:



Classes

- class [qpp::Init](#)
const Singleton class that performs additional initializations/cleanups

Namespaces

- [qpp](#)
Quantum++ main namespace.


8.7.1 Detailed Description

Initialization.

8.8 classes/noise.h File Reference

Noise models.

This graph shows which files directly or indirectly include this file:



Classes

- class [qpp::NoiseType](#)
Contains template tags used to specify the noise type.
- class [qpp::NoiseBase< T >](#)
Base class for all noise models, derive your particular noise model.
- class [qpp::QubitDepolarizingNoise](#)
Qubit depolarizing noise.
- class [qpp::QubitPhaseFlipNoise](#)
Qubit phase flip (dephasing) noise.
- class [qpp::QubitBitFlipNoise](#)
Qubit bit flip noise.
- class [qpp::QubitBitPhaseFlipNoise](#)
Qubit bit-phase flip (dephasing) noise.
- class [qpp::QubitAmplitudeDampingNoise](#)
Qubit amplitude damping noise, as described in Nielsen and Chuang.
- class [qpp::QubitPhaseDampingNoise](#)
Qubit phase damping noise, as described in Nielsen and Chuang.
- class [qpp::QuditDepolarizingNoise](#)
Qudit depolarizing noise.

Namespaces

- [qpp](#)
Quantum++ main namespace.


8.8.1 Detailed Description

Noise models.

8.9 classes/random_devices.h File Reference

Random devices.

This graph shows which files directly or indirectly include this file:



Classes

- class [qpp::RandomDevices](#)

Singleton class that manages the source of randomness in the library.

Namespaces

- [qpp](#)

Quantum++ main namespace.


8.9.1 Detailed Description

Random devices.

8.10 classes/reversible.h File Reference

Support for classical reversible circuits.

This graph shows which files directly or indirectly include this file:



Classes

- class [qpp::Dynamic_bitset](#)
Dynamic bitset class, allows the specification of the number of bits at runtime (unlike `std::bitset<N>`)
- class [qpp::Bit_circuit](#)
Classical reversible circuit simulator.
- struct [qpp::Bit_circuit::Gate_count](#)

Namespaces

- [qpp](#)
Quantum++ main namespace.


8.10.1 Detailed Description

Support for classical reversible circuits.

8.11 classes/states.h File Reference

Quantum states.

This graph shows which files directly or indirectly include this file:



Classes

- class [qpp::States](#)
const Singleton class that implements most commonly used states

Namespaces

- [qpp](#)
Quantum++ main namespace.


8.11.1 Detailed Description

Quantum states.

8.12 classes/timer.h File Reference

Timing.

This graph shows which files directly or indirectly include this file:



Classes

- class [qpp::Timer< T, CLOCK_T >](#)
Chronometer.

Namespaces

- [qpp](#)
Quantum++ main namespace.


8.12.1 Detailed Description

Timing.

8.13 constants.h File Reference

Constants.

This graph shows which files directly or indirectly include this file:



Namespaces

- [qpp](#)
Quantum++ main namespace.
- [qpp::literals](#)

Functions

- constexpr cplx [qpp::literals::operator"" _i](#) (unsigned long long int x) noexcept
User-defined literal for complex $i = \sqrt{-1}$ (integer overload)
- constexpr cplx [qpp::operator"" _i](#) (long double x) noexcept
User-defined literal for complex $i = \sqrt{-1}$ (real overload)
- cplx [qpp::omega](#) (idx D)
D-th root of unity.

Variables

- constexpr double [qpp::chop](#) = 1e-10
Used in [qpp::disp\(\)](#) for setting to zero numbers that have their absolute value smaller than [qpp::chop](#).
- constexpr idx [qpp::maxn](#) = 64
Maximum number of allowed qubits/qudits (subsystems)
- constexpr double [qpp::pi](#) = 3.141592653589793238462643383279502884
 π
- constexpr double [qpp::ee](#) = 2.718281828459045235360287471352662497
Base of natural logarithm, e .
- constexpr double [qpp::infy](#) = std::numeric_limits<double>::max()
Used to denote infinity in double precision.


8.13.1 Detailed Description

Constants.

8.14 entanglement.h File Reference

Entanglement functions.

This graph shows which files directly or indirectly include this file:



Namespaces

- [qpp](#)
Quantum++ main namespace.

Functions

- `template<typename Derived >`
`dyn_col_vect< double > qpp::schmidtcoeffs (const Eigen::MatrixBase< Derived > &A, const std::vector< idx > &dims)`
Schmidt coefficients of the bi-partite pure state A.
- `template<typename Derived >`
`dyn_col_vect< double > qpp::schmidtcoeffs (const Eigen::MatrixBase< Derived > &A, idx d=2)`
Schmidt coefficients of the bi-partite pure state A.
- `template<typename Derived >`
`cmat qpp::schmidtA (const Eigen::MatrixBase< Derived > &A, const std::vector< idx > &dims)`
Schmidt basis on Alice side.
- `template<typename Derived >`
`cmat qpp::schmidtA (const Eigen::MatrixBase< Derived > &A, idx d=2)`
Schmidt basis on Alice side.
- `template<typename Derived >`
`cmat qpp::schmidtB (const Eigen::MatrixBase< Derived > &A, const std::vector< idx > &dims)`
Schmidt basis on Bob side.
- `template<typename Derived >`
`cmat qpp::schmidtB (const Eigen::MatrixBase< Derived > &A, idx d=2)`

Schmidt basis on Bob side.

- `template<typename Derived >`
`std::vector< double > qpp::schmidtprobs (const Eigen::MatrixBase< Derived > &A, const std::vector< idx`
`> &dims)`

Schmidt probabilities of the bi-partite pure state A.

- `template<typename Derived >`
`std::vector< double > qpp::schmidtprobs (const Eigen::MatrixBase< Derived > &A, idx d=2)`

Schmidt probabilities of the bi-partite pure state A.

- `template<typename Derived >`
`double qpp::entanglement (const Eigen::MatrixBase< Derived > &A, const std::vector< idx > &dims)`

Entanglement of the bi-partite pure state A.

- `template<typename Derived >`
`double qpp::entanglement (const Eigen::MatrixBase< Derived > &A, idx d=2)`

Entanglement of the bi-partite pure state A.

- `template<typename Derived >`
`double qpp::gconcurrence (const Eigen::MatrixBase< Derived > &A)`

G-concurrence of the bi-partite pure state A.

- `template<typename Derived >`
`double qpp::negativity (const Eigen::MatrixBase< Derived > &A, const std::vector< idx > &dims)`

Negativity of the bi-partite mixed state A.

- `template<typename Derived >`
`double qpp::negativity (const Eigen::MatrixBase< Derived > &A, idx d=2)`

Negativity of the bi-partite mixed state A.

- `template<typename Derived >`
`double qpp::lognegativity (const Eigen::MatrixBase< Derived > &A, const std::vector< idx > &dims)`

Logarithmic negativity of the bi-partite mixed state A.

- `template<typename Derived >`
`double qpp::lognegativity (const Eigen::MatrixBase< Derived > &A, idx d=2)`

Logarithmic negativity of the bi-partite mixed state A.

- `template<typename Derived >`
`double qpp::concurrence (const Eigen::MatrixBase< Derived > &A)`

Wootters concurrence of the bi-partite qubit mixed state A.


8.14.1 Detailed Description

Entanglement functions.

8.15 entropies.h File Reference

Entropy functions.

This graph shows which files directly or indirectly include this file:



Namespaces

- [qpp](#)
Quantum++ main namespace.

Functions

- `template<typename Derived >`
`double qpp::entropy (const Eigen::MatrixBase< Derived > &A)`
von-Neumann entropy of the density matrix A
- `double qpp::entropy (const std::vector< double > &prob)`
Shannon entropy of the probability distribution prob.
- `template<typename Derived >`
`double qpp::renyi (const Eigen::MatrixBase< Derived > &A, double alpha)`
Renyi- α entropy of the density matrix A, for $\alpha \geq 0$.
- `double qpp::renyi (const std::vector< double > &prob, double alpha)`
Renyi- α entropy of the probability distribution prob, for $\alpha \geq 0$.
- `template<typename Derived >`
`double qpp::tsallis (const Eigen::MatrixBase< Derived > &A, double q)`
Tsallis- q entropy of the density matrix A, for $q \geq 0$.
- `double qpp::tsallis (const std::vector< double > &prob, double q)`
Tsallis- q entropy of the probability distribution prob, for $q \geq 0$.
- `template<typename Derived >`
`double qpp::qmutualinfo (const Eigen::MatrixBase< Derived > &A, const std::vector< idx > &subsysA, const std::vector< idx > &subsysB, const std::vector< idx > &dims)`
Quantum mutual information between 2 subsystems of a composite system.
- `template<typename Derived >`
`double qpp::qmutualinfo (const Eigen::MatrixBase< Derived > &A, const std::vector< idx > &subsysA, const std::vector< idx > &subsysB, idx d=2)`
Quantum mutual information between 2 subsystems of a composite system.

8.15.1 Detailed Description

Entropy functions.

8.16 experimental/experimental.h File Reference

Experimental/test functions/classes.

Namespaces

- [qpp](#)
Quantum++ main namespace.
- [qpp::experimental](#)
Experimental/test functions/classes, do not use or modify.


8.16.1 Detailed Description

Experimental/test functions/classes.

8.17 functions.h File Reference

Generic quantum computing functions.

This graph shows which files directly or indirectly include this file:



Classes

- class [qpp::internal::HashEigen](#)
Functor for hashing Eigen expressions.
- class [qpp::internal::EqualEigen](#)
Functor for comparing Eigen expressions for equality.

Namespaces

- [qpp](#)
Quantum++ main namespace.
- [qpp::literals](#)
- [qpp::internal](#)
Internal utility functions, do not use them directly or modify them.

Functions

- `template<typename Derived >`
`dyn_mat< typename Derived::Scalar > qpp::transpose (const Eigen::MatrixBase< Derived > &A)`
Transpose.
- `template<typename Derived >`
`dyn_mat< typename Derived::Scalar > qpp::conjugate (const Eigen::MatrixBase< Derived > &A)`
Complex conjugate.
- `template<typename Derived >`
`dyn_mat< typename Derived::Scalar > qpp::adjoint (const Eigen::MatrixBase< Derived > &A)`
Adjoint.
- `template<typename Derived >`
`dyn_mat< typename Derived::Scalar > qpp::inverse (const Eigen::MatrixBase< Derived > &A)`
Inverse.
- `template<typename Derived >`
`Derived::Scalar qpp::trace (const Eigen::MatrixBase< Derived > &A)`
Trace.
- `template<typename Derived >`
`Derived::Scalar qpp::det (const Eigen::MatrixBase< Derived > &A)`
Determinant.
- `template<typename Derived >`
`Derived::Scalar qpp::logdet (const Eigen::MatrixBase< Derived > &A)`
Logarithm of the determinant.
- `template<typename Derived >`
`Derived::Scalar qpp::sum (const Eigen::MatrixBase< Derived > &A)`
Element-wise sum of A.
- `template<typename Derived >`
`Derived::Scalar qpp::prod (const Eigen::MatrixBase< Derived > &A)`
Element-wise product of A.
- `template<typename Derived >`
`double qpp::norm (const Eigen::MatrixBase< Derived > &A)`
Frobenius norm.
- `template<typename Derived >`
`dyn_mat< typename Derived::Scalar > qpp::normalize (const Eigen::MatrixBase< Derived > &A)`
Normalizes state vector (column or row vector) or density matrix.
- `template<typename Derived >`
`std::pair< dyn_col_vect< cplx >, cmat > qpp::eig (const Eigen::MatrixBase< Derived > &A)`
Full eigen decomposition.
- `template<typename Derived >`
`dyn_col_vect< cplx > qpp::evals (const Eigen::MatrixBase< Derived > &A)`
Eigenvalues.
- `template<typename Derived >`
`cmat qpp::evecs (const Eigen::MatrixBase< Derived > &A)`
Eigenvectors.
- `template<typename Derived >`
`std::pair< dyn_col_vect< double >, cmat > qpp::heig (const Eigen::MatrixBase< Derived > &A)`
Full eigen decomposition of Hermitian expression.
- `template<typename Derived >`
`dyn_col_vect< double > qpp::hevals (const Eigen::MatrixBase< Derived > &A)`
Hermitian eigenvalues.
- `template<typename Derived >`
`cmat qpp::hevecs (const Eigen::MatrixBase< Derived > &A)`
Eigenvectors of Hermitian matrix.

- `template<typename Derived >`
`std::tuple< cmat, dyn_col_vect< double >, cmat > qpp::svd (const Eigen::MatrixBase< Derived > &A)`
Full singular value decomposition.
- `template<typename Derived >`
`dyn_col_vect< double > qpp::svals (const Eigen::MatrixBase< Derived > &A)`
Singular values.
- `template<typename Derived >`
`cmat qpp::svdU (const Eigen::MatrixBase< Derived > &A)`
Left singular vectors.
- `template<typename Derived >`
`cmat qpp::svdV (const Eigen::MatrixBase< Derived > &A)`
Right singular vectors.
- `template<typename Derived >`
`cmat qpp::funm (const Eigen::MatrixBase< Derived > &A, cplx(*f)(const cplx &))`
Functional calculus $f(A)$
- `template<typename Derived >`
`cmat qpp::sqrtm (const Eigen::MatrixBase< Derived > &A)`
Matrix square root.
- `template<typename Derived >`
`cmat qpp::absm (const Eigen::MatrixBase< Derived > &A)`
Matrix absolute value.
- `template<typename Derived >`
`cmat qpp::expm (const Eigen::MatrixBase< Derived > &A)`
Matrix exponential.
- `template<typename Derived >`
`cmat qpp::logm (const Eigen::MatrixBase< Derived > &A)`
Matrix logarithm.
- `template<typename Derived >`
`cmat qpp::sinm (const Eigen::MatrixBase< Derived > &A)`
Matrix sin.
- `template<typename Derived >`
`cmat qpp::cosm (const Eigen::MatrixBase< Derived > &A)`
Matrix cos.
- `template<typename Derived >`
`cmat qpp::spectralpowm (const Eigen::MatrixBase< Derived > &A, const cplx z)`
Matrix power.
- `template<typename Derived >`
`dyn_mat< typename Derived::Scalar > qpp::powm (const Eigen::MatrixBase< Derived > &A, idx n)`
Fast matrix power based on the SQUARE-AND-MULTIPLY algorithm.
- `template<typename Derived >`
`double qpp::schatten (const Eigen::MatrixBase< Derived > &A, double p)`
Schatten matrix norm.
- `template<typename OutputScalar, typename Derived >`
`dyn_mat< OutputScalar > qpp::cwise (const Eigen::MatrixBase< Derived > &A, OutputScalar(*f)(const`
`typename Derived::Scalar &))`
Functor.
- `template<typename T >`
`dyn_mat< typename T::Scalar > qpp::kron (const T &head)`
Kronecker product.
- `template<typename T, typename... Args>`
`dyn_mat< typename T::Scalar > qpp::kron (const T &head, const Args &... tail)`
Kronecker product.

- `template<typename Derived >`
`dyn_mat< typename Derived::Scalar > qpp::kron (const std::vector< Derived > &As)`
Kronecker product.
- `template<typename Derived >`
`dyn_mat< typename Derived::Scalar > qpp::kron (const std::initializer_list< Derived > &As)`
Kronecker product.
- `template<typename Derived >`
`dyn_mat< typename Derived::Scalar > qpp::kronpow (const Eigen::MatrixBase< Derived > &A, idx n)`
Kronecker power.
- `template<typename T >`
`dyn_mat< typename T::Scalar > qpp::dirsum (const T &head)`
Direct sum.
- `template<typename T, typename... Args>`
`dyn_mat< typename T::Scalar > qpp::dirsum (const T &head, const Args &... tail)`
Direct sum.
- `template<typename Derived >`
`dyn_mat< typename Derived::Scalar > qpp::dirsum (const std::vector< Derived > &As)`
Direct sum.
- `template<typename Derived >`
`dyn_mat< typename Derived::Scalar > qpp::dirsum (const std::initializer_list< Derived > &As)`
Direct sum.
- `template<typename Derived >`
`dyn_mat< typename Derived::Scalar > qpp::dirsumpow (const Eigen::MatrixBase< Derived > &A, idx n)`
Direct sum power.
- `template<typename Derived >`
`dyn_mat< typename Derived::Scalar > qpp::reshape (const Eigen::MatrixBase< Derived > &A, idx rows, idx cols)`
Reshape.
- `template<typename Derived1, typename Derived2 >`
`dyn_mat< typename Derived1::Scalar > qpp::comm (const Eigen::MatrixBase< Derived1 > &A, const Eigen::MatrixBase< Derived2 > &B)`
Commutator.
- `template<typename Derived1, typename Derived2 >`
`dyn_mat< typename Derived1::Scalar > qpp::anticomm (const Eigen::MatrixBase< Derived1 > &A, const Eigen::MatrixBase< Derived2 > &B)`
Anti-commutator.
- `template<typename Derived >`
`dyn_mat< typename Derived::Scalar > qpp::prj (const Eigen::MatrixBase< Derived > &A)`
Projector.
- `template<typename Derived >`
`dyn_mat< typename Derived::Scalar > qpp::grams (const std::vector< Derived > &As)`
Gram-Schmidt orthogonalization.
- `template<typename Derived >`
`dyn_mat< typename Derived::Scalar > qpp::grams (const std::initializer_list< Derived > &As)`
Gram-Schmidt orthogonalization.
- `template<typename Derived >`
`dyn_mat< typename Derived::Scalar > qpp::grams (const Eigen::MatrixBase< Derived > &A)`
Gram-Schmidt orthogonalization.
- `std::vector< idx > qpp::n2multiidx (idx n, const std::vector< idx > &dims)`
Non-negative integer index to multi-index.
- `idx qpp::multiidx2n (const std::vector< idx > &midx, const std::vector< idx > &dims)`
Multi-index to non-negative integer index.
- `ket qpp::mket (const std::vector< idx > &mask, const std::vector< idx > &dims)`

- Multi-partite qudit ket.*

 - ket [qpp::mket](#) (const std::vector< idx > &mask, idx d=2)

Multi-partite qudit ket.

 - cmat [qpp::mprj](#) (const std::vector< idx > &mask, const std::vector< idx > &dims)

Projector onto multi-partite qudit ket.

 - cmat [qpp::mprj](#) (const std::vector< idx > &mask, idx d=2)

Projector onto multi-partite qudit ket.

 - template<typename InputIterator >
std::vector< double > [qpp::abssq](#) (InputIterator first, InputIterator last)
Computes the absolute values squared of an STL-like range of complex numbers.
 - template<typename Container >
std::vector< double > [qpp::abssq](#) (const Container &c, typename std::enable_if< is_iterable< Container >::value >::type *!=nullptr)
Computes the absolute values squared of an STL-like container.
 - template<typename Derived >
std::vector< double > [qpp::abssq](#) (const Eigen::MatrixBase< Derived > &A)
Computes the absolute values squared of an Eigen expression.
 - template<typename InputIterator >
std::iterator_traits< InputIterator >::value_type [qpp::sum](#) (InputIterator first, InputIterator last)
Element-wise sum of an STL-like range.
 - template<typename Container >
Container::value_type [qpp::sum](#) (const Container &c, typename std::enable_if< is_iterable< Container >::value >::type *!=nullptr)
Element-wise sum of the elements of an STL-like container.
 - template<typename InputIterator >
std::iterator_traits< InputIterator >::value_type [qpp::prod](#) (InputIterator first, InputIterator last)
Element-wise product of an STL-like range.
 - template<typename Container >
Container::value_type [qpp::prod](#) (const Container &c, typename std::enable_if< is_iterable< Container >::value >::type *!=nullptr)
Element-wise product of the elements of an STL-like container.
 - template<typename Derived >
dyn_col_vect< typename Derived::Scalar > [qpp::rho2pure](#) (const Eigen::MatrixBase< Derived > &A)
Finds the pure state representation of a matrix proportional to a projector onto a pure state.
 - std::vector< idx > [qpp::complement](#) (std::vector< idx > subsys, idx n)
Constructs the complement of a subsystem vector.
 - template<typename Derived >
std::vector< double > [qpp::rho2bloch](#) (const Eigen::MatrixBase< Derived > &A)
Computes the 3-dimensional real Bloch vector corresponding to the qubit density matrix A.
 - cmat [qpp::bloch2rho](#) (const std::vector< double > &r)
Computes the density matrix corresponding to the 3-dimensional real Bloch vector r.
 - template<char... Bits>
ket [qpp::literals::operator"" _ket](#) ()
Multi-partite qubit ket user-defined literal.
 - template<char... Bits>
bra [qpp::literals::operator"" _bra](#) ()
Multi-partite qubit bra user-defined literal.
 - template<char... Bits>
cmat [qpp::literals::operator"" _prj](#) ()
Multi-partite qubit projector user-defined literal.
 - template<class T >
void [qpp::internal::hash_combine](#) (std::size_t &seed, const T &v)
 - template<typename Derived >
std::size_t [qpp::hash_eigen](#) (const Eigen::MatrixBase< Derived > &A, std::size_t seed=0)
Computes the hash of an Eigen matrix/vector/expression.


8.17.1 Detailed Description

Generic quantum computing functions.

8.18 input_output.h File Reference

Input/output functions.

This graph shows which files directly or indirectly include this file:



Namespaces

- [qpp](#)
Quantum++ main namespace.

Functions

- `template<typename Derived >`
`internal::IOManipEigen qpp::disp (const Eigen::MatrixBase< Derived > &A, double chop=qpp::chop)`
Eigen expression ostream manipulator.
- `internal::IOManipEigen qpp::disp (cplx z, double chop=qpp::chop)`
Complex number ostream manipulator.
- `template<typename InputIterator >`
`internal::IOManipRange< InputIterator > qpp::disp (InputIterator first, InputIterator last, const std::string &separator, const std::string &start="[" , const std::string &end="]")`
Range ostream manipulator.
- `template<typename Container >`
`internal::IOManipRange< typename Container::const_iterator > qpp::disp (const Container &c, const std::string &separator, const std::string &start="[" , const std::string &end="]", typename std::enable_if< is_iterable< Container >::value >::type !=nullptr)`
Standard container ostream manipulator. The container must support std::begin(), std::end() and forward iteration.
- `template<typename PointerType >`
`internal::IOManipPointer< PointerType > qpp::disp (const PointerType *p, idx N, const std::string &separator, const std::string &start="[" , const std::string &end="]")`
C-style pointer ostream manipulator.
- `template<typename Derived >`
`void qpp::save (const Eigen::MatrixBase< Derived > &A, const std::string &fname)`
Saves Eigen expression to a binary file (internal format) in double precision.
- `template<typename Derived >`
`dyn_mat< typename Derived::Scalar > qpp::load (const std::string &fname)`
Loads Eigen matrix from a binary file (internal format) in double precision.


8.18.1 Detailed Description

Input/output functions.

8.19 instruments.h File Reference

Measurement functions.

This graph shows which files directly or indirectly include this file:



Namespaces

- [qpp](#)
Quantum++ main namespace.

Functions

- `template<typename Derived >`
`dyn_col_vect< typename Derived::Scalar > qpp::ip (const Eigen::MatrixBase< Derived > &phi, const Eigen::MatrixBase< Derived > &psi, const std::vector< idx > &subsys, const std::vector< idx > &dims)`
Generalized inner product.
- `template<typename Derived >`
`dyn_col_vect< typename Derived::Scalar > qpp::ip (const Eigen::MatrixBase< Derived > &phi, const Eigen::MatrixBase< Derived > &psi, const std::vector< idx > &subsys, idx d=2)`
Generalized inner product.
- `template<typename Derived >`
`std::tuple< idx, std::vector< double >, std::vector< cmat > > qpp::measure (const Eigen::MatrixBase< Derived > &A, const std::vector< cmat > &Ks)`
Measures the state vector or density operator A using the set of Kraus operators Ks.
- `template<typename Derived >`
`std::tuple< idx, std::vector< double >, std::vector< cmat > > qpp::measure (const Eigen::MatrixBase< Derived > &A, const std::initializer_list< cmat > &Ks)`
Measures the state vector or density matrix A using the set of Kraus operators Ks.
- `template<typename Derived >`
`std::tuple< idx, std::vector< double >, std::vector< cmat > > qpp::measure (const Eigen::MatrixBase< Derived > &A, const cmat &U)`

Measures the state vector or density matrix A in the orthonormal basis specified by the unitary matrix U.

- `template<typename Derived >`
`std::tuple< idx, std::vector< double >, std::vector< cmat > > qpp::measure` (const Eigen::MatrixBase< Derived > &A, const std::vector< cmat > &Ks, const std::vector< idx > &target, const std::vector< idx > &dims)

Measures the part subsys of the multi-partite state vector or density matrix A using the set of Kraus operators Ks.

- `template<typename Derived >`
`std::tuple< idx, std::vector< double >, std::vector< cmat > > qpp::measure` (const Eigen::MatrixBase< Derived > &A, const std::initializer_list< cmat > &Ks, const std::vector< idx > &target, const std::vector< idx > &dims)

Measures the part target of the multi-partite state vector or density matrix A using the set of Kraus operators Ks.

- `template<typename Derived >`
`std::tuple< idx, std::vector< double >, std::vector< cmat > > qpp::measure` (const Eigen::MatrixBase< Derived > &A, const std::vector< cmat > &Ks, const std::vector< idx > &target, idx d=2)

Measures the part target of the multi-partite state vector or density matrix A using the set of Kraus operators Ks.

- `template<typename Derived >`
`std::tuple< idx, std::vector< double >, std::vector< cmat > > qpp::measure` (const Eigen::MatrixBase< Derived > &A, const std::initializer_list< cmat > &Ks, const std::vector< idx > &target, idx d=2)

Measures the part target of the multi-partite state vector or density matrix A using the set of Kraus operators Ks.

- `template<typename Derived >`
`std::tuple< idx, std::vector< double >, std::vector< cmat > > qpp::measure` (const Eigen::MatrixBase< Derived > &A, const cmat &V, const std::vector< idx > &target, const std::vector< idx > &dims)

Measures the part target of the multi-partite state vector or density matrix A in the orthonormal basis or rank-1 projectors specified by the columns of the matrix V.

- `template<typename Derived >`
`std::tuple< idx, std::vector< double >, std::vector< cmat > > qpp::measure` (const Eigen::MatrixBase< Derived > &A, const cmat &V, const std::vector< idx > &target, idx d=2)

Measures the part target of the multi-partite state vector or density matrix A in the orthonormal basis or rank-1 projectors specified by the columns of the matrix V.

- `template<typename Derived >`
`std::tuple< std::vector< idx >, double, cmat > qpp::measure_seq` (const Eigen::MatrixBase< Derived > &A, std::vector< idx > target, std::vector< idx > dims)

Sequentially measures the part target of the multi-partite state vector or density matrix A in the computational basis.

- `template<typename Derived >`
`std::tuple< std::vector< idx >, double, cmat > qpp::measure_seq` (const Eigen::MatrixBase< Derived > &A, std::vector< idx > target, idx d=2)

Sequentially measures the part target of the multi-partite state vector or density matrix A in the computational basis.


8.19.1 Detailed Description

Measurement functions.

8.20 internal/classes/iomanip.h File Reference

Input/output manipulators.

This graph shows which files directly or indirectly include this file:



Classes

- class [qpp::internal::IOManipRange< InputIterator >](#)
- class [qpp::internal::IOManipPointer< PointerType >](#)
- class [qpp::internal::IOManipEigen](#)

Namespaces

- [qpp](#)
Quantum++ main namespace.
- [qpp::internal](#)
Internal utility functions, do not use them directly or modify them.


8.20.1 Detailed Description

Input/output manipulators.

8.21 internal/classes/singleton.h File Reference

Singleton pattern via CRTP.

This graph shows which files directly or indirectly include this file:



Classes

- class [qpp::internal::Singleton< T >](#)
Singleton policy class, used internally to implement the singleton pattern via CRTP (Curiously recurring template pattern)

Namespaces

- [qpp](#)
Quantum++ main namespace.
- [qpp::internal](#)
Internal utility functions, do not use them directly or modify them.


8.21.1 Detailed Description

Singleton pattern via CRTP.

8.22 internal/util.h File Reference

Internal utility functions.

This graph shows which files directly or indirectly include this file:



Classes

- struct [qpp::internal::Display_Impl_](#)

Namespaces

- [qpp](#)
Quantum++ main namespace.
- [qpp::internal](#)
Internal utility functions, do not use them directly or modify them.

Functions

- void [qpp::internal::n2multiidx](#) (idx n, idx numdims, const idx *const dims, idx *result) noexcept
- idx [qpp::internal::multiidx2n](#) (const idx *const midx, idx numdims, const idx *const dims) noexcept
- template<typename Derived >
bool [qpp::internal::check_square_mat](#) (const Eigen::MatrixBase< Derived > &A)
- template<typename Derived >
bool [qpp::internal::check_vector](#) (const Eigen::MatrixBase< Derived > &A)
- template<typename Derived >
bool [qpp::internal::check_rvector](#) (const Eigen::MatrixBase< Derived > &A)
- template<typename Derived >
bool [qpp::internal::check_cvector](#) (const Eigen::MatrixBase< Derived > &A)
- template<typename T >
bool [qpp::internal::check_nonzero_size](#) (const T &x) noexcept
- template<typename T1 , typename T2 >
bool [qpp::internal::check_matching_sizes](#) (const T1 &lhs, const T2 &rhs) noexcept
- bool [qpp::internal::check_dims](#) (const std::vector< idx > &dims)
- template<typename Derived >
bool [qpp::internal::check_dims_match_mat](#) (const std::vector< idx > &dims, const Eigen::MatrixBase< Derived > &A)
- template<typename Derived >
bool [qpp::internal::check_dims_match_cvect](#) (const std::vector< idx > &dims, const Eigen::MatrixBase< Derived > &A)
- template<typename Derived >
bool [qpp::internal::check_dims_match_rvect](#) (const std::vector< idx > &dims, const Eigen::MatrixBase< Derived > &A)
- bool [qpp::internal::check_eq_dims](#) (const std::vector< idx > &dims, idx dim) noexcept
- bool [qpp::internal::check_no_duplicates](#) (std::vector< idx > v)
- bool [qpp::internal::check_subsys_match_dims](#) (const std::vector< idx > &subsys, const std::vector< idx > &dims)
- template<typename Derived >
bool [qpp::internal::check_qubit_matrix](#) (const Eigen::MatrixBase< Derived > &A) noexcept
- template<typename Derived >
bool [qpp::internal::check_qubit_cvector](#) (const Eigen::MatrixBase< Derived > &A) noexcept
- template<typename Derived >
bool [qpp::internal::check_qubit_rvector](#) (const Eigen::MatrixBase< Derived > &A) noexcept
- template<typename Derived >
bool [qpp::internal::check_qubit_vector](#) (const Eigen::MatrixBase< Derived > &A) noexcept
- bool [qpp::internal::check_perm](#) (const std::vector< idx > &perm)
- template<typename Derived1 , typename Derived2 >
dyn_mat< typename Derived1::Scalar > [qpp::internal::kron2](#) (const Eigen::MatrixBase< Derived1 > &A, const Eigen::MatrixBase< Derived2 > &B)
- template<typename Derived1 , typename Derived2 >
dyn_mat< typename Derived1::Scalar > [qpp::internal::dirsum2](#) (const Eigen::MatrixBase< Derived1 > &A, const Eigen::MatrixBase< Derived2 > &B)
- template<typename T >
void [qpp::internal::variadic_vector_emplace](#) (std::vector< T > &)
- template<typename T , typename First , typename... Args>
void [qpp::internal::variadic_vector_emplace](#) (std::vector< T > &v, First &&first, Args &&... args)
- idx [qpp::internal::get_num_subsys](#) (idx D, idx d)
- idx [qpp::internal::get_dim_subsys](#) (idx sz, idx N)

8.22.1 Detailed Description

Internal utility functions.

8.23 MATLAB/matlab.h File Reference

Input/output interfacing with MATLAB.

```
#include "mat.h"
#include "mex.h"
```

Namespaces

- [qpp](#)
Quantum++ main namespace.

Functions

- `template<typename Derived >`
`std::enable_if< std::is_same< typename Derived::Scalar, cplx >::value, dyn_mat< cplx > >::type`
[qpp::loadMATLAB](#) (const std::string &mat_file, const std::string &var_name)
Loads a complex Eigen dynamic matrix from a MATLAB .mat file,.
- `template<typename Derived >`
`std::enable_if<!std::is_same< typename Derived::Scalar, cplx >::value, dyn_mat< typename Derived::Scalar > >::type`
[qpp::loadMATLAB](#) (const std::string &mat_file, const std::string &var_name)
Loads a non-complex Eigen dynamic matrix from a MATLAB .mat file,.
- `template<typename Derived >`
`std::enable_if< std::is_same< typename Derived::Scalar, cplx >::value >::type`
[qpp::saveMATLAB](#) (const Eigen::MatrixBase< Derived > &A, const std::string &mat_file, const std::string &var_name, const std::string &mode)
Saves a complex Eigen dynamic matrix to a MATLAB .mat file,.
- `template<typename Derived >`
`std::enable_if< !std::is_same< typename Derived::Scalar, cplx >::value >::type`
[qpp::saveMATLAB](#) (const Eigen::MatrixBase< Derived > &A, const std::string &mat_file, const std::string &var_name, const std::string &mode)
Saves a non-complex Eigen dynamic matrix to a MATLAB .mat file,.


8.23.1 Detailed Description

Input/output interfacing with MATLAB.

8.24 number_theory.h File Reference

Number theory functions.

This graph shows which files directly or indirectly include this file:



Namespaces

- [qpp](#)
Quantum++ main namespace.

Functions

- `std::vector< int > qpp::x2contfrac (double x, idx N, idx cut=1e5)`
Simple continued fraction expansion.
- `double qpp::contfrac2x (const std::vector< int > &cf, idx N=idx(-1))`
Real representation of a simple continued fraction.
- `bigint qpp::gcd (bigint a, bigint b)`
Greatest common divisor of two integers.
- `bigint qpp::gcd (const std::vector< bigint > &as)`
Greatest common divisor of a list of integers.
- `bigint qpp::lcm (bigint a, bigint b)`
Least common multiple of two integers.
- `bigint qpp::lcm (const std::vector< bigint > &as)`
Least common multiple of a list of integers.
- `std::vector< idx > qpp::invperm (const std::vector< idx > &perm)`
Inverse permutation.
- `std::vector< idx > qpp::compperm (const std::vector< idx > &perm, const std::vector< idx > &sigma)`
Compose permutations.
- `std::vector< bigint > qpp::factors (bigint a)`
Prime factor decomposition.
- `bigint qpp::modmul (bigint a, bigint b, bigint p)`
Modular multiplication without overflow.
- `bigint qpp::modpow (bigint a, bigint n, bigint p)`
Fast integer power modulo p based on the SQUARE-AND-MULTIPLY algorithm.
- `std::tuple< bigint, bigint, bigint > qpp::egcd (bigint a, bigint b)`
Extended greatest common divisor of two integers.
- `bigint qpp::modinv (bigint a, bigint p)`
Modular inverse of a mod p.
- `bool qpp::isprime (bigint p, idx k=80)`

- Primality test based on the Miller-Rabin's algorithm.*
- bigint [qpp::randprime](#) (bigint a, bigint b, idx N=1000)
Generates a random big prime uniformly distributed in the interval [a, b].
- std::vector< std::pair< int, int > > [qpp::convergents](#) (const std::vector< int > &cf)
Convergents.
- std::vector< std::pair< int, int > > [qpp::convergents](#) (double x, idx N)
Convergents.


8.24.1 Detailed Description

Number theory functions.

8.25 operations.h File Reference

Quantum operation functions.

This graph shows which files directly or indirectly include this file:



Namespaces

- [qpp](#)
Quantum++ main namespace.

Functions

- template<typename Derived1 , typename Derived2 >
dyn_mat< typename Derived1::Scalar > [qpp::applyCTRL](#) (const Eigen::MatrixBase< Derived1 > &state, const Eigen::MatrixBase< Derived2 > &A, const std::vector< idx > &ctrl, const std::vector< idx > &target, const std::vector< idx > &dims)
Applies the controlled-gate A to the part target of the multi-partite state vector or density matrix state.
- template<typename Derived1 , typename Derived2 >
dyn_mat< typename Derived1::Scalar > [qpp::applyCTRL](#) (const Eigen::MatrixBase< Derived1 > &state, const Eigen::MatrixBase< Derived2 > &A, const std::vector< idx > &ctrl, const std::vector< idx > &target, idx d=2)

Applies the controlled-gate A to the part target of the multi-partite state vector or density matrix state.

- `template<typename Derived1 , typename Derived2 >`
`dyn_mat< typename Derived1::Scalar > qpp::apply (const Eigen::MatrixBase< Derived1 > &state, const Eigen::MatrixBase< Derived2 > &A, const std::vector< idx > &target, const std::vector< idx > &dims)`

Applies the gate A to the part target of the multi-partite state vector or density matrix state.

- `template<typename Derived1 , typename Derived2 >`
`dyn_mat< typename Derived1::Scalar > qpp::apply (const Eigen::MatrixBase< Derived1 > &state, const Eigen::MatrixBase< Derived2 > &A, const std::vector< idx > &target, idx d=2)`

Applies the gate A to the part target of the multi-partite state vector or density matrix state.

- `template<typename Derived >`
`cmat qpp::apply (const Eigen::MatrixBase< Derived > &A, const std::vector< cmat > &Ks)`

Applies the channel specified by the set of Kraus operators Ks to the density matrix A.

- `template<typename Derived >`
`cmat qpp::apply (const Eigen::MatrixBase< Derived > &A, const std::vector< cmat > &Ks, const std::vector< idx > &target, const std::vector< idx > &dims)`

Applies the channel specified by the set of Kraus operators Ks to the part target of the multi-partite density matrix A.

- `template<typename Derived >`
`cmat qpp::apply (const Eigen::MatrixBase< Derived > &A, const std::vector< cmat > &Ks, const std::vector< idx > &target, idx d=2)`

Applies the channel specified by the set of Kraus operators Ks to the part target of the multi-partite density matrix A.

- `cmat qpp::kraus2super (const std::vector< cmat > &Ks)`

Superoperator matrix.

- `cmat qpp::kraus2choi (const std::vector< cmat > &Ks)`

Choi matrix.

- `std::vector< cmat > qpp::choi2kraus (const cmat &A)`

Orthogonal Kraus operators from Choi matrix.

- `cmat qpp::choi2super (const cmat &A)`

Converts Choi matrix to superoperator matrix.

- `cmat qpp::super2choi (const cmat &A)`

Converts superoperator matrix to Choi matrix.

- `template<typename Derived >`
`dyn_mat< typename Derived::Scalar > qpp::ptrace1 (const Eigen::MatrixBase< Derived > &A, const std::vector< idx > &dims)`

Partial trace.

- `template<typename Derived >`
`dyn_mat< typename Derived::Scalar > qpp::ptrace1 (const Eigen::MatrixBase< Derived > &A, idx d=2)`

Partial trace.

- `template<typename Derived >`
`dyn_mat< typename Derived::Scalar > qpp::ptrace2 (const Eigen::MatrixBase< Derived > &A, const std::vector< idx > &dims)`

Partial trace.

- `template<typename Derived >`
`dyn_mat< typename Derived::Scalar > qpp::ptrace2 (const Eigen::MatrixBase< Derived > &A, idx d=2)`

Partial trace.

- `template<typename Derived >`
`dyn_mat< typename Derived::Scalar > qpp::ptrace (const Eigen::MatrixBase< Derived > &A, const std::vector< idx > &target, const std::vector< idx > &dims)`

Partial trace.

- `template<typename Derived >`
`dyn_mat< typename Derived::Scalar > qpp::ptrace (const Eigen::MatrixBase< Derived > &A, const std::vector< idx > &target, idx d=2)`

Partial trace.

- `template<typename Derived >`
`dyn_mat< typename Derived::Scalar > qpp::ptranspose (const Eigen::MatrixBase< Derived > &A, const std::vector< idx > &target, const std::vector< idx > &dims)`
Partial transpose.
- `template<typename Derived >`
`dyn_mat< typename Derived::Scalar > qpp::ptranspose (const Eigen::MatrixBase< Derived > &A, const std::vector< idx > &target, idx d=2)`
Partial transpose.
- `template<typename Derived >`
`dyn_mat< typename Derived::Scalar > qpp::syspermute (const Eigen::MatrixBase< Derived > &A, const std::vector< idx > &perm, const std::vector< idx > &dims)`
Subsystem permutation.
- `template<typename Derived >`
`dyn_mat< typename Derived::Scalar > qpp::syspermute (const Eigen::MatrixBase< Derived > &A, const std::vector< idx > &perm, idx d=2)`
Subsystem permutation.
- `template<typename Derived >`
`dyn_mat< typename Derived::Scalar > qpp::applyQFT (const Eigen::MatrixBase< Derived > &A, const std::vector< idx > &target, idx d=2, bool swap=true)`
Applies the qudit quantum Fourier transform to the part target of the multi-partite state vector or density matrix A.
- `template<typename Derived >`
`dyn_mat< typename Derived::Scalar > qpp::applyTFQ (const Eigen::MatrixBase< Derived > &A, const std::vector< idx > &target, idx d=2, bool swap=true)`
Applies the inverse (adjoint) qudit quantum Fourier transform to the part target of the multi-partite state vector or density matrix A.
- `template<typename Derived >`
`dyn_col_vect< typename Derived::Scalar > qpp::TFQ (const Eigen::MatrixBase< Derived > &A, idx d=2, bool swap=true)`
Inverse (adjoint) qudit quantum Fourier transform.
- `template<typename Derived >`
`dyn_col_vect< typename Derived::Scalar > qpp::QFT (const Eigen::MatrixBase< Derived > &A, idx d=2, bool swap=true)`
Qudit quantum Fourier transform.

8.25.1 Detailed Description

Quantum operation functions.

8.26 qpp.h File Reference

Quantum++ main header file, includes all other necessary headers.

```
#include <algorithm>
#include <cassert>
#include <chrono>
#include <cmath>
#include <complex>
#include <cstdlib>
#include <cstring>
#include <exception>
#include <fstream>
```

```

#include <functional>
#include <initializer_list>
#include <iomanip>
#include <iterator>
#include <limits>
#include <memory>
#include <numeric>
#include <ostream>
#include <random>
#include <sstream>
#include <stdexcept>
#include <string>
#include <tuple>
#include <type_traits>
#include <unordered_map>
#include <utility>
#include <vector>
#include <Eigen/Dense>
#include <Eigen/SVD>
#include "types.h"
#include "classes/exception.h"
#include "constants.h"
#include "traits.h"
#include "classes/idisplay.h"
#include "internal/util.h"
#include "internal/classes/iomanip.h"
#include "input_output.h"
#include "internal/classes/singleton.h"
#include "classes/random_devices.h"
#include "random.h"
#include "number_theory.h"
#include "functions.h"
#include "classes/init.h"
#include "classes/codes.h"
#include "classes/gates.h"
#include "classes/states.h"
#include "statistics.h"
#include "operations.h"
#include "entropies.h"
#include "entanglement.h"
#include "classes/timer.h"
#include "instruments.h"
#include "classes/reversible.h"
#include "classes/noise.h"
#include "classes/circuits/circuits.h"
#include "classes/circuits/engines.h"

```

Namespaces

- [qpp](#)
Quantum++ main namespace.

Macros

- `#define QPP_UNUSED_`

8.26.1 Detailed Description

Quantum++ main header file, includes all other necessary headers.

8.26.2 Macro Definition Documentation


8.26.2.1 QPP_UNUSED_

```
#define QPP_UNUSED_
```

8.27 random.h File Reference

Randomness-related functions.

This graph shows which files directly or indirectly include this file:



Namespaces

- [qpp](#)

Quantum++ main namespace.

Functions

- double `qpp::rand` (double a, double b)
Generates a random real number uniformly distributed in the interval [a, b]
- bigint `qpp::rand` (bigint a, bigint b)
Generates a random big integer uniformly distributed in the interval [a, b].
- idx `qpp::randidx` (idx a=std::numeric_limits< idx >::min(), idx b=std::numeric_limits< idx >::max())
Generates a random index (idx) uniformly distributed in the interval [a, b].
- template<typename Derived >
 Derived `qpp::rand` (idx rows `QPP_UNUSED_`, idx cols `QPP_UNUSED_`, double a `QPP_UNUSED_=0`, double b `QPP_UNUSED_=1`)
Generates a random matrix with entries uniformly distributed in the interval [a, b]
- template<>
 dmat `qpp::rand` (idx rows, idx cols, double a, double b)
Generates a random real matrix with entries uniformly distributed in the interval [a, b], specialization for double matrices (`qpp::dmat`)
- template<>
 cmat `qpp::rand` (idx rows, idx cols, double a, double b)
Generates a random complex matrix with entries (both real and imaginary) uniformly distributed in the interval [a, b], specialization for complex matrices (`qpp::cmat`)
- template<typename Derived >
 Derived `qpp::randn` (idx rows `QPP_UNUSED_`, idx cols `QPP_UNUSED_`, double mean `QPP_UNUSED_=0`, double sigma `QPP_UNUSED_=1`)
Generates a random matrix with entries normally distributed in $N(\text{mean}, \text{sigma})$
- template<>
 dmat `qpp::randn` (idx rows, idx cols, double mean, double sigma)
Generates a random real matrix with entries normally distributed in $N(\text{mean}, \text{sigma})$, specialization for double matrices (`qpp::dmat`)
- template<>
 cmat `qpp::randn` (idx rows, idx cols, double mean, double sigma)
Generates a random complex matrix with entries (both real and imaginary) normally distributed in $N(\text{mean}, \text{sigma})$, specialization for complex matrices (`qpp::cmat`)
- double `qpp::randn` (double mean=0, double sigma=1)
Generates a random real number (double) normally distributed in $N(\text{mean}, \text{sigma})$
- cmat `qpp::randU` (idx D=2)
Generates a random unitary matrix.
- cmat `qpp::randV` (idx Din, idx Dout)
Generates a random isometry matrix.
- std::vector< cmat > `qpp::randkraus` (idx N, idx D=2)
Generates a set of random Kraus operators.
- cmat `qpp::randH` (idx D=2)
Generates a random Hermitian matrix.
- ket `qpp::randket` (idx D=2)
Generates a random normalized ket (pure state vector)
- cmat `qpp::randrho` (idx D=2)
Generates a random density matrix.
- std::vector< idx > `qpp::randperm` (idx N)
Generates a random uniformly distributed permutation.
- std::vector< double > `qpp::randprob` (idx N)
Generates a random probability vector uniformly distributed over the probability simplex.


8.27.1 Detailed Description

Randomness-related functions.

8.28 statistics.h File Reference

Statistics functions.

This graph shows which files directly or indirectly include this file:



Namespaces

- [qpp](#)
Quantum++ main namespace.

Functions

- `std::vector< double > qpp::uniform (idx N)`
Uniform probability distribution vector.
- `std::vector< double > qpp::marginalX (const dmat &probXY)`
Marginal distribution.
- `std::vector< double > qpp::marginalY (const dmat &probXY)`
Marginal distribution.
- `template<typename Container >`
`double qpp::avg (const std::vector< double > &prob, const Container &X, typename std::enable_if< is_↔`
`iterable< Container >::value >::type *==nullptr)`
Average.
- `template<typename Container >`
`double qpp::cov (const dmat &probXY, const Container &X, const Container &Y, typename std::enable_if<`
`is_iterable< Container >::value >::type *==nullptr)`
Covariance.
- `template<typename Container >`
`double qpp::var (const std::vector< double > &prob, const Container &X, typename std::enable_if< is_↔`
`iterable< Container >::value >::type *==nullptr)`
Variance.

- `template<typename Container >`
`double qpp::sigma (const std::vector< double > &prob, const Container &X, typename std::enable_if< is_↵`
`iterable< Container >::value >::type * = nullptr)`
Standard deviation.
- `template<typename Container >`
`double qpp::cor (const dmat &probXY, const Container &X, const Container &Y, typename std::enable_if<`
`is_iterable< Container >::value >::type * = nullptr)`
Correlation.


8.28.1 Detailed Description

Statistics functions.

8.29 traits.h File Reference

Type traits.

This graph shows which files directly or indirectly include this file:



Classes

- `struct qpp::make_void< Ts >`
Helper for `qpp::to_void<>` alias template.
- `struct qpp::is_iterable< T, typename >`
Checks whether `T` is compatible with an STL-like iterable container.
- `struct qpp::is_iterable< T, to_void< decltype(std::declval< T >().begin()), decltype(std::declval< T >().end()), decltype(*(std::`
Checks whether `T` is compatible with an STL-like iterable container, specialization for STL-like iterable containers.
- `struct qpp::is_matrix_expression< Derived >`
Checks whether the type is an Eigen matrix expression.
- `struct qpp::is_complex< T >`
Checks whether the type is a complex type.
- `struct qpp::is_complex< std::complex< T > >`
Checks whether the type is a complex number type, specialization for complex types.

Namespaces

- [qpp](#)

Quantum++ main namespace.

Typedefs

- `template<typename... Ts>
using qpp::to_void = typename make_void< Ts... >::type`

Alias template that implements the proposal for void_t.


8.29.1 Detailed Description

Type traits.

8.30 types.h File Reference

Type aliases.

This graph shows which files directly or indirectly include this file:



Namespaces

- [qpp](#)

Quantum++ main namespace.

Typedefs

- using `qpp::idx` = `std::size_t`
Non-negative integer index, make sure you use an unsigned type.
- using `qpp::bigint` = `long long int`
Big integer.
- using `qpp::cplx` = `std::complex< double >`
Complex number in double precision.
- using `qpp::ket` = `Eigen::VectorXcd`
Complex (double precision) dynamic Eigen column vector.
- using `qpp::bra` = `Eigen::RowVectorXcd`
Complex (double precision) dynamic Eigen row vector.
- using `qpp::cmat` = `Eigen::MatrixXcd`
Complex (double precision) dynamic Eigen matrix.
- using `qpp::dmat` = `Eigen::MatrixXd`
Real (double precision) dynamic Eigen matrix.
- template<typename Scalar >
using `qpp::dyn_mat` = `Eigen::Matrix< Scalar, Eigen::Dynamic, Eigen::Dynamic >`
Dynamic Eigen matrix over the field specified by Scalar.
- template<typename Scalar >
using `qpp::dyn_col_vect` = `Eigen::Matrix< Scalar, Eigen::Dynamic, 1 >`
Dynamic Eigen column vector over the field specified by Scalar.
- template<typename Scalar >
using `qpp::dyn_row_vect` = `Eigen::Matrix< Scalar, 1, Eigen::Dynamic >`
Dynamic Eigen row vector over the field specified by Scalar.

8.30.1 Detailed Description

Type aliases.

8.31 /Users/vlad/qpp/README.md File Reference

Index

/Users/vlad/qpp/README.md, [402](#)

~Codes

qpp::Codes, [138](#)

~Dynamic_bitset

qpp::Dynamic_bitset, [160](#)

~Gates

qpp::Gates, [176](#)

~IDisplay

qpp::IDisplay, [192](#)

~IJSON

qpp::IJSON, [195](#)

~Init

qpp::Init, [197](#)

~NoiseBase

qpp::NoiseBase, [243](#)

~QCircuit

qpp::QCircuit, [276](#)

~QEngine

qpp::QEngine, [302](#)

~RandomDevices

qpp::RandomDevices, [328](#)

~Singleton

qpp::internal::Singleton, [332](#)

~States

qpp::States, [338](#)

~Timer

qpp::Timer, [349](#)

A_

qpp::internal::IOManipEigen, [202](#)

absm

qpp, [31](#)

abssq

qpp, [31](#), [32](#)

add_hash_

qpp::QCircuit, [276](#)

adjoint

qpp, [32](#)

all

qpp::Dynamic_bitset, [160](#)

anticomm

qpp, [33](#)

any

qpp::Dynamic_bitset, [160](#)

apply

qpp, [33–35](#)

applyCTRL

qpp, [36](#)

applyQFT

qpp, [37](#)

applyTFQ

qpp, [38](#)

avg

qpp, [38](#)

b00

qpp::States, [340](#)

b01

qpp::States, [341](#)

b10

qpp::States, [341](#)

b11

qpp::States, [341](#)

begin

qpp::QCircuit, [276](#)

bigint

qpp, [28](#)

Bit_circuit

qpp::Bit_circuit, [133](#)

bloch2rho

qpp, [38](#)

bra

qpp, [28](#)

c_reg_

qpp::QCircuit::MeasureStep, [238](#)

cCTRL_custom

qpp::QCircuit, [279](#)

cCTRL

qpp::QCircuit, [277](#), [278](#)

CNOTba

qpp::Gates, [185](#)

CNOT

qpp::Bit_circuit, [133](#)

qpp::Bit_circuit::Gate_count, [172](#)

qpp::Gates, [185](#)

CTRL_custom

qpp::QCircuit, [282](#)

CTRL

qpp::Gates, [177](#)

qpp::QCircuit, [280](#), [281](#)

cbegin

qpp::QCircuit, [277](#)

cend

qpp::QCircuit, [279](#)

check_cvector

qpp::internal, [122](#)

check_dims

qpp::internal, [122](#)

check_dims_match_cvect

- qpp::internal, 122
- check_dims_match_mat
 - qpp::internal, 122
- check_dims_match_rvect
 - qpp::internal, 122
- check_eq_dims
 - qpp::internal, 123
- check_matching_sizes
 - qpp::internal, 123
- check_no_duplicates
 - qpp::internal, 123
- check_nonzero_size
 - qpp::internal, 123
- check_perm
 - qpp::internal, 123
- check_qubit_cvector
 - qpp::internal, 123
- check_qubit_matrix
 - qpp::internal, 124
- check_qubit_rvector
 - qpp::internal, 124
- check_qubit_vector
 - qpp::internal, 124
- check_rvector
 - qpp::internal, 124
- check_square_mat
 - qpp::internal, 124
- check_subsys_match_dims
 - qpp::internal, 124
- check_vector
 - qpp::internal, 125
- choi2kraus
 - qpp, 39
- choi2super
 - qpp, 39
- chop
 - qpp, 118
- chop_
 - qpp::internal::IOManipEigen, 202
- classes/circuits/circuits.h, 365
- classes/circuits/engines.h, 366
- classes/codes.h, 367
- classes/exception.h, 367
- classes/gates.h, 369
- classes/ideisplay.h, 370
- classes/init.h, 371
- classes/noise.h, 372
- classes/random_devices.h, 373
- classes/reversible.h, 373
- classes/states.h, 374
- classes/timer.h, 375
- cmat
 - qpp, 29
- cmat_hash_tbl_
 - qpp::QCircuit, 297
- Codes
 - qpp::Codes, 138
- codeword
 - qpp::Codes, 138
- comm
 - qpp, 40
- complement
 - qpp, 40
- compperm
 - qpp, 41
- compute_probs_
 - qpp::NoiseBase, 244
- compute_state_
 - qpp::NoiseBase, 244
- concurrency
 - qpp, 41
- conjugate
 - qpp, 42
- const_iterator
 - qpp::QCircuit, 274
- constants.h, 376
- contrfrac2x
 - qpp, 42
- convergents
 - qpp, 42, 43
- cor
 - qpp, 43
- cosm
 - qpp, 44
- count
 - qpp::Dynamic_bitset, 160
- count_
 - qpp::QCircuit, 297
- cov
 - qpp, 44
- cplx
 - qpp, 29
- ctrl_
 - qpp::QCircuit::GateStep, 189
- CustomException
 - qpp::exception::CustomException, 140
- cwise
 - qpp, 45
- CZ
 - qpp::Gates, 185
- d_
 - qpp::NoiseBase, 247
 - qpp::QCircuit, 297
- data
 - qpp::Dynamic_bitset, 160
- depth_
 - qpp::QCircuit, 297
- det
 - qpp, 45
- difference_type
 - qpp::QCircuit::iterator, 215
- dirsum
 - qpp, 46, 47
- dirsum2
 - qpp::internal, 125
- dirsumpow

- qpp, 47
- disp
 - qpp, 48–50
- display
 - qpp::Dynamic_bitset, 161
 - qpp::IDisplay, 193
 - qpp::QCircuit, 282
 - qpp::QCircuit::iterator::value_type_, 360
 - qpp::QEngine, 303
 - qpp::Timer, 349
 - qpp::internal::LOManipEigen, 202
 - qpp::internal::LOManipPointer, 204
 - qpp::internal::LOManipRange, 207
- display_impl_
 - qpp::internal::Display_Impl_, 154
- dits_
 - qpp::QEngine, 309
- dmat
 - qpp, 29
- dyn_col_vect
 - qpp, 29
- dyn_mat
 - qpp, 29
- dyn_row_vect
 - qpp, 30
- Dynamic_bitset
 - qpp::Bit_circuit, 134
 - qpp::Dynamic_bitset, 159
- ee
 - qpp, 118
- egcd
 - qpp, 50
- eig
 - qpp, 51
- elem_
 - qpp::QCircuit::iterator, 219
- end
 - qpp::QCircuit, 282, 283
- end_
 - qpp::Timer, 351
 - qpp::internal::LOManipPointer, 205
 - qpp::internal::LOManipRange, 208
- entanglement
 - qpp, 51, 52
- entanglement.h, 377
- entropies.h, 378
- entropy
 - qpp, 52, 53
- evals
 - qpp, 53
- evects
 - qpp, 53
- Exception
 - qpp::exception::DimsInvalid, 143
 - qpp::exception::DimsMismatchCvector, 145
 - qpp::exception::DimsMismatchMatrix, 147
 - qpp::exception::DimsMismatchRvector, 149
 - qpp::exception::DimsMismatchVector, 151
 - qpp::exception::DimsNotEqual, 153
 - qpp::exception::Duplicates, 156
 - qpp::exception::Exception, 171
 - qpp::exception::InvalidIterator, 199
 - qpp::exception::MatrixMismatchSubsys, 221
 - qpp::exception::MatrixNotCvector, 223
 - qpp::exception::MatrixNotRvector, 225
 - qpp::exception::MatrixNotSquare, 227
 - qpp::exception::MatrixNotSquareNorCvector, 229
 - qpp::exception::MatrixNotSquareNorRvector, 231
 - qpp::exception::MatrixNotSquareNorVector, 233
 - qpp::exception::MatrixNotVector, 235
 - qpp::exception::NoCodeword, 240
 - qpp::exception::NotBipartite, 250
 - qpp::exception::NotImplemented, 252
 - qpp::exception::NotQubitCvector, 254
 - qpp::exception::NotQubitMatrix, 256
 - qpp::exception::NotQubitRvector, 258
 - qpp::exception::NotQubitSubsys, 260
 - qpp::exception::NotQubitVector, 262
 - qpp::exception::OutOfRange, 264
 - qpp::exception::PermInvalid, 266
 - qpp::exception::PermMismatchDims, 268
 - qpp::exception::QuditAlreadyMeasured, 323
 - qpp::exception::SizeMismatch, 334
 - qpp::exception::SubsysMismatchDims, 346
 - qpp::exception::TypeMismatch, 353
 - qpp::exception::UndefinedType, 355
 - qpp::exception::Unknown, 357
 - qpp::exception::ZeroSize, 363
- execute
 - qpp::QEngine, 303
 - qpp::QNoisyEngine, 312
- expandout
 - qpp::Gates, 177, 178
- experimental/experimental.h, 380
- expm
 - qpp, 54
- FRED
 - qpp::Bit_circuit, 134
 - qpp::Bit_circuit::Gate_count, 173
 - qpp::Gates, 185
- factors
 - qpp, 54
- Fd
 - qpp::Gates, 179
- fill_Ks_
 - qpp::QuditDepolarizingNoise, 326
- fill_probs_
 - qpp::QuditDepolarizingNoise, 326
- first_
 - qpp::internal::LOManipRange, 208
- flip
 - qpp::Dynamic_bitset, 161
- functions.h, 380
- funm
 - qpp, 55

- GHZ
 - qpp::States, 341
- gate
 - qpp::QCircuit, 283, 284
- gate_count
 - qpp::Bit_circuit, 136
- gate_custom
 - qpp::QCircuit, 284
- gate_fan
 - qpp::QCircuit, 285, 286
- gate_hash_
 - qpp::QCircuit::GateStep, 189
- gate_type_
 - qpp::QCircuit::GateStep, 189
- GateStep
 - qpp::QCircuit::GateStep, 188
- GateType
 - qpp::QCircuit, 274
- Gates
 - qpp::Gates, 176
- gates_
 - qpp::QCircuit, 297
- gates_ip_
 - qpp::QCircuit::iterator::value_type_, 360
- gcd
 - qpp, 55
- gconcurrency
 - qpp, 56
- generated_
 - qpp::NoiseBase, 247
- get
 - qpp::Dynamic_bitset, 162
- get_Ks
 - qpp::NoiseBase, 245
- get_circuit
 - qpp::QEngine, 304
- get_cmat_hash_tbl_
 - qpp::QCircuit, 286
- get_d
 - qpp::NoiseBase, 244
 - qpp::QCircuit, 286
- get_dim_subsys
 - qpp::internal, 125
- get_dit
 - qpp::QEngine, 304
- get_dits
 - qpp::QEngine, 304
- get_duration
 - qpp::Timer, 350
- get_gate_count
 - qpp::QCircuit, 286, 287
- get_gate_depth
 - qpp::QCircuit, 287
- get_gates_
 - qpp::QCircuit, 288
- get_instance
 - qpp::internal::Singleton, 332
- get_last_idx
 - qpp::NoiseBase, 245
- get_last_K
 - qpp::NoiseBase, 245
- get_last_p
 - qpp::NoiseBase, 245
- get_measured
 - qpp::QCircuit, 288
 - qpp::QEngine, 304, 305
- get_measurement_count
 - qpp::QCircuit, 288, 289
- get_measurements_
 - qpp::QCircuit, 289
- get_name
 - qpp::Gates, 180
 - qpp::QCircuit, 289
- get_nc
 - qpp::QCircuit, 289
- get_noise_results
 - qpp::QNoisyEngine, 312
- get_non_measured
 - qpp::QCircuit, 290
 - qpp::QEngine, 305
- get_nop_count
 - qpp::QCircuit, 290
- get_nq
 - qpp::QCircuit, 290
- get_num_subsys
 - qpp::internal, 125
- get_prng
 - qpp::RandomDevices, 329
- get_probs
 - qpp::NoiseBase, 246
 - qpp::QEngine, 305
- get_psi
 - qpp::QEngine, 306
- get_relative_pos_
 - qpp::QEngine, 306
- get_step_count
 - qpp::QCircuit, 290
- get_thread_local_instance
 - qpp::internal::Singleton, 332
- grams
 - qpp, 56, 57
- H
 - qpp::Gates, 185
- hash_combine
 - qpp::internal, 125
- hash_eigen
 - qpp, 58
- heig
 - qpp, 58
- hevals
 - qpp, 59
- hevects
 - qpp, 59
- i_
 - qpp::NoiseBase, 248

- IDisplay
 - qpp::IDisplay, [192](#)
- IJSON
 - qpp::IJSON, [195](#)
- IOManipEigen
 - qpp::internal::IOManipEigen, [201](#)
- IOManipPointer
 - qpp::internal::IOManipPointer, [204](#)
- IOManipRange
 - qpp::internal::IOManipRange, [207](#)
- Id
 - qpp::Gates, [180](#)
- Id2
 - qpp::Gates, [186](#)
- idx
 - qpp, [30](#)
- index_
 - qpp::Dynamic_bitset, [162](#)
- infty
 - qpp, [118](#)
- Init
 - qpp::Init, [197](#)
- input_output.h, [385](#)
- instruments.h, [386](#)
- internal/classes/iomanip.h, [387](#)
- internal/classes/singleton.h, [388](#)
- internal/util.h, [389](#)
- internal::Singleton< const Codes >
 - qpp::Codes, [139](#)
- internal::Singleton< const Gates >
 - qpp::Gates, [185](#)
- internal::Singleton< const Init >
 - qpp::Init, [198](#)
- internal::Singleton< const States >
 - qpp::States, [340](#)
- internal::Singleton< RandomDevices >
 - qpp::RandomDevices, [330](#)
- inverse
 - qpp, [59](#)
- invperm
 - qpp, [60](#)
- ip
 - qpp, [60](#), [61](#)
- ip_
 - qpp::QCircuit::iterator::value_type_, [361](#)
- isprime
 - qpp, [61](#)
- iterator
 - qpp::QCircuit::iterator, [216](#)
- iterator_category
 - qpp::QCircuit::iterator, [215](#)
- jn
 - qpp::States, [338](#)
- ket
 - qpp, [30](#)
- kraus2choi
 - qpp, [61](#)
- kraus2super
 - qpp, [62](#)
- kron
 - qpp, [62–64](#)
- kron2
 - qpp::internal, [125](#)
- kronpow
 - qpp, [64](#)
- Ks_
 - qpp::NoiseBase, [248](#)
- last_
 - qpp::internal::IOManipRange, [208](#)
- lcm
 - qpp, [65](#)
- load
 - qpp, [66](#)
 - qpp::RandomDevices, [329](#)
- loadMATLAB
 - qpp, [66](#), [67](#)
- logdet
 - qpp, [68](#)
- logm
 - qpp, [68](#)
- lognegativity
 - qpp, [69](#)
- MATLAB/matlab.h, [391](#)
- MODMUL
 - qpp::Gates, [180](#)
- marginalX
 - qpp, [69](#)
- marginalY
 - qpp, [71](#)
- mats_hash_
 - qpp::QCircuit::MeasureStep, [238](#)
- maxn
 - qpp, [118](#)
- measure
 - qpp, [71–76](#)
- measure_seq
 - qpp, [76](#), [77](#)
- MeasureStep
 - qpp::QCircuit::MeasureStep, [237](#)
- MeasureType
 - qpp::QCircuit, [275](#)
- measured_
 - qpp::QCircuit, [298](#)
- measurement_count_
 - qpp::QCircuit, [298](#)
- measurement_type_
 - qpp::QCircuit::MeasureStep, [238](#)
- measurements_
 - qpp::QCircuit, [298](#)
- measurements_ip_
 - qpp::QCircuit::iterator::value_type_, [361](#)
- measureV
 - qpp::QCircuit, [291](#)
- measureZ

- qpp::QCircuit, 292
- mes
 - qpp::States, 338
- minus
 - qpp::States, 339
- mket
 - qpp, 77, 78
- modinv
 - qpp, 78
- modmul
 - qpp, 79
- modpow
 - qpp, 79
- mprj
 - qpp, 80
- msg_
 - qpp::exception::Exception, 172
- multiidx2n
 - qpp, 81
 - qpp::internal, 126
- n2multiidx
 - qpp, 81
 - qpp::internal, 126
- N_
 - qpp::Dynamic_bitset, 167
 - qpp::internal::IOManipPointer, 205
- NOT
 - qpp::Bit_circuit, 134
 - qpp::Bit_circuit::Gate_count, 173
- name_
 - qpp::QCircuit, 298
 - qpp::QCircuit::GateStep, 189
 - qpp::QCircuit::MeasureStep, 238
- nc_
 - qpp::QCircuit, 298
- negativity
 - qpp, 82
- noise_
 - qpp::QNoisyEngine, 313
- noise_results_
 - qpp::QNoisyEngine, 313
- noise_type
 - qpp::NoiseBase, 242
- NoiseBase
 - qpp::NoiseBase, 243
- none
 - qpp::Dynamic_bitset, 162
- nop
 - qpp::QCircuit, 292
- norm
 - qpp, 83
- normalize
 - qpp, 83
- nq_
 - qpp::QCircuit, 298
- number_theory.h, 391
- offset_
 - qpp::Dynamic_bitset, 163
- omega
 - qpp, 84
- one
 - qpp::States, 339
- operations.h, 393
- operator!=
 - qpp::Dynamic_bitset, 163
 - qpp::QCircuit::iterator, 216
- operator<<
 - qpp::IDisplay, 193
 - qpp::QCircuit, 295, 296
- operator*
 - qpp::QCircuit::iterator, 217
- operator()
 - qpp::NoiseBase, 246, 247
 - qpp::internal::EqualEigen, 168
 - qpp::internal::HashEigen, 190
- operator++
 - qpp::QCircuit::iterator, 217
- operator-
 - qpp::Dynamic_bitset, 163
- operator=
 - qpp::IDisplay, 193
 - qpp::IJSON, 195
 - qpp::QCircuit::iterator, 217
 - qpp::QCircuit::iterator::value_type_, 360
 - qpp::QEngine, 307
 - qpp::Timer, 350
 - qpp::internal::IOManipPointer, 204
 - qpp::internal::IOManipRange, 207
 - qpp::internal::Singleton, 332
- operator==
 - qpp::Dynamic_bitset, 164
 - qpp::QCircuit::iterator, 218
- operator""_bra
 - qpp::literals, 127
- operator""_i
 - qpp, 84
 - qpp::literals, 127
- operator""_ket
 - qpp::literals, 128
- operator""_prj
 - qpp::literals, 128
- p_
 - qpp::internal::IOManipPointer, 205
- pGHZ
 - qpp::States, 342
- pb00
 - qpp::States, 341
- pb01
 - qpp::States, 341
- pb10
 - qpp::States, 342
- pb11
 - qpp::States, 342
- pi
 - qpp, 118

- plus
 - qpp::States, 339
- pointer
 - qpp::QCircuit::iterator, 215
- powm
 - qpp, 84
- prj
 - qpp, 85
- prng_
 - qpp::RandomDevices, 330
- probs_
 - qpp::NoiseBase, 248
 - qpp::QEngine, 309
- prod
 - qpp, 85, 86
- psi_
 - qpp::QEngine, 309
- ptrace
 - qpp, 86, 87
- ptrace1
 - qpp, 87, 88
- ptrace2
 - qpp, 88, 89
- ptranspose
 - qpp, 89, 90
- pW
 - qpp::States, 342
- px0
 - qpp::States, 342
- px1
 - qpp::States, 342
- py0
 - qpp::States, 343
- py1
 - qpp::States, 343
- pz0
 - qpp::States, 343
- pz1
 - qpp::States, 343
- QCircuit
 - qpp::QCircuit, 275
- QEngine
 - qpp::QCircuit, 297
 - qpp::QEngine, 301, 302
- QFT
 - qpp, 90
 - qpp::QCircuit, 292, 293
- QNoisyEngine
 - qpp::QNoisyEngine, 311
- QPP_UNUSED_
 - qpp.h, 397
- qc_
 - qpp::QCircuit::iterator, 219
 - qpp::QEngine, 309
- qmutualinfo
 - qpp, 91
- qpp, 15
 - absm, 31
 - abssq, 31, 32
 - adjoint, 32
 - anticomm, 33
 - apply, 33–35
 - applyCTRL, 36
 - applyQFT, 37
 - applyTFQ, 38
 - avg, 38
 - bigint, 28
 - bloch2rho, 38
 - bra, 28
 - choi2kraus, 39
 - choi2super, 39
 - chop, 118
 - cmat, 29
 - comm, 40
 - complement, 40
 - compperm, 41
 - concurrence, 41
 - conjugate, 42
 - contrfrac2x, 42
 - convergents, 42, 43
 - cor, 43
 - cosm, 44
 - cov, 44
 - cplx, 29
 - cwise, 45
 - det, 45
 - dirsum, 46, 47
 - dirsumpow, 47
 - disp, 48–50
 - dmat, 29
 - dyn_col_vect, 29
 - dyn_mat, 29
 - dyn_row_vect, 30
 - ee, 118
 - egcd, 50
 - eig, 51
 - entanglement, 51, 52
 - entropy, 52, 53
 - evals, 53
 - evects, 53
 - expm, 54
 - factors, 54
 - funm, 55
 - gcd, 55
 - gconcurrence, 56
 - grams, 56, 57
 - hash_eigen, 58
 - heig, 58
 - hevals, 59
 - hevects, 59
 - idx, 30
 - infty, 118
 - inverse, 59
 - invperm, 60
 - ip, 60, 61
 - isprime, 61

- ket, 30
- kraus2choi, 61
- kraus2super, 62
- kron, 62–64
- kronpow, 64
- lcm, 65
- load, 66
- loadMATLAB, 66, 67
- logdet, 68
- logm, 68
- lognegativity, 69
- marginalX, 69
- marginalY, 71
- maxn, 118
- measure, 71–76
- measure_seq, 76, 77
- mket, 77, 78
- modinv, 78
- modmul, 79
- modpow, 79
- mprj, 80
- multiidx2n, 81
- n2multiidx, 81
- negativity, 82
- norm, 83
- normalize, 83
- omega, 84
- operator""_i, 84
- pi, 118
- powm, 84
- prj, 85
- prod, 85, 86
- ptrace, 86, 87
- ptrace1, 87, 88
- ptrace2, 88, 89
- ptranspose, 89, 90
- QFT, 90
- qmutualinfo, 91
- rand, 92–94
- randH, 94
- randidx, 95
- randket, 95
- randkraus, 95
- randn, 96, 97
- randperm, 98
- randprime, 98
- randprob, 99
- randrho, 99
- randU, 99
- randV, 100
- renyi, 100, 101
- reshape, 101
- rho2bloch, 102
- rho2pure, 102
- save, 103
- saveMATLAB, 103, 104
- schatten, 104
- schmidtA, 105
- schmidtB, 105, 106
- schmidtcoeffs, 106, 107
- schmidtprobs, 107, 108
- sigma, 108
- sinm, 109
- spectralpowm, 109
- sqrtn, 110
- sum, 110, 111
- super2choi, 111
- svals, 112
- svd, 112
- svdU, 112
- svdV, 113
- syspermute, 113, 114
- TFQ, 114
- to_void, 30
- trace, 114
- transpose, 115
- tsallis, 115, 116
- uniform, 116
- var, 117
- x2contfrac, 117
- qpp.h, 395
 - QPP_UNUSED_, 397
- qpp::Bit_circuit, 131
 - Bit_circuit, 133
 - CNOT, 133
 - Dynamic_bitset, 134
 - FRED, 134
 - gate_count, 136
 - NOT, 134
 - reset, 134
 - SWAP, 135
 - TOF, 135
 - X, 135
- qpp::Bit_circuit::Gate_count, 172
 - CNOT, 172
 - FRED, 173
 - NOT, 173
 - SWAP, 173
 - TOF, 173
 - X, 173
- qpp::Codes, 136
 - ~Codes, 138
 - Codes, 138
 - codeword, 138
 - internal::Singleton< const Codes >, 139
 - Type, 137
- qpp::Dynamic_bitset, 157
 - ~Dynamic_bitset, 160
 - all, 160
 - any, 160
 - count, 160
 - data, 160
 - display, 161
 - Dynamic_bitset, 159
 - flip, 161
 - get, 162

- index_, 162
- N_, 167
- none, 162
- offset_, 163
- operator!=, 163
- operator-, 163
- operator==, 164
- rand, 164, 165
- reset, 165
- set, 165, 166
- size, 166
- storage_size, 166
- storage_size_, 167
- storage_type, 159
- to_string, 166
- v_, 167
- value_type, 159
- qpp::Gates, 174
 - ~Gates, 176
 - CNOTba, 185
 - CNOT, 185
 - CTRL, 177
 - CZ, 185
 - expandout, 177, 178
 - FRED, 185
 - Fd, 179
 - Gates, 176
 - get_name, 180
 - H, 185
 - Id, 180
 - Id2, 186
 - internal::Singleton< const Gates >, 185
 - MODMUL, 180
 - Rn, 181
 - RX, 181
 - RY, 182
 - RZ, 182
 - S, 186
 - SWAPd, 182
 - SWAP, 186
 - T, 186
 - TOF, 186
 - X, 186
 - Xd, 184
 - Y, 187
 - Z, 187
 - Zd, 184
- qpp::IDisplay, 191
 - ~IDisplay, 192
 - display, 193
 - IDisplay, 192
 - operator<<, 193
 - operator=, 193
- qpp::IJSON, 194
 - ~IJSON, 195
 - IJSON, 195
 - operator=, 195
 - to_JSON, 196
- qpp::Init, 196
 - ~Init, 197
 - Init, 197
 - internal::Singleton< const Init >, 198
- qpp::NoiseBase
 - ~NoiseBase, 243
 - compute_probs_, 244
 - compute_state_, 244
 - d_, 247
 - generated_, 247
 - get_Ks, 245
 - get_d, 244
 - get_last_idx, 245
 - get_last_K, 245
 - get_last_p, 245
 - get_probs, 246
 - i_, 248
 - Ks_, 248
 - noise_type, 242
 - NoiseBase, 243
 - operator(), 246, 247
 - probs_, 248
- qpp::NoiseBase< T >, 241
- qpp::NoiseType, 248
- qpp::NoiseType::StateDependent, 335
- qpp::NoiseType::StateIndependent, 335
- qpp::QCCircuit, 269
 - ~QCCircuit, 276
 - add_hash_, 276
 - begin, 276
 - cCTRL_custom, 279
 - cCTRL, 277, 278
 - CTRL_custom, 282
 - CTRL, 280, 281
 - cbegin, 277
 - cend, 279
 - cmat_hash_tbl_, 297
 - const_iterator, 274
 - count_, 297
 - d_, 297
 - depth_, 297
 - display, 282
 - end, 282, 283
 - gate, 283, 284
 - gate_custom, 284
 - gate_fan, 285, 286
 - GateType, 274
 - gates_, 297
 - get_cmat_hash_tbl_, 286
 - get_d, 286
 - get_gate_count, 286, 287
 - get_gate_depth, 287
 - get_gates_, 288
 - get_measured, 288
 - get_measurement_count, 288, 289
 - get_measurements_, 289
 - get_name, 289
 - get_nc, 289

- get_non_measured, 290
- get_nop_count, 290
- get_nq, 290
- get_step_count, 290
- MeasureType, 275
- measured_, 298
- measurement_count_, 298
- measurements_, 298
- measureV, 291
- measureZ, 292
- name_, 298
- nc_, 298
- nop, 292
- nq_, 298
- operator<<, 295, 296
- QCircuit, 275
- QEngine, 297
- QFT, 292, 293
- step_types_, 299
- StepType, 275
- TFQ, 293, 294
- to_JSON, 295
- qpp::QCircuit::GateStep, 187
 - ctrl_, 189
 - gate_hash_, 189
 - gate_type_, 189
 - GateStep, 188
 - name_, 189
 - target_, 189
- qpp::QCircuit::MeasureStep, 236
 - c_reg_, 238
 - mats_hash_, 238
 - MeasureStep, 237
 - measurement_type_, 238
 - name_, 238
 - target_, 238
- qpp::QCircuit::iterator, 214
 - difference_type, 215
 - elem_, 219
 - iterator, 216
 - iterator_category, 215
 - operator!=, 216
 - operator*, 217
 - operator++, 217
 - operator=, 217
 - operator==, 218
 - pointer, 215
 - qc_, 219
 - reference, 216
 - set_begin_, 218
 - set_end_, 218
 - value_type, 216
- qpp::QCircuit::iterator::value_type_, 358
 - display, 360
 - gates_ip_, 360
 - ip_, 361
 - measurements_ip_, 361
 - operator=, 360
 - type_, 361
 - value_type_, 359, 360
 - value_type_qc_, 361
- qpp::QEngine, 299
 - ~QEngine, 302
 - display, 303
 - dits_, 309
 - execute, 303
 - get_circuit, 304
 - get_dit, 304
 - get_dits, 304
 - get_measured, 304, 305
 - get_non_measured, 305
 - get_probs, 305
 - get_psi, 306
 - get_relative_pos_, 306
 - operator=, 307
 - probs_, 309
 - psi_, 309
 - QEngine, 301, 302
 - qc_, 309
 - reset, 307
 - set_dit, 307
 - set_measured_, 307
 - set_psi, 308
 - subsys_, 309
 - to_JSON, 308
- qpp::QNoisyEngine
 - execute, 312
 - get_noise_results, 312
 - noise_, 313
 - noise_results_, 313
 - QNoisyEngine, 311
- qpp::QNoisyEngine< NoiseModel >, 310
- qpp::QubitAmplitudeDampingNoise, 313
 - QubitAmplitudeDampingNoise, 314
- qpp::QubitBitFlipNoise, 315
 - QubitBitFlipNoise, 316
- qpp::QubitBitPhaseFlipNoise, 316
 - QubitBitPhaseFlipNoise, 317
- qpp::QubitDepolarizingNoise, 318
 - QubitDepolarizingNoise, 319
- qpp::QubitPhaseDampingNoise, 319
 - QubitPhaseDampingNoise, 320
- qpp::QubitPhaseFlipNoise, 321
 - QubitPhaseFlipNoise, 322
- qpp::QuditDepolarizingNoise, 324
 - fill_Ks_, 326
 - fill_probs_, 326
 - QuditDepolarizingNoise, 325
- qpp::RandomDevices, 327
 - ~RandomDevices, 328
 - get_prng, 329
 - internal::Singleton< RandomDevices >, 330
 - load, 329
 - prng_, 330
 - RandomDevices, 328
 - rd_, 330

- save, 329
- qpp::States, 335
 - ~States, 338
 - b00, 340
 - b01, 341
 - b10, 341
 - b11, 341
 - GHZ, 341
 - internal::Singleton< const States >, 340
 - jn, 338
 - mes, 338
 - minus, 339
 - one, 339
 - pGHZ, 342
 - pb00, 341
 - pb01, 341
 - pb10, 342
 - pb11, 342
 - plus, 339
 - pW, 342
 - px0, 342
 - px1, 342
 - py0, 343
 - py1, 343
 - pz0, 343
 - pz1, 343
 - States, 338
 - W, 343
 - x0, 343
 - x1, 344
 - y0, 344
 - y1, 344
 - z0, 344
 - z1, 344
 - zero, 340
- qpp::Timer
 - ~Timer, 349
 - display, 349
 - end_, 351
 - get_duration, 350
 - operator=, 350
 - start_, 351
 - tic, 350
 - tics, 351
 - Timer, 348, 349
 - toc, 351
- qpp::Timer< T, CLOCK_T >, 347
- qpp::exception, 118
- qpp::exception::CustomException, 139
 - CustomException, 140
 - type_description, 141
 - what_, 141
- qpp::exception::DimsInvalid, 142
 - Exception, 143
 - type_description, 143
- qpp::exception::DimsMismatchCvector, 144
 - Exception, 145
 - type_description, 145
- qpp::exception::DimsMismatchMatrix, 146
 - Exception, 147
 - type_description, 147
- qpp::exception::DimsMismatchRvector, 148
 - Exception, 149
 - type_description, 149
- qpp::exception::DimsMismatchVector, 150
 - Exception, 151
 - type_description, 151
- qpp::exception::DimsNotEqual, 152
 - Exception, 153
 - type_description, 153
- qpp::exception::Duplicates, 155
 - Exception, 156
 - type_description, 156
- qpp::exception::Exception, 169
 - Exception, 171
 - msg_, 172
 - type_description, 171
 - what, 171
 - where_, 172
- qpp::exception::InvalidIterator, 198
 - Exception, 199
 - type_description, 200
- qpp::exception::MatrixMismatchSubsys, 220
 - Exception, 221
 - type_description, 222
- qpp::exception::MatrixNotCvector, 222
 - Exception, 223
 - type_description, 224
- qpp::exception::MatrixNotRvector, 224
 - Exception, 225
 - type_description, 226
- qpp::exception::MatrixNotSquare, 226
 - Exception, 227
 - type_description, 228
- qpp::exception::MatrixNotSquareNorCvector, 228
 - Exception, 229
 - type_description, 230
- qpp::exception::MatrixNotSquareNorRvector, 230
 - Exception, 231
 - type_description, 232
- qpp::exception::MatrixNotSquareNorVector, 232
 - Exception, 233
 - type_description, 234
- qpp::exception::MatrixNotVector, 234
 - Exception, 235
 - type_description, 236
- qpp::exception::NoCodeword, 239
 - Exception, 240
 - type_description, 240
- qpp::exception::NotBipartite, 249
 - Exception, 250
 - type_description, 251
- qpp::exception::NotImplemented, 251
 - Exception, 252
 - type_description, 253
- qpp::exception::NotQubitCvector, 253

- Exception, 254
- type_description, 255
- qpp::exception::NotQubitMatrix, 255
 - Exception, 256
 - type_description, 257
- qpp::exception::NotQubitRvector, 257
 - Exception, 258
 - type_description, 259
- qpp::exception::NotQubitSubsys, 259
 - Exception, 260
 - type_description, 261
- qpp::exception::NotQubitVector, 261
 - Exception, 262
 - type_description, 263
- qpp::exception::OutOfRange, 263
 - Exception, 264
 - type_description, 265
- qpp::exception::PermInvalid, 265
 - Exception, 266
 - type_description, 267
- qpp::exception::PermMismatchDims, 267
 - Exception, 268
 - type_description, 269
- qpp::exception::QuditAlreadyMeasured, 322
 - Exception, 323
 - type_description, 324
- qpp::exception::SizeMismatch, 333
 - Exception, 334
 - type_description, 334
- qpp::exception::SubsysMismatchDims, 345
 - Exception, 346
 - type_description, 346
- qpp::exception::TypeMismatch, 352
 - Exception, 353
 - type_description, 354
- qpp::exception::UndefinedType, 354
 - Exception, 355
 - type_description, 356
- qpp::exception::Unknown, 356
 - Exception, 357
 - type_description, 358
- qpp::exception::ZeroSize, 362
 - Exception, 363
 - type_description, 363
- qpp::experimental, 120
- qpp::internal, 120
 - check_cvector, 122
 - check_dims, 122
 - check_dims_match_cvect, 122
 - check_dims_match_mat, 122
 - check_dims_match_rvect, 122
 - check_eq_dims, 123
 - check_matching_sizes, 123
 - check_no_duplicates, 123
 - check_nonzero_size, 123
 - check_perm, 123
 - check_qubit_cvector, 123
 - check_qubit_matrix, 124
 - check_qubit_rvector, 124
 - check_qubit_vector, 124
 - check_rvector, 124
 - check_square_mat, 124
 - check_subsys_match_dims, 124
 - check_vector, 125
 - dirsum2, 125
 - get_dim_subsys, 125
 - get_num_subsys, 125
 - hash_combine, 125
 - kron2, 125
 - multiidx2n, 126
 - n2multiidx, 126
 - variadic_vector_emplace, 126
- qpp::internal::Display_Impl_, 154
 - display_impl_, 154
- qpp::internal::EqualEigen, 168
 - operator(), 168
- qpp::internal::HashEigen, 190
 - operator(), 190
- qpp::internal::IOManipEigen, 200
 - A_, 202
 - chop_, 202
 - display, 202
 - IOManipEigen, 201
- qpp::internal::IOManipPointer
 - display, 204
 - end_, 205
 - IOManipPointer, 204
 - N_, 205
 - operator=, 204
 - p_, 205
 - separator_, 205
 - start_, 205
- qpp::internal::IOManipPointer< PointerType >, 203
- qpp::internal::IOManipRange
 - display, 207
 - end_, 208
 - first_, 208
 - IOManipRange, 207
 - last_, 208
 - operator=, 207
 - separator_, 208
 - start_, 208
- qpp::internal::IOManipRange< InputIterator >, 206
- qpp::internal::Singleton
 - ~Singleton, 332
 - get_instance, 332
 - get_thread_local_instance, 332
 - operator=, 332
 - Singleton, 331, 332
- qpp::internal::Singleton< T >, 330
- qpp::is_complex< std::complex< T > >, 210
- qpp::is_complex< T >, 209
- qpp::is_iterable< T, to_void< decltype(std::declval< T >().begin()), decltype(std::declval< T >().begin()), decltype(std::declval< T >().begin())> >, 212

- qpp::is_iterable< T, typename >, 211
- qpp::is_matrix_expression< Derived >, 213
- qpp::literals, 127
 - operator""_bra, 127
 - operator""_i, 127
 - operator""_ket, 128
 - operator""_prj, 128
- qpp::make_void
 - type, 220
- qpp::make_void< Ts >, 219
- QubitAmplitudeDampingNoise
 - qpp::QubitAmplitudeDampingNoise, 314
- QubitBitFlipNoise
 - qpp::QubitBitFlipNoise, 316
- QubitBitPhaseFlipNoise
 - qpp::QubitBitPhaseFlipNoise, 317
- QubitDepolarizingNoise
 - qpp::QubitDepolarizingNoise, 319
- QubitPhaseDampingNoise
 - qpp::QubitPhaseDampingNoise, 320
- QubitPhaseFlipNoise
 - qpp::QubitPhaseFlipNoise, 322
- QuditDepolarizingNoise
 - qpp::QuditDepolarizingNoise, 325
- rand
 - qpp, 92–94
 - qpp::Dynamic_bitset, 164, 165
- randH
 - qpp, 94
- randidx
 - qpp, 95
- randket
 - qpp, 95
- randkraus
 - qpp, 95
- randn
 - qpp, 96, 97
- random.h, 397
- RandomDevices
 - qpp::RandomDevices, 328
- randperm
 - qpp, 98
- randprime
 - qpp, 98
- randprob
 - qpp, 99
- randrho
 - qpp, 99
- randU
 - qpp, 99
- randV
 - qpp, 100
- rd_
 - qpp::RandomDevices, 330
- reference
 - qpp::QCircuit::iterator, 216
- renyi
 - qpp, 100, 101
- reset
 - qpp::Bit_circuit, 134
 - qpp::Dynamic_bitset, 165
 - qpp::QEngine, 307
- reshape
 - qpp, 101
- rho2bloch
 - qpp, 102
- rho2pure
 - qpp, 102
- Rn
 - qpp::Gates, 181
- RX
 - qpp::Gates, 181
- RY
 - qpp::Gates, 182
- RZ
 - qpp::Gates, 182
- S
 - qpp::Gates, 186
- SWAPd
 - qpp::Gates, 182
- SWAP
 - qpp::Bit_circuit, 135
 - qpp::Bit_circuit::Gate_count, 173
 - qpp::Gates, 186
- save
 - qpp, 103
 - qpp::RandomDevices, 329
- saveMATLAB
 - qpp, 103, 104
- schatten
 - qpp, 104
- schmidtA
 - qpp, 105
- schmidtB
 - qpp, 105, 106
- schmidtcoeffs
 - qpp, 106, 107
- schmidtprobs
 - qpp, 107, 108
- separator_
 - qpp::internal::IOManipPointer, 205
 - qpp::internal::IOManipRange, 208
- set
 - qpp::Dynamic_bitset, 165, 166
- set_begin_
 - qpp::QCircuit::iterator, 218
- set_dit
 - qpp::QEngine, 307
- set_end_
 - qpp::QCircuit::iterator, 218
- set_measured_
 - qpp::QEngine, 307
- set_psi
 - qpp::QEngine, 308
- sigma
 - qpp, 108

- Singleton
 - qpp::internal::Singleton, [331](#), [332](#)
- sinm
 - qpp, [109](#)
- size
 - qpp::Dynamic_bitset, [166](#)
- spectralpowm
 - qpp, [109](#)
- sqrtn
 - qpp, [110](#)
- start_
 - qpp::Timer, [351](#)
 - qpp::internal::LOManipPointer, [205](#)
 - qpp::internal::LOManipRange, [208](#)
- States
 - qpp::States, [338](#)
- statistics.h, [399](#)
- step_types_
 - qpp::QCircuit, [299](#)
- StepType
 - qpp::QCircuit, [275](#)
- storage_size
 - qpp::Dynamic_bitset, [166](#)
- storage_size_
 - qpp::Dynamic_bitset, [167](#)
- storage_type
 - qpp::Dynamic_bitset, [159](#)
- subsys_
 - qpp::QEngine, [309](#)
- sum
 - qpp, [110](#), [111](#)
- super2choi
 - qpp, [111](#)
- svals
 - qpp, [112](#)
- svd
 - qpp, [112](#)
- svdU
 - qpp, [112](#)
- svdV
 - qpp, [113](#)
- syspermute
 - qpp, [113](#), [114](#)
- T
 - qpp::Gates, [186](#)
- TFQ
 - qpp, [114](#)
 - qpp::QCircuit, [293](#), [294](#)
- TOF
 - qpp::Bit_circuit, [135](#)
 - qpp::Bit_circuit::Gate_count, [173](#)
 - qpp::Gates, [186](#)
- target_
 - qpp::QCircuit::GateStep, [189](#)
 - qpp::QCircuit::MeasureStep, [238](#)
- tic
 - qpp::Timer, [350](#)
- tics
 - qpp::Timer, [351](#)
- Timer
 - qpp::Timer, [348](#), [349](#)
- to_JSON
 - qpp::IJSON, [196](#)
 - qpp::QCircuit, [295](#)
 - qpp::QEngine, [308](#)
- to_string
 - qpp::Dynamic_bitset, [166](#)
- to_void
 - qpp, [30](#)
- toc
 - qpp::Timer, [351](#)
- trace
 - qpp, [114](#)
- traits.h, [400](#)
- transpose
 - qpp, [115](#)
- tsallis
 - qpp, [115](#), [116](#)
- Type
 - qpp::Codes, [137](#)
- type
 - qpp::make_void, [220](#)
- type_
 - qpp::QCircuit::iterator::value_type_, [361](#)
- type_description
 - qpp::exception::CustomException, [141](#)
 - qpp::exception::DimsInvalid, [143](#)
 - qpp::exception::DimsMismatchCvector, [145](#)
 - qpp::exception::DimsMismatchMatrix, [147](#)
 - qpp::exception::DimsMismatchRvector, [149](#)
 - qpp::exception::DimsMismatchVector, [151](#)
 - qpp::exception::DimsNotEqual, [153](#)
 - qpp::exception::Duplicates, [156](#)
 - qpp::exception::Exception, [171](#)
 - qpp::exception::InvalidIterator, [200](#)
 - qpp::exception::MatrixMismatchSubsys, [222](#)
 - qpp::exception::MatrixNotCvector, [224](#)
 - qpp::exception::MatrixNotRvector, [226](#)
 - qpp::exception::MatrixNotSquare, [228](#)
 - qpp::exception::MatrixNotSquareNorCvector, [230](#)
 - qpp::exception::MatrixNotSquareNorRvector, [232](#)
 - qpp::exception::MatrixNotSquareNorVector, [234](#)
 - qpp::exception::MatrixNotVector, [236](#)
 - qpp::exception::NoCodeword, [240](#)
 - qpp::exception::NotBipartite, [251](#)
 - qpp::exception::NotImplemented, [253](#)
 - qpp::exception::NotQubitCvector, [255](#)
 - qpp::exception::NotQubitMatrix, [257](#)
 - qpp::exception::NotQubitRvector, [259](#)
 - qpp::exception::NotQubitSubsys, [261](#)
 - qpp::exception::NotQubitVector, [263](#)
 - qpp::exception::OutOfRange, [265](#)
 - qpp::exception::PermInvalid, [267](#)
 - qpp::exception::PermMismatchDims, [269](#)
 - qpp::exception::QuditAlreadyMeasured, [324](#)
 - qpp::exception::SizeMismatch, [334](#)

- qpp::exception::SubsysMismatchDims, [346](#)
 - qpp::exception::TypeMismatch, [354](#)
 - qpp::exception::UndefinedType, [356](#)
 - qpp::exception::Unknown, [358](#)
 - qpp::exception::ZeroSize, [363](#)
- types.h, [401](#)
- uniform
 - qpp, [116](#)
- v_
 - qpp::Dynamic_bitset, [167](#)
- value_type
 - qpp::Dynamic_bitset, [159](#)
 - qpp::QCircuit::iterator, [216](#)
- value_type_
 - qpp::QCircuit::iterator::value_type_, [359](#), [360](#)
- value_type_qc_
 - qpp::QCircuit::iterator::value_type_, [361](#)
- var
 - qpp, [117](#)
- variadic_vector_emplace
 - qpp::internal, [126](#)
- W
 - qpp::States, [343](#)
- what
 - qpp::exception::Exception, [171](#)
- what_
 - qpp::exception::CustomException, [141](#)
- where_
 - qpp::exception::Exception, [172](#)
- X
 - qpp::Bit_circuit, [135](#)
 - qpp::Bit_circuit::Gate_count, [173](#)
 - qpp::Gates, [186](#)
- x0
 - qpp::States, [343](#)
- x1
 - qpp::States, [344](#)
- x2contfrac
 - qpp, [117](#)
- Xd
 - qpp::Gates, [184](#)
- Y
 - qpp::Gates, [187](#)
- y0
 - qpp::States, [344](#)
- y1
 - qpp::States, [344](#)
- Z
 - qpp::Gates, [187](#)
- z0
 - qpp::States, [344](#)
- z1
 - qpp::States, [344](#)
- Zd
 - qpp::Gates, [184](#)
 - zero
 - qpp::States, [340](#)