

Quantum++  
v0.8.9-devel

Generated by Doxygen 1.8.9.1

Mon Oct 10 2016 01:01:07



# Contents

<b>1</b>	<b>Quantum++</b>	<b>1</b>
<b>2</b>	<b>Namespace Index</b>	<b>5</b>
2.1	Namespace List . . . . .	5
<b>3</b>	<b>Hierarchical Index</b>	<b>7</b>
3.1	Class Hierarchy . . . . .	7
<b>4</b>	<b>Class Index</b>	<b>9</b>
4.1	Class List . . . . .	9
<b>5</b>	<b>File Index</b>	<b>11</b>
5.1	File List . . . . .	11
<b>6</b>	<b>Namespace Documentation</b>	<b>13</b>
6.1	qpp Namespace Reference . . . . .	13
6.1.1	Detailed Description . . . . .	25
6.1.2	Typedef Documentation . . . . .	25
6.1.2.1	bigint . . . . .	25
6.1.2.2	bra . . . . .	25
6.1.2.3	cmat . . . . .	25
6.1.2.4	cplx . . . . .	25
6.1.2.5	dmat . . . . .	25
6.1.2.6	dyn_col_vect . . . . .	25
6.1.2.7	dyn_mat . . . . .	25
6.1.2.8	dyn_row_vect . . . . .	26
6.1.2.9	idx . . . . .	26
6.1.2.10	ket . . . . .	26
6.1.2.11	to_void . . . . .	26
6.1.3	Function Documentation . . . . .	26
6.1.3.1	absm . . . . .	26
6.1.3.2	abssq . . . . .	26
6.1.3.3	abssq . . . . .	26

6.1.3.4	abssq	27
6.1.3.5	adjoint	27
6.1.3.6	anticomm	27
6.1.3.7	apply	28
6.1.3.8	apply	28
6.1.3.9	apply	28
6.1.3.10	apply	29
6.1.3.11	apply	30
6.1.3.12	applyCTRL	30
6.1.3.13	applyCTRL	31
6.1.3.14	avg	31
6.1.3.15	bloch2rho	31
6.1.3.16	choi2kraus	32
6.1.3.17	choi2super	32
6.1.3.18	comm	32
6.1.3.19	complement	32
6.1.3.20	compperm	33
6.1.3.21	concurrence	33
6.1.3.22	conjugate	33
6.1.3.23	contfrac2x	33
6.1.3.24	contfrac2x	34
6.1.3.25	cor	34
6.1.3.26	cosm	34
6.1.3.27	cov	34
6.1.3.28	cwise	35
6.1.3.29	det	35
6.1.3.30	dirsum	35
6.1.3.31	dirsum	36
6.1.3.32	dirsum	36
6.1.3.33	dirsum	36
6.1.3.34	dirsumpow	37
6.1.3.35	disp	37
6.1.3.36	disp	37
6.1.3.37	disp	37
6.1.3.38	disp	38
6.1.3.39	disp	38
6.1.3.40	egcd	38
6.1.3.41	eig	39
6.1.3.42	entanglement	39
6.1.3.43	entropy	39

6.1.3.44	entropy	40
6.1.3.45	evals	40
6.1.3.46	evects	40
6.1.3.47	expm	40
6.1.3.48	factors	41
6.1.3.49	funm	41
6.1.3.50	gcd	41
6.1.3.51	gcd	42
6.1.3.52	gconcurrency	42
6.1.3.53	grams	42
6.1.3.54	grams	42
6.1.3.55	grams	43
6.1.3.56	heig	43
6.1.3.57	hevals	43
6.1.3.58	hevects	44
6.1.3.59	inverse	44
6.1.3.60	invperm	44
6.1.3.61	ip	44
6.1.3.62	ip	45
6.1.3.63	isprime	45
6.1.3.64	kraus2choi	45
6.1.3.65	kraus2super	46
6.1.3.66	kron	46
6.1.3.67	kron	46
6.1.3.68	kron	47
6.1.3.69	kron	47
6.1.3.70	kronpow	47
6.1.3.71	lcm	48
6.1.3.72	lcm	48
6.1.3.73	load	48
6.1.3.74	loadMATLABmatrix	49
6.1.3.75	loadMATLABmatrix	49
6.1.3.76	loadMATLABmatrix	49
6.1.3.77	logdet	50
6.1.3.78	logm	50
6.1.3.79	lognegativity	50
6.1.3.80	marginalX	50
6.1.3.81	marginalY	51
6.1.3.82	measure	51
6.1.3.83	measure	51

6.1.3.84	measure	51
6.1.3.85	measure	52
6.1.3.86	measure	52
6.1.3.87	measure	53
6.1.3.88	measure	53
6.1.3.89	measure	54
6.1.3.90	measure	54
6.1.3.91	measure_seq	55
6.1.3.92	measure_seq	55
6.1.3.93	mket	56
6.1.3.94	mket	56
6.1.3.95	modinv	56
6.1.3.96	modmul	56
6.1.3.97	modpow	57
6.1.3.98	mprj	57
6.1.3.99	mprj	57
6.1.3.100	multiidx2n	58
6.1.3.101	n2multiidx	58
6.1.3.102	negativity	58
6.1.3.103	norm	59
6.1.3.104	omega	59
6.1.3.105	operator""_i	59
6.1.3.106	operator""_i	59
6.1.3.107	powm	59
6.1.3.108	prj	60
6.1.3.109	prod	60
6.1.3.110	prod	60
6.1.3.111	prod	60
6.1.3.112	ptrace	61
6.1.3.113	ptrace	61
6.1.3.114	ptrace1	61
6.1.3.115	ptrace2	63
6.1.3.116	ptranspose	63
6.1.3.117	ptranspose	63
6.1.3.118	qmutualinfo	64
6.1.3.119	qmutualinfo	64
6.1.3.120	rand	64
6.1.3.121	rand	65
6.1.3.122	rand	66
6.1.3.123	rand	66

6.1.3.124 rand	66
6.1.3.125 randH	67
6.1.3.126 randidx	67
6.1.3.127 randket	67
6.1.3.128 randkraus	67
6.1.3.129 randn	68
6.1.3.130 randn	68
6.1.3.131 randn	68
6.1.3.132 randn	69
6.1.3.133 randperm	69
6.1.3.134 randprime	69
6.1.3.135 randrho	69
6.1.3.136 randU	70
6.1.3.137 randV	70
6.1.3.138 renyi	70
6.1.3.139 renyi	70
6.1.3.140 reshape	71
6.1.3.141 rho2bloch	71
6.1.3.142 rho2pure	71
6.1.3.143 save	72
6.1.3.144 saveMATLABmatrix	72
6.1.3.145 saveMATLABmatrix	72
6.1.3.146 saveMATLABmatrix	72
6.1.3.147 schatten	73
6.1.3.148 schmidtA	73
6.1.3.149 schmidtB	73
6.1.3.150 schmidtcoeffs	73
6.1.3.151 schmidtprobs	74
6.1.3.152 sigma	74
6.1.3.153 sinm	74
6.1.3.154 spectralpowm	75
6.1.3.155 sqrtm	75
6.1.3.156 sum	75
6.1.3.157 sum	75
6.1.3.158 sum	76
6.1.3.159 super2choi	76
6.1.3.160 svals	76
6.1.3.161 svd	76
6.1.3.162 svdU	77
6.1.3.163 svdV	77

6.1.3.164	syspermute	77
6.1.3.165	syspermute	77
6.1.3.166	trace	78
6.1.3.167	transpose	78
6.1.3.168	tsallis	78
6.1.3.169	tsallis	78
6.1.3.170	uniform	79
6.1.3.171	var	79
6.1.3.172	x2contfrac	79
6.1.4	Variable Documentation	79
6.1.4.1	chop	79
6.1.4.2	ee	80
6.1.4.3	eps	80
6.1.4.4	infty	80
6.1.4.5	maxn	80
6.1.4.6	pi	80
6.2	qpp::experimental Namespace Reference	80
6.2.1	Detailed Description	80
6.3	qpp::internal Namespace Reference	80
6.3.1	Detailed Description	81
6.3.2	Function Documentation	82
6.3.2.1	check_cvector	82
6.3.2.2	check_dims	82
6.3.2.3	check_dims_match_cvect	82
6.3.2.4	check_dims_match_mat	82
6.3.2.5	check_dims_match_rvect	82
6.3.2.6	check_eq_dims	82
6.3.2.7	check_matching_sizes	82
6.3.2.8	check_nonzero_size	82
6.3.2.9	check_perm	82
6.3.2.10	check_qubit_cvector	82
6.3.2.11	check_qubit_matrix	82
6.3.2.12	check_qubit_rvector	82
6.3.2.13	check_qubit_vector	82
6.3.2.14	check_rvector	82
6.3.2.15	check_square_mat	82
6.3.2.16	check_subsys_match_dims	82
6.3.2.17	check_vector	82
6.3.2.18	dirsum2	82
6.3.2.19	get_dim_subsys	82



6.3.2.20	<a href="#">get_num_subsys</a>	82
6.3.2.21	<a href="#">kron2</a>	82
6.3.2.22	<a href="#">multiidx2n</a>	82
6.3.2.23	<a href="#">n2multiidx</a>	83
6.3.2.24	<a href="#">variadic_vector_emplace</a>	83
6.3.2.25	<a href="#">variadic_vector_emplace</a>	83
6.4	<a href="#">qpp::internal::details_ Namespace Reference</a>	83
<b>7</b>	<b>Class Documentation</b>	<b>85</b>
7.1	<a href="#">qpp::Codes Class Reference</a>	85
7.1.1	<a href="#">Detailed Description</a>	86
7.1.2	<a href="#">Member Enumeration Documentation</a>	86
7.1.2.1	<a href="#">Type</a>	86
7.1.3	<a href="#">Constructor &amp; Destructor Documentation</a>	86
7.1.3.1	<a href="#">Codes</a>	86
7.1.3.2	<a href="#">~Codes</a>	86
7.1.4	<a href="#">Member Function Documentation</a>	87
7.1.4.1	<a href="#">codeword</a>	87
7.1.5	<a href="#">Friends And Related Function Documentation</a>	87
7.1.5.1	<a href="#">internal::Singleton&lt; const Codes &gt;</a>	87
7.2	<a href="#">qpp::internal::details_::Display_Impl_ Struct Reference</a>	87
7.2.1	<a href="#">Member Function Documentation</a>	88
7.2.1.1	<a href="#">display_impl_</a>	88
7.3	<a href="#">qpp::Exception Class Reference</a>	88
7.3.1	<a href="#">Detailed Description</a>	89
7.3.2	<a href="#">Member Enumeration Documentation</a>	89
7.3.2.1	<a href="#">Type</a>	89
7.3.3	<a href="#">Constructor &amp; Destructor Documentation</a>	90
7.3.3.1	<a href="#">Exception</a>	90
7.3.3.2	<a href="#">Exception</a>	91
7.3.4	<a href="#">Member Function Documentation</a>	91
7.3.4.1	<a href="#">construct_exception_msg_</a>	91
7.3.4.2	<a href="#">what</a>	91
7.3.5	<a href="#">Member Data Documentation</a>	91
7.3.5.1	<a href="#">custom_</a>	91
7.3.5.2	<a href="#">msg_</a>	91
7.3.5.3	<a href="#">type_</a>	91
7.3.5.4	<a href="#">where_</a>	91
7.4	<a href="#">qpp::Gates Class Reference</a>	91
7.4.1	<a href="#">Detailed Description</a>	93

7.4.2	Constructor & Destructor Documentation . . . . .	94
7.4.2.1	Gates . . . . .	94
7.4.2.2	~Gates . . . . .	94
7.4.3	Member Function Documentation . . . . .	94
7.4.3.1	CTRL . . . . .	94
7.4.3.2	expandout . . . . .	94
7.4.3.3	Fd . . . . .	95
7.4.3.4	Id . . . . .	95
7.4.3.5	Rn . . . . .	95
7.4.3.6	Xd . . . . .	96
7.4.3.7	Zd . . . . .	96
7.4.4	Friends And Related Function Documentation . . . . .	96
7.4.4.1	internal::Singleton< const Gates > . . . . .	96
7.4.5	Member Data Documentation . . . . .	96
7.4.5.1	CNOT . . . . .	96
7.4.5.2	CNOTba . . . . .	96
7.4.5.3	CZ . . . . .	96
7.4.5.4	FRED . . . . .	96
7.4.5.5	H . . . . .	97
7.4.5.6	Id2 . . . . .	97
7.4.5.7	S . . . . .	97
7.4.5.8	SWAP . . . . .	97
7.4.5.9	T . . . . .	97
7.4.5.10	TOF . . . . .	97
7.4.5.11	X . . . . .	97
7.4.5.12	Y . . . . .	97
7.4.5.13	Z . . . . .	97
7.5	qpp::IDisplay Class Reference . . . . .	97
7.5.1	Detailed Description . . . . .	99
7.5.2	Constructor & Destructor Documentation . . . . .	99
7.5.2.1	IDisplay . . . . .	99
7.5.2.2	IDisplay . . . . .	99
7.5.2.3	IDisplay . . . . .	99
7.5.2.4	~IDisplay . . . . .	99
7.5.3	Member Function Documentation . . . . .	99
7.5.3.1	display . . . . .	99
7.5.3.2	operator= . . . . .	99
7.5.3.3	operator= . . . . .	99
7.5.4	Friends And Related Function Documentation . . . . .	99
7.5.4.1	operator<< . . . . .	99

7.6	qpp::Init Class Reference . . . . .	100
7.6.1	Detailed Description . . . . .	101
7.6.2	Constructor & Destructor Documentation . . . . .	101
7.6.2.1	Init . . . . .	101
7.6.2.2	~Init . . . . .	101
7.6.3	Friends And Related Function Documentation . . . . .	101
7.6.3.1	internal::Singleton< const Init > . . . . .	101
7.7	qpp::internal::IOManipEigen Class Reference . . . . .	101
7.7.1	Constructor & Destructor Documentation . . . . .	102
7.7.1.1	IOManipEigen . . . . .	102
7.7.1.2	IOManipEigen . . . . .	102
7.7.2	Member Function Documentation . . . . .	102
7.7.2.1	display . . . . .	102
7.7.3	Member Data Documentation . . . . .	103
7.7.3.1	A_ . . . . .	103
7.7.3.2	chop_ . . . . .	103
7.8	qpp::internal::IOManipPointer< PointerType > Class Template Reference . . . . .	103
7.8.1	Constructor & Destructor Documentation . . . . .	104
7.8.1.1	IOManipPointer . . . . .	104
7.8.1.2	IOManipPointer . . . . .	104
7.8.2	Member Function Documentation . . . . .	104
7.8.2.1	display . . . . .	104
7.8.2.2	operator= . . . . .	104
7.8.3	Member Data Documentation . . . . .	104
7.8.3.1	end_ . . . . .	104
7.8.3.2	N_ . . . . .	104
7.8.3.3	p_ . . . . .	104
7.8.3.4	separator_ . . . . .	105
7.8.3.5	start_ . . . . .	105
7.9	qpp::internal::IOManipRange< InputIterator > Class Template Reference . . . . .	105
7.9.1	Constructor & Destructor Documentation . . . . .	106
7.9.1.1	IOManipRange . . . . .	106
7.9.1.2	IOManipRange . . . . .	106
7.9.2	Member Function Documentation . . . . .	106
7.9.2.1	display . . . . .	106
7.9.2.2	operator= . . . . .	106
7.9.3	Member Data Documentation . . . . .	106
7.9.3.1	end_ . . . . .	106
7.9.3.2	first_ . . . . .	106
7.9.3.3	last_ . . . . .	106

7.9.3.4	<a href="#">separator_</a>	107
7.9.3.5	<a href="#">start_</a>	107
7.10	<a href="#">qpp::is_complex&lt; T &gt; Struct Template Reference</a>	107
7.10.1	<a href="#">Detailed Description</a>	107
7.11	<a href="#">qpp::is_complex&lt; std::complex&lt; T &gt; &gt; Struct Template Reference</a>	108
7.11.1	<a href="#">Detailed Description</a>	108
7.12	<a href="#">qpp::is_iterable&lt; T, typename &gt; Struct Template Reference</a>	109
7.12.1	<a href="#">Detailed Description</a>	109
7.13	<a href="#">qpp::is_iterable&lt; T, to_void&lt; decltype(std::declval&lt; T &gt;().begin()), decltype(std::declval&lt; T &gt;().end()), typename T::value_type &gt; &gt; Struct Template Reference</a>	110
7.13.1	<a href="#">Detailed Description</a>	110
7.14	<a href="#">qpp::is_matrix_expression&lt; Derived &gt; Struct Template Reference</a>	111
7.14.1	<a href="#">Detailed Description</a>	111
7.15	<a href="#">qpp::is_matrix_expression&lt; typename Eigen::MatrixBase&lt; Derived &gt; &gt; Struct Template Reference</a>	112
7.15.1	<a href="#">Detailed Description</a>	112
7.16	<a href="#">qpp::RandomDevices Class Reference</a>	113
7.16.1	<a href="#">Detailed Description</a>	114
7.16.2	<a href="#">Constructor &amp; Destructor Documentation</a>	114
7.16.2.1	<a href="#">RandomDevices</a>	114
7.16.2.2	<a href="#">~RandomDevices</a>	114
7.16.3	<a href="#">Friends And Related Function Documentation</a>	114
7.16.3.1	<a href="#">internal::Singleton&lt; RandomDevices &gt;</a>	114
7.16.4	<a href="#">Member Data Documentation</a>	114
7.16.4.1	<a href="#">rd_</a>	114
7.16.4.2	<a href="#">rng_</a>	114
7.17	<a href="#">qpp::internal::Singleton&lt; T &gt; Class Template Reference</a>	115
7.17.1	<a href="#">Detailed Description</a>	115
7.17.2	<a href="#">Constructor &amp; Destructor Documentation</a>	116
7.17.2.1	<a href="#">Singleton</a>	116
7.17.2.2	<a href="#">Singleton</a>	116
7.17.2.3	<a href="#">~Singleton</a>	116
7.17.3	<a href="#">Member Function Documentation</a>	116
7.17.3.1	<a href="#">get_instance</a>	116
7.17.3.2	<a href="#">get_thread_local_instance</a>	116
7.17.3.3	<a href="#">operator=</a>	116
7.18	<a href="#">qpp::States Class Reference</a>	116
7.18.1	<a href="#">Detailed Description</a>	118
7.18.2	<a href="#">Constructor &amp; Destructor Documentation</a>	118
7.18.2.1	<a href="#">States</a>	118
7.18.2.2	<a href="#">~States</a>	118

7.18.3 Friends And Related Function Documentation . . . . .	118
7.18.3.1 internal::Singleton< const States > . . . . .	118
7.18.4 Member Data Documentation . . . . .	118
7.18.4.1 b00 . . . . .	118
7.18.4.2 b01 . . . . .	119
7.18.4.3 b10 . . . . .	119
7.18.4.4 b11 . . . . .	119
7.18.4.5 GHZ . . . . .	119
7.18.4.6 pb00 . . . . .	119
7.18.4.7 pb01 . . . . .	119
7.18.4.8 pb10 . . . . .	119
7.18.4.9 pb11 . . . . .	119
7.18.4.10 pGHZ . . . . .	119
7.18.4.11 pW . . . . .	119
7.18.4.12 px0 . . . . .	119
7.18.4.13 px1 . . . . .	119
7.18.4.14 py0 . . . . .	120
7.18.4.15 py1 . . . . .	120
7.18.4.16 pz0 . . . . .	120
7.18.4.17 pz1 . . . . .	120
7.18.4.18 W . . . . .	120
7.18.4.19 x0 . . . . .	120
7.18.4.20 x1 . . . . .	120
7.18.4.21 y0 . . . . .	120
7.18.4.22 y1 . . . . .	120
7.18.4.23 z0 . . . . .	120
7.18.4.24 z1 . . . . .	120
7.19 qpp::Timer< T, CLOCK_T > Class Template Reference . . . . .	121
7.19.1 Detailed Description . . . . .	122
7.19.2 Constructor & Destructor Documentation . . . . .	122
7.19.2.1 Timer . . . . .	122
7.19.2.2 Timer . . . . .	122
7.19.2.3 Timer . . . . .	122
7.19.2.4 ~Timer . . . . .	122
7.19.3 Member Function Documentation . . . . .	123
7.19.3.1 display . . . . .	123
7.19.3.2 get_duration . . . . .	123
7.19.3.3 operator= . . . . .	123
7.19.3.4 operator= . . . . .	123
7.19.3.5 tic . . . . .	123

7.19.3.6	tics	123
7.19.3.7	toc	124
7.19.4	Member Data Documentation	124
7.19.4.1	end_	124
7.19.4.2	start_	124
<b>8</b>	<b>File Documentation</b>	<b>125</b>
8.1	classes/codes.h File Reference	125
8.1.1	Detailed Description	125
8.2	classes/exception.h File Reference	125
8.2.1	Detailed Description	126
8.3	classes/gates.h File Reference	126
8.3.1	Detailed Description	127
8.4	classes/ideplay.h File Reference	127
8.4.1	Detailed Description	127
8.5	classes/init.h File Reference	128
8.5.1	Detailed Description	128
8.6	classes/random_devices.h File Reference	128
8.6.1	Detailed Description	129
8.7	classes/states.h File Reference	129
8.7.1	Detailed Description	129
8.8	classes/timer.h File Reference	130
8.8.1	Detailed Description	130
8.9	constants.h File Reference	130
8.9.1	Detailed Description	131
8.10	entanglement.h File Reference	131
8.10.1	Detailed Description	132
8.11	entropies.h File Reference	132
8.11.1	Detailed Description	133
8.12	experimental/experimental.h File Reference	134
8.12.1	Detailed Description	134
8.13	functions.h File Reference	134
8.13.1	Detailed Description	138
8.14	input_output.h File Reference	138
8.14.1	Detailed Description	139
8.15	instruments.h File Reference	139
8.15.1	Detailed Description	141
8.16	internal/classes/iomanip.h File Reference	141
8.16.1	Detailed Description	142
8.17	internal/classes/singleton.h File Reference	142

8.17.1 Detailed Description . . . . .	143
8.18 internal/util.h File Reference . . . . .	143
8.18.1 Detailed Description . . . . .	144
8.19 macros.h File Reference . . . . .	144
8.19.1 Detailed Description . . . . .	145
8.19.2 Macro Definition Documentation . . . . .	145
8.19.2.1 ERROR . . . . .	145
8.19.2.2 ERRORLN . . . . .	145
8.19.2.3 PRINT . . . . .	145
8.19.2.4 PRINTLN . . . . .	145
8.20 MATLAB/matlab.h File Reference . . . . .	145
8.20.1 Detailed Description . . . . .	146
8.21 number_theory.h File Reference . . . . .	146
8.21.1 Detailed Description . . . . .	147
8.22 operations.h File Reference . . . . .	147
8.22.1 Detailed Description . . . . .	149
8.23 qpp.h File Reference . . . . .	149
8.23.1 Detailed Description . . . . .	151
8.23.2 Macro Definition Documentation . . . . .	151
8.23.2.1 QPP_UNUSED_ . . . . .	151
8.24 random.h File Reference . . . . .	151
8.24.1 Detailed Description . . . . .	152
8.25 statistics.h File Reference . . . . .	152
8.25.1 Detailed Description . . . . .	153
8.26 traits.h File Reference . . . . .	154
8.26.1 Detailed Description . . . . .	154
8.27 types.h File Reference . . . . .	155
8.27.1 Detailed Description . . . . .	156
<b>Index</b>	<b>157</b>





# Chapter 1

## Quantum++

### Version 0.8.9 - development

Quantum++ is a C++11 general purpose quantum computing library, composed solely of template header files. Quantum++ is written in standard C++11 and has very low external dependencies, using only the [Eigen 3](#) linear algebra header-only template library and, if available, the [OpenMP](#) multi-processing library.

Quantum++ is not restricted to qubit systems or specific quantum information processing tasks, being capable of simulating arbitrary quantum processes. The main design factors taken in consideration were the ease of use, high portability, and high performance.

If you are interesting in contributing, please contact me. To contribute, you need to have a good knowledge of C++ (preferably C++11), including templates and the standard library, a basic knowledge of quantum computing and linear algebra, and working experience with [Eigen 3](#).

For additional [Eigen 3](#) documentation see <http://eigen.tuxfamily.org/dox/>. For a simple [Eigen 3](#) quick ASCII reference see <http://eigen.tuxfamily.org/dox/AsciiQuickReference.txt>.

Copyright (c) 2013 - 2016 Vlad Gheorghiu, vgheorgh AT gmail DOT com.

Quantum++ is free software: you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation, either version 3 of the License, or (at your option) any later version.

Quantum++ is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

You should have received a copy of the GNU General Public License along with Quantum++. If not, see <http://www.gnu.org/licenses/>.

### Building instructions

#### Configuration:

- Compiler: [g++](#) version 4.8.2 or later (for good C++11 support)
- [Eigen 3](#) library located in `$HOME/eigen`
- Quantum++ library located in `$HOME/qpp`
- [MATLAB](#) compiler include header files: `/Applications/MATLAB_R2016a.app/extern/include`
- [MATLAB](#) compiler shared library files: `/Applications/MATLAB_R2016a.app/bin/maci64`

### Building without a build system

- Example file: `$HOME/qpp/examples/minimal.cpp`
- Output executable: `$HOME/qpp/examples/minimal`
- Must run the commands below from inside the directory `$HOME/qpp/examples`

#### Release version (without **MATLAB** support):

```
g++ -pedantic -std=c++11 -Wall -Wextra -Weffc++ -fopenmp \
    -O3 -DNDEBUG -DEIGEN_NO_DEBUG \
    -isystem $HOME/eigen -I $HOME/qpp/include \
    minimal.cpp -o minimal
```

#### Debug version (without **MATLAB** support):

```
g++ -pedantic -std=c++11 -Wall -Wextra -Weffc++ -fopenmp \
    -g3 -DDEBUG \
    -isystem $HOME/eigen -I $HOME/qpp/include \
    minimal.cpp -o minimal
```

#### Release version (with **MATLAB** support):

```
g++ -pedantic -std=c++11 -Wall -Wextra -Weffc++ -fopenmp \
    -O3 -DNDEBUG -DEIGEN_NO_DEBUG \
    -isystem $HOME/eigen -I $HOME/qpp/include \
    -I/Applications/MATLAB_R2016a.app/extern/include \
    -L/Applications/MATLAB_R2016a.app/bin/maci64 \
    -lmx -lmat minimal.cpp -o minimal
```

#### Debug version (with **MATLAB** support):

```
g++ -pedantic -std=c++11 -Wall -Wextra -Weffc++ -fopenmp \
    -g3 -DDEBUG \
    -isystem $HOME/eigen -I $HOME/qpp/include \
    -I /Applications/MATLAB_R2016a.app/extern/include \
    -L /Applications/MATLAB_R2016a.app/bin/maci64 \
    -lmx -lmat minimal.cpp -o minimal
```

### Building using **cmake** (version 3.0.0 or later)

The current version of the repository has a `./CMakeLists.txt` configuration file for building examples using **cmake**. To build an example using **cmake**, I recommend an out-of-source build, i.e., from the root of the project (where `./include` is located), type

```
mkdir ./build
cd ./build
cmake ..
make
```

The above commands build the release version (default) executable `qpp`, from the source file `./examples/minimal.cpp`, without **MATLAB** support (default), inside the directory `./build`. To build a different configuration, e.g. debug version with **MATLAB** support, type from the root of the project

```
cd ./build
rm -rf *
cmake -DCMAKE_BUILD_TYPE=Debug -DWITH_MATLAB=ON ..
make
```

Or, to disable **OpenMP** support (enabled by default), type

```
cd ./build
rm -rf *
cmake -DWITH_OPENMP=OFF ..
make
```

To change the name of the example file, the location of the **Eigen 3** library or the location of **MATLAB** installation, edit the `./CMakeLists.txt` file. See also `./CMakeLists.txt` for additional options. Do not forget to remove everything from the `./build` directory before a fresh build!

### Unit testing

**Google Mock 1.7.0** is included with the project. I strongly recommend to use **cmake** version 3.0.0 or later as a building system. By default the current `CMakeLists.txt` automatically builds all unit tests as `./build/unit_tests/tests/qpp_testing`. To disable automatic building of unit tests, type

```
cmake -DWITH_UNIT_TESTS=OFF ..
```

from inside `./build`.

### Additional remarks

- The C++ compiler must be C++11 compliant.
- If using **Windows**, I recommend compiling under **cygwin** via **cmake** and **g++**. See also <http://stackoverflow.com/questions/28997206/cygwin-support-for-c11-in-g4-9-2> for a bug related to lack of support for some C++11 math functions, and how to fix it. Quick fix: patch the standard library header file `<cmath>` using the provided patch `./cmath_cygwin.patch`.
- If your compiler does not support **OpenMP** (as it is the case e.g with **clang++**), disable **OpenMP** in your build, as otherwise the linker may not find the **gomp** library.
- If you run the program on **OS X** with **MATLAB** support, make sure that the environment variable `DYLD_LIBRARY_PATH` is set to point to the **MATLAB** compiler library location, see the `run_OSX_MATLAB` script. Otherwise, you will get a runtime error like `dyld: Library not loaded: @rpath/libmat.dylib`.

```
* I recommend running via a script, as otherwise setting the
'DYLD_LIBRARY_PATH' globally may interfere with
[macports](https://www.macports.org/) [cmake](http://www.cmake.org/)
installation (in case you use [cmake](http://www.cmake.org/) from
[macports](https://www.macports.org/)). If you use a script,
then the environment variable is local to the script and
does not interfere with the rest of the system.
```

```
* Example of script, assumed to be located in the root directory
of Quantum++:
```

```
#!/bin/sh

MATLAB=/Applications/MATLAB_R2016a.app
export DYLD_LIBRARY_PATH=$DYLD_LIBRARY_PATH:$MATLAB/bin/maci64

./build/qpp
```

- If you build a debug version with **g++** under **OS X** and use **gdb** to step inside template functions you may want to add `-fno-weak` compiler flag. See <http://stackoverflow.com/questions/23330641/gnu-gdb-can-not-step-into-template-functions-os-x-mavericks> for more details about this problem.



## Chapter 2

# Namespace Index

### 2.1 Namespace List

Here is a list of all namespaces with brief descriptions:

<a href="#">qpp</a>	Quantum++ main namespace . . . . .	13
<a href="#">qpp::experimental</a>	Experimental/test functions/classes, do not use or modify . . . . .	80
<a href="#">qpp::internal</a>	Internal utility functions, do not use/modify . . . . .	80
<a href="#">qpp::internal::details_</a>	. . . . .	83



## Chapter 3

# Hierarchical Index

### 3.1 Class Hierarchy

This inheritance list is sorted roughly, but not completely, alphabetically:

qpp::internal::details_::Display_Impl_ . . . . .	87
qpp::internal::IOManipEigen . . . . .	101
std::exception	
qpp::Exception . . . . .	88
false_type	
qpp::is_complex< T > . . . . .	107
qpp::is_iterable< T, typename > . . . . .	109
qpp::is_matrix_expression< Derived > . . . . .	111
qpp::IDisplay . . . . .	97
qpp::internal::IOManipEigen . . . . .	101
qpp::internal::IOManipPointer< PointerType > . . . . .	103
qpp::internal::IOManipRange< InputIterator > . . . . .	105
qpp::Timer< T, CLOCK_T > . . . . .	121
qpp::internal::Singleton< T > . . . . .	115
qpp::internal::Singleton< const Codes > . . . . .	115
qpp::Codes . . . . .	85
qpp::internal::Singleton< const Gates > . . . . .	115
qpp::Gates . . . . .	91
qpp::internal::Singleton< const Init > . . . . .	115
qpp::Init . . . . .	100
qpp::internal::Singleton< const States > . . . . .	115
qpp::States . . . . .	116
qpp::internal::Singleton< RandomDevices > . . . . .	115
qpp::RandomDevices . . . . .	113
true_type	
qpp::is_complex< std::complex< T > > . . . . .	108
qpp::is_iterable< T, to_void< decltype(std::declval< T >().begin()), decltype(std::declval< T >().end()), typename T::value_type > > . . . . .	110
qpp::is_matrix_expression< typename Eigen::MatrixBase< Derived > > . . . . .	112





## Chapter 4

# Class Index

### 4.1 Class List

Here are the classes, structs, unions and interfaces with brief descriptions:

<a href="#">qpp::Codes</a>	Const Singleton class that defines quantum error correcting codes . . . . .	85
<a href="#">qpp::internal::details_::Display_Impl_</a>	. . . . .	87
<a href="#">qpp::Exception</a>	Generates custom exceptions, used when validating function parameters . . . . .	88
<a href="#">qpp::Gates</a>	Const Singleton class that implements most commonly used gates . . . . .	91
<a href="#">qpp::IDisplay</a>	Abstract class (interface) that mandates the definition of virtual <code>std::ostream&amp; display(std::ostream&amp; os) const</code> . . . . .	97
<a href="#">qpp::Init</a>	Const Singleton class that performs additional initializations/cleanups . . . . .	100
<a href="#">qpp::internal::IOManipEigen</a>	. . . . .	101
<a href="#">qpp::internal::IOManipPointer&lt; PointerType &gt;</a>	. . . . .	103
<a href="#">qpp::internal::IOManipRange&lt; InputIterator &gt;</a>	. . . . .	105
<a href="#">qpp::is_complex&lt; T &gt;</a>	Checks whether the type is a complex type . . . . .	107
<a href="#">qpp::is_complex&lt; std::complex&lt; T &gt; &gt;</a>	Checks whether the type is a complex number type, specialization for complex types . . . . .	108
<a href="#">qpp::is_iterable&lt; T, typename &gt;</a>	Checks whether <i>T</i> is compatible with an STL-like iterable container . . . . .	109
<a href="#">qpp::is_iterable&lt; T, to_void&lt; decltype(std::declval&lt; T &gt;().begin()), decltype(std::declval&lt; T &gt;().end()), typename T::value_type &gt; &gt;</a>	Checks whether <i>T</i> is compatible with an STL-like iterable container, specialization for STL-like iterable containers . . . . .	110
<a href="#">qpp::is_matrix_expression&lt; Derived &gt;</a>	Checks whether the type is an Eigen matrix expression . . . . .	111
<a href="#">qpp::is_matrix_expression&lt; typename Eigen::MatrixBase&lt; Derived &gt; &gt;</a>	Checks whether the type is an Eigen matrix expression, specialization for Eigen matrix expressions . . . . .	112
<a href="#">qpp::RandomDevices</a>	Singleton class that manages the source of randomness in the library . . . . .	113
<a href="#">qpp::internal::Singleton&lt; T &gt;</a>	<a href="#">Singleton</a> policy class, used internally to implement the singleton pattern via CRTP (Curiously recurring template pattern) . . . . .	115
<a href="#">qpp::States</a>	Const Singleton class that implements most commonly used states . . . . .	116

[qpp::Timer< T, CLOCK\\_T >](#)  
    [Chronometer](#) . . . . . [121](#)

## Chapter 5

# File Index

### 5.1 File List

Here is a list of all files with brief descriptions:

<a href="#">constants.h</a>	
Constants . . . . .	130
<a href="#">entanglement.h</a>	
Entanglement functions . . . . .	131
<a href="#">entropies.h</a>	
Entropy functions . . . . .	132
<a href="#">functions.h</a>	
Generic quantum computing functions . . . . .	134
<a href="#">input_output.h</a>	
Input/output functions . . . . .	138
<a href="#">instruments.h</a>	
Measurement functions . . . . .	139
<a href="#">macros.h</a>	
Preprocessor macros . . . . .	144
<a href="#">number_theory.h</a>	
Number theory functions . . . . .	146
<a href="#">operations.h</a>	
Quantum operation functions . . . . .	147
<a href="#">qpp.h</a>	
Quantum++ main header file, includes all other necessary headers . . . . .	149
<a href="#">random.h</a>	
Randomness-related functions . . . . .	151
<a href="#">statistics.h</a>	
Statistics functions . . . . .	152
<a href="#">traits.h</a>	
Type traits . . . . .	154
<a href="#">types.h</a>	
Type aliases . . . . .	155
classes/ <a href="#">codes.h</a>	
Quantum error correcting codes . . . . .	125
classes/ <a href="#">exception.h</a>	
Exceptions . . . . .	125
classes/ <a href="#">gates.h</a>	
Quantum gates . . . . .	126
classes/ <a href="#">display.h</a>	
Display interface via the non-virtual interface (NVI) . . . . .	127
classes/ <a href="#">init.h</a>	
Initialization . . . . .	128

classes/ <a href="#">random_devices.h</a>	
Random devices . . . . .	128
classes/ <a href="#">states.h</a>	
Quantum states . . . . .	129
classes/ <a href="#">timer.h</a>	
Timing . . . . .	130
experimental/ <a href="#">experimental.h</a>	
Experimental/test functions/classes . . . . .	134
internal/ <a href="#">util.h</a>	
Internal utility functions . . . . .	143
internal/classes/ <a href="#">iomanip.h</a>	
Input/output manipulators . . . . .	141
internal/classes/ <a href="#">singleton.h</a>	
Singleton pattern via CRTP . . . . .	142
MATLAB/ <a href="#">matlab.h</a>	
Input/output interfacing with MATLAB . . . . .	145

## Chapter 6

# Namespace Documentation

### 6.1 qpp Namespace Reference

Quantum++ main namespace.

#### Namespaces

- [experimental](#)  
*Experimental/test functions/classes, do not use or modify.*
- [internal](#)  
*Internal utility functions, do not use/modify.*

#### Classes

- class [Codes](#)  
*const Singleton class that defines quantum error correcting codes*
- class [Exception](#)  
*Generates custom exceptions, used when validating function parameters.*
- class [Gates](#)  
*const Singleton class that implements most commonly used gates*
- class [IDisplay](#)  
*Abstract class (interface) that mandates the definition of virtual `std::ostream& display(std::ostream& os) const`.*
- class [Init](#)  
*const Singleton class that performs additional initializations/cleanups*
- struct [is\\_complex](#)  
*Checks whether the type is a complex type.*
- struct [is\\_complex< std::complex< T > >](#)  
*Checks whether the type is a complex number type, specialization for complex types.*
- struct [is\\_iterable](#)  
*Checks whether T is compatible with an STL-like iterable container.*
- struct [is\\_iterable< T, to\\_void< decltype\(std::declval< T >\(\).begin\(\)\), decltype\(std::declval< T >\(\).end\(\)\), typename T::value\\_type > >](#)  
*Checks whether T is compatible with an STL-like iterable container, specialization for STL-like iterable containers.*
- struct [is\\_matrix\\_expression](#)  
*Checks whether the type is an Eigen matrix expression.*
- struct [is\\_matrix\\_expression< typename Eigen::MatrixBase< Derived > >](#)  
*Checks whether the type is an Eigen matrix expression, specialization for Eigen matrix expressions.*

- class [RandomDevices](#)  
*Singleton class that manages the source of randomness in the library.*
- class [States](#)  
*const Singleton class that implements most commonly used states*
- class [Timer](#)  
*Chronometer.*

## Typedefs

- `template<typename... >`  
`using to\_void = void`  
*Alias template that implements the proposal for void\_ t.*
- `using idx = std::size_t`  
*Non-negative integer index.*
- `using bigint = long long int`  
*Big integer.*
- `using cplx = std::complex< double >`  
*Complex number in double precision.*
- `using ket = Eigen::VectorXcd`  
*Complex (double precision) dynamic Eigen column vector.*
- `using bra = Eigen::RowVectorXcd`  
*Complex (double precision) dynamic Eigen row vector.*
- `using cmat = Eigen::MatrixXcd`  
*Complex (double precision) dynamic Eigen matrix.*
- `using dmat = Eigen::MatrixXd`  
*Real (double precision) dynamic Eigen matrix.*
- `template<typename Scalar >`  
`using dyn\_mat = Eigen::Matrix< Scalar, Eigen::Dynamic, Eigen::Dynamic >`  
*Dynamic Eigen matrix over the field specified by Scalar.*
- `template<typename Scalar >`  
`using dyn\_col\_vect = Eigen::Matrix< Scalar, Eigen::Dynamic, 1 >`  
*Dynamic Eigen column vector over the field specified by Scalar.*
- `template<typename Scalar >`  
`using dyn\_row\_vect = Eigen::Matrix< Scalar, 1, Eigen::Dynamic >`  
*Dynamic Eigen row vector over the field specified by Scalar.*

## Functions

- `constexpr cplx operator""\_i (unsigned long long int x) noexcept`  
*User-defined literal for complex  $i = \sqrt{-1}$  (integer overload)*
- `constexpr cplx operator""\_i (long double x) noexcept`  
*User-defined literal for complex  $i = \sqrt{-1}$  (real overload)*
- `cplx omega (idx D)`  
*D-th root of unity.*
- `template<typename Derived >`  
`dyn\_col\_vect< double > schmidtcoeffs (const Eigen::MatrixBase< Derived > &A, const std::vector< idx > &dims)`  
*Schmidt coefficients of the bi-partite pure state A.*
- `template<typename Derived >`  
`cmat schmidtA (const Eigen::MatrixBase< Derived > &A, const std::vector< idx > &dims)`  
*Schmidt basis on Alice side.*

- `template<typename Derived >`  
`cmat schmidtB` (const Eigen::MatrixBase< Derived > &A, const std::vector< `idx` > &dims)  
*Schmidt basis on Bob side.*
- `template<typename Derived >`  
`std::vector< double > schmidtprobs` (const Eigen::MatrixBase< Derived > &A, const std::vector< `idx` > &dims)  
*Schmidt probabilities of the bi-partite pure state A.*
- `template<typename Derived >`  
`double entanglement` (const Eigen::MatrixBase< Derived > &A, const std::vector< `idx` > &dims)  
*Entanglement of the bi-partite pure state A.*
- `template<typename Derived >`  
`double gconcurrence` (const Eigen::MatrixBase< Derived > &A)  
*G-concurrence of the bi-partite pure state A.*
- `template<typename Derived >`  
`double negativity` (const Eigen::MatrixBase< Derived > &A, const std::vector< `idx` > &dims)  
*Negativity of the bi-partite mixed state A.*
- `template<typename Derived >`  
`double lognegativity` (const Eigen::MatrixBase< Derived > &A, const std::vector< `idx` > &dims)  
*Logarithmic negativity of the bi-partite mixed state A.*
- `template<typename Derived >`  
`double concurrence` (const Eigen::MatrixBase< Derived > &A)  
*Wootters concurrence of the bi-partite qubit mixed state A.*
- `template<typename Derived >`  
`double entropy` (const Eigen::MatrixBase< Derived > &A)  
*von-Neumann entropy of the density matrix A*
- `double entropy` (const std::vector< double > &prob)  
*Shannon entropy of the probability distribution prob.*
- `template<typename Derived >`  
`double renyi` (const Eigen::MatrixBase< Derived > &A, double alpha)  
*Renyi-  $\alpha$  entropy of the density matrix A, for  $\alpha \geq 0$ .*
- `double renyi` (const std::vector< double > &prob, double alpha)  
*Renyi-  $\alpha$  entropy of the probability distribution prob, for  $\alpha \geq 0$ .*
- `template<typename Derived >`  
`double tsallis` (const Eigen::MatrixBase< Derived > &A, double q)  
*Tsallis-  $q$  entropy of the density matrix A, for  $q \geq 0$ .*
- `double tsallis` (const std::vector< double > &prob, double q)  
*Tsallis-  $q$  entropy of the probability distribution prob, for  $q \geq 0$ .*
- `template<typename Derived >`  
`double qmutualinfo` (const Eigen::MatrixBase< Derived > &A, const std::vector< `idx` > &subsysA, const std::vector< `idx` > &subsysB, const std::vector< `idx` > &dims)  
*Quantum mutual information between 2 subsystems of a composite system.*
- `template<typename Derived >`  
`double qmutualinfo` (const Eigen::MatrixBase< Derived > &A, const std::vector< `idx` > &subsysA, const std::vector< `idx` > &subsysB, `idx` d=2)  
*Quantum mutual information between 2 subsystems of a composite system.*
- `template<typename Derived >`  
`dyn_mat< typename Derived::Scalar > transpose` (const Eigen::MatrixBase< Derived > &A)  
*Transpose.*
- `template<typename Derived >`  
`dyn_mat< typename Derived::Scalar > conjugate` (const Eigen::MatrixBase< Derived > &A)  
*Complex conjugate.*
- `template<typename Derived >`  
`dyn_mat< typename Derived::Scalar > adjoint` (const Eigen::MatrixBase< Derived > &A)

*Adjoint.*

- `template<typename Derived >`  
`dyn_mat< typename Derived::Scalar > inverse` (const Eigen::MatrixBase< Derived > &A)

*Inverse.*

- `template<typename Derived >`  
`Derived::Scalar trace` (const Eigen::MatrixBase< Derived > &A)

*Trace.*

- `template<typename Derived >`  
`Derived::Scalar det` (const Eigen::MatrixBase< Derived > &A)

*Determinant.*

- `template<typename Derived >`  
`Derived::Scalar logdet` (const Eigen::MatrixBase< Derived > &A)

*Logarithm of the determinant.*

- `template<typename Derived >`  
`Derived::Scalar sum` (const Eigen::MatrixBase< Derived > &A)

*Element-wise sum of A.*

- `template<typename Derived >`  
`Derived::Scalar prod` (const Eigen::MatrixBase< Derived > &A)

*Element-wise product of A.*

- `template<typename Derived >`  
`double norm` (const Eigen::MatrixBase< Derived > &A)

*Frobenius norm.*

- `template<typename Derived >`  
`std::pair< dyn_col_vect< cplx >, cmat > eig` (const Eigen::MatrixBase< Derived > &A)

*Full eigen decomposition.*

- `template<typename Derived >`  
`dyn_col_vect< cplx > evals` (const Eigen::MatrixBase< Derived > &A)

*Eigenvalues.*

- `template<typename Derived >`  
`cmat evects` (const Eigen::MatrixBase< Derived > &A)

*Eigenvectors.*

- `template<typename Derived >`  
`std::pair< dyn_col_vect< double >, cmat > heig` (const Eigen::MatrixBase< Derived > &A)

*Full eigen decomposition of Hermitian expression.*

- `template<typename Derived >`  
`dyn_col_vect< double > hevals` (const Eigen::MatrixBase< Derived > &A)

*Hermitian eigenvalues.*

- `template<typename Derived >`  
`cmat hevects` (const Eigen::MatrixBase< Derived > &A)

*Hermitian eigenvectors.*

- `template<typename Derived >`  
`std::tuple< cmat, dyn_col_vect< double >, cmat > svd` (const Eigen::MatrixBase< Derived > &A)

*Full singular value decomposition.*

- `template<typename Derived >`  
`dyn_col_vect< double > svals` (const Eigen::MatrixBase< Derived > &A)

*Singular values.*

- `template<typename Derived >`  
`cmat svdU` (const Eigen::MatrixBase< Derived > &A)

*Left singular vectors.*

- `template<typename Derived >`  
`cmat svdV` (const Eigen::MatrixBase< Derived > &A)

*Right singular vectors.*



- template<typename Derived >  
`cmat funm` (const Eigen::MatrixBase< Derived > &A, `cplx`(\*f)(const `cplx` &))  
*Functional calculus  $f(A)$*
- template<typename Derived >  
`cmat sqrtm` (const Eigen::MatrixBase< Derived > &A)  
*Matrix square root.*
- template<typename Derived >  
`cmat absm` (const Eigen::MatrixBase< Derived > &A)  
*Matrix absolute value.*
- template<typename Derived >  
`cmat expm` (const Eigen::MatrixBase< Derived > &A)  
*Matrix exponential.*
- template<typename Derived >  
`cmat logm` (const Eigen::MatrixBase< Derived > &A)  
*Matrix logarithm.*
- template<typename Derived >  
`cmat sinm` (const Eigen::MatrixBase< Derived > &A)  
*Matrix sin.*
- template<typename Derived >  
`cmat cosm` (const Eigen::MatrixBase< Derived > &A)  
*Matrix cos.*
- template<typename Derived >  
`cmat spectralpowm` (const Eigen::MatrixBase< Derived > &A, const `cplx` z)  
*Matrix power.*
- template<typename Derived >  
`dyn_mat`< typename Derived::Scalar > `powm` (const Eigen::MatrixBase< Derived > &A, `idx` n)  
*Fast matrix power based on the SQUARE-AND-MULTIPLY algorithm.*
- template<typename Derived >  
`double Schatten` (const Eigen::MatrixBase< Derived > &A, double p)  
*Schatten matrix norm.*
- template<typename OutputScalar , typename Derived >  
`dyn_mat`< OutputScalar > `cwise` (const Eigen::MatrixBase< Derived > &A, OutputScalar(\*f)(const type-  
name Derived::Scalar &))  
*Functor.*
- template<typename T >  
`dyn_mat`< typename T::Scalar > `kron` (const T &head)  
*Kronecker product.*
- template<typename T , typename... Args>  
`dyn_mat`< typename T::Scalar > `kron` (const T &head, const Args &...tail)  
*Kronecker product.*
- template<typename Derived >  
`dyn_mat`< typename Derived::Scalar > `kron` (const std::vector< Derived > &As)  
*Kronecker product.*
- template<typename Derived >  
`dyn_mat`< typename Derived::Scalar > `kron` (const std::initializer\_list< Derived > &As)  
*Kronecker product.*
- template<typename Derived >  
`dyn_mat`< typename Derived::Scalar > `kronpow` (const Eigen::MatrixBase< Derived > &A, `idx` n)  
*Kronecker power.*
- template<typename T >  
`dyn_mat`< typename T::Scalar > `dirsum` (const T &head)  
*Direct sum.*

- `template<typename T, typename... Args>`  
`dyn_mat< typename T::Scalar > dirsum` (const T &head, const Args &...tail)  
*Direct sum.*
- `template<typename Derived >`  
`dyn_mat< typename Derived::Scalar > dirsum` (const std::vector< Derived > &As)  
*Direct sum.*
- `template<typename Derived >`  
`dyn_mat< typename Derived::Scalar > dirsum` (const std::initializer\_list< Derived > &As)  
*Direct sum.*
- `template<typename Derived >`  
`dyn_mat< typename Derived::Scalar > dirsumpow` (const Eigen::MatrixBase< Derived > &A, `idx` n)  
*Direct sum power.*
- `template<typename Derived >`  
`dyn_mat< typename Derived::Scalar > reshape` (const Eigen::MatrixBase< Derived > &A, `idx` rows, `idx` cols)  
*Reshape.*
- `template<typename Derived1, typename Derived2 >`  
`dyn_mat< typename Derived1::Scalar > comm` (const Eigen::MatrixBase< Derived1 > &A, const Eigen::MatrixBase< Derived2 > &B)  
*Commutator.*
- `template<typename Derived1, typename Derived2 >`  
`dyn_mat< typename Derived1::Scalar > anticomm` (const Eigen::MatrixBase< Derived1 > &A, const Eigen::MatrixBase< Derived2 > &B)  
*Anti-commutator.*
- `template<typename Derived >`  
`dyn_mat< typename Derived::Scalar > prj` (const Eigen::MatrixBase< Derived > &V)  
*Projector.*
- `template<typename Derived >`  
`dyn_mat< typename Derived::Scalar > grams` (const std::vector< Derived > &Vs)  
*Gram-Schmidt orthogonalization.*
- `template<typename Derived >`  
`dyn_mat< typename Derived::Scalar > grams` (const std::initializer\_list< Derived > &Vs)  
*Gram-Schmidt orthogonalization.*
- `template<typename Derived >`  
`dyn_mat< typename Derived::Scalar > grams` (const Eigen::MatrixBase< Derived > &A)  
*Gram-Schmidt orthogonalization.*
- `std::vector< idx > n2multiidx` (`idx` n, const std::vector< `idx` > &dims)  
*Non-negative integer index to multi-index.*
- `idx multiidx2n` (const std::vector< `idx` > &midx, const std::vector< `idx` > &dims)  
*Multi-index to non-negative integer index.*
- `ket mket` (const std::vector< `idx` > &mask, const std::vector< `idx` > &dims)  
*Multi-partite qudit ket.*
- `ket mket` (const std::vector< `idx` > &mask, `idx` d=2)  
*Multi-partite qudit ket.*
- `cmat mprj` (const std::vector< `idx` > &mask, const std::vector< `idx` > &dims)  
*Projector onto multi-partite qudit ket.*
- `cmat mprj` (const std::vector< `idx` > &mask, `idx` d=2)  
*Projector onto multi-partite qudit ket.*
- `template<typename InputIterator >`  
`std::vector< double > abssq` (InputIterator first, InputIterator last)  
*Computes the absolute values squared of an STL-like range of complex numbers.*

- `template<typename Container >`  
`std::vector< double > abssq (const Container &c, typename std::enable_if< is\_iterable< Container >::value >::type * = nullptr)`  
*Computes the absolute values squared of an STL-like container.*
- `template<typename Derived >`  
`std::vector< double > abssq (const Eigen::MatrixBase< Derived > &A)`  
*Computes the absolute values squared of an Eigen expression.*
- `template<typename InputIterator >`  
`std::iterator_traits< InputIterator >::value_type sum (InputIterator first, InputIterator last)`  
*Element-wise sum of an STL-like range.*
- `template<typename Container >`  
`Container::value_type sum (const Container &c, typename std::enable_if< is\_iterable< Container >::value >::type * = nullptr)`  
*Element-wise sum of the elements of an STL-like container.*
- `template<typename InputIterator >`  
`std::iterator_traits< InputIterator >::value_type prod (InputIterator first, InputIterator last)`  
*Element-wise product of an STL-like range.*
- `template<typename Container >`  
`Container::value_type prod (const Container &c, typename std::enable_if< is\_iterable< Container >::value >::type * = nullptr)`  
*Element-wise product of the elements of an STL-like container.*
- `template<typename Derived >`  
`dyn\_col\_vect< typename Derived::Scalar > rho2pure (const Eigen::MatrixBase< Derived > &A)`  
*Finds the pure state representation of a matrix proportional to a projector onto a pure state.*
- `template<typename T >`  
`std::vector< T > complement (std::vector< T > subsys, idx N)`  
*Constructs the complement of a subsystem vector.*
- `template<typename Derived >`  
`std::vector< double > rho2bloch (const Eigen::MatrixBase< Derived > &A)`  
*Computes the 3-dimensional real Bloch vector corresponding to the qubit density matrix A.*
- `cmat bloch2rho (const std::vector< double > &r)`  
*Computes the density matrix corresponding to the 3-dimensional real Bloch vector r.*
- `template<typename Derived >`  
`internal::IOManipEigen disp (const Eigen::MatrixBase< Derived > &A, double chop=qpp::chop)`  
*Eigen expression ostream manipulator.*
- `internal::IOManipEigen disp (cplx z, double chop=qpp::chop)`  
*Complex number ostream manipulator.*
- `template<typename InputIterator >`  
`internal::IOManipRange< InputIterator > disp (InputIterator first, InputIterator last, const std::string &separator, const std::string &start="[" , const std::string &end="]")`  
*Range ostream manipulator.*
- `template<typename Container >`  
`internal::IOManipRange< typename Container::const_iterator > disp (const Container &c, const std::string &separator, const std::string &start="[" , const std::string &end="]", typename std::enable_if< is\_iterable< Container >::value >::type * = nullptr)`  
*Standard container ostream manipulator. The container must support std::begin(), std::end() and forward iteration.*
- `template<typename PointerType >`  
`internal::IOManipPointer< PointerType > disp (const PointerType *p, idx N, const std::string &separator, const std::string &start="[" , const std::string &end="]")`  
*C-style pointer ostream manipulator.*
- `template<typename Derived >`  
`void save (const Eigen::MatrixBase< Derived > &A, const std::string &fname)`  
*Saves Eigen expression to a binary file (internal format) in double precision.*

- `template<typename Derived >`  
`dyn_mat< typename Derived::Scalar > load` (const std::string &fname)  
*Loads Eigen matrix from a binary file (internal format) in double precision.*
- `template<typename Derived >`  
`dyn_col_vect< typename Derived::Scalar > ip` (const Eigen::MatrixBase< Derived > &phi, const Eigen::MatrixBase< Derived > &psi, const std::vector< idx > &subsys, const std::vector< idx > &dims)  
*Generalized inner product.*
- `template<typename Derived >`  
`dyn_col_vect< typename Derived::Scalar > ip` (const Eigen::MatrixBase< Derived > &phi, const Eigen::MatrixBase< Derived > &psi, const std::vector< idx > &subsys, idx d=2)  
*Generalized inner product.*
- `template<typename Derived >`  
`std::tuple< idx, std::vector< double >, std::vector< cmat > > measure` (const Eigen::MatrixBase< Derived > &A, const std::vector< cmat > &Ks)  
*Measures the state A using the set of Kraus operators Ks.*
- `template<typename Derived >`  
`std::tuple< idx, std::vector< double >, std::vector< cmat > > measure` (const Eigen::MatrixBase< Derived > &A, const std::initializer\_list< cmat > &Ks)  
*Measures the state A using the set of Kraus operators Ks.*
- `template<typename Derived >`  
`std::tuple< idx, std::vector< double >, std::vector< cmat > > measure` (const Eigen::MatrixBase< Derived > &A, const cmat &U)  
*Measures the state A in the orthonormal basis specified by the unitary matrix U.*
- `template<typename Derived >`  
`std::tuple< idx, std::vector< double >, std::vector< cmat > > measure` (const Eigen::MatrixBase< Derived > &A, const std::vector< cmat > &Ks, const std::vector< idx > &subsys, const std::vector< idx > &dims)  
*Measures the part subsys of the multi-partite state vector or density matrix A using the set of Kraus operators Ks.*
- `template<typename Derived >`  
`std::tuple< idx, std::vector< double >, std::vector< cmat > > measure` (const Eigen::MatrixBase< Derived > &A, const std::initializer\_list< cmat > &Ks, const std::vector< idx > &subsys, const std::vector< idx > &dims)  
*Measures the part subsys of the multi-partite state vector or density matrix A using the set of Kraus operators Ks.*
- `template<typename Derived >`  
`std::tuple< idx, std::vector< double >, std::vector< cmat > > measure` (const Eigen::MatrixBase< Derived > &A, const std::vector< cmat > &Ks, const std::vector< idx > &subsys, idx d=2)  
*Measures the part subsys of the multi-partite state vector or density matrix A using the set of Kraus operators Ks.*
- `template<typename Derived >`  
`std::tuple< idx, std::vector< double >, std::vector< cmat > > measure` (const Eigen::MatrixBase< Derived > &A, const std::initializer\_list< cmat > &Ks, const std::vector< idx > &subsys, idx d=2)  
*Measures the part subsys of the multi-partite state vector or density matrix A using the set of Kraus operators Ks.*
- `template<typename Derived >`  
`std::tuple< idx, std::vector< double >, std::vector< cmat > > measure` (const Eigen::MatrixBase< Derived > &A, const cmat &V, const std::vector< idx > &subsys, const std::vector< idx > &dims)  
*Measures the part subsys of the multi-partite state vector or density matrix A in the orthonormal basis or rank-1 POVM specified by the matrix V.*
- `template<typename Derived >`  
`std::tuple< idx, std::vector< double >, std::vector< cmat > > measure` (const Eigen::MatrixBase< Derived > &A, const cmat &V, const std::vector< idx > &subsys, idx d=2)  
*Measures the part subsys of the multi-partite state vector or density matrix A in the orthonormal basis or rank-1 POVM specified by the matrix V.*
- `template<typename Derived >`  
`std::tuple< std::vector< idx >, double, cmat > measure_seq` (const Eigen::MatrixBase< Derived > &A, std::vector< idx > subsys, std::vector< idx > dims)  
*Sequentially measures the part subsys of the multi-partite state vector or density matrix A in the computational basis.*

- `template<typename Derived >`  
`std::tuple< std::vector< idx >, double, cmat > measure\_seq (const Eigen::MatrixBase< Derived > &A,`  
`std::vector< idx > subsys, idx d=2)`  
*Sequentially measures the part subsys of the multi-partite state vector or density matrix A in the computational basis.*
- `template<typename Derived >`  
`Derived loadMATLABmatrix (const std::string &, const std::string &)`  
*Loads an Eigen dynamic matrix from a MATLAB .mat file, generic version.*
- `template<>`  
`dmat loadMATLABmatrix (const std::string &mat_file, const std::string &var_name)`  
*Loads an Eigen dynamic matrix from a MATLAB .mat file, specialization for double matrices ([qpp::dmat](#))*
- `template<>`  
`cmat loadMATLABmatrix (const std::string &mat_file, const std::string &var_name)`  
*Loads an Eigen dynamic matrix from a MATLAB .mat file, specialization for complex matrices ([qpp::cmat](#))*
- `template<typename Derived >`  
`void saveMATLABmatrix (const Eigen::MatrixBase< Derived > &, const std::string &, const std::string &,`  
`const std::string &)`  
*Saves an Eigen dynamic matrix to a MATLAB .mat file, generic version.*
- `template<>`  
`void saveMATLABmatrix (const Eigen::MatrixBase< dmat > &A, const std::string &mat_file, const std::string`  
`&var_name, const std::string &mode)`  
*Saves an Eigen dynamic matrix to a MATLAB .mat file, specialization for double matrices ([qpp::dmat](#))*
- `template<>`  
`void saveMATLABmatrix (const Eigen::MatrixBase< cmat > &A, const std::string &mat_file, const std::string`  
`&var_name, const std::string &mode)`  
*Saves an Eigen dynamic matrix to a MATLAB .mat file, specialization for complex matrices ([qpp::cmat](#))*
- `std::vector< int > x2contfrac (double x, idx N, idx cut=1e5)`  
*Simple continued fraction expansion.*
- `double contfrac2x (const std::vector< int > &cf, idx N)`  
*Real representation of a simple continued fraction.*
- `double contfrac2x (const std::vector< int > &cf)`  
*Real representation of a simple continued fraction.*
- `bigint gcd (bigint a, bigint b)`  
*Greatest common divisor of two integers.*
- `bigint gcd (const std::vector< bigint > &as)`  
*Greatest common divisor of a list of integers.*
- `bigint lcm (bigint a, bigint b)`  
*Least common multiple of two integers.*
- `bigint lcm (const std::vector< bigint > &as)`  
*Least common multiple of a list of integers.*
- `std::vector< idx > invperm (const std::vector< idx > &perm)`  
*Inverse permutation.*
- `std::vector< idx > compperm (const std::vector< idx > &perm, const std::vector< idx > &sigma)`  
*Compose permutations.*
- `std::vector< bigint > factors (bigint a)`  
*Prime factor decomposition.*
- `bigint modmul (bigint a, bigint b, bigint p)`  
*Modular multiplication without overflow.*
- `bigint modpow (bigint a, bigint n, bigint p)`  
*Fast integer power modulo p based on the SQUARE-AND-MULTIPLY algorithm.*
- `std::tuple< bigint, bigint, bigint > egcd (bigint a, bigint b)`  
*Extended greatest common divisor of two integers.*
- `bigint modinv (bigint a, bigint p)`

- Modular inverse of a mod p.*

  - `bool isprime (bigint p, idx k=80)`  
*Primality test based on the Miller-Rabin's algorithm.*
  - `bigint randprime (bigint a, bigint b, idx N=1000)`  
*Generates a random big prime uniformly distributed in the interval [a, b].*
- template<typename Derived1 , typename Derived2 >  
`dyn_mat< typename Derived1::Scalar > applyCTRL (const Eigen::MatrixBase< Derived1 > &state, const Eigen::MatrixBase< Derived2 > &A, const std::vector< idx > &ctrl, const std::vector< idx > &subsys, const std::vector< idx > &dims)`  
*Applies the controlled-gate A to the part subsys of the multi-partite state vector or density matrix state.*

template<typename Derived1 , typename Derived2 >  
`dyn_mat< typename Derived1::Scalar > applyCTRL (const Eigen::MatrixBase< Derived1 > &state, const Eigen::MatrixBase< Derived2 > &A, const std::vector< idx > &ctrl, const std::vector< idx > &subsys, idx d=2)`  
*Applies the controlled-gate A to the part subsys of the multi-partite state vector or density matrix state.*

template<typename Derived1 , typename Derived2 >  
`dyn_mat< typename Derived1::Scalar > apply (const Eigen::MatrixBase< Derived1 > &state, const Eigen::MatrixBase< Derived2 > &A, const std::vector< idx > &subsys, const std::vector< idx > &dims)`  
*Applies the gate A to the part subsys of the multi-partite state vector or density matrix state.*

template<typename Derived1 , typename Derived2 >  
`dyn_mat< typename Derived1::Scalar > apply (const Eigen::MatrixBase< Derived1 > &state, const Eigen::MatrixBase< Derived2 > &A, const std::vector< idx > &subsys, idx d=2)`  
*Applies the gate A to the part subsys of the multi-partite state vector or density matrix state.*

template<typename Derived >  
`cmat apply (const Eigen::MatrixBase< Derived > &rho, const std::vector< cmat > &Ks)`  
*Applies the channel specified by the set of Kraus operators Ks to the density matrix rho.*

template<typename Derived >  
`cmat apply (const Eigen::MatrixBase< Derived > &rho, const std::vector< cmat > &Ks, const std::vector< idx > &subsys, const std::vector< idx > &dims)`  
*Applies the channel specified by the set of Kraus operators Ks to the part subsys of the multi-partite density matrix rho.*

template<typename Derived >  
`cmat apply (const Eigen::MatrixBase< Derived > &rho, const std::vector< cmat > &Ks, const std::vector< idx > &subsys, idx d=2)`  
*Applies the channel specified by the set of Kraus operators Ks to the part subsys of the multi-partite density matrix rho.*

- `cmat kraus2super (const std::vector< cmat > &Ks)`  
*Superoperator matrix.*
- `cmat kraus2choi (const std::vector< cmat > &Ks)`  
*Choi matrix.*
- `std::vector< cmat > choi2kraus (const cmat &A)`  
*Orthogonal Kraus operators from Choi matrix.*
- `cmat choi2super (const cmat &A)`  
*Converts Choi matrix to superoperator matrix.*
- `cmat super2choi (const cmat &A)`  
*Converts superoperator matrix to Choi matrix.*
- template<typename Derived >  
`dyn_mat< typename Derived::Scalar > ptrace1 (const Eigen::MatrixBase< Derived > &A, const std::vector< idx > &dims)`  
*Partial trace.*

template<typename Derived >  
`dyn_mat< typename Derived::Scalar > ptrace2 (const Eigen::MatrixBase< Derived > &A, const std::vector< idx > &dims)`  
*Partial trace.*

- `template<typename Derived >`  
`dyn_mat< typename Derived::Scalar > ptrace` (const Eigen::MatrixBase< Derived > &A, const std::vector< `idx` > &subsys, const std::vector< `idx` > &dims)  
*Partial trace.*
- `template<typename Derived >`  
`dyn_mat< typename Derived::Scalar > ptrace` (const Eigen::MatrixBase< Derived > &A, const std::vector< `idx` > &subsys, `idx` d=2)  
*Partial trace.*
- `template<typename Derived >`  
`dyn_mat< typename Derived::Scalar > ptranspose` (const Eigen::MatrixBase< Derived > &A, const std::vector< `idx` > &subsys, const std::vector< `idx` > &dims)  
*Partial transpose.*
- `template<typename Derived >`  
`dyn_mat< typename Derived::Scalar > ptranspose` (const Eigen::MatrixBase< Derived > &A, const std::vector< `idx` > &subsys, `idx` d=2)  
*Partial transpose.*
- `template<typename Derived >`  
`dyn_mat< typename Derived::Scalar > syspermute` (const Eigen::MatrixBase< Derived > &A, const std::vector< `idx` > &perm, const std::vector< `idx` > &dims)  
*Subsystem permutation.*
- `template<typename Derived >`  
`dyn_mat< typename Derived::Scalar > syspermute` (const Eigen::MatrixBase< Derived > &A, const std::vector< `idx` > &perm, `idx` d=2)  
*Subsystem permutation.*
- `double rand` (double a, double b)  
*Generates a random real number uniformly distributed in the interval [a, b]*
- `bigint rand` (bigint a, bigint b)  
*Generates a random big integer uniformly distributed in the interval [a, b].*
- `idx randidx` (`idx` a=std::numeric\_limits< `idx` >::min(), `idx` b=std::numeric\_limits< `idx` >::max())  
*Generates a random index (idx) uniformly distributed in the interval [a, b].*
- `template<typename Derived >`  
`Derived rand` (`idx` rows, `idx` cols, double a=0, double b=1)  
*Generates a random matrix with entries uniformly distributed in the interval [a, b]*
- `template<>`  
`dmat rand` (`idx` rows, `idx` cols, double a, double b)  
*Generates a random real matrix with entries uniformly distributed in the interval [a, b], specialization for double matrices (`qpp::dmat`)*
- `template<>`  
`cmat rand` (`idx` rows, `idx` cols, double a, double b)  
*Generates a random complex matrix with entries (both real and imaginary) uniformly distributed in the interval [a, b], specialization for complex matrices (`qpp::cmat`)*
- `template<typename Derived >`  
`Derived randn` (`idx` rows, `idx` cols, double mean=0, double `sigma`=1)  
*Generates a random matrix with entries normally distributed in N(mean, sigma)*
- `template<>`  
`dmat randn` (`idx` rows, `idx` cols, double mean, double `sigma`)  
*Generates a random real matrix with entries normally distributed in N(mean, sigma), specialization for double matrices (`qpp::dmat`)*
- `template<>`  
`cmat randn` (`idx` rows, `idx` cols, double mean, double `sigma`)  
*Generates a random complex matrix with entries (both real and imaginary) normally distributed in N(mean, sigma), specialization for complex matrices (`qpp::cmat`)*
- `double randn` (double mean=0, double `sigma`=1)  
*Generates a random real number (double) normally distributed in N(mean, sigma)*



- `cmat randU (idx D)`  
*Generates a random unitary matrix.*
- `cmat randV (idx Din, idx Dout)`  
*Generates a random isometry matrix.*
- `std::vector< cmat > randkraus (idx N, idx D)`  
*Generates a set of random Kraus operators.*
- `cmat randH (idx D)`  
*Generates a random Hermitian matrix.*
- `ket randket (idx D)`  
*Generates a random normalized ket (pure state vector)*
- `cmat randrho (idx D)`  
*Generates a random density matrix.*
- `std::vector< idx > randperm (idx N)`  
*Generates a random uniformly distributed permutation.*
- `std::vector< double > uniform (idx N)`  
*Uniform probability distribution vector.*
- `std::vector< double > marginalX (const dmat &probXY)`  
*Marginal distribution.*
- `std::vector< double > marginalY (const dmat &probXY)`  
*Marginal distribution.*
- `template<typename Container >  
double avg (const std::vector< double > &prob, const Container &X, typename std::enable_if< is_iterable< Container >::value >::type != nullptr)`  
*Average.*
- `template<typename Container >  
double cov (const dmat &probXY, const Container &X, const Container &Y, typename std::enable_if< is_↵iterable< Container >::value >::type != nullptr)`  
*Covariance.*
- `template<typename Container >  
double var (const std::vector< double > &prob, const Container &X, typename std::enable_if< is_iterable< Container >::value >::type != nullptr)`  
*Variance.*
- `template<typename Container >  
double sigma (const std::vector< double > &prob, const Container &X, typename std::enable_if< is_↵iterable< Container >::value >::type != nullptr)`  
*Standard deviation.*
- `template<typename Container >  
double cor (const dmat &probXY, const Container &X, const Container &Y, typename std::enable_if< is_↵iterable< Container >::value >::type != nullptr)`  
*Correlation.*

## Variables

- `constexpr double chop = 1e-10`  
*Used in `qpp::disp()` for setting to zero numbers that have their absolute value smaller than `qpp::chop`.*
- `constexpr double eps = 1e-12`  
*Used to decide whether a number or expression in double precision is zero or not.*
- `constexpr idx maxn = 64`  
*Maximum number of allowed qu(d)its (subsystems)*
- `constexpr double pi = 3.141592653589793238462643383279502884`  
 $\pi$
- `constexpr double ee = 2.718281828459045235360287471352662497`



*Base of natural logarithm,  $e$ .*

- `constexpr double infy = std::numeric_limits<double>::infinity()`

*Used to denote infinity in double precision.*

### 6.1.1 Detailed Description

Quantum++ main namespace.

### 6.1.2 Typedef Documentation

#### 6.1.2.1 `using qpp::bigint = typedef long long int`

Big integer.

#### 6.1.2.2 `using qpp::bra = typedef Eigen::RowVectorXcd`

Complex (double precision) dynamic Eigen row vector.

#### 6.1.2.3 `using qpp::cmat = typedef Eigen::MatrixXcd`

Complex (double precision) dynamic Eigen matrix.

#### 6.1.2.4 `using qpp::cplx = typedef std::complex<double>`

Complex number in double precision.

#### 6.1.2.5 `using qpp::dmat = typedef Eigen::MatrixXd`

Real (double precision) dynamic Eigen matrix.

#### 6.1.2.6 `template<typename Scalar > using qpp::dyn_col_vect = typedef Eigen::Matrix<Scalar, Eigen::Dynamic, 1>`

Dynamic Eigen column vector over the field specified by *Scalar*.

Example:

```
// type of colvect is Eigen::Matrix<float, Eigen::Dynamic, 1>
auto colvect = dyn_col_vect<float>(2);
```

#### 6.1.2.7 `template<typename Scalar > using qpp::dyn_mat = typedef Eigen::Matrix<Scalar, Eigen::Dynamic, Eigen::Dynamic>`

Dynamic Eigen matrix over the field specified by *Scalar*.

Example:

```
// type of mat is Eigen::Matrix<float, Eigen::Dynamic, Eigen::Dynamic>
auto mat = dyn_mat<float>(2,3);
```

**6.1.2.8** `template<typename Scalar > using qpp::dyn_row_vect = typedef Eigen::Matrix<Scalar, 1, Eigen::Dynamic>`

Dynamic Eigen row vector over the field specified by *Scalar*.

Example:

```
// type of rowvect is Eigen::Matrix<float, 1, Eigen::Dynamic>
auto rowvect = dyn_row_vect<float>(3);
```

**6.1.2.9** `using qpp::idx = typedef std::size_t`

Non-negative integer index.

**6.1.2.10** `using qpp::ket = typedef Eigen::VectorXcd`

Complex (double precision) dynamic Eigen column vector.

**6.1.2.11** `template<typename... > using qpp::to_void = typedef void`

Alias template that implements the proposal for `void_t`.

See also

<http://www.open-std.org/jtc1/sc22/wg21/docs/papers/2014/n3911>

## 6.1.3 Function Documentation

**6.1.3.1** `template<typename Derived > cmat qpp::absm ( const Eigen::MatrixBase< Derived > & A )`

Matrix absolute value.

Parameters

<i>A</i>	Eigen expression
----------	------------------

Returns

Matrix absolute value of *A*

**6.1.3.2** `template<typename InputIterator > std::vector<double> qpp::abssq ( InputIterator first, InputIterator last )`

Computes the absolute values squared of an STL-like range of complex numbers.

Parameters

<i>first</i>	Iterator to the first element of the range
<i>last</i>	Iterator to the last element of the range

Returns

Real vector consisting of the range absolute values squared

**6.1.3.3** `template<typename Container > std::vector<double> qpp::abssq ( const Container & c, typename std::enable_if< is_iterable< Container >::value >::type * = nullptr )`

Computes the absolute values squared of an STL-like container.

## Parameters

<i>c</i>	STL-like container
----------	--------------------

## Returns

Real vector consisting of the container's absolute values squared

6.1.3.4 `template<typename Derived > std::vector<double> qpp::abssq ( const Eigen::MatrixBase< Derived > & A )`

Computes the absolute values squared of an Eigen expression.

## Parameters

<i>A</i>	Eigen expression
----------	------------------

## Returns

Real vector consisting of the absolute values squared

6.1.3.5 `template<typename Derived > dyn_mat<typename Derived::Scalar> qpp::adjoint ( const Eigen::MatrixBase< Derived > & A )`

Adjoint.

## Parameters

<i>A</i>	Eigen expression
----------	------------------

## Returns

Adjoint (Hermitian conjugate) of *A*, as a dynamic matrix over the same scalar field as *A*

6.1.3.6 `template<typename Derived1 , typename Derived2 > dyn_mat<typename Derived1::Scalar> qpp::anticomm ( const Eigen::MatrixBase< Derived1 > & A, const Eigen::MatrixBase< Derived2 > & B )`

Anti-commutator.

## See also

[qpp::comm\(\)](#)

Anti-commutator  $\{A, B\} = AB + BA$ . Both *A* and *B* must be Eigen expressions over the same scalar field.

## Parameters

<i>A</i>	Eigen expression
<i>B</i>	Eigen expression

## Returns

Anti-commutator  $AB + BA$ , as a dynamic matrix over the same scalar field as *A*

6.1.3.7 `template<typename Derived1 , typename Derived2 > dyn_mat<typename Derived1::Scalar> qpp::apply ( const Eigen::MatrixBase< Derived1 > & state, const Eigen::MatrixBase< Derived2 > & A, const std::vector< idx > & subsys, const std::vector< idx > & dims )`

Applies the gate *A* to the part *subsys* of the multi-partite state vector or density matrix *state*.

#### Note

The dimension of the gate *A* must match the dimension of *subsys*

#### Parameters

<i>state</i>	Eigen expression
<i>A</i>	Eigen expression
<i>subsys</i>	Subsystem indexes where the gate <i>A</i> is applied
<i>dims</i>	Dimensions of the multi-partite system

#### Returns

Gate *A* applied to the part *subsys* of *state*

6.1.3.8 `template<typename Derived1 , typename Derived2 > dyn_mat<typename Derived1::Scalar> qpp::apply ( const Eigen::MatrixBase< Derived1 > & state, const Eigen::MatrixBase< Derived2 > & A, const std::vector< idx > & subsys, idx d = 2 )`

Applies the gate *A* to the part *subsys* of the multi-partite state vector or density matrix *state*.

#### Note

The dimension of the gate *A* must match the dimension of *subsys*

#### Parameters

<i>state</i>	Eigen expression
<i>A</i>	Eigen expression
<i>subsys</i>	Subsystem indexes where the gate <i>A</i> is applied
<i>d</i>	Subsystem dimensions

#### Returns

Gate *A* applied to the part *subsys* of *state*

6.1.3.9 `template<typename Derived > cmat qpp::apply ( const Eigen::MatrixBase< Derived > & rho, const std::vector< cmat > & Ks )`

Applies the channel specified by the set of Kraus operators *Ks* to the density matrix *rho*.

#### Parameters

<i>rho</i>	Eigen expression
<i>Ks</i>	Set of Kraus operators

#### Returns

Output density matrix after the action of the channel

6.1.3.10 `template<typename Derived> cmat qpp::apply ( const Eigen::MatrixBase< Derived> & rho, const std::vector< cmat> & Ks, const std::vector< idx> & subsys, const std::vector< idx> & dims )`

Applies the channel specified by the set of Kraus operators *Ks* to the part *subsys* of the multi-partite density matrix *rho*.

## Parameters

<i>rho</i>	Eigen expression
<i>Ks</i>	Set of Kraus operators
<i>subsys</i>	Subsystem indexes where the Kraus operators <i>Ks</i> are applied
<i>dims</i>	Dimensions of the multi-partite system

## Returns

Output density matrix after the action of the channel

6.1.3.11 `template<typename Derived> cmat qpp::apply ( const Eigen::MatrixBase< Derived > & rho, const std::vector< cmat > & Ks, const std::vector< idx > & subsys, idx d = 2 )`

Applies the channel specified by the set of Kraus operators *Ks* to the part *subsys* of the multi-partite density matrix *rho*.

## Parameters

<i>rho</i>	Eigen expression
<i>Ks</i>	Set of Kraus operators
<i>subsys</i>	Subsystem indexes where the Kraus operators <i>Ks</i> are applied
<i>d</i>	Subsystem dimensions

## Returns

Output density matrix after the action of the channel

6.1.3.12 `template<typename Derived1, typename Derived2> dyn_mat<typename Derived1::Scalar> qpp::applyCTRL ( const Eigen::MatrixBase< Derived1 > & state, const Eigen::MatrixBase< Derived2 > & A, const std::vector< idx > & ctrl, const std::vector< idx > & subsys, const std::vector< idx > & dims )`

Applies the controlled-gate *A* to the part *subsys* of the multi-partite state vector or density matrix *state*.

## See also

[qpp::Gates::CTRL\(\)](#)

## Note

The dimension of the gate *A* must match the dimension of *subsys*. Also, all control subsystems in *ctrl* must have the same dimension.

## Parameters

<i>state</i>	Eigen expression
<i>A</i>	Eigen expression
<i>ctrl</i>	Control subsystem indexes
<i>subsys</i>	Subsystem indexes where the gate <i>A</i> is applied
<i>dims</i>	Dimensions of the multi-partite system

## Returns

CTRL-A gate applied to the part *subsys* of *state*

6.1.3.13 `template<typename Derived1 , typename Derived2 > dyn_mat<typename Derived1::Scalar> qpp::applyCTRL ( const Eigen::MatrixBase< Derived1 > & state, const Eigen::MatrixBase< Derived2 > & A, const std::vector< idx > & ctrl, const std::vector< idx > & subsys, idx d = 2 )`

Applies the controlled-gate *A* to the part *subsys* of the multi-partite state vector or density matrix *state*.

See also

[qpp::Gates::CTRL\(\)](#)

Note

The dimension of the gate *A* must match the dimension of *subsys*

Parameters

<i>state</i>	Eigen expression
<i>A</i>	Eigen expression
<i>ctrl</i>	Control subsystem indexes
<i>subsys</i>	Subsystem indexes where the gate <i>A</i> is applied
<i>d</i>	Subsystem dimensions

Returns

CTRL-A gate applied to the part *subsys* of *state*

6.1.3.14 `template<typename Container > double qpp::avg ( const std::vector< double > & prob, const Container & X, typename std::enable_if< is_iterable< Container >::value >::type * = nullptr )`

Average.

Parameters

<i>prob</i>	Real probability vector representing the probability distribution of <i>X</i>
<i>X</i>	Random variable values represented by an STL-like container

Returns

Average of *X*

6.1.3.15 `cmat qpp::bloch2rho ( const std::vector< double > & r ) [inline]`

Computes the density matrix corresponding to the 3-dimensional real Bloch vector *r*.

See also

[qpp::rho2bloch\(\)](#)

Parameters

<i>r</i>	3-dimensional real vector
----------	---------------------------

Returns

Qubit density matrix

6.1.3.16 `std::vector<cmat> qpp::choi2kraus ( const cmat & A ) [inline]`

Orthogonal Kraus operators from Choi matrix.

See also

[qpp::kraus2choi\(\)](#)

Extracts a set of orthogonal (under Hilbert-Schmidt operator norm) Kraus operators from the Choi matrix  $A$

Note

The Kraus operators satisfy  $Tr(K_i^\dagger K_j) = \delta_{ij}$  for all  $i \neq j$

Parameters

$A$	Choi matrix
-----	-------------

Returns

Set of orthogonal Kraus operators

6.1.3.17 `cmat qpp::choi2super ( const cmat & A ) [inline]`

Converts Choi matrix to superoperator matrix.

See also

[qpp::super2choi\(\)](#)

Parameters

$A$	Choi matrix
-----	-------------

Returns

Superoperator matrix

6.1.3.18 `template<typename Derived1 , typename Derived2 > dyn_mat<typename Derived1::Scalar> qpp::comm ( const Eigen::MatrixBase< Derived1 > & A, const Eigen::MatrixBase< Derived2 > & B )`

Commutator.

See also

[qpp::anticomm\(\)](#)

Commutator  $[A, B] = AB - BA$ . Both  $A$  and  $B$  must be Eigen expressions over the same scalar field.

Parameters

$A$	Eigen expression
$B$	Eigen expression

Returns

Commutator  $AB - BA$ , as a dynamic matrix over the same scalar field as  $A$

6.1.3.19 `template<typename T> std::vector<T> qpp::complement ( std::vector< T > subsys, idx N )`

Constructs the complement of a subsystem vector.



## Parameters

<i>subsys</i>	Subsystem vector
<i>N</i>	Total number of systems

## Returns

The complement of *subsys* with respect to the set  $\{0, 1, \dots, N - 1\}$

**6.1.3.20** `std::vector<idx> qpp::compperm ( const std::vector< idx > & perm, const std::vector< idx > & sigma )`  
`[inline]`

Compose permutations.

## Parameters

<i>perm</i>	Permutation
<i>sigma</i>	Permutation

## Returns

Composition of the permutations  $perm \circ sigma = perm(sigma)$

**6.1.3.21** `template<typename Derived> double qpp::concurrence ( const Eigen::MatrixBase< Derived > & A )`

Wootters concurrence of the bi-partite qubit mixed state *A*.

## Parameters

<i>A</i>	Eigen expression
----------	------------------

## Returns

Wootters concurrence

**6.1.3.22** `template<typename Derived> dyn_mat<typename Derived::Scalar> qpp::conjugate ( const Eigen::MatrixBase< Derived > & A )`

Complex conjugate.

## Parameters

<i>A</i>	Eigen expression
----------	------------------

## Returns

Complex conjugate of *A*, as a dynamic matrix over the same scalar field as *A*

**6.1.3.23** `double qpp::contfrac2x ( const std::vector< int > & cf, idx N )` `[inline]`

Real representation of a simple continued fraction.

See also

[qpp::x2contfrac\(\)](#)

## Parameters

<i>cf</i>	Integer vector containing the simple continued fraction expansion
<i>N</i>	Number of terms considered in the continued fraction expansion. If <i>N</i> is greater than the size of <i>cf</i> , then all terms in <i>cf</i> are considered.

## Returns

Real representation of the simple continued fraction

6.1.3.24 `double qpp::contfrac2x ( const std::vector< int > & cf ) [inline]`

Real representation of a simple continued fraction.

## See also

[qpp::x2contfrac\(\)](#)

## Parameters

<i>cf</i>	Integer vector containing the simple continued fraction expansion
-----------	-------------------------------------------------------------------

## Returns

Real representation of the simple continued fraction

6.1.3.25 `template<typename Container > double qpp::cor ( const dmat & probXY, const Container & X, const Container & Y, typename std::enable_if< is_iterable< Container >::value >::type * = nullptr )`

Correlation.

## Parameters

<i>probXY</i>	Real matrix representing the joint probability distribution of <i>X</i> and <i>Y</i> in lexicographical order ( <i>X</i> labels the rows, <i>Y</i> labels the columns)
<i>X</i>	Random variable values represented by an STL-like container
<i>Y</i>	Random variable values represented by an STL-like container

## Returns

Correlation of *X* and *Y*

6.1.3.26 `template<typename Derived > cmat qpp::cosm ( const Eigen::MatrixBase< Derived > & A )`

Matrix cos.

## Parameters

<i>A</i>	Eigen expression
----------	------------------

## Returns

Matrix cosine of *A*

6.1.3.27 `template<typename Container > double qpp::cov ( const dmat & probXY, const Container & X, const Container & Y, typename std::enable_if< is_iterable< Container >::value >::type * = nullptr )`

Covariance.

## Parameters

<i>probXY</i>	Real matrix representing the joint probability distribution of $X$ and $Y$ in lexicographical order ( $X$ labels the rows, $Y$ labels the columns)
$X$	Random variable values represented by an STL-like container
$Y$	Random variable values represented by an STL-like container

## Returns

Covariance of  $X$  and  $Y$

6.1.3.28 `template<typename OutputScalar, typename Derived> dyn_mat<OutputScalar> qpp::cwise ( const Eigen::MatrixBase< Derived> & A, OutputScalar (*)(const typename Derived::Scalar &) f )`

Functor.

## Parameters

$A$	Eigen expression
$f$	Pointer-to-function from scalars of $A$ to <i>OutputScalar</i>

## Returns

Component-wise  $f(A)$ , as a dynamic matrix over the *OutputScalar* scalar field

6.1.3.29 `template<typename Derived> Derived::Scalar qpp::det ( const Eigen::MatrixBase< Derived> & A )`

Determinant.

## Parameters

$A$	Eigen expression
-----	------------------

## Returns

Determinant of  $A$ , as a scalar over the same scalar field as  $A$ . Returns  $\pm\infty$  when the determinant overflows/underflows.

6.1.3.30 `template<typename T> dyn_mat<typename T::Scalar> qpp::dirsum ( const T & head )`

Direct sum.

See also

[qpp::dirsumpow\(\)](#)

Used to stop the recursion for the variadic template version of [qpp::dirsum\(\)](#)

## Parameters

<i>head</i>	Eigen expression
-------------	------------------

## Returns

Its argument *head*

6.1.3.31 `template<typename T, typename... Args> dyn_mat<typename T::Scalar> qpp::dirsum ( const T & head, const Args &... tail )`

Direct sum.

See also

[qpp::dirsumpow\(\)](#)

Parameters

<i>head</i>	Eigen expression
<i>tail</i>	Variadic Eigen expression (zero or more parameters)

Returns

Direct sum of all input parameters, evaluated from left to right, as a dynamic matrix over the same scalar field as its arguments

6.1.3.32 `template<typename Derived > dyn_mat<typename Derived::Scalar> qpp::dirsum ( const std::vector< Derived > & As )`

Direct sum.

See also

[qpp::dirsumpow\(\)](#)

Parameters

<i>As</i>	std::vector of Eigen expressions
-----------	----------------------------------

Returns

Direct sum of all elements in *As*, evaluated from left to right, as a dynamic matrix over the same scalar field as its arguments

6.1.3.33 `template<typename Derived > dyn_mat<typename Derived::Scalar> qpp::dirsum ( const std::initializer_list< Derived > & As )`

Direct sum.

See also

[qpp::dirsumpow\(\)](#)

Parameters

<i>As</i>	std::initializer_list of Eigen expressions, such as { <i>A1</i> , <i>A2</i> , ... , <i>Ak</i> }
-----------	-------------------------------------------------------------------------------------------------

Returns

Direct sum of all elements in *As*, evaluated from left to right, as a dynamic matrix over the same scalar field as its arguments

6.1.3.34 `template<typename Derived > dyn_mat<typename Derived::Scalar> qpp::dirsumpow ( const Eigen::MatrixBase< Derived > & A, idx n )`

Direct sum power.

See also

[qpp::dirsum\(\)](#)

Parameters

$A$	Eigen expression
$n$	Non-negative integer

Returns

Direct sum of  $A$  with itself  $n$  times  $A^{\oplus n}$ , as a dynamic matrix over the same scalar field as  $A$

6.1.3.35 `template<typename Derived > internal::IOManipEigen qpp::disp ( const Eigen::MatrixBase< Derived > & A, double chop = qpp::chop )`

Eigen expression ostream manipulator.

Parameters

$A$	Eigen expression
$chop$	Set to zero the elements smaller in absolute value than $chop$

Returns

Instance of `qpp::internal::internal::IOManipEigen`

6.1.3.36 `internal::IOManipEigen qpp::disp ( cplx z, double chop = qpp::chop ) [inline]`

Complex number ostream manipulator.

Parameters

$z$	Complex number (or any other type implicitly cast-able to <code>std::complex&lt;double&gt;</code> )
$chop$	Set to zero the elements smaller in absolute value than $chop$

Returns

Instance of `qpp::internal::internal::IOManipEigen`

6.1.3.37 `template<typename InputIterator > internal::IOManipRange<InputIterator> qpp::disp ( InputIterator first, InputIterator last, const std::string & separator, const std::string & start = " [ ", const std::string & end = " ] " )`

Range ostream manipulator.

Parameters

<i>first</i>	Iterator to the first element of the range
<i>last</i>	Iterator to the last element of the range
<i>separator</i>	Separator
<i>start</i>	Left marking
<i>end</i>	Right marking

**Returns**

Instance of `qpp::internal::internal::IOManipRange`

**6.1.3.38** `template<typename Container > internal::IOManipRange<typename Container::const_iterator> qpp::disp ( const Container & c, const std::string & separator, const std::string & start = " [ ", const std::string & end = " ] ", typename std::enable_if< is_iterable< Container >::value >::type * = nullptr )`

Standard container ostream manipulator. The container must support `std::begin()`, `std::end()` and forward iteration.

**Parameters**

<i>c</i>	Container
<i>separator</i>	Separator
<i>start</i>	Left marking
<i>end</i>	Right marking

**Returns**

Instance of `qpp::internal::internal::IOManipRange`

**6.1.3.39** `template<typename PointerType > internal::IOManipPointer<PointerType> qpp::disp ( const PointerType * p, idx N, const std::string & separator, const std::string & start = " [ ", const std::string & end = " ] " )`

C-style pointer ostream manipulator.

**Parameters**

<i>p</i>	Pointer to the first element
<i>N</i>	Number of elements to be displayed
<i>separator</i>	Separator
<i>start</i>	Left marking
<i>end</i>	Right marking

**Returns**

Instance of `qpp::internal::internal::IOManipPointer`

**6.1.3.40** `std::tuple<bigint, bigint, bigint> qpp::egcd ( bigint a, bigint b ) [inline]`

Extended greatest common divisor of two integers.

**See also**

[qpp::gcd\(\)](#)

## Parameters

<i>a</i>	Integer
<i>b</i>	Integer

## Returns

Tuple of: 1. Integer  $m$ , 2. Integer  $n$ , and 3. Non-negative integer  $\gcd(a, b)$  such that  $ma + nb = \gcd(a, b)$

6.1.3.41 `template<typename Derived> std::pair<dyn_col_vect<cplx>, cmat> qpp::eig ( const Eigen::MatrixBase<Derived> & A )`

Full eigen decomposition.

See also

[qpp::heig\(\)](#)

## Parameters

<i>A</i>	Eigen expression
----------	------------------

## Returns

Pair of: 1. Eigenvalues of  $A$ , as a complex dynamic column vector, and 2. Eigenvectors of  $A$ , as columns of a complex dynamic matrix

6.1.3.42 `template<typename Derived> double qpp::entanglement ( const Eigen::MatrixBase<Derived> & A, const std::vector<idx> & dims )`

Entanglement of the bi-partite pure state  $A$ .

Defined as the von-Neumann entropy of the reduced density matrix of one of the subsystems

See also

[qpp::entropy\(\)](#)

## Parameters

<i>A</i>	Eigen expression
<i>dims</i>	Dimensions of the bi-partite system

## Returns

Entanglement, with the logarithm in base 2

6.1.3.43 `template<typename Derived> double qpp::entropy ( const Eigen::MatrixBase<Derived> & A )`

von-Neumann entropy of the density matrix  $A$

## Parameters

$A$	Eigen expression
-----	------------------

## Returns

von-Neumann entropy, with the logarithm in base 2

**6.1.3.44** `double qpp::entropy ( const std::vector< double > & prob )` `[inline]`

Shannon entropy of the probability distribution *prob*.

## Parameters

<i>prob</i>	Real probability vector
-------------	-------------------------

## Returns

Shannon entropy, with the logarithm in base 2

**6.1.3.45** `template<typename Derived > dyn_col_vect<cplx> qpp::evals ( const Eigen::MatrixBase< Derived > & A )`

Eigenvalues.

## See also

[qpp::hevals\(\)](#)

## Parameters

$A$	Eigen expression
-----	------------------

## Returns

Eigenvalues of  $A$ , as a complex dynamic column vector

**6.1.3.46** `template<typename Derived > cmat qpp::evecs ( const Eigen::MatrixBase< Derived > & A )`

Eigenvectors.

## See also

[qpp::hevecs\(\)](#)

## Parameters

$A$	Eigen expression
-----	------------------

## Returns

Eigenvectors of  $A$ , as columns of a complex dynamic matrix

**6.1.3.47** `template<typename Derived > cmat qpp::expm ( const Eigen::MatrixBase< Derived > & A )`

Matrix exponential.



## Parameters

$A$	Eigen expression
-----	------------------

## Returns

Matrix exponential of  $A$

**6.1.3.48** `std::vector<bigint> qpp::factors ( bigint a )` `[inline]`

Prime factor decomposition.

## Note

Runs in  $\mathcal{O}(\sqrt{n})$  time complexity

## Parameters

$a$	Integer different from 0, 1 or -1
-----	-----------------------------------

## Returns

Integer vector containing the factors

**6.1.3.49** `template<typename Derived > cmat qpp::funm ( const Eigen::MatrixBase< Derived > & A, cplx(*) (const cplx &) f )`

Functional calculus  $f(A)$

## Parameters

$A$	Eigen expression
$f$	Pointer-to-function from complex to complex

## Returns

$f(A)$

**6.1.3.50** `bigint qpp::gcd ( bigint a, bigint b )` `[inline]`

Greatest common divisor of two integers.

## See also

[qpp::lcm\(\)](#)

## Parameters

$a$	Integer
$b$	Integer

## Returns

Greatest common divisor of  $a$  and  $b$

6.1.3.51 `bigint qpp::gcd ( const std::vector< bigint > & as ) [inline]`

Greatest common divisor of a list of integers.

See also

[qpp::lcm\(\)](#)

Parameters

<code>as</code>	List of integers
-----------------	------------------

Returns

Greatest common divisor of all numbers in `as`

6.1.3.52 `template<typename Derived > double qpp::gconcurrence ( const Eigen::MatrixBase< Derived > & A )`

G-concurrence of the bi-partite pure state  $A$ .

Note

Both local dimensions must be equal

Uses [qpp::logdet\(\)](#) to avoid overflows

See also

[qpp::logdet\(\)](#)

Parameters

<code>A</code>	Eigen expression
----------------	------------------

Returns

G-concurrence

6.1.3.53 `template<typename Derived > dyn_mat<typename Derived::Scalar> qpp::grams ( const std::vector< Derived > & Vs )`

Gram-Schmidt orthogonalization.

Parameters

<code>Vs</code>	std::vector of Eigen expressions as column vectors
-----------------	----------------------------------------------------

Returns

Gram-Schmidt vectors of  $Vs$  as columns of a dynamic matrix over the same scalar field as its arguments

6.1.3.54 `template<typename Derived > dyn_mat<typename Derived::Scalar> qpp::grams ( const std::initializer_list< Derived > & Vs )`

Gram-Schmidt orthogonalization.

## Parameters

$V$ s	std::initializer_list of Eigen expressions as column vectors
-------	--------------------------------------------------------------

## Returns

Gram-Schmidt vectors of  $V$ s as columns of a dynamic matrix over the same scalar field as its arguments

6.1.3.55 `template<typename Derived> dyn_mat<typename Derived::Scalar> qpp::grams ( const Eigen::MatrixBase<Derived> & A )`

Gram-Schmidt orthogonalization.

## Parameters

$A$	Eigen expression, the input vectors are the columns of $A$
-----	------------------------------------------------------------

## Returns

Gram-Schmidt vectors of the columns of  $A$ , as columns of a dynamic matrix over the same scalar field as  $A$

6.1.3.56 `template<typename Derived> std::pair<dyn_col_vect<double>, cmat> qpp::heig ( const Eigen::MatrixBase<Derived> & A )`

Full eigen decomposition of Hermitian expression.

## See also

[qpp::eig\(\)](#)

## Parameters

$A$	Eigen expression
-----	------------------

## Returns

Pair of: 1. Eigenvalues of  $A$ , as a real dynamic column vector, and 2. Eigenvectors of  $A$ , as columns of a complex dynamic matrix

6.1.3.57 `template<typename Derived> dyn_col_vect<double> qpp::hevals ( const Eigen::MatrixBase<Derived> & A )`

Hermitian eigenvalues.

## See also

[qpp::evals\(\)](#)

## Parameters

$A$	Eigen expression
-----	------------------

## Returns

Eigenvalues of Hermitian  $A$ , as a real dynamic column vector

6.1.3.58 `template<typename Derived > cmat qpp::hevects ( const Eigen::MatrixBase< Derived > & A )`

Hermitian eigenvectors.

See also

[qpp::evects\(\)](#)

Parameters

<i>A</i>	Eigen expression
----------	------------------

Returns

Eigenvectors of Hermitian *A*, as columns of a complex matrix

6.1.3.59 `template<typename Derived > dyn_mat<typename Derived::Scalar> qpp::inverse ( const Eigen::MatrixBase< Derived > & A )`

Inverse.

Parameters

<i>A</i>	Eigen expression
----------	------------------

Returns

Inverse of *A*, as a dynamic matrix over the same scalar field as *A*

6.1.3.60 `std::vector<idx> qpp::invperm ( const std::vector< idx > & perm ) [inline]`

Inverse permutation.

Parameters

<i>perm</i>	Permutation
-------------	-------------

Returns

Inverse of the permutation *perm*

6.1.3.61 `template<typename Derived > dyn_col_vect<typename Derived::Scalar> qpp::ip ( const Eigen::MatrixBase< Derived > & phi, const Eigen::MatrixBase< Derived > & psi, const std::vector< idx > & subsys, const std::vector< idx > & dims )`

Generalized inner product.

Parameters

<i>phi</i>	Column vector Eigen expression
<i>psi</i>	Column vector Eigen expression
<i>subsys</i>	Subsystem indexes over which <i>phi</i> is defined

<i>dims</i>	Dimensions of the multi-partite system
-------------	----------------------------------------

**Returns**

The inner product  $\langle \phi_{subsys} | \psi \rangle$ , as a scalar or column vector over the remaining Hilbert space

**6.1.3.62** `template<typename Derived> dyn_col_vect<typename Derived::Scalar> qpp::ip ( const Eigen::MatrixBase<Derived> & phi, const Eigen::MatrixBase<Derived> & psi, const std::vector<idx> & subsys, idx d = 2 )`

Generalized inner product.

**Parameters**

<i>phi</i>	Column vector Eigen expression
<i>psi</i>	Column vector Eigen expression
<i>subsys</i>	Subsystem indexes over which <i>phi</i> is defined
<i>d</i>	Subsystem dimensions

**Returns**

The inner product  $\langle \phi_{subsys} | \psi \rangle$ , as a scalar or column vector over the remaining Hilbert space

**6.1.3.63** `bool qpp::isprime ( bigint p, idx k = 80 ) [inline]`

Primality test based on the Miller-Rabin's algorithm.

**Parameters**

<i>p</i>	Integer different from 0, 1 or -1
<i>k</i>	Number of iterations. The probability of a false positive is $2^{-k}$ .

**Returns**

True if the number is (most-likely) prime, false otherwise

**6.1.3.64** `cmat qpp::kraus2choi ( const std::vector< cmat > & Ks ) [inline]`

Choi matrix.

**See also**

[qpp::choi2kraus\(\)](#)

Constructs the Choi matrix of the channel specified by the set of Kraus operators *Ks* in the standard operator basis  $\{|i\rangle\langle j|\}$  ordered in lexicographical order, i.e.  $|0\rangle\langle 0|$ ,  $|0\rangle\langle 1|$  etc.

**Note**

The superoperator matrix *S* and the Choi matrix *C* are related by  $S_{ab,mn} = C_{ma,nb}$

## Parameters

<i>Ks</i>	Set of Kraus operators
-----------	------------------------

## Returns

Choi matrix

**6.1.3.65** `cmat qpp::kraus2super ( const std::vector< cmat > & Ks ) [inline]`

Superoperator matrix.

Constructs the superoperator matrix of the channel specified by the set of Kraus operators *Ks* in the standard operator basis  $\{|i\rangle\langle j|\}$  ordered in lexicographical order, i.e.  $|0\rangle\langle 0|$ ,  $|0\rangle\langle 1|$  etc.

## Parameters

<i>Ks</i>	Set of Kraus operators
-----------	------------------------

## Returns

Superoperator matrix

**6.1.3.66** `template<typename T> dyn_mat<typename T::Scalar> qpp::kron ( const T & head )`

Kronecker product.

See also

[qpp::kronpow\(\)](#)

Used to stop the recursion for the variadic template version of [qpp::kron\(\)](#)

## Parameters

<i>head</i>	Eigen expression
-------------	------------------

## Returns

Its argument *head*

**6.1.3.67** `template<typename T, typename... Args> dyn_mat<typename T::Scalar> qpp::kron ( const T & head, const Args &... tail )`

Kronecker product.

See also

[qpp::kronpow\(\)](#)

## Parameters

<i>head</i>	Eigen expression
<i>tail</i>	Variadic Eigen expression (zero or more parameters)

**Returns**

Kronecker product of all input parameters, evaluated from left to right, as a dynamic matrix over the same scalar field as its arguments

**6.1.3.68** `template<typename Derived > dyn_mat<typename Derived::Scalar> qpp::kron ( const std::vector< Derived > & As )`

Kronecker product.

**See also**

[qpp::kronpow\(\)](#)

**Parameters**

<i>As</i>	std::vector of Eigen expressions
-----------	----------------------------------

**Returns**

Kronecker product of all elements in *As*, evaluated from left to right, as a dynamic matrix over the same scalar field as its arguments

**6.1.3.69** `template<typename Derived > dyn_mat<typename Derived::Scalar> qpp::kron ( const std::initializer_list< Derived > & As )`

Kronecker product.

**See also**

[qpp::kronpow\(\)](#)

**Parameters**

<i>As</i>	std::initializer_list of Eigen expressions, such as {A1, A2, ... ,Ak}
-----------	-----------------------------------------------------------------------

**Returns**

Kronecker product of all elements in *As*, evaluated from left to right, as a dynamic matrix over the same scalar field as its arguments

**6.1.3.70** `template<typename Derived > dyn_mat<typename Derived::Scalar> qpp::kronpow ( const Eigen::MatrixBase< Derived > & A, idx n )`

Kronecker power.

**See also**

[qpp::kron\(\)](#)

## Parameters

$A$	Eigen expression
$n$	Non-negative integer

## Returns

Kronecker product of  $A$  with itself  $n$  times  $A^{\otimes n}$ , as a dynamic matrix over the same scalar field as  $A$

### 6.1.3.71 `bigint qpp::lcm ( bigint a, bigint b )` [inline]

Least common multiple of two integers.

## See also

[qpp::gcd\(\)](#)

## Parameters

$a$	Integer
$b$	Integer

## Returns

Least common multiple of  $a$  and  $b$

### 6.1.3.72 `bigint qpp::lcm ( const std::vector< bigint > & as )` [inline]

Least common multiple of a list of integers.

## See also

[qpp::gcd\(\)](#)

## Parameters

$as$	List of integers
------	------------------

## Returns

Least common multiple of all numbers in  $as$

### 6.1.3.73 `template<typename Derived> dyn_mat<typename Derived::Scalar> qpp::load ( const std::string & fname )`

Loads Eigen matrix from a binary file (internal format) in double precision.

## See also

[qpp::save\(\)](#)

The template parameter cannot be automatically deduced and must be explicitly provided, depending on the scalar field of the matrix that is being loaded.

## Example:

```
// loads a previously saved Eigen dynamic complex matrix from "input.bin"
auto mat = load<cmat>("input.bin");
```



## Parameters

<i>fname</i>	Output file name
--------------	------------------

6.1.3.74 `template<typename Derived > Derived qpp::loadMATLABmatrix ( const std::string & , const std::string & )`

Loads an Eigen dynamic matrix from a MATLAB .mat file, generic version.

See also

[qpp::saveMATLABmatrix\(\)](#)

This is the generic version that always throws [qpp::Exception::Type::UNDEFINED\\_TYPE](#). It is specialized only for [qpp::dmat](#) and [qpp::cmat](#) (the only matrix types that can be loaded)

6.1.3.75 `template<> dmat qpp::loadMATLABmatrix ( const std::string & mat_file, const std::string & var_name )`  
[inline]

Loads an Eigen dynamic matrix from a MATLAB .mat file, specialization for double matrices ([qpp::dmat](#))

See also

[qpp::saveMATLABmatrix\(\)](#)

The template parameter cannot be automatically deduced and must be explicitly provided

Example:

```
// loads a previously saved Eigen dynamic double matrix
// from the MATLAB file "input.mat"
auto mat = loadMATLABmatrix<dmat>("input.mat");
```

## Note

If *var\_name* is a complex matrix, only the real part is loaded

## Parameters

<i>mat_file</i>	MATALB .mat file
<i>var_name</i>	Variable name in the .mat file representing the matrix to be loaded

## Returns

Eigen double dynamic matrix ([qpp::dmat](#))

6.1.3.76 `template<> cmat qpp::loadMATLABmatrix ( const std::string & mat_file, const std::string & var_name )`  
[inline]

Loads an Eigen dynamic matrix from a MATLAB .mat file, specialization for complex matrices ([qpp::cmat](#))

See also

[qpp::saveMATLABmatrix\(\)](#)

The template parameter cannot be automatically deduced and must be explicitly provided

Example:

```
// loads a previously saved Eigen dynamic complex matrix
// from the MATLAB file "input.mat"
auto mat = loadMATLABmatrix<cmat>("input.mat");
```

## Parameters

<i>mat_file</i>	MATALB .mat file
<i>var_name</i>	Variable name in the .mat file representing the matrix to be loaded

## Returns

Eigen complex dynamic matrix ([qpp::cmat](#))

6.1.3.77 `template<typename Derived> Derived::Scalar qpp::logdet ( const Eigen::MatrixBase< Derived > & A )`

Logarithm of the determinant.

Useful when the determinant overflows/underflows

## Parameters

<i>A</i>	Eigen expression
----------	------------------

## Returns

Logarithm of the determinant of *A*, as a scalar over the same scalar field as *A*

6.1.3.78 `template<typename Derived> cmat qpp::logm ( const Eigen::MatrixBase< Derived > & A )`

Matrix logarithm.

## Parameters

<i>A</i>	Eigen expression
----------	------------------

## Returns

Matrix logarithm of *A*

6.1.3.79 `template<typename Derived> double qpp::lognegativity ( const Eigen::MatrixBase< Derived > & A, const std::vector< idx > & dims )`

Logarithmic negativity of the bi-partite mixed state *A*.

## Parameters

<i>A</i>	Eigen expression
<i>dims</i>	Dimensions of the bi-partite system

## Returns

Logarithmic negativity, with the logarithm in base 2

6.1.3.80 `std::vector<double> qpp::marginalX ( const dmat & probXY ) [inline]`

Marginal distribution.

## Parameters

<i>probXY</i>	Real matrix representing the joint probability distribution of $X$ and $Y$ in lexicographical order ( $X$ labels the rows, $Y$ labels the columns)
---------------	----------------------------------------------------------------------------------------------------------------------------------------------------

## Returns

Real vector consisting of the marginal distribution of  $X$

6.1.3.81 `std::vector<double> qpp::marginalY ( const dmat & probXY ) [inline]`

Marginal distribution.

## Parameters

<i>probXY</i>	Real matrix representing the joint probability distribution of $X$ and $Y$ in lexicographical order ( $X$ labels the rows, $Y$ labels the columns)
---------------	----------------------------------------------------------------------------------------------------------------------------------------------------

## Returns

Real vector consisting of the marginal distribution of  $Y$

6.1.3.82 `template<typename Derived > std::tuple<idx, std::vector<double>, std::vector<cmat> > qpp::measure ( const Eigen::MatrixBase< Derived > & A, const std::vector< cmat > & Ks )`

Measures the state  $A$  using the set of Kraus operators  $Ks$ .

## Parameters

$A$	Eigen expression
$Ks$	Set of Kraus operators

## Returns

Tuple of: 1. Result of the measurement, 2. Vector of outcome probabilities, and 3. Vector of post-measurement normalized states

6.1.3.83 `template<typename Derived > std::tuple<idx, std::vector<double>, std::vector<cmat> > qpp::measure ( const Eigen::MatrixBase< Derived > & A, const std::initializer_list< cmat > & Ks )`

Measures the state  $A$  using the set of Kraus operators  $Ks$ .

## Parameters

$A$	Eigen expression
$Ks$	Set of Kraus operators

## Returns

Tuple of: 1. Result of the measurement, 2. Vector of outcome probabilities, and 3. Vector of post-measurement normalized states

6.1.3.84 `template<typename Derived > std::tuple<idx, std::vector<double>, std::vector<cmat> > qpp::measure ( const Eigen::MatrixBase< Derived > & A, const cmat & U )`

Measures the state  $A$  in the orthonormal basis specified by the unitary matrix  $U$ .

## Parameters

$A$	Eigen expression
$U$	Unitary matrix whose columns represent the measurement basis vectors

## Returns

Tuple of: 1. Result of the measurement, 2. Vector of outcome probabilities, and 3. Vector of post-measurement normalized states

```
6.1.3.85  template<typename Derived > std::tuple<idx, std::vector<double>, std::vector<cmat> > qpp::measure ( const
Eigen::MatrixBase< Derived > & A, const std::vector< cmat > & Ks, const std::vector< idx > & subsys, const
std::vector< idx > & dims )
```

Measures the part *subsys* of the multi-partite state vector or density matrix *A* using the set of Kraus operators *Ks*.

## See also

[qpp::measure\\_seq\(\)](#)

## Note

The dimension of all *Ks* must match the dimension of *subsys*. The measurement is destructive, i.e. the measured subsystems are traced away.

## Parameters

$A$	Eigen expression
$Ks$	Set of Kraus operators
<i>subsys</i>	Subsystem indexes that are measured
<i>dims</i>	Dimensions of the multi-partite system

## Returns

Tuple of: 1. Result of the measurement, 2. Vector of outcome probabilities, and 3. Vector of post-measurement normalized states

```
6.1.3.86  template<typename Derived > std::tuple<idx, std::vector<double>, std::vector<cmat> > qpp::measure ( const
Eigen::MatrixBase< Derived > & A, const std::initializer_list< cmat > & Ks, const std::vector< idx > & subsys,
const std::vector< idx > & dims )
```

Measures the part *subsys* of the multi-partite state vector or density matrix *A* using the set of Kraus operators *Ks*.

## See also

[qpp::measure\\_seq\(\)](#)

## Note

The dimension of all *Ks* must match the dimension of *subsys*. The measurement is destructive, i.e. the measured subsystems are traced away.

## Parameters

<i>A</i>	Eigen expression
<i>Ks</i>	Set of Kraus operators
<i>subsys</i>	Subsystem indexes that are measured
<i>dims</i>	Dimensions of the multi-partite system

## Returns

Tuple of: 1. Result of the measurement, 2. Vector of outcome probabilities, and 3. Vector of post-measurement normalized states

```
6.1.3.87  template<typename Derived> std::tuple<idx, std::vector<double>, std::vector<cmat>> qpp::measure ( const
Eigen::MatrixBase< Derived> & A, const std::vector< cmat> & Ks, const std::vector< idx> & subsys, idx d =
2 )
```

Measures the part *subsys* of the multi-partite state vector or density matrix *A* using the set of Kraus operators *Ks*.

## See also

[qpp::measure\\_seq\(\)](#)

## Note

The dimension of all *Ks* must match the dimension of *subsys*. The measurement is destructive, i.e. the measured subsystems are traced away.

## Parameters

<i>A</i>	Eigen expression
<i>Ks</i>	Set of Kraus operators
<i>subsys</i>	Subsystem indexes that are measured
<i>d</i>	Subsystem dimensions

## Returns

Tuple of: 1. Result of the measurement, 2. Vector of outcome probabilities, and 3. Vector of post-measurement normalized states

```
6.1.3.88  template<typename Derived> std::tuple<idx, std::vector<double>, std::vector<cmat>> qpp::measure ( const
Eigen::MatrixBase< Derived> & A, const std::initializer_list< cmat> & Ks, const std::vector< idx> & subsys,
idx d = 2 )
```

Measures the part *subsys* of the multi-partite state vector or density matrix *A* using the set of Kraus operators *Ks*.

## See also

[qpp::measure\\_seq\(\)](#)

## Note

The dimension of all *Ks* must match the dimension of *subsys*. The measurement is destructive, i.e. the measured subsystems are traced away.

## Parameters

$A$	Eigen expression
$Ks$	Set of Kraus operators
$subsys$	Subsystem indexes that are measured
$d$	Subsystem dimensions

## Returns

Tuple of: 1. Result of the measurement, 2. Vector of outcome probabilities, and 3. Vector of post-measurement normalized states

```
6.1.3.89  template<typename Derived > std::tuple<idx, std::vector<double>, std::vector<cmat> > qpp::measure ( const
Eigen::MatrixBase< Derived > & A, const cmat & V, const std::vector< idx > & subsys, const std::vector< idx >
& dims )
```

Measures the part *subsys* of the multi-partite state vector or density matrix *A* in the orthonormal basis or rank-1 POVM specified by the matrix *V*.

## See also

[qpp::measure\\_seq\(\)](#)

## Note

The dimension of *V* must match the dimension of *subsys*. The measurement is destructive, i.e. the measured subsystems are traced away.

## Parameters

$A$	Eigen expression
$V$	Matrix whose columns represent the measurement basis vectors or the bra parts of the rank-1 POVM
$subsys$	Subsystem indexes that are measured
$dims$	Dimensions of the multi-partite system

## Returns

Tuple of: 1. Result of the measurement, 2. Vector of outcome probabilities, and 3. Vector of post-measurement normalized states

```
6.1.3.90  template<typename Derived > std::tuple<idx, std::vector<double>, std::vector<cmat> > qpp::measure ( const
Eigen::MatrixBase< Derived > & A, const cmat & V, const std::vector< idx > & subsys, idx d = 2 )
```

Measures the part *subsys* of the multi-partite state vector or density matrix *A* in the orthonormal basis or rank-1 POVM specified by the matrix *V*.

## See also

[qpp::measure\\_seq\(\)](#)

## Note

The dimension of *V* must match the dimension of *subsys*. The measurement is destructive, i.e. the measured subsystems are traced away.

## Parameters

$A$	Eigen expression
$V$	Matrix whose columns represent the measurement basis vectors or the bra parts of the rank-1 POVM
<i>subsys</i>	Subsystem indexes that are measured
$d$	Subsystem dimensions

## Returns

Tuple of: 1. Result of the measurement, 2. Vector of outcome probabilities, and 3. Vector of post-measurement normalized states

6.1.3.91 `template<typename Derived> std::tuple<std::vector<idx>, double, cmat> qpp::measure_seq ( const Eigen::MatrixBase< Derived> & A, std::vector< idx> subsys, std::vector< idx> dims )`

Sequentially measures the part *subsys* of the multi-partite state vector or density matrix *A* in the computational basis.

## See also

[qpp::measure\(\)](#)

## Parameters

$A$	Eigen expression
<i>subsys</i>	Subsystem indexes that are measured
<i>dims</i>	Dimensions of the multi-partite system

## Returns

Tuple of: 1. Vector of outcome results of the measurement (ordered in increasing order with respect to *subsys*, i.e. first measurement result corresponds to the subsystem with the smallest index), 2. Outcome probability, and 3. Post-measurement normalized state

6.1.3.92 `template<typename Derived> std::tuple<std::vector<idx>, double, cmat> qpp::measure_seq ( const Eigen::MatrixBase< Derived> & A, std::vector< idx> subsys, idx d = 2 )`

Sequentially measures the part *subsys* of the multi-partite state vector or density matrix *A* in the computational basis.

## See also

[qpp::measure\(\)](#)

## Parameters

$A$	Eigen expression
<i>subsys</i>	Subsystem indexes that are measured
$d$	Subsystem dimensions

## Returns

Tuple of: 1. Vector of outcome results of the measurement (ordered in increasing order with respect to *subsys*, i.e. first measurement result corresponds to the subsystem with the smallest index), 2. Outcome probability, and 3. Post-measurement normalized state

**6.1.3.93** `ket qpp::mket ( const std::vector< idx > & mask, const std::vector< idx > & dims )` `[inline]`

Multi-partite qudit ket.

Constructs the multi-partite qudit ket  $|\text{mask}\rangle$ , where *mask* is a `std::vector` of non-negative integers. Each element in *mask* has to be smaller than the corresponding element in *dims*.

Parameters

<i>mask</i>	<code>std::vector</code> of non-negative integers
<i>dims</i>	Dimensions of the multi-partite system

Returns

Multi-partite qudit state vector, as a complex dynamic column vector

**6.1.3.94** `ket qpp::mket ( const std::vector< idx > & mask, idx d = 2 )` `[inline]`

Multi-partite qudit ket.

Constructs the multi-partite qudit ket  $|\text{mask}\rangle$ , all subsystem having equal dimension *d*. *mask* is a `std::vector` of non-negative integers, and each element in *mask* has to be strictly smaller than *d*.

Parameters

<i>mask</i>	<code>std::vector</code> of non-negative integers
<i>d</i>	Subsystem dimensions

Returns

Multi-partite qudit state vector, as a complex dynamic column vector

**6.1.3.95** `bigint qpp::modinv ( bigint a, bigint p )` `[inline]`

Modular inverse of *a* mod *p*.

See also

[qpp::egcd\(\)](#)

Note

*a* and *p* must be co-prime

Parameters

<i>a</i>	Non-negative integer
<i>p</i>	Non-negative integer

Returns

Modular inverse  $a^{-1} \bmod p$

**6.1.3.96** `bigint qpp::modmul ( bigint a, bigint b, bigint p )` `[inline]`

Modular multiplication without overflow.

Computes  $ab \bmod p$  without overflow



## Parameters

$a$	Integer
$b$	Integer
$p$	Positive integer

## Returns

$ab \bmod p$  avoiding overflow

6.1.3.97 `bigint qpp::modpow ( bigint a, bigint n, bigint p )` `[inline]`

Fast integer power modulo  $p$  based on the SQUARE-AND-MULTIPLY algorithm.

## Note

Uses `qpp::modmul()` that avoids overflows

Computes  $a^n \bmod p$

## Parameters

$a$	Non-negative integer
$n$	Non-negative integer
$p$	Strictly positive integer

## Returns

$a^n \bmod p$

6.1.3.98 `cmat qpp::mprj ( const std::vector< idx > & mask, const std::vector< idx > & dims )` `[inline]`

Projector onto multi-partite qudit ket.

Constructs the projector onto the multi-partite qudit ket  $|\text{mask}\rangle$ , where  $\text{mask}$  is a `std::vector` of non-negative integers. Each element in  $\text{mask}$  has to be smaller than the corresponding element in  $\text{dims}$ .

## Parameters

$\text{mask}$	<code>std::vector</code> of non-negative integers
$\text{dims}$	Dimensions of the multi-partite system

## Returns

Projector onto multi-partite qudit state vector, as a complex dynamic matrix

6.1.3.99 `cmat qpp::mprj ( const std::vector< idx > & mask, idx d = 2 )` `[inline]`

Projector onto multi-partite qudit ket.

Constructs the projector onto the multi-partite qudit ket  $|\text{mask}\rangle$ , all subsystem having equal dimension  $d$ .  $\text{mask}$  is a `std::vector` of non-negative integers, and each element in  $\text{mask}$  has to be strictly smaller than  $d$ .

## Parameters

<i>mask</i>	std::vector of non-negative integers
<i>d</i>	Subsystem dimensions

## Returns

Projector onto multi-partite qudit state vector, as a complex dynamic matrix

6.1.3.100 `idx qpp::multiidx2n ( const std::vector< idx > & midx, const std::vector< idx > & dims ) [inline]`

Multi-index to non-negative integer index.

## See also

[qpp::n2multiidx\(\)](#)

Uses standard lexicographical order, i.e. 00...0, 00...1 etc.

## Parameters

<i>midx</i>	Multi-index
<i>dims</i>	Dimensions of the multi-partite system

## Returns

Non-negative integer index

6.1.3.101 `std::vector<idx> qpp::n2multiidx ( idx n, const std::vector< idx > & dims ) [inline]`

Non-negative integer index to multi-index.

## See also

[qpp::multiidx2n\(\)](#)

Uses standard lexicographical order, i.e. 00...0, 00...1 etc.

## Parameters

<i>n</i>	Non-negative integer index
<i>dims</i>	Dimensions of the multi-partite system

## Returns

Multi-index of the same size as *dims*

6.1.3.102 `template<typename Derived > double qpp::negativity ( const Eigen::MatrixBase< Derived > & A, const std::vector< idx > & dims )`

Negativity of the bi-partite mixed state *A*.

## Parameters

$A$	Eigen expression
$dims$	Dimensions of the bi-partite system

## Returns

Negativity

6.1.3.103 `template<typename Derived> double qpp::norm ( const Eigen::MatrixBase< Derived> & A )`

Frobenius norm.

## Parameters

$A$	Eigen expression
-----	------------------

## Returns

Frobenius norm of  $A$ 

6.1.3.104 `cplx qpp::omega ( idx D ) [inline]`

D-th root of unity.

## Parameters

$D$	Non-negative integer
-----	----------------------

## Returns

D-th root of unity  $\exp(2\pi i/D)$ 

6.1.3.105 `constexpr cplx qpp::operator""_i ( unsigned long long int x ) [inline],[noexcept]`

User-defined literal for complex  $i = \sqrt{-1}$  (integer overload)

Example:

```
auto z = 4_i; // type of z is std::complex<double>
```

6.1.3.106 `constexpr cplx qpp::operator""_i ( long double x ) [inline],[noexcept]`

User-defined literal for complex  $i = \sqrt{-1}$  (real overload)

Example:

```
auto z = 4.5_i; // type of z is std::complex<double>
```

6.1.3.107 `template<typename Derived> dyn_mat<typename Derived::Scalar> qpp::powm ( const Eigen::MatrixBase< Derived> & A, idx n )`

Fast matrix power based on the SQUARE-AND-MULTIPLY algorithm.

See also

[qpp::spectralpowm\(\)](#)Explicitly multiplies the matrix  $A$  with itself  $n$  times. By convention  $A^0 = I$ .

## Parameters

$A$	Eigen expression
$n$	Non-negative integer

## Returns

Matrix power  $A^n$ , as a dynamic matrix over the same scalar field as  $A$

6.1.3.108 `template<typename Derived > dyn_mat<typename Derived::Scalar> qpp::prj ( const Eigen::MatrixBase< Derived > & V )`

Projector.

Normalized projector onto state vector

## Parameters

$V$	Eigen expression
-----	------------------

## Returns

Projector onto the state vector  $V$ , or the matrix *Zero* if  $V$  has norm zero (i.e. smaller than `qpp::eps`), as a dynamic matrix over the same scalar field as  $A$

6.1.3.109 `template<typename Derived > Derived::Scalar qpp::prod ( const Eigen::MatrixBase< Derived > & A )`

Element-wise product of  $A$ .

## Parameters

$A$	Eigen expression
-----	------------------

## Returns

Element-wise product of  $A$ , as a scalar over the same scalar field as  $A$

6.1.3.110 `template<typename InputIterator > std::iterator_traits<InputIterator>::value_type qpp::prod ( InputIterator first, InputIterator last )`

Element-wise product of an STL-like range.

## Parameters

<i>first</i>	Iterator to the first element of the range
<i>last</i>	Iterator to the last element of the range

## Returns

Element-wise product of the range, as a scalar over the same scalar field as the range

6.1.3.111 `template<typename Container > Container::value_type qpp::prod ( const Container & c, typename std::enable_if< is_iterable< Container >::value >::type * = nullptr )`

Element-wise product of the elements of an STL-like container.

## Parameters

<i>c</i>	STL-like container
----------	--------------------

## Returns

Element-wise product of the elements of the container, as a scalar over the same scalar field as the container

6.1.3.112 `template<typename Derived > dyn_mat<typename Derived::Scalar> qpp::ptrace ( const Eigen::MatrixBase<Derived > & A, const std::vector< idx > & subsys, const std::vector< idx > & dims )`

Partial trace.

See also

[qpp::ptrace1\(\)](#), [qpp::ptrace2\(\)](#)

Partial trace of the multi-partite state vector or density matrix over a list of subsystems

## Parameters

<i>A</i>	Eigen expression
<i>subsys</i>	Subsystem indexes
<i>dims</i>	Dimensions of the multi-partite system

## Returns

Partial trace  $Tr_{subsys}(\cdot)$  over the subsystems *subsys* in a multi-partite system, as a dynamic matrix over the same scalar field as *A*

6.1.3.113 `template<typename Derived > dyn_mat<typename Derived::Scalar> qpp::ptrace ( const Eigen::MatrixBase<Derived > & A, const std::vector< idx > & subsys, idx d = 2 )`

Partial trace.

See also

[qpp::ptrace1\(\)](#), [qpp::ptrace2\(\)](#)

Partial trace of the multi-partite state vector or density matrix over a list of subsystems

## Parameters

<i>A</i>	Eigen expression
<i>subsys</i>	Subsystem indexes
<i>d</i>	Subsystem dimensions

## Returns

Partial trace  $Tr_{subsys}(\cdot)$  over the subsystems *subsys* in a multi-partite system, as a dynamic matrix over the same scalar field as *A*

6.1.3.114 `template<typename Derived > dyn_mat<typename Derived::Scalar> qpp::ptrace1 ( const Eigen::MatrixBase<Derived > & A, const std::vector< idx > & dims )`

Partial trace.

See also

[qpp::ptrace2\(\)](#)

Partial trace over the first subsystem of bi-partite state vector or density matrix

## Parameters

$A$	Eigen expression
$dims$	Dimensions of the bi-partite system (must be a <code>std::vector</code> with 2 elements)

## Returns

Partial trace  $Tr_A(\cdot)$  over the first subsystem  $A$  in a bi-partite system  $A \otimes B$ , as a dynamic matrix over the same scalar field as  $A$

6.1.3.115 `template<typename Derived > dyn_mat<typename Derived::Scalar> qpp::ptrace2 ( const Eigen::MatrixBase<Derived> & A, const std::vector< idx > & dims )`

Partial trace.

See also

[qpp::ptrace1\(\)](#)

Partial trace over the second subsystem of bi-partite state vector or density matrix

## Parameters

$A$	Eigen expression
$dims$	Dimensions of the bi-partite system (must be a <code>std::vector</code> with 2 elements)

## Returns

Partial trace  $Tr_B(\cdot)$  over the second subsystem  $B$  in a bi-partite system  $A \otimes B$ , as a dynamic matrix over the same scalar field as  $A$

6.1.3.116 `template<typename Derived > dyn_mat<typename Derived::Scalar> qpp::ptrtranspose ( const Eigen::MatrixBase<Derived> & A, const std::vector< idx > & subsys, const std::vector< idx > & dims )`

Partial transpose.

Partial transpose of the multi-partite state vector or density matrix over a list of subsystems

## Parameters

$A$	Eigen expression
$subsys$	Subsystem indexes
$dims$	Dimensions of the multi-partite system

## Returns

Partial transpose  $(\cdot)^{T_{subsys}}$  over the subsystems  $subsys$  in a multi-partite system, as a dynamic matrix over the same scalar field as  $A$

6.1.3.117 `template<typename Derived > dyn_mat<typename Derived::Scalar> qpp::ptrtranspose ( const Eigen::MatrixBase<Derived> & A, const std::vector< idx > & subsys, idx d = 2 )`

Partial transpose.

Partial transpose of the multi-partite state vector or density matrix over a list of subsystems

## Parameters

$A$	Eigen expression
$subsys$	Subsystem indexes
$d$	Subsystem dimensions

## Returns

Partial transpose  $(\cdot)^{T_{subsys}}$  over the subsystems  $subsys$  in a multi-partite system, as a dynamic matrix over the same scalar field as  $A$

6.1.3.118 `template<typename Derived > double qpp::qmutualinfo ( const Eigen::MatrixBase< Derived > & A, const std::vector< idx > & subsysA, const std::vector< idx > & subsysB, const std::vector< idx > & dims )`

Quantum mutual information between 2 subsystems of a composite system.

## Parameters

$A$	Eigen expression
$subsysA$	Indexes of the first subsystem
$subsysB$	Indexes of the second subsystem
$dims$	Dimensions of the multi-partite system

## Returns

Mutual information between the 2 subsystems

6.1.3.119 `template<typename Derived > double qpp::qmutualinfo ( const Eigen::MatrixBase< Derived > & A, const std::vector< idx > & subsysA, const std::vector< idx > & subsysB, idx d = 2 )`

Quantum mutual information between 2 subsystems of a composite system.

## Parameters

$A$	Eigen expression
$subsysA$	Indexes of the first subsystem
$subsysB$	Indexes of the second subsystem
$d$	Subsystem dimensions

## Returns

Mutual information between the 2 subsystems

6.1.3.120 `double qpp::rand ( double a, double b ) [inline]`

Generates a random real number uniformly distributed in the interval [a, b)

## Parameters

$a$	Beginning of the interval, belongs to it
$b$	End of the interval, does not belong to it

## Returns

Random real number (double) uniformly distributed in the interval [a, b)



6.1.3.121 `bigint qpp::rand ( bigint a, bigint b )` `[inline]`

Generates a random big integer uniformly distributed in the interval [a, b].

**Parameters**

<i>a</i>	Beginning of the interval, belongs to it
<i>b</i>	End of the interval, belongs to it

**Returns**

Random big integer uniformly distributed in the interval [a, b]

**6.1.3.122** `template<typename Derived > Derived qpp::rand ( idx rows, idx cols, double a = 0, double b = 1 )`

Generates a random matrix with entries uniformly distributed in the interval [a, b)

If complex, then both real and imaginary parts are uniformly distributed in [a, b)

This is the generic version that always throws `qpp::Exception::Type::UNDEFINED_TYPE`. It is specialized only for `qpp::dmat` and `qpp::cmat`

**6.1.3.123** `template<> dmat qpp::rand ( idx rows, idx cols, double a, double b ) [inline]`

Generates a random real matrix with entries uniformly distributed in the interval [a, b), specialization for double matrices (`qpp::dmat`)

The template parameter cannot be automatically deduced and must be explicitly provided

Example:

```
// generates a 3 x 3 random Eigen::MatrixXd,
// with entries uniformly distributed in [-1,1)
auto mat = rand<dmat>(3, 3, -1, 1);
```

**Parameters**

<i>rows</i>	Number of rows of the random generated matrix
<i>cols</i>	Number of columns of the random generated matrix
<i>a</i>	Beginning of the interval, belongs to it
<i>b</i>	End of the interval, does not belong to it

**Returns**

Random real matrix

**6.1.3.124** `template<> cmat qpp::rand ( idx rows, idx cols, double a, double b ) [inline]`

Generates a random complex matrix with entries (both real and imaginary) uniformly distributed in the interval [a, b), specialization for complex matrices (`qpp::cmat`)

The template parameter cannot be automatically deduced and must be explicitly provided

Example:

```
// generates a 3 x 3 random Eigen::MatrixXcd,
// with entries (both real and imaginary) uniformly distributed in [-1,1)
auto mat = rand<cmat>(3, 3, -1, 1);
```

## Parameters

<i>rows</i>	Number of rows of the random generated matrix
<i>cols</i>	Number of columns of the random generated matrix
<i>a</i>	Beginning of the interval, belongs to it
<i>b</i>	End of the interval, does not belong to it

## Returns

Random complex matrix

6.1.3.125 `cmat qpp::randH ( idx D ) [inline]`

Generates a random Hermitian matrix.

## Parameters

<i>D</i>	Dimension of the Hilbert space
----------	--------------------------------

## Returns

Random Hermitian matrix

6.1.3.126 `idx qpp::randidx ( idx a = std::numeric_limits<idx>::min(), idx b = std::numeric_limits<idx>::max() ) [inline]`

Generates a random index (idx) uniformly distributed in the interval [a, b].

## Parameters

<i>a</i>	Beginning of the interval, belongs to it
<i>b</i>	End of the interval, belongs to it

## Returns

Random index (idx) uniformly distributed in the interval [a, b]

6.1.3.127 `ket qpp::randket ( idx D ) [inline]`

Generates a random normalized ket (pure state vector)

## Parameters

<i>D</i>	Dimension of the Hilbert space
----------	--------------------------------

## Returns

Random normalized ket

6.1.3.128 `std::vector<cmat> qpp::randkraus ( idx N, idx D ) [inline]`

Generates a set of random Kraus operators.

## Note

The set of Kraus operators satisfy the closure condition  $\sum_i K_i^\dagger K_i = I$

**Parameters**

$N$	Number of Kraus operators
$D$	Dimension of the Hilbert space

**Returns**

Set of  $N$  Kraus operators satisfying the closure condition

**6.1.3.129** `template<typename Derived > Derived qpp::randn ( idx rows, idx cols, double mean = 0, double sigma = 1 )`

Generates a random matrix with entries normally distributed in  $N(\text{mean}, \text{sigma})$

If complex, then both real and imaginary parts are normally distributed in  $N(\text{mean}, \text{sigma})$

This is the generic version that always throws `qpp::Exception::Type::UNDEFINED_TYPE`. It is specialized only for `qpp::dmat` and `qpp::cmat`

**6.1.3.130** `template<> dmat qpp::randn ( idx rows, idx cols, double mean, double sigma ) [inline]`

Generates a random real matrix with entries normally distributed in  $N(\text{mean}, \text{sigma})$ , specialization for double matrices (`qpp::dmat`)

The template parameter cannot be automatically deduced and must be explicitly provided

Example:

```
// generates a 3 x 3 random Eigen::MatrixXd,
// with entries normally distributed in N(0,2)
auto mat = randn<dmat>(3, 3, 0, 2);
```

**Parameters**

<i>rows</i>	Number of rows of the random generated matrix
<i>cols</i>	Number of columns of the random generated matrix
<i>mean</i>	Mean
<i>sigma</i>	Standard deviation

**Returns**

Random real matrix

**6.1.3.131** `template<> cmat qpp::randn ( idx rows, idx cols, double mean, double sigma ) [inline]`

Generates a random complex matrix with entries (both real and imaginary) normally distributed in  $N(\text{mean}, \text{sigma})$ , specialization for complex matrices (`qpp::cmat`)

The template parameter cannot be automatically deduced and must be explicitly provided

Example:

```
// generates a 3 x 3 random Eigen::MatrixXcd,
// with entries (both real and imaginary) normally distributed in N(0,2)
auto mat = randn<cmat>(3, 3, 0, 2);
```

## Parameters

<i>rows</i>	Number of rows of the random generated matrix
<i>cols</i>	Number of columns of the random generated matrix
<i>mean</i>	Mean
<i>sigma</i>	Standard deviation

## Returns

Random complex matrix

**6.1.3.132** `double qpp::randn ( double mean = 0, double sigma = 1 )` `[inline]`

Generates a random real number (double) normally distributed in  $N(\text{mean}, \text{sigma})$

## Parameters

<i>mean</i>	Mean
<i>sigma</i>	Standard deviation

## Returns

Random real number normally distributed in  $N(\text{mean}, \text{sigma})$

**6.1.3.133** `std::vector<idx> qpp::randperm ( idx N )` `[inline]`

Generates a random uniformly distributed permutation.

Uses Knuth shuffle method (as implemented by `std::shuffle`), so that all permutations are equally probable

## Parameters

<i>N</i>	Size of the permutation
----------	-------------------------

## Returns

Random permutation of size *N*

**6.1.3.134** `bigint qpp::randprime ( bigint a, bigint b, idx N = 1000 )` `[inline]`

Generates a random big prime uniformly distributed in the interval  $[a, b]$ .

## Parameters

<i>a</i>	Beginning of the interval, belongs to it
<i>b</i>	End of the interval, belongs to it
<i>N</i>	Maximum number of candidates

## Returns

Random big integer uniformly distributed in the interval  $[a, b]$

**6.1.3.135** `cmat qpp::randrho ( idx D )` `[inline]`

Generates a random density matrix.

## Parameters

<i>D</i>	Dimension of the Hilbert space
----------	--------------------------------

## Returns

Random density matrix

**6.1.3.136** `cmat qpp::randU ( idx D )` `[inline]`

Generates a random unitary matrix.

## Parameters

<i>D</i>	Dimension of the Hilbert space
----------	--------------------------------

## Returns

Random unitary

**6.1.3.137** `cmat qpp::randV ( idx Din, idx Dout )` `[inline]`

Generates a random isometry matrix.

## Parameters

<i>Din</i>	Size of the input Hilbert space
<i>Dout</i>	Size of the output Hilbert space

## Returns

Random isometry matrix

**6.1.3.138** `template<typename Derived > double qpp::renyi ( const Eigen::MatrixBase< Derived > & A, double alpha )`

Renyi-  $\alpha$  entropy of the density matrix *A*, for  $\alpha \geq 0$ .

## Note

When  $\alpha \rightarrow 1$  the Renyi entropy converges to the von-Neumann entropy, with the logarithm in base 2

## Parameters

<i>A</i>	Eigen expression
<i>alpha</i>	Non-negative real number, use <code>qpp::infy</code> for $\alpha = \infty$

## Returns

Renyi-  $\alpha$  entropy, with the logarithm in base 2

**6.1.3.139** `double qpp::renyi ( const std::vector< double > & prob, double alpha )` `[inline]`

Renyi-  $\alpha$  entropy of the probability distribution *prob*, for  $\alpha \geq 0$ .

## Note

When  $\alpha \rightarrow 1$  the Renyi entropy converges to the Shannon entropy, with the logarithm in base 2

## Parameters

<i>prob</i>	Real probability vector
<i>alpha</i>	Non-negative real number, use <a href="#">qpp::infy</a> for $\alpha = \infty$

## Returns

Renyi-  $\alpha$  entropy, with the logarithm in base 2

6.1.3.140 `template<typename Derived > dyn_mat<typename Derived::Scalar> qpp::reshape ( const Eigen::MatrixBase<Derived > & A, idx rows, idx cols )`

Reshape.

Uses column-major order when reshaping (same as MATLAB)

## Parameters

<i>A</i>	Eigen expression
<i>rows</i>	Number of rows of the reshaped matrix
<i>cols</i>	Number of columns of the reshaped matrix

## Returns

Reshaped matrix with *rows* rows and *cols* columns, as a dynamic matrix over the same scalar field as *A*

6.1.3.141 `template<typename Derived > std::vector<double> qpp::rho2bloch ( const Eigen::MatrixBase<Derived > & A )`

Computes the 3-dimensional real Bloch vector corresponding to the qubit density matrix *A*.

## See also

[qpp::bloch2rho\(\)](#)

## Note

It is implicitly assumed that the density matrix is Hermitian

## Parameters

<i>A</i>	Eigen expression
----------	------------------

## Returns

3-dimensional Bloch vector

6.1.3.142 `template<typename Derived > dyn_col_vect<typename Derived::Scalar> qpp::rho2pure ( const Eigen::MatrixBase<Derived > & A )`

Finds the pure state representation of a matrix proportional to a projector onto a pure state.

## Note

No purity check is done, the input state *A* must have rank one, otherwise the function returns the first non-zero eigenvector of *A*

## Parameters

<i>A</i>	Eigen expression, assumed to be proportional to a projector onto a pure state, i.e. <i>A</i> is assumed to have rank one
----------	--------------------------------------------------------------------------------------------------------------------------

## Returns

The unique non-zero eigenvector of *A*, as a dynamic column vector over the same scalar field as *A*

6.1.3.143 `template<typename Derived > void qpp::save ( const Eigen::MatrixBase< Derived > & A, const std::string & fname )`

Saves Eigen expression to a binary file (internal format) in double precision.

## See also

[qpp::load\(\)](#)

## Parameters

<i>A</i>	Eigen expression
<i>fname</i>	Output file name

6.1.3.144 `template<typename Derived > void qpp::saveMATLABmatrix ( const Eigen::MatrixBase< Derived > & , const std::string & , const std::string & , const std::string & )`

Saves an Eigen dynamic matrix to a MATLAB .mat file, generic version.

## See also

[qpp::loadMATLABmatrix\(\)](#)

This is the generic version that always throws [qpp::Exception::Type::UNDEFINED\\_TYPE](#). It is specialized only for [qpp::dmat](#) and [qpp::cmat](#) (the only matrix types that can be saved)

6.1.3.145 `template<> void qpp::saveMATLABmatrix ( const Eigen::MatrixBase< dmat > & A, const std::string & mat_file, const std::string & var_name, const std::string & mode ) [inline]`

Saves an Eigen dynamic matrix to a MATLAB .mat file, specialization for double matrices ([qpp::dmat](#))

## See also

[qpp::loadMATLABmatrix\(\)](#)

## Parameters

<i>A</i>	Eigen expression over the complex field
<i>mat_file</i>	MATLAB .mat file
<i>var_name</i>	Variable name in the .mat file representing the matrix to be saved
<i>mode</i>	Saving mode (append, overwrite etc.), see MATLAB <i>matOpen()</i> documentation for details

6.1.3.146 `template<> void qpp::saveMATLABmatrix ( const Eigen::MatrixBase< cmat > & A, const std::string & mat_file, const std::string & var_name, const std::string & mode ) [inline]`

Saves an Eigen dynamic matrix to a MATLAB .mat file, specialization for complex matrices ([qpp::cmat](#))



See also

[qpp::loadMATLABmatrix\(\)](#)

Parameters

<i>A</i>	Eigen expression over the complex field
<i>mat_file</i>	MATLAB .mat file
<i>var_name</i>	Variable name in the .mat file representing the matrix to be saved
<i>mode</i>	Saving mode (append, overwrite etc.), see MATLAB <i>matOpen()</i> documentation for details

6.1.3.147 `template<typename Derived > double qpp::schatten ( const Eigen::MatrixBase< Derived > &A, double p )`

Schatten matrix norm.

Parameters

<i>A</i>	Eigen expression
<i>p</i>	Real number, greater or equal to 1, use <a href="#">qpp::infy</a> for $p = \infty$

Returns

Schatten- $p$  matrix norm of  $A$

6.1.3.148 `template<typename Derived > cmat qpp::schmidtA ( const Eigen::MatrixBase< Derived > &A, const std::vector< idx > &dims )`

Schmidt basis on Alice side.

Parameters

<i>A</i>	Eigen expression
<i>dims</i>	Dimensions of the bi-partite system

Returns

Unitary matrix  $U$  whose columns represent the Schmidt basis vectors on Alice side.

6.1.3.149 `template<typename Derived > cmat qpp::schmidtB ( const Eigen::MatrixBase< Derived > &A, const std::vector< idx > &dims )`

Schmidt basis on Bob side.

Parameters

<i>A</i>	Eigen expression
<i>dims</i>	Dimensions of the bi-partite system

Returns

Unitary matrix  $V$  whose columns represent the Schmidt basis vectors on Bob side.

6.1.3.150 `template<typename Derived > dyn_col_vect<double> qpp::schmidtcoeffs ( const Eigen::MatrixBase< Derived > &A, const std::vector< idx > &dims )`

Schmidt coefficients of the bi-partite pure state  $A$ .

**Note**

The sum of the squares of the Schmidt coefficients equals 1

**See also**

[qpp::schmidtprobs\(\)](#)

**Parameters**

<i>A</i>	Eigen expression
<i>dims</i>	Dimensions of the bi-partite system

**Returns**

Schmidt coefficients of *A*, as a real dynamic column vector

6.1.3.151 `template<typename Derived > std::vector<double> qpp::schmidtprobs ( const Eigen::MatrixBase< Derived > & A, const std::vector< idx > & dims )`

Schmidt probabilities of the bi-partite pure state *A*.

Defined as the squares of the Schmidt coefficients. The sum of the Schmidt probabilities equals 1.

**See also**

[qpp::schmidtcoeffs\(\)](#)

**Parameters**

<i>A</i>	Eigen expression
<i>dims</i>	Dimensions of the bi-partite system

**Returns**

Real vector consisting of the Schmidt probabilities of *A*

6.1.3.152 `template<typename Container > double qpp::sigma ( const std::vector< double > & prob, const Container & X, typename std::enable_if< is_iterable< Container >::value >::type * = nullptr )`

Standard deviation.

**Parameters**

<i>prob</i>	Real probability vector representing the probability distribution of <i>X</i>
<i>X</i>	Random variable values represented by an STL-like container

**Returns**

Standard deviation of *X*

6.1.3.153 `template<typename Derived > cmat qpp::sinm ( const Eigen::MatrixBase< Derived > & A )`

Matrix sin.

## Parameters

$A$	Eigen expression
-----	------------------

## Returns

Matrix sine of  $A$

6.1.3.154 `template<typename Derived> cmat qpp::spectralpowm ( const Eigen::MatrixBase< Derived> & A, const cplx z )`

Matrix power.

## See also

[qpp::powm\(\)](#)

Uses the spectral decomposition of  $A$  to compute the matrix power. By convention  $A^0 = I$ .

## Parameters

$A$	Eigen expression
$z$	Complex number

## Returns

Matrix power  $A^z$

6.1.3.155 `template<typename Derived> cmat qpp::sqrtm ( const Eigen::MatrixBase< Derived> & A )`

Matrix square root.

## Parameters

$A$	Eigen expression
-----	------------------

## Returns

Matrix square root of  $A$

6.1.3.156 `template<typename Derived> Derived::Scalar qpp::sum ( const Eigen::MatrixBase< Derived> & A )`

Element-wise sum of  $A$ .

## Parameters

$A$	Eigen expression
-----	------------------

## Returns

Element-wise sum of  $A$ , as a scalar over the same scalar field as  $A$

6.1.3.157 `template<typename InputIterator> std::iterator_traits<InputIterator>::value_type qpp::sum ( InputIterator first, InputIterator last )`

Element-wise sum of an STL-like range.

## Parameters

<i>first</i>	Iterator to the first element of the range
<i>last</i>	Iterator to the last element of the range

## Returns

Element-wise sum of the range, as a scalar over the same scalar field as the range

6.1.3.158 `template<typename Container > Container::value_type qpp::sum ( const Container & c, typename std::enable_if<is_iterable< Container >::value >::type * = nullptr )`

Element-wise sum of the elements of an STL-like container.

## Parameters

<i>c</i>	STL-like container
----------	--------------------

## Returns

Element-wise sum of the elements of the container, as a scalar over the same scalar field as the container

6.1.3.159 `cmat qpp::super2choi ( const cmat & A ) [inline]`

Converts superoperator matrix to Choi matrix.

## See also

[qpp::choi2super\(\)](#)

## Parameters

<i>A</i>	Superoperator matrix
----------	----------------------

## Returns

Choi matrix

6.1.3.160 `template<typename Derived > dyn_col_vect<double> qpp::svals ( const Eigen::MatrixBase< Derived > & A )`

Singular values.

## Parameters

<i>A</i>	Eigen expression
----------	------------------

## Returns

Singular values of *A*, ordered in decreasing order, as a real dynamic column vector

6.1.3.161 `template<typename Derived > std::tuple<cmat, dyn_col_vect<double>, cmat> qpp::svd ( const Eigen::MatrixBase< Derived > & A )`

Full singular value decomposition.

## Parameters

$A$	Eigen expression
-----	------------------

## Returns

Tuple of: 1. Left singular vectors of  $A$ , as columns of a complex dynamic matrix, 2. Singular values of  $A$ , ordered in decreasing order, as a real dynamic column vector, and 3. Right singular vectors of  $A$ , as columns of a complex dynamic matrix

6.1.3.162 `template<typename Derived > cmat qpp::svdU ( const Eigen::MatrixBase< Derived > & A )`

Left singular vectors.

## Parameters

$A$	Eigen expression
-----	------------------

## Returns

Complex dynamic matrix, whose columns are the left singular vectors of  $A$

6.1.3.163 `template<typename Derived > cmat qpp::svdV ( const Eigen::MatrixBase< Derived > & A )`

Right singular vectors.

## Parameters

$A$	Eigen expression
-----	------------------

## Returns

Complex dynamic matrix, whose columns are the right singular vectors of  $A$

6.1.3.164 `template<typename Derived > dyn_mat<typename Derived::Scalar> qpp::syspermute ( const Eigen::MatrixBase< Derived > & A, const std::vector< idx > & perm, const std::vector< idx > & dims )`

Subsystem permutation.

Permutes the subsystems of a state vector or density matrix. The qubit  $perm[i]$  is permuted to the location  $i$ .

## Parameters

$A$	Eigen expression
$perm$	Permutation
$dims$	Dimensions of the multi-partite system

## Returns

Permuted system, as a dynamic matrix over the same scalar field as  $A$

6.1.3.165 `template<typename Derived > dyn_mat<typename Derived::Scalar> qpp::syspermute ( const Eigen::MatrixBase< Derived > & A, const std::vector< idx > & perm, idx d = 2 )`

Subsystem permutation.

Permutes the subsystems of a state vector or density matrix. The qubit  $perm[i]$  is permuted to the location  $i$ .

## Parameters

$A$	Eigen expression
$perm$	Permutation
$d$	Subsystem dimensions

## Returns

Permuted system, as a dynamic matrix over the same scalar field as  $A$

6.1.3.166 `template<typename Derived > Derived::Scalar qpp::trace ( const Eigen::MatrixBase< Derived > & A )`

Trace.

## Parameters

$A$	Eigen expression
-----	------------------

## Returns

Trace of  $A$ , as a scalar over the same scalar field as  $A$

6.1.3.167 `template<typename Derived > dyn_mat<typename Derived::Scalar> qpp::transpose ( const Eigen::MatrixBase< Derived > & A )`

Transpose.

## Parameters

$A$	Eigen expression
-----	------------------

## Returns

Transpose of  $A$ , as a dynamic matrix over the same scalar field as  $A$

6.1.3.168 `template<typename Derived > double qpp::tsallis ( const Eigen::MatrixBase< Derived > & A, double q )`

Tsallis-  $q$  entropy of the density matrix  $A$ , for  $q \geq 0$ .

## Note

When  $q \rightarrow 1$  the Tsallis entropy converges to the von-Neumann entropy, with the logarithm in base  $e$

## Parameters

$A$	Eigen expression
$q$	Non-negative real number

## Returns

Tsallis-  $q$  entropy

6.1.3.169 `double qpp::tsallis ( const std::vector< double > & prob, double q ) [inline]`

Tsallis-  $q$  entropy of the probability distribution  $prob$ , for  $q \geq 0$ .

## Note

When  $q \rightarrow 1$  the Tsallis entropy converges to the Shannon entropy, with the logarithm in base  $e$

## Parameters

<i>prob</i>	Real probability vector
<i>q</i>	Non-negative real number

## Returns

Tsallis-  $q$  entropy

6.1.3.170 `std::vector<double> qpp::uniform ( idx  $N$  ) [inline]`

Uniform probability distribution vector.

## Parameters

$N$	Size of the alphabet
-----	----------------------

## Returns

Real vector consisting of a uniform distribution of size  $N$

6.1.3.171 `template<typename Container > double qpp::var ( const std::vector< double > & prob, const Container &  $X$ ,  
typename std::enable_if< is_iterable< Container >::value >::type * = nullptr )`

Variance.

## Parameters

<i>prob</i>	Real probability vector representing the probability distribution of $X$
$X$	Random variable values represented by an STL-like container

## Returns

Variance of  $X$

6.1.3.172 `std::vector<int> qpp::x2contfrac ( double  $x$ , idx  $N$ , idx cut = 1e5 ) [inline]`

Simple continued fraction expansion.

See also

[qpp::contfrac2x\(\)](#)

## Parameters

$x$	Real number
$N$	Maximum number of terms in the expansion
<i>cut</i>	Stop the expansion when the next term is greater than <i>cut</i>

## Returns

Integer vector containing the simple continued fraction expansion of  $x$ . If there are  $M$  less than  $N$  terms in the expansion, a shorter vector with  $M$  components is returned.

## 6.1.4 Variable Documentation

6.1.4.1 `constexpr double qpp::chop = 1e-10`

Used in [qpp::disp\(\)](#) for setting to zero numbers that have their absolute value smaller than [qpp::chop](#).

6.1.4.2 `constexpr double qpp::ee = 2.718281828459045235360287471352662497`

Base of natural logarithm,  $e$ .

6.1.4.3 `constexpr double qpp::eps = 1e-12`

Used to decide whether a number or expression in double precision is zero or not.

Example:

```
if(std::abs(x) < qpp::eps) // x is zero
```

6.1.4.4 `constexpr double qpp::infy = std::numeric_limits<double>::infinity()`

Used to denote infinity in double precision.

6.1.4.5 `constexpr idx qpp::maxn = 64`

Maximum number of allowed qu(d)its (subsystems)

Used internally to allocate arrays on the stack (for speed reasons)

6.1.4.6 `constexpr double qpp::pi = 3.141592653589793238462643383279502884`

$\pi$

## 6.2 qpp::experimental Namespace Reference

Experimental/test functions/classes, do not use or modify.

### 6.2.1 Detailed Description

Experimental/test functions/classes, do not use or modify.

## 6.3 qpp::internal Namespace Reference

Internal utility functions, do not use/modify.

### Namespaces

- [details\\_](#)

### Classes

- class [IOManipEigen](#)
- class [IOManipPointer](#)
- class [IOManipRange](#)
- class [Singleton](#)

*[Singleton](#) policy class, used internally to implement the singleton pattern via CRTP (Curiously recurring template pattern)*



## Functions

- void [n2multiidx](#) ([idx](#) n, [idx](#) numdims, const [idx](#) \*dims, [idx](#) \*result) noexcept
- [idx multiidx2n](#) (const [idx](#) \*midx, [idx](#) numdims, const [idx](#) \*dims) noexcept
- template<typename Derived >  
bool [check\\_square\\_mat](#) (const Eigen::MatrixBase< Derived > &A)
- template<typename Derived >  
bool [check\\_vector](#) (const Eigen::MatrixBase< Derived > &A)
- template<typename Derived >  
bool [check\\_rvector](#) (const Eigen::MatrixBase< Derived > &A)
- template<typename Derived >  
bool [check\\_cvector](#) (const Eigen::MatrixBase< Derived > &A)
- template<typename T >  
bool [check\\_nonzero\\_size](#) (const T &x) noexcept
- template<typename T1 , typename T2 >  
bool [check\\_matching\\_sizes](#) (const T1 &lhs, const T2 &rhs) noexcept
- bool [check\\_dims](#) (const std::vector< [idx](#) > &dims)
- template<typename Derived >  
bool [check\\_dims\\_match\\_mat](#) (const std::vector< [idx](#) > &dims, const Eigen::MatrixBase< Derived > &A)
- template<typename Derived >  
bool [check\\_dims\\_match\\_cvect](#) (const std::vector< [idx](#) > &dims, const Eigen::MatrixBase< Derived > &V)
- template<typename Derived >  
bool [check\\_dims\\_match\\_rvect](#) (const std::vector< [idx](#) > &dims, const Eigen::MatrixBase< Derived > &V)
- bool [check\\_eq\\_dims](#) (const std::vector< [idx](#) > &dims, [idx](#) dim) noexcept
- bool [check\\_subsys\\_match\\_dims](#) (const std::vector< [idx](#) > &subsys, const std::vector< [idx](#) > &dims)
- template<typename Derived >  
bool [check\\_qubit\\_matrix](#) (const Eigen::MatrixBase< Derived > &A) noexcept
- template<typename Derived >  
bool [check\\_qubit\\_cvector](#) (const Eigen::MatrixBase< Derived > &V) noexcept
- template<typename Derived >  
bool [check\\_qubit\\_rvector](#) (const Eigen::MatrixBase< Derived > &V) noexcept
- template<typename Derived >  
bool [check\\_qubit\\_vector](#) (const Eigen::MatrixBase< Derived > &V) noexcept
- bool [check\\_perm](#) (const std::vector< [idx](#) > &perm)
- template<typename Derived1 , typename Derived2 >  
[dyn\\_mat](#)< typename Derived1::Scalar > [kron2](#) (const Eigen::MatrixBase< Derived1 > &A, const Eigen::MatrixBase< Derived2 > &B)
- template<typename Derived1 , typename Derived2 >  
[dyn\\_mat](#)< typename Derived1::Scalar > [dirsum2](#) (const Eigen::MatrixBase< Derived1 > &A, const Eigen::MatrixBase< Derived2 > &B)
- template<typename T >  
void [variadic\\_vector\\_emplace](#) (std::vector< T > &)
- template<typename T , typename First , typename... Args>  
void [variadic\\_vector\\_emplace](#) (std::vector< T > &v, First &&first, Args &&...args)
- [idx get\\_num\\_subsys](#) ([idx](#) sz, [idx](#) d)
- [idx get\\_dim\\_subsys](#) ([idx](#) sz, [idx](#) N)

### 6.3.1 Detailed Description

Internal utility functions, do not use/modify.

### 6.3.2 Function Documentation

- 6.3.2.1 `template<typename Derived > bool qpp::internal::check_cvector ( const Eigen::MatrixBase< Derived > & A )`
- 6.3.2.2 `bool qpp::internal::check_dims ( const std::vector< idx > & dims ) [inline]`
- 6.3.2.3 `template<typename Derived > bool qpp::internal::check_dims_match_cvect ( const std::vector< idx > & dims, const Eigen::MatrixBase< Derived > & V )`
- 6.3.2.4 `template<typename Derived > bool qpp::internal::check_dims_match_mat ( const std::vector< idx > & dims, const Eigen::MatrixBase< Derived > & A )`
- 6.3.2.5 `template<typename Derived > bool qpp::internal::check_dims_match_rvect ( const std::vector< idx > & dims, const Eigen::MatrixBase< Derived > & V )`
- 6.3.2.6 `bool qpp::internal::check_eq_dims ( const std::vector< idx > & dims, idx dim ) [inline], [noexcept]`
- 6.3.2.7 `template<typename T1 , typename T2 > bool qpp::internal::check_matching_sizes ( const T1 & lhs, const T2 & rhs ) [noexcept]`
- 6.3.2.8 `template<typename T > bool qpp::internal::check_nonzero_size ( const T & x ) [noexcept]`
- 6.3.2.9 `bool qpp::internal::check_perm ( const std::vector< idx > & perm ) [inline]`
- 6.3.2.10 `template<typename Derived > bool qpp::internal::check_qubit_cvector ( const Eigen::MatrixBase< Derived > & V ) [noexcept]`
- 6.3.2.11 `template<typename Derived > bool qpp::internal::check_qubit_matrix ( const Eigen::MatrixBase< Derived > & A ) [noexcept]`
- 6.3.2.12 `template<typename Derived > bool qpp::internal::check_qubit_rvector ( const Eigen::MatrixBase< Derived > & V ) [noexcept]`
- 6.3.2.13 `template<typename Derived > bool qpp::internal::check_qubit_vector ( const Eigen::MatrixBase< Derived > & V ) [noexcept]`
- 6.3.2.14 `template<typename Derived > bool qpp::internal::check_rvector ( const Eigen::MatrixBase< Derived > & A )`
- 6.3.2.15 `template<typename Derived > bool qpp::internal::check_square_mat ( const Eigen::MatrixBase< Derived > & A )`
- 6.3.2.16 `bool qpp::internal::check_subsys_match_dims ( const std::vector< idx > & subsys, const std::vector< idx > & dims ) [inline]`
- 6.3.2.17 `template<typename Derived > bool qpp::internal::check_vector ( const Eigen::MatrixBase< Derived > & A )`
- 6.3.2.18 `template<typename Derived1 , typename Derived2 > dyn_mat<typename Derived1::Scalar> qpp::internal::dirsum2 ( const Eigen::MatrixBase< Derived1 > & A, const Eigen::MatrixBase< Derived2 > & B )`
- 6.3.2.19 `idx qpp::internal::get_dim_subsys ( idx sz, idx N ) [inline]`
- 6.3.2.20 `idx qpp::internal::get_num_subsys ( idx sz, idx d ) [inline]`
- 6.3.2.21 `template<typename Derived1 , typename Derived2 > dyn_mat<typename Derived1::Scalar> qpp::internal::kron2 ( const Eigen::MatrixBase< Derived1 > & A, const Eigen::MatrixBase< Derived2 > & B )`
- 6.3.2.22 `idx qpp::internal::multiidx2n ( const idx * midx, idx numdims, const idx * dims ) [inline], [noexcept]`

6.3.2.23 void qpp::internal::n2multiidx ( idx *n*, idx *numdims*, const idx \* *dims*, idx \* *result* ) [inline],  
[noexcept]

6.3.2.24 template<typename T> void qpp::internal::variadic\_vector\_emplace ( std::vector< T> & )

6.3.2.25 template<typename T, typename First, typename... Args> void qpp::internal::variadic\_vector\_emplace ( std::vector< T> & v, First && *first*, Args &&... *args* )

## 6.4 qpp::internal::details\_ Namespace Reference

### Classes

- struct [Display\\_Impl\\_](#)



## Chapter 7


# Class Documentation

### 7.1 qpp::Codes Class Reference


const Singleton class that defines quantum error correcting codes

```
#include <classes/codes.h>
```

Inheritance diagram for qpp::Codes:



Collaboration diagram for qpp::Codes:



## Public Types

- enum `Type` { `Type::FIVE_QUBIT` = 1, `Type::SEVEN_QUBIT_STEANE`, `Type::NINE_QUBIT_SHOR` }  
Code types, add more codes here if needed.

## Public Member Functions

- `ket codeword` (`Type` type, `idx` i) const  
Returns the codeword of the specified code type.

## Private Member Functions

- `Codes` ()  
Default constructor.
- `~Codes` ()=default  
Default destructor.

## Friends

- class `internal::Singleton< const Codes >`

## Additional Inherited Members

### 7.1.1 Detailed Description

const Singleton class that defines quantum error correcting codes

### 7.1.2 Member Enumeration Documentation

#### 7.1.2.1 enum `qpp::Codes::Type` [strong]

Code types, add more codes here if needed.

See also

`qpp::Codes::codeword()`

#### Enumerator

**`FIVE_QUBIT`** [[5,1,3]] qubit code  
**`SEVEN_QUBIT_STEANE`** [[7,1,3]] Steane qubit code  
**`NINE_QUBIT_SHOR`** [[9,1,3]] Shor qubit code

### 7.1.3 Constructor & Destructor Documentation

#### 7.1.3.1 `qpp::Codes::Codes ( )` [inline],[private]

Default constructor.

#### 7.1.3.2 `qpp::Codes::~Codes ( )` [private],[default]

Default destructor.

### 7.1.4 Member Function Documentation

#### 7.1.4.1 ket qpp::Codes::codeword ( Type *type*, idx *i* ) const [inline]

Returns the codeword of the specified code type.

See also

[qpp::Codes::Type](#)

#### Parameters

<i>type</i>	Code type
<i>i</i>	Codeword index

#### Returns

*i*-th codeword of the code *type*

### 7.1.5 Friends And Related Function Documentation

#### 7.1.5.1 friend class internal::Singleton< const Codes > [friend]


The documentation for this class was generated from the following file:

- [classes/codes.h](#)

## 7.2 qpp::internal::details\_::Display\_Impl\_ Struct Reference

```
#include <internal/classes/iomanip.h>
```

Inheritance diagram for qpp::internal::details\_::Display\_Impl\_:



### Public Member Functions

- `template<typename T >`  
`std::ostream & display_impl_ (const T &A, std::ostream &os, double chop=qpp::chop) const`

### 7.2.1 Member Function Documentation

7.2.1.1 `template<typename T > std::ostream& qpp::internal::details::Display_Impl::display_impl_( const T & A, std::ostream & os, double chop = qpp::chop ) const [inline]`

The documentation for this struct was generated from the following file:


- [internal/classes/iomanip.h](#)

## 7.3 qpp::Exception Class Reference


Generates custom exceptions, used when validating function parameters.

```
#include <classes/exception.h>
```

Inheritance diagram for qpp::Exception:



Collaboration diagram for qpp::Exception:





## Public Types

- enum [Type](#) {  
[Type::UNKNOWN\\_EXCEPTION](#) = 1, [Type::ZERO\\_SIZE](#), [Type::MATRIX\\_NOT\\_SQUARE](#), [Type::MATRIX\\_↵  
NOT\\_CVECTOR](#),  
[Type::MATRIX\\_NOT\\_RVECTOR](#), [Type::MATRIX\\_NOT\\_VECTOR](#), [Type::MATRIX\\_NOT\\_SQUARE\\_OR\\_C↵  
VECTOR](#), [Type::MATRIX\\_NOT\\_SQUARE\\_OR\\_RVECTOR](#),  
[Type::MATRIX\\_NOT\\_SQUARE\\_OR\\_VECTOR](#), [Type::MATRIX\\_MISMATCH\\_SUBSYS](#), [Type::DIMS\\_INVA↵  
LID](#), [Type::DIMS\\_NOT\\_EQUAL](#),  
[Type::DIMS\\_MISMATCH\\_MATRIX](#), [Type::DIMS\\_MISMATCH\\_CVECTOR](#), [Type::DIMS\\_MISMATCH\\_RVE↵  
CTOR](#), [Type::DIMS\\_MISMATCH\\_VECTOR](#),  
[Type::SUBSYS\\_MISMATCH\\_DIMS](#), [Type::PERM\\_INVALID](#), [Type::PERM\\_MISMATCH\\_DIMS](#), [Type::NOT↵  
\\_QUBIT\\_MATRIX](#),  
[Type::NOT\\_QUBIT\\_CVECTOR](#), [Type::NOT\\_QUBIT\\_RVECTOR](#), [Type::NOT\\_QUBIT\\_VECTOR](#), [Type::NO↵  
T\\_QUBIT\\_SUBSYS](#),  
[Type::NOT\\_BIPARTITE](#), [Type::NO\\_CODEWORD](#), [Type::OUT\\_OF\\_RANGE](#), [Type::TYPE\\_MISMATCH](#),  
[Type::SIZE\\_MISMATCH](#), [Type::UNDEFINED\\_TYPE](#), [Type::CUSTOM\\_EXCEPTION](#) }

*Exception types, add more here if needed.*

## Public Member Functions

- [Exception](#) (const std::string &where, const [Type](#) &type)  
*Constructs an exception.*
- [Exception](#) (const std::string &where, const std::string &custom)  
*Constructs an exception.*
- virtual const char \* [what](#) () const noexcept override  
*Overrides std::exception::what()*

## Private Member Functions

- void [construct\\_exception\\_msg\\_](#) ()  
*Constructs the exception description from its type.*

## Private Attributes

- std::string [where\\_](#)
- std::string [msg\\_](#)
- [Type](#) [type\\_](#)
- std::string [custom\\_](#)

### 7.3.1 Detailed Description

Generates custom exceptions, used when validating function parameters.

Customize this class if more exceptions are needed

### 7.3.2 Member Enumeration Documentation

#### 7.3.2.1 enum qpp::Exception::Type [strong]

[Exception](#) types, add more here if needed.

See also

[qpp::Exception::construct\\_exception\\_msg\\_\(\)](#)

Enumerator

**UNKNOWN\_EXCEPTION** Unknown exception

**ZERO\_SIZE** Zero sized object, e.g. empty `Eigen::Matrix` or `std::vector<>` with no elements

**MATRIX\_NOT\_SQUARE** `Eigen::Matrix` is not square

**MATRIX\_NOT\_CVECTOR** `Eigen::Matrix` is not a column vector

**MATRIX\_NOT\_RVECTOR** `Eigen::Matrix` is not a row vector

**MATRIX\_NOT\_VECTOR** `Eigen::Matrix` is not a row/column vector

**MATRIX\_NOT\_SQUARE\_OR\_CVECTOR** `Eigen::Matrix` is not square nor a column vector

**MATRIX\_NOT\_SQUARE\_OR\_RVECTOR** `Eigen::Matrix` is not square nor a row vector

**MATRIX\_NOT\_SQUARE\_OR\_VECTOR** `Eigen::Matrix` is not square nor a row/column vector

**MATRIX\_MISMATCH\_SUBSYS** Matrix size mismatch subsystem sizes (e.g. in [qpp::apply\(\)](#))

**DIMS\_INVALID** `std::vector<idx>` of dimensions has zero size or contains zeros

**DIMS\_NOT\_EQUAL** Local/global dimensions are not equal

**DIMS\_MISMATCH\_MATRIX** Product of the elements of `std::vector<idx>` of dimensions is not equal to the number of rows of `Eigen::Matrix` (assumed to be a square matrix)

**DIMS\_MISMATCH\_CVECTOR** Product of the elements of `std::vector<idx>` of dimensions is not equal to the number of elements of `Eigen::Matrix` (assumed to be a column vector)

**DIMS\_MISMATCH\_RVECTOR** Product of the elements of `std::vector<idx>` of dimensions is not equal to the number of elements of `Eigen::Matrix` (assumed to be a row vector)

**DIMS\_MISMATCH\_VECTOR** Product of the elements of `std::vector<idx>` of dimensions is not equal to the number of elements of `Eigen::Matrix` (assumed to be a row/column vector)

**SUBSYS\_MISMATCH\_DIMS** `std::vector<idx>` of subsystem labels has duplicates, or has entries that are larger than the size of the `std::vector<idx>` of dimensions

**PERM\_INVALID** `std::vector<idx>` does not represent a valid permutation

**PERM\_MISMATCH\_DIMS** Size of the `std::vector<idx>` representing the permutation is different from the size of the `std::vector<idx>` of dimensions

**NOT\_QUBIT\_MATRIX** `Eigen::Matrix` is not 2 x 2

**NOT\_QUBIT\_CVECTOR** `Eigen::Matrix` is not 2 x 1

**NOT\_QUBIT\_RVECTOR** `Eigen::Matrix` is not 1 x 2

**NOT\_QUBIT\_VECTOR** `Eigen::Matrix` is not 1 x 2 nor 2 x 1

**NOT\_QUBIT\_SUBSYS** Subsystems are not 2-dimensional

**NOT\_BIPARTITE** `std::vector<idx>` of dimensions has size different from 2

**NO\_CODEWORD** Codeword does not exist, thrown when calling [qpp::Codes::codeword\(\)](#) with invalid index *i*

**OUT\_OF\_RANGE** Parameter out of range

**TYPE\_MISMATCH** Scalar types do not match

**SIZE\_MISMATCH** Sizes do not match

**UNDEFINED\_TYPE** Templated specialization not defined for this type

**CUSTOM\_EXCEPTION** Custom exception, user must provide a custom message

### 7.3.3 Constructor & Destructor Documentation

7.3.3.1 `qpp::Exception::Exception ( const std::string & where, const Type & type )` `[inline]`

Constructs an exception.

## Parameters

<i>where</i>	Text representing where the exception occurred
<i>type</i>	<a href="#">Exception</a> type, defined in <a href="#">qpp::Exception::Type</a>

7.3.3.2 `qpp::Exception::Exception ( const std::string & where, const std::string & custom ) [inline]`

Constructs an exception.

This is an overloaded member function, provided for convenience. It differs from the above function only in what argument(s) it accepts.

## Parameters

<i>where</i>	Text representing where the exception occurred
<i>custom</i>	<a href="#">Exception</a> description

## 7.3.4 Member Function Documentation

7.3.4.1 `void qpp::Exception::construct_exception_msg_ ( ) [inline], [private]`

Constructs the exception description from its type.

See also

[qpp::Exception::Type](#)

Must modify the code of this function if more exceptions are added

7.3.4.2 `virtual const char* qpp::Exception::what ( ) const [inline], [override], [virtual], [noexcept]`

Overrides `std::exception::what()`

## Returns

[Exception](#) description

## 7.3.5 Member Data Documentation

7.3.5.1 `std::string qpp::Exception::custom_ [private]`7.3.5.2 `std::string qpp::Exception::msg_ [private]`7.3.5.3 `Type qpp::Exception::type_ [private]`7.3.5.4 `std::string qpp::Exception::where_ [private]`

The documentation for this class was generated from the following file:


- `classes/exception.h`

7.4 `qpp::Gates` Class Reference


const Singleton class that implements most commonly used gates

```
#include <classes/gates.h>
```

Inheritance diagram for qpp::Gates:



Collaboration diagram for qpp::Gates:



## Public Member Functions

- `cmat Rn` (double theta, const std::vector< double > &n) const  
*Qubit rotation of theta about the 3-dimensional real (unit) vector n.*
- `cmat Zd` (idx D) const  
*Generalized Z gate for qudits.*
- `cmat Fd` (idx D) const  
*Fourier transform gate for qudits.*
- `cmat Xd` (idx D) const  
*Generalized X gate for qudits.*
- `template<typename Derived = Eigen::MatrixXcd>`  
`Derived Id` (idx D) const  
*Identity gate.*
- `template<typename Derived >`  
`dyn_mat`< typename Derived::Scalar > `CTRL` (const Eigen::MatrixBase< Derived > &A, const std::vector< idx > &ctrl, const std::vector< idx > &subsys, idx N, idx d=2) const  
*Generates the multi-partite multiple-controlled-A gate in matrix form.*

- `template<typename Derived >`  
`dyn_mat< typename Derived::Scalar > expandout (const Eigen::MatrixBase< Derived > &A, idx pos, const`  
`std::vector< idx > &dims) const`  
*Expands out.*

## Public Attributes

- `cmat Id2 {cmat::Identity(2, 2)}`  
*Identity gate.*
- `cmat H {cmat::Zero(2, 2)}`  
*Hadamard gate.*
- `cmat X {cmat::Zero(2, 2)}`  
*Pauli Sigma-X gate.*
- `cmat Y {cmat::Zero(2, 2)}`  
*Pauli Sigma-Y gate.*
- `cmat Z {cmat::Zero(2, 2)}`  
*Pauli Sigma-Z gate.*
- `cmat S {cmat::Zero(2, 2)}`  
*S gate.*
- `cmat T {cmat::Zero(2, 2)}`  
*T gate.*
- `cmat CNOT {cmat::Identity(4, 4)}`  
*Controlled-NOT control target gate.*
- `cmat CZ {cmat::Identity(4, 4)}`  
*Controlled-Phase gate.*
- `cmat CNOTba {cmat::Zero(4, 4)}`  
*Controlled-NOT target control gate.*
- `cmat SWAP {cmat::Identity(4, 4)}`  
*SWAP gate.*
- `cmat TOF {cmat::Identity(8, 8)}`  
*Toffoli gate.*
- `cmat FRED {cmat::Identity(8, 8)}`  
*Fredkin gate.*

## Private Member Functions

- `Gates ()`  
*Initializes the gates.*
- `~Gates ()=default`  
*Default destructor.*

## Friends

- class `internal::Singleton< const Gates >`

## Additional Inherited Members

### 7.4.1 Detailed Description

const Singleton class that implements most commonly used gates

## 7.4.2 Constructor & Destructor Documentation

### 7.4.2.1 `qpp::Gates::Gates ( ) [inline], [private]`

Initializes the gates.

### 7.4.2.2 `qpp::Gates::~~Gates ( ) [private], [default]`

Default destructor.

## 7.4.3 Member Function Documentation

### 7.4.3.1 `template<typename Derived > dyn_mat<typename Derived::Scalar> qpp::Gates::CTRL ( const Eigen::MatrixBase<Derived > & A, const std::vector< idx > & ctrl, const std::vector< idx > & subsys, idx N, idx d = 2 ) const [inline]`

Generates the multi-partite multiple-controlled- $A$  gate in matrix form.

See also

[qpp::applyCTRL\(\)](#)

Note

The dimension of the gate  $A$  must match the dimension of *subsys*

Parameters

$A$	Eigen expression
<i>ctrl</i>	Control subsystem indexes
<i>subsys</i>	Subsystem indexes where the gate $A$ is applied
$N$	Total number of subsystems
$d$	Subsystem dimensions

Returns

CTRL- $A$  gate, as a matrix over the same scalar field as  $A$

### 7.4.3.2 `template<typename Derived > dyn_mat<typename Derived::Scalar> qpp::Gates::expandout ( const Eigen::MatrixBase< Derived > & A, idx pos, const std::vector< idx > & dims ) const [inline]`

Expands out.

See also

[qpp::kron\(\)](#)

Expands out  $A$  as a matrix in a multi-partite system. Faster than using [qpp::kron\(I, I, ..., I, A, I, ..., I\)](#).

Parameters

$A$	Eigen expression
-----	------------------

<i>pos</i>	Position
<i>dims</i>	Dimensions of the multi-partite system

**Returns**

Tensor product  $I \otimes \dots \otimes I \otimes A \otimes I \otimes \dots \otimes I$ , with  $A$  on position  $pos$ , as a dynamic matrix over the same scalar field as  $A$

**7.4.3.3 cmat qpp::Gates::Fd ( idx  $D$  ) const [inline]**

Fourier transform gate for qudits.

**Note**

Defined as  $F = \sum_{jk} \exp(2\pi i jk/D) |j\rangle\langle k|$

**Parameters**

$D$	Dimension of the Hilbert space
-----	--------------------------------

**Returns**

Fourier transform gate for qudits

**7.4.3.4 template<typename Derived = Eigen::MatrixXcd> Derived qpp::Gates::Id ( idx  $D$  ) const [inline]**

Identity gate.

**Note**

Can change the return type from complex matrix (default) by explicitly specifying the template parameter

**Parameters**

$D$	Dimension of the Hilbert space
-----	--------------------------------

**Returns**

Identity gate

**7.4.3.5 cmat qpp::Gates::Rn ( double  $\theta$ , const std::vector< double > &  $n$  ) const [inline]**

Qubit rotation of  $\theta$  about the 3-dimensional real (unit) vector  $n$ .

**Parameters**

$\theta$	Rotation angle
$n$	3-dimensional real (unit) vector

**Returns**

Rotation gate

#### 7.4.3.6 `cmat qpp::Gates::Xd ( idx D ) const [inline]`

Generalized X gate for qudits.

##### Note

Defined as  $X = \sum_j |j \oplus 1\rangle\langle j|$ , i.e. raising operator  $X|j\rangle = |j \oplus 1\rangle$

##### Parameters

$D$	Dimension of the Hilbert space
-----	--------------------------------

##### Returns

Generalized X gate for qudits

#### 7.4.3.7 `cmat qpp::Gates::Zd ( idx D ) const [inline]`

Generalized Z gate for qudits.

##### Note

Defined as  $Z = \sum_j \exp(2\pi i j / D) |j\rangle\langle j|$

##### Parameters

$D$	Dimension of the Hilbert space
-----	--------------------------------

##### Returns

Generalized Z gate for qudits

### 7.4.4 Friends And Related Function Documentation

#### 7.4.4.1 `friend class internal::Singleton< const Gates > [friend]`

### 7.4.5 Member Data Documentation

#### 7.4.5.1 `cmat qpp::Gates::CNOT {cmat::Identity(4, 4)}`

Controlled-NOT control target gate.

#### 7.4.5.2 `cmat qpp::Gates::CNOTba {cmat::Zero(4, 4)}`

Controlled-NOT target control gate.

#### 7.4.5.3 `cmat qpp::Gates::CZ {cmat::Identity(4, 4)}`

Controlled-Phase gate.

#### 7.4.5.4 `cmat qpp::Gates::FRED {cmat::Identity(8, 8)}`

Fredkin gate.



7.4.5.5 `cmat qpp::Gates::H {cmat::Zero(2, 2)}`

Hadamard gate.

7.4.5.6 `cmat qpp::Gates::Id2 {cmat::Identity(2, 2)}`

Identity gate.

7.4.5.7 `cmat qpp::Gates::S {cmat::Zero(2, 2)}`

S gate.

7.4.5.8 `cmat qpp::Gates::SWAP {cmat::Identity(4, 4)}`

SWAP gate.

7.4.5.9 `cmat qpp::Gates::T {cmat::Zero(2, 2)}`

T gate.

7.4.5.10 `cmat qpp::Gates::TOF {cmat::Identity(8, 8)}`

Toffoli gate.

7.4.5.11 `cmat qpp::Gates::X {cmat::Zero(2, 2)}`

Pauli Sigma-X gate.

7.4.5.12 `cmat qpp::Gates::Y {cmat::Zero(2, 2)}`

Pauli Sigma-Y gate.

7.4.5.13 `cmat qpp::Gates::Z {cmat::Zero(2, 2)}`

Pauli Sigma-Z gate.

The documentation for this class was generated from the following file:


- [classes/gates.h](#)

## 7.5 qpp::IDisplay Class Reference

Abstract class (interface) that mandates the definition of virtual `std::ostream& display(std::ostream& os) const`.

```
#include <classes/ideisplay.h>
```

Inheritance diagram for qpp::IDisplay:



## Public Member Functions

- `IDisplay()`=default  
*Default constructor.*
- `IDisplay(const IDisplay &)=default`  
*Default copy constructor.*
- `IDisplay(IDisplay &&)=default`  
*Default move constructor.*
- `IDisplay & operator= (const IDisplay &)=default`  
*Default copy assignment operator.*
- `IDisplay & operator= (IDisplay &&)=default`  
*Default move assignment operator.*
- `virtual ~IDisplay()`=default  
*Default virtual destructor.*

## Private Member Functions

- `virtual std::ostream & display (std::ostream &os) const =0`  
*Must be overridden by all derived classes.*

## Friends

- `std::ostream & operator<< (std::ostream &os, const IDisplay &rhs)`  
*Overloads the extraction operator.*

### 7.5.1 Detailed Description

Abstract class (interface) that mandates the definition of virtual `std::ostream& display(std::ostream& os) const`.

This class defines friend inline `std::ostream& operator<< (std::ostream& os, const qpp::IDisplay& rhs)`. The latter delegates the work to the pure private virtual function `qpp::IDisplay::display()` which has to be overridden by all derived classes.

### 7.5.2 Constructor & Destructor Documentation

#### 7.5.2.1 `qpp::IDisplay::IDisplay ( )` [default]

Default constructor.

#### 7.5.2.2 `qpp::IDisplay::IDisplay ( const IDisplay & )` [default]

Default copy constructor.

#### 7.5.2.3 `qpp::IDisplay::IDisplay ( IDisplay && )` [default]

Default move constructor.

#### 7.5.2.4 `virtual qpp::IDisplay::~IDisplay ( )` [virtual], [default]

Default virtual destructor.

### 7.5.3 Member Function Documentation

#### 7.5.3.1 `virtual std::ostream& qpp::IDisplay::display ( std::ostream & os ) const` [private], [pure virtual]

Must be overridden by all derived classes.

The actual stream extraction processing is performed by the overridden member function in the derived class. This function is automatically invoked by friend inline `std::ostream& operator<<(std::ostream& os, const IDisplay& rhs)`.

Implemented in `qpp::internal::IOManipEigen`, `qpp::internal::IOManipPointer< PointerType >`, `qpp::internal::IO↔ManipRange< InputIterator >`, and `qpp::Timer< T, CLOCK_T >`.

#### 7.5.3.2 `IDisplay& qpp::IDisplay::operator= ( const IDisplay & )` [default]

Default copy assignment operator.

#### 7.5.3.3 `IDisplay& qpp::IDisplay::operator= ( IDisplay && )` [default]

Default move assignment operator.

### 7.5.4 Friends And Related Function Documentation

#### 7.5.4.1 `std::ostream& operator<< ( std::ostream & os, const IDisplay & rhs )` [friend]

Overloads the extraction operator.

Delegates the work to the virtual function `qpp::IDisplay::display()`

The documentation for this class was generated from the following file:


- [classes/ideplay.h](#)

## 7.6 qpp::Init Class Reference


const Singleton class that performs additional initializations/cleanups

```
#include <classes/init.h>
```

Inheritance diagram for qpp::Init:



Collaboration diagram for qpp::Init:



### Private Member Functions

- [Init \(\)](#)  
*Additional initializations.*
- [~Init \(\)](#)  
*Cleanups.*

### Friends

- class [internal::Singleton< const Init >](#)

## Additional Inherited Members

### 7.6.1 Detailed Description

const Singleton class that performs additional initializations/cleanups

### 7.6.2 Constructor & Destructor Documentation

#### 7.6.2.1 qpp::Init::Init( ) [inline], [private]

Additional initializations.

#### 7.6.2.2 qpp::Init::~~Init( ) [inline], [private]

Cleanups.

### 7.6.3 Friends And Related Function Documentation

#### 7.6.3.1 friend class internal::Singleton< const Init > [friend]


The documentation for this class was generated from the following file:

- [classes/init.h](#)


## 7.7 qpp::internal::IOManipEigen Class Reference

```
#include <internal/classes/iomanip.h>
```

Inheritance diagram for qpp::internal::IOManipEigen:



Collaboration diagram for `qpp::internal::IOManipEigen`:



## Public Member Functions

- `template<typename Derived > IOManipEigen (const Eigen::MatrixBase< Derived > &A, double chop=qpp::chop)`
- `IOManipEigen (const cplx z, double chop=qpp::chop)`

## Private Member Functions

- `std::ostream & display (std::ostream &os) const` override  
*Must be overridden by all derived classes.*

## Private Attributes

- `cmat A_`
- `double chop_`

### 7.7.1 Constructor & Destructor Documentation

7.7.1.1 `template<typename Derived > qpp::internal::IOManipEigen::IOManipEigen ( const Eigen::MatrixBase< Derived > &A, double chop = qpp::chop ) [inline],[explicit]`

7.7.1.2 `qpp::internal::IOManipEigen::IOManipEigen ( const cplx z, double chop = qpp::chop ) [inline],[explicit]`

### 7.7.2 Member Function Documentation

7.7.2.1 `std::ostream& qpp::internal::IOManipEigen::display ( std::ostream & os ) const [inline],[override],[private],[virtual]`

Must be overridden by all derived classes.

The actual stream extraction processing is performed by the overridden member function in the derived class. This function is automatically invoked by friend inline `std::ostream& operator<<(std::ostream& os, const IDisplay& rhs)`.

Implements `qpp::IDisplay`.

### 7.7.3 Member Data Documentation

7.7.3.1 `cmat qpp::internal::IManipEigen::A_` [private]

7.7.3.2 `double qpp::internal::IManipEigen::chop_` [private]


The documentation for this class was generated from the following file:

- [internal/classes/iomanip.h](#)


## 7.8 qpp::internal::IManipPointer< PointerType > Class Template Reference

```
#include <internal/classes/iomanip.h>
```

Inheritance diagram for `qpp::internal::IManipPointer< PointerType >`:



Collaboration diagram for `qpp::internal::IManipPointer< PointerType >`:



## Public Member Functions

- [IOManipPointer](#) (const PointerType \*p, [idx](#) N, const std::string &separator, const std::string &start="[" , const std::string &end="]")
- [IOManipPointer](#) (const [IOManipPointer](#) &)=default
- [IOManipPointer](#) & [operator=](#) (const [IOManipPointer](#) &)=default

## Private Member Functions

- std::ostream & [display](#) (std::ostream &os) const override  
*Must be overridden by all derived classes.*

## Private Attributes

- const PointerType \* [p\\_](#)
- [idx](#) [N\\_](#)
- std::string [separator\\_](#)
- std::string [start\\_](#)
- std::string [end\\_](#)

## 7.8.1 Constructor & Destructor Documentation

- 7.8.1.1 `template<typename PointerType> qpp::internal::IOManipPointer< PointerType >::IOManipPointer ( const PointerType * p, idx N, const std::string & separator, const std::string & start = " [ ", const std::string & end = " ] " ) [inline], [explicit]`
- 7.8.1.2 `template<typename PointerType> qpp::internal::IOManipPointer< PointerType >::IOManipPointer ( const IOManipPointer< PointerType > & ) [default]`

## 7.8.2 Member Function Documentation

- 7.8.2.1 `template<typename PointerType> std::ostream& qpp::internal::IOManipPointer< PointerType >::display ( std::ostream & os ) const [inline], [override], [private], [virtual]`

Must be overridden by all derived classes.

The actual stream extraction processing is performed by the overridden member function in the derived class. This function is automatically invoked by friend inline std::ostream& operator<<(std::ostream& os, const [IDisplay](#)& rhs).

Implements [qpp::IDisplay](#).

- 7.8.2.2 `template<typename PointerType> IOManipPointer& qpp::internal::IOManipPointer< PointerType >::operator= ( const IOManipPointer< PointerType > & ) [default]`

## 7.8.3 Member Data Documentation

- 7.8.3.1 `template<typename PointerType> std::string qpp::internal::IOManipPointer< PointerType >::end_ [private]`
- 7.8.3.2 `template<typename PointerType> idx qpp::internal::IOManipPointer< PointerType >::N_ [private]`
- 7.8.3.3 `template<typename PointerType> const PointerType* qpp::internal::IOManipPointer< PointerType >::p_ [private]`



7.8.3.4 `template<typename PointerType> std::string qpp::internal::IOManipPointer< PointerType >::separator_  
[private]`

7.8.3.5 `template<typename PointerType> std::string qpp::internal::IOManipPointer< PointerType >::start_  
[private]`


The documentation for this class was generated from the following file:

- [internal/classes/iomanip.h](#)


## 7.9 qpp::internal::IOManipRange< InputIterator > Class Template Reference

```
#include <internal/classes/iomanip.h>
```

Inheritance diagram for `qpp::internal::IOManipRange< InputIterator >`:



Collaboration diagram for `qpp::internal::IOManipRange< InputIterator >`:



## Public Member Functions

- [IOManipRange](#) (InputIterator first, InputIterator last, const std::string &separator, const std::string &start="[,", const std::string &end="]")
- [IOManipRange](#) (const [IOManipRange](#) &)=default
- [IOManipRange](#) & [operator=](#) (const [IOManipRange](#) &)=default

## Private Member Functions

- std::ostream & [display](#) (std::ostream &os) const override  
*Must be overridden by all derived classes.*

## Private Attributes

- InputIterator [first\\_](#)
- InputIterator [last\\_](#)
- std::string [separator\\_](#)
- std::string [start\\_](#)
- std::string [end\\_](#)

### 7.9.1 Constructor & Destructor Documentation

- 7.9.1.1 `template<typename InputIterator> qpp::internal::IOManipRange< InputIterator >::IOManipRange ( InputIterator first, InputIterator last, const std::string & separator, const std::string & start = " [,", const std::string & end = "]" ) [inline],[explicit]`
- 7.9.1.2 `template<typename InputIterator> qpp::internal::IOManipRange< InputIterator >::IOManipRange ( const IOManipRange< InputIterator > & ) [default]`

### 7.9.2 Member Function Documentation

- 7.9.2.1 `template<typename InputIterator> std::ostream& qpp::internal::IOManipRange< InputIterator >::display ( std::ostream & os ) const [inline],[override],[private],[virtual]`

Must be overridden by all derived classes.

The actual stream extraction processing is performed by the overridden member function in the derived class. This function is automatically invoked by friend inline std::ostream& operator<<(std::ostream& os, const [IDisplay](#)& rhs).

Implements [qpp::IDisplay](#).

- 7.9.2.2 `template<typename InputIterator> IOManipRange& qpp::internal::IOManipRange< InputIterator >::operator= ( const IOManipRange< InputIterator > & ) [default]`

### 7.9.3 Member Data Documentation

- 7.9.3.1 `template<typename InputIterator> std::string qpp::internal::IOManipRange< InputIterator >::end_ [private]`
- 7.9.3.2 `template<typename InputIterator> InputIterator qpp::internal::IOManipRange< InputIterator >::first_ [private]`
- 7.9.3.3 `template<typename InputIterator> InputIterator qpp::internal::IOManipRange< InputIterator >::last_ [private]`

7.9.3.4 `template<typename InputIterator> std::string qpp::internal::IOManipRange< InputIterator >::separator_`  
`[private]`

7.9.3.5 `template<typename InputIterator> std::string qpp::internal::IOManipRange< InputIterator >::start_`  
`[private]`

The documentation for this class was generated from the following file:

- [internal/classes/iomanip.h](#)

## 7.10 qpp::is\_complex< T > Struct Template Reference

Checks whether the type is a complex type.

`#include <traits.h>`

Inheritance diagram for `qpp::is_complex< T >`:



Collaboration diagram for `qpp::is_complex< T >`:



### 7.10.1 Detailed Description

`template<typename T> struct qpp::is_complex< T >`

Checks whether the type is a complex type.

Provides the member constant *value* which is equal to *true*, if the type is a complex type, i.e. `std::complex< T >`

The documentation for this struct was generated from the following file:


- [traits.h](#)

## 7.11 qpp::is\_complex< std::complex< T > > Struct Template Reference


Checks whether the type is a complex number type, specialization for complex types.

```
#include <traits.h>
```

Inheritance diagram for qpp::is\_complex< std::complex< T > >:



Collaboration diagram for qpp::is\_complex< std::complex< T > >:



### 7.11.1 Detailed Description

```
template<typename T>struct qpp::is_complex< std::complex< T > >
```

Checks whether the type is a complex number type, specialization for complex types.

The documentation for this struct was generated from the following file:


- [traits.h](#)

## 7.12 qpp::is\_iterable< T, typename > Struct Template Reference


Checks whether *T* is compatible with an STL-like iterable container.

```
#include <traits.h>
```

Inheritance diagram for qpp::is\_iterable< T, typename >:



Collaboration diagram for qpp::is\_iterable< T, typename >:



### 7.12.1 Detailed Description

```
template<typename T, typename = void>struct qpp::is_iterable< T, typename >
```

Checks whether *T* is compatible with an STL-like iterable container.

Provides the member constant *value* which is equal to *true*, if *T* is compatible with an iterable container, i.e. provides at least *begin()* and *end()* member functions. Otherwise, *value* is equal to *false*.

The documentation for this struct was generated from the following file:


- [traits.h](#)

### 7.13 qpp::is\_iterable< T, to\_void< decltype(std::declval< T >().begin()), decltype(std::declval< T >().end()), typename T::value\_type > > Struct Template Reference


Checks whether *T* is compatible with an STL-like iterable container, specialization for STL-like iterable containers.

```
#include <traits.h>
```

Inheritance diagram for qpp::is\_iterable< T, to\_void< decltype(std::declval< T >().begin()), decltype(std::declval< T >().end()), typename T::value\_type > >:



Collaboration diagram for qpp::is\_iterable< T, to\_void< decltype(std::declval< T >().begin()), decltype(std::declval< T >().end()), typename T::value\_type > >:



#### 7.13.1 Detailed Description

```
template<typename T>struct qpp::is_iterable< T, to_void< decltype(std::declval< T >().begin()), decltype(std::declval< T >().end()), typename T::value_type > >
```

Checks whether *T* is compatible with an STL-like iterable container, specialization for STL-like iterable containers.

The documentation for this struct was generated from the following file:


- [traits.h](#)

## 7.14 qpp::is\_matrix\_expression< Derived > Struct Template Reference


Checks whether the type is an Eigen matrix expression.

```
#include <traits.h>
```

Inheritance diagram for qpp::is\_matrix\_expression< Derived >:



Collaboration diagram for qpp::is\_matrix\_expression< Derived >:



### 7.14.1 Detailed Description

```
template<typename Derived>struct qpp::is_matrix_expression< Derived >
```

Checks whether the type is an Eigen matrix expression.

Provides the member constant *value* which is equal to *true*, if the type is an Eigen matrix expression of type *Eigen::MatrixBase<Derived>*. Otherwise, *value* is equal to *false*.

The documentation for this struct was generated from the following file:


- [traits.h](#)

## 7.15 qpp::is\_matrix\_expression< typename Eigen::MatrixBase< Derived > > Struct Template Reference


Checks whether the type is an Eigen matrix expression, specialization for Eigen matrix expressions.

```
#include <traits.h>
```

Inheritance diagram for qpp::is\_matrix\_expression< typename Eigen::MatrixBase< Derived > >:



Collaboration diagram for qpp::is\_matrix\_expression< typename Eigen::MatrixBase< Derived > >:



### 7.15.1 Detailed Description

```
template<typename Derived> struct qpp::is_matrix_expression< typename Eigen::MatrixBase< Derived > >
```

Checks whether the type is an Eigen matrix expression, specialization for Eigen matrix expressions.



The documentation for this struct was generated from the following file:


- [traits.h](#)

## 7.16 qpp::RandomDevices Class Reference


Singleton class that manages the source of randomness in the library.

```
#include <classes/random_devices.h>
```

Inheritance diagram for qpp::RandomDevices:



Collaboration diagram for qpp::RandomDevices:



### Public Attributes

- `std::mt19937 rng_`  
*Mersenne twister random number generator.*

### Private Member Functions

- `RandomDevices ()`  
*Initializes and seeds the random number generators.*

- [~RandomDevices](#) ()=default  
*Default destructor.*

## Private Attributes

- `std::random_device rd_`  
*used to seed std::mt19937 rng\_*

## Friends

- class [internal::Singleton< RandomDevices >](#)

## Additional Inherited Members

### 7.16.1 Detailed Description

Singleton class that manages the source of randomness in the library.

Consists of a wrapper around an `std::mt19937` Mersenne twister random number generator engine and an `std::random_device` engine. The latter is used to seed the Mersenne twister.

#### Warning

This class DOES NOT seed the standard C number generator used by `Eigen::Matrix::Random()`, since it is not thread safe. Do not use `Eigen::Matrix::Random()` or functions that depend on the C style random number engine, but use [qpp::rand\(\)](#) instead!

### 7.16.2 Constructor & Destructor Documentation

#### 7.16.2.1 `qpp::RandomDevices::RandomDevices ( )` [`inline`], [`private`]

Initializes and seeds the random number generators.

#### 7.16.2.2 `qpp::RandomDevices::~~RandomDevices ( )` [`private`], [`default`]

Default destructor.

### 7.16.3 Friends And Related Function Documentation

#### 7.16.3.1 `friend class internal::Singleton< RandomDevices >` [`friend`]

### 7.16.4 Member Data Documentation

#### 7.16.4.1 `std::random_device qpp::RandomDevices::rd_` [`private`]

used to seed `std::mt19937 rng_`

#### 7.16.4.2 `std::mt19937 qpp::RandomDevices::rng_`

Mersenne twister random number generator.

The documentation for this class was generated from the following file:

- `classes/random_devices.h`

## 7.17 qpp::internal::Singleton< T > Class Template Reference

[Singleton](#) policy class, used internally to implement the singleton pattern via CRTP (Curiously recurring template pattern)

```
#include <internal/classes/singleton.h>
```

### Static Public Member Functions

- static T & [get\\_instance](#) () noexcept(std::is\_nothrow\_constructible< T >::value)
- static T & [get\\_thread\\_local\\_instance](#) () noexcept(std::is\_nothrow\_constructible< T >::value)

### Protected Member Functions

- [Singleton](#) () noexcept=default
- [Singleton](#) (const [Singleton](#) &)=delete
- [Singleton](#) & [operator=](#) (const [Singleton](#) &)=delete
- virtual [~Singleton](#) ()=default

### 7.17.1 Detailed Description

```
template<typename T>class qpp::internal::Singleton< T >
```

[Singleton](#) policy class, used internally to implement the singleton pattern via CRTP (Curiously recurring template pattern)

To implement a singleton, derive your class from [qpp::internal::Singleton](#), make [qpp::internal::Singleton](#) a friend of your class, then declare the constructor and destructor of your class as private. To get an instance, use the static member function [qpp::internal::Singleton::get\\_instance\(\)](#) ([qpp::internal::Singleton::get\\_thread\\_local\\_instance\(\)](#)), which returns a reference (thread\_local reference) to your newly created singleton (thread-safe in C++11).

Example:

```
class MySingleton: public qpp::internal::Singleton<MySingleton>
{
    friend class qpp::internal::Singleton<MySingleton>;
public:
    // Declare all public members here
private:
    MySingleton()
    {
        // Implement the constructor here
    }
    ~MySingleton()
    {
        // Implement the destructor here
    }
};

MySingleton& mySingleton = MySingleton::get_instance(); // Get an instance
thread_local MySingleton& tls = MySingleton::get_thread_local_instance();
// Get a thread_local instance
```

### See also

Code of [qpp::Codes](#), [qpp::Gates](#), [qpp::Init](#), [qpp::RandomDevices](#), [qpp::States](#) or [qpp.h](#) for real world examples of usage.

## 7.17.2 Constructor & Destructor Documentation

7.17.2.1 `template<typename T> qpp::internal::Singleton< T >::Singleton ( )` [protected], [default], [noexcept]

7.17.2.2 `template<typename T> qpp::internal::Singleton< T >::Singleton ( const Singleton< T > & )` [protected], [delete]

7.17.2.3 `template<typename T> virtual qpp::internal::Singleton< T >::~~Singleton ( )` [protected], [virtual], [default]

## 7.17.3 Member Function Documentation

7.17.3.1 `template<typename T> static T& qpp::internal::Singleton< T >::get_instance ( )` [inline], [static], [noexcept]

7.17.3.2 `template<typename T> static T& qpp::internal::Singleton< T >::get_thread_local_instance ( )` [inline], [static], [noexcept]

7.17.3.3 `template<typename T> Singleton& qpp::internal::Singleton< T >::operator= ( const Singleton< T > & )` [protected], [delete]

The documentation for this class was generated from the following file:


- [internal/classes/singleton.h](#)

## 7.18 qpp::States Class Reference


const Singleton class that implements most commonly used states

```
#include <classes/states.h>
```

Inheritance diagram for qpp::States:



Collaboration diagram for qpp::States:



## Public Attributes

- **ket x0** {ket::Zero(2)}  
*Pauli Sigma-X 0-eigenstate  $|+\rangle$*
- **ket x1** {ket::Zero(2)}  
*Pauli Sigma-X 1-eigenstate  $|-\rangle$*
- **ket y0** {ket::Zero(2)}  
*Pauli Sigma-Y 0-eigenstate  $|y+\rangle$*
- **ket y1** {ket::Zero(2)}  
*Pauli Sigma-Y 1-eigenstate  $|y-\rangle$*
- **ket z0** {ket::Zero(2)}  
*Pauli Sigma-Z 0-eigenstate  $|0\rangle$*
- **ket z1** {ket::Zero(2)}  
*Pauli Sigma-Z 1-eigenstate  $|1\rangle$*
- **cmat px0** {cmat::Zero(2, 2)}  
*Projector onto the Pauli Sigma-X 0-eigenstate  $|+\rangle\langle+|$ .*
- **cmat px1** {cmat::Zero(2, 2)}  
*Projector onto the Pauli Sigma-X 1-eigenstate  $|-\rangle\langle-|$ .*
- **cmat py0** {cmat::Zero(2, 2)}  
*Projector onto the Pauli Sigma-Y 0-eigenstate  $|y+\rangle\langle y+|$ .*
- **cmat py1** {cmat::Zero(2, 2)}  
*Projector onto the Pauli Sigma-Y 1-eigenstate  $|y-\rangle\langle y-|$ .*
- **cmat pz0** {cmat::Zero(2, 2)}  
*Projector onto the Pauli Sigma-Z 0-eigenstate  $|0\rangle\langle 0|$ .*
- **cmat pz1** {cmat::Zero(2, 2)}  
*Projector onto the Pauli Sigma-Z 1-eigenstate  $|1\rangle\langle 1|$ .*
- **ket b00** {ket::Zero(4)}  
*Bell-00 state (following the convention in Nielsen and Chuang)*
- **ket b01** {ket::Zero(4)}  
*Bell-01 state (following the convention in Nielsen and Chuang)*
- **ket b10** {ket::Zero(4)}  
*Bell-10 state (following the convention in Nielsen and Chuang)*
- **ket b11** {ket::Zero(4)}  
*Bell-11 state (following the convention in Nielsen and Chuang)*
- **cmat pb00** {cmat::Zero(4, 4)}

- Projector onto the Bell-00 state.*
- `cmat pb01` {`cmat::Zero(4, 4)`}
- Projector onto the Bell-01 state.*
- `cmat pb10` {`cmat::Zero(4, 4)`}
- Projector onto the Bell-10 state.*
- `cmat pb11` {`cmat::Zero(4, 4)`}
- Projector onto the Bell-11 state.*
- `ket GHZ` {`ket::Zero(8)`}
- GHZ state.*
- `ket W` {`ket::Zero(8)`}
- W state.*
- `cmat pGHZ` {`cmat::Zero(8, 8)`}
- Projector onto the GHZ state.*
- `cmat pW` {`cmat::Zero(8, 8)`}
- Projector onto the W state.*

## Private Member Functions

- `States()`
  - `~States()`=default
- Default destructor.*

## Friends

- class `internal::Singleton< const States >`

## Additional Inherited Members

### 7.18.1 Detailed Description

const Singleton class that implements most commonly used states

### 7.18.2 Constructor & Destructor Documentation

#### 7.18.2.1 `qpp::States::States ( )` [inline], [private]

Initialize the states

#### 7.18.2.2 `qpp::States::~~States ( )` [private], [default]

Default destructor.

### 7.18.3 Friends And Related Function Documentation

#### 7.18.3.1 `friend class internal::Singleton< const States >` [friend]

### 7.18.4 Member Data Documentation

#### 7.18.4.1 `ket qpp::States::b00` {`ket::Zero(4)`}

Bell-00 state (following the convention in Nielsen and Chuang)

## 7.18.4.2 ket qpp::States::b01 {ket::Zero(4)}

Bell-01 state (following the convention in Nielsen and Chuang)

## 7.18.4.3 ket qpp::States::b10 {ket::Zero(4)}

Bell-10 state (following the convention in Nielsen and Chuang)

## 7.18.4.4 ket qpp::States::b11 {ket::Zero(4)}

Bell-11 state (following the convention in Nielsen and Chuang)

## 7.18.4.5 ket qpp::States::GHZ {ket::Zero(8)}

GHZ state.

## 7.18.4.6 cmat qpp::States::pb00 {cmat::Zero(4, 4)}

Projector onto the Bell-00 state.

## 7.18.4.7 cmat qpp::States::pb01 {cmat::Zero(4, 4)}

Projector onto the Bell-01 state.

## 7.18.4.8 cmat qpp::States::pb10 {cmat::Zero(4, 4)}

Projector onto the Bell-10 state.

## 7.18.4.9 cmat qpp::States::pb11 {cmat::Zero(4, 4)}

Projector onto the Bell-11 state.

## 7.18.4.10 cmat qpp::States::pGHZ {cmat::Zero(8, 8)}

Projector onto the GHZ state.

## 7.18.4.11 cmat qpp::States::pW {cmat::Zero(8, 8)}

Projector onto the W state.

## 7.18.4.12 cmat qpp::States::px0 {cmat::Zero(2, 2)}

Projector onto the Pauli Sigma-X 0-eigenstate  $|+\rangle\langle+|$ .

## 7.18.4.13 cmat qpp::States::px1 {cmat::Zero(2, 2)}

Projector onto the Pauli Sigma-X 1-eigenstate  $|-\rangle\langle-|$ .

7.18.4.14 `cmat qpp::States::py0 {cmat::Zero(2, 2)}`

Projector onto the Pauli Sigma-Y 0-eigenstate  $|y+\rangle\langle y+|$ .

7.18.4.15 `cmat qpp::States::py1 {cmat::Zero(2, 2)}`

Projector onto the Pauli Sigma-Y 1-eigenstate  $|y-\rangle\langle y-|$ .

7.18.4.16 `cmat qpp::States::pz0 {cmat::Zero(2, 2)}`

Projector onto the Pauli Sigma-Z 0-eigenstate  $|0\rangle\langle 0|$ .

7.18.4.17 `cmat qpp::States::pz1 {cmat::Zero(2, 2)}`

Projector onto the Pauli Sigma-Z 1-eigenstate  $|1\rangle\langle 1|$ .

7.18.4.18 `ket qpp::States::W {ket::Zero(8)}`

W state.

7.18.4.19 `ket qpp::States::x0 {ket::Zero(2)}`

Pauli Sigma-X 0-eigenstate  $|+\rangle$

7.18.4.20 `ket qpp::States::x1 {ket::Zero(2)}`

Pauli Sigma-X 1-eigenstate  $|-\rangle$

7.18.4.21 `ket qpp::States::y0 {ket::Zero(2)}`

Pauli Sigma-Y 0-eigenstate  $|y+\rangle$

7.18.4.22 `ket qpp::States::y1 {ket::Zero(2)}`

Pauli Sigma-Y 1-eigenstate  $|y-\rangle$

7.18.4.23 `ket qpp::States::z0 {ket::Zero(2)}`

Pauli Sigma-Z 0-eigenstate  $|0\rangle$

7.18.4.24 `ket qpp::States::z1 {ket::Zero(2)}`

Pauli Sigma-Z 1-eigenstate  $|1\rangle$

The documentation for this class was generated from the following file:

- [classes/states.h](#)




## 7.19 qpp::Timer< T, CLOCK\_T > Class Template Reference


Chronometer.

```
#include <classes/timer.h>
```

Inheritance diagram for qpp::Timer< T, CLOCK\_T >:



Collaboration diagram for qpp::Timer< T, CLOCK\_T >:



### Public Member Functions

- `Timer ()` noexcept  
*Constructs an instance with the current time as the starting point.*
- `void tic ()` noexcept  
*Resets the chronometer.*
- `const Timer & toc ()` noexcept  
*Stops the chronometer.*
- `double tics ()` const noexcept  
*Time passed in the duration specified by T.*
- `template<typename U = T>`  
  `U get_duration ()` const noexcept  
*Duration specified by U.*
- `Timer (const Timer &)=default`  
*Default copy constructor.*
- `Timer (Timer &&)=default`

*Default move constructor.*

- `Timer & operator= (const Timer &)=default`

*Default copy assignment operator.*

- `Timer & operator= (Timer &&)=default`

*Default move assignment operator.*

- `virtual ~Timer ()=default`

*Default virtual destructor.*

## Protected Attributes

- `CLOCK_T::time_point start_`
- `CLOCK_T::time_point end_`

## Private Member Functions

- `std::ostream & display (std::ostream &os) const` override  
*qpp::IDisplay::display() override*

### 7.19.1 Detailed Description

`template<typename T = std::chrono::duration<double>, typename CLOCK_T = std::chrono::steady_clock> class qpp::Timer< T, CLOCK_T >`

Chronometer.

Template Parameters

<i>T</i>	Tics duration, default is <code>std::chrono::duration&lt;double, 1&gt;</code> , i.e. seconds in double precision
<i>CLOCK_T</i>	Clock's type, default is <code>std::chrono::steady_clock</code> , not affected by wall clock changes during runtime

### 7.19.2 Constructor & Destructor Documentation

7.19.2.1 `template<typename T = std::chrono::duration<double>, typename CLOCK_T = std::chrono::steady_clock> qpp::Timer< T, CLOCK_T >::Timer ( ) [inline], [noexcept]`

Constructs an instance with the current time as the starting point.

7.19.2.2 `template<typename T = std::chrono::duration<double>, typename CLOCK_T = std::chrono::steady_clock> qpp::Timer< T, CLOCK_T >::Timer ( const Timer< T, CLOCK_T > & ) [default]`

Default copy constructor.

7.19.2.3 `template<typename T = std::chrono::duration<double>, typename CLOCK_T = std::chrono::steady_clock> qpp::Timer< T, CLOCK_T >::Timer ( Timer< T, CLOCK_T > && ) [default]`

Default move constructor.

7.19.2.4 `template<typename T = std::chrono::duration<double>, typename CLOCK_T = std::chrono::steady_clock> virtual qpp::Timer< T, CLOCK_T >::~~Timer ( ) [virtual], [default]`

Default virtual destructor.

### 7.19.3 Member Function Documentation

7.19.3.1 `template<typename T = std::chrono::duration<double>, typename CLOCK_T = std::chrono::steady_clock>  
std::ostream& qpp::Timer< T, CLOCK_T >::display ( std::ostream & os ) const [inline], [override],  
[private], [virtual]`

[qpp::IDisplay::display\(\)](#) override

Parameters

<code>os</code>	Output stream
-----------------	---------------

Returns

Writes to the output stream the number of tics (specified by T) that passed between the instantiation/reset and invocation of [qpp::Timer::toc\(\)](#).

Implements [qpp::IDisplay](#).

7.19.3.2 `template<typename T = std::chrono::duration<double>, typename CLOCK_T = std::chrono::steady_clock>  
template<typename U = T> U qpp::Timer< T, CLOCK_T >::get_duration ( ) const [inline],  
[noexcept]`

Duration specified by U.

Template Parameters

<code>U</code>	Duration, default is T, which defaults to <code>std::chrono::duration&lt;double, 1&gt;</code> , i.e. seconds in double precision
----------------	----------------------------------------------------------------------------------------------------------------------------------

Returns

Duration that passed between the instantiation/reset and invocation of [qpp::Timer::toc\(\)](#)

7.19.3.3 `template<typename T = std::chrono::duration<double>, typename CLOCK_T = std::chrono::steady_clock> Timer&  
qpp::Timer< T, CLOCK_T >::operator= ( const Timer< T, CLOCK_T > & ) [default]`

Default copy assignment operator.

7.19.3.4 `template<typename T = std::chrono::duration<double>, typename CLOCK_T = std::chrono::steady_clock> Timer&  
qpp::Timer< T, CLOCK_T >::operator= ( Timer< T, CLOCK_T > && ) [default]`

Default move assignment operator.

7.19.3.5 `template<typename T = std::chrono::duration<double>, typename CLOCK_T = std::chrono::steady_clock> void  
qpp::Timer< T, CLOCK_T >::tic ( ) [inline], [noexcept]`

Resets the chronometer.

Resets the starting/ending point to the current time

7.19.3.6 `template<typename T = std::chrono::duration<double>, typename CLOCK_T = std::chrono::steady_clock> double  
qpp::Timer< T, CLOCK_T >::tics ( ) const [inline], [noexcept]`

Time passed in the duration specified by T.

**Returns**

Number of tics (specified by T) that passed between the instantiation/reset and invocation of [qpp::Timer::toc\(\)](#)

**7.19.3.7** `template<typename T = std::chrono::duration<double>, typename CLOCK_T = std::chrono::steady_clock> const  
Timer& qpp::Timer< T, CLOCK_T >::toc ( ) [inline], [noexcept]`

Stops the chronometer.

Set the current time as the ending point

**Returns**

Current instance

**7.19.4 Member Data Documentation**

**7.19.4.1** `template<typename T = std::chrono::duration<double>, typename CLOCK_T = std::chrono::steady_clock>  
CLOCK_T::time_point qpp::Timer< T, CLOCK_T >::end_ [protected]`

**7.19.4.2** `template<typename T = std::chrono::duration<double>, typename CLOCK_T = std::chrono::steady_clock>  
CLOCK_T::time_point qpp::Timer< T, CLOCK_T >::start_ [protected]`

The documentation for this class was generated from the following file:

- [classes/timer.h](#)

## Chapter 8

# File Documentation

### 8.1 classes/codes.h File Reference

Quantum error correcting codes.

This graph shows which files directly or indirectly include this file:



#### Classes

- class [qpp::Codes](#)  
*const Singleton class that defines quantum error correcting codes*

#### Namespaces

- [qpp](#)  
*Quantum++ main namespace.*

#### 8.1.1 Detailed Description

Quantum error correcting codes.

### 8.2 classes/exception.h File Reference

Exceptions.

This graph shows which files directly or indirectly include this file:



## Classes

- class [qpp::Exception](#)  
*Generates custom exceptions, used when validating function parameters.*

## Namespaces

- [qpp](#)  
*Quantum++ main namespace.*


### 8.2.1 Detailed Description

Exceptions.

## 8.3 classes/gates.h File Reference

Quantum gates.

This graph shows which files directly or indirectly include this file:



## Classes

- class [qpp::Gates](#)  
*const Singleton class that implements most commonly used gates*

## Namespaces

- [qpp](#)  
*Quantum++ main namespace.*


### 8.3.1 Detailed Description

Quantum gates.

## 8.4 classes/ideisplay.h File Reference

Display interface via the non-virtual interface (NVI)

This graph shows which files directly or indirectly include this file:



## Classes

- class [qpp::IDisplay](#)  
*Abstract class (interface) that mandates the definition of virtual `std::ostream& display(std::ostream& os) const`.*

## Namespaces

- [qpp](#)  
*Quantum++ main namespace.*

### 8.4.1 Detailed Description

Display interface via the non-virtual interface (NVI)

## 8.5 classes/init.h File Reference

Initialization.

This graph shows which files directly or indirectly include this file:



### Classes

- class [qpp::Init](#)  
*const Singleton class that performs additional initializations/cleanups*

### Namespaces

- [qpp](#)  
*Quantum++ main namespace.*


### 8.5.1 Detailed Description

Initialization.

## 8.6 classes/random\_devices.h File Reference

Random devices.

This graph shows which files directly or indirectly include this file:





## Classes

- class [qpp::RandomDevices](#)

*Singleton class that manages the source of randomness in the library.*

## Namespaces

- [qpp](#)

*Quantum++ main namespace.*


### 8.6.1 Detailed Description

Random devices.

## 8.7 classes/states.h File Reference

Quantum states.

This graph shows which files directly or indirectly include this file:



## Classes

- class [qpp::States](#)

*const Singleton class that implements most commonly used states*

## Namespaces

- [qpp](#)

*Quantum++ main namespace.*

### 8.7.1 Detailed Description

Quantum states.

## 8.8 classes/timer.h File Reference

Timing.

This graph shows which files directly or indirectly include this file:



### Classes

- class [qpp::Timer< T, CLOCK\\_T >](#)  
*Chronometer.*

### Namespaces

- [qpp](#)  
*Quantum++ main namespace.*

### 8.8.1 Detailed Description

Timing.

## 8.9 constants.h File Reference

Constants.

This graph shows which files directly or indirectly include this file:



## Namespaces

- [qpp](#)  
*Quantum++ main namespace.*

## Functions

- constexpr cplx [qpp::operator""\\_i](#) (unsigned long long int x) noexcept  
*User-defined literal for complex  $i = \sqrt{-1}$  (integer overload)*
- constexpr cplx [qpp::operator""\\_i](#) (long double x) noexcept  
*User-defined literal for complex  $i = \sqrt{-1}$  (real overload)*
- cplx [qpp::omega](#) (idx D)  
*D-th root of unity.*

## Variables

- constexpr double [qpp::chop](#) = 1e-10  
*Used in [qpp::disp\(\)](#) for setting to zero numbers that have their absolute value smaller than [qpp::chop](#).*
- constexpr double [qpp::eps](#) = 1e-12  
*Used to decide whether a number or expression in double precision is zero or not.*
- constexpr idx [qpp::maxn](#) = 64  
*Maximum number of allowed qu(d)its (subsystems)*
- constexpr double [qpp::pi](#) = 3.141592653589793238462643383279502884  
 $\pi$
- constexpr double [qpp::ee](#) = 2.718281828459045235360287471352662497  
*Base of natural logarithm, e.*
- constexpr double [qpp::infy](#) = std::numeric\_limits<double>::infinity()  
*Used to denote infinity in double precision.*

### 8.9.1 Detailed Description

Constants.

## 8.10 entanglement.h File Reference

Entanglement functions.

This graph shows which files directly or indirectly include this file:



## Namespaces

- [qpp](#)

*Quantum++ main namespace.*

## Functions

- `template<typename Derived >  
dyn_col_vect< double > qpp::schmidtcoeffs (const Eigen::MatrixBase< Derived > &A, const std::vector< idx > &dims)`  
*Schmidt coefficients of the bi-partite pure state A.*
- `template<typename Derived >  
cmat qpp::schmidtA (const Eigen::MatrixBase< Derived > &A, const std::vector< idx > &dims)`  
*Schmidt basis on Alice side.*
- `template<typename Derived >  
cmat qpp::schmidtB (const Eigen::MatrixBase< Derived > &A, const std::vector< idx > &dims)`  
*Schmidt basis on Bob side.*
- `template<typename Derived >  
std::vector< double > qpp::schmidtprobs (const Eigen::MatrixBase< Derived > &A, const std::vector< idx > &dims)`  
*Schmidt probabilities of the bi-partite pure state A.*
- `template<typename Derived >  
double qpp::entanglement (const Eigen::MatrixBase< Derived > &A, const std::vector< idx > &dims)`  
*Entanglement of the bi-partite pure state A.*
- `template<typename Derived >  
double qpp::gconcurrence (const Eigen::MatrixBase< Derived > &A)`  
*G-concurrence of the bi-partite pure state A.*
- `template<typename Derived >  
double qpp::negativity (const Eigen::MatrixBase< Derived > &A, const std::vector< idx > &dims)`  
*Negativity of the bi-partite mixed state A.*
- `template<typename Derived >  
double qpp::lognegativity (const Eigen::MatrixBase< Derived > &A, const std::vector< idx > &dims)`  
*Logarithmic negativity of the bi-partite mixed state A.*
- `template<typename Derived >  
double qpp::concurrence (const Eigen::MatrixBase< Derived > &A)`  
*Wootters concurrence of the bi-partite qubit mixed state A.*


### 8.10.1 Detailed Description

Entanglement functions.

## 8.11 entropies.h File Reference

Entropy functions.

This graph shows which files directly or indirectly include this file:



## Namespaces

- [qpp](#)  
*Quantum++ main namespace.*

## Functions

- `template<typename Derived >`  
`double qpp::entropy (const Eigen::MatrixBase< Derived > &A)`  
*von-Neumann entropy of the density matrix A*
- `double qpp::entropy (const std::vector< double > &prob)`  
*Shannon entropy of the probability distribution prob.*
- `template<typename Derived >`  
`double qpp::renyi (const Eigen::MatrixBase< Derived > &A, double alpha)`  
*Renyi-  $\alpha$  entropy of the density matrix A, for  $\alpha \geq 0$ .*
- `double qpp::renyi (const std::vector< double > &prob, double alpha)`  
*Renyi-  $\alpha$  entropy of the probability distribution prob, for  $\alpha \geq 0$ .*
- `template<typename Derived >`  
`double qpp::tsallis (const Eigen::MatrixBase< Derived > &A, double q)`  
*Tsallis- q entropy of the density matrix A, for  $q \geq 0$ .*
- `double qpp::tsallis (const std::vector< double > &prob, double q)`  
*Tsallis- q entropy of the probability distribution prob, for  $q \geq 0$ .*
- `template<typename Derived >`  
`double qpp::qmutualinfo (const Eigen::MatrixBase< Derived > &A, const std::vector< idx > &subsysA, const std::vector< idx > &subsysB, const std::vector< idx > &dims)`  
*Quantum mutual information between 2 subsystems of a composite system.*
- `template<typename Derived >`  
`double qpp::qmutualinfo (const Eigen::MatrixBase< Derived > &A, const std::vector< idx > &subsysA, const std::vector< idx > &subsysB, idx d=2)`  
*Quantum mutual information between 2 subsystems of a composite system.*

### 8.11.1 Detailed Description

Entropy functions.

## 8.12 experimental/experimental.h File Reference

Experimental/test functions/classes.

### Namespaces

- [qpp](#)  
*Quantum++ main namespace.*
- [qpp::experimental](#)  
*Experimental/test functions/classes, do not use or modify.*


### 8.12.1 Detailed Description

Experimental/test functions/classes.

## 8.13 functions.h File Reference

Generic quantum computing functions.

This graph shows which files directly or indirectly include this file:



### Namespaces

- [qpp](#)  
*Quantum++ main namespace.*

### Functions

- `template<typename Derived >`  
`dyn_mat< typename Derived::Scalar > qpp::transpose (const Eigen::MatrixBase< Derived > &A)`  
*Transpose.*
- `template<typename Derived >`  
`dyn_mat< typename Derived::Scalar > qpp::conjugate (const Eigen::MatrixBase< Derived > &A)`  
*Complex conjugate.*
- `template<typename Derived >`  
`dyn_mat< typename Derived::Scalar > qpp::adjoint (const Eigen::MatrixBase< Derived > &A)`  
*Adjoint.*

- template<typename Derived >  
dyn\_mat< typename Derived::Scalar > [qpp::inverse](#) (const Eigen::MatrixBase< Derived > &A)  
*Inverse.*
- template<typename Derived >  
Derived::Scalar [qpp::trace](#) (const Eigen::MatrixBase< Derived > &A)  
*Trace.*
- template<typename Derived >  
Derived::Scalar [qpp::det](#) (const Eigen::MatrixBase< Derived > &A)  
*Determinant.*
- template<typename Derived >  
Derived::Scalar [qpp::logdet](#) (const Eigen::MatrixBase< Derived > &A)  
*Logarithm of the determinant.*
- template<typename Derived >  
Derived::Scalar [qpp::sum](#) (const Eigen::MatrixBase< Derived > &A)  
*Element-wise sum of A.*
- template<typename Derived >  
Derived::Scalar [qpp::prod](#) (const Eigen::MatrixBase< Derived > &A)  
*Element-wise product of A.*
- template<typename Derived >  
double [qpp::norm](#) (const Eigen::MatrixBase< Derived > &A)  
*Frobenius norm.*
- template<typename Derived >  
std::pair< dyn\_col\_vect< cplx >, cmat > [qpp::eig](#) (const Eigen::MatrixBase< Derived > &A)  
*Full eigen decomposition.*
- template<typename Derived >  
dyn\_col\_vect< cplx > [qpp::evals](#) (const Eigen::MatrixBase< Derived > &A)  
*Eigenvalues.*
- template<typename Derived >  
cmat [qpp::evecs](#) (const Eigen::MatrixBase< Derived > &A)  
*Eigenvectors.*
- template<typename Derived >  
std::pair< dyn\_col\_vect< double >, cmat > [qpp::heig](#) (const Eigen::MatrixBase< Derived > &A)  
*Full eigen decomposition of Hermitian expression.*
- template<typename Derived >  
dyn\_col\_vect< double > [qpp::hevals](#) (const Eigen::MatrixBase< Derived > &A)  
*Hermitian eigenvalues.*
- template<typename Derived >  
cmat [qpp::hevecs](#) (const Eigen::MatrixBase< Derived > &A)  
*Hermitian eigenvectors.*
- template<typename Derived >  
std::tuple< cmat, dyn\_col\_vect< double >, cmat > [qpp::svd](#) (const Eigen::MatrixBase< Derived > &A)  
*Full singular value decomposition.*
- template<typename Derived >  
dyn\_col\_vect< double > [qpp::svals](#) (const Eigen::MatrixBase< Derived > &A)  
*Singular values.*
- template<typename Derived >  
cmat [qpp::svdU](#) (const Eigen::MatrixBase< Derived > &A)  
*Left singular vectors.*
- template<typename Derived >  
cmat [qpp::svdV](#) (const Eigen::MatrixBase< Derived > &A)  
*Right singular vectors.*
- template<typename Derived >  
cmat [qpp::funm](#) (const Eigen::MatrixBase< Derived > &A, cplx(\*f)(const cplx &))

- Functional calculus  $f(A)$*

  - `template<typename Derived >`  
`cmat qpp::sqrtm (const Eigen::MatrixBase< Derived > &A)`  
*Matrix square root.*
  - `template<typename Derived >`  
`cmat qpp::absm (const Eigen::MatrixBase< Derived > &A)`  
*Matrix absolute value.*
  - `template<typename Derived >`  
`cmat qpp::expm (const Eigen::MatrixBase< Derived > &A)`  
*Matrix exponential.*
  - `template<typename Derived >`  
`cmat qpp::logm (const Eigen::MatrixBase< Derived > &A)`  
*Matrix logarithm.*
  - `template<typename Derived >`  
`cmat qpp::sinm (const Eigen::MatrixBase< Derived > &A)`  
*Matrix sin.*
  - `template<typename Derived >`  
`cmat qpp::cosm (const Eigen::MatrixBase< Derived > &A)`  
*Matrix cos.*
  - `template<typename Derived >`  
`cmat qpp::spectralpowm (const Eigen::MatrixBase< Derived > &A, const cplx z)`  
*Matrix power.*
  - `template<typename Derived >`  
`dyn_mat< typename Derived::Scalar > qpp::powm (const Eigen::MatrixBase< Derived > &A, idx n)`  
*Fast matrix power based on the SQUARE-AND-MULTIPLY algorithm.*
  - `template<typename Derived >`  
`double qpp::schatten (const Eigen::MatrixBase< Derived > &A, double p)`  
*Schatten matrix norm.*
  - `template<typename OutputScalar , typename Derived >`  
`dyn_mat< OutputScalar > qpp::cwise (const Eigen::MatrixBase< Derived > &A, OutputScalar(*f)(const typename Derived::Scalar &))`  
*Functor.*
  - `template<typename T >`  
`dyn_mat< typename T::Scalar > qpp::kron (const T &head)`  
*Kronecker product.*
  - `template<typename T , typename... Args>`  
`dyn_mat< typename T::Scalar > qpp::kron (const T &head, const Args &...tail)`  
*Kronecker product.*
  - `template<typename Derived >`  
`dyn_mat< typename Derived::Scalar > qpp::kron (const std::vector< Derived > &As)`  
*Kronecker product.*
  - `template<typename Derived >`  
`dyn_mat< typename Derived::Scalar > qpp::kron (const std::initializer_list< Derived > &As)`  
*Kronecker product.*
  - `template<typename Derived >`  
`dyn_mat< typename Derived::Scalar > qpp::kronpow (const Eigen::MatrixBase< Derived > &A, idx n)`  
*Kronecker power.*
  - `template<typename T >`  
`dyn_mat< typename T::Scalar > qpp::dirsum (const T &head)`  
*Direct sum.*
  - `template<typename T , typename... Args>`  
`dyn_mat< typename T::Scalar > qpp::dirsum (const T &head, const Args &...tail)`  
*Direct sum.*



- `template<typename Derived >`  
`dyn_mat< typename Derived::Scalar > qpp::dirsum (const std::vector< Derived > &As)`  
*Direct sum.*
- `template<typename Derived >`  
`dyn_mat< typename Derived::Scalar > qpp::dirsum (const std::initializer_list< Derived > &As)`  
*Direct sum.*
- `template<typename Derived >`  
`dyn_mat< typename Derived::Scalar > qpp::dirsumpow (const Eigen::MatrixBase< Derived > &A, idx n)`  
*Direct sum power.*
- `template<typename Derived >`  
`dyn_mat< typename Derived::Scalar > qpp::reshape (const Eigen::MatrixBase< Derived > &A, idx rows, idx cols)`  
*Reshape.*
- `template<typename Derived1 , typename Derived2 >`  
`dyn_mat< typename Derived1::Scalar > qpp::comm (const Eigen::MatrixBase< Derived1 > &A, const Eigen::MatrixBase< Derived2 > &B)`  
*Commutator.*
- `template<typename Derived1 , typename Derived2 >`  
`dyn_mat< typename Derived1::Scalar > qpp::anticomm (const Eigen::MatrixBase< Derived1 > &A, const Eigen::MatrixBase< Derived2 > &B)`  
*Anti-commutator.*
- `template<typename Derived >`  
`dyn_mat< typename Derived::Scalar > qpp::prj (const Eigen::MatrixBase< Derived > &V)`  
*Projector.*
- `template<typename Derived >`  
`dyn_mat< typename Derived::Scalar > qpp::grams (const std::vector< Derived > &Vs)`  
*Gram-Schmidt orthogonalization.*
- `template<typename Derived >`  
`dyn_mat< typename Derived::Scalar > qpp::grams (const std::initializer_list< Derived > &Vs)`  
*Gram-Schmidt orthogonalization.*
- `template<typename Derived >`  
`dyn_mat< typename Derived::Scalar > qpp::grams (const Eigen::MatrixBase< Derived > &A)`  
*Gram-Schmidt orthogonalization.*
- `std::vector< idx > qpp::n2multiidx (idx n, const std::vector< idx > &dims)`  
*Non-negative integer index to multi-index.*
- `idx qpp::multiidx2n (const std::vector< idx > &midx, const std::vector< idx > &dims)`  
*Multi-index to non-negative integer index.*
- `ket qpp::mket (const std::vector< idx > &mask, const std::vector< idx > &dims)`  
*Multi-partite qudit ket.*
- `ket qpp::mket (const std::vector< idx > &mask, idx d=2)`  
*Multi-partite qudit ket.*
- `cmat qpp::mprj (const std::vector< idx > &mask, const std::vector< idx > &dims)`  
*Projector onto multi-partite qudit ket.*
- `cmat qpp::mprj (const std::vector< idx > &mask, idx d=2)`  
*Projector onto multi-partite qudit ket.*
- `template<typename InputIterator >`  
`std::vector< double > qpp::abssq (InputIterator first, InputIterator last)`  
*Computes the absolute values squared of an STL-like range of complex numbers.*
- `template<typename Container >`  
`std::vector< double > qpp::abssq (const Container &c, typename std::enable_if< is_iterable< Container >::value >::type * = nullptr)`  
*Computes the absolute values squared of an STL-like container.*

- `template<typename Derived >`  
`std::vector< double > qpp::abssq (const Eigen::MatrixBase< Derived > &A)`  
*Computes the absolute values squared of an Eigen expression.*
- `template<typename InputIterator >`  
`std::iterator_traits< InputIterator >::value_type qpp::sum (InputIterator first, InputIterator last)`  
*Element-wise sum of an STL-like range.*
- `template<typename Container >`  
`Container::value_type qpp::sum (const Container &c, typename std::enable_if< is_iterable< Container >::value >::type * = nullptr)`  
*Element-wise sum of the elements of an STL-like container.*
- `template<typename InputIterator >`  
`std::iterator_traits< InputIterator >::value_type qpp::prod (InputIterator first, InputIterator last)`  
*Element-wise product of an STL-like range.*
- `template<typename Container >`  
`Container::value_type qpp::prod (const Container &c, typename std::enable_if< is_iterable< Container >::value >::type * = nullptr)`  
*Element-wise product of the elements of an STL-like container.*
- `template<typename Derived >`  
`dyn_col_vect< typename Derived::Scalar > qpp::rho2pure (const Eigen::MatrixBase< Derived > &A)`  
*Finds the pure state representation of a matrix proportional to a projector onto a pure state.*
- `template<typename T >`  
`std::vector< T > qpp::complement (std::vector< T > subsys, idx N)`  
*Constructs the complement of a subsystem vector.*
- `template<typename Derived >`  
`std::vector< double > qpp::rho2bloch (const Eigen::MatrixBase< Derived > &A)`  
*Computes the 3-dimensional real Bloch vector corresponding to the qubit density matrix A.*
- `cmat qpp::bloch2rho (const std::vector< double > &r)`  
*Computes the density matrix corresponding to the 3-dimensional real Bloch vector r.*


### 8.13.1 Detailed Description

Generic quantum computing functions.

## 8.14 input\_output.h File Reference

Input/output functions.

This graph shows which files directly or indirectly include this file:



## Namespaces

- [qpp](#)

*Quantum++ main namespace.*

## Functions

- `template<typename Derived >`  
`internal::IOManipEigen qpp::disp (const Eigen::MatrixBase< Derived > &A, double chop=qpp::chop)`  
*Eigen expression ostream manipulator.*
- `internal::IOManipEigen qpp::disp (cplx z, double chop=qpp::chop)`  
*Complex number ostream manipulator.*
- `template<typename InputIterator >`  
`internal::IOManipRange< InputIterator > qpp::disp (InputIterator first, InputIterator last, const std::string &separator, const std::string &start="[" , const std::string &end="]")`  
*Range ostream manipulator.*
- `template<typename Container >`  
`internal::IOManipRange< typename Container::const_iterator > qpp::disp (const Container &c, const std::string &separator, const std::string &start="[" , const std::string &end="]", typename std::enable_if< is_iterable< Container >::value >::type !=nullptr)`  
*Standard container ostream manipulator. The container must support std::begin(), std::end() and forward iteration.*
- `template<typename PointerType >`  
`internal::IOManipPointer< PointerType > qpp::disp (const PointerType *p, idx N, const std::string &separator, const std::string &start="[" , const std::string &end="]")`  
*C-style pointer ostream manipulator.*
- `template<typename Derived >`  
`void qpp::save (const Eigen::MatrixBase< Derived > &A, const std::string &fname)`  
*Saves Eigen expression to a binary file (internal format) in double precision.*
- `template<typename Derived >`  
`dyn_mat< typename Derived::Scalar > qpp::load (const std::string &fname)`  
*Loads Eigen matrix from a binary file (internal format) in double precision.*


### 8.14.1 Detailed Description

Input/output functions.

## 8.15 instruments.h File Reference

Measurement functions.

This graph shows which files directly or indirectly include this file:



## Namespaces

- [qpp](#)  
*Quantum++ main namespace.*

## Functions

- `template<typename Derived >`  
`dyn_col_vect< typename Derived::Scalar > qpp::ip (const Eigen::MatrixBase< Derived > &phi, const Eigen::MatrixBase< Derived > &psi, const std::vector< idx > &subsys, const std::vector< idx > &dims)`  
*Generalized inner product.*
- `template<typename Derived >`  
`dyn_col_vect< typename Derived::Scalar > qpp::ip (const Eigen::MatrixBase< Derived > &phi, const Eigen::MatrixBase< Derived > &psi, const std::vector< idx > &subsys, idx d=2)`  
*Generalized inner product.*
- `template<typename Derived >`  
`std::tuple< idx, std::vector< double >, std::vector< cmat > > qpp::measure (const Eigen::MatrixBase< Derived > &A, const std::vector< cmat > &Ks)`  
*Measures the state A using the set of Kraus operators Ks.*
- `template<typename Derived >`  
`std::tuple< idx, std::vector< double >, std::vector< cmat > > qpp::measure (const Eigen::MatrixBase< Derived > &A, const std::initializer_list< cmat > &Ks)`  
*Measures the state A using the set of Kraus operators Ks.*
- `template<typename Derived >`  
`std::tuple< idx, std::vector< double >, std::vector< cmat > > qpp::measure (const Eigen::MatrixBase< Derived > &A, const cmat &U)`  
*Measures the state A in the orthonormal basis specified by the unitary matrix U.*
- `template<typename Derived >`  
`std::tuple< idx, std::vector< double >, std::vector< cmat > > qpp::measure (const Eigen::MatrixBase< Derived > &A, const std::vector< cmat > &Ks, const std::vector< idx > &subsys, const std::vector< idx > &dims)`  
*Measures the part subsys of the multi-partite state vector or density matrix A using the set of Kraus operators Ks.*
- `template<typename Derived >`  
`std::tuple< idx, std::vector< double >, std::vector< cmat > > qpp::measure (const Eigen::MatrixBase< Derived > &A, const std::initializer_list< cmat > &Ks, const std::vector< idx > &subsys, const std::vector< idx > &dims)`  
*Measures the part subsys of the multi-partite state vector or density matrix A using the set of Kraus operators Ks.*

- `template<typename Derived >`  
`std::tuple< idx, std::vector< double >, std::vector< cmat > > qpp::measure` (const Eigen::MatrixBase< Derived > &A, const std::vector< cmat > &Ks, const std::vector< idx > &subsys, idx d=2)  
*Measures the part subsys of the multi-partite state vector or density matrix A using the set of Kraus operators Ks.*
- `template<typename Derived >`  
`std::tuple< idx, std::vector< double >, std::vector< cmat > > qpp::measure` (const Eigen::MatrixBase< Derived > &A, const std::initializer\_list< cmat > &Ks, const std::vector< idx > &subsys, idx d=2)  
*Measures the part subsys of the multi-partite state vector or density matrix A using the set of Kraus operators Ks.*
- `template<typename Derived >`  
`std::tuple< idx, std::vector< double >, std::vector< cmat > > qpp::measure` (const Eigen::MatrixBase< Derived > &A, const cmat &V, const std::vector< idx > &subsys, const std::vector< idx > &dims)  
*Measures the part subsys of the multi-partite state vector or density matrix A in the orthonormal basis or rank-1 POVM specified by the matrix V.*
- `template<typename Derived >`  
`std::tuple< idx, std::vector< double >, std::vector< cmat > > qpp::measure` (const Eigen::MatrixBase< Derived > &A, const cmat &V, const std::vector< idx > &subsys, idx d=2)  
*Measures the part subsys of the multi-partite state vector or density matrix A in the orthonormal basis or rank-1 POVM specified by the matrix V.*
- `template<typename Derived >`  
`std::tuple< std::vector< idx >, double, cmat > qpp::measure_seq` (const Eigen::MatrixBase< Derived > &A, std::vector< idx > subsys, std::vector< idx > dims)  
*Sequentially measures the part subsys of the multi-partite state vector or density matrix A in the computational basis.*
- `template<typename Derived >`  
`std::tuple< std::vector< idx >, double, cmat > qpp::measure_seq` (const Eigen::MatrixBase< Derived > &A, std::vector< idx > subsys, idx d=2)  
*Sequentially measures the part subsys of the multi-partite state vector or density matrix A in the computational basis.*


### 8.15.1 Detailed Description

Measurement functions.

## 8.16 internal/classes/iomanip.h File Reference

Input/output manipulators.

This graph shows which files directly or indirectly include this file:



## Classes

- struct [qpp::internal::details\\_::Display\\_Impl\\_](#)
- class [qpp::internal::IOManipRange< InputIterator >](#)
- class [qpp::internal::IOManipPointer< PointerType >](#)
- class [qpp::internal::IOManipEigen](#)

## Namespaces

- [qpp](#)  
*Quantum++ main namespace.*
- [qpp::internal](#)  
*Internal utility functions, do not use/modify.*
- [qpp::internal::details\\_](#)


### 8.16.1 Detailed Description

Input/output manipulators.

### 8.17 internal/classes/singleton.h File Reference

Singleton pattern via CRTP.

This graph shows which files directly or indirectly include this file:



## Classes

- class [qpp::internal::Singleton< T >](#)  
*[Singleton](#) policy class, used internally to implement the singleton pattern via CRTP (Curiously recurring template pattern)*

## Namespaces

- [qpp](#)  
*Quantum++ main namespace.*
- [qpp::internal](#)  
*Internal utility functions, do not use/modify.*


### 8.17.1 Detailed Description

Singleton pattern via CRTP.

## 8.18 internal/util.h File Reference

Internal utility functions.

This graph shows which files directly or indirectly include this file:



### Namespaces

- [qpp](#)  
*Quantum++ main namespace.*
- [qpp::internal](#)  
*Internal utility functions, do not use/modify.*

### Functions

- void [qpp::internal::n2multiidx](#) (idx n, idx numdims, const idx \*dims, idx \*result) noexcept
- idx [qpp::internal::multiidx2n](#) (const idx \*midx, idx numdims, const idx \*dims) noexcept
- template<typename Derived >  
bool [qpp::internal::check\\_square\\_mat](#) (const Eigen::MatrixBase< Derived > &A)
- template<typename Derived >  
bool [qpp::internal::check\\_vector](#) (const Eigen::MatrixBase< Derived > &A)
- template<typename Derived >  
bool [qpp::internal::check\\_rvector](#) (const Eigen::MatrixBase< Derived > &A)
- template<typename Derived >  
bool [qpp::internal::check\\_cvector](#) (const Eigen::MatrixBase< Derived > &A)
- template<typename T >  
bool [qpp::internal::check\\_nonzero\\_size](#) (const T &x) noexcept
- template<typename T1 , typename T2 >  
bool [qpp::internal::check\\_matching\\_sizes](#) (const T1 &lhs, const T2 &rhs) noexcept
- bool [qpp::internal::check\\_dims](#) (const std::vector< idx > &dims)
- template<typename Derived >  
bool [qpp::internal::check\\_dims\\_match\\_mat](#) (const std::vector< idx > &dims, const Eigen::MatrixBase< Derived > &A)
- template<typename Derived >  
bool [qpp::internal::check\\_dims\\_match\\_cvect](#) (const std::vector< idx > &dims, const Eigen::MatrixBase< Derived > &V)

- `template<typename Derived >`  
`bool qpp::internal::check_dims_match_rvect (const std::vector< idx > &dims, const Eigen::MatrixBase< Derived > &V)`
- `bool qpp::internal::check_eq_dims (const std::vector< idx > &dims, idx dim) noexcept`
- `bool qpp::internal::check_subsys_match_dims (const std::vector< idx > &subsys, const std::vector< idx > &dims)`
- `template<typename Derived >`  
`bool qpp::internal::check_qubit_matrix (const Eigen::MatrixBase< Derived > &A) noexcept`
- `template<typename Derived >`  
`bool qpp::internal::check_qubit_cvector (const Eigen::MatrixBase< Derived > &V) noexcept`
- `template<typename Derived >`  
`bool qpp::internal::check_qubit_rvector (const Eigen::MatrixBase< Derived > &V) noexcept`
- `template<typename Derived >`  
`bool qpp::internal::check_qubit_vector (const Eigen::MatrixBase< Derived > &V) noexcept`
- `bool qpp::internal::check_perm (const std::vector< idx > &perm)`
- `template<typename Derived1 , typename Derived2 >`  
`dyn_mat< typename Derived1::Scalar > qpp::internal::kron2 (const Eigen::MatrixBase< Derived1 > &A, const Eigen::MatrixBase< Derived2 > &B)`
- `template<typename Derived1 , typename Derived2 >`  
`dyn_mat< typename Derived1::Scalar > qpp::internal::dirsum2 (const Eigen::MatrixBase< Derived1 > &A, const Eigen::MatrixBase< Derived2 > &B)`
- `template<typename T >`  
`void qpp::internal::variadic_vector_emplace (std::vector< T > &)`
- `template<typename T , typename First , typename... Args>`  
`void qpp::internal::variadic_vector_emplace (std::vector< T > &v, First &&first, Args &&...args)`
- `idx qpp::internal::get_num_subsys (idx sz, idx d)`
- `idx qpp::internal::get_dim_subsys (idx sz, idx N)`


### 8.18.1 Detailed Description

Internal utility functions.

## 8.19 macros.h File Reference

Preprocessor macros.

This graph shows which files directly or indirectly include this file:





## Macros

- `#define PRINT(x)`
- `#define PRINTLN(x)`
- `#define ERROR(x)`
- `#define ERRORLN(x)`

### 8.19.1 Detailed Description

Preprocessor macros.

### 8.19.2 Macro Definition Documentation

#### 8.19.2.1 `#define ERROR( x )`

Prints an error message to `std::cerr`

#### 8.19.2.2 `#define ERRORLN( x )`

Prints an error message to `std::cerr` and adds a new line

#### 8.19.2.3 `#define PRINT( x )`

Prints a message

#### 8.19.2.4 `#define PRINTLN( x )`

Prints a message and adds a new line

## 8.20 MATLAB/matlab.h File Reference

Input/output interfacing with MATLAB.

```
#include "mat.h"
#include "mex.h"
```

## Namespaces

- [qpp](#)  
*Quantum++ main namespace.*

## Functions

- `template<typename Derived >`  
`Derived qpp::loadMATLABmatrix (const std::string &, const std::string &)`  
*Loads an Eigen dynamic matrix from a MATLAB .mat file, generic version.*
- `template<>`  
`dmat qpp::loadMATLABmatrix (const std::string &mat_file, const std::string &var_name)`  
*Loads an Eigen dynamic matrix from a MATLAB .mat file, specialization for double matrices ([qpp::dmat](#))*

- `template<>`  
`cmat qpp::loadMATLABmatrix (const std::string &mat_file, const std::string &var_name)`  
*Loads an Eigen dynamic matrix from a MATLAB .mat file, specialization for complex matrices ([qpp::cmat](#))*
- `template<typename Derived >`  
`void qpp::saveMATLABmatrix (const Eigen::MatrixBase< Derived > &, const std::string &, const std::string &, const std::string &)`  
*Saves an Eigen dynamic matrix to a MATLAB .mat file, generic version.*
- `template<>`  
`void qpp::saveMATLABmatrix (const Eigen::MatrixBase< dmat > &A, const std::string &mat_file, const std::string &var_name, const std::string &mode)`  
*Saves an Eigen dynamic matrix to a MATLAB .mat file, specialization for double matrices ([qpp::dmat](#))*
- `template<>`  
`void qpp::saveMATLABmatrix (const Eigen::MatrixBase< cmat > &A, const std::string &mat_file, const std::string &var_name, const std::string &mode)`  
*Saves an Eigen dynamic matrix to a MATLAB .mat file, specialization for complex matrices ([qpp::cmat](#))*


## 8.20.1 Detailed Description

Input/output interfacing with MATLAB.

## 8.21 number\_theory.h File Reference

Number theory functions.

This graph shows which files directly or indirectly include this file:



## Namespaces

- [qpp](#)  
*Quantum++ main namespace.*

## Functions

- `std::vector< int > qpp::x2contfrac (double x, idx N, idx cut=1e5)`  
*Simple continued fraction expansion.*
- `double qpp::contfrac2x (const std::vector< int > &cf, idx N)`  
*Real representation of a simple continued fraction.*

- double `qpp::contfrac2x` (const std::vector< int > &cf)  
*Real representation of a simple continued fraction.*
- bigint `qpp::gcd` (bigint a, bigint b)  
*Greatest common divisor of two integers.*
- bigint `qpp::gcd` (const std::vector< bigint > &as)  
*Greatest common divisor of a list of integers.*
- bigint `qpp::lcm` (bigint a, bigint b)  
*Least common multiple of two integers.*
- bigint `qpp::lcm` (const std::vector< bigint > &as)  
*Least common multiple of a list of integers.*
- std::vector< idx > `qpp::invperm` (const std::vector< idx > &perm)  
*Inverse permutation.*
- std::vector< idx > `qpp::compperm` (const std::vector< idx > &perm, const std::vector< idx > &sigma)  
*Compose permutations.*
- std::vector< bigint > `qpp::factors` (bigint a)  
*Prime factor decomposition.*
- bigint `qpp::modmul` (bigint a, bigint b, bigint p)  
*Modular multiplication without overflow.*
- bigint `qpp::modpow` (bigint a, bigint n, bigint p)  
*Fast integer power modulo p based on the SQUARE-AND-MULTIPLY algorithm.*
- std::tuple< bigint, bigint, bigint > `qpp::egcd` (bigint a, bigint b)  
*Extended greatest common divisor of two integers.*
- bigint `qpp::modinv` (bigint a, bigint p)  
*Modular inverse of a mod p.*
- bool `qpp::isprime` (bigint p, idx k=80)  
*Primality test based on the Miller-Rabin's algorithm.*
- bigint `qpp::randprime` (bigint a, bigint b, idx N=1000)  
*Generates a random big prime uniformly distributed in the interval [a, b].*


### 8.21.1 Detailed Description

Number theory functions.

## 8.22 operations.h File Reference

Quantum operation functions.

This graph shows which files directly or indirectly include this file:



## Namespaces

- [qpp](#)

*Quantum++ main namespace.*

## Functions

- `template<typename Derived1 , typename Derived2 >  
dyn_mat< typename Derived1::Scalar > qpp::applyCTRL (const Eigen::MatrixBase< Derived1 > &state,  
const Eigen::MatrixBase< Derived2 > &A, const std::vector< idx > &ctrl, const std::vector< idx > &subsys,  
const std::vector< idx > &dims)`  
*Applies the controlled-gate A to the part subsys of the multi-partite state vector or density matrix state.*
- `template<typename Derived1 , typename Derived2 >  
dyn_mat< typename Derived1::Scalar > qpp::applyCTRL (const Eigen::MatrixBase< Derived1 > &state,  
const Eigen::MatrixBase< Derived2 > &A, const std::vector< idx > &ctrl, const std::vector< idx > &subsys,  
idx d=2)`  
*Applies the controlled-gate A to the part subsys of the multi-partite state vector or density matrix state.*
- `template<typename Derived1 , typename Derived2 >  
dyn_mat< typename Derived1::Scalar > qpp::apply (const Eigen::MatrixBase< Derived1 > &state, const  
Eigen::MatrixBase< Derived2 > &A, const std::vector< idx > &subsys, const std::vector< idx > &dims)`  
*Applies the gate A to the part subsys of the multi-partite state vector or density matrix state.*
- `template<typename Derived1 , typename Derived2 >  
dyn_mat< typename Derived1::Scalar > qpp::apply (const Eigen::MatrixBase< Derived1 > &state, const  
Eigen::MatrixBase< Derived2 > &A, const std::vector< idx > &subsys, idx d=2)`  
*Applies the gate A to the part subsys of the multi-partite state vector or density matrix state.*
- `template<typename Derived >  
cmat qpp::apply (const Eigen::MatrixBase< Derived > &rho, const std::vector< cmat > &Ks)`  
*Applies the channel specified by the set of Kraus operators Ks to the density matrix rho.*
- `template<typename Derived >  
cmat qpp::apply (const Eigen::MatrixBase< Derived > &rho, const std::vector< cmat > &Ks, const std::vector< idx > &subsys, const std::vector< idx > &dims)`  
*Applies the channel specified by the set of Kraus operators Ks to the part subsys of the multi-partite density matrix rho.*
- `template<typename Derived >  
cmat qpp::apply (const Eigen::MatrixBase< Derived > &rho, const std::vector< cmat > &Ks, const std::vector< idx > &subsys, idx d=2)`  
*Applies the channel specified by the set of Kraus operators Ks to the part subsys of the multi-partite density matrix rho.*
- `cmat qpp::kraus2super (const std::vector< cmat > &Ks)`  
*Superoperator matrix.*
- `cmat qpp::kraus2choi (const std::vector< cmat > &Ks)`  
*Choi matrix.*
- `std::vector< cmat > qpp::choi2kraus (const cmat &A)`  
*Orthogonal Kraus operators from Choi matrix.*
- `cmat qpp::choi2super (const cmat &A)`  
*Converts Choi matrix to superoperator matrix.*
- `cmat qpp::super2choi (const cmat &A)`  
*Converts superoperator matrix to Choi matrix.*
- `template<typename Derived >  
dyn_mat< typename Derived::Scalar > qpp::ptrace1 (const Eigen::MatrixBase< Derived > &A, const std::vector< idx > &dims)`  
*Partial trace.*

- `template<typename Derived >`  
`dyn_mat< typename Derived::Scalar > qpp::ptrace2 (const Eigen::MatrixBase< Derived > &A, const std::vector< idx > &dims)`

*Partial trace.*

- `template<typename Derived >`  
`dyn_mat< typename Derived::Scalar > qpp::ptrace (const Eigen::MatrixBase< Derived > &A, const std::vector< idx > &subsys, const std::vector< idx > &dims)`

*Partial trace.*

- `template<typename Derived >`  
`dyn_mat< typename Derived::Scalar > qpp::ptrace (const Eigen::MatrixBase< Derived > &A, const std::vector< idx > &subsys, idx d=2)`

*Partial trace.*

- `template<typename Derived >`  
`dyn_mat< typename Derived::Scalar > qpp::ptranspose (const Eigen::MatrixBase< Derived > &A, const std::vector< idx > &subsys, const std::vector< idx > &dims)`

*Partial transpose.*

- `template<typename Derived >`  
`dyn_mat< typename Derived::Scalar > qpp::ptranspose (const Eigen::MatrixBase< Derived > &A, const std::vector< idx > &subsys, idx d=2)`

*Partial transpose.*

- `template<typename Derived >`  
`dyn_mat< typename Derived::Scalar > qpp::syspermute (const Eigen::MatrixBase< Derived > &A, const std::vector< idx > &perm, const std::vector< idx > &dims)`

*Subsystem permutation.*

- `template<typename Derived >`  
`dyn_mat< typename Derived::Scalar > qpp::syspermute (const Eigen::MatrixBase< Derived > &A, const std::vector< idx > &perm, idx d=2)`

*Subsystem permutation.*

### 8.22.1 Detailed Description

Quantum operation functions.

## 8.23 qpp.h File Reference

Quantum++ main header file, includes all other necessary headers.

```
#include <algorithm>
#include <cassert>
#include <chrono>
#include <cmath>
#include <complex>
#include <cstdlib>
#include <cstring>
#include <exception>
#include <fstream>
#include <functional>
#include <initializer_list>
#include <iomanip>
#include <iterator>
#include <limits>
#include <numeric>
#include <ostream>
#include <random>
#include <sstream>
#include <stdexcept>
#include <string>
#include <tuple>
#include <type_traits>
#include <utility>
#include <vector>
#include <Eigen/Dense>
#include <Eigen/SVD>
#include "macros.h"
#include "types.h"
#include "classes/exception.h"
#include "constants.h"
#include "traits.h"
#include "classes/idisplay.h"
#include "internal/util.h"
#include "internal/classes/iomanip.h"
#include "input_output.h"
#include "internal/classes/singleton.h"
#include "classes/init.h"
#include "functions.h"
#include "classes/codes.h"
#include "classes/gates.h"
#include "classes/states.h"
#include "classes/random_devices.h"
#include "statistics.h"
#include "operations.h"
#include "entropies.h"
#include "entanglement.h"
#include "random.h"
#include "classes/timer.h"
#include "instruments.h"
#include "number_theory.h"
```

## Namespaces

- [qpp](#)

*Quantum++ main namespace.*

## Macros

- `#define QPP_UNUSED_`

### 8.23.1 Detailed Description

Quantum++ main header file, includes all other necessary headers.


### 8.23.2 Macro Definition Documentation

#### 8.23.2.1 `#define QPP_UNUSED_`

## 8.24 random.h File Reference

Randomness-related functions.

This graph shows which files directly or indirectly include this file:



## Namespaces

- `qpp`  
*Quantum++ main namespace.*

## Functions

- double `qpp::rand` (double a, double b)  
*Generates a random real number uniformly distributed in the interval [a, b).*
- bigint `qpp::rand` (bigint a, bigint b)  
*Generates a random big integer uniformly distributed in the interval [a, b].*
- idx `qpp::randidx` (idx a=std::numeric\_limits< idx >::min(), idx b=std::numeric\_limits< idx >::max())  
*Generates a random index (idx) uniformly distributed in the interval [a, b].*
- template<typename Derived >  
Derived `qpp::rand` (idx rows, idx cols, double a=0, double b=1)  
*Generates a random matrix with entries uniformly distributed in the interval [a, b)*
- template<>  
dmat `qpp::rand` (idx rows, idx cols, double a, double b)  
*Generates a random real matrix with entries uniformly distributed in the interval [a, b), specialization for double matrices (`qpp::dmat`)*

- `template<>`  
`cmat qpp::rand` (idx rows, idx cols, double a, double b)  
*Generates a random complex matrix with entries (both real and imaginary) uniformly distributed in the interval [a, b), specialization for complex matrices ([qpp::cmat](#))*
- `template<typename Derived >`  
`Derived qpp::randn` (idx rows, idx cols, double mean=0, double sigma=1)  
*Generates a random matrix with entries normally distributed in  $N(\text{mean}, \text{sigma})$*
- `template<>`  
`dmat qpp::randn` (idx rows, idx cols, double mean, double sigma)  
*Generates a random real matrix with entries normally distributed in  $N(\text{mean}, \text{sigma})$ , specialization for double matrices ([qpp::dmat](#))*
- `template<>`  
`cmat qpp::randn` (idx rows, idx cols, double mean, double sigma)  
*Generates a random complex matrix with entries (both real and imaginary) normally distributed in  $N(\text{mean}, \text{sigma})$ , specialization for complex matrices ([qpp::cmat](#))*
- `double qpp::randn` (double mean=0, double sigma=1)  
*Generates a random real number (double) normally distributed in  $N(\text{mean}, \text{sigma})$*
- `cmat qpp::randU` (idx D)  
*Generates a random unitary matrix.*
- `cmat qpp::randV` (idx Din, idx Dout)  
*Generates a random isometry matrix.*
- `std::vector< cmat > qpp::randkraus` (idx N, idx D)  
*Generates a set of random Kraus operators.*
- `cmat qpp::randH` (idx D)  
*Generates a random Hermitian matrix.*
- `ket qpp::randket` (idx D)  
*Generates a random normalized ket (pure state vector)*
- `cmat qpp::randrho` (idx D)  
*Generates a random density matrix.*
- `std::vector< idx > qpp::randperm` (idx N)  
*Generates a random uniformly distributed permutation.*

### 8.24.1 Detailed Description


Randomness-related functions.

## 8.25 statistics.h File Reference

Statistics functions.



This graph shows which files directly or indirectly include this file:



## Namespaces

- [qpp](#)  
*Quantum++ main namespace.*

## Functions

- `std::vector< double > qpp::uniform (idx N)`  
*Uniform probability distribution vector.*
- `std::vector< double > qpp::marginalX (const dmat &probXY)`  
*Marginal distribution.*
- `std::vector< double > qpp::marginalY (const dmat &probXY)`  
*Marginal distribution.*
- `template<typename Container >`  
`double qpp::avg (const std::vector< double > &prob, const Container &X, typename std::enable_if< is_↔`  
`iterable< Container >::value >::type !=nullptr)`  
*Average.*
- `template<typename Container >`  
`double qpp::cov (const dmat &probXY, const Container &X, const Container &Y, typename std::enable_if<`  
`is_iterable< Container >::value >::type !=nullptr)`  
*Covariance.*
- `template<typename Container >`  
`double qpp::var (const std::vector< double > &prob, const Container &X, typename std::enable_if< is_↔`  
`iterable< Container >::value >::type !=nullptr)`  
*Variance.*
- `template<typename Container >`  
`double qpp::sigma (const std::vector< double > &prob, const Container &X, typename std::enable_if< is_↔`  
`iterable< Container >::value >::type !=nullptr)`  
*Standard deviation.*
- `template<typename Container >`  
`double qpp::cor (const dmat &probXY, const Container &X, const Container &Y, typename std::enable_if<`  
`is_iterable< Container >::value >::type !=nullptr)`  
*Correlation.*


### 8.25.1 Detailed Description

Statistics functions.

## 8.26 traits.h File Reference

Type traits.

This graph shows which files directly or indirectly include this file:



### Classes

- struct `qpp::is_iterable< T, typename >`  
*Checks whether T is compatible with an STL-like iterable container.*
- struct `qpp::is_iterable< T, to_void< decltype(std::declval< T >().begin()), decltype(std::declval< T >().end()), typename T::value_type > >`  
*Checks whether T is compatible with an STL-like iterable container, specialization for STL-like iterable containers.*
- struct `qpp::is_matrix_expression< Derived >`  
*Checks whether the type is an Eigen matrix expression.*
- struct `qpp::is_matrix_expression< typename Eigen::MatrixBase< Derived > >`  
*Checks whether the type is an Eigen matrix expression, specialization for Eigen matrix expressions.*
- struct `qpp::is_complex< T >`  
*Checks whether the type is a complex type.*
- struct `qpp::is_complex< std::complex< T > >`  
*Checks whether the type is a complex number type, specialization for complex types.*

### Namespaces

- `qpp`  
*Quantum++ main namespace.*

### Typedefs

- `template<typename... >`  
`using qpp::to_void = void`  
*Alias template that implements the proposal for `void_t`.*


#### 8.26.1 Detailed Description

Type traits.

## 8.27 types.h File Reference

Type aliases.

This graph shows which files directly or indirectly include this file:



### Namespaces

- [qpp](#)  
*Quantum++ main namespace.*

### Typedefs

- using [qpp::idx](#) = std::size\_t  
*Non-negative integer index.*
- using [qpp::bigint](#) = long long int  
*Big integer.*
- using [qpp::cplx](#) = std::complex< double >  
*Complex number in double precision.*
- using [qpp::ket](#) = Eigen::VectorXcd  
*Complex (double precision) dynamic Eigen column vector.*
- using [qpp::bra](#) = Eigen::RowVectorXcd  
*Complex (double precision) dynamic Eigen row vector.*
- using [qpp::cmat](#) = Eigen::MatrixXcd  
*Complex (double precision) dynamic Eigen matrix.*
- using [qpp::dmat](#) = Eigen::MatrixXd  
*Real (double precision) dynamic Eigen matrix.*
- template<typename Scalar >  
using [qpp::dyn\\_mat](#) = Eigen::Matrix< Scalar, Eigen::Dynamic, Eigen::Dynamic >  
*Dynamic Eigen matrix over the field specified by Scalar.*
- template<typename Scalar >  
using [qpp::dyn\\_col\\_vect](#) = Eigen::Matrix< Scalar, Eigen::Dynamic, 1 >  
*Dynamic Eigen column vector over the field specified by Scalar.*
- template<typename Scalar >  
using [qpp::dyn\\_row\\_vect](#) = Eigen::Matrix< Scalar, 1, Eigen::Dynamic >  
*Dynamic Eigen row vector over the field specified by Scalar.*

### 8.27.1 Detailed Description

Type aliases.

# Index

- ~Codes
  - qpp::Codes, [86](#)
- ~Gates
  - qpp::Gates, [94](#)
- ~IDisplay
  - qpp::IDisplay, [99](#)
- ~Init
  - qpp::Init, [101](#)
- ~RandomDevices
  - qpp::RandomDevices, [114](#)
- ~Singleton
  - qpp::internal::Singleton, [116](#)
- ~States
  - qpp::States, [118](#)
- ~Timer
  - qpp::Timer, [122](#)
- A\_
  - qpp::internal::IOManipEigen, [103](#)
- absm
  - qpp, [26](#)
- abssq
  - qpp, [26](#), [27](#)
- adjoint
  - qpp, [27](#)
- anticomm
  - qpp, [27](#)
- apply
  - qpp, [27](#), [28](#), [30](#)
- applyCTRL
  - qpp, [30](#)
- avg
  - qpp, [31](#)
- b00
  - qpp::States, [118](#)
- b01
  - qpp::States, [118](#)
- b10
  - qpp::States, [119](#)
- b11
  - qpp::States, [119](#)
- bigint
  - qpp, [25](#)
- bloch2rho
  - qpp, [31](#)
- bra
  - qpp, [25](#)
- CNOT
  - qpp::Gates, [96](#)
- CNOTba
  - qpp::Gates, [96](#)
- CTRL
  - qpp::Gates, [94](#)
- CUSTOM\_EXCEPTION
  - qpp::Exception, [90](#)
- CZ
  - qpp::Gates, [96](#)
- check\_cvector
  - qpp::internal, [82](#)
- check\_dims
  - qpp::internal, [82](#)
- check\_dims\_match\_cvect
  - qpp::internal, [82](#)
- check\_dims\_match\_mat
  - qpp::internal, [82](#)
- check\_dims\_match\_rvect
  - qpp::internal, [82](#)
- check\_eq\_dims
  - qpp::internal, [82](#)
- check\_matching\_sizes
  - qpp::internal, [82](#)
- check\_nonzero\_size
  - qpp::internal, [82](#)
- check\_perm
  - qpp::internal, [82](#)
- check\_qubit\_cvector
  - qpp::internal, [82](#)
- check\_qubit\_matrix
  - qpp::internal, [82](#)
- check\_qubit\_rvector
  - qpp::internal, [82](#)
- check\_qubit\_vector
  - qpp::internal, [82](#)
- check\_rvector
  - qpp::internal, [82](#)
- check\_square\_mat
  - qpp::internal, [82](#)
- check\_subsys\_match\_dims
  - qpp::internal, [82](#)
- check\_vector
  - qpp::internal, [82](#)
- choi2kraus
  - qpp, [31](#)
- choi2super
  - qpp, [32](#)
- chop
  - qpp, [79](#)

- chop\_
  - qpp::internal::LOManipEigen, 103
- classes/codes.h, 125
- classes/exception.h, 125
- classes/gates.h, 126
- classes/ideisplay.h, 127
- classes/init.h, 128
- classes/random\_devices.h, 128
- classes/states.h, 129
- classes/timer.h, 130
- cmat
  - qpp, 25
- Codes
  - qpp::Codes, 86
- codeword
  - qpp::Codes, 87
- comm
  - qpp, 32
- complement
  - qpp, 32
- compperm
  - qpp, 33
- concurrency
  - qpp, 33
- conjugate
  - qpp, 33
- constants.h, 130
- construct\_exception\_msg\_
  - qpp::Exception, 91
- contrac2x
  - qpp, 33, 34
- cor
  - qpp, 34
- cosm
  - qpp, 34
- cov
  - qpp, 34
- cplx
  - qpp, 25
- custom\_
  - qpp::Exception, 91
- cwise
  - qpp, 35
- DIMS\_INVALID
  - qpp::Exception, 90
- DIMS\_MISMATCH\_CVECTOR
  - qpp::Exception, 90
- DIMS\_MISMATCH\_MATRIX
  - qpp::Exception, 90
- DIMS\_MISMATCH\_RVECTOR
  - qpp::Exception, 90
- DIMS\_MISMATCH\_VECTOR
  - qpp::Exception, 90
- DIMS\_NOT\_EQUAL
  - qpp::Exception, 90
- det
  - qpp, 35
- dirsum
  - qpp, 35, 36
- dirsum2
  - qpp::internal, 82
- dirsumpow
  - qpp, 36
- disp
  - qpp, 37, 38
- display
  - qpp::IDisplay, 99
  - qpp::Timer, 123
  - qpp::internal::LOManipEigen, 102
  - qpp::internal::LOManipPointer, 104
  - qpp::internal::LOManipRange, 106
- display\_impl\_
  - qpp::internal::details\_::Display\_Impl\_, 88
- dmat
  - qpp, 25
- dyn\_col\_vect
  - qpp, 25
- dyn\_mat
  - qpp, 25
- dyn\_row\_vect
  - qpp, 25
- ERROR
  - macros.h, 145
- ERRORLN
  - macros.h, 145
- ee
  - qpp, 79
- egcd
  - qpp, 38
- eig
  - qpp, 39
- end\_
  - qpp::Timer, 124
  - qpp::internal::LOManipPointer, 104
  - qpp::internal::LOManipRange, 106
- entanglement
  - qpp, 39
- entanglement.h, 131
- entropies.h, 132
- entropy
  - qpp, 39, 40
- eps
  - qpp, 80
- evals
  - qpp, 40
- evects
  - qpp, 40
- Exception
  - qpp::Exception, 90, 91
- expandout
  - qpp::Gates, 94
- experimental/experimental.h, 134
- expm
  - qpp, 40
- FIVE\_QUBIT

- qpp::Codes, 86
- FRED
  - qpp::Gates, 96
- factors
  - qpp, 41
- Fd
  - qpp::Gates, 95
- first\_
  - qpp::internal::IOManipRange, 106
- functions.h, 134
- funm
  - qpp, 41
- GHZ
  - qpp::States, 119
- Gates
  - qpp::Gates, 94
- gcd
  - qpp, 41
- gconcurrency
  - qpp, 42
- get\_dim\_subsys
  - qpp::internal, 82
- get\_duration
  - qpp::Timer, 123
- get\_instance
  - qpp::internal::Singleton, 116
- get\_num\_subsys
  - qpp::internal, 82
- get\_thread\_local\_instance
  - qpp::internal::Singleton, 116
- grams
  - qpp, 42, 43
- H
  - qpp::Gates, 96
- heig
  - qpp, 43
- hevals
  - qpp, 43
- hevects
  - qpp, 43
- IDisplay
  - qpp::IDisplay, 99
- IOManipEigen
  - qpp::internal::IOManipEigen, 102
- IOManipPointer
  - qpp::internal::IOManipPointer, 104
- IOManipRange
  - qpp::internal::IOManipRange, 106
- Id
  - qpp::Gates, 95
- Id2
  - qpp::Gates, 97
- idx
  - qpp, 26
- infy
  - qpp, 80
- Init
  - qpp::Init, 101
- input\_output.h, 138
- instruments.h, 139
- internal/classes/iomanip.h, 141
- internal/classes/singleton.h, 142
- internal/util.h, 143
- internal::Singleton< const Codes >
  - qpp::Codes, 87
- internal::Singleton< const Gates >
  - qpp::Gates, 96
- internal::Singleton< const Init >
  - qpp::Init, 101
- internal::Singleton< const States >
  - qpp::States, 118
- internal::Singleton< RandomDevices >
  - qpp::RandomDevices, 114
- inverse
  - qpp, 44
- invperm
  - qpp, 44
- ip
  - qpp, 44, 45
- isprime
  - qpp, 45
- ket
  - qpp, 26
- kraus2choi
  - qpp, 45
- kraus2super
  - qpp, 46
- kron
  - qpp, 46, 47
- kron2
  - qpp::internal, 82
- kronpow
  - qpp, 47
- last\_
  - qpp::internal::IOManipRange, 106
- lcm
  - qpp, 48
- load
  - qpp, 48
- loadMATLABmatrix
  - qpp, 49
- logdet
  - qpp, 50
- logm
  - qpp, 50
- lognegativity
  - qpp, 50
- MATLAB/matlab.h, 145
- MATRIX\_MISMATCH\_SUBSYS
  - qpp::Exception, 90
- MATRIX\_NOT\_CVECTOR
  - qpp::Exception, 90

MATRIX\_NOT\_RVECTOR  
     qpp::Exception, 90  
 MATRIX\_NOT\_SQUARE  
     qpp::Exception, 90  
 MATRIX\_NOT\_SQUARE\_OR\_CVECTOR  
     qpp::Exception, 90  
 MATRIX\_NOT\_SQUARE\_OR\_RVECTOR  
     qpp::Exception, 90  
 MATRIX\_NOT\_SQUARE\_OR\_VECTOR  
     qpp::Exception, 90  
 MATRIX\_NOT\_VECTOR  
     qpp::Exception, 90  
 macros.h, 144  
     ERROR, 145  
     ERRORLN, 145  
     PRINT, 145  
     PRINTLN, 145  
 marginalX  
     qpp, 50  
 marginalY  
     qpp, 51  
 maxn  
     qpp, 80  
 measure  
     qpp, 51–54  
 measure\_seq  
     qpp, 55  
 mket  
     qpp, 55, 56  
 modinv  
     qpp, 56  
 modmul  
     qpp, 56  
 modpow  
     qpp, 57  
 mprj  
     qpp, 57  
 msg\_  
     qpp::Exception, 91  
 multiidx2n  
     qpp, 58  
     qpp::internal, 82  
  
 n2multiidx  
     qpp, 58  
     qpp::internal, 82  
 N\_  
     qpp::internal::IOManipPointer, 104  
 NINE\_QUBIT\_SHOR  
     qpp::Codes, 86  
 NO\_CODEWORD  
     qpp::Exception, 90  
 NOT\_BIPARTITE  
     qpp::Exception, 90  
 NOT\_QUBIT\_CVECTOR  
     qpp::Exception, 90  
 NOT\_QUBIT\_MATRIX  
     qpp::Exception, 90  
 NOT\_QUBIT\_RVECTOR  
     qpp::Exception, 90  
 NOT\_QUBIT\_SUBSYS  
     qpp::Exception, 90  
 NOT\_QUBIT\_VECTOR  
     qpp::Exception, 90  
 negativity  
     qpp, 58  
 norm  
     qpp, 59  
 number\_theory.h, 146  
  
 OUT\_OF\_RANGE  
     qpp::Exception, 90  
 omega  
     qpp, 59  
 operations.h, 147  
 operator<<  
     qpp::IDisplay, 99  
 operator=  
     qpp::IDisplay, 99  
     qpp::Timer, 123  
     qpp::internal::IOManipPointer, 104  
     qpp::internal::IOManipRange, 106  
     qpp::internal::Singleton, 116  
 operator""\_i  
     qpp, 59  
  
 p\_  
     qpp::internal::IOManipPointer, 104  
 PERM\_INVALID  
     qpp::Exception, 90  
 PERM\_MISMATCH\_DIMS  
     qpp::Exception, 90  
 pGHZ  
     qpp::States, 119  
 PRINT  
     macros.h, 145  
 PRINTLN  
     macros.h, 145  
 pW  
     qpp::States, 119  
 pb00  
     qpp::States, 119  
 pb01  
     qpp::States, 119  
 pb10  
     qpp::States, 119  
 pb11  
     qpp::States, 119  
 pi  
     qpp, 80  
 powm  
     qpp, 59  
 prj  
     qpp, 60  
 prod  
     qpp, 60  
 ptrace  
     qpp, 61



ptrace1  
     qpp, 61  
 ptrace2  
     qpp, 63  
 ptranspose  
     qpp, 63  
 px0  
     qpp::States, 119  
 px1  
     qpp::States, 119  
 py0  
     qpp::States, 119  
 py1  
     qpp::States, 120  
 pz0  
     qpp::States, 120  
 pz1  
     qpp::States, 120  
 QPP\_UNUSED\_  
     qpp.h, 151  
 qmutualinfo  
     qpp, 64  
 qpp, 13  
     absm, 26  
     abssq, 26, 27  
     adjoint, 27  
     anticomm, 27  
     apply, 27, 28, 30  
     applyCTRL, 30  
     avg, 31  
     bigint, 25  
     bloch2rho, 31  
     bra, 25  
     choi2kraus, 31  
     choi2super, 32  
     chop, 79  
     cmat, 25  
     comm, 32  
     complement, 32  
     compperm, 33  
     concurrence, 33  
     conjugate, 33  
     contrfrac2x, 33, 34  
     cor, 34  
     cosm, 34  
     cov, 34  
     cplx, 25  
     cwise, 35  
     det, 35  
     dirsum, 35, 36  
     dirsumpow, 36  
     disp, 37, 38  
     dmat, 25  
     dyn\_col\_vect, 25  
     dyn\_mat, 25  
     dyn\_row\_vect, 25  
     ee, 79  
     egcd, 38  
     eig, 39  
     entanglement, 39  
     entropy, 39, 40  
     eps, 80  
     evals, 40  
     evects, 40  
     expm, 40  
     factors, 41  
     funm, 41  
     gcd, 41  
     gconcurrence, 42  
     grams, 42, 43  
     heig, 43  
     hevals, 43  
     hevects, 43  
     idx, 26  
     infty, 80  
     inverse, 44  
     invperm, 44  
     ip, 44, 45  
     isprime, 45  
     ket, 26  
     kraus2choi, 45  
     kraus2super, 46  
     kron, 46, 47  
     kronpow, 47  
     lcm, 48  
     load, 48  
     loadMATLABmatrix, 49  
     logdet, 50  
     logm, 50  
     lognegativity, 50  
     marginalX, 50  
     marginalY, 51  
     maxn, 80  
     measure, 51–54  
     measure\_seq, 55  
     mket, 55, 56  
     modinv, 56  
     modmul, 56  
     modpow, 57  
     mprj, 57  
     multiidx2n, 58  
     n2multiidx, 58  
     negativity, 58  
     norm, 59  
     omega, 59  
     operator""\_i, 59  
     pi, 80  
     powm, 59  
     prj, 60  
     prod, 60  
     ptrace, 61  
     ptrace1, 61  
     ptrace2, 63  
     ptranspose, 63  
     qmutualinfo, 64  
     rand, 64, 66

- randH, 67
- randU, 70
- randV, 70
- randidx, 67
- randket, 67
- randkraus, 67
- randn, 68, 69
- randperm, 69
- randprime, 69
- randrho, 69
- renyi, 70
- reshape, 71
- rho2bloch, 71
- rho2pure, 71
- save, 72
- saveMATLABmatrix, 72
- schatten, 73
- schmidtA, 73
- schmidtB, 73
- schmidtcoeffs, 73
- schmidtprobs, 74
- sigma, 74
- sinm, 74
- spectralpowm, 75
- sqrtn, 75
- sum, 75, 76
- super2choi, 76
- svals, 76
- svd, 76
- svdU, 77
- svdV, 77
- syspermute, 77
- to\_void, 26
- trace, 78
- transpose, 78
- tsallis, 78
- uniform, 79
- var, 79
- x2confrac, 79
- qpp.h, 149
  - QPP\_UNUSED\_, 151
- qpp::Codes, 85
  - ~Codes, 86
  - Codes, 86
  - codeword, 87
  - FIVE\_QUBIT, 86
  - internal::Singleton< const Codes >, 87
  - NINE\_QUBIT\_SHOR, 86
  - SEVEN\_QUBIT\_STEANE, 86
  - Type, 86
- qpp::Exception, 88
  - CUSTOM\_EXCEPTION, 90
  - construct\_exception\_msg\_, 91
  - custom\_, 91
  - DIMS\_INVALID, 90
  - DIMS\_MISMATCH\_CVECTOR, 90
  - DIMS\_MISMATCH\_MATRIX, 90
  - DIMS\_MISMATCH\_RVECTOR, 90
  - DIMS\_MISMATCH\_VECTOR, 90
  - DIMS\_NOT\_EQUAL, 90
  - Exception, 90, 91
  - MATRIX\_MISMATCH\_SUBSYS, 90
  - MATRIX\_NOT\_CVECTOR, 90
  - MATRIX\_NOT\_RVECTOR, 90
  - MATRIX\_NOT\_SQUARE, 90
  - MATRIX\_NOT\_SQUARE\_OR\_CVECTOR, 90
  - MATRIX\_NOT\_SQUARE\_OR\_RVECTOR, 90
  - MATRIX\_NOT\_SQUARE\_OR\_VECTOR, 90
  - MATRIX\_NOT\_VECTOR, 90
  - msg\_, 91
  - NO\_CODEWORD, 90
  - NOT\_BIPARTITE, 90
  - NOT\_QUBIT\_CVECTOR, 90
  - NOT\_QUBIT\_MATRIX, 90
  - NOT\_QUBIT\_RVECTOR, 90
  - NOT\_QUBIT\_SUBSYS, 90
  - NOT\_QUBIT\_VECTOR, 90
  - OUT\_OF\_RANGE, 90
  - PERM\_INVALID, 90
  - PERM\_MISMATCH\_DIMS, 90
  - SIZE\_MISMATCH, 90
  - SUBSYS\_MISMATCH\_DIMS, 90
  - TYPE\_MISMATCH, 90
  - Type, 89
  - type\_, 91
  - UNDEFINED\_TYPE, 90
  - UNKNOWN\_EXCEPTION, 90
  - what, 91
  - where\_, 91
  - ZERO\_SIZE, 90
- qpp::Gates, 91
  - ~Gates, 94
  - CNOT, 96
  - CNOTba, 96
  - CTRL, 94
  - CZ, 96
  - expandout, 94
  - FRED, 96
  - Fd, 95
  - Gates, 94
  - H, 96
  - Id, 95
  - Id2, 97
  - internal::Singleton< const Gates >, 96
  - Rn, 95
  - S, 97
  - SWAP, 97
  - T, 97
  - TOF, 97
  - X, 97
  - Xd, 95
  - Y, 97
  - Z, 97
  - Zd, 96
- qpp::IDisplay, 97
  - ~IDisplay, 99

- display, 99
- IDisplay, 99
- operator<<, 99
- operator=, 99
- qpp::Init, 100
  - ~Init, 101
  - Init, 101
  - internal::Singleton< const Init >, 101
- qpp::RandomDevices, 113
  - ~RandomDevices, 114
  - internal::Singleton< RandomDevices >, 114
  - RandomDevices, 114
  - rd\_, 114
  - rng\_, 114
- qpp::States, 116
  - ~States, 118
  - b00, 118
  - b01, 118
  - b10, 119
  - b11, 119
  - GHZ, 119
  - internal::Singleton< const States >, 118
  - pGHZ, 119
  - pW, 119
  - pb00, 119
  - pb01, 119
  - pb10, 119
  - pb11, 119
  - px0, 119
  - px1, 119
  - py0, 119
  - py1, 120
  - pz0, 120
  - pz1, 120
  - States, 118
  - W, 120
  - x0, 120
  - x1, 120
  - y0, 120
  - y1, 120
  - z0, 120
  - z1, 120
- qpp::Timer
  - ~Timer, 122
  - display, 123
  - end\_, 124
  - get\_duration, 123
  - operator=, 123
  - start\_, 124
  - tic, 123
  - tics, 123
  - Timer, 122
  - toc, 124
- qpp::Timer< T, CLOCK\_T >, 121
- qpp::experimental, 80
- qpp::internal, 80
  - check\_cvector, 82
  - check\_dims, 82
  - check\_dims\_match\_cvect, 82
  - check\_dims\_match\_mat, 82
  - check\_dims\_match\_rvect, 82
  - check\_eq\_dims, 82
  - check\_matching\_sizes, 82
  - check\_nonzero\_size, 82
  - check\_perm, 82
  - check\_qubit\_cvector, 82
  - check\_qubit\_matrix, 82
  - check\_qubit\_rvector, 82
  - check\_qubit\_vector, 82
  - check\_rvector, 82
  - check\_square\_mat, 82
  - check\_subsys\_match\_dims, 82
  - check\_vector, 82
  - dirsum2, 82
  - get\_dim\_subsys, 82
  - get\_num\_subsys, 82
  - kron2, 82
  - multiidx2n, 82
  - n2multiidx, 82
  - variadic\_vector\_emplace, 83
- qpp::internal::IOManipEigen, 101
  - A\_, 103
  - chop\_, 103
  - display, 102
  - IOManipEigen, 102
- qpp::internal::IOManipPointer
  - display, 104
  - end\_, 104
  - IOManipPointer, 104
  - N\_, 104
  - operator=, 104
  - p\_, 104
  - separator\_, 104
  - start\_, 105
- qpp::internal::IOManipPointer< PointerType >, 103
- qpp::internal::IOManipRange
  - display, 106
  - end\_, 106
  - first\_, 106
  - IOManipRange, 106
  - last\_, 106
  - operator=, 106
  - separator\_, 106
  - start\_, 107
- qpp::internal::IOManipRange< InputIterator >, 105
- qpp::internal::Singleton
  - ~Singleton, 116
  - get\_instance, 116
  - get\_thread\_local\_instance, 116
  - operator=, 116
  - Singleton, 116
- qpp::internal::Singleton< T >, 115
- qpp::internal::details\_, 83
- qpp::internal::details::Display\_Impl\_, 87
  - display\_impl\_, 88
- qpp::is\_complex< std::complex< T > >, 108

- qpp::is\_complex< T >, 107
- qpp::is\_iterable< T, to\_void< decltype(std::declval< T >().begin()), decltype(std::declval< T >().end()), typename T::value\_type > >, 110
- qpp::is\_iterable< T, typename >, 109
- qpp::is\_matrix\_expression< Derived >, 111
- qpp::is\_matrix\_expression< typename Eigen::Matrix< Base< Derived > >, 112
- rand
  - qpp, 64, 66
- randH
  - qpp, 67
- randU
  - qpp, 70
- randV
  - qpp, 70
- randidx
  - qpp, 67
- randket
  - qpp, 67
- randkraus
  - qpp, 67
- randn
  - qpp, 68, 69
- random.h, 151
- RandomDevices
  - qpp::RandomDevices, 114
- randperm
  - qpp, 69
- randprime
  - qpp, 69
- randrho
  - qpp, 69
- rd\_
  - qpp::RandomDevices, 114
- renyi
  - qpp, 70
- reshape
  - qpp, 71
- rho2bloch
  - qpp, 71
- rho2pure
  - qpp, 71
- Rn
  - qpp::Gates, 95
- rng\_
  - qpp::RandomDevices, 114
- S
  - qpp::Gates, 97
- SEVEN\_QUBIT\_STEANE
  - qpp::Codes, 86
- SIZE\_MISMATCH
  - qpp::Exception, 90
- SUBSYS\_MISMATCH\_DIMS
  - qpp::Exception, 90
- SWAP
  - qpp::Gates, 97
- save
  - qpp, 72
- saveMATLABmatrix
  - qpp, 72
- schatten
  - qpp, 73
- schmidtA
  - qpp, 73
- schmidtB
  - qpp, 73
- schmidtcoeffs
  - qpp, 73
- schmidtprobs
  - qpp, 74
- separator\_
  - qpp::internal::IOManipPointer, 104
  - qpp::internal::IOManipRange, 106
- sigma
  - qpp, 74
- Singleton
  - qpp::internal::Singleton, 116
- sinm
  - qpp, 74
- spectralpowm
  - qpp, 75
- sqrtn
  - qpp, 75
- start\_
  - qpp::Timer, 124
  - qpp::internal::IOManipPointer, 105
  - qpp::internal::IOManipRange, 107
- States
  - qpp::States, 118
- statistics.h, 152
- sum
  - qpp, 75, 76
- super2choi
  - qpp, 76
- svals
  - qpp, 76
- svd
  - qpp, 76
- svdU
  - qpp, 77
- svdV
  - qpp, 77
- syspermute
  - qpp, 77
- T
  - qpp::Gates, 97
- TOF
  - qpp::Gates, 97
- TYPE\_MISMATCH
  - qpp::Exception, 90
- tic
  - qpp::Timer, 123
- tics
  - qpp::Timer, 123

Timer  
    qpp::Timer, [122](#)  
to\_void  
    qpp, [26](#)  
toc  
    qpp::Timer, [124](#)  
trace  
    qpp, [78](#)  
traits.h, [154](#)  
transpose  
    qpp, [78](#)  
tsallis  
    qpp, [78](#)  
Type  
    qpp::Codes, [86](#)  
    qpp::Exception, [89](#)  
type\_  
    qpp::Exception, [91](#)  
types.h, [155](#)  
  
UNDEFINED\_TYPE  
    qpp::Exception, [90](#)  
UNKNOWN\_EXCEPTION  
    qpp::Exception, [90](#)  
uniform  
    qpp, [79](#)  
  
var  
    qpp, [79](#)  
variadic\_vector\_emplace  
    qpp::internal, [83](#)  
  
W  
    qpp::States, [120](#)  
what  
    qpp::Exception, [91](#)  
where\_  
    qpp::Exception, [91](#)  
  
X  
    qpp::Gates, [97](#)  
x0  
    qpp::States, [120](#)  
x1  
    qpp::States, [120](#)  
x2contfrac  
    qpp, [79](#)  
Xd  
    qpp::Gates, [95](#)  
  
Y  
    qpp::Gates, [97](#)  
y0  
    qpp::States, [120](#)  
y1  
    qpp::States, [120](#)  
  
Z  
    qpp::Gates, [97](#)  
z0  
    qpp::States, [120](#)  
z1  
    qpp::States, [120](#)  
ZERO\_SIZE  
    qpp::Exception, [90](#)  
Zd  
    qpp::Gates, [96](#)