

quantum++
0.1

Generated by Doxygen 1.8.7

Wed Nov 12 2014 23:09:01

Contents

1	Quantum++ - A C++11 quantum computing library	1
2	Namespace Index	5
2.1	Namespace List	5
3	Hierarchical Index	7
3.1	Class Hierarchy	7
4	Class Index	9
4.1	Class List	9
5	File Index	11
5.1	File List	11
6	Namespace Documentation	13
6.1	qpp Namespace Reference	13
6.1.1	Typedef Documentation	22
6.1.1.1	bra	22
6.1.1.2	cmat	22
6.1.1.3	cplx	22
6.1.1.4	dmat	23
6.1.1.5	DynColVect	23
6.1.1.6	DynMat	23
6.1.1.7	DynRowVect	23
6.1.1.8	ket	23
6.1.2	Function Documentation	23
6.1.2.1	absm	23
6.1.2.2	abssq	23
6.1.2.3	abssq	24
6.1.2.4	adjoint	24
6.1.2.5	anticomm	24
6.1.2.6	apply	24
6.1.2.7	apply	25

6.1.2.8	<code>applyCTRL</code>	25
6.1.2.9	<code>applyCTRL</code>	26
6.1.2.10	<code>channel</code>	26
6.1.2.11	<code>channel</code>	26
6.1.2.12	<code>channel</code>	26
6.1.2.13	<code>choi</code>	27
6.1.2.14	<code>choi2kraus</code>	27
6.1.2.15	<code>comm</code>	27
6.1.2.16	<code>compperm</code>	28
6.1.2.17	<code>concurrence</code>	28
6.1.2.18	<code>conjugate</code>	28
6.1.2.19	<code>contfrac2x</code>	28
6.1.2.20	<code>contfrac2x</code>	29
6.1.2.21	<code>cosm</code>	29
6.1.2.22	<code>cwise</code>	29
6.1.2.23	<code>det</code>	29
6.1.2.24	<code>disp</code>	30
6.1.2.25	<code>disp</code>	30
6.1.2.26	<code>disp</code>	30
6.1.2.27	<code>disp</code>	30
6.1.2.28	<code>disp</code>	31
6.1.2.29	<code>entanglement</code>	31
6.1.2.30	<code>evals</code>	31
6.1.2.31	<code>evects</code>	32
6.1.2.32	<code>expm</code>	32
6.1.2.33	<code>funm</code>	32
6.1.2.34	<code>gcd</code>	32
6.1.2.35	<code>gcd</code>	33
6.1.2.36	<code>gconcurrence</code>	33
6.1.2.37	<code>grams</code>	33
6.1.2.38	<code>grams</code>	33
6.1.2.39	<code>grams</code>	34
6.1.2.40	<code>hevals</code>	34
6.1.2.41	<code>hevects</code>	34
6.1.2.42	<code>inverse</code>	34
6.1.2.43	<code>invperm</code>	35
6.1.2.44	<code>kron</code>	35
6.1.2.45	<code>kron</code>	35
6.1.2.46	<code>kron</code>	35
6.1.2.47	<code>kron</code>	36

6.1.2.48	kronpow	36
6.1.2.49	lcm	36
6.1.2.50	lcm	36
6.1.2.51	load	37
6.1.2.52	loadMATLABmatrix	37
6.1.2.53	loadMATLABmatrix	37
6.1.2.54	loadMATLABmatrix	38
6.1.2.55	logdet	38
6.1.2.56	logm	38
6.1.2.57	lognegativity	38
6.1.2.58	measure	39
6.1.2.59	measure	39
6.1.2.60	measure	40
6.1.2.61	measure	40
6.1.2.62	measure	40
6.1.2.63	measure	41
6.1.2.64	measure	41
6.1.2.65	measure	41
6.1.2.66	measure	42
6.1.2.67	mket	42
6.1.2.68	mket	42
6.1.2.69	mprj	43
6.1.2.70	mprj	43
6.1.2.71	multiidx2n	43
6.1.2.72	n2multiidx	43
6.1.2.73	negativity	44
6.1.2.74	norm	44
6.1.2.75	omega	44
6.1.2.76	operator""_i	44
6.1.2.77	operator""_i	45
6.1.2.78	powm	45
6.1.2.79	prj	45
6.1.2.80	prod	45
6.1.2.81	prod	45
6.1.2.82	ptrace	46
6.1.2.83	ptrace1	46
6.1.2.84	ptrace2	46
6.1.2.85	ptranspose	47
6.1.2.86	qmutualinfo	47
6.1.2.87	rand	47

6.1.2.88	rand	47
6.1.2.89	rand	48
6.1.2.90	rand	48
6.1.2.91	randH	48
6.1.2.92	randint	49
6.1.2.93	randket	49
6.1.2.94	randkraus	49
6.1.2.95	randn	49
6.1.2.96	randn	50
6.1.2.97	randn	50
6.1.2.98	randn	50
6.1.2.99	randperm	51
6.1.2.100	randrho	51
6.1.2.101	randU	51
6.1.2.102	randV	51
6.1.2.103	renyi	51
6.1.2.104	reshape	52
6.1.2.105	rho2pure	52
6.1.2.106	save	52
6.1.2.107	saveMATLABmatrix	53
6.1.2.108	saveMATLABmatrix	53
6.1.2.109	saveMATLABmatrix	53
6.1.2.110	schatten	53
6.1.2.111	schmidtcoeff	53
6.1.2.112	schmidtprob	54
6.1.2.113	schmidtU	54
6.1.2.114	schmidtV	54
6.1.2.115	shannon	55
6.1.2.116	sinm	55
6.1.2.117	spectralpowm	55
6.1.2.118	sqrtm	55
6.1.2.119	sum	56
6.1.2.120	sum	56
6.1.2.121	super	56
6.1.2.122	svals	56
6.1.2.123	svdU	57
6.1.2.124	svdV	57
6.1.2.125	syspermute	57
6.1.2.126	trace	57
6.1.2.127	transpose	58

6.1.2.128	tsallis	58
6.1.2.129	x2confrac	58
6.1.3	Variable Documentation	58
6.1.3.1	chop	58
6.1.3.2	codes	59
6.1.3.3	ee	59
6.1.3.4	eps	59
6.1.3.5	gt	59
6.1.3.6	infty	59
6.1.3.7	init	59
6.1.3.8	maxn	59
6.1.3.9	pi	59
6.1.3.10	rdevs	59
6.1.3.11	st	59
6.2	qpp::experimental Namespace Reference	60
6.2.1	Detailed Description	60
6.3	qpp::internal Namespace Reference	60
6.3.1	Detailed Description	61
6.3.2	Function Documentation	61
6.3.2.1	_check_col_vector	61
6.3.2.2	_check_dims	61
6.3.2.3	_check_dims_match_cvect	61
6.3.2.4	_check_dims_match_mat	61
6.3.2.5	_check_dims_match_rvect	61
6.3.2.6	_check_eq_dims	61
6.3.2.7	_check_nonzero_size	61
6.3.2.8	_check_perm	61
6.3.2.9	_check_row_vector	61
6.3.2.10	_check_square_mat	61
6.3.2.11	_check_subsys_match_dims	61
6.3.2.12	_check_vector	61
6.3.2.13	_kron2	61
6.3.2.14	_multiidx2n	61
6.3.2.15	_n2multiidx	61
6.3.2.16	variadic_vector_emplace	61
6.3.2.17	variadic_vector_emplace	61
7	Class Documentation	63
7.1	qpp::Codes Class Reference	63
7.1.1	Detailed Description	64

7.1.2	Member Enumeration Documentation	64
7.1.2.1	Type	64
7.1.3	Constructor & Destructor Documentation	64
7.1.3.1	Codes	64
7.1.4	Member Function Documentation	64
7.1.4.1	codeword	64
7.1.5	Friends And Related Function Documentation	65
7.1.5.1	internal::Singleton< const Codes >	65
7.2	qpp::Exception Class Reference	65
7.2.1	Detailed Description	67
7.2.2	Member Enumeration Documentation	67
7.2.2.1	Type	67
7.2.3	Constructor & Destructor Documentation	68
7.2.3.1	Exception	68
7.2.3.2	Exception	68
7.2.4	Member Function Documentation	68
7.2.4.1	_construct_exception_msg	68
7.2.4.2	what	68
7.2.5	Member Data Documentation	69
7.2.5.1	_custom	69
7.2.5.2	_msg	69
7.2.5.3	_type	69
7.2.5.4	_where	69
7.3	qpp::Gates Class Reference	69
7.3.1	Detailed Description	71
7.3.2	Constructor & Destructor Documentation	71
7.3.2.1	Gates	71
7.3.3	Member Function Documentation	71
7.3.3.1	CTRL	71
7.3.3.2	expandout	71
7.3.3.3	Fd	72
7.3.3.4	Id	72
7.3.3.5	Rn	72
7.3.3.6	Xd	73
7.3.3.7	Zd	73
7.3.4	Friends And Related Function Documentation	73
7.3.4.1	internal::Singleton< const Gates >	73
7.3.5	Member Data Documentation	73
7.3.5.1	CNOTab	73
7.3.5.2	CNOTba	73

7.3.5.3	CZ	73
7.3.5.4	FRED	73
7.3.5.5	H	74
7.3.5.6	Id2	74
7.3.5.7	S	74
7.3.5.8	SWAP	74
7.3.5.9	T	74
7.3.5.10	TOF	74
7.3.5.11	X	74
7.3.5.12	Y	74
7.3.5.13	Z	74
7.4	qpp::Init Class Reference	74
7.4.1	Detailed Description	75
7.4.2	Constructor & Destructor Documentation	76
7.4.2.1	Init	76
7.4.2.2	~Init	76
7.4.3	Friends And Related Function Documentation	76
7.4.3.1	internal::Singleton< const Init >	76
7.5	qpp::internal::IOManipEigen Class Reference	76
7.5.1	Constructor & Destructor Documentation	76
7.5.1.1	IOManipEigen	76
7.5.1.2	IOManipEigen	76
7.5.2	Friends And Related Function Documentation	76
7.5.2.1	operator<<	77
7.5.3	Member Data Documentation	77
7.5.3.1	_A	77
7.5.3.2	_chop	77
7.6	qpp::internal::IOManipPointer< PointerType > Class Template Reference	77
7.6.1	Constructor & Destructor Documentation	78
7.6.1.1	IOManipPointer	78
7.6.1.2	IOManipPointer	78
7.6.2	Member Function Documentation	78
7.6.2.1	operator=	78
7.6.3	Friends And Related Function Documentation	78
7.6.3.1	operator<<	78
7.6.4	Member Data Documentation	78
7.6.4.1	_end	78
7.6.4.2	_n	78
7.6.4.3	_p	78
7.6.4.4	_separator	78

7.6.4.5	<code>_start</code>	78
7.7	<code>qpp::internal::IOManipRange< InputIterator ></code> Class Template Reference	78
7.7.1	Constructor & Destructor Documentation	79
7.7.1.1	<code>IOManipRange</code>	79
7.7.2	Friends And Related Function Documentation	79
7.7.2.1	<code>operator<<</code>	80
7.7.3	Member Data Documentation	80
7.7.3.1	<code>_end</code>	80
7.7.3.2	<code>_first</code>	80
7.7.3.3	<code>_last</code>	80
7.7.3.4	<code>_separator</code>	80
7.7.3.5	<code>_start</code>	80
7.8	<code>qpp::RandomDevices</code> Class Reference	80
7.8.1	Detailed Description	81
7.8.2	Constructor & Destructor Documentation	81
7.8.2.1	<code>RandomDevices</code>	81
7.8.3	Friends And Related Function Documentation	82
7.8.3.1	<code>internal::Singleton< RandomDevices ></code>	82
7.8.4	Member Data Documentation	82
7.8.4.1	<code>_rd</code>	82
7.8.4.2	<code>_rng</code>	82
7.9	<code>qpp::internal::Singleton< T ></code> Class Template Reference	82
7.9.1	Detailed Description	82
7.9.2	Constructor & Destructor Documentation	83
7.9.2.1	<code>Singleton</code>	83
7.9.2.2	<code>~Singleton</code>	83
7.9.2.3	<code>Singleton</code>	83
7.9.3	Member Function Documentation	83
7.9.3.1	<code>get_instance</code>	83
7.9.3.2	<code>operator=</code>	83
7.10	<code>qpp::States</code> Class Reference	83
7.10.1	Detailed Description	85
7.10.2	Constructor & Destructor Documentation	85
7.10.2.1	<code>States</code>	85
7.10.3	Friends And Related Function Documentation	85
7.10.3.1	<code>internal::Singleton< const States ></code>	85
7.10.4	Member Data Documentation	85
7.10.4.1	<code>b00</code>	85
7.10.4.2	<code>b01</code>	85
7.10.4.3	<code>b10</code>	86

7.10.4.4	b11	86
7.10.4.5	GHZ	86
7.10.4.6	pb00	86
7.10.4.7	pb01	86
7.10.4.8	pb10	86
7.10.4.9	pb11	86
7.10.4.10	pGHZ	86
7.10.4.11	pW	86
7.10.4.12	px0	86
7.10.4.13	px1	86
7.10.4.14	py0	86
7.10.4.15	py1	87
7.10.4.16	pz0	87
7.10.4.17	pz1	87
7.10.4.18	W	87
7.10.4.19	x0	87
7.10.4.20	x1	87
7.10.4.21	y0	87
7.10.4.22	y1	87
7.10.4.23	z0	87
7.10.4.24	z1	87
7.11	qpp::Timer Class Reference	87
7.11.1	Detailed Description	88
7.11.2	Constructor & Destructor Documentation	88
7.11.2.1	Timer	88
7.11.3	Member Function Documentation	88
7.11.3.1	seconds	88
7.11.3.2	tic	88
7.11.3.3	toc	89
7.11.4	Friends And Related Function Documentation	89
7.11.4.1	operator<<	89
7.11.5	Member Data Documentation	89
7.11.5.1	_end	89
7.11.5.2	_start	89
8	File Documentation	91
8.1	include/classes/codes.h File Reference	91
8.2	include/classes/exception.h File Reference	92
8.3	include/classes/gates.h File Reference	92
8.4	include/classes/init.h File Reference	93

8.5	include/classes/random_devices.h File Reference	93
8.6	include/classes/singleton.h File Reference	94
8.7	include/classes/states.h File Reference	95
8.8	include/classes/timer.h File Reference	95
8.9	include/constants.h File Reference	96
8.10	include/entanglement.h File Reference	97
8.11	include/entropies.h File Reference	98
8.12	include/experimental/test.h File Reference	98
8.13	include/functions.h File Reference	99
8.14	include/internal/functions.h File Reference	102
8.15	include/input_output.h File Reference	103
8.16	include/instruments.h File Reference	104
8.17	include/internal/classes/iomanip.h File Reference	106
8.18	include/MATLAB/matlab.h File Reference	106
8.19	include/number_theory.h File Reference	107
8.20	include/operations.h File Reference	108
8.21	include/qpp.h File Reference	110
8.22	include/random.h File Reference	111
8.23	include/types.h File Reference	112
8.24	mainpage.dox File Reference	113
	Index	114

Chapter 1

Quantum++ - A C++11 quantum computing library

Version

0.1

Author

Vlad Gheorghiu (vgheorgh@gmail.com)

Copyright

(c) 2013 - 2014 Vlad Gheorghiu (vgheorgh@gmail.com)

An example is worth more than one thousand words.

```
#include "qpp.h"

// #include "MATLAB/matlab.h" // support for MATLAB

using namespace qpp;

int main()
{
    // Qudit teleportation
    {
        std::size_t D = 3; // size of the system
        std::cout << std::endl << "**** Qudit teleportation, D = " << D << " ****" << std::endl;
        ket mes_AB = ket::Zero(D * D); // maximally entangled state resource
        for (std::size_t i = 0; i < D; i++)
            mes_AB += mket({i, i}, D);
        mes_AB /= std::sqrt((double) D);
        // circuit that measures in the qudit Bell basis
        cmat Bell_aA = adjoint(gt.CTRL(gt.Xd(D), {0}, {1}, 2, D) *
            kron(gt.Fd(D), gt.Id(D)));
        ket psi_a = randket(D); // random state as input on a
        std::cout << ">> Initial state:" << std::endl;
        std::cout << disp(psi_a) << std::endl;
        ket input_aAB = kron(psi_a, mes_AB); // joint input state aAB
        // output before measurement
        ket output_aAB = apply(input_aAB, Bell_aA, {0, 1}, D);
        auto measured_aA = measure(output_aAB, gt.Id(D * D), {0, 1}, D); // measure on aA
        std::size_t m = std::get<0>(measured_aA); // measurement result
        auto midx = n2multiidx(m, {D, D});
        std::cout << ">> Alice's measurement result: ";
        std::cout << m << " -> " << disp(midx, " ") << std::endl;
        std::cout << ">> Alice's measurement probabilities: ";
        std::cout << disp(std::get<1>(measured_aA), " ") << std::endl;
        // conditional result on B before correction
        cmat output_m_B = std::get<2>(measured_aA)[m];
        cmat correction_B = powm(gt.Zd(D), midx[0]) * powm(
            adjoint(gt.Xd(D)), midx[1]); // correction operator
        // apply correction on B
        std::cout << ">> Bob must apply the correction operator Z^" << midx[0] << " X^" << D - midx[1] <<
            std::endl;
        cmat rho_B = correction_B * output_m_B * adjoint(correction_B);
    }
}
```

```

std::cout << ">> Bob's final state (after correction): " << std::endl;
std::cout << disp(rho_B) << std::endl;
// verification
std::cout << ">> Norm difference: " << norm(rho_B - prj(psi_a)) << std::endl;
}

// Qudit dense coding
{
    std::size_t D = 3; // size of the system
    std::cout << std::endl << "**** Qudit dense coding, D = " << D << " ****" << std::endl;
    ket mes_AB = ket::Zero(D * D); // maximally entangled state resource
    for (std::size_t i = 0; i < D; i++)
        mes_AB += mket({i, i}, D);
    mes_AB /= std::sqrt((double) D);
    // circuit that measures in the qudit Bell basis
    cmat Bell_AB = adjoint(gt.CTRL(gt.Xd(D), {0}, {1}, 2, D) *
kron(gt.Fd(D), gt.Id(D)));
    // equal probabilities of choosing a message
    std::uniform_int_distribution<std::size_t> uid(0, D * D - 1);
    std::size_t m_A = uid(rdevs._rng); // sample, obtain the message index
    auto midx = n2multiidx(m_A, {D, D});
    std::cout << ">> Alice sent: " << m_A << " -> ";
    std::cout << disp(midx, " ") << std::endl;
    // Alice's operation
    cmat U_A = powm(gt.Zd(D), midx[0]) * powm(adjoint(
gt.Xd(D)), midx[1]);
    // Alice encodes the message
    ket psi_AB = apply(mes_AB, U_A, {0}, D);
    // Bob measures the joint system in the qudit Bell basis
    psi_AB = apply(psi_AB, Bell_AB, {0, 1}, D);
    auto measured = measure(psi_AB, gt.Id(D * D));
    std::cout << ">> Bob's measurement probabilities: ";
    std::cout << disp(std::get<1>(measured), " ") << std::endl;
    // Bob samples according to the measurement probabilities
    std::size_t m_B = std::get<0>(measured);
    std::cout << ">> Bob received: ";
    std::cout << m_B << " -> " << disp(n2multiidx(m_B, {D, D}), " ") << std::endl;
}

// Grover's search algorithm, we time it
{
    Timer t; // set a timer
    std::size_t n = 4; // number of qubits
    std::cout << std::endl << "**** Grover on n = " << n << " qubits ****" << std::endl;
    std::vector<std::size_t> dims(n, 2); // local dimensions
    std::size_t N = std::pow(2, n); // number of elements in the database
    std::cout << ">> Database size: " << N << std::endl;
    // mark an element randomly
    std::uniform_int_distribution<std::size_t> uid(0, N - 1);
    std::size_t marked = uid(rdevs._rng);
    std::cout << ">> Marked state: " << marked << " -> ";
    std::cout << disp(n2multiidx(marked, dims), " ") << std::endl;
    ket psi = mket(n2multiidx(0, dims)); // computational  $|0\rangle^{\otimes n}$ 
    psi = (kronpow(gt.H, n) * psi).eval(); // apply  $H^{\otimes n}$ , no aliasing
    cmat G = 2 * prj(psi) - gt.Id(N); // Diffusion operator
    // number of queries
    std::size_t nqueries = std::ceil(pi * std::sqrt(N) / 4.);
    std::cout << ">> We run " << nqueries << " queries" << std::endl;
    for (std::size_t i = 0; i < nqueries; i++)
    {
        psi(marked) = -psi(marked); // apply the oracle first, no aliasing
        psi = (G * psi).eval(); // then the diffusion operator, no aliasing
    }
    // we now measure the state in the computational basis
    auto measured = measure(psi, gt.Id(N));
    std::cout << ">> Probability of the marked state: " << std::get<1>(measured)[marked] << std::endl;
    std::cout << ">> Probability of all results: ";
    std::cout << disp(std::get<1>(measured), " ") << std::endl;
    std::cout << ">> Let's sample..." << std::endl;
    std::size_t result = std::get<0>(measured);
    if (result == marked)
        std::cout << ">> Hooray, we obtained the correct result: ";
    else
        std::cout << ">> Not there yet... we obtained: ";
    std::cout << result << " -> ";
    std::cout << disp(n2multiidx(result, dims), " ") << std::endl;
    // stop the timer and display it
    std::cout << ">> It took " << t.toc() << " seconds to simulate Grover on " << n << " qubits." <<
std::endl;
}

// Entanglement
{
    std::cout << std::endl << "**** Entanglement ****" << std::endl;
    cmat rho = 0.2 * st.pb00 + 0.8 * st.pb11;
    std::cout << ">> rho: " << std::endl;
    std::cout << disp(rho) << std::endl;
}

```

```

std::cout << ">> Concurrence of rho: " << concurrence(rho) << std::endl;
std::cout << ">> Negativity of rho: " << negativity(rho, {2, 2}) << std::endl;
std::cout << ">> Logarithmic negativity of rho: " << lognegativity(rho, {2, 2}) <<
std::endl;
ket psi = 0.8 * mket({0, 0}) + 0.6 * mket({1, 1});
// apply some local random unitaries
psi = kron(randU(2), randU(2)) * psi;
std::cout << ">> psi: " << std::endl;
std::cout << disp(psi) << std::endl;
std::cout << ">> Entanglement of psi: " << entanglement(psi, {2, 2}) << std::endl;
std::cout << ">> Concurrence of psi: " << concurrence(prj(psi)) << std::endl;
std::cout << ">> G-Concurrence of psi: " << gconcurrence(psi) << std::endl;
std::cout << ">> Schmidt coefficients of psi: " << std::endl;
std::cout << disp(schmidtcoeff(psi, {2, 2})) << std::endl;
std::cout << ">> Schmidt probabilities of psi: " << std::endl;
std::cout << disp(schmidtprob(psi, {2, 2})) << std::endl;
cmat U = schmidtU(psi, {2, 2});
cmat V = schmidtV(psi, {2, 2});
std::cout << ">> Schmidt vectors on Alice's side: " << std::endl;
std::cout << disp(U) << std::endl;
std::cout << ">> Schmidt vectors on Bob's side: " << std::endl;
std::cout << disp(V) << std::endl;
std::cout << ">> State psi in the Schmidt basis: " << std::endl;
std::cout << disp(adjoint(kron(U, V)) * psi) << std::endl;
// reconstructed state
ket psi_from_schmidt = schmidtcoeff(psi, {2, 2})(0) *
kron(U.col(0), V.col(0))
+ schmidtcoeff(psi, {2, 2})(1) * kron(U.col(1), V.col(1));
std::cout << ">> State psi reconstructed from the Schmidt decomposition: " << std::endl;
std::cout << disp(psi_from_schmidt) << std::endl;
// verification
std::cout << ">> Norm difference: " << norm(psi - psi_from_schmidt) << std::endl;
}

// Quantum error correcting codes
{
std::cout << std::endl << "**** Quantum error correcting codes ****" << std::endl;
ket a0 = codes.codeword(Codes::Type::FIVE_QUBIT, 0);
ket a1 = codes.codeword(Codes::Type::FIVE_QUBIT, 1);
ket b0 = codes.codeword(Codes::Type::SEVEN_QUBIT_STEANE
, 0);
ket b1 = codes.codeword(Codes::Type::SEVEN_QUBIT_STEANE
, 1);
ket c0 = codes.codeword(Codes::Type::NINE_QUBIT_SHOR, 0
);
ket c1 = codes.codeword(Codes::Type::NINE_QUBIT_SHOR, 1
);
std::cout << ">> [[5, 1, 3]] Five qubit code. ";
std::cout << "Checking codeword orthogonality." << std::endl;
std::cout << ">> |<0L|1L>| = ";
std::cout << disp(adjoint(a0) * a1) << std::endl;
std::cout << ">> [[7, 1, 3]] Seven qubit Steane code. ";
std::cout << "Checking codeword orthogonality." << std::endl;
std::cout << ">> |<0L|1L>| = ";
std::cout << disp(adjoint(b0) * b1) << std::endl;
std::cout << ">> [[9, 1, 3]] Nine qubit Shor code. ";
std::cout << "Checking codeword orthogonality." << std::endl;
std::cout << ">> |<0L|1L>| = ";
std::cout << disp(adjoint(c0) * c1) << std::endl;
}

// Timing tests
{
std::cout << std::endl << "**** Timing tests ****" << std::endl;

std::size_t n = 12; // number of qubits
std::size_t N = std::pow(2, n);
std::vector<std::size_t> dims(n, 2); // local dimensions
std::cout << ">> n = " << n << " qubits, matrix size " << N << " x " << N << "." << std::endl;
cmat randcmat = cmat::Random(N, N);

// ptrace
std::cout << std::endl << "**** qpp::ptrace() timing ****" << std::endl;
std::vector<std::size_t> subsys_ptrace = {0};
std::cout << ">> Subsystem(s): ";
std::cout << disp(subsys_ptrace, ", ") << std::endl;
Timer t;
ptrace(randcmat, subsys_ptrace, dims);
std::cout << ">> It took " << t.toc() << " seconds." << std::endl;

// ptranspose
std::cout << std::endl << "**** qpp::ptranspose() timing ****" << std::endl;
std::vector<std::size_t> subsys_ptranspose; // partially transpose n-1 subsystems
for (std::size_t i = 0; i < n - 1; i++)
subsys_ptranspose.push_back(i);
std::cout << ">> Subsystem(s): ";
std::cout << disp(subsys_ptranspose, ", ") << std::endl;
}

```

```
t.tic();
ptranspose(randcmat, subsys_ptranspose, dims);
std::cout << ">> It took " << t.toc() << " seconds." << std::endl;

// syspermute
std::cout << std::endl << "**** qpp::syspermute() timing ****" << std::endl;
std::vector<std::size_t> perm; // left-shift all subsystems by 1
for (std::size_t i = 0; i < n; i++)
    perm.push_back((i + 1) % n);
std::cout << ">> Subsystem(s): ";
std::cout << disp(perm, ", ") << std::endl;
t.tic();
syspermute(randcmat, perm, dims);
std::cout << ">> It took " << t.toc() << " seconds." << std::endl;
}
}
```


Chapter 2

Namespace Index

2.1 Namespace List

Here is a list of all namespaces with brief descriptions:

qpp	13
qpp::experimental	60
qpp::internal	60

Chapter 3

Hierarchical Index

3.1 Class Hierarchy

This inheritance list is sorted roughly, but not completely, alphabetically:

std::exception	
qpp::Exception	65
qpp::internal::IOManipEigen	76
qpp::internal::IOManipPointer< PointerType >	77
qpp::internal::IOManipRange< InputIterator >	78
qpp::internal::Singleton< T >	82
qpp::internal::Singleton< const Codes >	82
qpp::Codes	63
qpp::internal::Singleton< const Gates >	82
qpp::Gates	69
qpp::internal::Singleton< const Init >	82
qpp::Init	74
qpp::internal::Singleton< const States >	82
qpp::States	83
qpp::internal::Singleton< RandomDevices >	82
qpp::RandomDevices	80
qpp::Timer	87

Chapter 4

Class Index

4.1 Class List

Here are the classes, structs, unions and interfaces with brief descriptions:

qpp::Codes	Const Singleton class that defines quantum error correcting codes	63
qpp::Exception	Generates custom exceptions, used when validating function parameters	65
qpp::Gates	Const Singleton class that implements most commonly used gates	69
qpp::Init	Const Singleton class that performs additional initializations/cleanups	74
qpp::internal::IOManipEigen	76
qpp::internal::IOManipPointer< PointerType >	77
qpp::internal::IOManipRange< InputIterator >	78
qpp::RandomDevices	Singleton class that manages the source of randomness in the library	80
qpp::internal::Singleton< T >	Singleton policy class, used internally to implement the singleton pattern via CRTP (Curiously recurring template pattern)	82
qpp::States	Const Singleton class that implements most commonly used states	83
qpp::Timer	Measures time	87

Chapter 5

File Index

5.1 File List

Here is a list of all files with brief descriptions:

include/	constants.h	96
include/	entanglement.h	97
include/	entropies.h	98
include/	functions.h	99
include/	input_output.h	103
include/	instruments.h	104
include/	number_theory.h	107
include/	operations.h	108
include/	qpp.h	110
include/	random.h	111
include/	types.h	112
include/classes/	codes.h	91
include/classes/	exception.h	92
include/classes/	gates.h	92
include/classes/	init.h	93
include/classes/	random_devices.h	93
include/classes/	singleton.h	94
include/classes/	states.h	95
include/classes/	timer.h	95
include/experimental/	test.h	98
include/internal/	functions.h	102
include/internal/classes/	iomanip.h	106
include/MATLAB/	matlab.h	106

Chapter 6

Namespace Documentation

6.1 qpp Namespace Reference

Namespaces

- [experimental](#)
- [internal](#)

Classes

- class [Codes](#)
const Singleton class that defines quantum error correcting codes
- class [Exception](#)
Generates custom exceptions, used when validating function parameters.
- class [Gates](#)
const Singleton class that implements most commonly used gates
- class [Init](#)
const Singleton class that performs additional initializations/cleanups
- class [RandomDevices](#)
Singleton class that manages the source of randomness in the library.
- class [States](#)
const Singleton class that implements most commonly used states
- class [Timer](#)
Measures time.

Typedefs

- using [cplx](#) = std::complex< double >
Complex number in double precision.
- template<typename Scalar >
using [DynMat](#) = Eigen::Matrix< Scalar, Eigen::Dynamic, Eigen::Dynamic >
Dynamic Eigen matrix over the field specified by Scalar.
- template<typename Scalar >
using [DynColVect](#) = Eigen::Matrix< Scalar, Eigen::Dynamic, 1 >
Dynamic Eigen column vector over the field specified by Scalar.
- template<typename Scalar >
using [DynRowVect](#) = Eigen::Matrix< Scalar, 1, Eigen::Dynamic >

- *Dynamic Eigen row vector over the field specified by Scalar.*
using `ket = DynColVect< cplx >`
Complex (double precision) dynamic Eigen column vector.
- using `bra = DynRowVect< cplx >`
Complex (double precision) dynamic Eigen row vector.
- using `cmat = DynMat< cplx >`
Complex (double precision) dynamic Eigen matrix.
- using `dmat = DynMat< double >`
Real (double precision) dynamic Eigen matrix.

Functions

- `constexpr std::complex< double > operator""_i (unsigned long long int x)`
User-defined literal for complex $i = \sqrt{-1}$ (integer overload)
- `constexpr std::complex< double > operator""_i (long double x)`
User-defined literal for complex $i = \sqrt{-1}$ (real overload)
- `std::complex< double > omega (std::size_t D)`
D-th root of unity.
- `template<typename Derived >`
`DynColVect< cplx > schmidtcoeff (const Eigen::MatrixBase< Derived > &A, const std::vector< std::size_t > &dims)`
Schmidt coefficients of the bi-partite pure state A.
- `template<typename Derived >`
`cmat schmidtU (const Eigen::MatrixBase< Derived > &A, const std::vector< std::size_t > &dims)`
Schmidt basis on Alice's side.
- `template<typename Derived >`
`cmat schmidtV (const Eigen::MatrixBase< Derived > &A, const std::vector< std::size_t > &dims)`
Schmidt basis on Bob's side.
- `template<typename Derived >`
`DynColVect< double > schmidtprob (const Eigen::MatrixBase< Derived > &A, const std::vector< std::size_t > &dims)`
Schmidt probabilities of the bi-partite pure state A.
- `template<typename Derived >`
`double entanglement (const Eigen::MatrixBase< Derived > &A, const std::vector< std::size_t > &dims)`
Entanglement of the bi-partite pure state A.
- `template<typename Derived >`
`double gconcurrence (const Eigen::MatrixBase< Derived > &A)`
G-concurrence of the bi-partite pure state A.
- `template<typename Derived >`
`double negativity (const Eigen::MatrixBase< Derived > &A, const std::vector< std::size_t > &dims)`
Negativity of the bi-partite mixed state A.
- `template<typename Derived >`
`double lognegativity (const Eigen::MatrixBase< Derived > &A, const std::vector< std::size_t > &dims)`
Logarithmic negativity of the bi-partite mixed state A.
- `template<typename Derived >`
`double concurrence (const Eigen::MatrixBase< Derived > &A)`
Wootters concurrence of the bi-partite qubit mixed state A.
- `template<typename Derived >`
`double shannon (const Eigen::MatrixBase< Derived > &A)`
Shannon/von-Neumann entropy of the probability distribution/density matrix A.
- `template<typename Derived >`
`double renyi (const Eigen::MatrixBase< Derived > &A, double alpha)`

- Renyi- α entropy of the probability distribution/density matrix A , for $\alpha \geq 0$.*

 - template<typename Derived >
double **tsallis** (const Eigen::MatrixBase< Derived > &A, double alpha)

Tsallis- α entropy of the probability distribution/density matrix A , for $\alpha \geq 0$.

 - template<typename Derived >
double **qmutualinfo** (const Eigen::MatrixBase< Derived > &A, const std::vector< std::size_t > &subsysA, const std::vector< std::size_t > &subsysB, const std::vector< std::size_t > &dims)

Quantum mutual information between 2 subsystems of a composite system.

 - template<typename Derived >
DynMat< typename Derived::Scalar > **transpose** (const Eigen::MatrixBase< Derived > &A)

Transpose.

 - template<typename Derived >
DynMat< typename Derived::Scalar > **conjugate** (const Eigen::MatrixBase< Derived > &A)

Complex conjugate.

 - template<typename Derived >
DynMat< typename Derived::Scalar > **adjoint** (const Eigen::MatrixBase< Derived > &A)

Adjoint.

 - template<typename Derived >
DynMat< typename Derived::Scalar > **inverse** (const Eigen::MatrixBase< Derived > &A)

Inverse.

 - template<typename Derived >
Derived::Scalar **trace** (const Eigen::MatrixBase< Derived > &A)

Trace.

 - template<typename Derived >
Derived::Scalar **det** (const Eigen::MatrixBase< Derived > &A)

Determinant.

 - template<typename Derived >
Derived::Scalar **logdet** (const Eigen::MatrixBase< Derived > &A)

Logarithm of the determinant.

 - template<typename Derived >
Derived::Scalar **sum** (const Eigen::MatrixBase< Derived > &A)

Element-wise sum of A .

 - template<typename Derived >
Derived::Scalar **prod** (const Eigen::MatrixBase< Derived > &A)

Element-wise product of A .

 - template<typename Derived >
double **norm** (const Eigen::MatrixBase< Derived > &A)

Frobenius norm.

 - template<typename Derived >
DynColVect< cplx > **evals** (const Eigen::MatrixBase< Derived > &A)

Eigenvalues.

 - template<typename Derived >
cmat evecs (const Eigen::MatrixBase< Derived > &A)

Eigenvectors.

 - template<typename Derived >
DynColVect< double > **hevals** (const Eigen::MatrixBase< Derived > &A)

Hermitian eigenvalues.

 - template<typename Derived >
cmat hevecs (const Eigen::MatrixBase< Derived > &A)

Hermitian eigenvectors.

 - template<typename Derived >
DynColVect< double > **svals** (const Eigen::MatrixBase< Derived > &A)

Singular values.

- `template<typename Derived >`
`cmat svdU` (const Eigen::MatrixBase< Derived > &A)
Left singular vectors.
- `template<typename Derived >`
`cmat svdV` (const Eigen::MatrixBase< Derived > &A)
Right singular vectors.
- `template<typename Derived >`
`cmat funm` (const Eigen::MatrixBase< Derived > &A, `cplx`(*f)(const `cplx` &))
Functional calculus $f(A)$
- `template<typename Derived >`
`cmat sqrtm` (const Eigen::MatrixBase< Derived > &A)
Matrix square root.
- `template<typename Derived >`
`cmat absm` (const Eigen::MatrixBase< Derived > &A)
Matrix absolut value.
- `template<typename Derived >`
`cmat expm` (const Eigen::MatrixBase< Derived > &A)
Matrix exponential.
- `template<typename Derived >`
`cmat logm` (const Eigen::MatrixBase< Derived > &A)
Matrix logarithm.
- `template<typename Derived >`
`cmat sinm` (const Eigen::MatrixBase< Derived > &A)
Matrix sin.
- `template<typename Derived >`
`cmat cosm` (const Eigen::MatrixBase< Derived > &A)
Matrix cos.
- `template<typename Derived >`
`cmat spectralpovm` (const Eigen::MatrixBase< Derived > &A, const `cplx` z)
Matrix power.
- `template<typename Derived >`
`DynMat< typename Derived::Scalar > povm` (const Eigen::MatrixBase< Derived > &A, std::size_t n)
Matrix power.
- `template<typename Derived >`
`double Schatten` (const Eigen::MatrixBase< Derived > &A, std::size_t p)
Schatten norm.
- `template<typename OutputScalar , typename Derived >`
`DynMat< OutputScalar > cwise` (const Eigen::MatrixBase< Derived > &A, OutputScalar(*f)(const typename Derived::Scalar &))
Functor.
- `template<typename T >`
`DynMat< typename T::Scalar > kron` (const T &head)
Kronecker product.
- `template<typename T , typename... Args>`
`DynMat< typename T::Scalar > kron` (const T &head, const Args &...tail)
Kronecker product.
- `template<typename Derived >`
`DynMat< typename Derived::Scalar > kron` (const std::vector< Derived > &As)
Kronecker product.
- `template<typename Derived >`
`DynMat< typename Derived::Scalar > kron` (const std::initializer_list< Derived > &As)
Kronecker product.

- `template<typename Derived >`
`DynMat< typename Derived::Scalar > kronpow` (const Eigen::MatrixBase< Derived > &A, std::size_t n)
Kronecker power.
- `template<typename Derived >`
`DynMat< typename Derived::Scalar > reshape` (const Eigen::MatrixBase< Derived > &A, std::size_t rows, std::size_t cols)
Reshape.
- `template<typename Derived1 , typename Derived2 >`
`DynMat< typename Derived1::Scalar > comm` (const Eigen::MatrixBase< Derived1 > &A, const Eigen::MatrixBase< Derived2 > &B)
Commutator.
- `template<typename Derived1 , typename Derived2 >`
`DynMat< typename Derived1::Scalar > anticomm` (const Eigen::MatrixBase< Derived1 > &A, const Eigen::MatrixBase< Derived2 > &B)
Anti-commutator.
- `template<typename Derived >`
`DynMat< typename Derived::Scalar > prj` (const Eigen::MatrixBase< Derived > &V)
Projector.
- `template<typename Derived >`
`DynMat< typename Derived::Scalar > grams` (const std::vector< Derived > &Vs)
Gram-Schmidt orthogonalization.
- `template<typename Derived >`
`DynMat< typename Derived::Scalar > grams` (const std::initializer_list< Derived > &Vs)
Gram-Schmidt orthogonalization.
- `template<typename Derived >`
`DynMat< typename Derived::Scalar > grams` (const Eigen::MatrixBase< Derived > &A)
Gram-Schmidt orthogonalization.
- `std::vector< std::size_t > n2multiidx` (std::size_t n, const std::vector< std::size_t > &dims)
Non-negative integer index to multi-index.
- `std::size_t multiidx2n` (const std::vector< std::size_t > &midx, const std::vector< std::size_t > &dims)
Multi-index to non-negative integer index.
- `ket mket` (const std::vector< std::size_t > &mask, const std::vector< std::size_t > &dims)
Multi-partite qudit ket.
- `ket mket` (const std::vector< std::size_t > &mask, std::size_t d=2)
Multi-partite qudit ket.
- `cmat mprj` (const std::vector< std::size_t > &mask, const std::vector< std::size_t > &dims)
Projector onto multi-partite qudit ket.
- `cmat mprj` (const std::vector< std::size_t > &mask, std::size_t d=2)
Projector onto multi-partite qudit ket.
- `template<typename InputIterator >`
`std::vector< double > abssq` (InputIterator first, InputIterator last)
Computes the absolut values squared of a range of complex numbers.
- `template<typename Derived >`
`std::vector< double > abssq` (const Eigen::MatrixBase< Derived > &V)
Computes the absolut values squared of a column vector.
- `template<typename InputIterator >`
`auto sum` (InputIterator first, InputIterator last) -> typename InputIterator::value_type
Element-wise sum of a range.
- `template<typename InputIterator >`
`auto prod` (InputIterator first, InputIterator last) -> typename InputIterator::value_type
Element-wise product of a range.

- `template<typename Derived >`
`DynColVect< typename`
`Derived::Scalar > rho2pure` (const Eigen::MatrixBase< Derived > &A)
Finds the pure state representation of a matrix proportional to a projector onto a pure state.
- `template<typename Derived >`
`internal::IOManipEigen disp` (const Eigen::MatrixBase< Derived > &A, double chop=qpp::chop)
Eigen expression ostream manipulator.
- `internal::IOManipEigen disp` (cplx z, double chop=qpp::chop)
Complex number ostream manipulator.
- `template<typename InputIterator >`
`internal::IOManipRange`
`< InputIterator > disp` (const InputIterator &first, const InputIterator &last, const std::string &separator, const std::string &start="[", const std::string &end="]")
Range ostream manipulator.
- `template<typename Container >`
`internal::IOManipRange`
`< typename`
`Container::const_iterator > disp` (const Container &c, const std::string &separator, const std::string &start="[", const std::string &end="]")
Standard container ostream manipulator. The container must support std::begin(), std::end() and forward iteration.
- `template<typename PointerType >`
`internal::IOManipPointer`
`< PointerType > disp` (const PointerType *p, std::size_t n, const std::string &separator, const std::string &start="[", const std::string &end="]")
C-style pointer ostream manipulator.
- `template<typename Derived >`
`void save` (const Eigen::MatrixBase< Derived > &A, const std::string &fname)
Saves Eigen expression to a binary file (internal format) in double precision.
- `template<typename Derived >`
`DynMat< typename Derived::Scalar > load` (const std::string &fname)
Loads Eigen matrix from a binary file (internal format) in double precision.
- `template<typename Derived >`
`std::tuple< std::size_t,`
`std::vector< double >`
`, std::vector< cmat > > measure` (const Eigen::MatrixBase< Derived > &A, const std::vector< cmat > &Ks, const std::vector< std::size_t > &subsys, const std::vector< std::size_t > &dims)
Measures the part subsys of the multi-partite state vector or density matrix A using the set of Kraus operators Ks.
- `template<typename Derived >`
`std::tuple< std::size_t,`
`std::vector< double >`
`, std::vector< cmat > > measure` (const Eigen::MatrixBase< Derived > &A, const std::initializer_list< cmat > &Ks, const std::vector< std::size_t > &subsys, const std::vector< std::size_t > &dims)
Measures the part subsys of the multi-partite state vector or density matrix A using the set of Kraus operators Ks.
- `template<typename Derived >`
`std::tuple< std::size_t,`
`std::vector< double >`
`, std::vector< cmat > > measure` (const Eigen::MatrixBase< Derived > &A, const std::vector< cmat > &Ks, const std::vector< std::size_t > &subsys, const std::size_t d=2)
Measures the part subsys of the multi-partite state vector or density matrix A using the set of Kraus operators Ks.
- `template<typename Derived >`
`std::tuple< std::size_t,`
`std::vector< double >`
`, std::vector< cmat > > measure` (const Eigen::MatrixBase< Derived > &A, const std::initializer_list< cmat > &Ks, const std::vector< std::size_t > &subsys, const std::size_t d=2)
Measures the part subsys of the multi-partite state vector or density matrix A using the set of Kraus operators Ks.

- `template<typename Derived >`
`std::tuple< std::size_t,`
`std::vector< double >`
`, std::vector< cmat > > measure` (const Eigen::MatrixBase< Derived > &A, const cmat &U, const std::vector< std::size_t > &subsys, const std::vector< std::size_t > &dims)
- Measures the part subsys of the multi-partite state A in the orthonormal basis specified by the unitary matrix U.*
- `template<typename Derived >`
`std::tuple< std::size_t,`
`std::vector< double >`
`, std::vector< cmat > > measure` (const Eigen::MatrixBase< Derived > &A, const cmat &U, const std::vector< std::size_t > &subsys, const std::size_t d=2)
- Measures the part subsys of the multi-partite state A in the orthonormal basis specified by the unitary matrix U.*
- `template<typename Derived >`
`std::tuple< std::size_t,`
`std::vector< double >`
`, std::vector< cmat > > measure` (const Eigen::MatrixBase< Derived > &A, const std::vector< cmat > &Ks)
- Measures the state A using the set of Kraus operators Ks.*
- `template<typename Derived >`
`std::tuple< std::size_t,`
`std::vector< double >`
`, std::vector< cmat > > measure` (const Eigen::MatrixBase< Derived > &A, const std::initializer_list< cmat > &Ks)
- Measures the state A using the set of Kraus operators Ks.*
- `template<typename Derived >`
`std::tuple< std::size_t,`
`std::vector< double >`
`, std::vector< cmat > > measure` (const Eigen::MatrixBase< Derived > &A, const cmat &U)
- Measures the state A in the orthonormal basis specified by the unitary matrix U.*
- `template<typename Derived >`
`Derived loadMATLABmatrix` (const std::string &mat_file, const std::string &var_name)
- Loads an Eigen dynamic matrix from a MATLAB .mat file, generic version.*
- `template<>`
`dmat loadMATLABmatrix` (const std::string &mat_file, const std::string &var_name)
- Loads an Eigen dynamic matrix from a MATLAB .mat file, specialization for double matrices (qpp::dmat)*
- `template<>`
`cmat loadMATLABmatrix` (const std::string &mat_file, const std::string &var_name)
- Loads an Eigen dynamic matrix from a MATLAB .mat file, specialization for complex matrices (qpp::cmat)*
- `template<typename Derived >`
`void saveMATLABmatrix` (const Eigen::MatrixBase< Derived > &A, const std::string &mat_file, const std::string &var_name, const std::string &mode)
- Saves an Eigen dynamic matrix to a MATLAB .mat file, generic version.*
- `template<>`
`void saveMATLABmatrix` (const Eigen::MatrixBase< dmat > &A, const std::string &mat_file, const std::string &var_name, const std::string &mode)
- Saves an Eigen dynamic matrix to a MATLAB .mat file, specialization for double matrices (qpp::dmat)*
- `template<>`
`void saveMATLABmatrix` (const Eigen::MatrixBase< cmat > &A, const std::string &mat_file, const std::string &var_name, const std::string &mode)
- Saves an Eigen dynamic matrix to a MATLAB .mat file, specialization for complex matrices (qpp::cmat)*
- `std::vector< int > x2confrac` (double x, std::size_t n, std::size_t cut=1e5)
- Simple continued fraction expansion.*
- `double confrac2x` (const std::vector< int > &cf, std::size_t n)
- Real representation of a simple continued fraction.*
- `double confrac2x` (const std::vector< int > &cf)

- Real representation of a simple continued fraction.*

 - `std::size_t gcd (std::size_t m, std::size_t n)`

Greatest common divisor of two non-negative integers.

 - `std::size_t gcd (const std::vector< std::size_t > &ns)`

Greatest common divisor of a list of non-negative integers.

 - `std::size_t lcm (std::size_t m, std::size_t n)`

Least common multiple of two positive integers.

 - `std::size_t lcm (const std::vector< std::size_t > &ns)`

Least common multiple of a list of positive integers.

 - `std::vector< std::size_t > invperm (const std::vector< std::size_t > &perm)`

Inverse permutation.

 - `std::vector< std::size_t > compperm (const std::vector< std::size_t > &perm, const std::vector< std::size_t > &sigma)`

Compose permutations.

 - `template<typename Derived1, typename Derived2 > DynMat< typename Derived1::Scalar > applyCTRL (const Eigen::MatrixBase< Derived1 > &state, const Eigen::MatrixBase< Derived2 > &A, const std::vector< std::size_t > &ctrl, const std::vector< std::size_t > &subsys, const std::vector< std::size_t > &dims)`

Applies the controlled-gate A to the part subsys of the multi-partite state vector or density matrix state.

 - `template<typename Derived1, typename Derived2 > DynMat< typename Derived1::Scalar > applyCTRL (const Eigen::MatrixBase< Derived1 > &state, const Eigen::MatrixBase< Derived2 > &A, const std::vector< std::size_t > &ctrl, const std::vector< std::size_t > &subsys, std::size_t d=2)`

Applies the controlled-gate A to the part subsys of the multi-partite state vector or density matrix state.

 - `template<typename Derived1, typename Derived2 > DynMat< typename Derived1::Scalar > apply (const Eigen::MatrixBase< Derived1 > &state, const Eigen::MatrixBase< Derived2 > &A, const std::vector< std::size_t > &subsys, const std::vector< std::size_t > &dims)`

Applies the gate A to the part subsys of the multi-partite state vector or density matrix state.

 - `template<typename Derived1, typename Derived2 > DynMat< typename Derived1::Scalar > apply (const Eigen::MatrixBase< Derived1 > &state, const Eigen::MatrixBase< Derived2 > &A, const std::vector< std::size_t > &subsys, std::size_t d=2)`

Applies the gate A to the part subsys of the multi-partite state vector or density matrix state.

 - `template<typename Derived > cmat channel (const Eigen::MatrixBase< Derived > &rho, const std::vector< cmat > &Ks)`

Applies the channel specified by the set of Kraus operators Ks to the density matrix rho.

 - `template<typename Derived > cmat channel (const Eigen::MatrixBase< Derived > &rho, const std::vector< cmat > &Ks, const std::vector< std::size_t > &subsys, const std::vector< std::size_t > &dims)`

Applies the channel specified by the set of Kraus operators Ks to the part subsys of the multi-partite density matrix rho.

 - `template<typename Derived > cmat channel (const Eigen::MatrixBase< Derived > &rho, const std::vector< cmat > &Ks, const std::vector< std::size_t > &subsys, std::size_t d=2)`

Applies the channel specified by the set of Kraus operators Ks to the part subsys of the multi-partite density matrix rho.

 - `cmat super (const std::vector< cmat > &Ks)`

Superoperator matrix representation.

 - `cmat choi (const std::vector< cmat > &Ks)`

Choi matrix representation.

 - `std::vector< cmat > choi2kraus (const cmat &A)`

Extracts orthogonal Kraus operators from Choi matrix.

- `template<typename Derived >`
`DynMat< typename Derived::Scalar > ptrace1` (const Eigen::MatrixBase< Derived > &A, const std::vector< std::size_t > &dims)
Partial trace.
- `template<typename Derived >`
`DynMat< typename Derived::Scalar > ptrace2` (const Eigen::MatrixBase< Derived > &A, const std::vector< std::size_t > &dims)
Partial trace.
- `template<typename Derived >`
`DynMat< typename Derived::Scalar > ptrace` (const Eigen::MatrixBase< Derived > &A, const std::vector< std::size_t > &subsys, const std::vector< std::size_t > &dims)
Partial trace.
- `template<typename Derived >`
`DynMat< typename Derived::Scalar > ptranspose` (const Eigen::MatrixBase< Derived > &A, const std::vector< std::size_t > &subsys, const std::vector< std::size_t > &dims)
Partial transpose.
- `template<typename Derived >`
`DynMat< typename Derived::Scalar > syspermute` (const Eigen::MatrixBase< Derived > &A, const std::vector< std::size_t > &perm, const std::vector< std::size_t > &dims)
System permutation.
- `template<typename Derived >`
`Derived rand` (std::size_t rows, std::size_t cols, double a=0, double b=1)
Generates a random matrix with entries uniformly distributed in the interval [a, b]
- `template<>`
`dmat rand` (std::size_t rows, std::size_t cols, double a, double b)
Generates a random real matrix with entries uniformly distributed in the interval [a, b], specialization for double matrices ([qpp::dmat](#))
- `template<>`
`cmat rand` (std::size_t rows, std::size_t cols, double a, double b)
Generates a random complex matrix with entries (both real and imaginary) uniformly distributed in the interval [a, b], specialization for complex matrices ([qpp::cmat](#))
- `double rand` (double a=0, double b=1)
Generates a random real number uniformly distributed in the interval [a, b]
- `int randint` (int a=std::numeric_limits< int >::min(), int b=std::numeric_limits< int >::max())
Generates a random integer (int) uniformly distributed in the interval [a, b].
- `template<typename Derived >`
`Derived randn` (std::size_t rows, std::size_t cols, double mean=0, double sigma=1)
Generates a random matrix with entries normally distributed in $N(\text{mean}, \text{sigma})$
- `template<>`
`dmat randn` (std::size_t rows, std::size_t cols, double mean, double sigma)
Generates a random real matrix with entries normally distributed in $N(\text{mean}, \text{sigma})$, specialization for double matrices ([qpp::dmat](#))
- `template<>`
`cmat randn` (std::size_t rows, std::size_t cols, double mean, double sigma)
Generates a random complex matrix with entries (both real and imaginary) normally distributed in $N(\text{mean}, \text{sigma})$, specialization for complex matrices ([qpp::cmat](#))
- `double randn` (double mean=0, double sigma=1)
Generates a random real number (double) normally distributed in $N(\text{mean}, \text{sigma})$
- `cmat randU` (std::size_t D)
Generates a random unitary matrix.
- `cmat randV` (std::size_t Din, std::size_t Dout)
Generates a random isometry matrix.
- `std::vector< cmat > randkraus` (std::size_t N, std::size_t D)

- Generates a set of random Kraus operators.
- `cmat randH` (`std::size_t D`)
Generates a random Hermitian matrix.
- `ket randket` (`std::size_t D`)
Generates a random normalized ket (pure state vector)
- `cmat randrho` (`std::size_t D`)
Generates a random density matrix.
- `std::vector< std::size_t > randperm` (`std::size_t n`)
Generates a random uniformly distributed permutation.

Variables

- `constexpr double chop` = 1e-10
Used in `qpp::disp()` and `qpp::displn()` for setting to zero numbers that have their absolute value smaller than `qpp::ct←::chop`.
- `constexpr double eps` = 1e-12
Used to decide whether a number or expression in double precision is zero or not.
- `constexpr std::size_t maxn` = 64
Maximum number of qubits.
- `constexpr double pi` = 3.141592653589793238462643383279502884
 π
- `constexpr double ee` = 2.718281828459045235360287471352662497
Base of natural logarithm, e .
- `constexpr std::size_t infy` = -1
Used to denote infinity.
- `const Init & init` = `Init::get_instance()`
`qpp::Init` const Singleton
- `const Codes & codes` = `Codes::get_instance()`
`qpp::Codes` const Singleton
- `const Gates & gt` = `Gates::get_instance()`
`qpp::Gates` const Singleton
- `const States & st` = `States::get_instance()`
`qpp::States` const Singleton
- `RandomDevices & rdevs` = `RandomDevices::get_instance()`
`qpp::RandomDevices` Singleton

6.1.1 Typedef Documentation

6.1.1.1 using `qpp::bra` = `typedef DynRowVect<cplx>`

Complex (double precision) dynamic Eigen row vector.

6.1.1.2 using `qpp::cmat` = `typedef DynMat<cplx>`

Complex (double precision) dynamic Eigen matrix.

6.1.1.3 using `qpp::cplx` = `typedef std::complex<double>`

Complex number in double precision.

6.1.1.4 using qpp::dmat = typedef DynMat<double>

Real (double precision) dynamic Eigen matrix.

6.1.1.5 template<typename Scalar > using qpp::DynColVect = typedef Eigen::Matrix<Scalar, Eigen::Dynamic, 1>

Dynamic Eigen column vector over the field specified by *Scalar*.

Example:

```
auto colvect = DynColVect<float>(2); // type of colvect is Eigen::Matrix<float, Eigen::Dynamic, 1>
```

6.1.1.6 template<typename Scalar > using qpp::DynMat = typedef Eigen::Matrix<Scalar, Eigen::Dynamic, Eigen::Dynamic>

Dynamic Eigen matrix over the field specified by *Scalar*.

Example:

```
auto mat = DynMat<float>(2,3); // type of mat is Eigen::Matrix<float, Eigen::Dynamic, Eigen::Dynamic>
```

6.1.1.7 template<typename Scalar > using qpp::DynRowVect = typedef Eigen::Matrix<Scalar, 1, Eigen::Dynamic>

Dynamic Eigen row vector over the field specified by *Scalar*.

Example:

```
auto rowvect = DynRowVect<float>(3); // type of rowvect is Eigen::Matrix<float, 1, Eigen::Dynamic>
```

6.1.1.8 using qpp::ket = typedef DynColVect<cplx>

Complex (double precision) dynamic Eigen column vector.

6.1.2 Function Documentation**6.1.2.1 template<typename Derived > cmat qpp::absm (const Eigen::MatrixBase< Derived > & A)**

Matrix absolut value.

Parameters

<i>A</i>	Eigen expression
----------	------------------

Returns

Matrix absolut value of *A*

6.1.2.2 template<typename InputIterator > std::vector<double> qpp::abssq (InputIterator first, InputIterator last)

Computes the absolut values squared of a range of complex numbers.

Parameters

<i>first</i>	Iterator to the first element of the range
<i>last</i>	Iterator to the last element of the range

Returns

Real vector consisting of the range's absolut values squared

6.1.2.3 `template<typename Derived > std::vector<double> qpp::abssq (const Eigen::MatrixBase< Derived > & V)`

Computes the absolut values squared of a column vector.

Parameters

<i>V</i>	Eigen expression
----------	------------------

Returns

Real vector consisting of the absolut values squared

6.1.2.4 `template<typename Derived > DynMat<typename Derived::Scalar> qpp::adjoint (const Eigen::MatrixBase< Derived > & A)`

Adjoint.

Parameters

<i>A</i>	Eigen expression
----------	------------------

Returns

Adjoint (Hermitian conjugate) of *A*, as a dynamic matrix over the same scalar field as *A*

6.1.2.5 `template<typename Derived1 , typename Derived2 > DynMat<typename Derived1::Scalar> qpp::anticomm (const Eigen::MatrixBase< Derived1 > & A, const Eigen::MatrixBase< Derived2 > & B)`

Anti-commutator.

Anti-commutator $\{A, B\} = AB + BA$. Both *A* and *B* must be Eigen expressions over the same scalar field.

Parameters

<i>A</i>	Eigen expression
<i>B</i>	Eigen expression

Returns

Anti-commutator $AB + BA$, as a dynamic matrix over the same scalar field as *A*

6.1.2.6 `template<typename Derived1 , typename Derived2 > DynMat<typename Derived1::Scalar> qpp::apply (const Eigen::MatrixBase< Derived1 > & state, const Eigen::MatrixBase< Derived2 > & A, const std::vector< std::size_t > & subsys, const std::vector< std::size_t > & dims)`

Applies the gate *A* to the part *subsys* of the multi-partite state vector or density matrix *state*.

Note

The dimension of the gate *A* must match the dimension of *subsys*

Parameters

<i>state</i>	Eigen expression
<i>A</i>	Eigen expression
<i>subsys</i>	Subsystem indexes where the gate <i>A</i> is applied
<i>dims</i>	Dimensions of the multi-partite system

Returns

Gate *A* applied to the part *subsys* of *state*

6.1.2.7 `template<typename Derived1 , typename Derived2 > DynMat<typename Derived1::Scalar> qpp::apply (const Eigen::MatrixBase< Derived1 > & state, const Eigen::MatrixBase< Derived2 > & A, const std::vector< std::size_t > & subsys, std::size_t d = 2)`

Applies the gate *A* to the part *subsys* of the multi-partite state vector or density matrix *state*.

Note

The dimension of the gate *A* must match the dimension of *subsys*

Parameters

<i>state</i>	Eigen expression
<i>A</i>	Eigen expression
<i>subsys</i>	Subsystem indexes where the gate <i>A</i> is applied
<i>d</i>	Subsystem dimensions

Returns

Gate *A* applied to the part *subsys* of *state*

6.1.2.8 `template<typename Derived1 , typename Derived2 > DynMat<typename Derived1::Scalar> qpp::applyCTRL (const Eigen::MatrixBase< Derived1 > & state, const Eigen::MatrixBase< Derived2 > & A, const std::vector< std::size_t > & ctrl, const std::vector< std::size_t > & subsys, const std::vector< std::size_t > & dims)`

Applies the controlled-gate *A* to the part *subsys* of the multi-partite state vector or density matrix *state*.

Note

The dimension of the gate *A* must match the dimension of *subsys*. Also, all control subsystems in *ctrl* must have the same dimension.

Parameters

<i>state</i>	Eigen expression
<i>A</i>	Eigen expression
<i>ctrl</i>	Control subsystem indexes
<i>subsys</i>	Subsystem indexes where the gate <i>A</i> is applied
<i>dims</i>	Dimensions of the multi-partite system

Returns

CTRL-A gate applied to the part *subsys* of *state*

6.1.2.9 `template<typename Derived1 , typename Derived2 > DynMat<typename Derived1::Scalar> qpp::applyCTRL (const Eigen::MatrixBase< Derived1 > & state, const Eigen::MatrixBase< Derived2 > & A, const std::vector< std::size_t > & ctrl, const std::vector< std::size_t > & subsys, std::size_t d = 2)`

Applies the controlled-gate A to the part $subsys$ of the multi-partite state vector or density matrix $state$.

Note

The dimension of the gate A must match the dimension of $subsys$

Parameters

$state$	Eigen expression
A	Eigen expression
$ctrl$	Control subsystem indexes
$subsys$	Subsystem indexes where the gate A is applied
d	Subsystem dimensions

Returns

CTRL-A gate applied to the part $subsys$ of $state$

6.1.2.10 `template<typename Derived > cmat qpp::channel (const Eigen::MatrixBase< Derived > & rho, const std::vector< cmat > & Ks)`

Applies the channel specified by the set of Kraus operators Ks to the density matrix rho .

Parameters

rho	Eigen expression
Ks	Set of Kraus operators

Returns

Output density matrix after the action of the channel

6.1.2.11 `template<typename Derived > cmat qpp::channel (const Eigen::MatrixBase< Derived > & rho, const std::vector< cmat > & Ks, const std::vector< std::size_t > & subsys, const std::vector< std::size_t > & dims)`

Applies the channel specified by the set of Kraus operators Ks to the part $subsys$ of the multi-partite density matrix rho .

Parameters

rho	Eigen expression
Ks	Set of Kraus operators
$subsys$	Subsystem indexes where the Kraus operators Ks are applied
$dims$	Dimensions of the multi-partite system

Returns

Output density matrix after the action of the channel

6.1.2.12 `template<typename Derived > cmat qpp::channel (const Eigen::MatrixBase< Derived > & rho, const std::vector< cmat > & Ks, const std::vector< std::size_t > & subsys, std::size_t d = 2)`

Applies the channel specified by the set of Kraus operators Ks to the part $subsys$ of the multi-partite density matrix rho .

Parameters

<i>rho</i>	Eigen expression
<i>Ks</i>	Set of Kraus operators
<i>subsys</i>	Subsystem indexes where the Kraus operators <i>Ks</i> are applied
<i>d</i>	Subsystem dimensions

Returns

Output density matrix after the action of the channel

6.1.2.13 `cmat qpp::choi (const std::vector< cmat > & Ks)`

Choi matrix representation.

Constructs the Choi matrix of the channel specified by the set of Kraus operators *Ks* in the standard operator basis $\{|i\rangle\langle j|\}$ ordered in lexicographical order, i.e. $|0\rangle\langle 0|$, $|0\rangle\langle 1|$ etc.

Note

The superoperator matrix *S* and the Choi matrix *C* are related by $S_{ab,mn} = C_{ma,nb}$

Parameters

<i>Ks</i>	Set of Kraus operators
-----------	------------------------

Returns

Choi matrix representation

6.1.2.14 `std::vector<cmat> qpp::choi2kraus (const cmat & A)`

Extracts orthogonal Kraus operators from Choi matrix.

Extracts a set of orthogonal (under Hilbert-Schmidt operator norm) Kraus operators from the Choi representation *A* of the channel

Note

The Kraus operators satisfy $Tr(K_i^\dagger K_j) = \delta_{ij}$ for all $i \neq j$

Parameters

<i>A</i>	Choi matrix
----------	-------------

Returns

Set of Kraus operators

6.1.2.15 `template<typename Derived1, typename Derived2> DynMat<typename Derived1::Scalar> qpp::comm (const Eigen::MatrixBase< Derived1 > & A, const Eigen::MatrixBase< Derived2 > & B)`

Commutator.

Commutator $[A, B] = AB - BA$. Both *A* and *B* must be Eigen expressions over the same scalar field.

Parameters

A	Eigen expression
B	Eigen expression

Returns

Commutator $AB - BA$, as a dynamic matrix over the same scalar field as A

6.1.2.16 `std::vector<std::size_t> qpp::compperm (const std::vector< std::size_t > & perm, const std::vector< std::size_t > & sigma)`

Compose permutations.

Parameters

$perm$	Permutation
$sigma$	Permutation

Returns

Composition of the permutations $perm \circ sigma = perm(sigma)$

6.1.2.17 `template<typename Derived > double qpp::concurrence (const Eigen::MatrixBase< Derived > & A)`

Wootters concurrence of the bi-partite qubit mixed state A .

Parameters

A	Eigen expression
-----	------------------

Returns

Wootters concurrence

6.1.2.18 `template<typename Derived > DynMat<typename Derived::Scalar> qpp::conjugate (const Eigen::MatrixBase< Derived > & A)`

Complex conjugate.

Parameters

A	Eigen expression
-----	------------------

Returns

Complex conjugate of A , as a dynamic matrix over the same scalar field as A

6.1.2.19 `double qpp::contfrac2x (const std::vector< int > & cf, std::size_t n)`

Real representation of a simple continued fraction.

Parameters

<i>cf</i>	Integer vector containing the simple continued fraction expansion
<i>n</i>	Number of terms considered in the continued fraction expansion. If <i>n</i> is greater than the size of <i>cf</i> , then all terms in <i>cf</i> are considered.

Returns

Real representation of the simple continued fraction

6.1.2.20 `double qpp::contfrac2x (const std::vector< int > & cf)`

Real representation of a simple continued fraction.

Parameters

<i>cf</i>	Integer vector containing the simple continued fraction expansion
-----------	---

Returns

Real representation of the simple continued fraction

6.1.2.21 `template<typename Derived > cmat qpp::cosm (const Eigen::MatrixBase< Derived > & A)`

Matrix cos.

Parameters

<i>A</i>	Eigen expression
----------	------------------

Returns

Matrix cosine of *A*

6.1.2.22 `template<typename OutputScalar , typename Derived > DynMat<OutputScalar> qpp::cwise (const Eigen::MatrixBase< Derived > & A, OutputScalar (*)(const typename Derived::Scalar &) f)`

Functor.

Parameters

<i>A</i>	Eigen expression
<i>f</i>	Pointer-to-function from scalars of <i>A</i> to <i>OutputScalar</i>

Returns

Component-wise $f(A)$, as a dynamic matrix over the *OutputScalar* scalar field

6.1.2.23 `template<typename Derived > Derived::Scalar qpp::det (const Eigen::MatrixBase< Derived > & A)`

Determinant.

Parameters

<i>A</i>	Eigen expression
----------	------------------

Returns

Determinant of *A*, as a scalar in the same scalar field as *A*. Returns $\pm\infty$ when the determinant overflows/underflows.

6.1.2.24 `template<typename Derived> internal::IOManipEigen qpp::disp (const Eigen::MatrixBase< Derived> & A, double chop = qpp::chop)`

Eigen expression ostream manipulator.

Parameters

<i>A</i>	Eigen expression
<i>chop</i>	Set to zero the elements smaller in absolute value than <i>chop</i>

Returns

Instance of `qpp::internal::internal::IOManipEigen`

6.1.2.25 `internal::IOManipEigen qpp::disp (cplx z, double chop = qpp::chop)`

Complex number ostream manipulator.

Parameters

<i>z</i>	Complex number (or any other type implicitly cast-able to <code>std::complex<double></code>)
<i>chop</i>	Set to zero the elements smaller in absolute value than <i>chop</i>

Returns

Instance of `qpp::internal::internal::IOManipEigen`

6.1.2.26 `template<typename InputIterator> internal::IOManipRange<InputIterator> qpp::disp (const InputIterator & first, const InputIterator & last, const std::string & separator, const std::string & start = " [", const std::string & end = "] ")`

Range ostream manipulator.

Parameters

<i>first</i>	Iterator to the first element of the range
<i>last</i>	Iterator to the last element of the range
<i>separator</i>	Separator
<i>start</i>	Left marking
<i>end</i>	Right marking

Returns

Instance of `qpp::internal::internal::IOManipRange`

6.1.2.27 `template<typename Container> internal::IOManipRange<typename Container::const_iterator> qpp::disp (const Container & c, const std::string & separator, const std::string & start = " [", const std::string & end = "] ")`

Standard container ostream manipulator. The container must support `std::begin()`, `std::end()` and forward iteration.

Parameters

<i>x</i>	Container
<i>separator</i>	Separator
<i>start</i>	Left marking
<i>end</i>	Right marking

Returns

Instance of `qpp::internal::internal::IOManipRange`

6.1.2.28 `template<typename PointerType > internal::IOManipPointer<PointerType> qpp::disp (const PointerType * p, std::size_t n, const std::string & separator, const std::string & start = " [", const std::string & end = "] ")`

C-style pointer ostream manipulator.

Parameters

<i>x</i>	Pointer to the first element
<i>n</i>	Number of elements to be displayed
<i>separator</i>	Separator
<i>start</i>	Left marking
<i>end</i>	Right marking

Returns

Instance of `qpp::internal::internal::IOManipPointer`

6.1.2.29 `template<typename Derived > double qpp::entanglement (const Eigen::MatrixBase< Derived > & A, const std::vector< std::size_t > & dims)`

Entanglement of the bi-partite pure state *A*.

Defined as the von-Neumann entropy of the reduced density matrix of one of the subsystems

See also

[qpp::shannon\(\)](#)

Parameters

<i>A</i>	Eigen expression
<i>dims</i>	Dimensions of the bi-partite system

Returns

Entanglement, with the logarithm in base 2

6.1.2.30 `template<typename Derived > DynColVect<cplx> qpp::evals (const Eigen::MatrixBase< Derived > & A)`

Eigenvalues.

Parameters

A	Eigen expression
-----	------------------

Returns

Eigenvalues of A , as a complex dynamic column vector

6.1.2.31 `template<typename Derived> cmat qpp::evecs (const Eigen::MatrixBase< Derived> & A)`

Eigenvectors.

Parameters

A	Eigen expression
-----	------------------

Returns

Eigenvectors of A , as columns of a complex matrix

6.1.2.32 `template<typename Derived> cmat qpp::expm (const Eigen::MatrixBase< Derived> & A)`

Matrix exponential.

Parameters

A	Eigen expression
-----	------------------

Returns

Matrix exponential of A

6.1.2.33 `template<typename Derived> cmat qpp::funm (const Eigen::MatrixBase< Derived> & A, cplx(*) (const cplx &) f)`

Functional calculus $f(A)$

Parameters

A	Eigen expression
f	Pointer-to-function from complex to complex

Returns

$f(A)$

6.1.2.34 `std::size_t qpp::gcd (std::size_t m, std::size_t n)`

Greatest common divisor of two non-negative integers.

Parameters

m	Non-negative integer
-----	----------------------

<i>n</i>	Non-negative integer
----------	----------------------

Returns

Greatest common divisor of m and n

6.1.2.35 `std::size_t qpp::gcd (const std::vector< std::size_t > & ns)`

Greatest common divisor of a list of non-negative integers.

Parameters

<i>ns</i>	List of non-negative integers
-----------	-------------------------------

Returns

Greatest common divisor of all numbers in *ns*

6.1.2.36 `template<typename Derived > double qpp::gconcurrence (const Eigen::MatrixBase< Derived > & A)`

G-concurrence of the bi-partite pure state A .

Note

Both local dimensions must be equal

Uses [qpp::logdet\(\)](#) to avoid overflows

See also

[qpp::logdet\(\)](#)

Parameters

A	Eigen expression
-----	------------------

Returns

G-concurrence

6.1.2.37 `template<typename Derived > DynMat<typename Derived::Scalar> qpp::grams (const std::vector< Derived > & Vs)`

Gram-Schmidt orthogonalization.

Parameters

<i>Vs</i>	std::vector of Eigen expressions as column vectors
-----------	--

Returns

Gram-Schmidt vectors of *Vs* as columns of a dynamic matrix over the same scalar field as its arguments

6.1.2.38 `template<typename Derived > DynMat<typename Derived::Scalar> qpp::grams (const std::initializer_list< Derived > & Vs)`

Gram-Schmidt orthogonalization.

Parameters

V s	std::initializer_list of Eigen expressions as column vectors
-------	--

Returns

Gram-Schmidt vectors of V s as columns of a dynamic matrix over the same scalar field as its arguments

6.1.2.39 `template<typename Derived> DynMat<typename Derived::Scalar> qpp::grams (const Eigen::MatrixBase<Derived> & A)`

Gram-Schmidt orthogonalization.

Parameters

A	Eigen expression, the input vectors are the columns of A
-----	--

Returns

Gram-Schmidt vectors of the columns of A , as columns of a dynamic matrix over the same scalar field as A

6.1.2.40 `template<typename Derived> DynColVect<double> qpp::hevals (const Eigen::MatrixBase<Derived> & A)`

Hermitian eigenvalues.

Parameters

A	Eigen expression
-----	------------------

Returns

Eigenvalues of Hermitian A , as a real dynamic column vector

6.1.2.41 `template<typename Derived> cmat qpp::hevects (const Eigen::MatrixBase<Derived> & A)`

Hermitian eigenvectors.

Parameters

A	Eigen expression
-----	------------------

Returns

Eigenvectors of Hermitian A , as columns of a complex matrix

6.1.2.42 `template<typename Derived> DynMat<typename Derived::Scalar> qpp::inverse (const Eigen::MatrixBase<Derived> & A)`

Inverse.

Parameters

--	--

<i>A</i>	Eigen expression
----------	------------------

Returns

Inverse of *A*, as a dynamic matrix over the same scalar field as *A*

6.1.2.43 `std::vector<std::size_t> qpp::invperm (const std::vector< std::size_t > & perm)`

Inverse permutation.

Parameters

<i>perm</i>	Permutation
-------------	-------------

Returns

Inverse of the permutation *perm*

6.1.2.44 `template<typename T> DynMat<typename T::Scalar> qpp::kron (const T & head)`

Kronecker product.

Used to stop the recursion for the variadic template version of [qpp::kron\(\)](#)

Parameters

<i>head</i>	Eigen expression
-------------	------------------

Returns

Its argument *head*

6.1.2.45 `template<typename T, typename... Args> DynMat<typename T::Scalar> qpp::kron (const T & head, const Args &... tail)`

Kronecker product.

Parameters

<i>head</i>	Eigen expression
<i>tail</i>	Variadic Eigen expression (zero or more parameters)

Returns

Kronecker product of all input parameters, evaluated from left to right, as a dynamic matrix over the same scalar field as its arguments

6.1.2.46 `template<typename Derived> DynMat<typename Derived::Scalar> qpp::kron (const std::vector< Derived > & As)`

Kronecker product.

Parameters

<i>As</i>	std::vector of Eigen expressions
-----------	----------------------------------

Returns

Kronecker product of all elements in *As*, evaluated from left to right, as a dynamic matrix over the same scalar field as its arguments

6.1.2.47 `template<typename Derived> DynMat<typename Derived::Scalar> qpp::kron (const std::initializer_list< Derived> & As)`

Kronecker product.

Parameters

<i>As</i>	std::initializer_list of Eigen expressions, such as { <i>A1</i> , <i>A2</i> , ... , <i>Ak</i> }
-----------	---

Returns

Kronecker product of all elements in *As*, evaluated from left to right, as a dynamic matrix over the same scalar field as its arguments

6.1.2.48 `template<typename Derived> DynMat<typename Derived::Scalar> qpp::kronpow (const Eigen::MatrixBase< Derived> & A, std::size_t n)`

Kronecker power.

Parameters

<i>A</i>	Eigen expression
<i>n</i>	Non-negative integer

Returns

Kronecker product of *A* with itself *n* times $A^{\otimes n}$, as a dynamic matrix over the same scalar field as *A*

6.1.2.49 `std::size_t qpp::lcm (std::size_t m, std::size_t n)`

Least common multiple of two positive integers.

Parameters

<i>m</i>	Positive integer
<i>n</i>	Positive integer

Returns

Least common multiple of *m* and *n*

6.1.2.50 `std::size_t qpp::lcm (const std::vector< std::size_t> & ns)`

Least common multiple of a list of positive integers.

Parameters

<i>ns</i>	List of positive integers
-----------	---------------------------

Returns

Least common multiple of all numbers in *ns*

6.1.2.51 `template<typename Derived > DynMat<typename Derived::Scalar> qpp::load (const std::string & fname)`

Loads Eigen matrix from a binary file (internal format) in double precision.

The template parameter cannot be automatically deduced and must be explicitly provided, depending on the scalar field of the matrix that is being loaded.

Example:

```
// loads a previously saved Eigen dynamic complex matrix from "input.bin"
auto mat = load<cmat>("input.bin");
```

See also

[qpp::loadMATLABmatrix\(\)](#)

Parameters

<i>A</i>	Eigen expression
<i>fname</i>	Output file name

6.1.2.52 `template<typename Derived > Derived qpp::loadMATLABmatrix (const std::string & mat_file, const std::string & var_name)`

Loads an Eigen dynamic matrix from a MATLAB .mat file, generic version.

This is the generic version that always throws [qpp::Exception::Type::UNDEFINED_TYPE](#). It is specialized only for [qpp::dmat](#) and [qpp::cmat](#) (the only matrix types that can be loaded)

6.1.2.53 `template<> dmat qpp::loadMATLABmatrix (const std::string & mat_file, const std::string & var_name)` [inline]

Loads an Eigen dynamic matrix from a MATLAB .mat file, specialization for double matrices ([qpp::dmat](#))

The template parameter cannot be automatically deduced and must be explicitly provided

Example:

```
// loads a previously saved Eigen dynamic double matrix from the
MATLAB file "input.mat"
auto mat = loadMATLABmatrix<dmat>("input.mat");
```

Note

If *var_name* is a complex matrix, only the real part is loaded

Parameters

<i>mat_file</i>	MATALB .mat file
<i>var_name</i>	Variable name in the .mat file representing the matrix to be loaded

Returns

Eigen double dynamic matrix ([qpp::dmat](#))

6.1.2.54 `template<> cmat qpp::loadMATLABmatrix (const std::string & mat_file, const std::string & var_name)`
`[inline]`

Loads an Eigen dynamic matrix from a MATLAB .mat file, specialization for complex matrices ([qpp::cmat](#))

The template parameter cannot be automatically deduced and must be explicitly provided

Example:

```
// loads a previously saved Eigen dynamic complex matrix from the
MATLAB file "input.mat"
auto mat = loadMATLABmatrix<cmat>("input.mat");
```

Parameters

<i>mat_file</i>	MATALB .mat file
<i>var_name</i>	Variable name in the .mat file representing the matrix to be loaded

Returns

Eigen complex dynamic matrix ([qpp::cmat](#))

6.1.2.55 `template<typename Derived > Derived::Scalar qpp::logdet (const Eigen::MatrixBase< Derived > & A)`

Logarithm of the determinant.

Useful when the determinant overflows/underflows

Parameters

<i>A</i>	Eigen expression
----------	------------------

Returns

Logarithm of the determinant of *A*, as a scalar in the same scalar field as *A*

6.1.2.56 `template<typename Derived > cmat qpp::logm (const Eigen::MatrixBase< Derived > & A)`

Matrix logarithm.

Parameters

<i>A</i>	Eigen expression
----------	------------------

Returns

Matrix logarithm of *A*

6.1.2.57 `template<typename Derived > double qpp::lognegativity (const Eigen::MatrixBase< Derived > & A, const std::vector< std::size_t > & dims)`

Logarithmic negativity of the bi-partite mixed state *A*.

Parameters

<i>A</i>	Eigen expression
<i>dims</i>	Dimensions of the bi-partite system

Returns

Logarithmic negativity, with the logarithm in base 2

6.1.2.58 `template<typename Derived > std::tuple<std::size_t, std::vector<double>, std::vector<cmat> > qpp::measure (const Eigen::MatrixBase< Derived > & A, const std::vector< cmat > & Ks, const std::vector< std::size_t > & subsys, const std::vector< std::size_t > & dims)`

Measures the part *subsys* of the multi-partite state vector or density matrix *A* using the set of Kraus operators *Ks*.

Note

The dimension of all *Ks* must match the dimension of *subsys*.

Parameters

<i>A</i>	Eigen expression
<i>Ks</i>	Set of Kraus operators
<i>subsys</i>	Subsystem indexes that are measured
<i>dims</i>	Dimensions of the multi-partite system

Returns

Tuple consisting of the result of the measurement, the vector of outcome probabilities and the vector of post-measurement normalized states

6.1.2.59 `template<typename Derived > std::tuple<std::size_t, std::vector<double>, std::vector<cmat> > qpp::measure (const Eigen::MatrixBase< Derived > & A, const std::initializer_list< cmat > & Ks, const std::vector< std::size_t > & subsys, const std::vector< std::size_t > & dims)`

Measures the part *subsys* of the multi-partite state vector or density matrix *A* using the set of Kraus operators *Ks*.

Note

The dimension of all *Ks* must match the dimension of *subsys*.

Parameters

<i>A</i>	Eigen expression
<i>subsys</i>	Subsystem indexes that are measured
<i>dims</i>	Dimensions of the multi-partite system
<i>Ks</i>	Set of Kraus operators

Returns

Tuple consisting of the result of the measurement, the vector of outcome probabilities and the vector of post-measurement normalized states

6.1.2.60 `template<typename Derived > std::tuple<std::size_t, std::vector<double>, std::vector<cmat> > qpp::measure (const Eigen::MatrixBase< Derived > & A, const std::vector< cmat > & Ks, const std::vector< std::size_t > & subsys, const std::size_t d = 2)`

Measures the part *subsys* of the multi-partite state vector or density matrix *A* using the set of Kraus operators *Ks*.

Note

The dimension of all *Ks* must match the dimension of *subsys*.

Parameters

<i>A</i>	Eigen expression
<i>subsys</i>	Subsystem indexes that are measured
<i>d</i>	Subsystem dimensions
<i>Ks</i>	Set of Kraus operators

Returns

Tuple consisting of the result of the measurement, the vector of outcome probabilities and the vector of post-measurement normalized states

6.1.2.61 `template<typename Derived > std::tuple<std::size_t, std::vector<double>, std::vector<cmat> > qpp::measure (const Eigen::MatrixBase< Derived > & A, const std::initializer_list< cmat > & Ks, const std::vector< std::size_t > & subsys, const std::size_t d = 2)`

Measures the part *subsys* of the multi-partite state vector or density matrix *A* using the set of Kraus operators *Ks*.

Note

The dimension of all *Ks* must match the dimension of *subsys*.

Parameters

<i>A</i>	Eigen expression
<i>subsys</i>	Subsystem indexes that are measured
<i>d</i>	Subsystem dimensions
<i>Ks</i>	Set of Kraus operators

Returns

Tuple consisting of the result of the measurement, the vector of outcome probabilities and the vector of post-measurement normalized states

6.1.2.62 `template<typename Derived > std::tuple<std::size_t, std::vector<double>, std::vector<cmat> > qpp::measure (const Eigen::MatrixBase< Derived > & A, const cmat & U, const std::vector< std::size_t > & subsys, const std::vector< std::size_t > & dims)`

Measures the part *subsys* of the multi-partite state *A* in the orthonormal basis specified by the unitary matrix *U*.

Note

The dimension of *U* must match the dimension of *subsys*.

Parameters

A	Eigen expression
$subsys$	Subsystem indexes that are measured
$dims$	Dimensions of the multi-partite system
U	Unitary matrix whose columns represent the measurement basis vectors

Returns

Tuple consisting of the result of the measurement, the vector of outcome probabilities and the vector of post-measurement normalized states

6.1.2.63 `template<typename Derived> std::tuple<std::size_t, std::vector<double>, std::vector<cmat>> qpp::measure (const Eigen::MatrixBase< Derived> & A, const cmat & U, const std::vector< std::size_t> & subsys, const std::size_t d = 2)`

Measures the part $subsys$ of the multi-partite state A in the orthonormal basis specified by the unitary matrix U .

Note

The dimension of U must match the dimension of $subsys$.

Parameters

A	Eigen expression
$subsys$	Subsystem indexes that are measured
d	Subsystem dimensions
U	Unitary matrix whose columns represent the measurement basis vectors

Returns

Tuple consisting of the result of the measurement, the vector of outcome probabilities and the vector of post-measurement normalized states

6.1.2.64 `template<typename Derived> std::tuple<std::size_t, std::vector<double>, std::vector<cmat>> qpp::measure (const Eigen::MatrixBase< Derived> & A, const std::vector< cmat> & Ks)`

Measures the state A using the set of Kraus operators Ks .

Parameters

A	Eigen expression
Ks	Set of Kraus operators

Returns

Tuple consisting of the result of the measurement, the vector of outcome probabilities and the vector of post-measurement normalized states

6.1.2.65 `template<typename Derived> std::tuple<std::size_t, std::vector<double>, std::vector<cmat>> qpp::measure (const Eigen::MatrixBase< Derived> & A, const std::initializer_list< cmat> & Ks)`

Measures the state A using the set of Kraus operators Ks .

Parameters

A	Eigen expression
Ks	Set of Kraus operators

Returns

Tuple consisting of the result of the measurement, the vector of outcome probabilities and the vector of post-measurement normalized states

6.1.2.66 `template<typename Derived> std::tuple<std::size_t, std::vector<double>, std::vector<cmat>> qpp::measure (const Eigen::MatrixBase< Derived> & A, const cmat & U)`

Measures the state A in the orthonormal basis specified by the unitary matrix U .

Parameters

A	Eigen expression
U	Unitary matrix whose columns represent the measurement basis vectors

Returns

Tuple consisting of the result of the measurement, the vector of outcome probabilities and the vector of post-measurement normalized states

6.1.2.67 `ket qpp::mket (const std::vector< std::size_t> & mask, const std::vector< std::size_t> & dims)`

Multi-partite qudit ket.

Constructs the multi-partite qudit ket $|\text{mask}\rangle$, where mask is a `std::vector` of non-negative integers. Each element in mask has to be smaller than the corresponding element in dims .

Parameters

mask	<code>std::vector</code> of non-negative integers
dims	Dimensions of the multi-partite system

Returns

Multi-partite qudit state vector, as a complex dynamic column vector

6.1.2.68 `ket qpp::mket (const std::vector< std::size_t> & mask, std::size_t d = 2)`

Multi-partite qudit ket.

Constructs the multi-partite qudit ket $|\text{mask}\rangle$, all subsystem having equal dimension d . mask is a `std::vector` of non-negative integers, and each element in mask has to be strictly smaller than d .

Parameters

mask	<code>std::vector</code> of non-negative integers
d	Subsystem dimensions

Returns

Multi-partite qudit state vector, as a complex dynamic column vector

6.1.2.69 `cmat qpp::mprj (const std::vector< std::size_t > & mask, const std::vector< std::size_t > & dims)`

Projector onto multi-partite qudit ket.

Constructs the projector onto the multi-partite qudit ket $|\text{mask}\rangle$, where *mask* is a `std::vector` of non-negative integers. Each element in *mask* has to be smaller than the corresponding element in *dims*.

Parameters

<i>mask</i>	<code>std::vector</code> of non-negative integers
<i>dims</i>	Dimensions of the multi-partite system

Returns

Projector onto multi-partite qudit state vector, as a complex dynamic matrix

6.1.2.70 `cmat qpp::mprj (const std::vector< std::size_t > & mask, std::size_t d = 2)`

Projector onto multi-partite qudit ket.

Constructs the projector onto the multi-partite qudit ket $|\text{mask}\rangle$, all subsystem having equal dimension *d*. *mask* is a `std::vector` of non-negative integers, and each element in *mask* has to be strictly smaller than *d*.

Parameters

<i>mask</i>	<code>std::vector</code> of non-negative integers
<i>d</i>	Subsystem dimensions

Returns

Projector onto multi-partite qudit state vector, as a complex dynamic matrix

6.1.2.71 `std::size_t qpp::multiidx2n (const std::vector< std::size_t > & midx, const std::vector< std::size_t > & dims)`

Multi-index to non-negative integer index.

Uses standard lexicographical order, i.e. 00...0, 00...1 etc.

Parameters

<i>midx</i>	Multi-index
<i>dims</i>	Dimensions of the multi-partite system

Returns

Non-negative integer index

6.1.2.72 `std::vector<std::size_t> qpp::n2multiidx (std::size_t n, const std::vector< std::size_t > & dims)`

Non-negative integer index to multi-index.

Uses standard lexicographical order, i.e. 00...0, 00...1 etc.

Parameters

n	Non-negative integer index
$dims$	Dimensions of the multi-partite system

Returns

Multi-index of the same size as $dims$

6.1.2.73 `template<typename Derived > double qpp::negativity (const Eigen::MatrixBase< Derived > & A, const std::vector< std::size_t > & dims)`

Negativity of the bi-partite mixed state A .

Parameters

A	Eigen expression
$dims$	Dimensions of the bi-partite system

Returns

Negativity

6.1.2.74 `template<typename Derived > double qpp::norm (const Eigen::MatrixBase< Derived > & A)`

Frobenius norm.

Parameters

A	Eigen expression
-----	------------------

Returns

Frobenius norm of A , as a real number

6.1.2.75 `std::complex<double> qpp::omega (std::size_t D)`

D -th root of unity.

Parameters

D	Non-negative integer
-----	----------------------

Returns

D -th root of unity $\exp(2\pi i/D)$

6.1.2.76 `constexpr std::complex<double> qpp::operator""_i (unsigned long long int x)`

User-defined literal for complex $i = \sqrt{-1}$ (integer overload)

Example:

```
auto z = 4_i; // type of z is std::complex<double>
```


6.1.2.77 `constexpr std::complex<double> qpp::operator""_i (long double x)`

User-defined literal for complex $i = \sqrt{-1}$ (real overload)

Example:

```
auto z = 4.5_i; // type of z is std::complex<double>
```

6.1.2.78 `template<typename Derived > DynMat<typename Derived::Scalar> qpp::powm (const Eigen::MatrixBase< Derived > & A, std::size_t n)`

Matrix power.

Explicitly multiplies the matrix A with itself n times. By convention $A^0 = I$.

Parameters

A	Eigen expression
n	Non-negative integer

Returns

Matrix power A^n , as a dynamic matrix over the same scalar field as A

6.1.2.79 `template<typename Derived > DynMat<typename Derived::Scalar> qpp::prj (const Eigen::MatrixBase< Derived > & V)`

Projector.

Normalized projector onto state vector

Parameters

V	Eigen expression
-----	------------------

Returns

Projector onto the state vector V , or the matrix *Zero* if V has norm zero (i.e. smaller than `qpp::eps`), as a dynamic matrix over the same scalar field as A

6.1.2.80 `template<typename Derived > Derived::Scalar qpp::prod (const Eigen::MatrixBase< Derived > & A)`

Element-wise product of A .

Parameters

A	Eigen expression
-----	------------------

Returns

Element-wise product of A , as a scalar in the same scalar field as A

6.1.2.81 `template<typename InputIterator > auto qpp::prod (InputIterator first, InputIterator last) -> typename InputIterator::value_type`

Element-wise product of a range.

Parameters

<i>first</i>	Iterator to the first element of the range
<i>last</i>	Iterator to the last element of the range

Returns

Element-wise product of the range, as a scalar in the same scalar field as the range

6.1.2.82 `template<typename Derived> DynMat<typename Derived::Scalar> qpp::ptrace (const Eigen::MatrixBase<Derived> & A, const std::vector< std::size_t > & subsys, const std::vector< std::size_t > & dims)`

Partial trace.

Partial trace of the multi-partite density matrix over a list of subsystems

Parameters

<i>A</i>	Eigen expression
<i>subsys</i>	Subsystem indexes
<i>dims</i>	Dimensions of the multi-partite system

Returns

Partial trace $Tr_{subsys}(\cdot)$ over the subsystems *subsys* in a multi-partite system, as a dynamic matrix over the same scalar field as *A*

6.1.2.83 `template<typename Derived> DynMat<typename Derived::Scalar> qpp::ptrace1 (const Eigen::MatrixBase<Derived> & A, const std::vector< std::size_t > & dims)`

Partial trace.

Partial trace of density matrix over the first subsystem in a bi-partite system

Parameters

<i>A</i>	Eigen expression
<i>dims</i>	Dimensions of the bi-partite system (must be a std::vector with 2 elements)

Returns

Partial trace $Tr_A(\cdot)$ over the first subsystem *A* in a bi-partite system $A \otimes B$, as a dynamic matrix over the same scalar field as *A*

6.1.2.84 `template<typename Derived> DynMat<typename Derived::Scalar> qpp::ptrace2 (const Eigen::MatrixBase<Derived> & A, const std::vector< std::size_t > & dims)`

Partial trace.

Parameters

<i>A</i>	Eigen expression
<i>dims</i>	Dimensions of the bi-partite system (must be a std::vector with 2 elements)

Returns

Partial trace $Tr_B(\cdot)$ over the second subsystem *B* in a bi-partite system $A \otimes B$, as a dynamic matrix over the same scalar field as *A*

6.1.2.85 `template<typename Derived> DynMat<typename Derived::Scalar> qpp::ptranspose (const Eigen::MatrixBase<Derived> & A, const std::vector< std::size_t > & subsys, const std::vector< std::size_t > & dims)`

Partial transpose.

Partial transpose of the multi-partite density matrix over a list of subsystems

Parameters

<i>A</i>	Eigen expression
<i>subsys</i>	Subsystem indexes
<i>dims</i>	Dimensions of the multi-partite system

Returns

Partial transpose $(\cdot)^{T_{subsys}}$ over the subsystems *subsys* in a multi-partite system, as a dynamic matrix over the same scalar field as *A*

6.1.2.86 `template<typename Derived> double qpp::qmutualinfo (const Eigen::MatrixBase<Derived> & A, const std::vector< std::size_t > & subsysA, const std::vector< std::size_t > & subsysB, const std::vector< std::size_t > & dims)`

Quantum mutual information between 2 subsystems of a composite system.

Parameters

<i>A</i>	Eigen expression
<i>subsysA</i>	Indexes of the first subsystem
<i>subsysB</i>	Indexes of the second subsystem
<i>dims</i>	Dimensions of the multi-partite system

Returns

Mutual information between the 2 subsystems

6.1.2.87 `template<typename Derived> Derived qpp::rand (std::size_t rows, std::size_t cols, double a = 0, double b = 1)`

Generates a random matrix with entries uniformly distributed in the interval [a, b)

If complex, then both real and imaginary parts are uniformly distributed in [a, b)

This is the generic version that always throws [qpp::Exception::Type::UNDEFINED_TYPE](#). It is specialized only for [qpp::dmat](#) and [qpp::cmat](#)

6.1.2.88 `template<> dmat qpp::rand (std::size_t rows, std::size_t cols, double a, double b) [inline]`

Generates a random real matrix with entries uniformly distributed in the interval [a, b), specialization for double matrices ([qpp::dmat](#))

The template parameter cannot be automatically deduced and must be explicitly provided

Example:

```
// generates a 3 x 3 random Eigen::MatrixXd, with entries uniformly distributed in [-1,1)
auto mat = rand<dmat>(3, 3, -1, 1);
```

Parameters

<i>rows</i>	Number of rows of the random generated matrix
<i>cols</i>	Number of columns of the random generated matrix
<i>a</i>	Beginning of the interval, belongs to it
<i>b</i>	End of the interval, does not belong to it

Returns

Random real matrix

6.1.2.89 `template<> cmat qpp::rand (std::size_t rows, std::size_t cols, double a, double b)` `[inline]`

Generates a random complex matrix with entries (both real and imaginary) uniformly distributed in the interval [a, b), specialization for complex matrices ([qpp::cmat](#))

The template parameter cannot be automatically deduced and must be explicitly provided

Example:

```
// generates a 3 x 3 random Eigen::MatrixXcd, with entries (both real and imaginary) uniformly distributed
// in [-1,1)
auto mat = rand<cmat>(3, 3, -1, 1);
```

Parameters

<i>rows</i>	Number of rows of the random generated matrix
<i>cols</i>	Number of columns of the random generated matrix
<i>a</i>	Beginning of the interval, belongs to it
<i>b</i>	End of the interval, does not belong to it

Returns

Random complex matrix

6.1.2.90 `double qpp::rand (double a = 0, double b = 1)`

Generates a random real number uniformly distributed in the interval [a, b)

Parameters

<i>a</i>	Beginning of the interval, belongs to it
<i>b</i>	End of the interval, does not belong to it

Returns

Random real number (double) uniformly distributed in the interval [a, b)

6.1.2.91 `cmat qpp::randH (std::size_t D)`

Generates a random Hermitian matrix.

Parameters

D	Dimension of the Hilbert space
-----	--------------------------------

Returns

Random Hermitian matrix

6.1.2.92 `int qpp::randint (int a = std::numeric_limits<int>::min(), int b = std::numeric_limits<int>::max())`

Generates a random integer (int) uniformly distributed in the interval [a, b].

Parameters

a	Beginning of the interval, belongs to it
b	End of the interval, does not belong to it

Returns

Random integer (int) uniformly distributed in the interval [a, b]

6.1.2.93 `ket qpp::randket (std::size_t D)`

Generates a random normalized ket (pure state vector)

Parameters

D	Dimension of the Hilbert space
-----	--------------------------------

Returns

Random normalized ket

6.1.2.94 `std::vector<cmat> qpp::randkraus (std::size_t N , std::size_t D)`

Generates a set of random Kraus operators.

Note

The set of Kraus operators satisfy the closure condition $\sum_i K_i^\dagger K_i = I$

Parameters

N	Number of Kraus operators
D	Dimension of the Hilbert space

Returns

Set of N Kraus operators satisfying the closure condition

6.1.2.95 `template<typename Derived > Derived qpp::randn (std::size_t $rows$, std::size_t $cols$, double $mean$ = 0, double $sigma$ = 1)`

Generates a random matrix with entries normally distributed in $N(mean, sigma)$

If complex, then both real and imaginary parts are normally distributed in $N(mean, sigma)$

This is the generic version that always throws [qpp::Exception::Type::UNDEFINED_TYPE](#). It is specialized only for [qpp::dmat](#) and [qpp::cmat](#)

6.1.2.96 `template<> dmat qpp::randn (std::size_t rows, std::size_t cols, double mean, double sigma) [inline]`

Generates a random real matrix with entries normally distributed in $N(\text{mean}, \text{sigma})$, specialization for double matrices ([qpp::dmat](#))

The template parameter cannot be automatically deduced and must be explicitly provided

Example:

```
// generates a 3 x 3 random Eigen::MatrixXd, with entries normally distributed in N(0,2)
auto mat = randn<dmat>(3, 3, 0, 2);
```

Parameters

<i>rows</i>	Number of rows of the random generated matrix
<i>cols</i>	Number of columns of the random generated matrix
<i>mean</i>	Mean
<i>sigma</i>	Standard deviation

Returns

Random real matrix

6.1.2.97 `template<> cmat qpp::randn (std::size_t rows, std::size_t cols, double mean, double sigma) [inline]`

Generates a random complex matrix with entries (both real and imaginary) normally distributed in $N(\text{mean}, \text{sigma})$, specialization for complex matrices ([qpp::cmat](#))

The template parameter cannot be automatically deduced and must be explicitly provided

Example:

```
// generates a 3 x 3 random Eigen::MatrixXcd, with entries (both real and imaginary) normally distributed
// in N(0,2)
auto mat = randn<cmat>(3, 3, 0, 2);
```

Parameters

<i>rows</i>	Number of rows of the random generated matrix
<i>cols</i>	Number of columns of the random generated matrix
<i>mean</i>	Mean
<i>sigma</i>	Standard deviation

Returns

Random complex matrix

6.1.2.98 `double qpp::randn (double mean = 0, double sigma = 1)`

Generates a random real number (double) normally distributed in $N(\text{mean}, \text{sigma})$

Parameters

<i>mean</i>	Mean
<i>sigma</i>	Standard deviation

Returns

Random real number normally distributed in $N(\text{mean}, \text{sigma})$

6.1.2.99 `std::vector<std::size_t> qpp::randperm (std::size_t n)`

Generates a random uniformly distributed permutation.

Uses Knuth's shuffle method (as implemented by `std::shuffle`), so that all permutations are equally probable

Parameters

<i>n</i>	Size of the permutation
----------	-------------------------

Returns

Random permutation of size *n*

6.1.2.100 `cmat qpp::randrho (std::size_t D)`

Generates a random density matrix.

Parameters

<i>D</i>	Dimension of the Hilbert space
----------	--------------------------------

Returns

Random density matrix

6.1.2.101 `cmat qpp::randU (std::size_t D)`

Generates a random unitary matrix.

Parameters

<i>D</i>	Dimension of the Hilbert space
----------	--------------------------------

Returns

Random unitary

6.1.2.102 `cmat qpp::randV (std::size_t Din, std::size_t Dout)`

Generates a random isometry matrix.

Parameters

<i>Din</i>	Size of the input Hilbert space
<i>Dout</i>	Size of the output Hilbert space

Returns

Random isometry matrix

6.1.2.103 `template<typename Derived > double qpp::renyi (const Eigen::MatrixBase< Derived > & A, double alpha)`

Renyi- α entropy of the probability distribution/density matrix *A*, for $\alpha \geq 0$.

Parameters

A	Eigen expression, representing a probability distribution (real dynamic column vector) or a density matrix (complex dynamic matrix)
α	Non-negative real number, use qpp::infy for $\alpha = \infty$

Returns

Renyi- α entropy, with the logarithm in base 2

6.1.2.104 `template<typename Derived > DynMat<typename Derived::Scalar> qpp::reshape (const Eigen::MatrixBase< Derived > & A, std::size_t rows, std::size_t cols)`

Reshape.

Uses column-major order when reshaping (same as MATLAB)

Parameters

A	Eigen expression
<i>rows</i>	Number of rows of the reshaped matrix
<i>cols</i>	Number of columns of the reshaped matrix

Returns

Reshaped matrix with *rows* rows and *cols* columns, as a dynamic matrix over the same scalar field as A

6.1.2.105 `template<typename Derived > DynColVect<typename Derived::Scalar> qpp::rho2pure (const Eigen::MatrixBase< Derived > & A)`

Finds the pure state representation of a matrix proportional to a projector onto a pure state.

Note

No purity check is done, the input state A must have rank one, otherwise the function returns the first non-zero eigenvector of A

Parameters

A	Eigen expression, assumed to be proportional to a projector onto a pure state, i.e. A is assumed to have rank one
-----	---

Returns

The unique non-zero eigenvector of A , as a dynamic column vector over the same scalar field as A

6.1.2.106 `template<typename Derived > void qpp::save (const Eigen::MatrixBase< Derived > & A, const std::string & fname)`

Saves Eigen expression to a binary file (internal format) in double precision.

See also

[qpp::saveMATLABmatrix\(\)](#)

Parameters

<i>A</i>	Eigen expression
<i>fname</i>	Output file name

6.1.2.107 `template<typename Derived > void qpp::saveMATLABmatrix (const Eigen::MatrixBase< Derived > & A, const std::string & mat_file, const std::string & var_name, const std::string & mode)`

Saves an Eigen dynamic matrix to a MATLAB .mat file, generic version.

This is the generic version that always throws `qpp::Exception::Type::UNDEFINED_TYPE`. It is specialized only for `qpp::dmat` and `qpp::cmat` (the only matrix types that can be saved)

6.1.2.108 `template<> void qpp::saveMATLABmatrix (const Eigen::MatrixBase< dmat > & A, const std::string & mat_file, const std::string & var_name, const std::string & mode) [inline]`

Saves an Eigen dynamic matrix to a MATLAB .mat file, specialization for double matrices (`qpp::dmat`)

Parameters

<i>A</i>	Eigen expression over the complex field
<i>mat_file</i>	MATALB .mat file
<i>var_name</i>	Variable name in the .mat file representing the matrix to be saved
<i>mode</i>	Saving mode (append, overwrite etc.), see MATLAB's <code>matOpen()</code> documentation for details

6.1.2.109 `template<> void qpp::saveMATLABmatrix (const Eigen::MatrixBase< cmat > & A, const std::string & mat_file, const std::string & var_name, const std::string & mode) [inline]`

Saves an Eigen dynamic matrix to a MATLAB .mat file, specialization for complex matrices (`qpp::cmat`)

Parameters

<i>A</i>	Eigen expression over the complex field
<i>mat_file</i>	MATALB .mat file
<i>var_name</i>	Variable name in the .mat file representing the matrix to be saved
<i>mode</i>	Saving mode (append, overwrite etc.), see MATLAB's <code>matOpen()</code> documentation for details

6.1.2.110 `template<typename Derived > double qpp::schatten (const Eigen::MatrixBase< Derived > & A, std::size_t p)`

Schatten norm.

Parameters

<i>A</i>	Eigen expression
<i>p</i>	Integer, greater or equal to 1

Returns

Schatten-*p* norm of *A*, as a real number

6.1.2.111 `template<typename Derived > DynColVect<cplx> qpp::schmidtcoeff (const Eigen::MatrixBase< Derived > & A, const std::vector< std::size_t > & dims)`

Schmidt coefficients of the bi-partite pure state *A*.

Note

The sum of the squares of the Schmidt coefficients equals 1

See also

[qpp::schmidtprob\(\)](#)

Parameters

<i>A</i>	Eigen expression
<i>dims</i>	Dimensions of the bi-partite system

Returns

Schmidt coefficients of *A*, as a complex dynamic column vector

6.1.2.112 `template<typename Derived > DynColVect<double> qpp::schmidtprob (const Eigen::MatrixBase< Derived > & A, const std::vector< std::size_t > & dims)`

Schmidt probabilities of the bi-partite pure state *A*.

Defined as the squares of the Schmidt coefficients. The sum of the Schmidt probabilities equals 1.

See also

[qpp::schmidtcoeff\(\)](#)

Parameters

<i>A</i>	Eigen expression
<i>dims</i>	Dimensions of the bi-partite system

Returns

Schmidt probabilities of *A*, as a real dynamic column vector

6.1.2.113 `template<typename Derived > cmat qpp::schmidtU (const Eigen::MatrixBase< Derived > & A, const std::vector< std::size_t > & dims)`

Schmidt basis on Alice's side.

Parameters

<i>A</i>	Eigen expression
<i>dims</i>	Dimensions of the bi-partite system

Returns

Unitary matrix *U* whose columns represent the Schmidt basis vectors on Alice's side.

6.1.2.114 `template<typename Derived > cmat qpp::schmidtV (const Eigen::MatrixBase< Derived > & A, const std::vector< std::size_t > & dims)`

Schmidt basis on Bob's side.

Parameters

<i>A</i>	Eigen expression
<i>dims</i>	Dimensions of the bi-partite system

Returns

Unitary matrix V whose columns represent the Schmidt basis vectors on Bob's side.

6.1.2.115 `template<typename Derived> double qpp::shannon (const Eigen::MatrixBase< Derived> & A)`

Shannon/von-Neumann entropy of the probability distribution/density matrix A .

Parameters

<i>A</i>	Eigen expression, representing a probability distribution (real dynamic column vector) or a density matrix (complex dynamic matrix)
----------	---

Returns

Shannon/von-Neumann entropy, with the logarithm in base 2

6.1.2.116 `template<typename Derived> cmat qpp::sinm (const Eigen::MatrixBase< Derived> & A)`

Matrix sin.

Parameters

<i>A</i>	Eigen expression
----------	------------------

Returns

Matrix sine of A

6.1.2.117 `template<typename Derived> cmat qpp::spectralpowm (const Eigen::MatrixBase< Derived> & A, const cplx z)`

Matrix power.

Uses the spectral decomposition of A to compute the matrix power. By convention $A^0 = I$.

Parameters

<i>A</i>	Eigen expression
<i>z</i>	Complex number

Returns

Matrix power A^z

6.1.2.118 `template<typename Derived> cmat qpp::sqrtm (const Eigen::MatrixBase< Derived> & A)`

Matrix square root.

Parameters

A	Eigen expression
-----	------------------

Returns

Matrix square root of A

6.1.2.119 `template<typename Derived > Derived::Scalar qpp::sum (const Eigen::MatrixBase< Derived > & A)`

Element-wise sum of A .

Parameters

A	Eigen expression
-----	------------------

Returns

Element-wise sum of A , as a scalar in the same scalar field as A

6.1.2.120 `template<typename InputIterator > auto qpp::sum (InputIterator first, InputIterator last) -> typename InputIterator::value_type`

Element-wise sum of a range.

Parameters

<i>first</i>	Iterator to the first element of the range
<i>last</i>	Iterator to the last element of the range

Returns

Element-wise sum of the range, as a scalar in the same scalar field as the range

6.1.2.121 `cmat qpp::super (const std::vector< cmat > & Ks)`

Superoperator matrix representation.

Constructs the superoperator matrix of the channel specified by the set of Kraus operators K_s in the standard operator basis $\{|i\rangle\langle j|\}$ ordered in lexicographical order, i.e. $|0\rangle\langle 0|$, $|0\rangle\langle 1|$ etc.

Parameters

K_s	Set of Kraus operators
-------	------------------------

Returns

Superoperator matrix representation

6.1.2.122 `template<typename Derived > DynColVect<double> qpp::svals (const Eigen::MatrixBase< Derived > & A)`

Singular values.

Parameters

A	Eigen expression
-----	------------------

Returns

Singular values of A , as a real dynamic column vector

6.1.2.123 `template<typename Derived > cmat qpp::svdU (const Eigen::MatrixBase< Derived > & A)`

Left singular vectors.

Parameters

A	Eigen expression
-----	------------------

Returns

Complex dynamic matrix, whose columns are the left singular vectors of A

6.1.2.124 `template<typename Derived > cmat qpp::svdV (const Eigen::MatrixBase< Derived > & A)`

Right singular vectors.

Parameters

A	Eigen expression
-----	------------------

Returns

Complex dynamic matrix, whose columns are the right singular vectors of A

6.1.2.125 `template<typename Derived > DynMat<typename Derived::Scalar> qpp::syspermute (const Eigen::MatrixBase< Derived > & A, const std::vector< std::size_t > & perm, const std::vector< std::size_t > & dims)`

System permutation.

Permutes the subsystems in a state vector or density matrix. The qubit $perm[i]$ is permuted to the location i .

Parameters

A	Eigen expression
$perm$	Permutation
$dims$	Dimensions of the multi-partite system

Returns

Permuted system, as a dynamic matrix over the same scalar field as A

6.1.2.126 `template<typename Derived > Derived::Scalar qpp::trace (const Eigen::MatrixBase< Derived > & A)`

Trace.

Parameters

A	Eigen expression
-----	------------------

Returns

Trace of A , as a scalar in the same scalar field as A

6.1.2.127 `template<typename Derived > DynMat<typename Derived::Scalar> qpp::transpose (const Eigen::MatrixBase<Derived > & A)`

Transpose.

Parameters

A	Eigen expression
-----	------------------

Returns

Transpose of A , as a dynamic matrix over the same scalar field as A

6.1.2.128 `template<typename Derived > double qpp::tsallis (const Eigen::MatrixBase< Derived > & A, double α)`

Tsallis- α entropy of the probability distribution/density matrix A , for $\alpha \geq 0$.

When $\alpha \rightarrow 1$ the Tsallis entropy converges to the Shannon/von-Neumann entropy, with the logarithm in base e

Parameters

A	Eigen expression, representing a probability distribution (real dynamic column vector) or a density matrix (complex dynamic matrix)
α	Non-negative real number

Returns

Renyi- α entropy, with the logarithm in base 2

6.1.2.129 `std::vector<int> qpp::x2contfrac (double x , std::size_t n , std::size_t $cut = 1e5$)`

Simple continued fraction expansion.

Parameters

x	Real number
n	Number of terms in the expansion
cut	Stop the expansion when the next term is greater than cut

Returns

Integer vector containing the simple continued fraction expansion of x . If there are m less than n terms in the expansion, a shorter vector with m components is returned.

6.1.3 Variable Documentation

6.1.3.1 `constexpr double qpp::chop = 1e-10`

Used in `qpp::disp()` and `qpp::displn()` for setting to zero numbers that have their absolute value smaller than `qpp::ct::chop`.

6.1.3.2 `const Codes& qpp::codes = Codes::get_instance()`[qpp::Codes](#) const SingletonInitializes the codes, see the class [qpp::Codes](#)**6.1.3.3** `constexpr double qpp::ee = 2.718281828459045235360287471352662497`Base of natural logarithm, e .**6.1.3.4** `constexpr double qpp::eps = 1e-12`

Used to decide whether a number or expression in double precision is zero or not.

Example:

```
if (std::abs(x) < qpp::eps) // x is zero
```

6.1.3.5 `const Gates& qpp::gt = Gates::get_instance()`[qpp::Gates](#) const SingletonInitializes the gates, see the class [qpp::Gates](#)**6.1.3.6** `constexpr std::size_t qpp::infy = -1`

Used to denote infinity.

6.1.3.7 `const Init& qpp::init = Init::get_instance()`[qpp::Init](#) const Singleton

Additional initializations/cleanups

6.1.3.8 `constexpr std::size_t qpp::maxn = 64`

Maximum number of qubits.

Used internally to allocate arrays on the stack (for speed reasons)

6.1.3.9 `constexpr double qpp::pi = 3.141592653589793238462643383279502884` π **6.1.3.10** `RandomDevices& qpp::rdevs = RandomDevices::get_instance()`[qpp::RandomDevices](#) SingletonInitializes the random devices, see the class [qpp::RandomDevices](#)**6.1.3.11** `const States& qpp::st = States::get_instance()`[qpp::States](#) const SingletonInitializes the states, see the class [qpp::States](#)

6.2 qpp::experimental Namespace Reference

6.2.1 Detailed Description

Experimental/test functions/classes, do not use or modify these functions/classes

6.3 qpp::internal Namespace Reference

Classes

- class [IOManipEigen](#)
- class [IOManipPointer](#)
- class [IOManipRange](#)
- class [Singleton](#)

[Singleton](#) policy class, used internally to implement the singleton pattern via CRTP (Curiously recurring template pattern)

Functions

- void [_n2multiidx](#) (std::size_t n, std::size_t numdims, const std::size_t *dims, std::size_t *result)
- std::size_t [_multiidx2n](#) (const std::size_t *midx, std::size_t numdims, const std::size_t *dims)
- template<typename Derived >
bool [_check_square_mat](#) (const Eigen::MatrixBase< Derived > &A)
- template<typename Derived >
bool [_check_vector](#) (const Eigen::MatrixBase< Derived > &A)
- template<typename Derived >
bool [_check_row_vector](#) (const Eigen::MatrixBase< Derived > &A)
- template<typename Derived >
bool [_check_col_vector](#) (const Eigen::MatrixBase< Derived > &A)
- template<typename T >
bool [_check_nonzero_size](#) (const T &x)
- bool [_check_dims](#) (const std::vector< std::size_t > &dims)
- template<typename Derived >
bool [_check_dims_match_mat](#) (const std::vector< std::size_t > &dims, const Eigen::MatrixBase< Derived > &A)
- template<typename Derived >
bool [_check_dims_match_cvect](#) (const std::vector< std::size_t > &dims, const Eigen::MatrixBase< Derived > &V)
- template<typename Derived >
bool [_check_dims_match_rvect](#) (const std::vector< std::size_t > &dims, const Eigen::MatrixBase< Derived > &V)
- bool [_check_eq_dims](#) (const std::vector< std::size_t > &dims, std::size_t dim)
- bool [_check_subsys_match_dims](#) (const std::vector< std::size_t > &subsys, const std::vector< std::size_t > &dims)
- bool [_check_perm](#) (const std::vector< std::size_t > &perm)
- template<typename Derived1 , typename Derived2 >
[DynMat](#)< typename Derived1::Scalar > [_kron2](#) (const Eigen::MatrixBase< Derived1 > &A, const Eigen::MatrixBase< Derived2 > &B)
- template<typename T >
void [variadic_vector_emplace](#) (std::vector< T > &)
- template<typename T , typename First , typename... Args>
void [variadic_vector_emplace](#) (std::vector< T > &v, First &&first, Args &&...args)

6.3.1 Detailed Description

Internal implementation details, do not use/modify these functions/classes

6.3.2 Function Documentation

- 6.3.2.1 `template<typename Derived > bool qpp::internal::_check_col_vector (const Eigen::MatrixBase< Derived > & A)`
- 6.3.2.2 `bool qpp::internal::_check_dims (const std::vector< std::size_t > & dims)`
- 6.3.2.3 `template<typename Derived > bool qpp::internal::_check_dims_match_cvect (const std::vector< std::size_t > & dims, const Eigen::MatrixBase< Derived > & V)`
- 6.3.2.4 `template<typename Derived > bool qpp::internal::_check_dims_match_mat (const std::vector< std::size_t > & dims, const Eigen::MatrixBase< Derived > & A)`
- 6.3.2.5 `template<typename Derived > bool qpp::internal::_check_dims_match_rvect (const std::vector< std::size_t > & dims, const Eigen::MatrixBase< Derived > & V)`
- 6.3.2.6 `bool qpp::internal::_check_eq_dims (const std::vector< std::size_t > & dims, std::size_t dim)`
- 6.3.2.7 `template<typename T > bool qpp::internal::_check_nonzero_size (const T & x)`
- 6.3.2.8 `bool qpp::internal::_check_perm (const std::vector< std::size_t > & perm)`
- 6.3.2.9 `template<typename Derived > bool qpp::internal::_check_row_vector (const Eigen::MatrixBase< Derived > & A)`
- 6.3.2.10 `template<typename Derived > bool qpp::internal::_check_square_mat (const Eigen::MatrixBase< Derived > & A)`
- 6.3.2.11 `bool qpp::internal::_check_subsys_match_dims (const std::vector< std::size_t > & subsys, const std::vector< std::size_t > & dims)`
- 6.3.2.12 `template<typename Derived > bool qpp::internal::_check_vector (const Eigen::MatrixBase< Derived > & A)`
- 6.3.2.13 `template<typename Derived1, typename Derived2 > DynMat<typename Derived1::Scalar> qpp::internal::_kron2 (const Eigen::MatrixBase< Derived1 > & A, const Eigen::MatrixBase< Derived2 > & B)`
- 6.3.2.14 `std::size_t qpp::internal::_multiidx2n (const std::size_t * midx, std::size_t numdims, const std::size_t * dims)`
[inline]
- 6.3.2.15 `void qpp::internal::_n2multiidx (std::size_t n, std::size_t numdims, const std::size_t * dims, std::size_t * result)`
[inline]
- 6.3.2.16 `template<typename T > void qpp::internal::_variadic_vector_emplace (std::vector< T > &)`
- 6.3.2.17 `template<typename T, typename First, typename... Args> void qpp::internal::_variadic_vector_emplace (std::vector< T > & v, First && first, Args &&... args)`

Chapter 7


Class Documentation

7.1 qpp::Codes Class Reference


const Singleton class that defines quantum error correcting codes

```
#include <codes.h>
```

Inheritance diagram for qpp::Codes:



Collaboration diagram for qpp::Codes:



Public Types

- enum `Type` { `Type::FIVE_QUBIT` = 1, `Type::SEVEN_QUBIT_STEANE`, `Type::NINE_QUBIT_SHOR` }
Code types, add more codes here if needed.

Public Member Functions

- `ket codeword` (`Type` type, `std::size_t` i) const
Returns the codeword of the specified code.

Private Member Functions

- `Codes` ()
Default constructor.

Friends

- class `internal::Singleton< const Codes >`

Additional Inherited Members

7.1.1 Detailed Description

const Singleton class that defines quantum error correcting codes

7.1.2 Member Enumeration Documentation

7.1.2.1 enum `qpp::Codes::Type` [strong]

Code types, add more codes here if needed.

See also

`qpp::Codes::codeword()`

Enumerator

`FIVE_QUBIT` [[5,1,3]] qubit code
`SEVEN_QUBIT_STEANE` [[7,1,3]] Steane qubit code
`NINE_QUBIT_SHOR` [[9,1,3]] Shor qubit code

7.1.3 Constructor & Destructor Documentation

7.1.3.1 `qpp::Codes::Codes ()` [inline], [private]

Default constructor.

7.1.4 Member Function Documentation

7.1.4.1 `ket qpp::Codes::codeword (Type type, std::size_t i) const` [inline]

Returns the codeword of the specified code.

Parameters

<i>type</i>	Code type, defined in the enum <code>qpp::Codes::Types</code>
<i>i</i>	Codeword index

Returns

i-th codeword of the code *type*

7.1.5 Friends And Related Function Documentation

7.1.5.1 `friend class internal::Singleton< const Codes > [friend]`

The documentation for this class was generated from the following file:


- `include/classes/codes.h`

7.2 qpp::Exception Class Reference


Generates custom exceptions, used when validating function parameters.

```
#include <exception.h>
```

Inheritance diagram for `qpp::Exception`:



Collaboration diagram for `qpp::Exception`:



Public Types

- enum `Type` {
`Type::UNKNOWN_EXCEPTION = 1`, `Type::ZERO_SIZE`, `Type::MATRIX_NOT_SQUARE`, `Type::MATRIX_NOT_CVECTOR`,
`Type::MATRIX_NOT_RVECTOR`, `Type::MATRIX_NOT_VECTOR`, `Type::MATRIX_NOT_SQUARE_OR_CVECTOR`, `Type::MATRIX_NOT_SQUARE_OR_RVECTOR`,
`Type::MATRIX_NOT_SQUARE_OR_VECTOR`, `Type::MATRIX_MISMATCH_SUBSYS`, `Type::DIMS_INVALID`, `Type::DIMS_NOT_EQUAL`,
`Type::DIMS_MISMATCH_MATRIX`, `Type::DIMS_MISMATCH_CVECTOR`, `Type::DIMS_MISMATCH_RVECTOR`, `Type::DIMS_MISMATCH_VECTOR`,
`Type::SUBSYS_MISMATCH_DIMS`, `Type::NOT_QUBIT_GATE`, `Type::NOT_QUBIT_SUBSYS`, `Type::NOT_BIPARTITE`,
`Type::NO_CODEWORD`, `Type::PERM_INVALID`, `Type::OUT_OF_RANGE`, `Type::TYPE_MISMATCH`,
`Type::UNDEFINED_TYPE`, `Type::CUSTOM_EXCEPTION` }
Exception types, add more exceptions here if needed.

Public Member Functions

- `Exception` (const `std::string` &where, const `Type` &type)
Constructs an exception.
- `Exception` (const `std::string` &where, const `std::string` &custom)
Constructs an exception.
- virtual const char * `what` () const noexcept override
Overrides `std::exception::what()`

Private Member Functions

- `std::string` `_construct_exception_msg` ()
Constructs the exception's description from its type.

Private Attributes

- `std::string _where`
- `std::string _msg`
- `Type _type`
- `std::string _custom`

7.2.1 Detailed Description

Generates custom exceptions, used when validating function parameters.

Customize this class if more exceptions are needed

7.2.2 Member Enumeration Documentation

7.2.2.1 `enum qpp::Exception::Type` [strong]

[Exception](#) types, add more exceptions here if needed.

See also

`qpp::Exception::_construct_exception_msg()`

Enumerator

UNKNOWN_EXCEPTION UNKNOWN_EXCEPTION. Unknown exception

ZERO_SIZE ZERO_SIZE. Zero sized object, e.g. empty `Eigen::Matrix` or `std::vector` with no elements

MATRIX_NOT_SQUARE MATRIX_NOT_SQUARE. `Eigen::Matrix` is not square

MATRIX_NOT_CVECTOR MATRIX_NOT_CVECTOR. `Eigen::Matrix` is not a column vector

MATRIX_NOT_RVECTOR MATRIX_NOT_RVECTOR. `Eigen::Matrix` is not a row vector

MATRIX_NOT_VECTOR MATRIX_NOT_VECTOR. `Eigen::Matrix` is not a row/column vector

MATRIX_NOT_SQUARE_OR_CVECTOR MATRIX_NOT_SQUARE_OR_CVECTOR. `Eigen::Matrix` is not square nor a column vector

MATRIX_NOT_SQUARE_OR_RVECTOR MATRIX_NOT_SQUARE_OR_RVECTOR. `Eigen::Matrix` is not square nor a row vector

MATRIX_NOT_SQUARE_OR_VECTOR MATRIX_NOT_SQUARE_OR_VECTOR. `Eigen::Matrix` is not square nor a row/column vector

MATRIX_MISMATCH_SUBSYS MATRIX_MISMATCH_SUBSYS.

DIMS_INVALID DIMS_INVALID. Matrix size mismatch subsystem sizes (e.g. in `qpp::apply()`, or `qpp::channel()` `std::vector<std::size_t>` representing the dimensions has zero size or contains zeros

DIMS_NOT_EQUAL DIMS_NOT_EQUAL. `std::vector<std::size_t>` representing the dimensions contains non-equal elements

DIMS_MISMATCH_MATRIX DIMS_MISMATCH_MATRIX. Product of the dimensions' `std::vector<std::size_t>` is not equal to the number of rows of `Eigen::Matrix` (assumed to be square)

DIMS_MISMATCH_CVECTOR DIMS_MISMATCH_CVECTOR. Product of the dimensions' `std::vector<std::size_t>` is not equal to the number of cols of `Eigen::Matrix` (assumed to be a column vector)

DIMS_MISMATCH_RVECTOR DIMS_MISMATCH_RVECTOR. Product of the dimensions' `std::vector<std::size_t>` is not equal to the number of cols of `Eigen::Matrix` (assumed to be a row vector)

DIMS_MISMATCH_VECTOR DIMS_MISMATCH_VECTOR. Product of the dimensions' `std::vector<std::size_t>` is not equal to the number of cols of `Eigen::Matrix` (assumed to be a row/column vector)

SUBSYS_MISMATCH_DIMS SUBSYS_MISMATCH_DIMS. `std::vector<std::size_t>` representing the subsystem labels has duplicates, or has entries that are larger than the size of the `std::vector<std::size_t>` representing the dimensions

NOT_QUBIT_GATE NOT_QUBIT_GATE. Eigen::Matrix is not 2 x 2

NOT_QUBIT_SUBSYS NOT_QUBIT_SUBSYS. Subsystems are not 2-dimensional

NOT_BIPARTITE NOT_BIPARTITE. std::vector<std::size_t> representing the dimensions has size different from 2

NO_CODEWORD NO_CODEWORD. Codeword does not exist, thrown when calling [qpp::Codes::codeword\(\)](#) with invalid *i*

PERM_INVALID PERM_INVALID. Invalid std::vector<std::size_t> permutation

OUT_OF_RANGE OUT_OF_RANGE. Parameter out of range

TYPE_MISMATCH TYPE_MISMATCH. Types do not match (i.e. Matrix<double> vs Matrix<cplx>)

UNDEFINED_TYPE UNDEFINED_TYPE. Templated function not defined for this type

CUSTOM_EXCEPTION CUSTOM_EXCEPTION. Custom exception, user must provide a custom message

7.2.3 Constructor & Destructor Documentation

7.2.3.1 [qpp::Exception::Exception](#) (const std::string & *where*, const **Type** & *type*) [inline]

Constructs an exception.

Parameters

<i>where</i>	Text representing where the exception occurred
<i>type</i>	Exception 's type, see the strong enumeration qpp::Exception::Type

7.2.3.2 [qpp::Exception::Exception](#) (const std::string & *where*, const std::string & *custom*) [inline]

Constructs an exception.

This is an overloaded member function, provided for convenience. It differs from the above function only in what argument(s) it accepts.

Parameters

<i>where</i>	Text representing where the exception occurred
<i>custom</i>	Exception 's description

7.2.4 Member Function Documentation

7.2.4.1 std::string [qpp::Exception::_construct_exception_msg](#) () [inline], [private]

Constructs the exception's description from its type.

Must modify the code of this function if more exceptions are added

Returns

[Exception](#)'s description

7.2.4.2 virtual const char* [qpp::Exception::what](#) () const [inline], [override], [virtual], [noexcept]

Overrides std::exception::what()

Returns

[Exception](#)'s description

7.2.5 Member Data Documentation

7.2.5.1 `std::string qpp::Exception::_custom` [private]

7.2.5.2 `std::string qpp::Exception::_msg` [private]

7.2.5.3 `Type qpp::Exception::_type` [private]

7.2.5.4 `std::string qpp::Exception::_where` [private]

The documentation for this class was generated from the following file:


- [include/classes/exception.h](#)

7.3 qpp::Gates Class Reference


const Singleton class that implements most commonly used gates

```
#include <gates.h>
```

Inheritance diagram for qpp::Gates:



Collaboration diagram for qpp::Gates:



Public Member Functions

- [cmat Rn](#) (double theta, std::vector< double > n) const
Rotation of theta about the 3-dimensional real unit vector n.
- [cmat Zd](#) (std::size_t D) const
Generalized Z gate for qudits.
- [cmat Fd](#) (std::size_t D) const
Fourier transform gate for qudits.
- [cmat Xd](#) (std::size_t D) const
Generalized X gate for qudits.
- template<typename Derived = Eigen::MatrixXcd>
Derived [Id](#) (std::size_t D) const
Identity gate.
- template<typename Derived >
[DynMat](#)< typename Derived::Scalar > [CTRL](#) (const Eigen::MatrixBase< Derived > &A, const std::vector< std::size_t > &ctrl, const std::vector< std::size_t > &subsys, std::size_t n, std::size_t d=2) const
Generates the multi-partite multiple-controlled-A gate in matrix form.
- template<typename Derived >
[DynMat](#)< typename Derived::Scalar > [expandout](#) (const Eigen::MatrixBase< Derived > &A, std::size_t pos, const std::vector< std::size_t > &dims) const
Expands out.

Public Attributes

- [cmat Id2](#) {cmat::Identity(2, 2)}
Identity gate.
- [cmat H](#) {cmat::Zero(2, 2)}
Hadamard gate.
- [cmat X](#) {cmat::Zero(2, 2)}
Pauli Sigma-X gate.
- [cmat Y](#) {cmat::Zero(2, 2)}
Pauli Sigma-Y gate.
- [cmat Z](#) {cmat::Zero(2, 2)}
Pauli Sigma-Z gate.
- [cmat S](#) {cmat::Zero(2, 2)}
S gate.
- [cmat T](#) {cmat::Zero(2, 2)}
T gate.
- [cmat CNOTab](#) {cmat::Identity(4, 4)}
Controlled-NOT control target gate.
- [cmat CZ](#) {cmat::Identity(4, 4)}
Controlled-Phase gate.
- [cmat CNOTba](#) {cmat::Zero(4, 4)}
Controlled-NOT target control gate.
- [cmat SWAP](#) {cmat::Identity(4, 4)}
SWAP gate.
- [cmat TOF](#) {cmat::Identity(8, 8)}
Toffoli gate.
- [cmat FRED](#) {cmat::Identity(8, 8)}
Fredkin gate.

Private Member Functions

- [Gates](#) ()
Initializes the gates.

Friends

- class [internal::Singleton](#)< const [Gates](#) >

Additional Inherited Members

7.3.1 Detailed Description

const Singleton class that implements most commonly used gates

7.3.2 Constructor & Destructor Documentation

7.3.2.1 `qpp::Gates::Gates () [inline], [private]`

Initializes the gates.

7.3.3 Member Function Documentation

7.3.3.1 `template<typename Derived > DynMat<typename Derived::Scalar> qpp::Gates::CTRL (const Eigen::MatrixBase< Derived > & A, const std::vector< std::size_t > & ctrl, const std::vector< std::size_t > & subsys, std::size_t n, std::size_t d = 2) const [inline]`

Generates the multi-partite multiple-controlled- A gate in matrix form.

Note

The dimension of the gate A must match the dimension of *subsys*

Parameters

A	Eigen expression
<i>ctrl</i>	Control subsystem indexes
<i>subsys</i>	Subsystem indexes where the gate A is applied
n	Total number of subsystems
d	Subsystem dimensions

Returns

CTRL- A gate, as a matrix over the same scalar field as A

7.3.3.2 `template<typename Derived > DynMat<typename Derived::Scalar> qpp::Gates::expandout (const Eigen::MatrixBase< Derived > & A, std::size_t pos, const std::vector< std::size_t > & dims) const [inline]`

Expands out.

Expands out A as a matrix in a multi-partite system. Faster than using [qpp::kron](#)($I, I, \dots, I, A, I, \dots, I$).

Parameters

A	Eigen expression
pos	Position
$dims$	Dimensions of the multi-partite system

Returns

Tensor product $I \otimes \cdots \otimes I \otimes A \otimes I \otimes \cdots \otimes I$, with A on position pos , as a dynamic matrix over the same scalar field as A

7.3.3.3 `cmat qpp::Gates::Fd (std::size_t D) const [inline]`

Fourier transform gate for qudits.

Note

Defined as $F = \sum_{jk} \exp(2\pi i jk/D) |j\rangle\langle k|$

Parameters

D	Dimension of the Hilbert space
-----	--------------------------------

Returns

Fourier transform gate for qudits

7.3.3.4 `template<typename Derived = Eigen::MatrixXcd> Derived qpp::Gates::Id (std::size_t D) const [inline]`

Identity gate.

Note

Can change the return type from complex matrix (default) by explicitly specifying the template parameter

Parameters

D	Dimension of the Hilbert space
-----	--------------------------------

Returns

Identity gate

7.3.3.5 `cmat qpp::Gates::Rn (double theta, std::vector< double > n) const [inline]`

Rotation of θ about the 3-dimensional real unit vector n .

Parameters

θ	Rotation angle
n	3-dimensional real unit vector

Returns

Rotation gate

7.3.3.6 `cmat qpp::Gates::Xd (std::size_t D) const [inline]`

Generalized X gate for qudits.

Note

Defined as $X = \sum_j |j \oplus 1\rangle \langle j|$

Parameters

D	Dimension of the Hilbert space
-----	--------------------------------

Returns

Generalized X gate for qudits

7.3.3.7 `cmat qpp::Gates::Zd (std::size_t D) const [inline]`

Generalized Z gate for qudits.

Note

Defined as $Z = \sum_j \exp(2\pi i j / D) |j\rangle \langle j|$

Parameters

D	Dimension of the Hilbert space
-----	--------------------------------

Returns

Generalized Z gate for qudits

7.3.4 Friends And Related Function Documentation**7.3.4.1** `friend class internal::Singleton< const Gates > [friend]`**7.3.5 Member Data Documentation****7.3.5.1** `cmat qpp::Gates::CNOTab {cmat::Identity(4, 4)}`

Controlled-NOT control target gate.

7.3.5.2 `cmat qpp::Gates::CNOTba {cmat::Zero(4, 4)}`

Controlled-NOT target control gate.

7.3.5.3 `cmat qpp::Gates::CZ {cmat::Identity(4, 4)}`

Controlled-Phase gate.

7.3.5.4 `cmat qpp::Gates::FRED {cmat::Identity(8, 8)}`

Fredkin gate.

7.3.5.5 `cmat qpp::Gates::H {cmat::Zero(2, 2)}`

Hadamard gate.

7.3.5.6 `cmat qpp::Gates::Id2 {cmat::Identity(2, 2)}`

Identity gate.

7.3.5.7 `cmat qpp::Gates::S {cmat::Zero(2, 2)}`

S gate.

7.3.5.8 `cmat qpp::Gates::SWAP {cmat::Identity(4, 4)}`

SWAP gate.

7.3.5.9 `cmat qpp::Gates::T {cmat::Zero(2, 2)}`

T gate.

7.3.5.10 `cmat qpp::Gates::TOF {cmat::Identity(8, 8)}`

Toffoli gate.

7.3.5.11 `cmat qpp::Gates::X {cmat::Zero(2, 2)}`

Pauli Sigma-X gate.

7.3.5.12 `cmat qpp::Gates::Y {cmat::Zero(2, 2)}`

Pauli Sigma-Y gate.

7.3.5.13 `cmat qpp::Gates::Z {cmat::Zero(2, 2)}`

Pauli Sigma-Z gate.

The documentation for this class was generated from the following file:


- [include/classes/gates.h](#)

7.4 `qpp::Init` Class Reference


const Singleton class that performs additional initializations/cleanups

```
#include <init.h>
```

Inheritance diagram for qpp::Init:



Collaboration diagram for qpp::Init:



Public Member Functions

- [Init \(\)](#)
Additional initializations.

Private Member Functions

- [~Init \(\)](#)
Cleanups.

Friends

- class [internal::Singleton< const Init >](#)

Additional Inherited Members

7.4.1 Detailed Description

const Singleton class that performs additional initializations/cleanups

7.4.2 Constructor & Destructor Documentation

7.4.2.1 `qpp::Init::Init ()` `[inline]`

Additional initializations.

7.4.2.2 `qpp::Init::~Init ()` `[inline]`, `[private]`

Cleanups.

7.4.3 Friends And Related Function Documentation

7.4.3.1 `friend class internal::Singleton< const Init >` `[friend]`

The documentation for this class was generated from the following file:

- [include/classes/init.h](#)

7.5 `qpp::internal::IOManipEigen` Class Reference

```
#include <iomanip.h>
```

Public Member Functions

- `template<typename Derived >`
`IOManipEigen` (`const Eigen::MatrixBase< Derived > &A`, `double chop=qpp::chop`)
- `IOManipEigen` (`const cplx z`, `double chop=qpp::chop`)

Private Attributes

- `cmat_A`
- `double _chop`

Friends

- `template<typename charT, typename traits >`
`std::basic_ostream< charT,`
`traits > &operator<< (std::basic_ostream< charT, traits > &os, const IOManipEigen &rhs)`

7.5.1 Constructor & Destructor Documentation

7.5.1.1 `template<typename Derived > qpp::internal::IOManipEigen::IOManipEigen (const Eigen::MatrixBase< Derived > &A, double chop = qpp::chop)` `[inline]`, `[explicit]`

7.5.1.2 `qpp::internal::IOManipEigen::IOManipEigen (const cplx z, double chop = qpp::chop)` `[inline]`, `[explicit]`

7.5.2 Friends And Related Function Documentation

7.5.2.1 `template<typename charT , typename traits > std::basic_ostream<charT, traits>& operator<< (std::basic_ostream< charT, traits > & os, const IOManipEigen & rhs) [friend]`

7.5.3 Member Data Documentation

7.5.3.1 `cmat qpp::internal::IOManipEigen::_A [private]`

7.5.3.2 `double qpp::internal::IOManipEigen::_chop [private]`


The documentation for this class was generated from the following file:

- [include/internal/classes/iomanip.h](#)

7.6 qpp::internal::IOManipPointer< PointerType > Class Template Reference

```
#include <iomanip.h>
```

Collaboration diagram for qpp::internal::IOManipPointer< PointerType >:



Public Member Functions

- [IOManipPointer](#) (const PointerType *p, const std::size_t n, const std::string &separator, const std::string &start="[", const std::string &end="]")
- [IOManipPointer](#) (const [IOManipPointer](#) &)=default
- [IOManipPointer](#) & [operator=](#) (const [IOManipPointer](#) &)=default

Private Attributes

- const PointerType * [_p](#)
- std::size_t [_n](#)

- `std::string _separator`
- `std::string _start`
- `std::string _end`

Friends

- `template<typename charT, typename traits >`
`std::basic_ostream< charT,`
`traits > & operator<< (std::basic_ostream< charT, traits > &os, const IOManipPointer &rhs)`

7.6.1 Constructor & Destructor Documentation

- 7.6.1.1 `template<typename PointerType > qpp::internal::IOManipPointer< PointerType >::IOManipPointer (const PointerType * p, const std::size_t n, const std::string & separator, const std::string & start = " [", const std::string & end = "] ") [inline],[explicit]`
- 7.6.1.2 `template<typename PointerType > qpp::internal::IOManipPointer< PointerType >::IOManipPointer (const IOManipPointer< PointerType > &) [default]`

7.6.2 Member Function Documentation

- 7.6.2.1 `template<typename PointerType > IOManipPointer& qpp::internal::IOManipPointer< PointerType >::operator= (const IOManipPointer< PointerType > &) [default]`

7.6.3 Friends And Related Function Documentation

- 7.6.3.1 `template<typename PointerType > template<typename charT, typename traits > std::basic_ostream<charT, traits>& operator<< (std::basic_ostream< charT, traits > & os, const IOManipPointer< PointerType > & rhs) [friend]`

7.6.4 Member Data Documentation

- 7.6.4.1 `template<typename PointerType > std::string qpp::internal::IOManipPointer< PointerType >::_end [private]`
- 7.6.4.2 `template<typename PointerType > std::size_t qpp::internal::IOManipPointer< PointerType >::_n [private]`
- 7.6.4.3 `template<typename PointerType > const PointerType* qpp::internal::IOManipPointer< PointerType >::_p [private]`
- 7.6.4.4 `template<typename PointerType > std::string qpp::internal::IOManipPointer< PointerType >::_separator [private]`
- 7.6.4.5 `template<typename PointerType > std::string qpp::internal::IOManipPointer< PointerType >::_start [private]`


The documentation for this class was generated from the following file:

- `include/internal/classes/iomanip.h`

7.7 `qpp::internal::IOManipRange< InputIterator >` Class Template Reference

```
#include <iomanip.h>
```

Collaboration diagram for qpp::internal::IOManipRange< InputIterator >:



Public Member Functions

- [IOManipRange](#) (InputIterator first, InputIterator last, const std::string &separator, const std::string &start="[, const std::string &end="]")

Private Attributes

- InputIterator [_first](#)
- InputIterator [_last](#)
- std::string [_separator](#)
- std::string [_start](#)
- std::string [_end](#)

Friends

- template<typename charT, typename traits >
std::basic_ostream< charT,
traits > & [operator<<](#) (std::basic_ostream< charT, traits > &os, const [IOManipRange](#) &rhs)

7.7.1 Constructor & Destructor Documentation

- 7.7.1.1 `template<typename InputIterator > qpp::internal::IOManipRange< InputIterator >::IOManipRange (InputIterator first, InputIterator last, const std::string & separator, const std::string & start = " [, const std::string & end = "]") [inline], [explicit]`

7.7.2 Friends And Related Function Documentation

7.7.2.1 `template<typename InputIterator > template<typename charT , typename traits > std::basic_ostream<charT, traits>& operator<< (std::basic_ostream< charT, traits > & os, const IManipRange< InputIterator > & rhs)`
`[friend]`

7.7.3 Member Data Documentation

7.7.3.1 `template<typename InputIterator > std::string qpp::internal::IManipRange< InputIterator >::_end`
`[private]`

7.7.3.2 `template<typename InputIterator > InputIterator qpp::internal::IManipRange< InputIterator >::_first`
`[private]`

7.7.3.3 `template<typename InputIterator > InputIterator qpp::internal::IManipRange< InputIterator >::_last`
`[private]`

7.7.3.4 `template<typename InputIterator > std::string qpp::internal::IManipRange< InputIterator >::_separator`
`[private]`

7.7.3.5 `template<typename InputIterator > std::string qpp::internal::IManipRange< InputIterator >::_start`
`[private]`

The documentation for this class was generated from the following file:


- `include/internal/classes/iomanip.h`

7.8 qpp::RandomDevices Class Reference


Singleton class that manages the source of randomness in the library.

`#include <random_devices.h>`

Inheritance diagram for `qpp::RandomDevices`:



Collaboration diagram for qpp::RandomDevices:



Public Attributes

- `std::mt19937 _rng`
Mersenne twister random number generator engine.

Private Member Functions

- `RandomDevices ()`
Initializes and seeds the random number generators.

Private Attributes

- `std::random_device _rd`
used to seed std::mt19937 _rng

Friends

- class `internal::Singleton< RandomDevices >`

Additional Inherited Members

7.8.1 Detailed Description

Singleton class that manages the source of randomness in the library.

It consists of a wrapper around an `std::mt19937` Mersenne twister random number generator engine and an `std::random_device` engine. The latter is used to seed the Mersenne twister. The class also seeds the standard `std::srand` C number generator, as it is used by Eigen.

7.8.2 Constructor & Destructor Documentation

7.8.2.1 `qpp::RandomDevices::RandomDevices ()` `[inline]`, `[private]`

Initializes and seeds the random number generators.

7.8.3 Friends And Related Function Documentation

7.8.3.1 friend class `internal::Singleton< RandomDevices >` [`friend`]

7.8.4 Member Data Documentation

7.8.4.1 `std::random_device qpp::RandomDevices::_rd` [`private`]

used to seed `std::mt19937 _rng`

7.8.4.2 `std::mt19937 qpp::RandomDevices::_rng`

Mersenne twister random number generator engine.

The documentation for this class was generated from the following file:

- `include/classes/random_devices.h`

7.9 `qpp::internal::Singleton< T >` Class Template Reference

`Singleton` policy class, used internally to implement the singleton pattern via CRTP (Curiously recurring template pattern)

```
#include <singleton.h>
```

Static Public Member Functions

- static `T & get_instance ()`

Protected Member Functions

- `Singleton ()`=default
- virtual `~Singleton ()`
- `Singleton (const Singleton &)=delete`
- `Singleton & operator= (const Singleton &)=delete`

7.9.1 Detailed Description

```
template<typename T>class qpp::internal::Singleton< T >
```

`Singleton` policy class, used internally to implement the singleton pattern via CRTP (Curiously recurring template pattern)

To implement a singleton, derive your class from `qpp::internal::Singleton`, make `qpp::internal::Singleton` a friend of your class, then declare the constructor of your class as private. To get an instance, use the static member function `qpp::internal::Singleton::get_instance()`, which returns a reference to your newly created singleton (thread-safe in C++11).

Example:

```
class MySingleton: public qpp::internal::Singleton<MySingleton>
{
    friend class qpp::internal::Singleton<MySingleton>;
public:
    // Declare all public members here
private:
    MySingleton()
```

```

    {
        // Implement the constructor here
    }
};

MySingleton& mySingleton = MySingleton::get_instance(); // Get an instance

```

See also

Code of [qpp::Codes](#), [qpp::Gates](#), [qpp::RandomDevices](#), [qpp::States](#) or [qpp.h](#) for real world examples of usage.

7.9.2 Constructor & Destructor Documentation

7.9.2.1 `template<typename T> qpp::internal::Singleton< T >::Singleton ()` [protected],[default]

7.9.2.2 `template<typename T> virtual qpp::internal::Singleton< T >::~~Singleton ()` [inline],[protected],[virtual]

7.9.2.3 `template<typename T> qpp::internal::Singleton< T >::Singleton (const Singleton< T > &)` [protected],[delete]

7.9.3 Member Function Documentation

7.9.3.1 `template<typename T> static T& qpp::internal::Singleton< T >::get_instance ()` [inline],[static]

7.9.3.2 `template<typename T> Singleton& qpp::internal::Singleton< T >::operator= (const Singleton< T > &)` [protected],[delete]

The documentation for this class was generated from the following file:


- [include/classes/singleton.h](#)

7.10 qpp::States Class Reference


const Singleton class that implements most commonly used states

```
#include <states.h>
```

Inheritance diagram for qpp::States:



Collaboration diagram for `qpp::States`:



Public Attributes

- `ket x0` {ket::Zero(2)}
Pauli Sigma-X 0-eigenstate $|+\rangle$
- `ket x1` {ket::Zero(2)}
Pauli Sigma-X 1-eigenstate $|-\rangle$
- `ket y0` {ket::Zero(2)}
Pauli Sigma-Y 0-eigenstate.
- `ket y1` {ket::Zero(2)}
Pauli Sigma-Y 1-eigenstate.
- `ket z0` {ket::Zero(2)}
Pauli Sigma-Z 0-eigenstate $|0\rangle$
- `ket z1` {ket::Zero(2)}
Pauli Sigma-Z 1-eigenstate $|1\rangle$
- `cmat px0` {cmat::Zero(2, 2)}
Projector onto the Pauli Sigma-X 0-eigenstate $|+\rangle\langle+|$.
- `cmat px1` {cmat::Zero(2, 2)}
Projector onto the Pauli Sigma-X 1-eigenstate $|-\rangle\langle-|$.
- `cmat py0` {cmat::Zero(2, 2)}
Projector onto the Pauli Sigma-Y 0-eigenstate.
- `cmat py1` {cmat::Zero(2, 2)}
Projector onto the Pauli Sigma-Y 1-eigenstate.
- `cmat pz0` {cmat::Zero(2, 2)}
Projector onto the Pauli Sigma-Z 0-eigenstate $|0\rangle\langle 0|$.
- `cmat pz1` {cmat::Zero(2, 2)}
Projector onto the Pauli Sigma-Z 1-eigenstate $|1\rangle\langle 1|$.
- `ket b00` {ket::Zero(4)}
Bell-00 state (following the convention in Nielsen and Chuang)
- `ket b01` {ket::Zero(4)}
Bell-01 state (following the convention in Nielsen and Chuang)
- `ket b10` {ket::Zero(4)}
Bell-10 state (following the convention in Nielsen and Chuang)
- `ket b11` {ket::Zero(4)}
Bell-11 state (following the convention in Nielsen and Chuang)
- `cmat pb00` {cmat::Zero(4, 4)}

- Projector onto the Bell-00 state.*
- [cmat pb01](#) {cmat::Zero(4, 4)}
- Projector onto the Bell-01 state.*
- [cmat pb10](#) {cmat::Zero(4, 4)}
- Projector onto the Bell-10 state.*
- [cmat pb11](#) {cmat::Zero(4, 4)}
- Projector onto the Bell-11 state.*
- [ket GHZ](#) {ket::Zero(8)}
- GHZ state.*
- [ket W](#) {ket::Zero(8)}
- W state.*
- [cmat pGHZ](#) {cmat::Zero(8, 8)}
- Projector onto the GHZ state.*
- [cmat pW](#) {cmat::Zero(8, 8)}
- Projector onto the W state.*

Private Member Functions

- [States](#) ()

Friends

- class [internal::Singleton< const States >](#)

Additional Inherited Members

7.10.1 Detailed Description

const Singleton class that implements most commonly used states

7.10.2 Constructor & Destructor Documentation

7.10.2.1 [qpp::States::States \(\)](#) [inline], [private]

Initialize the states

7.10.3 Friends And Related Function Documentation

7.10.3.1 [friend class internal::Singleton< const States >](#) [friend]

7.10.4 Member Data Documentation

7.10.4.1 [ket qpp::States::b00](#) {ket::Zero(4)}

Bell-00 state (following the convention in Nielsen and Chuang)

7.10.4.2 [ket qpp::States::b01](#) {ket::Zero(4)}

Bell-01 state (following the convention in Nielsen and Chuang)

7.10.4.3 `ket qpp::States::b10 {ket::Zero(4)}`

Bell-10 state (following the convention in Nielsen and Chuang)

7.10.4.4 `ket qpp::States::b11 {ket::Zero(4)}`

Bell-11 state (following the convention in Nielsen and Chuang)

7.10.4.5 `ket qpp::States::GHZ {ket::Zero(8)}`

GHZ state.

7.10.4.6 `cmat qpp::States::pb00 {cmat::Zero(4, 4)}`

Projector onto the Bell-00 state.

7.10.4.7 `cmat qpp::States::pb01 {cmat::Zero(4, 4)}`

Projector onto the Bell-01 state.

7.10.4.8 `cmat qpp::States::pb10 {cmat::Zero(4, 4)}`

Projector onto the Bell-10 state.

7.10.4.9 `cmat qpp::States::pb11 {cmat::Zero(4, 4)}`

Projector onto the Bell-11 state.

7.10.4.10 `cmat qpp::States::pGHZ {cmat::Zero(8, 8)}`

Projector onto the GHZ state.

7.10.4.11 `cmat qpp::States::pW {cmat::Zero(8, 8)}`

Projector onto the W state.

7.10.4.12 `cmat qpp::States::px0 {cmat::Zero(2, 2)}`

Projector onto the Pauli Sigma-X 0-eigenstate $|+\rangle\langle+|$.

7.10.4.13 `cmat qpp::States::px1 {cmat::Zero(2, 2)}`

Projector onto the Pauli Sigma-X 1-eigenstate $|-\rangle\langle-|$.

7.10.4.14 `cmat qpp::States::py0 {cmat::Zero(2, 2)}`

Projector onto the Pauli Sigma-Y 0-eigenstate.

7.10.4.15 `cmat qpp::States::py1 {cmat::Zero(2, 2)}`

Projector onto the Pauli Sigma-Y 1-eigenstate.

7.10.4.16 `cmat qpp::States::pz0 {cmat::Zero(2, 2)}`

Projector onto the Pauli Sigma-Z 0-eigenstate $|0\rangle\langle 0|$.

7.10.4.17 `cmat qpp::States::pz1 {cmat::Zero(2, 2)}`

Projector onto the Pauli Sigma-Z 1-eigenstate $|1\rangle\langle 1|$.

7.10.4.18 `ket qpp::States::W {ket::Zero(8)}`

W state.

7.10.4.19 `ket qpp::States::x0 {ket::Zero(2)}`

Pauli Sigma-X 0-eigenstate $|+\rangle$

7.10.4.20 `ket qpp::States::x1 {ket::Zero(2)}`

Pauli Sigma-X 1-eigenstate $|-\rangle$

7.10.4.21 `ket qpp::States::y0 {ket::Zero(2)}`

Pauli Sigma-Y 0-eigenstate.

7.10.4.22 `ket qpp::States::y1 {ket::Zero(2)}`

Pauli Sigma-Y 1-eigenstate.

7.10.4.23 `ket qpp::States::z0 {ket::Zero(2)}`

Pauli Sigma-Z 0-eigenstate $|0\rangle$

7.10.4.24 `ket qpp::States::z1 {ket::Zero(2)}`

Pauli Sigma-Z 1-eigenstate $|1\rangle$

The documentation for this class was generated from the following file:

- [include/classes/states.h](#)

7.11 qpp::Timer Class Reference

Measures time.

```
#include <timer.h>
```

Public Member Functions

- [Timer](#) ()
Constructs an instance with the current time as the starting point.
- void [tic](#) ()
Resets the chronometer.
- const [Timer](#) & [toc](#) ()
Stops the chronometer.
- double [seconds](#) () const
Time passed in seconds.

Protected Attributes

- std::chrono::steady_clock::time_point [_start](#)
- std::chrono::steady_clock::time_point [_end](#)

Friends

- std::ostream & [operator<<](#) (std::ostream &os, const [Timer](#) &rhs)
Overload for std::ostream operators.

7.11.1 Detailed Description

Measures time.

Uses a std::chrono::steady_clock. It is not affected by wall clock changes during runtime.

7.11.2 Constructor & Destructor Documentation

7.11.2.1 `qpp::Timer::Timer ()` `[inline]`

Constructs an instance with the current time as the starting point.

7.11.3 Member Function Documentation

7.11.3.1 `double qpp::Timer::seconds ()` `const` `[inline]`

Time passed in seconds.

Returns

Number of seconds that passed between the instantiation/reset and invocation of `qpp::Timer::toc()`

7.11.3.2 `void qpp::Timer::tic ()` `[inline]`

Resets the chronometer.

Resets the starting/ending point to the current time

7.11.3.3 const Timer& qpp::Timer::toc () [inline]

Stops the chronometer.

Set the current time as the ending point

Returns

Current instance

7.11.4 Friends And Related Function Documentation

7.11.4.1 std::ostream& operator<< (std::ostream & *os*, const Timer & *rhs*) [friend]

Overload for std::ostream operators.

Parameters

<i>os</i>	Output stream
<i>rhs</i>	Timer instance

Returns

Writes to the output stream the number of seconds that passed between the instantiation/reset and invocation of [qpp::Timer::toc\(\)](#).

7.11.5 Member Data Documentation

7.11.5.1 std::chrono::steady_clock::time_point qpp::Timer::_end [protected]

7.11.5.2 std::chrono::steady_clock::time_point qpp::Timer::_start [protected]

The documentation for this class was generated from the following file:


- include/classes/[timer.h](#)

Chapter 8

File Documentation

8.1 include/classes/codes.h File Reference

This graph shows which files directly or indirectly include this file:



Classes

- class [qpp::Codes](#)


const Singleton class that defines quantum error correcting codes

Namespaces

- [qpp](#)

8.2 include/classes/exception.h File Reference

This graph shows which files directly or indirectly include this file:



Classes


- class [qpp::Exception](#)
Generates custom exceptions, used when validating function parameters.

Namespaces

- [qpp](#)

8.3 include/classes/gates.h File Reference

This graph shows which files directly or indirectly include this file:



Classes


- class [qpp::Gates](#)
const Singleton class that implements most commonly used gates

Namespaces

- [qpp](#)

8.4 include/classes/init.h File Reference

This graph shows which files directly or indirectly include this file:



Classes


- class [qpp::Init](#)
const Singleton class that performs additional initializations/cleanups

Namespaces

- [qpp](#)

8.5 include/classes/random_devices.h File Reference

This graph shows which files directly or indirectly include this file:



Classes

- class [qpp::RandomDevices](#)


Singleton class that manages the source of randomness in the library.

Namespaces

- [qpp](#)

8.6 include/classes/singleton.h File Reference

This graph shows which files directly or indirectly include this file:



Classes

- class [qpp::internal::Singleton< T >](#)


[Singleton](#) policy class, used internally to implement the singleton pattern via CRTP (Curiously recurring template pattern)

Namespaces

- [qpp](#)
- [qpp::internal](#)

8.7 include/classes/states.h File Reference

This graph shows which files directly or indirectly include this file:



Classes


- class [qpp::States](#)
const Singleton class that implements most commonly used states

Namespaces

- [qpp](#)

8.8 include/classes/timer.h File Reference

This graph shows which files directly or indirectly include this file:



Classes


- class [qpp::Timer](#)
Measures time.

Namespaces

- [qpp](#)

8.9 include/constants.h File Reference

This graph shows which files directly or indirectly include this file:



Namespaces

- [qpp](#)

Functions


- constexpr std::complex< double > [qpp::operator""_i](#) (unsigned long long int x)
User-defined literal for complex $i = \sqrt{-1}$ (integer overload)
- constexpr std::complex< double > [qpp::operator""_i](#) (long double x)
User-defined literal for complex $i = \sqrt{-1}$ (real overload)
- std::complex< double > [qpp::omega](#) (std::size_t D)
D-th root of unity.

Variables

- constexpr double [qpp::chop](#) = 1e-10
Used in [qpp::disp\(\)](#) and [qpp::displn\(\)](#) for setting to zero numbers that have their absolute value smaller than [qpp::ct->::chop](#).
- constexpr double [qpp::eps](#) = 1e-12
Used to decide whether a number or expression in double precision is zero or not.
- constexpr std::size_t [qpp::maxn](#) = 64
Maximum number of qubits.
- constexpr double [qpp::pi](#) = 3.141592653589793238462643383279502884
 π
- constexpr double [qpp::ee](#) = 2.718281828459045235360287471352662497
Base of natural logarithm, e .
- constexpr std::size_t [qpp::infy](#) = -1
Used to denote infinity.

8.10 include/entanglement.h File Reference

This graph shows which files directly or indirectly include this file:



Namespaces


- [qpp](#)

Functions

- `template<typename Derived >`
`DynColVect< cplx > qpp::schmidtcoeff (const Eigen::MatrixBase< Derived > &A, const std::vector< std::size_t > &dims)`
Schmidt coefficients of the bi-partite pure state A.
- `template<typename Derived >`
`cmat qpp::schmidtU (const Eigen::MatrixBase< Derived > &A, const std::vector< std::size_t > &dims)`
Schmidt basis on Alice's side.
- `template<typename Derived >`
`cmat qpp::schmidtV (const Eigen::MatrixBase< Derived > &A, const std::vector< std::size_t > &dims)`
Schmidt basis on Bob's side.
- `template<typename Derived >`
`DynColVect< double > qpp::schmidtprob (const Eigen::MatrixBase< Derived > &A, const std::vector< std::size_t > &dims)`
Schmidt probabilities of the bi-partite pure state A.
- `template<typename Derived >`
`double qpp::entanglement (const Eigen::MatrixBase< Derived > &A, const std::vector< std::size_t > &dims)`
Entanglement of the bi-partite pure state A.
- `template<typename Derived >`
`double qpp::gconcurrence (const Eigen::MatrixBase< Derived > &A)`
G-concurrence of the bi-partite pure state A.
- `template<typename Derived >`
`double qpp::negativity (const Eigen::MatrixBase< Derived > &A, const std::vector< std::size_t > &dims)`
Negativity of the bi-partite mixed state A.
- `template<typename Derived >`
`double qpp::lognegativity (const Eigen::MatrixBase< Derived > &A, const std::vector< std::size_t > &dims)`
Logarithmic negativity of the bi-partite mixed state A.
- `template<typename Derived >`
`double qpp::concurrence (const Eigen::MatrixBase< Derived > &A)`
Wootters concurrence of the bi-partite qubit mixed state A.

8.11 include/entropies.h File Reference

This graph shows which files directly or indirectly include this file:



Namespaces

- [qpp](#)

Functions

- `template<typename Derived >`
`double qpp::shannon (const Eigen::MatrixBase< Derived > &A)`
Shannon/von-Neumann entropy of the probability distribution/density matrix A.
- `template<typename Derived >`
`double qpp::renyi (const Eigen::MatrixBase< Derived > &A, double alpha)`
Renyi- α entropy of the probability distribution/density matrix A, for $\alpha \geq 0$.
- `template<typename Derived >`
`double qpp::tsallis (const Eigen::MatrixBase< Derived > &A, double alpha)`
Tsallis- α entropy of the probability distribution/density matrix A, for $\alpha \geq 0$.
- `template<typename Derived >`
`double qpp::qmutualinfo (const Eigen::MatrixBase< Derived > &A, const std::vector< std::size_t > &subsysA, const std::vector< std::size_t > &subsysB, const std::vector< std::size_t > &dims)`
Quantum mutual information between 2 subsystems of a composite system.


8.12 include/experimental/test.h File Reference

Namespaces

- [qpp::experimental](#)
- [qpp](#)

8.13 include/functions.h File Reference

This graph shows which files directly or indirectly include this file:



Namespaces

- [qpp](#)

Functions

- `template<typename Derived >`
`DynMat< typename Derived::Scalar > qpp::transpose (const Eigen::MatrixBase< Derived > &A)`
Transpose.
- `template<typename Derived >`
`DynMat< typename Derived::Scalar > qpp::conjugate (const Eigen::MatrixBase< Derived > &A)`
Complex conjugate.
- `template<typename Derived >`
`DynMat< typename Derived::Scalar > qpp::adjoint (const Eigen::MatrixBase< Derived > &A)`
Adjoint.
- `template<typename Derived >`
`DynMat< typename Derived::Scalar > qpp::inverse (const Eigen::MatrixBase< Derived > &A)`
Inverse.
- `template<typename Derived >`
`Derived::Scalar qpp::trace (const Eigen::MatrixBase< Derived > &A)`
Trace.
- `template<typename Derived >`
`Derived::Scalar qpp::det (const Eigen::MatrixBase< Derived > &A)`
Determinant.
- `template<typename Derived >`
`Derived::Scalar qpp::logdet (const Eigen::MatrixBase< Derived > &A)`
Logarithm of the determinant.
- `template<typename Derived >`
`Derived::Scalar qpp::sum (const Eigen::MatrixBase< Derived > &A)`
Element-wise sum of A.
- `template<typename Derived >`
`Derived::Scalar qpp::prod (const Eigen::MatrixBase< Derived > &A)`
Element-wise product of A.
- `template<typename Derived >`
`double qpp::norm (const Eigen::MatrixBase< Derived > &A)`

Frobenius norm.

- `template<typename Derived >`
`DynColVect< cplx > qpp::evals (const Eigen::MatrixBase< Derived > &A)`

Eigenvalues.

- `template<typename Derived >`
`cmat qpp::evecs (const Eigen::MatrixBase< Derived > &A)`

Eigenvectors.

- `template<typename Derived >`
`DynColVect< double > qpp::hevals (const Eigen::MatrixBase< Derived > &A)`

Hermitian eigenvalues.

- `template<typename Derived >`
`cmat qpp::hevecs (const Eigen::MatrixBase< Derived > &A)`

Hermitian eigenvectors.

- `template<typename Derived >`
`DynColVect< double > qpp::svals (const Eigen::MatrixBase< Derived > &A)`

Singular values.

- `template<typename Derived >`
`cmat qpp::svdU (const Eigen::MatrixBase< Derived > &A)`

Left singular vectors.

- `template<typename Derived >`
`cmat qpp::svdV (const Eigen::MatrixBase< Derived > &A)`

Right singular vectors.

- `template<typename Derived >`
`cmat qpp::funm (const Eigen::MatrixBase< Derived > &A, cplx(*f)(const cplx &))`

Functional calculus $f(A)$

- `template<typename Derived >`
`cmat qpp::sqrtm (const Eigen::MatrixBase< Derived > &A)`

Matrix square root.

- `template<typename Derived >`
`cmat qpp::absm (const Eigen::MatrixBase< Derived > &A)`

Matrix absolut value.

- `template<typename Derived >`
`cmat qpp::expm (const Eigen::MatrixBase< Derived > &A)`

Matrix exponential.

- `template<typename Derived >`
`cmat qpp::logm (const Eigen::MatrixBase< Derived > &A)`

Matrix logarithm.

- `template<typename Derived >`
`cmat qpp::sinm (const Eigen::MatrixBase< Derived > &A)`

Matrix sin.

- `template<typename Derived >`
`cmat qpp::cosm (const Eigen::MatrixBase< Derived > &A)`

Matrix cos.

- `template<typename Derived >`
`cmat qpp::spectralpowm (const Eigen::MatrixBase< Derived > &A, const cplx z)`

Matrix power.

- `template<typename Derived >`
`DynMat< typename Derived::Scalar > qpp::powm (const Eigen::MatrixBase< Derived > &A, std::size_t n)`

Matrix power.

- `template<typename Derived >`
`double qpp::schatten (const Eigen::MatrixBase< Derived > &A, std::size_t p)`

Schatten norm.

- `template<typename OutputScalar , typename Derived >`
`DynMat< OutputScalar > qpp::cwise (const Eigen::MatrixBase< Derived > &A, OutputScalar(*f)(const type-
name Derived::Scalar &))`
Functor.
- `template<typename T >`
`DynMat< typename T::Scalar > qpp::kron (const T &head)`
Kronecker product.
- `template<typename T , typename... Args>`
`DynMat< typename T::Scalar > qpp::kron (const T &head, const Args &...tail)`
Kronecker product.
- `template<typename Derived >`
`DynMat< typename Derived::Scalar > qpp::kron (const std::vector< Derived > &As)`
Kronecker product.
- `template<typename Derived >`
`DynMat< typename Derived::Scalar > qpp::kron (const std::initializer_list< Derived > &As)`
Kronecker product.
- `template<typename Derived >`
`DynMat< typename Derived::Scalar > qpp::kronpow (const Eigen::MatrixBase< Derived > &A, std::size_t
n)`
Kronecker power.
- `template<typename Derived >`
`DynMat< typename Derived::Scalar > qpp::reshape (const Eigen::MatrixBase< Derived > &A, std::size_t
rows, std::size_t cols)`
Reshape.
- `template<typename Derived1 , typename Derived2 >`
`DynMat< typename Derived1::Scalar > qpp::comm (const Eigen::MatrixBase< Derived1 > &A, const
Eigen::MatrixBase< Derived2 > &B)`
Commutator.
- `template<typename Derived1 , typename Derived2 >`
`DynMat< typename Derived1::Scalar > qpp::anticomm (const Eigen::MatrixBase< Derived1 > &A, const
Eigen::MatrixBase< Derived2 > &B)`
Anti-commutator.
- `template<typename Derived >`
`DynMat< typename Derived::Scalar > qpp::prj (const Eigen::MatrixBase< Derived > &V)`
Projector.
- `template<typename Derived >`
`DynMat< typename Derived::Scalar > qpp::grams (const std::vector< Derived > &Vs)`
Gram-Schmidt orthogonalization.
- `template<typename Derived >`
`DynMat< typename Derived::Scalar > qpp::grams (const std::initializer_list< Derived > &Vs)`
Gram-Schmidt orthogonalization.
- `template<typename Derived >`
`DynMat< typename Derived::Scalar > qpp::grams (const Eigen::MatrixBase< Derived > &A)`
Gram-Schmidt orthogonalization.
- `std::vector< std::size_t > qpp::n2multiidx (std::size_t n, const std::vector< std::size_t > &dims)`
Non-negative integer index to multi-index.
- `std::size_t qpp::multiidx2n (const std::vector< std::size_t > &midx, const std::vector< std::size_t > &dims)`
Multi-index to non-negative integer index.
- `ket qpp::mket (const std::vector< std::size_t > &mask, const std::vector< std::size_t > &dims)`
Multi-partite qudit ket.
- `ket qpp::mket (const std::vector< std::size_t > &mask, std::size_t d=2)`
Multi-partite qudit ket.
- `cmat qpp::mprj (const std::vector< std::size_t > &mask, const std::vector< std::size_t > &dims)`

- Projector onto multi-partite qudit ket.*

• `cmat qpp::mprj (const std::vector< std::size_t > &mask, std::size_t d=2)`

Projector onto multi-partite qudit ket.
- `template<typename InputIterator >`
`std::vector< double > qpp::abssq (InputIterator first, InputIterator last)`

Computes the absolut values squared of a range of complex numbers.
- `template<typename Derived >`
`std::vector< double > qpp::abssq (const Eigen::MatrixBase< Derived > &V)`

Computes the absolut values squared of a column vector.
- `template<typename InputIterator >`
`auto qpp::sum (InputIterator first, InputIterator last) -> typename InputIterator::value_type`


Element-wise sum of a range.
- `template<typename InputIterator >`
`auto qpp::prod (InputIterator first, InputIterator last) -> typename InputIterator::value_type`

Element-wise product of a range.
- `template<typename Derived >`
`DynColVect< typename`
`Derived::Scalar > qpp::rho2pure (const Eigen::MatrixBase< Derived > &A)`

Finds the pure state representation of a matrix proportional to a projector onto a pure state.

8.14 include/internal/functions.h File Reference

This graph shows which files directly or indirectly include this file:



Namespaces

- [qpp::internal](#)
- [qpp](#)


Functions

- `void qpp::internal::_n2multiidx (std::size_t n, std::size_t numdims, const std::size_t *dims, std::size_t *result)`
- `std::size_t qpp::internal::_multiidx2n (const std::size_t *midx, std::size_t numdims, const std::size_t *dims)`
- `template<typename Derived >`
`bool qpp::internal::_check_square_mat (const Eigen::MatrixBase< Derived > &A)`
- `template<typename Derived >`
`bool qpp::internal::_check_vector (const Eigen::MatrixBase< Derived > &A)`

- template<typename Derived >
bool [qpp::internal::_check_row_vector](#) (const Eigen::MatrixBase< Derived > &A)
- template<typename Derived >
bool [qpp::internal::_check_col_vector](#) (const Eigen::MatrixBase< Derived > &A)
- template<typename T >
bool [qpp::internal::_check_nonzero_size](#) (const T &x)
- bool [qpp::internal::_check_dims](#) (const std::vector< std::size_t > &dims)
- template<typename Derived >
bool [qpp::internal::_check_dims_match_mat](#) (const std::vector< std::size_t > &dims, const Eigen::MatrixBase< Derived > &A)
- template<typename Derived >
bool [qpp::internal::_check_dims_match_cvect](#) (const std::vector< std::size_t > &dims, const Eigen::MatrixBase< Derived > &V)
- template<typename Derived >
bool [qpp::internal::_check_dims_match_rvect](#) (const std::vector< std::size_t > &dims, const Eigen::MatrixBase< Derived > &V)
- bool [qpp::internal::_check_eq_dims](#) (const std::vector< std::size_t > &dims, std::size_t dim)
- bool [qpp::internal::_check_subsys_match_dims](#) (const std::vector< std::size_t > &subsys, const std::vector< std::size_t > &dims)
- bool [qpp::internal::_check_perm](#) (const std::vector< std::size_t > &perm)
- template<typename Derived1 , typename Derived2 >
DynMat< typename Derived1::Scalar > [qpp::internal::_kron2](#) (const Eigen::MatrixBase< Derived1 > &A, const Eigen::MatrixBase< Derived2 > &B)
- template<typename T >
void [qpp::internal::variadic_vector_emplace](#) (std::vector< T > &)
- template<typename T , typename First , typename... Args>
void [qpp::internal::variadic_vector_emplace](#) (std::vector< T > &v, First &&first, Args &&...args)

8.15 include/input_output.h File Reference

This graph shows which files directly or indirectly include this file:



Namespaces

- [qpp](#)

Functions

- template<typename Derived >
internal::IOManipEigen [qpp::disp](#) (const Eigen::MatrixBase< Derived > &A, double chop=[qpp::chop](#))

Eigen expression ostream manipulator.

- `internal::IOManipEigen qpp::disp (cplx z, double chop=qpp::chop)`

Complex number ostream manipulator.

- `template<typename InputIterator >
internal::IOManipRange
< InputIterator > qpp::disp (const InputIterator &first, const InputIterator &last, const std::string &separator,
const std::string &start="[" , const std::string &end="]")`

Range ostream manipulator.

- `template<typename Container >
internal::IOManipRange
< typename
Container::const_iterator > qpp::disp (const Container &c, const std::string &separator, const std::string
&start="[" , const std::string &end="]")`

Standard container ostream manipulator. The container must support `std::begin()`, `std::end()` and forward iteration.

- `template<typename PointerType >
internal::IOManipPointer
< PointerType > qpp::disp (const PointerType *p, std::size_t n, const std::string &separator, const std::string
&start="[" , const std::string &end="]")`

C-style pointer ostream manipulator.

- `template<typename Derived >
void qpp::save (const Eigen::MatrixBase< Derived > &A, const std::string &fname)`


Saves Eigen expression to a binary file (internal format) in double precision.

- `template<typename Derived >
DynMat< typename Derived::Scalar > qpp::load (const std::string &fname)`

Loads Eigen matrix from a binary file (internal format) in double precision.

8.16 include/instruments.h File Reference

This graph shows which files directly or indirectly include this file:



Namespaces


- [qpp](#)

Functions

- `template<typename Derived >`
`std::tuple< std::size_t,`
`std::vector< double >`
`, std::vector< cmat > > qpp::measure (const Eigen::MatrixBase< Derived > &A, const std::vector< cmat >`
`&Ks, const std::vector< std::size_t > &subsys, const std::vector< std::size_t > &dims)`
Measures the part subsys of the multi-partite state vector or density matrix A using the set of Kraus operators Ks.
- `template<typename Derived >`
`std::tuple< std::size_t,`
`std::vector< double >`
`, std::vector< cmat > > qpp::measure (const Eigen::MatrixBase< Derived > &A, const std::initializer_list<`
`cmat > &Ks, const std::vector< std::size_t > &subsys, const std::vector< std::size_t > &dims)`
Measures the part subsys of the multi-partite state vector or density matrix A using the set of Kraus operators Ks.
- `template<typename Derived >`
`std::tuple< std::size_t,`
`std::vector< double >`
`, std::vector< cmat > > qpp::measure (const Eigen::MatrixBase< Derived > &A, const std::vector< cmat >`
`&Ks, const std::vector< std::size_t > &subsys, const std::size_t d=2)`
Measures the part subsys of the multi-partite state vector or density matrix A using the set of Kraus operators Ks.
- `template<typename Derived >`
`std::tuple< std::size_t,`
`std::vector< double >`
`, std::vector< cmat > > qpp::measure (const Eigen::MatrixBase< Derived > &A, const std::initializer_list<`
`cmat > &Ks, const std::vector< std::size_t > &subsys, const std::size_t d=2)`
Measures the part subsys of the multi-partite state vector or density matrix A using the set of Kraus operators Ks.
- `template<typename Derived >`
`std::tuple< std::size_t,`
`std::vector< double >`
`, std::vector< cmat > > qpp::measure (const Eigen::MatrixBase< Derived > &A, const cmat &U, const`
`std::vector< std::size_t > &subsys, const std::vector< std::size_t > &dims)`
Measures the part subsys of the multi-partite state A in the orthonormal basis specified by the unitary matrix U.
- `template<typename Derived >`
`std::tuple< std::size_t,`
`std::vector< double >`
`, std::vector< cmat > > qpp::measure (const Eigen::MatrixBase< Derived > &A, const cmat &U, const`
`std::vector< std::size_t > &subsys, const std::size_t d=2)`
Measures the part subsys of the multi-partite state A in the orthonormal basis specified by the unitary matrix U.
- `template<typename Derived >`
`std::tuple< std::size_t,`
`std::vector< double >`
`, std::vector< cmat > > qpp::measure (const Eigen::MatrixBase< Derived > &A, const std::vector< cmat >`
`&Ks)`
Measures the state A using the set of Kraus operators Ks.
- `template<typename Derived >`
`std::tuple< std::size_t,`
`std::vector< double >`
`, std::vector< cmat > > qpp::measure (const Eigen::MatrixBase< Derived > &A, const std::initializer_list<`
`cmat > &Ks)`
Measures the state A using the set of Kraus operators Ks.
- `template<typename Derived >`
`std::tuple< std::size_t,`
`std::vector< double >`
`, std::vector< cmat > > qpp::measure (const Eigen::MatrixBase< Derived > &A, const cmat &U)`
Measures the state A in the orthonormal basis specified by the unitary matrix U.

8.17 include/internal/classes/iomanip.h File Reference

This graph shows which files directly or indirectly include this file:



Classes

- class [qpp::internal::IOManipRange< InputIterator >](#)
- class [qpp::internal::IOManipPointer< PointerType >](#)
- class [qpp::internal::IOManipEigen](#)

Namespaces

- [qpp](#)
- [qpp::internal](#)

8.18 include/MATLAB/matlab.h File Reference

```
#include "mat.h"
#include "mex.h"
```

Namespaces

- [qpp](#)


Functions

- template<typename Derived >
Derived [qpp::loadMATLABmatrix](#) (const std::string &mat_file, const std::string &var_name)
Loads an Eigen dynamic matrix from a MATLAB .mat file, generic version.
- template<>
dmat [qpp::loadMATLABmatrix](#) (const std::string &mat_file, const std::string &var_name)
Loads an Eigen dynamic matrix from a MATLAB .mat file, specialization for double matrices ([qpp::dmat](#))
- template<>
cmat [qpp::loadMATLABmatrix](#) (const std::string &mat_file, const std::string &var_name)
Loads an Eigen dynamic matrix from a MATLAB .mat file, specialization for complex matrices ([qpp::cmat](#))

- `template<typename Derived >`
`void qpp::saveMATLABmatrix (const Eigen::MatrixBase< Derived > &A, const std::string &mat_file, const std::string &var_name, const std::string &mode)`
Saves an Eigen dynamic matrix to a MATLAB .mat file, generic version.
- `template<>`
`void qpp::saveMATLABmatrix (const Eigen::MatrixBase< dmat > &A, const std::string &mat_file, const std::string &var_name, const std::string &mode)`
Saves an Eigen dynamic matrix to a MATLAB .mat file, specialization for double matrices ([qpp::dmat](#))
- `template<>`
`void qpp::saveMATLABmatrix (const Eigen::MatrixBase< cmat > &A, const std::string &mat_file, const std::string &var_name, const std::string &mode)`
Saves an Eigen dynamic matrix to a MATLAB .mat file, specialization for complex matrices ([qpp::cmat](#))

8.19 include/number_theory.h File Reference

This graph shows which files directly or indirectly include this file:



Namespaces

- [qpp](#)


Functions

- `std::vector< int > qpp::x2contfrac (double x, std::size_t n, std::size_t cut=1e5)`
Simple continued fraction expansion.
- `double qpp::contfrac2x (const std::vector< int > &cf, std::size_t n)`
Real representation of a simple continued fraction.
- `double qpp::contfrac2x (const std::vector< int > &cf)`
Real representation of a simple continued fraction.
- `std::size_t qpp::gcd (std::size_t m, std::size_t n)`
Greatest common divisor of two non-negative integers.
- `std::size_t qpp::gcd (const std::vector< std::size_t > &ns)`
Greatest common divisor of a list of non-negative integers.
- `std::size_t qpp::lcm (std::size_t m, std::size_t n)`
Least common multiple of two positive integers.
- `std::size_t qpp::lcm (const std::vector< std::size_t > &ns)`
Least common multiple of a list of positive integers.

- `std::vector< std::size_t > qpp::invperm (const std::vector< std::size_t > &perm)`
Inverse permutation.
- `std::vector< std::size_t > qpp::compperm (const std::vector< std::size_t > &perm, const std::vector< std::size_t > &sigma)`
Compose permutations.

8.20 include/operations.h File Reference

This graph shows which files directly or indirectly include this file:



Namespaces

- [qpp](#)

Functions

- `template<typename Derived1 , typename Derived2 >`
`DynMat< typename Derived1::Scalar > qpp::applyCTRL (const Eigen::MatrixBase< Derived1 > &state, const Eigen::MatrixBase< Derived2 > &A, const std::vector< std::size_t > &ctrl, const std::vector< std::size_t > &subsys, const std::vector< std::size_t > &dims)`
Applies the controlled-gate A to the part subsys of the multi-partite state vector or density matrix state.
- `template<typename Derived1 , typename Derived2 >`
`DynMat< typename Derived1::Scalar > qpp::applyCTRL (const Eigen::MatrixBase< Derived1 > &state, const Eigen::MatrixBase< Derived2 > &A, const std::vector< std::size_t > &ctrl, const std::vector< std::size_t > &subsys, std::size_t d=2)`
Applies the controlled-gate A to the part subsys of the multi-partite state vector or density matrix state.
- `template<typename Derived1 , typename Derived2 >`
`DynMat< typename Derived1::Scalar > qpp::apply (const Eigen::MatrixBase< Derived1 > &state, const Eigen::MatrixBase< Derived2 > &A, const std::vector< std::size_t > &subsys, const std::vector< std::size_t > &dims)`
Applies the gate A to the part subsys of the multi-partite state vector or density matrix state.
- `template<typename Derived1 , typename Derived2 >`
`DynMat< typename Derived1::Scalar > qpp::apply (const Eigen::MatrixBase< Derived1 > &state, const Eigen::MatrixBase< Derived2 > &A, const std::vector< std::size_t > &subsys, std::size_t d=2)`
Applies the gate A to the part subsys of the multi-partite state vector or density matrix state.
- `template<typename Derived >`
`cmat qpp::channel (const Eigen::MatrixBase< Derived > &rho, const std::vector< cmat > &Ks)`
Applies the channel specified by the set of Kraus operators Ks to the density matrix rho.

- template<typename Derived >
cmat [qpp::channel](#) (const Eigen::MatrixBase< Derived > &rho, const std::vector< cmat > &Ks, const std::vector< std::size_t > &subsys, const std::vector< std::size_t > &dims)

Applies the channel specified by the set of Kraus operators Ks to the part subsys of the multi-partite density matrix rho.

- template<typename Derived >
cmat [qpp::channel](#) (const Eigen::MatrixBase< Derived > &rho, const std::vector< cmat > &Ks, const std::vector< std::size_t > &subsys, std::size_t d=2)

Applies the channel specified by the set of Kraus operators Ks to the part subsys of the multi-partite density matrix rho.

- cmat [qpp::super](#) (const std::vector< cmat > &Ks)

Superoperator matrix representation.

- cmat [qpp::choi](#) (const std::vector< cmat > &Ks)

Choi matrix representation.

- std::vector< cmat > [qpp::choi2kraus](#) (const cmat &A)

Extracts orthogonal Kraus operators from Choi matrix.

- template<typename Derived >
DynMat< typename Derived::Scalar > [qpp::ptrace1](#) (const Eigen::MatrixBase< Derived > &A, const std::vector< std::size_t > &dims)

Partial trace.

- template<typename Derived >
DynMat< typename Derived::Scalar > [qpp::ptrace2](#) (const Eigen::MatrixBase< Derived > &A, const std::vector< std::size_t > &dims)

Partial trace.

- template<typename Derived >
DynMat< typename Derived::Scalar > [qpp::ptrace](#) (const Eigen::MatrixBase< Derived > &A, const std::vector< std::size_t > &subsys, const std::vector< std::size_t > &dims)

Partial trace.

- template<typename Derived >
DynMat< typename Derived::Scalar > [qpp::ptranspose](#) (const Eigen::MatrixBase< Derived > &A, const std::vector< std::size_t > &subsys, const std::vector< std::size_t > &dims)

Partial transpose.

- template<typename Derived >
DynMat< typename Derived::Scalar > [qpp::syspermute](#) (const Eigen::MatrixBase< Derived > &A, const std::vector< std::size_t > &perm, const std::vector< std::size_t > &dims)

System permutation.

8.21 include/qpp.h File Reference

```
#include <algorithm>
#include <chrono>
#include <cmath>
#include <complex>
#include <cstdlib>
#include <cstring>
#include <ctime>
#include <exception>
#include <fstream>
#include <functional>
#include <initializer_list>
#include <iomanip>
#include <iostream>
#include <iterator>
#include <limits>
#include <numeric>
#include <ostream>
#include <random>
#include <sstream>
#include <stdexcept>
#include <string>
#include <tuple>
#include <type_traits>
#include <utility>
#include <vector>
#include <Eigen/Dense>
#include <Eigen/SVD>
#include "constants.h"
#include "types.h"
#include "classes/exception.h"
#include "internal/classes/iomanip.h"
#include "input_output.h"
#include "classes/singleton.h"
#include "classes/init.h"
#include "internal/functions.h"
#include "functions.h"
#include "classes/codes.h"
#include "classes/gates.h"
#include "classes/states.h"
#include "classes/random_devices.h"
#include "operations.h"
#include "entropies.h"
#include "entanglement.h"
#include "random.h"
#include "classes/timer.h"
#include "instruments.h"
#include "number_theory.h"
```

Namespaces


- [qpp](#)

Variables

- const Init & [qpp::init](#) = Init::get_instance()
[qpp::Init](#) const Singleton
- const Codes & [qpp::codes](#) = Codes::get_instance()
[qpp::Codes](#) const Singleton
- const Gates & [qpp::gt](#) = Gates::get_instance()
[qpp::Gates](#) const Singleton
- const States & [qpp::st](#) = States::get_instance()
[qpp::States](#) const Singleton
- RandomDevices & [qpp::rdevs](#) = RandomDevices::get_instance()
[qpp::RandomDevices](#) Singleton

8.22 include/random.h File Reference

This graph shows which files directly or indirectly include this file:



Namespaces

- [qpp](#)

Functions


- template<typename Derived >
Derived [qpp::rand](#) (std::size_t rows, std::size_t cols, double a=0, double b=1)
Generates a random matrix with entries uniformly distributed in the interval [a, b)
- template<>
dmat [qpp::rand](#) (std::size_t rows, std::size_t cols, double a, double b)
Generates a random real matrix with entries uniformly distributed in the interval [a, b), specialization for double matrices ([qpp::dmat](#))
- template<>
cmat [qpp::rand](#) (std::size_t rows, std::size_t cols, double a, double b)
Generates a random complex matrix with entries (both real and imaginary) uniformly distributed in the interval [a, b), specialization for complex matrices ([qpp::cmat](#))
- double [qpp::rand](#) (double a=0, double b=1)
Generates a random real number uniformly distributed in the interval [a, b)
- int [qpp::randint](#) (int a=std::numeric_limits< int >::min(), int b=std::numeric_limits< int >::max())

- Generates a random integer (int) uniformly distributed in the interval [a, b].*

 - `template<typename Derived >`
`Derived qpp::randn (std::size_t rows, std::size_t cols, double mean=0, double sigma=1)`
Generates a random matrix with entries normally distributed in $N(\text{mean}, \text{sigma})$
- `template<>`
`dmat qpp::randn (std::size_t rows, std::size_t cols, double mean, double sigma)`
Generates a random real matrix with entries normally distributed in $N(\text{mean}, \text{sigma})$, specialization for double matrices ([qpp::dmat](#))
- `template<>`
`cmat qpp::randn (std::size_t rows, std::size_t cols, double mean, double sigma)`
Generates a random complex matrix with entries (both real and imaginary) normally distributed in $N(\text{mean}, \text{sigma})$, specialization for complex matrices ([qpp::cmat](#))
- `double qpp::randn (double mean=0, double sigma=1)`
Generates a random real number (double) normally distributed in $N(\text{mean}, \text{sigma})$
- `cmat qpp::randU (std::size_t D)`
Generates a random unitary matrix.
- `cmat qpp::randV (std::size_t Din, std::size_t Dout)`
Generates a random isometry matrix.
- `std::vector< cmat > qpp::randkraus (std::size_t N, std::size_t D)`
Generates a set of random Kraus operators.
- `cmat qpp::randH (std::size_t D)`
Generates a random Hermitian matrix.
- `ket qpp::randket (std::size_t D)`
Generates a random normalized ket (pure state vector)
- `cmat qpp::randrho (std::size_t D)`
Generates a random density matrix.
- `std::vector< std::size_t > qpp::randperm (std::size_t n)`
Generates a random uniformly distributed permutation.

8.23 include/types.h File Reference

This graph shows which files directly or indirectly include this file:



Namespaces

- [qpp](#)

Typedefs

- using `qpp::cplx` = `std::complex< double >`
Complex number in double precision.
- template<typename Scalar >
using `qpp::DynMat` = `Eigen::Matrix< Scalar, Eigen::Dynamic, Eigen::Dynamic >`
Dynamic Eigen matrix over the field specified by Scalar.
- template<typename Scalar >
using `qpp::DynColVect` = `Eigen::Matrix< Scalar, Eigen::Dynamic, 1 >`
Dynamic Eigen column vector over the field specified by Scalar.
- template<typename Scalar >
using `qpp::DynRowVect` = `Eigen::Matrix< Scalar, 1, Eigen::Dynamic >`
Dynamic Eigen row vector over the field specified by Scalar.
- using `qpp::ket` = `DynColVect< cplx >`
Complex (double precision) dynamic Eigen column vector.
- using `qpp::bra` = `DynRowVect< cplx >`
Complex (double precision) dynamic Eigen row vector.
- using `qpp::cmat` = `DynMat< cplx >`
Complex (double precision) dynamic Eigen matrix.
- using `qpp::dmat` = `DynMat< double >`
Real (double precision) dynamic Eigen matrix.

8.24 mainpage.dox File Reference

Index

absm
 qpp, [23](#)
abssq
 qpp, [23](#), [24](#)
adjoint
 qpp, [24](#)
anticomm
 qpp, [24](#)
apply
 qpp, [24](#), [25](#)

bra
 qpp, [22](#)

CUSTOM_EXCEPTION
 qpp::Exception, [68](#)
channel
 qpp, [26](#)
choi
 qpp, [27](#)
choi2kraus
 qpp, [27](#)
chop
 qpp, [58](#)
cmat
 qpp, [22](#)
codes
 qpp, [58](#)
comm
 qpp, [27](#)
compperm
 qpp, [28](#)
concurrence
 qpp, [28](#)
conjugate
 qpp, [28](#)
contrac2x
 qpp, [28](#), [29](#)
cosm
 qpp, [29](#)
cplx
 qpp, [22](#)
cwise
 qpp, [29](#)

DIMS_INVALID
 qpp::Exception, [67](#)
DIMS_MISMATCH_CVECTOR
 qpp::Exception, [67](#)
DIMS_MISMATCH_MATRIX
 qpp::Exception, [67](#)
DIMS_MISMATCH_RVECTOR
 qpp::Exception, [67](#)
DIMS_MISMATCH_VECTOR
 qpp::Exception, [67](#)
DIMS_NOT_EQUAL
 qpp::Exception, [67](#)
det
 qpp, [29](#)
disp
 qpp, [30](#), [31](#)
dmat
 qpp, [22](#)

ee
 qpp, [59](#)
entanglement
 qpp, [31](#)
eps
 qpp, [59](#)
evals
 qpp, [31](#)
evects
 qpp, [32](#)
expm
 qpp, [32](#)

FIVE_QUBIT
 qpp::Codes, [64](#)
funm
 qpp, [32](#)

gcd
 qpp, [32](#), [33](#)
gconcurrence
 qpp, [33](#)
grams
 qpp, [33](#), [34](#)
gt
 qpp, [59](#)

hevals
 qpp, [34](#)
hevects
 qpp, [34](#)

infty
 qpp, [59](#)
init
 qpp, [59](#)
inverse

- qpp, [34](#)
- invperm
 - qpp, [35](#)
- ket
 - qpp, [23](#)
- kron
 - qpp, [35](#), [36](#)
- kronpow
 - qpp, [36](#)
- lcm
 - qpp, [36](#)
- load
 - qpp, [37](#)
- logdet
 - qpp, [38](#)
- logm
 - qpp, [38](#)
- lognegativity
 - qpp, [38](#)
- MATRIX_MISMATCH_SUBSYS
 - qpp::Exception, [67](#)
- MATRIX_NOT_CVECTOR
 - qpp::Exception, [67](#)
- MATRIX_NOT_RVECTOR
 - qpp::Exception, [67](#)
- MATRIX_NOT_SQUARE
 - qpp::Exception, [67](#)
- MATRIX_NOT_SQUARE_OR_CVECTOR
 - qpp::Exception, [67](#)
- MATRIX_NOT_SQUARE_OR_RVECTOR
 - qpp::Exception, [67](#)
- MATRIX_NOT_SQUARE_OR_VECTOR
 - qpp::Exception, [67](#)
- MATRIX_NOT_VECTOR
 - qpp::Exception, [67](#)
- maxn
 - qpp, [59](#)
- measure
 - qpp, [39–42](#)
- mket
 - qpp, [42](#)
- mprj
 - qpp, [42](#), [43](#)
- multiidx2n
 - qpp, [43](#)
- n2multiidx
 - qpp, [43](#)
- NINE_QUBIT_SHOR
 - qpp::Codes, [64](#)
- NO_CODEWORD
 - qpp::Exception, [68](#)
- NOT_BIPARTITE
 - qpp::Exception, [68](#)
- NOT_QUBIT_GATE
 - qpp::Exception, [67](#)
- NOT_QUBIT_SUBSYS
 - qpp::Exception, [68](#)
- negativity
 - qpp, [44](#)
- norm
 - qpp, [44](#)
- OUT_OF_RANGE
 - qpp::Exception, [68](#)
- omega
 - qpp, [44](#)
- PERM_INVALID
 - qpp::Exception, [68](#)
- pi
 - qpp, [59](#)
- powm
 - qpp, [45](#)
- prj
 - qpp, [45](#)
- prod
 - qpp, [45](#)
- ptrace
 - qpp, [46](#)
- ptrace1
 - qpp, [46](#)
- ptrace2
 - qpp, [46](#)
- ptranspose
 - qpp, [46](#)
- qmutualinfo
 - qpp, [47](#)
- qpp, [13](#)
 - absm, [23](#)
 - abssq, [23](#), [24](#)
 - adjoint, [24](#)
 - anticomm, [24](#)
 - apply, [24](#), [25](#)
 - bra, [22](#)
 - channel, [26](#)
 - choi, [27](#)
 - choi2kraus, [27](#)
 - chop, [58](#)
 - cmat, [22](#)
 - codes, [58](#)
 - comm, [27](#)
 - compperm, [28](#)
 - concurrence, [28](#)
 - conjugate, [28](#)
 - contfrac2x, [28](#), [29](#)
 - cosm, [29](#)
 - cplx, [22](#)
 - cwise, [29](#)
 - det, [29](#)
 - disp, [30](#), [31](#)
 - dmat, [22](#)
 - ee, [59](#)
 - entanglement, [31](#)

- eps, [59](#)
- evals, [31](#)
- evects, [32](#)
- expm, [32](#)
- funm, [32](#)
- gcd, [32](#), [33](#)
- gconcurrency, [33](#)
- grams, [33](#), [34](#)
- gt, [59](#)
- hevals, [34](#)
- hevects, [34](#)
- infty, [59](#)
- init, [59](#)
- inverse, [34](#)
- invperm, [35](#)
- ket, [23](#)
- kron, [35](#), [36](#)
- kronpow, [36](#)
- lcm, [36](#)
- load, [37](#)
- logdet, [38](#)
- logm, [38](#)
- lognegativity, [38](#)
- maxn, [59](#)
- measure, [39–42](#)
- mket, [42](#)
- mprj, [42](#), [43](#)
- multiidx2n, [43](#)
- n2multiidx, [43](#)
- negativity, [44](#)
- norm, [44](#)
- omega, [44](#)
- pi, [59](#)
- powm, [45](#)
- prj, [45](#)
- prod, [45](#)
- ptrace, [46](#)
- ptrace1, [46](#)
- ptrace2, [46](#)
- ptranspose, [46](#)
- qmutualinfo, [47](#)
- rand, [47](#), [48](#)
- randint, [49](#)
- randket, [49](#)
- randkraus, [49](#)
- randn, [49](#), [50](#)
- randperm, [50](#)
- randrho, [51](#)
- rdevs, [59](#)
- renyi, [51](#)
- reshape, [52](#)
- rho2pure, [52](#)
- save, [52](#)
- schatten, [53](#)
- schmidtcoeff, [53](#)
- schmidtprob, [54](#)
- shannon, [55](#)
- sinm, [55](#)
- spectralpowm, [55](#)
- sqrtn, [55](#)
- st, [59](#)
- sum, [56](#)
- super, [56](#)
- svals, [56](#)
- syspermute, [57](#)
- trace, [57](#)
- transpose, [58](#)
- tsallis, [58](#)
- x2contfrac, [58](#)
- qpp::Codes
 - FIVE_QUBIT, [64](#)
 - NINE_QUBIT_SHOR, [64](#)
 - SEVEN_QUBIT_STEANE, [64](#)
- qpp::Exception
 - CUSTOM_EXCEPTION, [68](#)
 - DIMS_INVALID, [67](#)
 - DIMS_MISMATCH_CVECTOR, [67](#)
 - DIMS_MISMATCH_MATRIX, [67](#)
 - DIMS_MISMATCH_RVECTOR, [67](#)
 - DIMS_MISMATCH_VECTOR, [67](#)
 - DIMS_NOT_EQUAL, [67](#)
 - MATRIX_MISMATCH_SUBSYS, [67](#)
 - MATRIX_NOT_CVECTOR, [67](#)
 - MATRIX_NOT_RVECTOR, [67](#)
 - MATRIX_NOT_SQUARE, [67](#)
 - MATRIX_NOT_SQUARE_OR_CVECTOR, [67](#)
 - MATRIX_NOT_SQUARE_OR_RVECTOR, [67](#)
 - MATRIX_NOT_SQUARE_OR_VECTOR, [67](#)
 - MATRIX_NOT_VECTOR, [67](#)
 - NO_CODEWORD, [68](#)
 - NOT_BIPARTITE, [68](#)
 - NOT_QUBIT_GATE, [67](#)
 - NOT_QUBIT_SUBSYS, [68](#)
 - OUT_OF_RANGE, [68](#)
 - PERM_INVALID, [68](#)
 - SUBSYS_MISMATCH_DIMS, [67](#)
 - TYPE_MISMATCH, [68](#)
 - UNDEFINED_TYPE, [68](#)
 - UNKNOWN_EXCEPTION, [67](#)
 - ZERO_SIZE, [67](#)
- rand
 - qpp, [47](#), [48](#)
- randint
 - qpp, [49](#)
- randket
 - qpp, [49](#)
- randkraus
 - qpp, [49](#)
- randn
 - qpp, [49](#), [50](#)
- randperm
 - qpp, [50](#)
- randrho
 - qpp, [51](#)
- rdevs
 - qpp, [59](#)

renyi
 qpp, [51](#)
reshape
 qpp, [52](#)
rho2pure
 qpp, [52](#)

SEVEN_QUBIT_STEANE
 qpp::Codes, [64](#)
SUBSYS_MISMATCH_DIMS
 qpp::Exception, [67](#)
save
 qpp, [52](#)
schatten
 qpp, [53](#)
schmidtcoeff
 qpp, [53](#)
schmidtprob
 qpp, [54](#)
shannon
 qpp, [55](#)
sinm
 qpp, [55](#)
spectralpowm
 qpp, [55](#)
sqrtm
 qpp, [55](#)
st
 qpp, [59](#)
sum
 qpp, [56](#)
super
 qpp, [56](#)
svals
 qpp, [56](#)
syspermute
 qpp, [57](#)

TYPE_MISMATCH
 qpp::Exception, [68](#)
trace
 qpp, [57](#)
transpose
 qpp, [58](#)
tsallis
 qpp, [58](#)

UNDEFINED_TYPE
 qpp::Exception, [68](#)
UNKNOWN_EXCEPTION
 qpp::Exception, [67](#)

x2contfrac
 qpp, [58](#)

ZERO_SIZE
 qpp::Exception, [67](#)