



ELSEVIER

Available online at www.sciencedirect.com



Journal of Computer and System Sciences 74 (2008) 775–795

JOURNAL OF
COMPUTER
AND SYSTEM
SCIENCES

www.elsevier.com/locate/jcss

Compact roundtrip routing with topology-independent node names

Marta Arias^{a,1}, Lenore J. Cowen^{b,2}, Kofi A. Laing^{b,*,3}

^a *Center for Computational Learning Systems, Columbia University, New York, NY 10115, USA*

^b *Department of Computer Science, Tufts University, Medford, MA 02155, USA*

Received 9 November 2004; received in revised form 24 January 2007

Available online 14 September 2007

Abstract

Consider a strongly connected directed weighted network with n nodes. This paper presents compact roundtrip routing schemes with $\tilde{O}(\sqrt{n})$ sized local tables⁴ and stretch 6 for any strongly connected directed network with arbitrary edge weights. A scheme with local tables of size $\tilde{O}(\epsilon^{-1}n^{2/k})$ and stretch $\min((2^{k/2} - 1)(k + \epsilon), 8k^2 + 4k - 4)$, for any $\epsilon > 0$ is also presented in the case where edge weights are restricted to be polynomially-sized. Both results are for the topology-independent node-name model.