

520M

Key Specs

Lift Capacity At Full Height - Measured At Pivot (U) - 2606.0 lb.
Boom Breakout Force - Measured At Pivot (Y) - 4793.0 lb.
Bucket Rollback Force Capacity At Ground-Level Line (ZZ) - 6742.0 lb.
Maximum Lift Height (A) - 132.0 in.
Clearance At Full Height - Bucket Dumped - 99.0 in.
Dump Angle (E) - -54.0 degree (angle)
Rollback Angle (G) - 43.0 degree (angle)

Tractor

Model - 5085E, 5090E, 5100E FT4
Front Tire - 320/85 R24 BKT (12.4 R24)
Rear Tire - 18.4 R30
Wheelbase - 90.0 in.
Pump Capacity - 11.0 gpm
Rated Pressure - 2828.0 psi

Loader

Leveling Configuration - Mechanical Self Leveling (MSL)
Bucket Used - General Purpose 1850 mm / 73 in.
Bucket Weight - 392.0 lb.
Lift Capacity At Full Height - Measured At Pivot (U) - 2606.0 lb.
Lift Capacity At Full Height - Measured At 800 mm Ahead Of Pivot - 2822.0 lb.

Loader
Lift Capacity At 59 in. (1500 mm) - Measured At Pivot - 3552.0 lb.
Lift Capacity At 59 in. (1500 mm) - Measured At 800 mm Ahead Of Pivot (X) - 3492.0 lb.
Boom Breakout Force - Measured At Pivot (Y) - 4793.0 lb.
Boom Breakout Force - Measured At 800 mm Ahead Of Pivot (Z) - 4048.0 lb.
At Maximum Height (VV) - 4154.0 lb.
At 59-in. (1500 mm) Lift Height (XX) - 6823.0 lb.
Bucket Rollback Force Capacity At Ground-Level Line (ZZ) - 6742.0 lb.
Maximum Lift Height (A) - 132.0 in.
At Full Height - Bucket Level (B) - 124.0 in.
Clearance At Full Height - Bucket Dumped - 99.0 in.
Overall Length (I+F) - 176.4 in.
Digging Depth (H) - 3.7 in.
Reach - At Maximum Height (D) - 33.0 in.
Reach - At Ground Level - Bucket Level - 85.5 in.
Dump Angle (E) - -54.0 degree (angle)
Rollback Angle (G) - 43.0 degree (angle)
Dump Angle, Ground - -109.0 degree (angle)
Loader Raise - 3.3 seconds
Loader Lower - 3.4 seconds
Bucket Dump - 2.6 seconds
Bucket Rollback - 2.6 seconds