

# Ubuntu 24.04 LTS — ClaudeManager Setup Guide

---

New desktop setup guide for moving ClaudeManager from Windows to Ubuntu 24.04 LTS.

---

## 1. Install Ubuntu 24.04 LTS

---

**Download the ISO:** <https://releases.ubuntu.com/24.04/ubuntu-24.04.2-desktop-amd64.iso>

**Create bootable USB (from Windows, using Rufus):**

1. Download Rufus: <https://rufus.ie>
  2. Insert USB ( $\geq 8\text{GB}$ ), open Rufus
  3. Select the ubuntu ISO, leave defaults (GPT + UEFI), click Start
  4. Boot from USB, choose "Install Ubuntu", follow the installer
- 

## 2. First-boot system updates

---

```
sudo apt update && sudo apt upgrade -y  
sudo apt install -y curl git tmux gnome-terminal xdotool build-essential
```

---

## 3. Install Node.js 20 LTS

---

```
curl -fsSL https://deb.nodesource.com/setup_20.x | sudo -E bash -  
sudo apt install -y nodejs  
node --version    # should be v20.x
```

---

## 4. Install Docker Engine

---

```
curl -fsSL https://get.docker.com | sudo sh  
sudo usermod -aG docker $USER  
newgrp docker    # or log out and back in  
docker --version
```

---

## 5. Install PM2

---

```
sudo npm install -g pm2
pm2 startup systemd -u $USER --hp $HOME
# Run the printed systemctl command as root, e.g.:
# sudo systemctl enable pm2-<username>
```

## 6. Install Claude Code CLI

---

```
npm install -g @anthropic-ai/claude-code
claude --version
```

## 7. Install Tailscale

---

```
curl -fsSL https://tailscale.com/install.sh | sh
sudo tailscale up
# Authenticate in the browser when prompted
tailscale ip -4 # note the IP – add to agent-server-url if needed
```

## 8. Transfer ClaudeManager

---

Option A — clone from GitHub (if the repo is pushed):

```
git clone https://github.com/your-org/ClaudeManager.git ~/ClaudeManager
```

Option B — copy from Windows over network:

```
# From Windows (Git Bash):
scp -r /c/Users/kuron/Research/ClaudeManager user@new-desktop:~/ClaudeManager
```

## 9. Configure credentials

---

```
mkdir -p ~/.claude

# Agent server URL (your Tailscale address or localhost)
echo "https://msi.tail06903c.ts.net" > ~/.claude/agent-server-url

# API key – copy from Windows machine:
#   Windows: type C:\Users\kuron\.claude\agent-manager-key
echo "your-api-key-here" > ~/.claude/agent-manager-key

# Anthropic API key
echo "export ANTHROPIC_API_KEY=sk-ant-..." >> ~/.bashrc
source ~/.bashrc
```

## 10. Start Docker services

---

```
cd ~/ClaudeManager
docker compose up -d
# Wait for backend health:
until curl -s http://localhost:3001/api/health; do sleep 3; done
echo "Backend ready"
```

## 11. Configure PM2 for launcher + watchdog

---

```
cd ~/ClaudeManager

# Start launcher
pm2 start launcher/launcher.js --name agent-launcher

# Start watchdog
pm2 start scripts/watchdog.js --name watchdog

# Save PM2 process list for auto-start on reboot
pm2 save
```

## 12. Configure auto-start on login

---

The systemd user service (`scripts/claude-manager-launcher.service`) handles startup.

```
mkdir -p ~/.config/systemd/user

# Create the service (replace USERNAME with your actual username)
sudo sed "s/%i/$USER/g" ~/ClaudeManager/scripts/claude-manager-launcher.service \
    > ~/.config/systemd/user/claude-manager.service

systemctl --user daemon-reload
systemctl --user enable claude-manager.service
systemctl --user start claude-manager.service

# Check status
systemctl --user status claude-manager.service
```

Alternatively, use the startup script directly:

```
chmod +x ~/ClaudeManager/scripts/startup.sh
# Add to ~/.config/autostart or call from ~/.profile:
~/ClaudeManager/scripts/startup.sh &
```

---

## 13. Verify the launcher

```
# Check launcher log
pm2 logs agent-launcher --lines 20

# It should print:
# [HH:MM:SS] Agent Launcher started – polling ...
# [HH:MM:SS] Platform: Linux
```

---

## 14. Terminal setup (tmux)

On Linux, named window groups use **tmux sessions** instead of Windows Terminal tabs.

```
# View all active agent sessions
tmux ls

# Attach to a project's session (e.g. DailyVacancy)
tmux attach -t DailyVacancy

# Navigate between agent tabs within a session
# Ctrl+B then n (next window) / p (previous window)
# Ctrl+B then w (window list)

# Detach from session without stopping agents
# Ctrl+B then d
```

---

## 15. Android ADB (for Android app testing)

---

```
sudo apt install -y android-tools-adb
# Enable USB debugging on your phone, then:
adb devices
# Build and install the APK:
cd ~/ClaudeManager/android
./gradlew assembleDebug
adb install app/build/outputs/apk/debug/app-debug.apk
```

Java/Android SDK are already handled by the Android Gradle plugin — install JDK 17:

```
sudo apt install -y openjdk-17-jdk
export JAVA_HOME=/usr/lib/jvm/java-17-openjdk-amd64
echo "export JAVA_HOME=/usr/lib/jvm/java-17-openjdk-amd64" >> ~/.bashrc
```

---

## 16. Key differences from Windows

| Feature              | Windows                                         | Linux                                         |
|----------------------|-------------------------------------------------|-----------------------------------------------|
| Terminal multiplexer | Windows Terminal ( <code>wt.exe</code> )        | tmux                                          |
| Named window groups  | <code>wt -w &lt;name&gt;</code>                 | <code>tmux new-session -s &lt;name&gt;</code> |
| Process termination  | <code>taskkill /PID /T /F</code>                | <code>kill -TERM / -KILL</code>               |
| PID check            | PowerShell <code>Get-Process</code>             | <code>kill -0 &lt;pid&gt;</code>              |
| Startup              | Task Scheduler / startup.bat                    | systemd user service / startup.sh             |
| Launcher mode        | Auto-detected ( <code>process.platform</code> ) | Same — <code>IS_LINUX=true</code> auto        |
| Signal/input         | WScript.Shell SendKeys                          | xdotool (install separately)                  |

## Quick reference paths

| Item             | Linux path                                      |
|------------------|-------------------------------------------------|
| ClaudeManager    | <code>~/ClaudeManager</code>                    |
| Claude config    | <code>~/.claude/</code>                         |
| Agent server URL | <code>~/.claude/agent-server-url</code>         |
| API key          | <code>~/.claude/agent-manager-key</code>        |
| PM2 logs         | <code>~/.pm2/logs/</code>                       |
| Docker data      | Docker named volume <code>agent-data</code>     |
| Startup script   | <code>~/ClaudeManager/scripts/startup.sh</code> |