

Machine Learning

# Machine learning system design

---

Prioritizing what to  
work on: Spam  
classification example

# Building a spam classifier

From: cheapsales@buystufffromme.com  
To: ang@cs.stanford.edu  
Subject: Buy now!

Deal of the week! Buy now!  
Rolex w4tchs - \$100  
Medicine (any kind) - \$50  
Also low cost M0rgages  
available.

From: Alfred Ng  
To: ang@cs.stanford.edu  
Subject: Christmas dates?

Hey Andrew,  
Was talking to Mom about plans  
for Xmas. When do you get off  
work. Meet Dec 22?  
Alf

## Building a spam classifier

Supervised learning.  $x$  = features of email.  $y$  = spam (1) or not spam (0).

Features  $x$ : Choose 100 words indicative of spam/not spam.

*E.g. deal, buy, discount, now, Andrew*

$$x = \begin{bmatrix} 1 \\ 1 \\ 0 \\ 1 \\ \dots \\ 0 \end{bmatrix} \begin{matrix} \textit{deal} \\ \textit{buy} \\ \textit{discount} \\ \textit{now} \\ \\ \textit{Andrew} \end{matrix}$$

$$x = \begin{cases} 1 & \textit{meet with certain rules} \\ 0 & \textit{otherwise} \end{cases}$$

**From:** cheapsales@buystufffromme.com  
**To:** ang@cs.stanford.edu  
**Subject:** Buy now!


**Deal of the week! Buy now!**

Note: In practice, take most frequently occurring  $n$  words ( 10,000 to 50,000) in training set, rather than manually pick 100 words.

## Building a spam classifier

How to spend your time to make it have low error?

- Collect lots of data
  - E.g. “honeypot” project.
- Develop sophisticated features based on email routing information (from email header).
- Develop sophisticated features for message body, e.g. should “discount” and “discounts” be treated as the same word? How about “deal” and “Dealer”? Features about punctuation?
- Develop sophisticated algorithm to detect misspellings (e.g. m0rtgage, med1cine, w4tches.)



Machine Learning

# Machine learning system design

---

# Error analysis

## Recommended approach

- Start with a simple algorithm that you can implement quickly. Implement it and test it on your cross-validation data.
- Plot learning curves to decide if more data, more features, etc. are likely to help.
- Error analysis: Manually examine the examples (in cross validation set) that your algorithm made errors on. See if you spot any systematic trend in what type of examples it is making errors on.

## Error Analysis

$m_{CV} = 500$  examples in cross validation set

Algorithm misclassifies 100 emails.

Manually examine the 100 errors, and categorize them based on:

- (i) What type of email it is
- (ii) What cues (features) you think would have helped the algorithm classify them correctly.

Pharma: 12

Replica/fake: 4

Steal passwords: 53

Other: 31

Deliberate misspellings: 5

(m0rgage, med1cine, etc.)

Unusual email routing: 16

Unusual (spamming) punctuation: 32

## The importance of numerical evaluation

Should discount/discounts/discounted/discounting be treated as the same word?

Can use “stemming” software (E.g. “Porter stemmer”)  
universe/university.


Error analysis may not be helpful for deciding if this is likely to improve performance. Only solution is to try it and see if it works.

Need numerical evaluation (e.g., cross validation error) of algorithm’s performance with and without stemming.

Without stemming: 5% error    With stemming: 3% error

Distinguish upper vs. lower case (Mom/mom):





Machine Learning

# Machine learning system design

---

## Error metrics for skewed classes

## Cancer classification example

Train logistic regression model  $h_{\theta}(x)$ . ( $y = 1$  if cancer,  $y = 0$  otherwise)

Find that you got 1% error on test set.  
(99% correct diagnoses)

Only 0.50% of patients have cancer.

```
function y = predictCancer(x)
    y = 0; %ignore x!
return
```

# Precision/Recall

$y = 1$  in presence of rare class that we want to detect

Confusion Matrix		Actual class	
		Positive	Negative
Predicted class	Positive	True Positive	False Positive
	Negative	False Negative	True Negative

## Precision

(Of all patients where we predicted  $y = 1$ , what fraction actually has cancer?)

$$\text{Precision rate} = \frac{\text{True Positive}}{\text{True Positive} + \text{False Positive}}$$

## Recall

(Of all patients that actually have cancer, what fraction did we correctly detect as having cancer?)

$$\text{Recall rate} = \frac{\text{True Positive}}{\text{True Positive} + \text{False Negative}}$$

		Actual class	
		1	0
Predicted class	1	80	20
	0	80	820

查准率（precision）是多少？ 查全率（recall）是多少？

A. ☐ 0.8

B. ☐ 0.5

C. ☐ 0.08


D. ☐ 0.1

A. ☐ 0.5

B. ☐ 0.8

C. ☐ 0.08

D. ☐ 0.1



Machine Learning

# Machine learning system design

---

## Trading off precision and recall

## Trading off precision and recall

Logistic regression:  $0 \leq h_{\theta}(x) \leq 1$

Predict 1 if  $h_{\theta}(x) \geq 0.5$

Predict 0 if  $h_{\theta}(x) < 0.5$

Suppose we want to predict  $y = 1$  (cancer) only if very confident.


*higher precision, lower recall*

Suppose we want to avoid missing too many cases of cancer (avoid false negatives).

*higher recall, lower precision*

More generally: Predict 1 if  $h_{\theta}(x) \geq \text{threshold}$ .

$$\text{precision} = \frac{\text{true positives}}{\text{no. of predicted positive}}$$
$$\text{recall} = \frac{\text{true positives}}{\text{no. of actual positive}}$$




## F<sub>1</sub> Score (F score)

How to compare precision/recall numbers?

	Precision(P)	Recall (R)
Algorithm 1	0.5	0.4
Algorithm 2	0.7	0.1
Algorithm 3	0.02	1.0

Average:  $\frac{P+R}{2}$

F<sub>1</sub> Score:  $2 \frac{PR}{P+R}$



Machine Learning

# Machine learning system design

---

## Data for machine learning



# Designing a high accuracy learning system


E.g. Classify between confusable words.

{to, two, too}, {then, than}

For breakfast I ate \_\_\_\_\_ eggs.

Algorithms

- Perceptron (Logistic regression)
- Winnow
- Memory-based
- Naïve Bayes



**“It’s not who has the best algorithm that wins.**

**It’s who has the most data.”**

## Large data rationale

Assume feature  $x \in \mathbb{R}^{n+1}$  has sufficient information to predict  $y$  accurately.

Example: For breakfast I ate \_\_\_\_\_ eggs.

Counterexample: Predict housing price from only size (feet<sup>2</sup>) and no other features.

Useful test: Given the input  $x$ , can a human expert confidently predict  $y$ ?

## Large data rationale

Use a learning algorithm with many parameters (e.g. logistic regression/linear regression with many features; neural network with many hidden units).

$J_{train}(\theta)$  will be small

Use a very large training set (unlikely to overfit)

$$J_{train}(\theta) \approx J_{test}(\theta)$$

$J_{test}(\theta)$  will be small