

10.129.136.187

1. Which TCP port is open on the machine?

Answer: 6379

2. Which service is running on the port that is open on the machine?

Answer: redis

3. What type of database is Redis? Choose from the following options: (i) In-memory Database, (ii) Traditional Database.

Al Overview

Redis (REmote Dictionary Server) is an open-source, in-memory data structure store that functions as a database, cache, and message broker.

Answer: In-memory Database

4. Which command-line utility is used to interact with the Redis server? Enter the program name you would enter into the terminal without any arguments.

Answer: redis-cli

5. Which flag is used with the Redis command-line utility to specify the hostname?

```
(kali⊕ kali)-[~/Desktop/HTB/labs]
$ redis-cli -h
redis-cli 8.0.2

Usage: redis-cli [OPTIONS] [cmd [arg [arg ...]]]
-h <hostname> Server hostname (default: 127.0.0.1).
```

Answer: -h

6. Once connected to a Redis server, which command is used to obtain the information and statistics about the Redis server?

Answer: info

7. What is the version of the Redis server being used on the target machine?

```
(kali@ kali)-[~/Desktop/HTB/labs]
$ redis-cli -h 10.129.136.187
10.129.136.187:6379> info
# Server
redis_version:5.0.7
```

Answer: 5.0.7

8. Which command is used to select the desired database in Redis?

Answer: SELECT

9. How many keys are present inside the database with index 0?

```
(kali⊗ kali)-[~/Desktop/HTB/labs]
$ redis-cli -h 10.129.136.187
10.129.136.187:6379> SELECT 0
OK
10.129.136.187:6379> DBSIZE
(integer) 4
10.129.136.187:6379>
```

Answer: 4

10. Which command is used to obtain all the keys in a database?

```
10.129.136.187:6379> KEYS *
1) "numb"
2) "flag"
3) "temp"
4) "stor"
```

Answer: KEYS *

11. Submit root flag.

10.129.136.187:6379> GET flag "03e1d2b376c37ab3f5319922053953eb"

Answer: 03e1d2b376c37ab3f5319922053953eb