

[Home](#) [Modules](#) [Agents](#) [How-to](#) [Handle parsing errors](#)

Handle parsing errors

Occasionally the LLM cannot determine what step to take because it outputs format in incorrect form to be handled by the output parser. In this case, by default the agent errors. But you can easily control this functionality with `handle_parsing_errors`! Let's explore how.

Setup

```
from langchain import (
    OpenAI,
    LLMChain,
    SerpAPIWrapper,
    SQLDatabase,
    SQLDatabaseChain,
)
from langchain.agents import initialize_agent, Tool
from langchain.agents import AgentType
from langchain.chat_models import ChatOpenAI
from langchain.agents.types import AGENT_TO_CLASS
```

```
search = SerpAPIWrapper()
tools = [
    Tool(
        name="Search",
```

```
func=search.run,  
description="useful for when you need to answer questions about current events. You should ask  
targeted questions",  
),  
]
```

Error

In this scenario, the agent will error (because it fails to output an Action string)

```
mrkl = initialize_agent(  
    tools,  
    ChatOpenAI(temperature=0),  
    agent=AgentType.CHAT_ZERO_SHOT_REACT_DESCRIPTION,  
    verbose=True,  
)
```

```
mrkl.run("Who is Leo DiCaprio's girlfriend? No need to add Action")
```

```
> Entering new AgentExecutor chain...
```

IndexError

Traceback (most recent call last)

```
File ~/workplace/langchain/langchain/agents/chat/output_parser.py:21, in ChatOutputParser.parse(self, text)
```

```
    20 try:
--> 21     action = text.split("`")[1]
    22     response = json.loads(action.strip())
```

IndexError: list index out of range

During handling of the above exception, another exception occurred:

OutputParserException

Traceback (most recent call last)

```
Cell In[4], line 1
```

```
----> 1 mrkl.run("Who is Leo DiCaprio's girlfriend? No need to add Action")
```

```
File ~/workplace/langchain/langchain/chains/base.py:236, in Chain.run(self, callbacks, *args, **kwargs)
```

```
    234     if len(args) != 1:
    235         raise ValueError("`run` supports only one positional argument.")
--> 236     return self(args[0], callbacks=callbacks)[self.output_keys[0]]
    238 if kwargs and not args:
    239     return self(kwargs, callbacks=callbacks)[self.output_keys[0]]
```

```
File ~/workplace/langchain/langchain/chains/base.py:140, in Chain.__call__(self, inputs, return_only_outputs, callbacks)
```

```
    138 except (KeyboardInterrupt, Exception) as e:
    139     run_manager.on_chain_error(e)
```

```
--> 140     raise e
    141 run_manager.on_chain_end(outputs)
    142 return self.prep_outputs(inputs, outputs, return_only_outputs)
```

File ~/workplace/langchain/langchain/chains/base.py:134, in Chain.__call__(self, inputs, return_only_outputs, callbacks)

```
    128 run_manager = callback_manager.on_chain_start(
    129     {"name": self.__class__.__name__},
    130     inputs,
    131 )
    132 try:
    133     outputs = (
--> 134         self._call(inputs, run_manager=run_manager)
    135         if new_arg_supported
    136         else self._call(inputs)
    137     )
    138 except (KeyboardInterrupt, Exception) as e:
    139     run_manager.on_chain_error(e)
```

File ~/workplace/langchain/langchain/agents/agent.py:947, in AgentExecutor._call(self, inputs, run_manager)

```
    945 # We now enter the agent loop (until it returns something).
    946 while self._should_continue(iterations, time_elapsed):
--> 947     next_step_output = self._take_next_step(
    948         name_to_tool_map,
    949         color_mapping,
    950         inputs,
    951         intermediate_steps,
    952         run_manager=run_manager,
    953     )
    954     if isinstance(next_step_output, AgentFinish):
```

```
955         return self._return(  
956             next_step_output, intermediate_steps, run_manager=run_manager  
957         )
```

File ~/workplace/langchain/langchain/agents/agent.py:773, in AgentExecutor._take_next_step(self, name_to_tool_map, color_mapping, inputs, intermediate_steps, run_manager)

```
771         raise_error = False  
772     if raise_error:  
--> 773         raise e  
774     text = str(e)  
775     if isinstance(self.handle_parsing_errors, bool):
```

File ~/workplace/langchain/langchain/agents/agent.py:762, in AgentExecutor._take_next_step(self, name_to_tool_map, color_mapping, inputs, intermediate_steps, run_manager)

```
756     """Take a single step in the thought-action-observation loop.  
757  
758     Override this to take control of how the agent makes and acts on choices.  
759     """  
760     try:  
761         # Call the LLM to see what to do.  
--> 762         output = self.agent.plan(  
763             intermediate_steps,  
764             callbacks=run_manager.get_child() if run_manager else None,  
765             **inputs,  
766         )  
767     except OutputParserException as e:  
768         if isinstance(self.handle_parsing_errors, bool):
```

File ~/workplace/langchain/langchain/agents/agent.py:444, in Agent.plan(self, intermediate_steps, callbacks, **kwargs)

```
442 full_inputs = self.get_full_inputs(intermediate_steps, **kwargs)
443 full_output = self.llm_chain.predict(callbacks=callbacks, **full_inputs)
--> 444 return self.output_parser.parse(full_output)
```

```
File ~/workplace/langchain/langchain/agents/chat/output_parser.py:26, in ChatOutputParser.parse(self,
text)
```

```
23     return AgentAction(response["action"], response["action_input"], text)
25 except Exception:
--> 26     raise OutputParserException(f"Could not parse LLM output: {text}")
```

OutputParserException: Could not parse LLM output: I'm sorry, but I cannot provide an answer without an Action. Please provide a valid Action in the format specified above.

Default error handling

Handle errors with `Invalid or incomplete response`

```
mrkl = initialize_agent(
    tools,
    ChatOpenAI(temperature=0),
    agent=AgentType.CHAT_ZERO_SHOT_REACT_DESCRIPTION,
    verbose=True,
    handle_parsing_errors=True,
)
```

```
mrkl.run("Who is Leo DiCaprio's girlfriend? No need to add Action")
```

```
> Entering new AgentExecutor chain...
```

```
Observation: Invalid or incomplete response
```

```
Thought:
```

```
Observation: Invalid or incomplete response
```

```
Thought:Search for Leo DiCaprio's current girlfriend
```

```
Action:
```

```
```
```

```
{
```

```
 "action": "Search",
```

```
 "action_input": "Leo DiCaprio current girlfriend"
```

```
}
```

```
```
```

```
Observation: Just Jared on Instagram: "Leonardo DiCaprio & girlfriend Camila Morrone couple up for a lunch date!
```

```
Thought:Camila Morrone is currently Leo DiCaprio's girlfriend
```

```
Final Answer: Camila Morrone
```

```
> Finished chain.
```

```
'Camila Morrone'
```

Custom Error Message

You can easily customize the message to use when there are parsing errors

```
mrkl = initialize_agent(  
    tools,  
    ChatOpenAI(temperature=0),  
    agent=AgentType.CHAT_ZERO_SHOT_REACT_DESCRIPTION,  
    verbose=True,  
    handle_parsing_errors="Check your output and make sure it conforms!",  
)
```

```
mrkl.run("Who is Leo DiCaprio's girlfriend? No need to add Action")
```

```
> Entering new AgentExecutor chain...
```

```
Observation: Could not parse LLM output: I'm sorry, but I cannot  
Thought: I need to use the Search tool to find the answer to the question.  
Action:  
...  
{  
  "action": "Search",  
  "action_input": "Who is Leo DiCaprio's girlfriend?"  
}  
...
```


Observation: DiCaprio broke up with girlfriend Camila Morrone, 25, in the summer of 2022, after dating for four years. He's since been linked to another famous supermodel – Gigi Hadid. The power couple were first supposedly an item in September after being spotted getting cozy during a party at New York Fashion Week.

Thought: The answer to the question is that Leo DiCaprio's current girlfriend is Gigi Hadid.

Final Answer: Gigi Hadid.

> Finished chain.

'Gigi Hadid.'

Custom Error Function

You can also customize the error to be a function that takes the error in and outputs a string.

```
def _handle_error(error) -> str:
    return str(error)[:50]

mrkl = initialize_agent(
    tools,
    ChatOpenAI(temperature=0),
    agent=AgentType.CHAT_ZERO_SHOT_REACT_DESCRIPTION,
    verbose=True,
    handle_parsing_errors=_handle_error,
)
```

```
mrkl.run("Who is Leo DiCaprio's girlfriend? No need to add Action")
```

```
> Entering new AgentExecutor chain...
```

```
Observation: Could not parse LLM output: I'm sorry, but I cannot
```

```
Thought:I need to use the Search tool to find the answer to the question.
```

```
Action:
```

```
```
```

```
{
 "action": "Search",
 "action_input": "Who is Leo DiCaprio's girlfriend?"
}
```
```

```
Observation: DiCaprio broke up with girlfriend Camila Morrone, 25, in the summer of 2022, after dating for four years. He's since been linked to another famous supermodel – Gigi Hadid. The power couple were first supposedly an item in September after being spotted getting cozy during a party at New York Fashion Week.
```

```
Thought:The current girlfriend of Leonardo DiCaprio is Gigi Hadid.
```

```
Final Answer: Gigi Hadid.
```

```
> Finished chain.
```

```
'Gigi Hadid.'
```

