

ALEXANDER TONG


Mechanical engineering | Recovery hardware and supersonic aerodynamics

Boston University, B.S. Mechanical Engineering, Aerospace Concentration | Expected May 2028
alto335@bu.edu | 860-706-3624 | alexandertong.space

TECHNICAL PORTFOLIO

Project Index


Page 2 / Separation & recovery	18.7 lbm within a 20 lbm allocation . Parachute-load sizing, CO2 hardware and an operational reduced-pressure test chamber.
Page 3 / Aerodynamic fairing	Three concept studies; Ansys CFD baseline converged and under review . Shared aerodynamic analysis, integration and manufacturing trade.
Page 4 / Plummer shaker hardware	Structural analysis, bored-bolt checks and CNC fabrication . Installed plate-and-bolt hardware at 93.9% lower estimated cost.



Plummer: machined adapter installed.



AIAA: assembled Prototype 1 aircraft.



Hybrid nozzle: hotfire test frame.

Additional Projects

Plummer Laboratory

CNC-machined shaker adapter; plate-and-bolt hardware estimate reduced from \$1,170 to \$71.11, excluding labor. Designed the matrix and procedure for 48 Instron tests.

AIAA Design-Build-Fly wing

Complete Prototype 1 wing 42.7% lighter than the previous complete wing; build time reduced from three months to one. Led design, fabrication and member training.

Hybrid rocket nozzle

73% mass reduction from my initial design; approximately two-second hotfire. Minimum yield FOS 7.8 in SolidWorks FEA for mechanical loads only; thermal effects excluded. Thrust gain unmeasured.

EK210 line-following car

Designed and programmed the vehicle: six loaded course runs in 70-86 seconds against a 90-second limit. Recorded component cost \$73.94 against a \$200 budget.

Culturon

Executed the company's first full-scale nanoparticle deposition map using microscopy and ImageJ. Designed adhesive-free sample racks; presented prevention concepts.

Manufacturing & mentoring

CNC and manual machining, hot-wire foam cutting and composite fabrication. Taught BURPG members turning and milling through the machinist's-hammer project beginning Fall 2025.

Additional research & coursework

Space Physics & Technology Lab: instrument-data analysis with Python/pySPEDAS and assistance with flight-spare laser calibration.
University of Sydney pulsed plasma thruster: inductor-spool design and coil-winding calculations. [ME360 course project](#) is in progress.

Argo Separation and Recovery Subsystem

Boston University Rocket Propulsion Group | Subsystem Co-Lead | June 2025-present

18.7 / 20 lbm

Subsystem mass / allocation; final BOM \$1,076



Recovery assembly before CO2 coldflow; integrated separation pending.

823 / 1,230 lbf

Calculated parachute opening / snatch loads



CO2 cartridge/piercer. CAD and fabrication shared by a three-person team.

352 L

Operational vacuum chamber; reported test pressure 0.011 atm



Door, adapter and seal: my design; co-lead fabrication and clamps.

Design and Test Leadership

Co-led four reviews; used five published load methods to size recovery lines and check hardware. Paired flight computers provide separate firing paths.

Authored the summer black-powder SOP and co-led two integrated tests, briefings, fire/abort decisions and failure assessment. One of three charges failed in each test; the second damaged the parachute bag and canopy.

Standalone vinyl-charge successes did not establish integrated reliability. End-seal manufacturing variability is the leading hypothesis; adjacent-charge damage was inferred afterward. Root cause remains unconfirmed.

Helped drive the CO2 pivot: sized piercers with pressure, Lamé thick-wall and thread-shear calculations; contributed CAD, drawings, machining and component testing in a three-person team.

Calculation basis

Recovery lines	Selected nominal 6,000 lbf line rating with termination efficiency considered. Nominal rating is not assembled splice strength.
CO2 deployment sizing	4.66 psi for four nylon shear pins plus estimated friction. Ideal-gas estimate for modeled free volume: 10.9 g versus a selected 16 g cartridge.
CO2 piercer housing	Minimum calculated factor of safety (FOS) 2.01 in Lamé hoop stress; internal-thread shear FOS 6.31. Analytical margins, not proof-test results.
Vacuum door / Roark	0.25 in 6061-T6; 12 in unsupported diameter; uniform 14.7 psi gives 1,663 lbf. Simply supported circumference. Roark deflection: 0.0848 in. Separately recorded calculator stress: 16.5 ksi; minimum yield FOS 2.12 using 240 MPa.
Legacy Catclaw body	Recorded minimum body FOS 2.01 after my material reduction and piston-retention-slot modification. This tie cutter is separate from the CO2 piercer.

Verification Status

Reduced-pressure CO2 component firing complete. Splice dynamic proof reached an estimated 1.5 FOS without observed slip, limited by the setup. Preparing the integrated CO2 test SOP; integrated separation and subscale testing remain pending.

Chamber instrumentation/data analysis by my co-lead. Door results are predictions; the recorded stress-based FOS is not independently reproduced. Selected yield is not stock certification.

[Recovery architecture, hardware & tests](#) | [CO2 sizing & stress calculations](#) | [Chamber design](#)

63 in × 1.6 in

Mach 2.0-2.81

3 concepts

Leading edge

Midsection

Trailing edge

Wave drag dominates

Friction drag dominates

Base drag/expansion wave drag dominates

*Total frontal drag = foredrag

*Total rear drag = afterbody drag

Figure 1 is a line graph titled "Simulation 1" showing the evolution of three variables over 400 days. The y-axis is labeled "Amount" and ranges from 0 to 30,000. The x-axis is labeled "Days" and ranges from 0 to 400. The three variables are: Susceptible (blue line), Exposed (red line), and Infected (green line). The Susceptible population starts at 30,000 and drops sharply to near zero by day 100. The Exposed population peaks at approximately 28,000 around day 100. The Infected population peaks at approximately 10,000 around day 100. Vertical dashed lines indicate "Quarantine" at day 100 and "Treatment" at day 200.

Analysis

Preliminary friction estimate

At Mach 2.81 and recorded $Re = 2.04 \times 10^8$: $CD,f \approx 0.0792$, using 477 in² wetted area, 7.99 in² reference area and a 10% preliminary roughness allowance.

Leading-edge surrogate

A 15° full-cone correlation gives $C_p \approx 0.1888$. It is a screening surrogate for the wedge-like legacy front, not the mounted fairing's total drag coefficient.

Contributions and Status

I developed the common analysis, integration/manufacturing trade and CoDR. Quinn Collieran, Hannah Ruan and Aaron Lin own the three concept geometries. My Icarus simulation in **Ansys CFD is converged and under review**; candidate ranking and adjoint optimization remain pending.

The investigation also led to a nine-profile-family nosecone sweep in RASAero II. A ranking difference from published comparisons prompted further investigation; it does not establish a better flight design.

Alexander Tong | Technical portfolio | October 9, 2026

Shaker Adapter and Mounting Bolts

Mechanical Design Assistant | June 2026-present

0.173 mm

Plate displacement predicted in the design-review FEA case


20.1 Hz

Shaker operating frequency; analyzed with a 3 kg fixture load



93.9% lower

Estimated plate-and-bolt hardware cost; labor excluded

The adapter mounts a physical Ising-model fixture for controlled shaker vibration tests of bistable buckling elements.



SolidWorks plate-displacement result: 0.173 mm maximum. This is a model prediction.



My 12 × 12 in adapter drawing, including underside geometry.

Design and Manufacturing

Replaced an estimated \$1,170 outsourced plate/custom-bolt solution with \$71.11 of in-house hardware. Developed SolidWorks CAD/FEA, drawings and CAM/G-code; machined the 6061-T6 plate on a Haas VF-2 and checked plate dimensions with calipers against the ± 0.005 in drawing tolerance.

Drilled 5 mm axial bores in standard medium-carbon-steel M10 bolts for the required shaker interface after unsuccessful stainless-steel machining attempts. The bored bolts and adapter are installed.

Structural calculation basis

Installed joint geometry	M10 × 1.5 with a 5 mm axial bore; modeled remaining tensile area 38.35 mm ² . Nominal Class 8.8 yield strength 640 MPa; local plate bearing thickness 9.7 mm.
Per-bolt load path	5 kg allowance (2 kg plate + 3 kg fixture) at 11 G, shared by four bolts: 134.9 N external load per bolt. Workbook conservatively adds the full external load to 16.36 kN preload: 16.50 kN combined; joint stiffness sharing is not modeled.
Static FOS by checked mode	Bolt tensile yield: 1.49 under preload plus full external load; preload alone gives 1.50. Plate bearing 2.46; pull-through 4.99; external-thread shear 3.71; internal-thread shear 3.60. These are mode-specific ratios, not an overall dynamic FOS.
Displacement checks	Selected L/240 limit for the 12 in plate span: 1.27 mm; review plate FEA: 0.173 mm. A separate later dynamic fixture model predicts 0.44 mm at 3 kg and 20.1 Hz. These are different load cases.

Preload maintains joint compression; bolt/joint stiffness determines cyclic load sharing. The 1.49 ratio checks static tensile yield, not fatigue at 20.1 Hz. Preload scatter, separation and fatigue are not quantified here. Displacements are predictions; cost covers plate and bolts only.

[Full calculations, drawings, FEA and machining evidence](#) | Sources: my design review and DSRF Calcs; joint interpretation: NASA TM-106943.