

[Guide] ML: How to Add HDEF/ssdt

For Realtek ALC AppleHDA

Realtek ALC AppleHDA audio HDEF ssdt Audio ID Injection; no kext or dsdt enabler required. Installation requires copying the downloaded SSDT-1.aml to Extra.

audio_ALCInjection

toleda/audio_ALCInjection

audio ssdt enabler

toleda/audio_ssdt_enabler

Requirements

- 1. OS X versions supported:
 - 1. Mountain Lion/10.8.4 and newer
 - 2. Mavericks/10.9 or newer
- 2. Realtek ALC, one of the following Device_ID Codec Name
 - 1. 10ec0885 ALC885/ALC889a
 - 2. 10ec0887 ALC887/ALC888b
 - 3. 10ec0888 ALC888/ALC888s
 - 4. 10ec0889 ALC889
 - 5. 10ec0892 ALC892
 - 6. 10ec0899 ALC898
 - 7. 10ec0900 ALC1150 10.8.5 or newer
- 3. Supported Audio-IDs (Audio ID = layout-id)
 - 1. Audio_ID: 1 5/6 port Realtek ALC onboard audio and HD5K/AMD/Nvidia HDMI audio
 - 2. Audio_ID: 2 3 port Realtek ALC onboard audio and HD5K/AMD/Nvidia HDMI audio
 - 3. Audio_IDs: 1 and 2 support analog 5.1 surround sound
 - 4. Audio_IDs: 1 and 2 equire HDMI audio dsdt edits/ssdts for HDMI audio.

Remove Enabler (if installed)

- 1. Remove any audio enablers
 - 1. kexts, S/L/E/HDAEnabler1.kext, HDAEnabler8--.kext, ALC8xxHDA.kext, etc.
 - 2. dsdt, remove dsdt/HDEF/layout-id

Tools

- MaciASL http://maciasl.sourceforge.net/
- IORegistryExplorer (use IOReg_v2.1: https://github.com/toleda/audio_ALCInjection/blob/

master/IORegistryExplorer_v2.1.zip)

3. Rebuild kernel cache: see DPCIManager 1.5 Open Beta

Downloads

- 1. audio ssdt enabler/audio ssdt-hdae-1.zip at master · toleda/audio ssdt enabler
- 2. audio ssdt enabler/audio ssdt-hdae-2.zip at master · toleda/audio ssdt enabler

Installation

- 1. Copy Downloads/ssdt-ami-8 series hdmi audio-1/SSDT-1.aml to Extra
 - If Extra/SSDT.aml is present, install Downloads/audio_ssdt-uefi_hdmi_v3/SSDT-1.aml as Extra/SSDT-1.aml
 - 2. If no Extra/SSDT.aml, rename Downloads/audio_ssdt-uefi_hdmi_v3/SSDT-1.aml to SSDT.aml and install as Extra/SSDT.aml
- 3. Rebuild kernel cache
- 4. Enable SSDT
 - 1. Chimera or Chameleon Extra/org.chameleon.Boot.plist
 - <key>DropSSDT</key>
 - <string>Yes</string>
 - 2. Clover_v2000+ EFI/CLOVER/config.plist/ACPI/SSDT
 - <key>DropOem</key>
 - <true/>

Verification

- 1. Restart
- 2. IORegistryExplorer
 - 1. Search: HDEF
 - 2. Locate: layout-id (right pane, scroll down)
 - 3. Verify:
 - <01 00 00 00> or
 - <02 00 00 00>

Troubleshooting

- 1. Realtek ALC AppleHDA Capabilities.pdf
- 2. Post to http://www.insanelymac.com/forum/topic/290796-realtek-alc-applehda-audio-injection/
- 3. Post to http://www.tonymacx86.com/audio/76309-mountain-lion-multibeast-no-audio-solutions-problem-reporting.html

Credits:

SJ_UnderWater: SourceForge.net: MaciASL - Project Web Hosting - Open Source Software

bcc9: http://www.insanelymac.com/forum/top...ort/?p=1934889
PikeRAlpha: Intel HD4600 with full resolution I Pike's Universum