

Alessandro Scala



Quantum Abstract Interpretation

Seminar for the **Introduction to Quantum Computing** course

Università di Pisa
Dipartimento di Informatica

Pisa, 24 Luglio 2023

Roadmap

① Introduction

Reasons

Abstract Interpretation

② Preliminaries

Density Matrix

Reduced Density Matrix

③ Abstract Domain

Abstraction and Concretization Functions

Abstract Operations

Assertions



Introduction

As quantum computing advances, we would like to have some means to prove correctness properties on quantum programs, *especially* since quantum programming is counterintuitive.



Reasons

The naive way to check properties of a program is to run it and observe its behaviour.



Reasons

The naive way to check properties of a program is to run it and **observe** its behaviour.

We **cannot observe** the state of a quantum program!



Reasons

The naive way to check properties of a program is to run it and **observe** its behaviour.

We **cannot observe** the state of a quantum program!

Could **simulation** on a classical machine solve this issue?



Reasons

The naive way to check properties of a program is to run it and **observe** its behaviour.

We **cannot observe** the state of a quantum program!

Could **simulation** on a classical machine solve this issue?

No: **exponential** space and time cost.



Example

$$n_{qubits} = 1$$

$$|0\rangle \langle 0|$$

$$\begin{pmatrix} 1 & 0 \\ 0 & 0 \end{pmatrix}$$

$$2^2 = 4 \text{ complex numbers}$$



Example

$$n_{\text{qubits}} = 2$$

$$|00\rangle \langle 00|$$

$$\begin{pmatrix} 1 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 \end{pmatrix}$$

$$2^4 = 16 \text{ complex numbers}$$



Example

$$n_{\text{qubits}} = 3$$

$$|000\rangle \langle 000|$$

$$\begin{pmatrix} 1 & 0 & 0 & 0 & 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 \end{pmatrix}$$

$$2^6 = 64 \text{ complex numbers}$$



Example

$$n_{\text{qubits}} = 300$$

$$|0\rangle^{\otimes 300} \langle 0|^{\otimes 300}$$

?????



Example

$$n_{\text{qubits}} = 300$$

$$|0\rangle^{\otimes 300} \langle 0|^{\otimes 300}$$

$2^{600} = 41495155688809929585124078636911611510124462322424368$
 $999956573296906528114129081463997070489471037942881978866113$
 $007891823951510754117753078868748341139636870611818034015095$
 23685376

Bigger than the number of atoms in the universe.



Reasons

The naive way to check properties of a program is to run it and **observe** its behaviour.

We **cannot observe** the state of a quantum program!

Could **simulation** on a classical machine solve this issue?

No: **exponential** space and time cost.



Reasons

The naive way to check properties of a program is to run it and **observe** its behaviour.

We **cannot observe** the state of a quantum program!

Could **simulation** on a classical machine solve this issue?

No: **exponential** space and time cost.

Static checking of programs by hand?



Reasons

The naive way to check properties of a program is to run it and **observe** its behaviour.

We **cannot observe** the state of a quantum program!

Could **simulation** on a classical machine solve this issue?

No: **exponential** space and time cost.

Static checking of programs by hand?

Yes, but time consuming. Needs to be adapted to the specific program.



Reasons

The naive way to check properties of a program is to run it and **observe** its behaviour.

We **cannot observe** the state of a quantum program!

Could **simulation** on a classical machine solve this issue?

No: **exponential** space and time cost.

Static checking of programs by hand?

Yes, but time consuming. Needs to be adapted to the specific program.

Solution: abstract interpretation



What is abstract interpretation?

Instead of considering the **concrete domain**, we restrict our analysis to a **more coarse domain**, an **abstract domain**.



What is abstract interpretation?

Instead of considering the **concrete domain**, we restrict our analysis to a **more coarse domain**, an **abstract domain**.

The abstract domain we consider should be:



What is abstract interpretation?

Instead of considering the **concrete domain**, we restrict our analysis to a **more coarse domain**, an **abstract domain**.

The abstract domain we consider should be:

fine enough to capture the information we are interested in
(e.g. the state of the quantum system belongs to the span of two vectors)



What is abstract interpretation?

Instead of considering the **concrete domain**, we restrict our analysis to a **more coarse domain**, an **abstract domain**.

The abstract domain we consider should be:

fine enough to capture the information we are interested in
(e.g. the state of the quantum system belongs to the span of two vectors)

as coarse as possible to discard information we are not interested in,
and thus be substantially more efficient to be analyzed



Ingredients

- Abstract domain



Ingredients

- Abstract domain
 - Abstraction function: from more concrete to more abstract domain



Ingredients

- Abstract domain
 - Abstraction function: from more concrete to more abstract domain
 - Concretization function: from more abstract to more concrete domain



Ingredients

- Abstract domain
 - Abstraction function: from more concrete to more abstract domain
 - Concretization function: from more abstract to more concrete domain
 - Abstract operations: to represent concrete operations in the abstract domain



Ingredients

- Abstract domain
 - Abstraction function: from more concrete to more abstract domain
 - Concretization function: from more abstract to more concrete domain
 - Abstract operations: to represent concrete operations in the abstract domain
- Assertions: properties we can prove with abstract interpretation



Roadmap

① Introduction

Reasons

Abstract Interpretation

② Preliminaries

Density Matrix

Reduced Density Matrix

③ Abstract Domain

Abstraction and Concretization Functions

Abstract Operations

Assertions



Density Matrix

Instead of dealing with a state $|\phi\rangle$ in vector form, we use its *density matrix*:

$$\rho_\phi = |\phi\rangle \langle\phi| \quad (\text{For a pure state})$$

- positive semi-definite
- $\text{Tr}(\rho) = 1$
- projection ($P = P^\dagger = P^2$)



Density Matrix

Instead of dealing with a state $|\phi\rangle$ in vector form, we use its *density matrix*:

$$\rho_\phi = |\phi\rangle \langle\phi| \quad (\text{For a pure state})$$

- positive semi-definite
- $\text{Tr}(\rho) = 1$
- projection ($P = P^\dagger = P^2$)

Example:

$$|\beta_{00}\rangle = \frac{|00\rangle + |11\rangle}{\sqrt{2}}$$

$$\rho_{\beta_{00}} = |\beta_{00}\rangle \langle\beta_{00}|$$



Density Matrix

Instead of dealing with a state $|\phi\rangle$ in vector form, we use its *density matrix*:

$$\rho_\phi = |\phi\rangle \langle\phi| \quad (\text{For a pure state})$$

- positive semi-definite
- $\text{Tr}(\rho) = 1$
- projection ($P = P^\dagger = P^2$)

Example:

$$|\beta_{00}\rangle = \frac{|00\rangle + |11\rangle}{\sqrt{2}}$$

$$\rho_{\beta_{00}} = |\beta_{00}\rangle \langle\beta_{00}| = \frac{1}{2}(|00\rangle + |11\rangle)(\langle 00| + \langle 11|)$$



Density Matrix

Instead of dealing with a state $|\phi\rangle$ in vector form, we use its *density matrix*:

$$\rho_\phi = |\phi\rangle \langle\phi| \quad (\text{For a pure state})$$

- positive semi-definite
- $\text{Tr}(\rho) = 1$
- projection ($P = P^\dagger = P^2$)

Example:

$$|\beta_{00}\rangle = \frac{|00\rangle + |11\rangle}{\sqrt{2}}$$

$$\begin{aligned} \rho_{\beta_{00}} &= |\beta_{00}\rangle \langle\beta_{00}| = \frac{1}{2}(|00\rangle + |11\rangle)(\langle 00| + \langle 11|) \\ &= \frac{1}{2}(|00\rangle \langle 00| + |00\rangle \langle 11| + |11\rangle \langle 00| + |11\rangle \langle 11|) \end{aligned}$$



Density Matrix

Instead of dealing with a state $|\phi\rangle$ in vector form, we use its *density matrix*:

$$\rho_\phi = |\phi\rangle \langle\phi| \quad (\text{For a pure state})$$

- positive semi-definite
- $\text{Tr}(\rho) = 1$
- projection ($P = P^\dagger = P^2$)

Example:

$$\begin{aligned} |\beta_{00}\rangle &= \frac{|00\rangle + |11\rangle}{\sqrt{2}} \\ \rho_{\beta_{00}} &= |\beta_{00}\rangle \langle\beta_{00}| = \frac{1}{2}(|00\rangle + |11\rangle)(\langle 00| + \langle 11|) \\ &= \frac{1}{2}(|00\rangle \langle 00| + |00\rangle \langle 11| + |11\rangle \langle 00| + |11\rangle \langle 11|) \\ &= \frac{1}{2} \begin{pmatrix} 1 & 0 & 0 & 1 \\ 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 \\ 1 & 0 & 0 & 1 \end{pmatrix} \end{aligned}$$



Reduced Density Matrix

Suppose we have a composite quantum system $AB = A \otimes B$, and we want to focus our attention on a state $|\phi\rangle \in AB$ with respect to subsystem A .



Reduced Density Matrix

Suppose we have a composite quantum system $AB = A \otimes B$, and we want to focus our attention on a state $|\phi\rangle \in AB$ with respect to subsystem A .

$$A = \mathbb{C}^{2^n} \times \mathbb{C}^{2^n} \quad B = \mathbb{C}^{2^m} \times \mathbb{C}^{2^m}$$
$$AB = (\mathbb{C}^{2^n} \times \mathbb{C}^{2^n}) \otimes (\mathbb{C}^{2^m} \times \mathbb{C}^{2^m})$$



Reduced Density Matrix

Suppose we have a composite quantum system $AB = A \otimes B$, and we want to focus our attention on a state $|\phi\rangle \in AB$ with respect to subsystem A .

$$A = \mathbb{C}^{2^n} \times \mathbb{C}^{2^n} \quad B = \mathbb{C}^{2^m} \times \mathbb{C}^{2^m}$$

$$AB = (\mathbb{C}^{2^n} \times \mathbb{C}^{2^n}) \otimes (\mathbb{C}^{2^m} \times \mathbb{C}^{2^m})$$

$$Tr_B[\rho] : AB \rightarrow A$$

$$Tr_A[\rho] : AB \rightarrow B$$

$$Tr_B[\alpha \otimes \beta] = \alpha \cdot Tr(\beta)$$

$$Tr_A[\alpha \otimes \beta] = Tr(\alpha) \cdot \beta$$

$$Tr_S[\rho + \sigma] = Tr_S[\rho] + Tr_S[\sigma] \text{ (Linearity)}$$



Reduced Density Matrix

Suppose we have a composite quantum system $AB = A \otimes B$, and we want to focus our attention on a state $|\phi\rangle \in AB$ with respect to subsystem A .

$$A = \mathbb{C}^{2^n} \times \mathbb{C}^{2^n} \quad B = \mathbb{C}^{2^m} \times \mathbb{C}^{2^m}$$

$$AB = (\mathbb{C}^{2^n} \times \mathbb{C}^{2^n}) \otimes (\mathbb{C}^{2^m} \times \mathbb{C}^{2^m})$$

$$Tr_B[\rho] : AB \rightarrow A$$

$$Tr_A[\rho] : AB \rightarrow B$$

$$Tr_B[\alpha \otimes \beta] = \alpha \cdot Tr(\beta)$$

$$Tr_A[\alpha \otimes \beta] = Tr(\alpha) \cdot \beta$$

$$Tr_S[\rho + \sigma] = Tr_S[\rho] + Tr_S[\sigma] \text{ (Linearity)}$$

Partial trace $Tr_B[\rho]$ **traces out** subsystem B .



Example

$$A = \mathbb{C}^2 \times \mathbb{C}^2 \quad B = \mathbb{C}^2 \times \mathbb{C}^2 \quad AB = A \otimes B$$

$$\rho_{\beta_{00}} = |\beta_{00}\rangle \langle \beta_{00}| = \frac{|00\rangle \langle 00| + |00\rangle \langle 11| + |11\rangle \langle 00| + |11\rangle \langle 11|}{2}$$

$$Tr_B[\rho_{\beta_{00}}] =$$



Example

$$A = \mathbb{C}^2 \times \mathbb{C}^2 \quad B = \mathbb{C}^2 \times \mathbb{C}^2 \quad AB = A \otimes B$$

$$\rho_{\beta_{00}} = |\beta_{00}\rangle \langle \beta_{00}| = \frac{|00\rangle \langle 00| + |00\rangle \langle 11| + |11\rangle \langle 00| + |11\rangle \langle 11|}{2}$$

$$\text{Tr}_B[\rho_{\beta_{00}}] = \frac{(\text{Tr}_B[|00\rangle \langle 00|] + \text{Tr}_b[|00\rangle \langle 11|] + \text{Tr}_b[|11\rangle \langle 00|] + \text{Tr}_b[|11\rangle \langle 11|])}{2}$$



Example

$$A = \mathbb{C}^2 \times \mathbb{C}^2 \quad B = \mathbb{C}^2 \times \mathbb{C}^2 \quad AB = A \otimes B$$

$$\rho_{\beta_{00}} = |\beta_{00}\rangle \langle \beta_{00}| = \frac{|00\rangle \langle 00| + |00\rangle \langle 11| + |11\rangle \langle 00| + |11\rangle \langle 11|}{2}$$

$$\begin{aligned} \text{Tr}_B[\rho_{\beta_{00}}] &= \frac{(\text{Tr}_B[|00\rangle \langle 00|] + \text{Tr}_B[|00\rangle \langle 11|] + \text{Tr}_B[|11\rangle \langle 00|] + \text{Tr}_B[|11\rangle \langle 11|])}{2} \\ &= \frac{(|0\rangle \langle 0| \cdot \langle 0|0\rangle) + (|0\rangle \langle 1| \cdot \langle 0|1\rangle) + (|1\rangle \langle 0| \cdot \langle 1|0\rangle) + (|1\rangle \langle 1| \cdot \langle 1|1\rangle)}{2} \end{aligned}$$



Example

$$A = \mathbb{C}^2 \times \mathbb{C}^2 \quad B = \mathbb{C}^2 \times \mathbb{C}^2 \quad AB = A \otimes B$$

$$\rho_{\beta_{00}} = |\beta_{00}\rangle \langle \beta_{00}| = \frac{|00\rangle \langle 00| + |00\rangle \langle 11| + |11\rangle \langle 00| + |11\rangle \langle 11|}{2}$$

$$\begin{aligned} \text{Tr}_B[\rho_{\beta_{00}}] &= \frac{(\text{Tr}_B[|00\rangle \langle 00|] + \text{Tr}_B[|00\rangle \langle 11|] + \text{Tr}_B[|11\rangle \langle 00|] + \text{Tr}_B[|11\rangle \langle 11|])}{2} \\ &= \frac{(|0\rangle \langle 0| \cdot \langle 0|0\rangle) + (|0\rangle \langle 1| \cdot \langle 0|1\rangle) + (|1\rangle \langle 0| \cdot \langle 1|0\rangle) + (|1\rangle \langle 1| \cdot \langle 1|1\rangle)}{2} \end{aligned}$$



Example

$$A = \mathbb{C}^2 \times \mathbb{C}^2 \quad B = \mathbb{C}^2 \times \mathbb{C}^2 \quad AB = A \otimes B$$

$$\rho_{\beta_{00}} = |\beta_{00}\rangle \langle \beta_{00}| = \frac{|00\rangle \langle 00| + |00\rangle \langle 11| + |11\rangle \langle 00| + |11\rangle \langle 11|}{2}$$

$$\begin{aligned} Tr_B[\rho_{\beta_{00}}] &= \frac{(Tr_B[|00\rangle \langle 00|] + Tr_B[|00\rangle \langle 11|] + Tr_B[|11\rangle \langle 00|] + Tr_B[|11\rangle \langle 11|])}{2} \\ &= \frac{(|0\rangle \langle 0| \cdot \langle 0|0\rangle) + (|0\rangle \langle 1| \cdot \langle 0|1\rangle) + (|1\rangle \langle 0| \cdot \langle 1|0\rangle) + (|1\rangle \langle 1| \cdot \langle 1|1\rangle)}{2} \\ &= \frac{|0\rangle \langle 0| + |1\rangle \langle 1|}{2} \end{aligned}$$



Loss of precision

Computing a reduced density matrix **discards information!**

$$\rho_{\beta_{00}} = \frac{|00\rangle\langle 00| + |00\rangle\langle 11| + |11\rangle\langle 00| + |11\rangle\langle 11|}{2} \quad (\text{Pure state})$$

$$\rho_2 = \frac{|00\rangle\langle 00| + |01\rangle\langle 01| + |10\rangle\langle 10| + |11\rangle\langle 11|}{4} \quad (\text{Mixed state})$$



Loss of precision

Computing a reduced density matrix **discards information!**

$$\rho_{\beta_{00}} = \frac{|00\rangle\langle 00| + |00\rangle\langle 11| + |11\rangle\langle 00| + |11\rangle\langle 11|}{2} \quad (\text{Pure state})$$

$$\rho_2 = \frac{|00\rangle\langle 00| + |01\rangle\langle 01| + |10\rangle\langle 10| + |11\rangle\langle 11|}{4} \quad (\text{Mixed state})$$

$$\text{Tr}_B[\rho_{\beta_{00}}] = \frac{|0\rangle\langle 0| + |1\rangle\langle 1|}{2} = \text{Tr}_B[\rho_2]$$

The partial traces of two different initial states can be equal.

For a state $\rho \in A \otimes B$, even if we know $\text{Tr}_B[\rho]$ and $\text{Tr}_A[\rho]$, we cannot uniquely determine ρ .



Projection Subspaces

Each projection P corresponds to a linear subspace $\{v \mid Pv = v\}$.

The support of a matrix P is the subspace orthogonal to its kernel, i.e., the set $\{v \mid Pv \neq 0\}$.



Roadmap

- ① Introduction
 - Reasons
 - Abstract Interpretation
- ② Preliminaries
 - Density Matrix
 - Reduced Density Matrix
- ③ Abstract Domain
 - Abstraction and Concretization Functions
 - Abstract Operations
 - Assertions



Abstract Domain

$$\mathcal{D} = \mathbb{C}^{2^n} \otimes \mathbb{C}^{2^n}, \quad S = (s_1, \dots, s_m), \quad 1 \leq m \leq 2^n, \quad s_i \subseteq [n]$$



Abstract Domain

$$\mathcal{D} = \mathbb{C}^{2^n} \otimes \mathbb{C}^{2^n}, \quad S = (s_1, \dots, s_m), \quad 1 \leq m \leq 2^n, \quad s_i \subseteq [n]$$

$$AbsDom(S) = \left\{ (P_{s_1}, \dots, P_{s_m}) \mid P_{s_i} \text{ is a projection in } \mathbb{C}^{2^{|s_i|}} \otimes \mathbb{C}^{2^{|s_i|}} \right\}$$



Abstract Domain

$$\mathcal{D} = \mathbb{C}^{2^n} \otimes \mathbb{C}^{2^n}, \quad S = (s_1, \dots, s_m), \quad 1 \leq m \leq 2^n, \quad s_i \subseteq [n]$$

$$AbsDom(S) = \left\{ (P_{s_1}, \dots, P_{s_m}) \mid P_{s_i} \text{ is a projection in } \mathbb{C}^{2^{|s_i|}} \otimes \mathbb{C}^{2^{|s_i|}} \right\}$$

Intuitively, given a tuple S of sets of qubits, an abstract state $\bar{\sigma} \in AbsDom(S)$ is a tuple of projections over those qubits.



Abstract Domain

$$\mathcal{D} = \mathbb{C}^{2^n} \otimes \mathbb{C}^{2^n}, \quad S = (s_1, \dots, s_m), \quad 1 \leq m \leq 2^n, \quad s_i \subseteq [n]$$

$$AbsDom(S) = \left\{ (P_{s_1}, \dots, P_{s_m}) \mid P_{s_i} \text{ is a projection in } \mathbb{C}^{2^{|s_i|}} \otimes \mathbb{C}^{2^{|s_i|}} \right\}$$

Intuitively, given a tuple S of sets of qubits, an abstract state $\bar{\sigma} \in AbsDom(S)$ is a tuple of projections over those qubits.

Special case:

$$T = ([n]) \Rightarrow AbsDom(T) \simeq \mathcal{D}$$



Fineness Relation

Let $S = (s_1, \dots, s_m)$ and $T = (t_1, \dots, t_m)$ (with $1 \leq m \leq 2^n$), then:

$$\underbrace{S \sqsubseteq T} \triangleq \forall i \in [m]. s_i \subseteq t_i$$

“T is finer than S”

T is “more concrete” than S .

Least element: $\perp = (\emptyset, \dots, \emptyset)$.

Greatest element: $\top = ([n], \dots, [n])$.

$AbsDom(\perp)$ corresponds to a state so abstract that it holds no information at all.

$AbsDom(\top)$ corresponds to tuples where every projection is a concrete state.



Abstraction Function

$$S \sqsubseteq T \triangleq \forall i \in [m]. s_i \subseteq t_i$$
$$\alpha_{T \rightarrow S} : AbsDom(T) \rightarrow AbsDom(S)$$



Abstraction Function

$$S \trianglelefteq T \triangleq \forall i \in [m]. s_i \subseteq t_i$$

$$\alpha_{T \rightarrow S} : \text{AbsDom}(T) \rightarrow \text{AbsDom}(S)$$

$$\alpha_{T \rightarrow S}(Q_{t_1}, \dots, Q_{t_m}) = (P_{s_1}, \dots, P_{s_m})$$

$$P_{s_i} = \bigcap_{t_j. s_i \subseteq t_j} \text{supp}(Tr_{t_j \setminus s_i}[Q_{t_j}])$$



Abstraction Function

$$S \trianglelefteq T \triangleq \forall i \in [m]. s_i \subseteq t_i$$

$$\alpha_{T \rightarrow S} : AbsDom(T) \rightarrow AbsDom(S)$$

$$\alpha_{T \rightarrow S}(Q_{t_1}, \dots, Q_{t_m}) = (P_{s_1}, \dots, P_{s_m})$$

$$P_{s_i} = \bigcap_{t_j. s_i \subseteq t_j} supp(Tr_{t_j \setminus s_i}[Q_{t_j}])$$

Given an abstract state $\bar{\tau} \in AbsDom(T) = (Q_{t_1}, \dots, Q_{t_m})$, we want to compute $\bar{\sigma} \in AbsDom(S) = (P_{s_1}, \dots, P_{s_m})$. For each $i \in [m]$:



Abstraction Function

$$S \sqsubseteq T \triangleq \forall i \in [m]. s_i \subseteq t_i$$

$$\alpha_{T \rightarrow S} : AbsDom(T) \rightarrow AbsDom(S)$$

$$\alpha_{T \rightarrow S}(Q_{t_1}, \dots, Q_{t_m}) = (P_{s_1}, \dots, P_{s_m})$$

$$P_{s_i} = \bigcap_{t_j. s_i \subseteq t_j} supp(Tr_{t_j \setminus s_i}[Q_{t_j}])$$

Given an abstract state $\bar{\tau} \in AbsDom(T) = (Q_{t_1}, \dots, Q_{t_m})$, we want to compute $\bar{\sigma} \in AbsDom(S) = (P_{s_1}, \dots, P_{s_m})$. For each $i \in [m]$:

- ① Find all Q_{t_j} s such that $s_i \subseteq t_j$. We know that at least one exists (for $j = i$), since $S \sqsubseteq T$.



Abstraction Function

$$S \trianglelefteq T \triangleq \forall i \in [m]. s_i \subseteq t_i$$

$$\alpha_{T \rightarrow S} : AbsDom(T) \rightarrow AbsDom(S)$$

$$\alpha_{T \rightarrow S}(Q_{t_1}, \dots, Q_{t_m}) = (P_{s_1}, \dots, P_{s_m})$$

$$P_{s_i} = \bigcap_{t_j. s_i \subseteq t_j} supp(Tr_{t_j \setminus s_i}[Q_{t_j}])$$

Given an abstract state $\bar{\tau} \in AbsDom(T) = (Q_{t_1}, \dots, Q_{t_m})$, we want to compute $\bar{\sigma} \in AbsDom(S) = (P_{s_1}, \dots, P_{s_m})$. For each $i \in [m]$:

- ① Find all Q_{t_j} s such that $s_i \subseteq t_j$. We know that at least one exists (for $j = i$), since $S \trianglelefteq T$.
- ② For each Q_{t_j} found, trace out the bits in t_j that are not in s_i .



Abstraction Function

$$S \trianglelefteq T \triangleq \forall i \in [m]. s_i \subseteq t_i$$

$$\alpha_{T \rightarrow S} : \text{AbsDom}(T) \rightarrow \text{AbsDom}(S)$$

$$\alpha_{T \rightarrow S}(Q_{t_1}, \dots, Q_{t_m}) = (P_{s_1}, \dots, P_{s_m})$$

$$P_{s_i} = \bigcap_{t_j. s_i \subseteq t_j} \text{supp}(\text{Tr}_{t_j \setminus s_i}[Q_{t_j}])$$

Given an abstract state $\bar{\tau} \in \text{AbsDom}(T) = (Q_{t_1}, \dots, Q_{t_m})$, we want to compute $\bar{\sigma} \in \text{AbsDom}(S) = (P_{s_1}, \dots, P_{s_m})$. For each $i \in [m]$:

- ① Find all Q_{t_j} s such that $s_i \subseteq t_j$. We know that at least one exists (for $j = i$), since $S \trianglelefteq T$.
- ② For each Q_{t_j} found, trace out the bits in t_j that are not in s_i .
- ③ Compute the support of the traced matrices (to preserve the structure of projections).



Abstraction Function

$$S \trianglelefteq T \triangleq \forall i \in [m]. s_i \subseteq t_i$$

$$\alpha_{T \rightarrow S} : \text{AbsDom}(T) \rightarrow \text{AbsDom}(S)$$

$$\alpha_{T \rightarrow S}(Q_{t_1}, \dots, Q_{t_m}) = (P_{s_1}, \dots, P_{s_m})$$

$$P_{s_i} = \bigcap_{t_j. s_i \subseteq t_j} \text{supp}(\text{Tr}_{t_j \setminus s_i}[Q_{t_j}])$$

Given an abstract state $\bar{\tau} \in \text{AbsDom}(T) = (Q_{t_1}, \dots, Q_{t_m})$, we want to compute $\bar{\sigma} \in \text{AbsDom}(S) = (P_{s_1}, \dots, P_{s_m})$. For each $i \in [m]$:

- ① Find all Q_{t_j} s such that $s_i \subseteq t_j$. We know that at least one exists (for $j = i$), since $S \trianglelefteq T$.
- ② For each Q_{t_j} found, trace out the bits in t_j that are not in s_i .
- ③ Compute the support of the traced matrices (to preserve the structure of projections).
- ④ Compute the intersection of the supports.



Concretization Function

$$S \sqsubseteq T \triangleq \forall i \in [m]. s_i \subseteq t_i$$

$$\gamma_{S \rightarrow T} : \text{AbsDom}(S) \rightarrow \text{AbsDom}(T)$$



Concretization Function

$$S \sqsubseteq T \triangleq \forall i \in [m]. s_i \subseteq t_i$$

$$\gamma_{S \rightarrow T} : \text{AbsDom}(S) \rightarrow \text{AbsDom}(T)$$

$$\gamma_{S \rightarrow T}(P_{s_1}, \dots, P_{s_m}) = (Q_{t_1}, \dots, Q_{t_m})$$

$$Q_{t_j} = \bigcap_{s_i. s_i \subseteq t_j} P_{s_i} \otimes I_{t_j \setminus s_i}$$



Concretization Function

$$S \sqsubseteq T \triangleq \forall i \in [m]. s_i \subseteq t_i$$

$$\gamma_{S \rightarrow T} : AbsDom(S) \rightarrow AbsDom(T)$$

$$\gamma_{S \rightarrow T}(P_{s_1}, \dots, P_{s_m}) = (Q_{t_1}, \dots, Q_{t_m})$$

$$Q_{t_j} = \bigcap_{s_i. s_i \subseteq t_j} P_{s_i} \otimes I_{t_j \setminus s_i}$$

Given an abstract state $\bar{\sigma} \in AbsDom(S) = (P_{s_1}, \dots, P_{s_m})$, we want to compute $\bar{\tau} \in AbsDom(T) = (Q_{t_1}, \dots, Q_{t_m})$. For each $j \in [m]$:



Concretization Function

$$S \sqsubseteq T \triangleq \forall i \in [m]. s_i \subseteq t_i$$

$$\gamma_{S \rightarrow T} : AbsDom(S) \rightarrow AbsDom(T)$$

$$\gamma_{S \rightarrow T}(P_{s_1}, \dots, P_{s_m}) = (Q_{t_1}, \dots, Q_{t_m})$$

$$Q_{t_j} = \bigcap_{s_i. s_i \subseteq t_j} P_{s_i} \otimes I_{t_j \setminus s_i}$$

Given an abstract state $\bar{\sigma} \in AbsDom(S) = (P_{s_1}, \dots, P_{s_m})$, we want to compute $\bar{\tau} \in AbsDom(T) = (Q_{t_1}, \dots, Q_{t_m})$. For each $j \in [m]$:

- 1 Find all P_{s_i} s such that $s_i \subseteq t_j$. We know at least one exists (for $i = j$), since $S \sqsubseteq T$.



Concretization Function

$$S \sqsubseteq T \triangleq \forall i \in [m]. s_i \subseteq t_i$$

$$\gamma_{S \rightarrow T} : AbsDom(S) \rightarrow AbsDom(T)$$

$$\gamma_{S \rightarrow T}(P_{s_1}, \dots, P_{s_m}) = (Q_{t_1}, \dots, Q_{t_m})$$

$$Q_{t_j} = \bigcap_{s_i. s_i \subseteq t_j} P_{s_i} \otimes I_{t_j \setminus s_i}$$

Given an abstract state $\bar{\sigma} \in AbsDom(S) = (P_{s_1}, \dots, P_{s_m})$, we want to compute $\bar{\tau} \in AbsDom(T) = (Q_{t_1}, \dots, Q_{t_m})$. For each $j \in [m]$:

- ① Find all P_{s_i} s such that $s_i \subseteq t_j$. We know at least one exists (for $i = j$), since $S \sqsubseteq T$.
- ② Extend the projection to the space of all qubits in t_j , by computing the tensor product with the identity matrix.



Concretization Function

$$S \sqsubseteq T \triangleq \forall i \in [m]. s_i \subseteq t_i$$

$$\gamma_{S \rightarrow T} : AbsDom(S) \rightarrow AbsDom(T)$$

$$\gamma_{S \rightarrow T}(P_{s_1}, \dots, P_{s_m}) = (Q_{t_1}, \dots, Q_{t_m})$$

$$Q_{t_j} = \bigcap_{s_i. s_i \subseteq t_j} P_{s_i} \otimes I_{t_j \setminus s_i}$$

Given an abstract state $\bar{\sigma} \in AbsDom(S) = (P_{s_1}, \dots, P_{s_m})$, we want to compute $\bar{\tau} \in AbsDom(T) = (Q_{t_1}, \dots, Q_{t_m})$. For each $j \in [m]$:

- ① Find all P_{s_i} s such that $s_i \subseteq t_j$. We know at least one exists (for $i = j$), since $S \sqsubseteq T$.
- ② Extend the projection to the space of all qubits in t_j , by computing the tensor product with the identity matrix.
- ③ Compute the intersection of the extended projections.



Order Relation on Abstract States

$$1 \leq m \leq 2^n, \quad S = (s_1, \dots, s_m), \quad \forall i \in [m]. \ s_i \subseteq [n]$$

$$\bar{\sigma} \in \text{AbsDom}(S) = (P_{s_1}, \dots, P_{s_m}), \quad \bar{\tau} \in \text{AbsDom}(S) = (Q_{s_1}, \dots, Q_{s_m})$$

$$\bar{\sigma} \sqsubseteq \bar{\tau} \triangleq \forall i \in [m]. \underbrace{P_{s_i} \subseteq Q_{s_i}}$$

Subspace interpretation
of projections



Monotonicity

$$S \trianglelefteq T$$

$$\forall \bar{\sigma}, \bar{\tau} \in \text{AbsDom}(T). \quad \bar{\sigma} \sqsubseteq \bar{\tau} \Rightarrow \alpha_{T \rightarrow S}(\bar{\sigma}) \sqsubseteq \alpha_{T \rightarrow S}(\bar{\tau})$$

$$\forall \bar{\sigma}, \bar{\tau} \in \text{AbsDom}(T). \quad \bar{\sigma} \sqsubseteq \bar{\tau} \Rightarrow \gamma_{T \rightarrow S}(\bar{\sigma}) \sqsubseteq \gamma_{T \rightarrow S}(\bar{\tau})$$



Galois connection

$$\begin{aligned}
 & S \trianglelefteq T \\
 & \forall \bar{\sigma} \in \text{AbsDom}(S). \forall \bar{\tau} \in \text{AbsDom}(T). \\
 & \left(\begin{array}{c} \bar{\tau} \sqsubseteq \gamma_{S \rightarrow T}(\bar{\sigma}) \Rightarrow \alpha_{T \rightarrow S}(\bar{\tau}) \sqsubseteq \bar{\sigma} \\ \wedge \\ (\exists \bar{\rho} \in \text{AbsDom}([n]^m). \bar{\tau} = \alpha_{[n]^m \rightarrow T}(\bar{\rho})) \Rightarrow \bar{\tau} \sqsubseteq \gamma_{S \rightarrow T}(\bar{\sigma}) \Leftrightarrow \alpha_{T \rightarrow S}(\bar{\tau}) \sqsubseteq \bar{\sigma} \end{array} \right)
 \end{aligned}$$

$$\begin{aligned}
 & \forall \bar{\sigma} \in \text{AbsDom}(S). \forall \bar{\tau} \in \text{AbsDom}([n]^m). \\
 & \bar{\tau} \sqsubseteq \gamma_{S \rightarrow [n]^m}(\bar{\sigma}) \Leftrightarrow \alpha_{[n]^m \rightarrow S}(\bar{\tau}) \sqsubseteq \bar{\sigma}
 \end{aligned}$$



Abstract Operations

Operations on the concrete domain are unitary operators U .

To apply them to a concrete state ρ we compute $U\rho U^\dagger$.

We want to define $U^\# : AbsDom(S) \rightarrow AbsDom(S)$.

Let $T = (t_1, \dots, t_m)$ s.t. $t_i = s_i \cup s_U$, where s_U denotes the set of qubits that matrix U acts on.

Let $U^{cg}(\bar{\sigma}) = (UT_{t_1}U^\dagger, \dots, UT_{t_m}U^\dagger)$, then

$$U^\# = \alpha_{T \rightarrow S} \circ U^{cg} \circ \gamma_{S \rightarrow T}$$



Focus

$$U^\sharp = \alpha_{T \rightarrow S} \circ U^{cg} \circ \gamma_{S \rightarrow T}$$



Focus

$$U^\sharp = \alpha_{T \rightarrow S} \circ U^{cg} \circ \gamma_{S \rightarrow T}$$

$$AbsDom(S) \xrightarrow[\text{Focus}]{\gamma_{S \rightarrow T}} AbsDom(T) \xrightarrow[\text{Apply}]{U^{cg}} AbsDom(T) \xrightarrow[\text{Unfocus}]{\alpha_{T \rightarrow S}} AbsDom(S)$$



Focus

$$U^\sharp = \alpha_{T \rightarrow S} \circ U^{cg} \circ \gamma_{S \rightarrow T}$$

$$AbsDom(S) \xrightarrow[\text{Focus}]{\gamma_{S \rightarrow T}} AbsDom(T) \xrightarrow[\text{Apply}]{U^{cg}} AbsDom(T) \xrightarrow[\text{Unfocus}]{\alpha_{T \rightarrow S}} AbsDom(S)$$

Focus - concretize to a new, finer domain with sufficient precision to accurately represent the operation;



Focus

$$U^\sharp = \alpha_{T \rightarrow S} \circ U^{cg} \circ \gamma_{S \rightarrow T}$$

$$AbsDom(S) \xrightarrow[\text{Focus}]{\gamma_{S \rightarrow T}} AbsDom(T) \xrightarrow[\text{Apply}]{U^{cg}} AbsDom(T) \xrightarrow[\text{Unfocus}]{\alpha_{T \rightarrow S}} AbsDom(S)$$

Focus - concretize to a new, finer domain with sufficient precision to accurately represent the operation;

Apply - apply the unitary operator to all the elements in the tuple



Focus

$$U^\sharp = \alpha_{T \rightarrow S} \circ U^{cg} \circ \gamma_{S \rightarrow T}$$

$$AbsDom(S) \xrightarrow[\text{Focus}]{\gamma_{S \rightarrow T}} AbsDom(T) \xrightarrow[\text{Apply}]{U^{cg}} AbsDom(T) \xrightarrow[\text{Unfocus}]{\alpha_{T \rightarrow S}} AbsDom(S)$$

Focus - concretize to a new, finer domain with sufficient precision to accurately represent the operation;

Apply - apply the unitary operator to all the elements in the tuple

Unfocus - abstract back to the original abstract domain to keep the representation more compact



Assertions

We want to check that a state of a program lies in the span of two vectors.

We define an assertion as:

$$A = \text{span}\{v_1 = |a_1\rangle \dots |a_n\rangle, v_2 = |b_1\rangle \dots |b_n\rangle\}$$

And a projection $\text{proj}(A)$ onto this subspace, such that:

$$\text{proj}(A)v_1 = v_1 \quad \text{proj}(A)v_2 = v_2$$



Connectivity

$$S = (s_1, \dots, s_m)$$

S is connected $\triangleq \forall k \in [n-1]. \exists r \in [m]. k \in s_r \wedge k+1 \in s_r$



Connectivity

$$S = (s_1, \dots, s_m)$$

S is connected $\triangleq \forall k \in [n-1]. \exists r \in [m]. k \in s_r \wedge k+1 \in s_r$

Example:

$$n = 5, \quad m = 3$$

$$S = (\{0, 2, 3\}, \{0, 1, 2\}, \{3, 4, 5\})$$



Connectivity

$$S = (s_1, \dots, s_m)$$

S is connected $\triangleq \forall k \in [n-1]. \exists r \in [m]. k \in s_r \wedge k+1 \in s_r$

Example:

$$n = 5, \quad m = 3$$

$$0, 1 \in \{0, 1, 2\}$$

$$S = (\{0, 2, 3\}, \{0, 1, 2\}, \{3, 4, 5\})$$



Connectivity

$$S = (s_1, \dots, s_m)$$

S is connected $\triangleq \forall k \in [n-1]. \exists r \in [m]. k \in s_r \wedge k+1 \in s_r$

Example:

$$n = 5, \quad m = 3$$

$$1, 2 \in \{0, 1, 2\}$$

$$S = (\{0, 2, 3\}, \{0, 1, 2\}, \{3, 4, 5\})$$



Connectivity

$$S = (s_1, \dots, s_m)$$

S is connected $\triangleq \forall k \in [n-1]. \exists r \in [m]. k \in s_r \wedge k+1 \in s_r$

Example:

$$n = 5, \quad m = 3$$

$$2, 3 \in \{0, 2, 3\}$$

$$S = (\{0, 2, 3\}, \{0, 1, 2\}, \{3, 4, 5\})$$



Connectivity

$$S = (s_1, \dots, s_m)$$

S is connected $\triangleq \forall k \in [n-1]. \exists r \in [m]. k \in s_r \wedge k+1 \in s_r$

Example:

$$n = 5, \quad m = 3$$

$$3, 4 \in \{3, 4, 5\}$$

$$S = (\{0, 2, 3\}, \{0, 1, 2\}, \{3, 4, 5\})$$



Connectivity

$$S = (s_1, \dots, s_m)$$

S is connected $\triangleq \forall k \in [n-1]. \exists r \in [m]. k \in s_r \wedge k+1 \in s_r$

Example:

$$n = 5, \quad m = 3$$

$$4, 5 \in \{3, 4, 5\}$$

$$S = (\{0, 2, 3\}, \{0, 1, 2\}, \{3, 4, 5\})$$



Connectivity

$$S = (s_1, \dots, s_m)$$

$$S \text{ is connected} \triangleq \forall k \in [n-1]. \exists r \in [m]. k \in s_r \wedge k+1 \in s_r$$

Example:

$$n = 5, \quad m = 3$$

$$S = (\{0, 2, 3\}, \{0, 1, 2\}, \{3, 4, 5\})$$

For an assertion A , if S is connected, then:

$$proj(A) = \gamma_{S \rightarrow [n]^m}(\alpha_{[n]^m \rightarrow S}(proj(A)))$$



Assertion Checking

Given an assertion A , if the final state of a computation is v and the final abstract state of the abstract interpretation is $\bar{v} \in \text{AbsDom}(S)$, with S connected, then:

$$\bar{v} \sqsubseteq \alpha_{[n]^m \rightarrow S}(\text{proj}(A)) \quad \Rightarrow \quad v \in A$$



Choice of Tuple S

Fundamental choice for the shape of the abstract domain and, in turn, the success of the analysis.



Choice of Tuple S

Fundamental choice for the shape of the abstract domain and, in turn, the success of the analysis.

Type of S	Pros	Cons
Less, smaller sets	Less computational cost and memory footprint	Less precision
More, bigger sets	More computational cost and memory footprint	More precision



Choice of Tuple S

Fundamental choice for the shape of the abstract domain and, in turn, the success of the analysis.

Type of S	Pros	Cons
Less, smaller sets	Less computational cost and memory footprint	Less precision
More, bigger sets	More computational cost and memory footprint	More precision

Examples:

- $S_0 =$ all 2^n combinations of up to n qubits
- $S_1 =$ all $\binom{n}{k}$ combinations of exactly k qubits
- $S_2 =$ sets that contain qubits used by at least two 3-qubit gates
- ...



Assertion Checking Example

We want to check (partial) correctness of Grover's algorithm.

Grover's algorithm steps:

- 1 Prepare the initial state $|\phi\rangle^{(0)}$
- 2 Repeat approx. $\frac{\pi}{4}\sqrt{N}$ times $|\phi\rangle^{(t+1)} = G|\phi\rangle^{(t)}$.
- 3 Measure in the computational basis.

With this abstract interpretation framework, we can prove the loop invariant:

$$|\phi\rangle^{(t)} \in A = \text{span}\{|\beta\rangle, |\phi\rangle\}$$



Assertion Checking Example (ctd.)

$$P(v) \triangleq v \in A = \text{span}\{|\beta\rangle, |\phi\rangle\}$$

$$G|\phi\rangle^{(t)} \in A = G|\beta\rangle \in A \wedge G|\phi\rangle \in A \quad \text{By linearity of } G \text{ and } |\phi\rangle^{(t)} \in A$$



Assertion Checking Example (ctd.)

$$P(v) \triangleq v \in A = \text{span}\{|\beta\rangle, |\phi\rangle\}$$

We need to check:

$$\textcircled{1} P(|\phi\rangle^{(0)})$$

$$G|\phi\rangle^{(t)} \in A = G|\beta\rangle \in A \wedge G|\phi\rangle \in A \quad \text{By linearity of } G \text{ and } |\phi\rangle^{(t)} \in A$$



Assertion Checking Example (ctd.)

$$P(v) \triangleq v \in A = \text{span}\{|\beta\rangle, |\phi\rangle\}$$

We need to check:

$$\textcircled{1} P(|\phi\rangle^{(0)}) \triangleq |\phi\rangle \in \text{span}\{|\beta\rangle, |\phi\rangle\}$$

$$G|\phi\rangle^{(t)} \in A = G|\beta\rangle \in A \wedge G|\phi\rangle \in A \quad \text{By linearity of } G \text{ and } |\phi\rangle^{(t)} \in A$$



Assertion Checking Example (ctd.)

$$P(v) \triangleq v \in A = \text{span}\{|\beta\rangle, |\phi\rangle\}$$

We need to check:

- ① $P(|\phi\rangle^{(0)}) \triangleq |\phi\rangle \in \text{span}\{|\beta\rangle, |\phi\rangle\}$
- ② $P(|\phi\rangle^{(t)}) \Rightarrow P(|\phi\rangle^{(t+1)})$

$$G|\phi\rangle^{(t)} \in A = G|\beta\rangle \in A \wedge G|\phi\rangle \in A \quad \text{By linearity of } G \text{ and } |\phi\rangle^{(t)} \in A$$



Assertion Checking Example (ctd.)

$$P(v) \triangleq v \in A = \text{span}\{|\beta\rangle, |\phi\rangle\}$$

We need to check:

$$\textcircled{1} P(|\phi\rangle^{(0)}) \triangleq |\phi\rangle \in \text{span}\{|\beta\rangle, |\phi\rangle\}$$

$$\textcircled{2} P(|\phi\rangle^{(t)}) \Rightarrow P(|\phi\rangle^{(t+1)}) \triangleq |\phi\rangle^{(t)} \in A \Rightarrow G|\phi\rangle^{(t)} \in A$$

$$G|\phi\rangle^{(t)} \in A = G|\beta\rangle \in A \wedge G|\phi\rangle \in A \quad \text{By linearity of } G \text{ and } |\phi\rangle^{(t)} \in A$$



Computing the Projection of a Support

To compute a projection corresponding to $\text{supp}(A)$, we:

- 1 take the rows $\{r_1, \dots, r_n\}$ of A ;
- 2 extract an orthonormal set of vectors $\{b_1, \dots, b_n\}$ that span the same subspace as the rows;
- 3 create the matrix $B = \begin{pmatrix} b_1 \\ \dots \\ b_n \end{pmatrix}$;
- 4 return BB^\dagger .



Computing the Projection of an Intersection

$$\{P_1, \dots, P_k\}, \quad \forall i \in [k]. \ P_i = C^n \times C^n$$
$$\bigcap_{i \in [k]} P_i \triangleq I_n - \text{supp}(kI_n - \sum_{i \in [k]} P_i)$$



Computing the Assertion Projection

Given two vectors

$$v_1 = |a_1\rangle \dots |a_n\rangle$$

$$v_2 = |b_1\rangle \dots |b_n\rangle$$

① Create a matrix $P = \begin{pmatrix} v_1^T \\ v_2^T \\ \mathbf{0} \\ \dots \\ \mathbf{0} \end{pmatrix}$

② Return $\text{supp}(P)$



Partial trace

Alternatively:

$$Tr_B[\rho] = \sum_{v=0}^{2^m} (I_A \otimes \langle v|) \rho (I_A \otimes |v\rangle) \quad Tr_A[\rho] = \sum_{v=0}^{2^n} (\langle v| \otimes I_B) \rho (|v\rangle \otimes I_B)$$

Where v labels vectors of an orthonormal basis of the subspace we are tracing out.

