

Alessandro Scala



# Quantum Abstract Interpretation

Seminar for the **Introduction to Quantum Computing** course

Università di Pisa  
Dipartimento di Informatica

Pisa, 24 Luglio 2023

# Roadmap

- ① Introduction
  - Reasons
  - Abstract Interpretation
- ② Preliminaries
  - Density Matrix
  - Reduced Density Matrix
- ③ Abstract Domain
  - Abstraction and Concretization Functions
  - Abstract Operations
  - Assertions
- ④ Conclusions



# Introduction

As quantum computing advances, we would like to have some means to prove correctness properties on quantum programs, *especially* since quantum programming is counterintuitive.



# Reasons

The naive way to check properties of a program is to run it and observe its behaviour.



# Reasons

The naive way to check properties of a program is to run it and **observe** its behaviour.

We **cannot observe** the state of a quantum program!



# Reasons

The naive way to check properties of a program is to run it and **observe** its behaviour.

We **cannot observe** the state of a quantum program!

Could **simulation** on a classical machine solve this issue?



# Reasons

The naive way to check properties of a program is to run it and **observe** its behaviour.

We **cannot observe** the state of a quantum program!

Could **simulation** on a classical machine solve this issue?

No: **exponential** space and time cost.



# Example

$$n_{qubits} = 1$$

$$|0\rangle \langle 0|$$

$$\begin{pmatrix} 1 & 0 \\ 0 & 0 \end{pmatrix}$$

$$2^2 = 4 \text{ complex numbers}$$





# Example

$$n_{qubits} = 2$$

$$|00\rangle \langle 00|$$

$$\begin{pmatrix} 1 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 \end{pmatrix}$$

$$2^4 = 16 \text{ complex numbers}$$



# Example

$$n_{qubits} = 3$$

$$|000\rangle \langle 000|$$

$$\begin{pmatrix} 1 & 0 & 0 & 0 & 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 \end{pmatrix}$$

$$2^6 = 64 \text{ complex numbers}$$



# Example

$$n_{\text{qubits}} = 300$$

$$|0\rangle^{\otimes 300} \langle 0|^{\otimes 300}$$

?????



# Example

$$n_{\text{qubits}} = 300$$

$$|0\rangle^{\otimes 300} \langle 0|^{\otimes 300}$$

$2^{600} = 4149515568809929585124078636911611510124462322424368$   
 $999956573296906528114129081463997070489471037942881978866113$   
 $007891823951510754117753078868748341139636870611818034015095$   
 $23685376$

Bigger than the number of atoms in the universe.



# Reasons

The naive way to check properties of a program is to run it and **observe** its behaviour.

We **cannot observe** the state of a quantum program!

Could **simulation** on a classical machine solve this issue?

No: **exponential** space and time cost.



# Reasons

The naive way to check properties of a program is to run it and **observe** its behaviour.

We **cannot observe** the state of a quantum program!

Could **simulation** on a classical machine solve this issue?

No: **exponential** space and time cost.

Static checking of programs by hand?



# Reasons

The naive way to check properties of a program is to run it and **observe** its behaviour.

We **cannot observe** the state of a quantum program!

Could **simulation** on a classical machine solve this issue?

No: **exponential** space and time cost.

Static checking of programs by hand?

Yes, but time consuming. Needs to be adapted to the specific program.



# Reasons

The naive way to check properties of a program is to run it and **observe** its behaviour.

We **cannot observe** the state of a quantum program!

Could **simulation** on a classical machine solve this issue?

No: **exponential** space and time cost.

Static checking of programs by hand?

Yes, but time consuming. Needs to be adapted to the specific program.

Solution: abstract interpretation





# What is abstract interpretation?

Instead of considering the **concrete domain**, we restrict our analysis to a **more coarse domain**, an **abstract domain**.



# What is abstract interpretation?

Instead of considering the **concrete domain**, we restrict our analysis to a **more coarse domain**, an **abstract domain**.

The abstract domain we consider should be:



# What is abstract interpretation?

Instead of considering the **concrete domain**, we restrict our analysis to a **more coarse domain**, an **abstract domain**.

The abstract domain we consider should be:

**fine enough** to capture the information we are interested in  
(e.g. the state of the quantum system belongs to the span  
of two vectors)



# What is abstract interpretation?

Instead of considering the **concrete domain**, we restrict our analysis to a **more coarse domain**, an **abstract domain**.

The abstract domain we consider should be:

**fine enough** to capture the information we are interested in  
(e.g. the state of the quantum system belongs to the span of two vectors)

**as coarse as possible** to discard information we are not interested in,  
and thus be substantially more efficient to be analyzed



# What is abstract interpretation?

Instead of considering the **concrete domain**, we restrict our analysis to a **more coarse domain**, an **abstract domain**.

The abstract domain we consider should be:

**fine enough** to capture the information we are interested in  
(e.g. the state of the quantum system belongs to the span of two vectors)

**as coarse as possible** to discard information we are not interested in,  
and thus be substantially more efficient to be analyzed

Abstract interpretation is usually sound, but not complete:

- AI returns **true**  $\Rightarrow$  Property is **true**
- AI returns **false**  $\Rightarrow$  Property can be either **true** or **false**



# Ingredients

- Abstract domain



# Ingredients

- Abstract domain
  - Abstraction function: from more concrete to more abstract domain



# Ingredients

- Abstract domain
  - Abstraction function: from more concrete to more abstract domain
  - Concretization function: from more abstract to more concrete domain





# Ingredients

- Abstract domain
  - Abstraction function: from more concrete to more abstract domain
  - Concretization function: from more abstract to more concrete domain
  - Abstract operations: to represent concrete operations in the abstract domain



# Ingredients

- Abstract domain
  - Abstraction function: from more concrete to more abstract domain
  - Concretization function: from more abstract to more concrete domain
  - Abstract operations: to represent concrete operations in the abstract domain
- Assertions: properties we can prove with abstract interpretation



# Roadmap

- ① Introduction
  - Reasons
  - Abstract Interpretation
- ② Preliminaries
  - Density Matrix
  - Reduced Density Matrix
- ③ Abstract Domain
  - Abstraction and Concretization Functions
  - Abstract Operations
  - Assertions
- ④ Conclusions



# Density Matrix

Instead of dealing with a state  $|\phi\rangle$  in vector form, we use its *density matrix*:

$$\rho_\phi = |\phi\rangle \langle\phi| \quad (\text{For a pure state})$$

- positive semi-definite
- $\text{Tr}(\rho) = 1$
- projection ( $P = P^\dagger = P^2$ )



# Density Matrix

Instead of dealing with a state  $|\phi\rangle$  in vector form, we use its *density matrix*:

$$\rho_\phi = |\phi\rangle \langle\phi| \quad (\text{For a pure state})$$

- positive semi-definite
- $\text{Tr}(\rho) = 1$
- projection ( $P = P^\dagger = P^2$ )

Example:

$$|\beta_{00}\rangle = \frac{|00\rangle + |11\rangle}{\sqrt{2}}$$

$$\rho_{\beta_{00}} = |\beta_{00}\rangle \langle\beta_{00}|$$



# Density Matrix

Instead of dealing with a state  $|\phi\rangle$  in vector form, we use its *density matrix*:

$$\rho_\phi = |\phi\rangle \langle\phi| \quad (\text{For a pure state})$$

- positive semi-definite
- $\text{Tr}(\rho) = 1$
- projection ( $P = P^\dagger = P^2$ )

Example:

$$|\beta_{00}\rangle = \frac{|00\rangle + |11\rangle}{\sqrt{2}}$$

$$\rho_{\beta_{00}} = |\beta_{00}\rangle \langle\beta_{00}| = \frac{1}{2}(|00\rangle + |11\rangle)(\langle 00| + \langle 11|)$$



# Density Matrix

Instead of dealing with a state  $|\phi\rangle$  in vector form, we use its *density matrix*:

$$\rho_\phi = |\phi\rangle \langle\phi| \quad (\text{For a pure state})$$

- positive semi-definite
- $\text{Tr}(\rho) = 1$
- projection ( $P = P^\dagger = P^2$ )

Example:

$$|\beta_{00}\rangle = \frac{|00\rangle + |11\rangle}{\sqrt{2}}$$

$$\begin{aligned} \rho_{\beta_{00}} &= |\beta_{00}\rangle \langle\beta_{00}| = \frac{1}{2}(|00\rangle + |11\rangle)(\langle 00| + \langle 11|) \\ &= \frac{1}{2}(|00\rangle \langle 00| + |00\rangle \langle 11| + |11\rangle \langle 00| + |11\rangle \langle 11|) \end{aligned}$$



# Density Matrix

Instead of dealing with a state  $|\phi\rangle$  in vector form, we use its *density matrix*:

$$\rho_\phi = |\phi\rangle \langle\phi| \quad (\text{For a pure state})$$

- positive semi-definite
- $\text{Tr}(\rho) = 1$
- projection ( $P = P^\dagger = P^2$ )

Example:

$$\begin{aligned} |\beta_{00}\rangle &= \frac{|00\rangle + |11\rangle}{\sqrt{2}} \\ \rho_{\beta_{00}} &= |\beta_{00}\rangle \langle\beta_{00}| = \frac{1}{2}(|00\rangle + |11\rangle)(\langle 00| + \langle 11|) \\ &= \frac{1}{2}(|00\rangle \langle 00| + |00\rangle \langle 11| + |11\rangle \langle 00| + |11\rangle \langle 11|) \\ &= \frac{1}{2} \begin{pmatrix} 1 & 0 & 0 & 1 \\ 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 \\ 1 & 0 & 0 & 1 \end{pmatrix} \end{aligned}$$





# Reduced Density Matrix

Suppose we have a composite quantum system  $AB = A \otimes B$ , and we want to focus our attention on a state  $|\phi\rangle \in AB$  with respect to subsystem  $A$ .



# Reduced Density Matrix

Suppose we have a composite quantum system  $AB = A \otimes B$ , and we want to focus our attention on a state  $|\phi\rangle \in AB$  with respect to subsystem  $A$ .

$$A = \mathbb{C}^{2^n} \times \mathbb{C}^{2^n} \quad B = \mathbb{C}^{2^m} \times \mathbb{C}^{2^m}$$
$$AB = (\mathbb{C}^{2^n} \times \mathbb{C}^{2^n}) \otimes (\mathbb{C}^{2^m} \times \mathbb{C}^{2^m})$$



# Reduced Density Matrix

Suppose we have a composite quantum system  $AB = A \otimes B$ , and we want to focus our attention on a state  $|\phi\rangle \in AB$  with respect to subsystem  $A$ .

$$A = \mathbb{C}^{2^n} \times \mathbb{C}^{2^n} \quad B = \mathbb{C}^{2^m} \times \mathbb{C}^{2^m}$$

$$AB = (\mathbb{C}^{2^n} \times \mathbb{C}^{2^n}) \otimes (\mathbb{C}^{2^m} \times \mathbb{C}^{2^m})$$

$$\text{Tr}_B[\rho] : AB \rightarrow A$$

$$\text{Tr}_A[\rho] : AB \rightarrow B$$

$$\text{Tr}_B[\alpha \otimes \beta] = \alpha \cdot \text{Tr}(\beta)$$

$$\text{Tr}_A[\alpha \otimes \beta] = \text{Tr}(\alpha) \cdot \beta$$

$$\left. \begin{aligned} \text{Tr}_S[\rho + \sigma] &= \text{Tr}_S[\rho] + \text{Tr}_S[\sigma] \\ \text{Tr}_S[a \cdot \rho] &= a \cdot \text{Tr}_S[\rho] \end{aligned} \right\} \text{ (Linearity)}$$



# Reduced Density Matrix

Suppose we have a composite quantum system  $AB = A \otimes B$ , and we want to focus our attention on a state  $|\phi\rangle \in AB$  with respect to subsystem  $A$ .

$$A = \mathbb{C}^{2^n} \times \mathbb{C}^{2^n} \quad B = \mathbb{C}^{2^m} \times \mathbb{C}^{2^m}$$

$$AB = (\mathbb{C}^{2^n} \times \mathbb{C}^{2^n}) \otimes (\mathbb{C}^{2^m} \times \mathbb{C}^{2^m})$$

$$Tr_B[\rho] : AB \rightarrow A$$

$$Tr_A[\rho] : AB \rightarrow B$$

$$Tr_B[\alpha \otimes \beta] = \alpha \cdot Tr(\beta)$$

$$Tr_A[\alpha \otimes \beta] = Tr(\alpha) \cdot \beta$$

$$\left. \begin{aligned} Tr_S[\rho + \sigma] &= Tr_S[\rho] + Tr_S[\sigma] \\ Tr_S[a \cdot \rho] &= a \cdot Tr_S[\rho] \end{aligned} \right\} \text{ (Linearity)}$$

Partial trace  $Tr_B[\rho]$  **traces out** subsystem  $B$ .



# Example

$$A = \mathbb{C}^2 \times \mathbb{C}^2 \quad B = \mathbb{C}^2 \times \mathbb{C}^2 \quad AB = A \otimes B$$

$$\rho_{\beta_{00}} = |\beta_{00}\rangle \langle \beta_{00}| = \frac{|00\rangle \langle 00| + |00\rangle \langle 11| + |11\rangle \langle 00| + |11\rangle \langle 11|}{2}$$

$$\text{Tr}_B[\rho_{\beta_{00}}] =$$



# Example

$$A = \mathbb{C}^2 \times \mathbb{C}^2 \quad B = \mathbb{C}^2 \times \mathbb{C}^2 \quad AB = A \otimes B$$

$$\rho_{\beta_{00}} = |\beta_{00}\rangle \langle \beta_{00}| = \frac{|00\rangle \langle 00| + |00\rangle \langle 11| + |11\rangle \langle 00| + |11\rangle \langle 11|}{2}$$

$$Tr_B[\rho_{\beta_{00}}] = \frac{(Tr_B[|00\rangle \langle 00|] + Tr_b[|00\rangle \langle 11|] + Tr_b[|11\rangle \langle 00|] + Tr_b[|11\rangle \langle 11|])}{2}$$



# Example

$$A = \mathbb{C}^2 \times \mathbb{C}^2 \quad B = \mathbb{C}^2 \times \mathbb{C}^2 \quad AB = A \otimes B$$

$$\rho_{\beta_{00}} = |\beta_{00}\rangle \langle \beta_{00}| = \frac{|00\rangle \langle 00| + |00\rangle \langle 11| + |11\rangle \langle 00| + |11\rangle \langle 11|}{2}$$

$$\begin{aligned} Tr_B[\rho_{\beta_{00}}] &= \frac{(Tr_B[|00\rangle \langle 00|] + Tr_B[|00\rangle \langle 11|] + Tr_B[|11\rangle \langle 00|] + Tr_B[|11\rangle \langle 11|])}{2} \\ &= \frac{(|0\rangle \langle 0| \cdot \langle 0|0\rangle) + (|0\rangle \langle 1| \cdot \langle 0|1\rangle) + (|1\rangle \langle 0| \cdot \langle 1|0\rangle) + (|1\rangle \langle 1| \cdot \langle 1|1\rangle)}{2} \end{aligned}$$



# Example

$$A = \mathbb{C}^2 \times \mathbb{C}^2 \quad B = \mathbb{C}^2 \times \mathbb{C}^2 \quad AB = A \otimes B$$

$$\rho_{\beta_{00}} = |\beta_{00}\rangle \langle \beta_{00}| = \frac{|00\rangle \langle 00| + |00\rangle \langle 11| + |11\rangle \langle 00| + |11\rangle \langle 11|}{2}$$

$$\begin{aligned} \text{Tr}_B[\rho_{\beta_{00}}] &= \frac{(\text{Tr}_B[|00\rangle \langle 00|] + \text{Tr}_B[|00\rangle \langle 11|] + \text{Tr}_B[|11\rangle \langle 00|] + \text{Tr}_B[|11\rangle \langle 11|])}{2} \\ &= \frac{(|0\rangle \langle 0| \cdot \langle 0|0\rangle) + (|0\rangle \langle 1| \cdot \langle 0|1\rangle) + (|1\rangle \langle 0| \cdot \langle 1|0\rangle) + (|1\rangle \langle 1| \cdot \langle 1|1\rangle)}{2} \end{aligned}$$





# Example

$$A = \mathbb{C}^2 \times \mathbb{C}^2 \quad B = \mathbb{C}^2 \times \mathbb{C}^2 \quad AB = A \otimes B$$

$$\rho_{\beta_{00}} = |\beta_{00}\rangle \langle \beta_{00}| = \frac{|00\rangle \langle 00| + |00\rangle \langle 11| + |11\rangle \langle 00| + |11\rangle \langle 11|}{2}$$

$$\begin{aligned} Tr_B[\rho_{\beta_{00}}] &= \frac{(Tr_B[|00\rangle \langle 00|] + Tr_B[|00\rangle \langle 11|] + Tr_B[|11\rangle \langle 00|] + Tr_B[|11\rangle \langle 11|])}{2} \\ &= \frac{(|0\rangle \langle 0| \cdot \langle 0|0\rangle) + (|0\rangle \langle 1| \cdot \langle 0|1\rangle) + (|1\rangle \langle 0| \cdot \langle 1|0\rangle) + (|1\rangle \langle 1| \cdot \langle 1|1\rangle)}{2} \\ &= \frac{|0\rangle \langle 0| + |1\rangle \langle 1|}{2} \end{aligned}$$



# Loss of precision

Computing a reduced density matrix **discards information!**

$$\rho_{\beta_{00}} = \frac{|00\rangle\langle 00| + |00\rangle\langle 11| + |11\rangle\langle 00| + |11\rangle\langle 11|}{2} \quad (\text{Pure state})$$

$$\rho_2 = \frac{|00\rangle\langle 00| + |01\rangle\langle 01| + |10\rangle\langle 10| + |11\rangle\langle 11|}{4} \quad (\text{Mixed state})$$



# Loss of precision

Computing a reduced density matrix **discards information!**

$$\rho_{\beta_{00}} = \frac{|00\rangle\langle 00| + |00\rangle\langle 11| + |11\rangle\langle 00| + |11\rangle\langle 11|}{2} \quad (\text{Pure state})$$

$$\rho_2 = \frac{|00\rangle\langle 00| + |01\rangle\langle 01| + |10\rangle\langle 10| + |11\rangle\langle 11|}{4} \quad (\text{Mixed state})$$

$$\text{Tr}_B[\rho_{\beta_{00}}] = \frac{|0\rangle\langle 0| + |1\rangle\langle 1|}{2} = \text{Tr}_B[\rho_2]$$

The partial traces of two different initial states can be equal.

For a state  $\rho \in A \otimes B$ , even if we know  $\text{Tr}_B[\rho]$  and  $\text{Tr}_A[\rho]$ , we cannot uniquely determine  $\rho$ .



# Projection Subspaces

Each projection  $P$  corresponds to a linear subspace  
 $S_P = \{v \mid Pv = v\}.$



# Projection Subspaces

Each projection  $P$  corresponds to a linear subspace  $S_P = \{v \mid Pv = v\}$ .

The support of a matrix  $P$  is the subspace orthogonal to its kernel, i.e., the set  $\text{supp}(P) = \{v \mid Pv \neq 0\}$ .



# Projection Subspaces

Each projection  $P$  corresponds to a linear subspace  $S_P = \{v \mid Pv = v\}$ .

The support of a matrix  $P$  is the subspace orthogonal to its kernel, i.e., the set  $\text{supp}(P) = \{v \mid Pv \neq 0\}$ .

This duality between projections and subspaces will be employed multiple times and will often be implied.



# Roadmap

- ① Introduction
  - Reasons
  - Abstract Interpretation
- ② Preliminaries
  - Density Matrix
  - Reduced Density Matrix
- ③ Abstract Domain
  - Abstraction and Concretization Functions
  - Abstract Operations
  - Assertions
- ④ Conclusions



# Abstract Domain

$$\mathcal{D} = \mathbb{C}^{2^n} \otimes \mathbb{C}^{2^n}, \quad S = (s_1, \dots, s_m), \quad 1 \leq m \leq 2^n, \quad s_i \subseteq [n]$$





# Abstract Domain

$$\mathcal{D} = \mathbb{C}^{2^n} \otimes \mathbb{C}^{2^n}, \quad S = (s_1, \dots, s_m), \quad 1 \leq m \leq 2^n, \quad s_i \subseteq [n]$$

$$AbsDom(S) = \left\{ (P_{s_1}, \dots, P_{s_m}) \mid P_{s_i} \text{ is a projection in } \mathbb{C}^{2^{|s_i|}} \otimes \mathbb{C}^{2^{|s_i|}} \right\}$$



# Abstract Domain

$$\mathcal{D} = \mathbb{C}^{2^n} \otimes \mathbb{C}^{2^n}, \quad S = (s_1, \dots, s_m), \quad 1 \leq m \leq 2^n, \quad s_i \subseteq [n]$$

$$AbsDom(S) = \left\{ (P_{s_1}, \dots, P_{s_m}) \mid P_{s_i} \text{ is a projection in } \mathbb{C}^{2^{|s_i|}} \otimes \mathbb{C}^{2^{|s_i|}} \right\}$$

Intuitively, given a tuple  $S$  of sets of qubits, an abstract state  $\bar{\sigma} \in AbsDom(S)$  is a tuple of projections over those qubits.



# Abstract Domain

$$\mathcal{D} = \mathbb{C}^{2^n} \otimes \mathbb{C}^{2^n}, \quad S = (s_1, \dots, s_m), \quad 1 \leq m \leq 2^n, \quad s_i \subseteq [n]$$

$$AbsDom(S) = \left\{ (P_{s_1}, \dots, P_{s_m}) \mid P_{s_i} \text{ is a projection in } \mathbb{C}^{2^{|s_i|}} \otimes \mathbb{C}^{2^{|s_i|}} \right\}$$

Intuitively, given a tuple  $S$  of sets of qubits, an abstract state  $\bar{\sigma} \in AbsDom(S)$  is a tuple of projections over those qubits.

Special case:

$$T = ([n]) \Rightarrow AbsDom(T) \simeq \mathcal{D}$$



# Fineness Relation

Let  $S = (s_1, \dots, s_m)$  and  $T = (t_1, \dots, t_m)$  (with  $1 \leq m \leq 2^n$ ), then:

$$\underbrace{S \sqsubseteq T} \triangleq \forall i \in [m]. s_i \subseteq t_i$$

"T is finer than S"

$T$  is "more concrete" than  $S$ .



# Fineness Relation

Let  $S = (s_1, \dots, s_m)$  and  $T = (t_1, \dots, t_m)$  (with  $1 \leq m \leq 2^n$ ), then:

$$\underbrace{S \sqsubseteq T} \triangleq \forall i \in [m]. s_i \subseteq t_i$$

“T is finer than S”

$T$  is “more concrete” than  $S$ .

Least element:  $\perp = (\emptyset, \dots, \emptyset)$ .

Greatest element:  $\top = ([n], \dots, [n]) = [n]^m$ .



# Fineness Relation

Let  $S = (s_1, \dots, s_m)$  and  $T = (t_1, \dots, t_m)$  (with  $1 \leq m \leq 2^n$ ), then:

$$\underbrace{S \sqsubseteq T} \triangleq \forall i \in [m]. s_i \subseteq t_i$$

“T is finer than S”

$T$  is “more concrete” than  $S$ .

Least element:  $\perp = (\emptyset, \dots, \emptyset)$ .

Greatest element:  $\top = ([n], \dots, [n]) = [n]^m$ .

$AbsDom(\perp)$  corresponds to a state so abstract that it holds no information at all.

$AbsDom(\top)$  corresponds to tuples where every projection is a concrete state.



# Abstraction Function

$$S \trianglelefteq T \triangleq \forall i \in [m]. s_i \subseteq t_i$$

$$\alpha_{T \rightarrow S} : \text{AbsDom}(T) \rightarrow \text{AbsDom}(S)$$



# Abstraction Function

$$S \trianglelefteq T \triangleq \forall i \in [m]. s_i \subseteq t_i$$

$$\alpha_{T \rightarrow S} : \text{AbsDom}(T) \rightarrow \text{AbsDom}(S)$$

$$\alpha_{T \rightarrow S}(Q_{t_1}, \dots, Q_{t_m}) = (P_{s_1}, \dots, P_{s_m})$$

$$P_{s_i} = \bigcap_{t_j. s_i \subseteq t_j} \text{supp}(\text{Tr}_{t_j \setminus s_i}[Q_{t_j}])$$





# Abstraction Function

$$S \trianglelefteq T \triangleq \forall i \in [m]. s_i \subseteq t_i$$

$$\alpha_{T \rightarrow S} : AbsDom(T) \rightarrow AbsDom(S)$$

$$\alpha_{T \rightarrow S}(Q_{t_1}, \dots, Q_{t_m}) = (P_{s_1}, \dots, P_{s_m})$$

$$P_{s_i} = \bigcap_{t_j. s_i \subseteq t_j} supp(Tr_{t_j \setminus s_i}[Q_{t_j}])$$

Given an abstract state  $\bar{\tau} \in AbsDom(T) = (Q_{t_1}, \dots, Q_{t_m})$ , we want to compute  $\bar{\sigma} \in AbsDom(S) = (P_{s_1}, \dots, P_{s_m})$ . For each  $i \in [m]$ :



# Abstraction Function

$$S \sqsubseteq T \triangleq \forall i \in [m]. s_i \subseteq t_i$$

$$\alpha_{T \rightarrow S} : AbsDom(T) \rightarrow AbsDom(S)$$

$$\alpha_{T \rightarrow S}(Q_{t_1}, \dots, Q_{t_m}) = (P_{s_1}, \dots, P_{s_m})$$

$$P_{s_i} = \bigcap_{t_j. s_i \subseteq t_j} supp(Tr_{t_j \setminus s_i}[Q_{t_j}])$$

Given an abstract state  $\bar{\tau} \in AbsDom(T) = (Q_{t_1}, \dots, Q_{t_m})$ , we want to compute  $\bar{\sigma} \in AbsDom(S) = (P_{s_1}, \dots, P_{s_m})$ . For each  $i \in [m]$ :

- 1 Find all  $Q_{t_j}$ s such that  $s_i \subseteq t_j$ . We know that at least one exists (for  $j = i$ ), since  $S \sqsubseteq T$ .



# Abstraction Function

$$S \trianglelefteq T \triangleq \forall i \in [m]. s_i \subseteq t_i$$

$$\alpha_{T \rightarrow S} : AbsDom(T) \rightarrow AbsDom(S)$$

$$\alpha_{T \rightarrow S}(Q_{t_1}, \dots, Q_{t_m}) = (P_{s_1}, \dots, P_{s_m})$$

$$P_{s_i} = \bigcap_{t_j. s_i \subseteq t_j} supp(Tr_{t_j \setminus s_i}[Q_{t_j}])$$

Given an abstract state  $\bar{\tau} \in AbsDom(T) = (Q_{t_1}, \dots, Q_{t_m})$ , we want to compute  $\bar{\sigma} \in AbsDom(S) = (P_{s_1}, \dots, P_{s_m})$ . For each  $i \in [m]$ :

- ① Find all  $Q_{t_j}$ s such that  $s_i \subseteq t_j$ . We know that at least one exists (for  $j = i$ ), since  $S \trianglelefteq T$ .
- ② For each  $Q_{t_j}$  found, trace out the qubits in  $t_j$  that are not in  $s_i$ .



# Abstraction Function

$$S \trianglelefteq T \triangleq \forall i \in [m]. s_i \subseteq t_i$$

$$\alpha_{T \rightarrow S} : AbsDom(T) \rightarrow AbsDom(S)$$

$$\alpha_{T \rightarrow S}(Q_{t_1}, \dots, Q_{t_m}) = (P_{s_1}, \dots, P_{s_m})$$

$$P_{s_i} = \bigcap_{t_j. s_i \subseteq t_j} \text{supp}(Tr_{t_j \setminus s_i}[Q_{t_j}])$$

Given an abstract state  $\bar{\tau} \in AbsDom(T) = (Q_{t_1}, \dots, Q_{t_m})$ , we want to compute  $\bar{\sigma} \in AbsDom(S) = (P_{s_1}, \dots, P_{s_m})$ . For each  $i \in [m]$ :

- ① Find all  $Q_{t_j}$ s such that  $s_i \subseteq t_j$ . We know that at least one exists (for  $j = i$ ), since  $S \trianglelefteq T$ .
- ② For each  $Q_{t_j}$  found, trace out the qubits in  $t_j$  that are not in  $s_i$ .
- ③ Compute the support of the traced matrices (to preserve the structure of projections).



# Abstraction Function

$$S \trianglelefteq T \triangleq \forall i \in [m]. s_i \subseteq t_i$$

$$\alpha_{T \rightarrow S} : AbsDom(T) \rightarrow AbsDom(S)$$

$$\alpha_{T \rightarrow S}(Q_{t_1}, \dots, Q_{t_m}) = (P_{s_1}, \dots, P_{s_m})$$

$$P_{s_i} = \bigcap_{t_j. s_i \subseteq t_j} supp(Tr_{t_j \setminus s_i}[Q_{t_j}])$$

Given an abstract state  $\bar{\tau} \in AbsDom(T) = (Q_{t_1}, \dots, Q_{t_m})$ , we want to compute  $\bar{\sigma} \in AbsDom(S) = (P_{s_1}, \dots, P_{s_m})$ . For each  $i \in [m]$ :

- ① Find all  $Q_{t_j}$ s such that  $s_i \subseteq t_j$ . We know that at least one exists (for  $j = i$ ), since  $S \trianglelefteq T$ .
- ② For each  $Q_{t_j}$  found, trace out the qubits in  $t_j$  that are not in  $s_i$ .
- ③ Compute the support of the traced matrices (to preserve the structure of projections).
- ④ Compute the intersection of the supports.



# Concretization Function

$$S \sqsubseteq T \triangleq \forall i \in [m]. s_i \subseteq t_i$$

$$\gamma_{S \rightarrow T} : \text{AbsDom}(S) \rightarrow \text{AbsDom}(T)$$



# Concretization Function

$$S \sqsubseteq T \triangleq \forall i \in [m]. s_i \subseteq t_i$$

$$\gamma_{S \rightarrow T} : \text{AbsDom}(S) \rightarrow \text{AbsDom}(T)$$

$$\gamma_{S \rightarrow T}(P_{s_1}, \dots, P_{s_m}) = (Q_{t_1}, \dots, Q_{t_m})$$

$$Q_{t_j} = \bigcap_{s_i. s_i \subseteq t_j} P_{s_i} \otimes I_{t_j \setminus s_i}$$



# Concretization Function

$$S \sqsubseteq T \triangleq \forall i \in [m]. s_i \subseteq t_i$$

$$\gamma_{S \rightarrow T} : AbsDom(S) \rightarrow AbsDom(T)$$

$$\gamma_{S \rightarrow T}(P_{s_1}, \dots, P_{s_m}) = (Q_{t_1}, \dots, Q_{t_m})$$

$$Q_{t_j} = \bigcap_{s_i. s_i \subseteq t_j} P_{s_i} \otimes I_{t_j \setminus s_i}$$

Given an abstract state  $\bar{\sigma} \in AbsDom(S) = (P_{s_1}, \dots, P_{s_m})$ , we want to compute  $\bar{\tau} \in AbsDom(T) = (Q_{t_1}, \dots, Q_{t_m})$ . For each  $j \in [m]$ :





# Concretization Function

$$S \sqsubseteq T \triangleq \forall i \in [m]. s_i \subseteq t_i$$

$$\gamma_{S \rightarrow T} : AbsDom(S) \rightarrow AbsDom(T)$$

$$\gamma_{S \rightarrow T}(P_{s_1}, \dots, P_{s_m}) = (Q_{t_1}, \dots, Q_{t_m})$$

$$Q_{t_j} = \bigcap_{s_i. s_i \subseteq t_j} P_{s_i} \otimes I_{t_j \setminus s_i}$$

Given an abstract state  $\bar{\sigma} \in AbsDom(S) = (P_{s_1}, \dots, P_{s_m})$ , we want to compute  $\bar{\tau} \in AbsDom(T) = (Q_{t_1}, \dots, Q_{t_m})$ . For each  $j \in [m]$ :

- ① Find all  $P_{s_i}$ s such that  $s_i \subseteq t_j$ . We know at least one exists (for  $i = j$ ), since  $S \sqsubseteq T$ .



# Concretization Function

$$S \sqsubseteq T \triangleq \forall i \in [m]. s_i \subseteq t_i$$

$$\gamma_{S \rightarrow T} : AbsDom(S) \rightarrow AbsDom(T)$$

$$\gamma_{S \rightarrow T}(P_{s_1}, \dots, P_{s_m}) = (Q_{t_1}, \dots, Q_{t_m})$$

$$Q_{t_j} = \bigcap_{s_i. s_i \subseteq t_j} P_{s_i} \otimes I_{t_j \setminus s_i}$$

Given an abstract state  $\bar{\sigma} \in AbsDom(S) = (P_{s_1}, \dots, P_{s_m})$ , we want to compute  $\bar{\tau} \in AbsDom(T) = (Q_{t_1}, \dots, Q_{t_m})$ . For each  $j \in [m]$ :

- ① Find all  $P_{s_i}$ s such that  $s_i \subseteq t_j$ . We know at least one exists (for  $i = j$ ), since  $S \sqsubseteq T$ .
- ② Extend the projection to the space of all qubits in  $t_j$ , by computing the tensor product with the identity matrix.



# Concretization Function

$$S \sqsubseteq T \triangleq \forall i \in [m]. s_i \subseteq t_i$$

$$\gamma_{S \rightarrow T} : AbsDom(S) \rightarrow AbsDom(T)$$

$$\gamma_{S \rightarrow T}(P_{s_1}, \dots, P_{s_m}) = (Q_{t_1}, \dots, Q_{t_m})$$

$$Q_{t_j} = \bigcap_{s_i. s_i \subseteq t_j} P_{s_i} \otimes I_{t_j \setminus s_i}$$

Given an abstract state  $\bar{\sigma} \in AbsDom(S) = (P_{s_1}, \dots, P_{s_m})$ , we want to compute  $\bar{\tau} \in AbsDom(T) = (Q_{t_1}, \dots, Q_{t_m})$ . For each  $j \in [m]$ :

- ① Find all  $P_{s_i}$ s such that  $s_i \subseteq t_j$ . We know at least one exists (for  $i = j$ ), since  $S \sqsubseteq T$ .
- ② Extend the projection to the space of all qubits in  $t_j$ , by computing the tensor product with the identity matrix.
- ③ Compute the intersection of the extended projections.



# Abstract Operations

Operations on the concrete domain are unitary operators  $U$ .  
To apply them to a concrete state  $\rho$  we compute  $U\rho U^\dagger$ .  
We want to define  $U^\sharp : \text{AbsDom}(S) \rightarrow \text{AbsDom}(S)$ .



# Abstract Operations

Operations on the concrete domain are unitary operators  $U$ .

To apply them to a concrete state  $\rho$  we compute  $U\rho U^\dagger$ .

We want to define  $U^\sharp : \text{AbsDom}(S) \rightarrow \text{AbsDom}(S)$ .

Let  $T = (t_1, \dots, t_m)$  s.t.  $t_i = s_i \cup s_U$ , where  $s_U$  denotes the set of qubits that matrix  $U$  acts on.



# Abstract Operations

Operations on the concrete domain are unitary operators  $U$ .

To apply them to a concrete state  $\rho$  we compute  $U\rho U^\dagger$ .

We want to define  $U^\# : \text{AbsDom}(S) \rightarrow \text{AbsDom}(S)$ .

Let  $T = (t_1, \dots, t_m)$  s.t.  $t_i = s_i \cup s_U$ , where  $s_U$  denotes the set of qubits that matrix  $U$  acts on.

Let  $U^{cg}(\bar{\sigma}) = (UT_{t_1}U^\dagger, \dots, UT_{t_m}U^\dagger)$



# Abstract Operations

Operations on the concrete domain are unitary operators  $U$ .

To apply them to a concrete state  $\rho$  we compute  $U\rho U^\dagger$ .

We want to define  $U^\# : \text{AbsDom}(S) \rightarrow \text{AbsDom}(S)$ .

Let  $T = (t_1, \dots, t_m)$  s.t.  $t_i = s_i \cup s_U$ , where  $s_U$  denotes the set of qubits that matrix  $U$  acts on.

Let  $U^{cg}(\bar{\sigma}) = (UT_{t_1}U^\dagger, \dots, UT_{t_m}U^\dagger)$ , then

$$U^\# = \alpha_{T \rightarrow S} \circ U^{cg} \circ \gamma_{S \rightarrow T}$$



# Focus

$$U^\sharp = \alpha_{T \rightarrow S} \circ U^{cg} \circ \gamma_{S \rightarrow T}$$





# Focus

$$U^\sharp = \alpha_{T \rightarrow S} \circ U^{cg} \circ \gamma_{S \rightarrow T}$$

$$AbsDom(S) \xrightarrow[\text{Focus}]{\gamma_{S \rightarrow T}} AbsDom(T) \xrightarrow[\text{Apply}]{U^{cg}} AbsDom(T) \xrightarrow[\text{Unfocus}]{\alpha_{T \rightarrow S}} AbsDom(S)$$



# Focus

$$U^\sharp = \alpha_{T \rightarrow S} \circ U^{cg} \circ \gamma_{S \rightarrow T}$$

$$AbsDom(S) \xrightarrow[\text{Focus}]{\gamma_{S \rightarrow T}} AbsDom(T) \xrightarrow[\text{Apply}]{U^{cg}} AbsDom(T) \xrightarrow[\text{Unfocus}]{\alpha_{T \rightarrow S}} AbsDom(S)$$

**Focus** - concretize to a new, finer domain with sufficient precision to accurately represent the operation;



# Focus

$$U^\sharp = \alpha_{T \rightarrow S} \circ U^{cg} \circ \gamma_{S \rightarrow T}$$

$$AbsDom(S) \xrightarrow[\text{Focus}]{\gamma_{S \rightarrow T}} AbsDom(T) \xrightarrow[\text{Apply}]{U^{cg}} AbsDom(T) \xrightarrow[\text{Unfocus}]{\alpha_{T \rightarrow S}} AbsDom(S)$$

**Focus** - concretize to a new, finer domain with sufficient precision to accurately represent the operation;

**Apply** - apply the unitary operator to all the elements in the tuple



# Focus

$$U^\sharp = \alpha_{T \rightarrow S} \circ U^{cg} \circ \gamma_{S \rightarrow T}$$

$$AbsDom(S) \xrightarrow[\text{Focus}]{\gamma_{S \rightarrow T}} AbsDom(T) \xrightarrow[\text{Apply}]{U^{cg}} AbsDom(T) \xrightarrow[\text{Unfocus}]{\alpha_{T \rightarrow S}} AbsDom(S)$$

**Focus** - concretize to a new, finer domain with sufficient precision to accurately represent the operation;

**Apply** - apply the unitary operator to all the elements in the tuple

**Unfocus** - abstract back to the original abstract domain to keep the representation more compact



# Assertions

We want to check that a state of a program lies in the span of two vectors.



# Assertions

We want to check that a state of a program lies in the span of two vectors.

We define an assertion as:

$$A = \text{span}\{v_1 = |a_1\rangle \dots |a_n\rangle, v_2 = |b_1\rangle \dots |b_n\rangle\}$$



# Assertions

We want to check that a state of a program lies in the span of two vectors.

We define an assertion as:

$$A = \text{span}\{v_1 = |a_1\rangle \dots |a_n\rangle, v_2 = |b_1\rangle \dots |b_n\rangle\}$$

And a projection  $\text{proj}(A)$  onto this subspace, such that:

$$\text{proj}(A)v_1 = v_1 \quad \text{proj}(A)v_2 = v_2$$



# Order Relation on Abstract States

$$1 \leq m \leq 2^n, \quad S = (s_1, \dots, s_m), \quad \forall i \in [m]. \quad s_i \subseteq [n]$$

$$\bar{\sigma} \in \text{AbsDom}(S) = (P_{s_1}, \dots, P_{s_m}), \quad \bar{\tau} \in \text{AbsDom}(S) = (Q_{s_1}, \dots, Q_{s_m})$$

$$\bar{\sigma} \sqsubseteq \bar{\tau} \triangleq \forall i \in [m]. \underbrace{P_{s_i} \subseteq Q_{s_i}}$$

Subspace interpretation  
of projections





# Monotonicity and Galois Connection

Monotonicity of *abstraction*, *concretization*, and *abstract operations*:

$$\begin{aligned}
 &S \sqsubseteq T \\
 &\forall \bar{\sigma}, \bar{\tau} \in \text{AbsDom}(T). \\
 &\left( \begin{array}{c} \bar{\sigma} \sqsubseteq \bar{\tau} \Rightarrow \alpha_{T \rightarrow S}(\bar{\sigma}) \sqsubseteq \alpha_{T \rightarrow S}(\bar{\tau}) \\ \wedge \\ \bar{\sigma} \sqsubseteq \bar{\tau} \Rightarrow \gamma_{T \rightarrow S}(\bar{\sigma}) \sqsubseteq \gamma_{T \rightarrow S}(\bar{\tau}) \\ \wedge \\ \bar{\sigma} \sqsubseteq \bar{\tau} \Rightarrow U^\sharp(\bar{\sigma}) \sqsubseteq U^\sharp(\bar{\tau}) \end{array} \right)
 \end{aligned}$$



# Monotonicity and Galois Connection

Monotonicity of *abstraction*, *concretization*, and *abstract operations*:

$$\begin{aligned}
 & S \sqsubseteq T \\
 & \forall \bar{\sigma}, \bar{\tau} \in \text{AbsDom}(T). \\
 & \left( \begin{array}{c} \bar{\sigma} \sqsubseteq \bar{\tau} \Rightarrow \alpha_{T \rightarrow S}(\bar{\sigma}) \sqsubseteq \alpha_{T \rightarrow S}(\bar{\tau}) \\ \wedge \\ \bar{\sigma} \sqsubseteq \bar{\tau} \Rightarrow \gamma_{T \rightarrow S}(\bar{\sigma}) \sqsubseteq \gamma_{T \rightarrow S}(\bar{\tau}) \\ \wedge \\ \bar{\sigma} \sqsubseteq \bar{\tau} \Rightarrow U^\#(\bar{\sigma}) \sqsubseteq U^\#(\bar{\tau}) \end{array} \right)
 \end{aligned}$$

Galois connection:

$$\begin{aligned}
 & \forall \bar{\sigma} \in \text{AbsDom}(S). \forall \bar{\tau} \in \text{AbsDom}([n]^m). \\
 & \bar{\tau} \sqsubseteq \gamma_{S \rightarrow [n]^m}(\bar{\sigma}) \quad \Leftrightarrow \quad \alpha_{[n]^m \rightarrow S}(\bar{\tau}) \sqsubseteq \bar{\sigma}
 \end{aligned}$$



# Connectivity

$$S = (s_1, \dots, s_m)$$

$S$  is connected  $\triangleq \forall k \in [n-1]. \exists r \in [m]. k \in s_r \wedge k+1 \in s_r$



# Connectivity

$$S = (s_1, \dots, s_m)$$

$S$  is connected  $\triangleq \forall k \in [n-1]. \exists r \in [m]. k \in s_r \wedge k+1 \in s_r$

Example:

$$n = 5, \quad m = 3$$

$$S = (\{0, 2, 3\}, \{0, 1, 2\}, \{3, 4, 5\})$$



# Connectivity

$$S = (s_1, \dots, s_m)$$

$S$  is connected  $\triangleq \forall k \in [n-1]. \exists r \in [m]. k \in s_r \wedge k+1 \in s_r$

Example:

$$n = 5, \quad m = 3$$

$$0, 1 \in \{0, 1, 2\}$$

$$S = (\{0, 2, 3\}, \{0, 1, 2\}, \{3, 4, 5\})$$



# Connectivity

$$S = (s_1, \dots, s_m)$$

$S$  is connected  $\triangleq \forall k \in [n-1]. \exists r \in [m]. k \in s_r \wedge k+1 \in s_r$

Example:

$$n = 5, \quad m = 3$$

$$1, 2 \in \{0, 1, 2\}$$

$$S = (\{0, 2, 3\}, \{0, 1, 2\}, \{3, 4, 5\})$$



# Connectivity

$$S = (s_1, \dots, s_m)$$

$S$  is connected  $\triangleq \forall k \in [n-1]. \exists r \in [m]. k \in s_r \wedge k+1 \in s_r$

Example:

$$n = 5, \quad m = 3$$

$$2, 3 \in \{0, 2, 3\}$$

$$S = (\{0, 2, 3\}, \{0, 1, 2\}, \{3, 4, 5\})$$



# Connectivity

$$S = (s_1, \dots, s_m)$$

$S$  is connected  $\triangleq \forall k \in [n-1]. \exists r \in [m]. k \in s_r \wedge k+1 \in s_r$

Example:

$$n = 5, \quad m = 3$$

$$3, 4 \in \{3, 4, 5\}$$

$$S = (\{0, 2, 3\}, \{0, 1, 2\}, \{3, 4, 5\})$$





# Connectivity

$$S = (s_1, \dots, s_m)$$

$S$  is connected  $\triangleq \forall k \in [n-1]. \exists r \in [m]. k \in s_r \wedge k+1 \in s_r$

Example:

$$n = 5, \quad m = 3$$

$$4, 5 \in \{3, 4, 5\}$$

$$S = (\{0, 2, 3\}, \{0, 1, 2\}, \{3, 4, 5\})$$



# Connectivity

$$S = (s_1, \dots, s_m)$$

$$S \text{ is connected} \triangleq \forall k \in [n-1]. \exists r \in [m]. k \in s_r \wedge k+1 \in s_r$$

Example:

$$n = 5, \quad m = 3$$

$$S = (\{0, 2, 3\}, \{0, 1, 2\}, \{3, 4, 5\})$$

For an assertion  $A$ , if  $S$  is connected, then:

$$proj(A) = \gamma_{S \rightarrow [n]^m}(\alpha_{[n]^m \rightarrow S}(proj(A)))$$



# Assertion Checking

Given an assertion  $A$ , if the final state of a computation is  $v$  and the final abstract state of the abstract interpretation is  $\bar{v} \in \text{AbsDom}(S)$ , with  $S$  connected, then:

$$\bar{v} \sqsubseteq \alpha_{[n]^m \rightarrow S}(\text{proj}(A)) \quad \Rightarrow \quad v \in A$$



# Assertion Checking

Given an assertion  $A$ , if the final state of a computation is  $v$  and the final abstract state of the abstract interpretation is  $\bar{v} \in \text{AbsDom}(S)$ , with  $S$  connected, then:

$$\bar{v} \sqsubseteq \alpha_{[n]^m \rightarrow S}(\text{proj}(A)) \quad \Rightarrow \quad v \in A$$

Essentially, if the abstract state satisfies the assertion, then the concrete one does as well.



# Choice of Tuple S

Fundamental choice for the shape of the abstract domain and, in turn, the success of the analysis.



# Choice of Tuple $S$

Fundamental choice for the shape of the abstract domain and, in turn, the success of the analysis.

Type of $S$	Pros	Cons
Less, smaller sets	Less computational cost and memory footprint	Less precision
More, bigger sets	More computational cost and memory footprint	More precision



# Choice of Tuple S

Fundamental choice for the shape of the abstract domain and, in turn, the success of the analysis.

Type of S	Pros	Cons
Less, smaller sets	Less computational cost and memory footprint	Less precision
More, bigger sets	More computational cost and memory footprint	More precision

## Examples:

- $S_0 =$  all  $2^n$  combinations of up to  $n$  qubits
- $S_1 =$  all  $\binom{n}{k}$  combinations of exactly  $k$  qubits
- $S_2 =$  sets that contain qubits used by at least two 3-qubit gates
- ...



# Choice of Tuple S (ctd.)

Another important factor in the choice for the abstract state is which qubits are put together in projections.

A good choice would make the abstract interpretation *flow-sensitive*.





# Choice of Tuple S (ctd.)

Another important factor in the choice for the abstract state is which qubits are put together in projections.

A good choice would make the abstract interpretation *flow-sensitive*.

## Example:

- $U_1$  acts on qubits  $\{1, 2, 3\}$  with  $\{1, 2\}$  as input and  $\{3\}$  as output.
- $U_2$  acts on qubits  $\{3, 4, 5\}$  with  $\{3, 4\}$  as input and  $\{5\}$  as output.



# Choice of Tuple S (ctd.)

Another important factor in the choice for the abstract state is which qubits are put together in projections.

A good choice would make the abstract interpretation *flow-sensitive*.

## Example:

- $U_1$  acts on qubits  $\{1, 2, 3\}$  with  $\{1, 2\}$  as input and  $\{3\}$  as output.
- $U_2$  acts on qubits  $\{3, 4, 5\}$  with  $\{3, 4\}$  as input and  $\{5\}$  as output.

A good choice which would improve the precision of the abstract interpretation is to have the set  $\{1, 2, 3, 4, 5\}$  in the abstract state.



# Assertion Checking Example

We want to check (partial) correctness of Grover's algorithm.



# Assertion Checking Example

We want to check (partial) correctness of Grover's algorithm.

Grover's algorithm steps:

- 1 Prepare the initial state  $|\phi\rangle^{(0)}$



# Assertion Checking Example

We want to check (partial) correctness of Grover's algorithm.

## Grover's algorithm steps:

- 1 Prepare the initial state  $|\phi\rangle^{(0)}$
- 2 Repeat approx.  $\frac{\pi}{4}\sqrt{N}$  times  $|\phi\rangle^{(t+1)} = G|\phi\rangle^{(t)}$ .



# Assertion Checking Example

We want to check (partial) correctness of Grover's algorithm.

## Grover's algorithm steps:

- 1 Prepare the initial state  $|\phi\rangle^{(0)}$
- 2 Repeat approx.  $\frac{\pi}{4}\sqrt{N}$  times  $|\phi\rangle^{(t+1)} = G|\phi\rangle^{(t)}$ .
- 3 Measure in the computational basis.



# Assertion Checking Example

We want to check (partial) correctness of Grover's algorithm.

## Grover's algorithm steps:

- 1 Prepare the initial state  $|\phi\rangle^{(0)}$
- 2 Repeat approx.  $\frac{\pi}{4}\sqrt{N}$  times  $|\phi\rangle^{(t+1)} = G|\phi\rangle^{(t)}$ .
- 3 Measure in the computational basis.

With this abstract interpretation framework, we can prove the loop invariant:

$$|\phi\rangle^{(t)} \in A = \text{span}\{|\beta\rangle, |\phi\rangle\}$$



# Assertion Checking Example (ctd.)

$$P(v) \triangleq v \in A = \text{span}\{|\beta\rangle, |\phi\rangle\}$$





# Assertion Checking Example (ctd.)

$$P(v) \triangleq v \in A = \text{span}\{|\beta\rangle, |\phi\rangle\}$$

We need to check:

①  $P(|\phi\rangle^{(0)})$



# Assertion Checking Example (ctd.)

$$P(v) \triangleq v \in A = \text{span}\{|\beta\rangle, |\phi\rangle\}$$

We need to check:

$$\textcircled{1} P(|\phi\rangle^{(0)}) \triangleq |\phi\rangle \in \text{span}\{|\beta\rangle, |\phi\rangle\}$$



# Assertion Checking Example (ctd.)

$$P(v) \triangleq v \in A = \text{span}\{|\beta\rangle, |\phi\rangle\}$$

We need to check:

- ①  $P(|\phi\rangle^{(0)}) \triangleq |\phi\rangle \in \text{span}\{|\beta\rangle, |\phi\rangle\}$
- ②  $P(|\phi\rangle^{(t)}) \Rightarrow P(|\phi\rangle^{(t+1)})$



# Assertion Checking Example (ctd.)

$$P(v) \triangleq v \in A = \text{span}\{|\beta\rangle, |\phi\rangle\}$$

We need to check:

$$\textcircled{1} P(|\phi\rangle^{(0)}) \triangleq |\phi\rangle \in \text{span}\{|\beta\rangle, |\phi\rangle\}$$

$$\textcircled{2} P(|\phi\rangle^{(t)}) \Rightarrow P(|\phi\rangle^{(t+1)}) \triangleq |\phi\rangle^{(t)} \in A \Rightarrow G|\phi\rangle^{(t)} \in A$$



# Assertion Checking Example (ctd.)

$$P(v) \triangleq v \in A = \text{span}\{|\beta\rangle, |\phi\rangle\}$$

We need to check:

$$\textcircled{1} P(|\phi\rangle^{(0)}) \triangleq |\phi\rangle \in \text{span}\{|\beta\rangle, |\phi\rangle\}$$

$$\textcircled{2} P(|\phi\rangle^{(t)}) \Rightarrow P(|\phi\rangle^{(t+1)}) \triangleq |\phi\rangle^{(t)} \in A \Rightarrow G|\phi\rangle^{(t)} \in A$$

$$G|\phi\rangle^{(t)} \in A = G|\beta\rangle \in A \wedge G|\phi\rangle \in A \quad \text{By linearity of } G \text{ and } |\phi\rangle^{(t)} \in A$$



# Roadmap

- ① Introduction
  - Reasons
  - Abstract Interpretation
- ② Preliminaries
  - Density Matrix
  - Reduced Density Matrix
- ③ Abstract Domain
  - Abstraction and Concretization Functions
  - Abstract Operations
  - Assertions
- ④ Conclusions



# Future developments

- Programs with measurements
- Conditionals
- Loops
- Mix of classical and quantum computation
- Choosing the optimal abstract space
- Other kinds of assertions



# Computing the Projection of a Support

[noframenumbering] To compute a projection corresponding to  $\text{supp}(A)$ , we:

- 1 take the rows  $\{r_1, \dots, r_n\}$  of  $A$ ;
- 2 extract an orthonormal set of vectors  $\{b_1, \dots, b_n\}$  that span the same subspace as the rows;
- 3 create the matrix  $B = \begin{pmatrix} b_1 \\ \dots \\ b_n \end{pmatrix}$ ;
- 4 return  $BB^\dagger$ .





# Computing the Projection of an Intersection

[noframenumbering]

$$\{P_1, \dots, P_k\}, \quad \forall i \in [k]. \quad P_i = C^n \times C^n$$
$$\bigcap_{i \in [k]} P_i \triangleq I_n - \text{supp}(kl_n - \sum_{i \in [k]} P_i)$$



# Computing the Assertion Projection

[noframenumbering] Given two vectors

$$v_1 = |a_1\rangle \dots |a_n\rangle$$

$$v_2 = |b_1\rangle \dots |b_n\rangle$$

① Create a matrix  $P = \begin{pmatrix} v_1^T \\ v_2^T \\ \mathbf{0} \\ \dots \\ \mathbf{0} \end{pmatrix}$

② Return  $\text{supp}(P)$



# Partial trace

$$Tr_B[\rho] = \sum_{v=0}^{2^m} (I_A \otimes \langle v|) \rho (I_A \otimes |v\rangle) \quad Tr_A[\rho] = \sum_{v=0}^{2^n} (\langle v| \otimes I_B) \rho (|v\rangle \otimes I_B)$$

Where  $v$  labels vectors of an orthonormal basis of the subspace we are tracing out.



# Weak Galois Connection

$$\begin{aligned}
 & S \trianglelefteq T \\
 & \forall \bar{\sigma} \in \text{AbsDom}(S). \forall \bar{\tau} \in \text{AbsDom}(T). \\
 & \left( \begin{array}{c} \bar{\tau} \sqsubseteq \gamma_{S \rightarrow T}(\bar{\sigma}) \Rightarrow \alpha_{T \rightarrow S}(\bar{\tau}) \sqsubseteq \bar{\sigma} \\ \wedge \\ (\exists \bar{\rho} \in \text{AbsDom}([n]^m). \bar{\tau} = \alpha_{[n]^m \rightarrow T}(\bar{\rho})) \Rightarrow \bar{\tau} \sqsubseteq \gamma_{S \rightarrow T}(\bar{\sigma}) \Leftrightarrow \alpha_{T \rightarrow S}(\bar{\tau}) \sqsubseteq \bar{\sigma} \end{array} \right)
 \end{aligned}$$



