

TaxoGen: Constructing Topical Concept Taxonomy by Adaptive Term Embedding and Clustering

Chao Zhang¹, Fangbo Tao², Xiushi Chen¹, Jiaming Shen¹, Meng Jiang³,

Brian Sadler⁴, Michelle Vanni⁴, and Jiawei Han¹

¹Dept. of Computer Science, University of Illinois at Urbana-Champaign, Urbana, IL, USA

²Facebook Inc., Menlo Park, CA, USA

³Dept. of Computer Science and Engineering, University of Notre Dame, Notre Dame, IN, USA

⁴U.S. Army Research Laboratory, Adelphi, MD, USA

¹{czhang82, xiusic, js2, hanj}@illinois.edu

²fangbo.tao@gmail.com ³mjiang2@nd.edu

⁴{brian.m.sadler6.civ, michelle.t.vanni.civ}@mail.mil

ABSTRACT

Taxonomy construction is not only a fundamental task for semantic analysis of text corpora, but also an important step for applications such as information filtering, recommendation, and Web search. Existing pattern-based methods extract hypernym-hyponym term pairs and then organize these pairs into a taxonomy. However, by considering each term as an independent concept node, they overlook the topical proximity and the semantic correlations among terms. In this paper, we propose a method for constructing *topical concept taxonomies*, wherein every node represents a conceptual topic and is defined as a cluster of semantically coherent concept terms. Our method, TAXOGEN, uses term embeddings and hierarchical clustering to construct a topical taxonomy in a recursive fashion. To ensure the quality of the recursive process, it consists of: (1) an adaptive spherical clustering module for allocating terms to proper levels when splitting a coarse topic into fine-grained ones; (2) a local embedding module for learning term embeddings that maintain strong discriminative power at different levels of the taxonomy. Our experiments on two real datasets demonstrate the effectiveness of TAXOGEN compared with baseline methods.

1 INTRODUCTION

Automatic taxonomy construction from a text corpus is a fundamental task for semantic analysis of text data and plays an important role in many applications. For example, organizing a massive news corpus into a well-structured taxonomy allows users to quickly navigate to their interested topics and easily acquire useful information. As another example, many recommender systems involve items with textual descriptions, and a taxonomy for these items can help the system better understand user interests to make more accurate recommendations [33].

Permission to make digital or hard copies of all or part of this work for personal or classroom use is granted without fee provided that copies are not made or distributed for profit or commercial advantage and that copies bear this notice and the full citation on the first page. Copyrights for components of this work owned by others than ACM must be honored. Abstracting with credit is permitted. To copy otherwise, or republish, to post on servers or to redistribute to lists, requires prior specific permission and/or a fee. Request permissions from permissions@acm.org.

Conference'17, July 2017, Washington, DC, USA

© 2018 Association for Computing Machinery.

ACM ISBN 978-x-xxxx-xxxx-x/YY/MM...\$15.00

<https://doi.org/10.1145/nnnnnnnn.nnnnnnnn>




Figure 1: An example topical taxonomy. Each node is a cluster of semantically coherent concept terms representing a conceptual topic.

Existing methods mostly generate a taxonomy wherein each node is a single term representing an independent concept [14, 19]. They use pre-defined lexico-syntactic patterns (e.g., A such as B, A is a B) to extract hypernym-hyponym term pairs, and then organize these pairs into a concept taxonomy by considering each term as a node. Although they can achieve high precision for the extracted hypernym-hyponym pairs, considering each term as an independent concept node causes three critical problems to the taxonomy: (1) *low coverage*: Since term correlations are not considered, only the pairs exactly matching the pre-defined patterns are extracted, which leads to low coverage of the result taxonomy. (2) *high redundancy*: As one concept can be expressed in different ways, the taxonomy is highly redundant because many nodes are just different expressions of the same concept (e.g., ‘information retrieval’ and ‘ir’). (3) *limited informativeness*: Representing a node with a single term provides limited information about the concept and causes ambiguity.

We study the problem of *topical concept taxonomy construction* from an input text corpus. In contrast to term-level taxonomies, each node in our topical taxonomy — representing a conceptual topic — is defined as a cluster of semantically coherent concept terms. Figure 1 shows an example. Assuming a collection of computer science research papers are given, we build a tree-structured hierarchy. The root node is the general topic ‘computer science’,

which is further split into sub-topics like ‘machine learning’ and ‘information retrieval’. For every topical node, we describe it with multiple concept terms that are semantically relevant. For instance, for the ‘information retrieval’ node, its associated terms include not only synonyms of ‘information retrieval’ (e.g., ‘ir’), but also different facets of the IR area (e.g., ‘text retrieval’ and ‘retrieval effectiveness’).

We propose a method named TAXOGEN for constructing topical taxonomies. It embeds the concept terms into a latent space to capture their semantics, and uses term embeddings to recursively construct the taxonomy based on hierarchical clustering. While the idea of combining term embedding and hierarchical clustering is intuitive by itself, two key challenges need to be addressed for building high-quality taxonomies. First, *it is nontrivial to determine the proper granularity levels for different concept terms*. When splitting a coarse topical node into fine-grained ones, not all the concept terms should be pushed down to the child level. For example, when splitting the computer science topic in Figure 1, general terms like ‘cs’ and ‘computer science’ should remain in the parent instead of being allocated into any child topics. Therefore, it is problematic to directly group parent terms to form child topics, but necessary to allocate different terms to different levels. Second, *global embeddings have limited discriminative power at lower levels*. Term embeddings are typically learned by collecting the context evidence from the corpus, such that terms sharing similar contexts tend to have close embeddings. However, as we move down in the hierarchy, the term embeddings learned based on the entire corpus have limited power in capturing subtle semantics. For example, when splitting the machine learning topic, we find that the terms ‘machine learning’ and ‘reinforcement learning’ have close global embeddings, and it is hard to discover quality sub-topics for the machine learning topic.

TAXOGEN consists of two novel modules for tackling the above challenges. The first is an adaptive spherical clustering module for allocating terms to proper levels when splitting a coarse topic. Relying on a ranking function that measures the representativeness of different terms to each child topic, the clustering module iteratively detects general terms that should remain in the parent topic and keeps refining the clustering boundaries of the child topics. The second is a local term embedding module. To enhance the discriminative powers of term embeddings at lower levels, TAXOGEN uses topic-relevant documents to learn local embeddings for the terms in each topic. The local embeddings capture term semantics at a finer granularity and are less constrained by the terms irrelevant to the topic. As such, they are discriminative enough to separate the terms with different semantics even at lower levels of the taxonomy.

We perform extensive experiments on two real data sets. Our qualitative results show that TAXOGEN can generate high-quality topical taxonomies, and our quantitative analysis based on user study shows that TAXOGEN outperforms baseline methods significantly.

To summarize, our contributions include: (1) a recursive framework that leverages term embeddings to construct topical taxonomies; (2) an adaptive spherical clustering module for allocating terms to proper levels when splitting a coarse topic; (3) a local embedding module for learning term embeddings that have strong discriminative power; and (4) extensive experiments that verify the effectiveness of TAXOGEN on real data.

2 RELATED WORK

In this section, we review existing taxonomy construction methods, including (1) pattern-based methods, (2) clustering-based methods, and (3) supervised methods.

2.1 Pattern-Based Methods

A considerable number of pattern-based methods have been proposed to construct hypernym-hyponym taxonomies wherein each node in the tree is an entity, and each parent-child pair expresses the “is-a” relation. Typically, these works first use pre-defined lexical patterns to extract hypernym-hyponym pairs from the corpus, and then organizes all the extracted pairs into a taxonomy tree. In pioneering studies, Hearst patterns like “NP such as NP, NP, and NP” were proposed to automatically acquire hyponymy relations from text data [14]. Then more kinds of lexical patterns have been manually designed and used to extract relations from the web corpus [5, 24, 26] or Wikipedia [13, 25]. With the development of the Snowball framework, researchers teach machines how to propagate knowledge among the massive text corpora using statistical approaches [1, 34]; Carlson et al. proposed a learning architecture for Never-Ending Language Learning (NELL) in 2010 [6]. PATTY leveraged parsing structures to derive relational patterns with semantic types and organizes the patterns into a taxonomy [23]. The recent MetaPAD [15] used context-aware phrasal segmentation to generate quality patterns and group synonymous patterns together for a large collection of facts of a specific relation. Pattern-based methods have demonstrated their effectiveness in finding particular relations based on hand-crafted rules or generated patterns. However, they are not suitable for constructing a topical concept taxonomy because of two reasons. First, different from hypernym-hyponym taxonomies, each node in a topical taxonomy can be a group of terms representing a conceptual topic. Second, pattern-based methods often suffer from low recall due to the large variation of expressions in natural language on parent-child relations.

2.2 Clustering-Based Methods

A great number of clustering methods have been proposed for constructing taxonomy from text corpus. These methods are more closely related to our problem of constructing a topical concept taxonomy. Generally, the clustering approaches first learn the representation of words or terms and then organize them into a structure based on their representation similarity [3] and cluster separation measures [9]. Fu et al. identified whether a candidate word pair has hypernym-hyponym (“is-a”) relation by using the word-embedding-based semantic projections between words and their hypernyms [12]. Luu et al. proposed to use dynamic weighting neural network to identify taxonomic relations via learning term embeddings [20]. Our *local term embedding* in TAXOGEN is quite different from the existing methods. First, we do not need labeled hypernym-hyponym pairs as supervision for learning either semantic projections or dynamic weighting neural network. Second, we learn local embeddings for each topic using only topic-relevant documents. The local embeddings capture fine-grained term semantics and thus well separate terms with subtle semantic differences. On the term organizing end, Ciniano et al. used a comparative measure to perform conceptual, divisive, and agglomerative clustering for taxonomy

learning [7]. Yang et al. also used an ontology metric, a score indicating semantic distance, to induce taxonomy [31]. Liu et al. used Bayesian rose tree to hierarchically cluster a given set of keywords into a taxonomy [18]. Wang et al. adopted a recursive way to construct topic hierarchies by clustering domain keyphrases [28]. Also, quite a number of hierarchical topic models have been proposed for term organization [4, 11, 22]. In our TAXOGEN, we develop an *adaptive spherical clustering* module to allocate terms into proper levels when we split a coarse topic. The module well groups terms of the same topic together and separates child topics (as term clusters) with significant distances.

2.3 Supervised Methods

There have also been (semi-)supervised learning methods for taxonomy construction [16, 17]. Basically the methods extract lexical features and learn a classifier that categorizes term pairs into relations or non-relations, based on curated training data of hypernym-hyponym pairs [8, 18, 27, 31], or syntactic contextual information harvested from NLP tools [19, 30]. Recent techniques [2, 12, 20, 29, 32] in this category leverage pre-trained word embeddings and then use curated hypernymy relation datasets to learn a relation classifier. However, the training data for all these methods are limited to extracting hypernym-hyponym relations and cannot be easily adapted for constructing a topical taxonomy. Furthermore, for massive domain-specific text data (like scientific publication data we used in this work), it is hardly possible to collect a rich set of supervised information from experts. Therefore, we focus on novel technical development in unsupervised taxonomy construction methods.

3 PROBLEM DESCRIPTION

The input for constructing a topical taxonomy includes two parts: (1) a corpus \mathcal{D} of documents; and (2) a set \mathcal{T} of seed terms. The seed terms in \mathcal{T} are the key terms extracted from \mathcal{D} , representing the terms of interest for taxonomy construction¹. Given the corpus \mathcal{D} and the term set \mathcal{T} , we aim to build a tree-structured hierarchy \mathcal{H} . Each node $C \in \mathcal{H}$ denotes a conceptual topic, which is described by a set of terms $\mathcal{T}_C \in \mathcal{T}$ that are semantically coherent. Suppose a node C has a set of children $\mathcal{S}_C = \{S_1, S_2, \dots, S_N\}$, then each $S_n (1 \leq n \leq N)$ should be a sub-topic of C , and have the same semantic granularity with its siblings in \mathcal{S}_C .

4 THE TAXOGEN METHOD

In this section, we describe our proposed TAXOGEN method. We first give an overview of it in Section 4.1. Then we introduce the details of the adaptive spherical clustering and local embedding modules in Section 4.2 and 4.3, respectively.

4.1 Method Overview

In a nutshell, TAXOGEN embeds all the concept terms into a latent space to capture their semantics, and uses the term embeddings to build the taxonomy recursively. As shown in Figure 2, at the top level, we initialize a root node containing all the terms from \mathcal{T} , which represents the most general topic for the given corpus

\mathcal{D} . Starting from the root node, we generate fine-grained topics level by level via top-down spherical clustering. The top-down construction process continues until a maximum number of levels L_{max} is reached.

Given a topic C , we use spherical clustering to split C into a set of fine-grained topics $\mathcal{S}_C = \{S_1, S_2, \dots, S_N\}$. As mentioned earlier, there are two challenges that need to be addressed in the recursive construction process: (1) when splitting a topic C , it is problematic to directly divide the terms in C into sub-topics, because general terms should remain in the parent topic C instead of being allocated to any sub-topics; (2) when we move down to lower levels, global term embeddings learned on the entire corpus are inadequate for capturing subtle term semantics. In the following, we introduce the adaptive clustering and local embedding modules in TAXOGEN for addressing these two challenges.

4.2 Adaptive Spherical Clustering

The adaptive clustering module in TAXOGEN is designed to split a coarse topic C into fine-grained ones. It is based on the spherical K -means algorithm [10], which groups a given set of term embeddings into K clusters such that the terms in the same cluster have similar embedding directions. Our choice of the spherical K -means algorithm is motivated by the effectiveness of the cosine similarity [21] in quantifying the similarities between word embeddings. The center direction of a topic acts as a semantic focus on the unit sphere, and the member terms of that topic falls around the center direction to represent a coherent semantic meaning.

4.2.1 The adaptive clustering process. Given a coarse topic C , a straightforward idea for generating the sub-topics of C is to directly apply spherical K -means to C , such that the terms in C are grouped into K clusters to form C 's sub-topics. Nevertheless, such a straightforward strategy is problematic because not all the terms in C should be allocated into the child topics. For example, in Figure 2, when splitting the root topic of computer science, terms like ‘computer science’ and ‘cs’ are general — they do not belong to any specific child topics but instead should remain in the parent. Furthermore, the existence of such general terms makes the clustering process more challenging. As such general terms can co-occur with various contexts in the corpus, their embeddings tend to fall on the boundaries of different sub-topics. Thus, the clustering structure for the sub-topics is blurred, making it harder to discover clear sub-topics.

Motivated by the above, we propose an *adaptive clustering module* in TAXOGEN. As shown in Figure 2, the key idea is to iteratively identify general terms and refine the sub-topics after pushing general terms back to the parent. Identifying general terms and refining child topics are two operations that can mutually enhance each other: excluding the general terms in the clustering process can make the boundaries of the sub-topics clearer; while the refined sub-topics boundaries enable detecting additional general terms.

Algorithm 1 shows the process for adaptive spherical clustering. As shown, given a parent topic C , it first puts all the terms of C into the sub-topic term set C_{sub} . Then it iteratively identifies general terms and refines the sub-topics. In each iteration, it computes the representativeness score of a term t for the sub-topic S_k , and excludes t if its representativeness is smaller than a threshold δ .

¹In our experiments, we extract all the noun phrases from \mathcal{D} to form the term set \mathcal{T} .




Figure 2: An overview of TAXOGEN. It uses term embeddings to construct the taxonomy in a top-down manner, with two novel components for ensuring the quality of the resursive process: (1) an adaptive clustering module that allocates terms to proper topic nodes; and (2) a local embedding module for learning term embeddings on topic-relevant documents.

Algorithm 1: Adaptive clustering for topic splitting.

Input: A parent topic C ; the number of sub-topics K ; the term representativeness threshold δ .

Output: K sub-topics of C .

```

1  $C_{sub} \leftarrow C$ ;
2 while True do
3    $S_1, S_2, \dots, S_K \leftarrow \text{SPHERICAL-KMEANS}(C_{sub}, K)$ ;
4   for  $k$  from 1 to  $K$  do
5     for  $t \in S_k$  do
6        $r(t, S_k) \leftarrow$  representativeness of term  $t$  for  $S_k$ ;
7       if  $r(t, S_k) < \delta$  then
8          $S_k \leftarrow S_k - \{t\}$ ;
9    $C'_{sub} \leftarrow S_1 \cup S_2 \cup \dots \cup S_K$ ;
10  if  $C'_{sub} = C_{sub}$  then
11    Break;
12   $C_{sub} \leftarrow C'_{sub}$ ;
13 Return  $S_1, S_2, \dots, S_K$ ;

```

After pushing up general terms, it re-forms the sub-topic term set C_{sub} and prepares for the next spherical clustering operation. The iterative process terminates when no more general terms can be detected, and the final set of sub-topics S_1, S_2, \dots, S_K are returned for C .

4.2.2 Measuring term representativeness. In Algorithm 1, the key question is how to measure the representativeness of a term t for a sub-topic S_k . While it is tempting to measure the representativeness of t by its closeness to the center of S_k in the embedding space, we find such a strategy is unreliable: general terms may also fall close to the cluster center of S_k , which renders the embedding-based detector inaccurate.

Our insight for addressing this problem is that, a representative term for S_k should appear frequently in S_k but not in the sibling topics of S_k . We hence measure term representativeness using the documents that belong to S_k . Based on the cluster memberships of terms, we first use the TF-IDF scheme to obtain the documents belonging to each topic S_k . With these S_k -related documents, we

consider the following two factors for computing the representativeness of a term t for topic S_k :

- **Popularity:** A representative term for S_k should appear frequently in the documents of S_k .
- **Concentration:** A representative term for S_k should be much more relevant to S_k compared to the sibling topics of S_k .

To combine the above two factors, we notice that they should have conjunctive conditions, namely a representative term should be both popular and concentrated for S_k . Thus we define the representativeness of term t for topic S_k as

$$r(t, S_k) = \sqrt{\text{pop}(t, S_k) \cdot \text{con}(t, S_k)} \quad (1)$$

where $\text{pop}(t, S_k)$ and $\text{con}(t, S_k)$ are the popularity and concentration scores of t for S_k . Let \mathcal{D}_k denotes the documents belonging to S_k , we define $\text{pop}(t, S_k)$ as the normalized term frequency of t in \mathcal{D}_k :

$$\text{pop}(t, S_k) = \frac{\log(\text{tf}(t, \mathcal{D}_k) + 1)}{\log \text{tf}(\mathcal{D}_k)},$$

where $\text{tf}(t, \mathcal{D}_k)$ is number of occurrences of term t in \mathcal{D}_k , and $\text{tf}(\mathcal{D}_k)$ is the total number of tokens in \mathcal{D}_k .

To compute the concentration score, we first form a pseudo document D_k for each sub-topic S_k by concatenating all the documents in \mathcal{D}_k . Then we define the concentration of term t on S_k based on its relevance to the pseudo document D_k :

$$\text{con}(t, S_k) = \frac{\exp(\text{rel}(t, D_k))}{1 + \sum_{1 \leq j \leq K} \exp(\text{rel}(t, D_j))},$$

where $\text{rel}(t, D_k)$ is the BM25 relevance of term t to the pseudo document D_k .

Example 4.1. Figure 2 shows the process of applying adaptive clustering for splitting the computer science topic into three sub-topics: computer graphics (CG), machine learning (ML), and information retrieval (IR). Given a sub-topic, for example ML, terms (e.g., ‘clustering’, ‘classification’) that are popular and concentrated in this cluster receive high representativeness scores. In contrast, terms (e.g., ‘computer science’) that are not representative for any sub-topics are considered as general terms and pushed back to the parent.

4.3 Local Embedding

The recursive taxonomy construction process of TAXOGEN relies on term embeddings, which encode term semantics by learning fixed-size vector representations for the terms. We use the SkipGram model [21] for learning term embeddings. Given a corpus, SkipGram models the relationship between a term and its context terms in a sliding window, such that the terms that share similar contexts tend to have close embeddings in the latent space. The result embeddings can well capture the semantics of different terms and been demonstrated useful for various NLP tasks.

Formally, given a corpus \mathcal{D} , for any token t , we consider a sliding window centered at t and use W_t to denote the tokens appearing in the context window. Then we define the log-probability of observing the contextual terms as

$$\log p(W_t|t) = \sum_{w \in W_t} \log p(w|t) = \sum_{w \in W_t} \log \frac{\mathbf{v}_t \mathbf{v}'_w}{\sum_{w' \in V} \mathbf{v}_t \mathbf{v}'_{w'}}$$

where \mathbf{v}_t is the embedding for term t , \mathbf{v}'_w is the contextual embedding for the term w , and V is the vocabulary of the corpus \mathcal{D} . Then the overall objective function of SkipGram is defined over all the tokens in \mathcal{D} , namely

$$L = \sum_{t \in \mathcal{D}} \sum_{w \in W_t} \log p(w|t),$$

and the term embeddings can be learned by maximizing the above objective with stochastic gradient descent and negative sampling [21].

However, when we use the term embeddings trained on the entire corpus \mathcal{D} for taxonomy construction, one drawback is that these global embeddings have limited discriminative powers at lower levels. Let us consider the term ‘reinforcement learning’ in Figure 2. In the entire corpus \mathcal{D} , it shares a lot of similar contexts with the term ‘machine learning’, and thus has an embedding close to ‘machine learning’ in the latent space. The proximity with ‘machine learning’ makes it successfully assigned into the machine learning topic when we are splitting the root topic. Nevertheless, as we move down to split the machine learning topic, the embeddings of ‘reinforcement learning’ and other machine learning terms are entangled together, making it difficult to discover sub-topics for machine learning.

Therefore, we propose the *local embedding module* to enhance the discriminative power of term embeddings at lower levels of the taxonomy. For any topic C that is not the root topic, we learn *local term embeddings* for splitting C . Specifically, we first retrieve a sub-corpus \mathcal{D}_C from \mathcal{D} that is relevant to the topic C . To obtain the sub-corpus \mathcal{D}_C , we first compute the embedding of any document $d \in \mathcal{D}$ using TF-IDF weighted average of the term embeddings in d . Based on the obtained document embeddings, we use the mean direction of the topic C as a query vector to retrieve the top- M closest documents and form the sub-corpus \mathcal{D}_C . Once the sub-corpus \mathcal{D}_C is retrieved, we apply the SkipGram model to the sub-corpus \mathcal{D}_C to obtain term embeddings that are tailored for splitting the topic C .

Example 4.2. Consider Figure 2 as an example, when splitting the machine learning topic, we first obtain a sub-corpus \mathcal{D}_{ml} that is relevant to machine learning. Within \mathcal{D}_{ml} , terms reflecting general

machine learning topics such as ‘machine learning’ and ‘ml’ appear in a large number of documents. They become similar to stopwords and can be easily separated from more specific terms. Meanwhile, for those terms that reflect different machine learning sub-topics (e.g., ‘classification’ and ‘clustering’), they are also better separated in the local embedding space. Since the local embeddings are trained to preserve the semantic information for topic-related documents, different terms have more freedom to span in the embedding space to reflect their subtle semantic differences.

5 EXPERIMENTS

5.1 Experimental Setup

5.1.1 Datasets. We use two datasets in our experiments: (1) DBLP contains around 600 thousand computer science paper titles from the areas of information retrieval, computer vision, robotics, security & network, and machine learning. From those paper titles, we use an existing NP chunker to extract all the noun phrases to form the term set, resulting in 13,345 distinct terms; (2) SP contains 91 thousand paper abstracts from the area of signal processing. Similarly, we extract all the noun phrases in those abstracts to form the term set and obtain 7,235 different terms.²

5.1.2 Compared Methods. We compare TAXOGEN with the following baseline methods that are capable of generating topical taxonomies:

- (1) HLDA (hierarchical Latent Dirichlet Allocation) [4] is a non-parametric hierarchical topic model. It models the probability of generating a document as choosing a path from the root to a leaf and sampling words along the path. We apply HLDA for topic-level taxonomy construction by regarding each topic in HLDA as a topic.
- (2) HPAM (hierarchical Pachinko Allocation Model) is a state-of-the-art hierarchical topic model [22]. Different from TAXOGEN that generates the taxonomy recursively, HPAM takes all the documents as its input and outputs a pre-defined number of topics at different levels based on the Pachinko Allocation Model.
- (3) HCLUS (hierarchical clustering) uses hierarchical clustering for taxonomy construction. We first apply the SkipGram model on the entire corpus to learn term embeddings, and then use spherical k-means to cluster those embeddings in a top-down manner.
- (4) NoAC is a variant of TAXOGEN without the adaptive clustering module. In other words, when splitting one coarse topic into fine-grained ones, it simply performs spherical clustering to group parent terms into child topics.
- (5) NoLE is a variant of TAXOGEN without the local embedding module. During the recursive construction process, it uses the global embeddings that are learned on the entire corpus throughout the construction process.

5.1.3 Parameter Settings. We use the methods to generate a four-level taxonomy on DBLP and a three-level taxonomy on SP. There are two key parameters in TAXOGEN: the number K for splitting a coarse topic and the representativeness threshold δ for identifying

²Code and data available at <https://github.com/franticnerd/local-embedding/>.

general terms. We set $K = 5$ as we found such a setting matches the intrinsic taxonomy structures well on both DBLP and SP. For δ , we set it to 0.25 on DBLP and 0.15 on SP after tuning, because we observed such a setting can robustly detect general terms that belong to parent topics at different levels in the construction process. For HLDA, it involves three hyper-parameters: (1) the smoothing parameter α over level distributions; (2) the smoothing parameter γ for the Chinese Restaurant Process; and (3) the smoothing parameter η over topic-word distributions. We set $\alpha = 0.1$, $\gamma = 1.0$, $\eta = 1.0$. Under such a setting, HLDA generates a comparable number of topics with TAXOGEN on both datasets. The method HPAM requires to set the mixture priors for super- and sub-topics. We find that the best values for these two priors are 1.5 and 1.0 on DBLP and SP, respectively. The remaining three methods (HCLUS, NoAC, and NoLE) have a subset of the parameters of TAXOGEN, and we set them to the same values as TAXOGEN.

5.2 Qualitative Results

In this subsection, we demonstrate the topic taxonomies generated by different methods on DBLP. We apply each method to generate a four-level taxonomy on DBLP, and each parent topic is split into five child topics by default (except for HLDA, which automatically determines the number of child topics based on the Chinese Restaurant Process).

Figure 3 shows parts of the taxonomy generated by TAXOGEN. As shown in Figure 3(a), given the DBLP corpus, TAXOGEN splits the root topic into five sub-topics: ‘intelligent agents’, ‘object recognition’, ‘learning algorithms’, ‘cryptographic’, and ‘information retrieval’. The labels for those topics are generated automatically by selecting the term that is most representative for a topic (Equation 1). We find those labels are of good quality and precisely summarize the major research areas covered by the DBLP corpus. The only minor flaw for the five labels is ‘object recognition’, which is too specific for the computer vision area. The reason is probably because the term ‘object recognition’ is too popular in the titles of computer vision papers, thus attracting the center of the spherical cluster towards itself.

In Figure 3(a) and 3(b), we also show how TAXOGEN splits level-two topics ‘information retrieval’ and ‘learning algorithms’ into more fine-grained topics. Taking ‘information retrieval’ as an example: (1) at level three, TAXOGEN can successfully find major areas in information retrieval: retrieval effectiveness, interlingual, Web search, rdf & xml query, and text mining; (2) at level four, TAXOGEN splits the Web search topic into more fine-grained problems: link analysis, social tagging, recommender systems & user profiling, blog search, and clickthrough models. Similarly for the machine learning topic (Figure 3(b)), TAXOGEN can discover level-three topics like ‘neural network’ and level-four topic like ‘recurrent neural network’. Moreover, the top terms for each topic are of good quality — they are semantically coherent and cover different aspects and expressions of the same topic.

We have also compared the taxonomies generated by TAXOGEN and other baseline methods, and found that TAXOGEN offers clearly better taxonomies from the quantitative perspective. Due to the space limit, we only show parts of the taxonomies generated by NoAC and NoLE to demonstrate the effectiveness of TAXOGEN.

Table 1: Similarity searches on DBLP for: (1) Q1 = ‘pose_estimation’; and (2) Q2 = ‘information_extraction’. For both queries, we use cosine similarity to retrieve the top-five terms in the vocabulary based on global and local embeddings. The local embedding results for ‘pose_estimation’ are obtained in the ‘object_recognition’ sub-topic, while the results for ‘information_extraction’ are obtained in the ‘learning_algorithms’ sub-topic.


Query	Global Embedding	Local Embedding
Q1	pose_estimation	pose_estimation
	single_camera	camera_pose_estimation
	monocular	dof
	d_reconstruction	dof_pose_estimation
	visual_servoing	uncalibrated
Q2	information_extraction	information_extraction
	information_extraction_ie	information_extraction_ie
	text_mining	ie
	named_entity_recognition	extracting_information_from
	natural_language_processing	question_answering_qa

As shown in Figure 4(a), NoLE can also find several sensible child topics for the parent topic (e.g., ‘blogs’ and ‘recommender system’ under ‘Web search’), but the major disadvantage is that a considerable number of the child topics are false positives. Specifically, a number of parent-child pairs (‘web search’ and ‘web search’, ‘neural networks’ and ‘neural networks’) actually represent the same topic instead of true hypernym-hyponym relations. The reason behind is that NoLE uses global term embeddings at all levels, and thus the terms for different semantic granularities have close embeddings and hard to be separated at lower levels. Such a problem also exists for NoAC, but with a different reason: NoAC does not leverage adaptive clustering to push up the terms that belong to the parent topic. Consequently, at fine-grained levels, terms that have different granularities are all involved in the clustering step, making the clustering boundaries less clear compared to TAXOGEN. Such quantitative results clearly show the advantages of TAXOGEN over the baseline methods, which are the key factors that leads to the performance gaps between them in our quantitative evaluation.


Table 1 further compares global and local term embeddings for similarity search tasks. As shown, for the given two queries, the top-five terms retrieved with global embeddings (*i.e.*, the embeddings trained on the entire corpus) are relevant to the queries, yet they are semantically dissimilar if we inspect them at a finer granularity. For example, for the query ‘information extraction’, the top-five similar terms cover various areas and semantic granularities in the NLP area, such as ‘text mining’, ‘named entity recognition’, and ‘natural language processing’. In contrast, the results returned based on local embeddings are more coherent and of the same semantic granularity as the given query.

5.3 Quantitative Analysis

In this subsection, we quantitatively evaluate the quality of the constructed topical taxonomies by different methods. The evaluation of a taxonomy is a challenging task, not only because there are no ground-truth taxonomies for our used datasets, but also that



(a) The sub-topics generated by TAXOGEN under the topics '*' (level 1), 'information retrieval' (level 2), and 'Web search' (level 3).



(b) The sub-topics generated by TAXOGEN under the topics 'learning algorithms' (level 2) and 'neural network' (level 3).

Figure 3: Parts of the taxonomy generated by TAXOGEN on the DBLP dataset. For each topic, we show its label and the top-eight representative terms generated by the ranking function of TAXOGEN. All the labels and terms are returned by TAXOGEN automatically without manual selection or filtering.

the quality of a taxonomy should be judged from different aspects. In our study, we consider the following aspects for evaluating a topic-level taxonomy:

- **Relation Accuracy** aims at measuring the portions of the true positive parent-child relations in a given taxonomy.
- **Term Coherency** aims at quantifying how semantically coherent the top terms are for a topic.
- **Cluster Quality** examines whether a topic and its siblings form quality clustering structures that are well separated in the semantic space.

We instantiate the evaluations of the above three aspects as follows. First, for the relation accuracy measure, we take all the parent-child pairs in a taxonomy and perform user study to judge these pairs. Specifically, we recruited 10 doctoral and post-doctoral researchers in Computer Science as human evaluators. For each parent-child pair, we show the parent and child topics (in the form of top-five representative terms) to at least three evaluators, and ask whether the given pair is a valid parent-child relation. After collecting the answers from the evaluators, we simply use majority voting to label the pairs and compute the ratio of true positives. Second, to measure term coherency, we perform a term intrusion

blogs	news_articles	web_search	web_documents	recommendation
blogs	news_articles	web_search	web_documents	recommendation
blog	sentiment	search_engine	web_document	collaborative_filtering
social_media	opinion	search_engines	world_wide_web	recommender_system
blogosphere	newspaper	web_search_engines	web_content	recommender_systems
twitter	email	web_search_engine	www	recommender
weblogs	opinion_mining	search_results	web_contents	recommendation_system
bloggers	summarizing	click	web_mining	recommendation_systems
news	genres	google	web_directories	recommendations

(a) The sub-topics generated by NoLE under the topic ‘web search’ (level 3).

bit_parity_problem	genetic_algorithm	neurons	neural_networks	artificial_neural_network
bit_parity_problem	genetic_algorithm	neurons	neural_networks	artificial_neural_network
hopfield_neural_network	genetic_algorithms	neural	nn	forecasting
single_layer	genetic	neural	nonlinear	forecast
hopfield	ant_colony_optimization	synaptic	ann	neuro_fuzzy
neat	evolutionary	neuron	cascade	ann
symbolic_regression	particle_swarm_optimization	spiking_neurons	self_organizing_maps	anfis
hnn	simulated_annealing	synapses	topologies	adaptive_control
lstm	evolutionary_algorithm	spiking	nonlinear_systems	multivariable

(b) The sub-topics generated by NoLE under the topic ‘neural networks’ (level 3).

artificial_neural_network_ann	backpropagation	takagi_sugeno	spiking_neurons	learning_vector_quantization
artificial_neural_network_ann	backpropagation	takagi_sugeno	spiking_neurons	learning_vector_quantization
artificial_neural_networks_ann	backpropagation_algorithm	fuzzy_inference_systems	spiking	learning_vector_quantization_lvq
artificial_neural_network	back_propagation_algorithm	tsk	spiking_neuron	lvq
ann	multilayer_perceptron	fuzzy_rule_base	neurons	competitive_learning
back_propagation_network	gradient_descent	fuzzy_controllers	spiking_neural_networks	kohonen
mfnn	rtl	fuzzy_inference	biologically_realistic	artificial_immune_system
backpropagation_neural_network	scaled_conjugate_gradient	fuzzy_neural	neural	unsupervised_classification
anns	backpropagation_bp	fuzzy_rules	biologically_plausible	self_organizing_maps_soms

(c) The sub-topics generated by NoAC under the topic ‘neural network’ (level 3).

Figure 4: Example topics generated by NoLE and NoAC on the DBLP dataset. Again, we show the label and the top-eight representative terms for each topic.

user study. Given the top five terms for a topic, we inject into these terms a fake term that is randomly chosen from a sibling topic. Subsequently, we show these six terms to an evaluator and ask which one is the injected term. Intuitively, the more coherent the top terms are, the more likely an evaluator can correctly identify the injected term, and thus we compute the ratio of correct instances as the term coherency score. Finally, to quantify cluster quality, we use the Davies-Bouldin (DB) Index measure: For any cluster C , we first compute the similarities between C and other clusters and assign the largest value to C as its cluster similarity. Then the DB index is obtained by averaging all the cluster similarities (see [9] for details). The smaller the DB index is, the better the clustering result is.

Table 2 shows the relation accuracy and term coherency of different methods. As shown, TAXOGEN achieves the best performance in terms of both measures. TAXOGEN significantly outperforms topic modeling methods as well as other embedding-based baseline methods. Comparing the performance of TAXOGEN, NoAC, and NoLE, we can see both the adaptive clustering and the local embedding modules play an important role in improving the quality of the result taxonomy: the adaptive clustering module can correctly push background terms back to parent topics; while the local embedding strategy can better capture subtle semantic differences of terms at lower levels. For both measures, the topic modeling methods

Table 2: Relation accuracy and term coherency of different methods on the DBLP and SP datasets.

	Relation Accuracy		Term Coherency	
Method	DBLP	SP	DBLP	SP
HPAM	0.109	0.160	0.173	0.163
HLDA	0.272	0.383	0.442	0.265
HCLUS	0.436	0.240	0.467	0.571
NoAC	0.563	0.208	0.35	0.428
NoLE	0.645	0.240	0.704	0.510
TAXOGEN	0.775	0.520	0.728	0.592

(HLDA and HPAM) perform significantly worse than embedding-based methods, especially on the short-document dataset DBLP. The reason is two-fold. First, HLDA and HPAM make stronger assumptions on document-topic and topic-term distributions, which may not fit the empirical data well. Second, the representative terms of topic modeling methods are selected purely based on the learned multinomial distributions, whereas embedding-based methods perform distinctness analysis to select terms that are more representative.

Figure 5 shows the DB index of all the embedding-based methods. TAXOGEN achieves the smallest DB index (the best clustering result) among these four methods. Such a phenomenon further validates




Figure 5: The Davies-Bouldin index of embedding-based methods on DBLP and SP.

the fact that both the adaptive clustering and local embedding modules are useful in producing clearer clustering structures: (1) The adaptive clustering process gradually identifies and eliminates the general terms, which typically lie in the boundaries of different clusters; (2) The local embedding module is capable of refining term embeddings using a topic-constrained sub-corpus, allowing the sub-topics to be well separated from each other at a finer granularity.

6 CONCLUSION AND DISCUSSION

We studied the problem of constructing topical concept taxonomies from a given text corpus. Our proposed method TAXOGEN relies on term embedding and spherical clustering to construct a topical concept taxonomy in a recursive way. It consists of an adaptive clustering module that allocates terms to proper levels when splitting a coarse topic, as well as a local embedding module that learns term embeddings to maintain strong discriminative power at lower levels. In our experiments, we have demonstrated that both two modules are useful in improving the quality of the resultant taxonomy, which renders TAXOGEN advantages over existing methods for building topical concept taxonomies.

One limitation of the current version of TAXOGEN is that it requires a pre-specified number of clusters when splitting a coarse topic into fine-grained ones. Since the number is determined beforehand and fixed for every topic, this mechanism may not produce the optimal taxonomies in practice. In the future, it is interesting to extend TAXOGEN to allow it to automatically determine the optimal number of children for each parent topic in the construction process. Promising approaches to this issue include clustering techniques based on non-parametric models (e.g., the Chinese Restaurant Process) and novel mechanisms that incorporate light-weight user interactions into the construction process.

REFERENCES

- [1] E. Agichtein and L. Gravano. Snowball: Extracting relations from large plain-text collections. In *ACM DL*, 2000.
- [2] L. E. Anke, J. Camacho-Collados, C. D. Bovi, and H. Saggion. Supervised distributional hypernym discovery via domain adaptation. In *EMNLP*, 2016.
- [3] M. Bansal, D. Burkett, G. de Melo, and D. Klein. Structured learning for taxonomy induction with belief propagation. In *ACL*, pages 1041–1051, 2014.
- [4] D. M. Blei, T. L. Griffiths, M. I. Jordan, and J. B. Tenenbaum. Hierarchical topic models and the nested chinese restaurant process. In *NIPS*, pages 17–24, 2003.
- [5] S. Brin. Extracting patterns and relations from the world wide web. In *International Workshop on The World Wide Web and Databases*, pages 172–183, 1998.
- [6] A. Carlson, J. Betteridge, B. Kisiel, B. Settles, E. R. Hruschka Jr, and T. M. Mitchell. Toward an architecture for never-ending language learning. In *AAAI*, volume 5, page 3, 2010.
- [7] P. Cimiano, A. Hotho, and S. Staab. Comparing conceptual, divisive and agglomerative clustering for learning taxonomies from text. In *ECAL*, pages 435–439, 2004.
- [8] B. Cui, J. Yao, G. Cong, and Y. Huang. Evolutionary taxonomy construction from dynamic tag space. In *WISE*, pages 105–119, 2010.
- [9] D. L. Davies and D. W. Bouldin. A cluster separation measure. *IEEE Trans. Pattern Anal. Mach. Intell.*, 1(2):224–227, 1979.
- [10] I. S. Dhillon and D. S. Modha. Concept decompositions for large sparse text data using clustering. *Machine Learning*, 42(1/2):143–175, 2001.
- [11] D. Downey, C. Bhagavatula, and Y. Yang. Efficient methods for inferring large sparse topic hierarchies. In *ACL*, 2015.
- [12] R. Fu, J. Guo, B. Qin, W. Che, H. Wang, and T. Liu. Learning semantic hierarchies via word embeddings. In *ACL*, pages 1199–1209, 2014.
- [13] G. Grefenstette. Inriasac: Simple hypernym extraction methods. In *SemEval@NAACL-HLT*, 2015.
- [14] M. A. Hearst. Automatic acquisition of hyponyms from large text corpora. In *COLING*, pages 539–545, 1992.
- [15] M. Jiang, J. Shang, T. Cassidy, X. Ren, L. M. Kaplan, T. P. Hanratty, and J. Han. Metapad: Meta pattern discovery from massive text corpora. In *KDD*, 2017.
- [16] Z. Kozareva and E. H. Hovy. A semi-supervised method to learn and construct taxonomies using the web. In *ACL*, pages 1110–1118, 2010.
- [17] R. Kumar, P. Raghavan, S. Rajagopalan, and A. Tomkins. On semi-automated web taxonomy construction. In *WebDB*, pages 91–96, 2001.
- [18] X. Liu, Y. Song, S. Liu, and H. Wang. Automatic taxonomy construction from keywords. In *KDD*, pages 1433–1441, 2012.
- [19] A. T. Luu, J. Kim, and S. Ng. Taxonomy construction using syntactic contextual evidence. In *EMNLP*, pages 810–819, 2014.
- [20] A. T. Luu, Y. Tay, S. C. Hui, and S. Ng. Learning term embeddings for taxonomic relation identification using dynamic weighting neural network. In *EMNLP*, pages 403–413, 2016.
- [21] T. Mikolov, I. Sutskever, K. Chen, G. S. Corrado, and J. Dean. Distributed representations of words and phrases and their compositionality. In *NIPS*, pages 3111–3119, 2013.
- [22] D. M. Mimno, W. Li, and A. McCallum. Mixtures of hierarchical topics with pachinko allocation. In *ICML*, pages 633–640, 2007.
- [23] N. Nakashole, G. Weikum, and F. Suchanek. Patty: A taxonomy of relational patterns with semantic types. In *EMNLP*, pages 1135–1145, 2012.
- [24] A. Panchenko, S. Faralli, E. Ruppert, S. Remus, H. Naets, C. Fairon, S. P. Ponzetto, and C. Biemann. Taxi at semeval-2016 task 13: a taxonomy induction method based on lexico-syntactic patterns, substrings and focused crawling. In *SemEval@NAACL-HLT*, 2016.
- [25] S. P. Ponzetto and M. Strube. Deriving a large-scale taxonomy from wikipedia. In *AAAI*, 2007.
- [26] J. Seitner, C. Bizer, K. Eckert, S. Faralli, R. Meusel, H. Paulheim, and S. P. Ponzetto. A large database of hypernymy relations extracted from the web. In *LREC*, 2016.
- [27] R. Shearer and I. Horrocks. Exploiting partial information in taxonomy construction. *The Semantic Web-ISWC 2009*, pages 569–584, 2009.
- [28] C. Wang, M. Danilevsky, N. Desai, Y. Zhang, P. Nguyen, T. Taula, and J. Han. A phrase mining framework for recursive construction of a topical hierarchy. In *KDD*, 2013.
- [29] J. Weeds, D. Clarke, J. Reffin, D. J. Weir, and B. Keller. Learning to distinguish hypernyms and co-hyponyms. In *COLING*, 2014.
- [30] W. Wu, H. Li, H. Wang, and K. Q. Zhu. Probasc: A probabilistic taxonomy for text understanding. In *Proceedings of the 2012 ACM SIGMOD International Conference on Management of Data*, pages 481–492. ACM, 2012.
- [31] H. Yang and J. Callan. A metric-based framework for automatic taxonomy induction. In *ACL*, pages 271–279, 2009.
- [32] Z. Yu, H. Wang, X. Lin, and M. Wang. Learning term embeddings for hypernymy identification. In *IJCAI*, 2015.
- [33] Y. Zhang, A. Ahmed, V. Josifovski, and A. J. Smola. Taxonomy discovery for personalized recommendation. In *WSDM*, 2014.
- [34] J. Zhu, Z. Nie, X. Liu, B. Zhang, and J.-R. Wen. Statsnowball: a statistical approach to extracting entity relationships. In *WWW*, 2009.