## Caveatron Bill of Materials – Main Body

Hardware Revision: A Date: 2017-09-10

## Red = No longer available - replaced in Hardware Rev. B Yellow = Limited availability (no longer manufactured). Replaced in Hardware Rev. B

Item	Qty	Manufacturer	Mfr. P/N	Description	Suggested Vendor Link	Photo
Main Processor	1	Arduino	Due	Arduino Due	Amazon	30 31 32 33 35 35 35 35 35 35 35 35 35 35 35 35

**Notes:** The main system processor. Available from many vendors. Third party clones are available at lower cost but may require modification of the reset circuit by adding a capacitor and/or resistor as per this link: <a href="https://forum.arduino.cc/index.php?topic=256771.0">https://forum.arduino.cc/index.php?topic=256771.0</a>

**Notes:** The display and user interface. The component used in Hardware revision A is no longer available. A revised component was released by the manufacturer with a new font IC and different display driver that requires revised code Caveatron firmware that is currently under development. The 4 inch 480x320 module produced by this manufacturer appears to use the previous font IC and driver so may work with original firmware, but has not been tested.

Item	Qty	Manufacturer	Mfr. P/N	Description	Suggested Vendor Link	Photo
Due LCD Interface Shield	1	Coldtears Electronics	N/A	TFT/SD Shield for Arduino DUE TFT LCD Module SD Card Adapter 2.8 3.2 inch Mega	Ebay	The last series and the last series are the last series and the last series and the last series and the last series and the last series are the la

**Notes:** Providea electrical interface from Arduino to the Touchscreen LCD.

Laser	1	Uni-T	UT390B	Laser	Ebay,
Rangefinder				Distance	Amazon, or
				Meter	other
					sources.
					Availability
					changes
					frequently.



**Notes:** *Used for station distance measurements.* This item appears to be discontinued but can still be found online from various sources. Do not confuse this with the UT390B+, which is widely available but does not have an accessible serial port, so is not useable. The UT390B+ has a bubble level in the upper left which the UT390B does not. The UT390B must be disassembled and the LCD removed to access the electronics board. The Caveatron hardware rev. B uses a new rangefinder that has assembly advantages, but operational disadvantages over this model.

Item	Qty	Manufacturer	Mfr. P/N	Description	Suggested Vendor Link	Photo
Compass Module	1	Pololu	LSM303D (#2127)	LSM303D 3D Compass and Accelerometer Carrier with Voltage Regulator	Pololu	
Notes: Used t	o meas	sure azimuth and i		DS3231 AT24C32 Real time	Ebay or	<del>-</del>
Clock and		N/A	N/A	clock module memory module	Ebay or other sources. Ebay sellers change frequently	

**Notes:** Provides date/time and used to store calibration and system parameters. This board contains a Maxim DS3231 real-time clock and an Atmel AT24C32 EEPROM memory IC. Requires a CR2032 battery to keep clock active. Available from many vendors and Ebay sellers

Item	Qty	Manufacturer	Mfr. P/N	Description	Suggested Vendor Link	Photo
Battery Pack	1	Adafruit	354	Lithium Ion Battery Pack - 3.7V 4400mAh	<u>Adafruit</u>	PKCELL ICR18650 4400mAh 3.7U
Notes: Primar	y syste	m battery.				
Battery Charging Module	1	Adafruit	259	USB Lilon/LiPoly charger - v1.2	<u>Adafruit</u>	O O O O O O O O O O O O O O O O O O O
					•	tch LED. Default charge current is 500 mA, but can be increased to 1000 nardware rev. B with a combined battery charger and fuel gauge module.
Battery Gauge Module	1	Sparkfun	TOL- 10617	LiPo Fuel Gauge	<u>Sparkfun</u>	

**Notes:** *Monitors battery level.* Contains a MAX17043 battery fuel gauge IC. These are also available at other, cheaper sources such as Ebay and Amazon, but sometimes use a counterfeit Maxim IC that does not function properly. This part has been replaced in Caveatron hardware rev. B with a combined battery charger and fuel gauge module.

Item	Qty	Manufacturer	Mfr. P/N	Description	Suggested Vendor Link	Photo
Voltage Regulator – 9V	1	Pololu	2116	9V Step-Up Voltage Regulator U3V12F9	<u>Pololu</u>	
Notes: Power	supply	for Arduino Due.			1	
Voltage Regulator – 5V	1	Pololu	2123	Pololu 5V Step-Up/Step- Down Voltage Regulator S7V8F5	Pololu	
Notes: Power	supply	for LIDAR Module	·.			
Voltage Regulator – Adjustable	1	Pololu	2118	Pololu Adjustable Step- Up/Step-Down Voltage Regulator S7V8A	Pololu	

Item	Qty	Manufacturer	Mfr. P/N	Description	Suggested Vendor Link	Photo
Piezoelectric Buzzer	1	Pololu	1260	30mm Piezo Buzzer: 1-30V	<u>Pololu</u>	SE
Notes: Indicat	or buzz	zer. Item has been	discontinued	I. A new part needs to be ident	ified for hardwa	re rev. B.
Power Switch & Charging LED	1	Adafruit	916	Rugged Metal On/Off Switch with Red LED Ring - 16mm Red On/Off	<u>Adafruit</u>	
Notes: On/Off	power	switch and charg	ie indicating r	ing LED. Several colors of the L	ED are available.	
USB Jack	1	GT Contact	GT114200 -10	Mini USB-B C2 size Plastic Panel Mount	USBFirewire .com	www.usafirewire.com
Notes: Mini-U	SB jack	for data downloo	ad, battery ch	arging, and loading of software	and calibration	parameters.
USB Cap	1	GT Contact	GT1C5221 22	Seal Cap	USBFirewire .com	Www.dsBFireWire.com
Notes: Water	proof c	ap for USB jack.	I		1	

Item	Qty	Manufacturer	Mfr. P/N	Description	Suggested Vendor Link	Photo
LIDAR Interface Jack	1	Conxall/ Switchcraft	17982- 6SG-300	Micro-Con-X 6 Position Circular Connector Receptacle, Female Sockets Solder Cup Gold	<u>Digikey</u>	
Notes: Jack fo	r LIDAI	R interface cable. I	Available fron	n multiple vendors.		
LIDAR Interface Cap	1	Conxall/ Switchcraft	16295	Micro-Con-X Receptacle Dust Cap	<u>Digikey</u>	
Notes: Cap fo	r LIDAR	R interface jack. Av	vailable from	multiple vendors.		
LCD Connector Cable	1	N/A	N/A	40 pin IDE Connector Cable, 6"	Ebay or Amazon	

well, but is a bit of a stretch. Available from multiple vendors.

Item	Qty	Manufacturer	Mfr. P/N	Description	Suggested Vendor Link	Photo
			•	=	-	ont window and machining of the cover to add screw holes for the LIDAR D, and LIDAR Interface Jack. Available from many vendors.
LIDAR Mounting Rail	1	Weaver	TO-9M	Tip-Off Aluminum Base	<u>Amazon</u>	
Notes: Rail fo	r moun	ting LIDAR modul	e. Weaver TO	-9 rail is identical but with a sh	iny finish. Availal	ble from multiple vendors
Plastic Base Material	1	Small Parts	STPVC- 0093-F	PVC Sheet, Opaque Gray, 0.093" Thickness, 12" Width, 24" Length	Amazon	


Notes: Plastic sheet for mounting internal components in Main Body Enclosure and LIDAR Enclosure. Requires cutting to size and drilling mounting holes.

Item	Qty	Manufacturer	Mfr. P/N	Description	Suggested Vendor Link	Photo
Window Material	1	Small Parts	50649812 12	Acrylic Sheet, Transparent Clear, 0.06" Thickness, 12" Width, 12" Length	Amazon	
						AR Module. Requires cutting to size. Acrylic seems to be the most tant for not interfering with the LIDAR and rangefinder readings.
Laser Rangefinder Optical Filter	1	Rosco	299	Roscolux 1.2 Neutral Density Filter, 20x24"	<u>Adorama</u>	
Notes: Filters	rangef.	 inder receiver to c	 only accept red	 adings from the retroreflective (	card.	
Screen Protector	1	iCarez	N/A	iPhone 5 Ultra Clear Screen Protector 6-pack	Amazon	iCarez Carante La ronnel Tez Larez L

**Notes:** *Protection film for touchscreen.* Also comes in a 3 pack. Needs to be cut to length. Most any screen protector film for iPhone 4, 4S, 5, 5s, or SE should work as they have the same screen width as the 3.5" LCD. Available from multiple vendors.

Item	Qty	Manufacturer	Mfr. P/N	Description	Suggested Vendor Link	Photo
Strap Attachment Hardware	1	122317	Hillman Group	D-Ring Hangers	Lowes	

**Notes:** *Small D-rings for attaching neck strap.* Available from multiple



Notes: Neck Strap. Recommend a nylon camera strap of 52-60" in length about 1.5" wide and about 3/8" wide in the ends. Original source no longer available.

Assorted Fastener Hardware: Screws, Washers, and Nuts

**Notes:** For assembly. Several sizes of standard hardware required. To be detailed in assembly instructions.

Assorted Electrical Hardware: Wire, Header Connectors, and JST Connectors.

**Notes:** For electrical interconnections between boards. To be detailed in assembly instructions.


## **New Components for Hardware Revision: B**

Date: 2017-09-10

Item	Qty	Manufacturer	Mfr. P/N	Description	Suggested Vendor Link	Photo
Touchscreen LCD	1	Coldtears Electronics	N/A	3.5 inch TFT LCD module w/Font IC 480x320 full angle Arduino DUE MEGA 3.2 4.3	<u>Ebay</u>	

**Notes:** The display and user interface. This replaces the Touchscreen LCD for hardware Rev A. This component uses a different Font IC so requires a different interface library and changes to the Caveatron GUI library. The display driver also appears to be slightly different and requires a small change to the display library code to work properly.

ŀ					100 1 511	-1	
	Laser	1	Unknown	Unknown	100m Laser Distance	Ebay	
	Rangefinder				Sensor Module	Availability	
						-	63
						changes	2
						frequently.	
							the S.
							35011
							V STORES
							and the same of th



**Notes:** *Used for station distance measurements.* This new rangefinder module is very similar in size to the one in hardware rev. A, is easier to mount due to the presence of mounting holes, is easier to attach wiring, has a simpler command and data structure, and has similar sensitivity. However, it's method of operation is less well suited to the Caveatron since it can take up to 3 sec to timeout with failed readings vs 1 sec on the old one, which does not work as well in Passage mode.

Item	Qty	Manufacturer	Mfr. P/N	Description	Suggested Vendor Link	Photo
Battery Charger and Gauge	1	Sparkfun	PRT- 13777	Battery Babysitter - LiPo Battery Manager	<u>Sparkfun</u>	

**Notes:** *Battery charge controller and fuel gauge.* This replaces both the separate charger and fuel gauge modules in hardware rev. A. It is more capable with a more reliable method for monitoring battery charge level and can be adjusted to charge at up to 1500mA. The only downside is that connecting wiring to the external charge indicator LED on the power switch is more difficult.

Piezoelectric	1	Unknown	Unknown	Unknown	Unknown
Buzzer					

**Notes:** *Indicator buzzer.* A couple of parts have been tested but have not been found to be a suitable replacement. It appears that a buzzer 16mm or larger is requires as smaller ones do not produce sufficient sound at lower frequencies. Many options remain available to test.

## Retroreflective Card Date: 2017-09-11

Item	Qty	Manufacturer	Mfr. P/N	Description	Suggested Vendor Link	Photo
Retro- reflective Sheet	1	3M	580 or 680	Scotchlite Reflective Film	B.C.I Imaging Supplies for 8" wide or larger sheet OR Seton for half width 4" rolls.	3M

**Notes:** Retroreflective film for station card. Required to obtain positive return signal from laser rangefinder for all measurements and scans. 3M 680 film is used currently. 580 film is more readily available and is identical except for being more permanent when applied. An 8" (200 mm) wide roll is ideal but is expensive unless you are making many cards. A much cheaper half-width roll could be used as two side by side strips. Many other reflective tapes are available and may work fine but have not been tested. I would suggest a uniform material like the 3M Scotchlite as I am not sure how well the prismatic style reflective tapes would work since they might provide too strong a reflection or a non-uniform reflection that depends on where on the card you hit. But they may work fine too.

Station Card Substrate	1	Small Parts	B00E8S5686 For 12x24" sheet – other sizes have	Kydex T Sheet, P3 Velour Matte, 0.028" thickness	Amazon		
			different part				
			numbers				

Notes: Substrate material for retroreflective station cards. Need to be cut to about 8"x8" (200x200 mm). Kydex was chosen since it is durable, thin and flexible, comes in a variety or bright colors easy to see in the cave, and is easy to cut. The material needs to be flexible since it will need to bend to accommodate some survey station locations. Other colors and sheet sizes available from this source – recommend getting a sheet big enough for at least two cards to have a spare. Many other plastics will work but I would not recommend using anything thicker as it may not be flexible enough.