

Week 1 Quiz

CALIFICACIÓN DEL ÚLTIMO ENVÍO

100%

1. The R language is a dialect of which of the following programming languages?

1 / 1 puntos

- ☐ Scheme
- ☐ Fortran
- ☐ Lisp
- ☒ S



Correcto

R is a dialect of the S language which was developed at Bell Labs.

2. The definition of free software consists of four freedoms (freedoms 0 through 3). Which of the following is NOT one of the freedoms that are part of the definition? Select all that apply.

1 / 1 puntos

- ☐ The freedom to run the program, for any purpose.
- ☐ The freedom to study how the program works, and adapt it to your needs.
- ☐ The freedom to redistribute copies so you can help your neighbor.
- ☐ The freedom to improve the program, and release your improvements to the public, so that the whole community benefits.
- ☒ The freedom to prevent users from using the software for undesirable purposes.



Correcto

This is not part of the free software definition. Freedom 0 requires that the users of free software be free to use the software for any purpose.

- ☒ The freedom to sell the software for any price.

Correcto

✓ **Correcto**

This is not part of the free software definition. The free software definition does not mention anything about selling software (although it does not disallow it).

☒ The freedom to restrict access to the source code for the software.

✓ **Correcto**

This is not part of the free software definition. Freedoms 1 and 3 require access to the source code.

3. In R the following are all atomic data types EXCEPT: (Select all that apply)

1 / 1 puntos

☐ logical

☒ data frame

✓ **Correcto**

'data frame' is not an atomic data type in R.

☒ list

✓ **Correcto**

'list' is not an atomic data type in R.

☒ table

✓ **Correcto**

'table' is not an atomic data type in R.

☐ integer

☒ matrix

✓ **Correcto**

'matrix' is not an atomic data type in R.

☒ array



Correcto

'array' is not an atomic data type in R.

☐ character

☐ complex

☐ numeric

4. If I execute the expression `x <- 4L` in R, what is the class of the object 'x' as determined by the `class()` function?

1 / 1 puntos

☐ logical

☒ integer

☐ matrix

☐ character

☐ numeric

☐ complex



Correcto

The 'L' suffix creates an integer vector as opposed to a numeric vector.

5. What is the class of the object defined by the expression `x <- c(4, "a", TRUE)`?

1 / 1 puntos

☐ numeric

☒ character

☐ logical

☐ mixed

☐ integer

Correcto



The character class is the "lowest common denominator" here and so all elements will be coerced into that class.

6. If I have two vectors `x <- c(1,3, 5)` and `y <- c(3, 2, 10)`, what is produced by the expression `rbind(x, y)`?

1 / 1 puntos

- ☐ a vector of length 3
- ☐ a vector of length 2
- ☐ a 2 by 2 matrix
- ☒ a matrix with two rows and three columns
- ☐ a 3 by 3 matrix
- ☐ a 3 by 2 matrix



Correcto

The 'rbind' function treats vectors as if they were rows of a matrix. It then takes those vectors and binds them together row-wise to create a matrix.

7. A key property of vectors in R is that

1 / 1 puntos

- ☐ the length of a vector must be less than 32,768
- ☐ elements of a vector can be of different classes
- ☐ elements of a vector can only be character or numeric
- ☒ elements of a vector all must be of the same class
- ☐ a vector cannot have have attributes like dimensions



Correcto

8. Suppose I have a list defined as `x <- list(2, "a", "b", TRUE)`. What does `x[[2]]` give me? Select all that apply.

1 / 1 puntos

- ☐ a character vector with the elements "a" and "b".

☒ a character vector of length 1.

 **Correcto**

☒ a character vector containing the letter "a".

 **Correcto**

☐ a list containing character vector with the letter "a".

☐ a list containing the number 2 and the letter "a".

9. Suppose I have a vector `x <- 1:4` and a vector `y <- 2`. What is produced by the expression `x + y`?

1 / 1 puntos

☒ a numeric vector with elements 3, 4, 5, 6.

☐ a numeric vector with elements 3, 2, 3, 4.

☐ a numeric vector with elements 1, 2, 3, 6.

☐ an integer vector with elements 3, 2, 3, 4.

☐ an integer vector with elements 3, 2, 3, 6.

☐ a numeric vector with elements 3, 2, 3, 6.

 **Correcto**

10. Suppose I have a vector `x <- c(3, 5, 1, 10, 12, 6)` and I want to set all elements of this vector that are less than 6 to be equal to zero. What R code achieves this? Select all that apply.

1 / 1 puntos

☐ `x[x > 6] <- 0`

☐ `x[x == 6] <- 0`

☒ `x[x %in% 1:5] <- 0`



Correcto

You can create a logical vector with the expression `x %in% 1:5` and then use the `[]` operator to subset the original vector `x`.

☒ `x[x <= 5] <- 0`



Correcto

You can create a logical vector with the expression `x <= 5` and then use the `[]` operator to subset the original vector `x`.

☐ `x[x == 0] < 6`

☒ `x[x < 6] <- 0`



Correcto

You can create a logical vector with the expression `x < 6` and then use the `[]` operator to subset the original vector `x`.

☐ `x[x == 0] <- 6`

☐ `x[x > 0] <- 6`

☐ `x[x != 6] <- 0`

☐ `x[x >= 6] <- 0`

☐ `x[x < 6] == 0`

11. Use the [Week 1 Quiz Data Set](#) to answer questions 11-20.

1 / 1 puntos

In the dataset provided for this Quiz, what are the column names of the dataset?

- ☐ Month, Day, Temp, Wind
- ☐ 1, 2, 3, 4, 5, 6
- ☐ Ozone, Solar.R, Wind
- ☒ Ozone, Solar.R, Wind, Temp, Month, Day

Correcto



You can get the column names of a data frame with the ``names()'` function.

12. Extract the first 2 rows of the data frame and print them to the console. What does the output look like? 1 / 1 puntos

☐

		Ozone	Solar.R	Wind	Temp	Month	Day
2	1	9	24	10.9	71	9	14
3	2	18	131	8.0	76	9	29

☒

		Ozone	Solar.R	Wind	Temp	Month	Day
2	1	41	190	7.4	67	5	1
3	2	36	118	8.0	72	5	2

☐

		Ozone	Solar.R	Wind	Temp	Month	Day
2	1	18	224	13.8	67	9	17
3	2	NA	258	9.7	81	7	22

☐

		Ozone	Solar.R	Wind	Temp	Month	Day
2	1	7	NA	6.9	74	5	11
3	2	35	274	10.3	82	7	17



Correcto

You can extract the first two rows using the `[` operator and an integer sequence to index the rows.

13. How many observations (i.e. rows) are in this data frame? 1 / 1 puntos

☐

45

☐

129

☒

153

☐

160



Correcto

You can use the ``nrows()'` function to compute the number of rows in a data frame.

14.

Extract the *last* 2 rows of the data frame and print them to the console. What does the output look like?

1 / 1 puntos



		Ozone	Solar.R	Wind	Temp	Month	Day
1							
2	152	18	131	8.0	76	9	29
3	153	20	223	11.5	68	9	30



		Ozone	Solar.R	Wind	Temp	Month	Day
1							
2	152	31	244	10.9	78	8	19
3	153	29	127	9.7	82	6	7



		Ozone	Solar.R	Wind	Temp	Month	Day
1							
2	152	34	307	12.0	66	5	17
3	153	13	27	10.3	76	9	18



		Ozone	Solar.R	Wind	Temp	Month	Day
1							
2	152	11	44	9.7	62	5	20
3	153	108	223	8.0	85	7	25



Correcto

The `tail()` function is an easy way to extract the last few elements of an R object.

15. What is the value of Ozone in the 47th row?

1 / 1 puntos



21



34



18



63



Correcto

The single bracket `[` operator can be used to extract individual rows of a data frame.

16. How many missing values are in the Ozone column of this data frame?

1 / 1 puntos



37



43

☐ 9

☐ 78



Correcto

The ``is.na'` function can be used to test for missing values.

17. What is the mean of the Ozone column in this dataset? Exclude missing values (coded as NA) from this calculation.

1 / 1 puntos

☐ 18.0

☐ 31.5

☒ 42.1

☐ 53.2



Correcto

The ``mean'` function can be used to calculate the mean.

18. Extract the subset of rows of the data frame where Ozone values are above 31 and Temp values are above 90. What is the mean of Solar.R in this subset?

1 / 1 puntos

☐ 334.0

☐ 185.9

☒ 212.8

☐ 205.0



Correcto

You need to construct a logical vector in R to match the question's requirements. Then use that logical vector to subset the data frame.

19. What is the mean of "Temp" when "Month" is equal to 6?

1 / 1 puntos

☐ 85.6

☐ 90.2

☐ 75.3

☒ 79.1

 **Correcto**

20. What was the maximum ozone value in the month of May (i.e. Month is equal to 5)?

1 / 1 puntos

☐ 18

☒ 115

☐ 97

☐ 100

 **Correcto**