Aral SuperTronic E 0W-30

Engine oil in Aral Synthetic-Technology

Description

Aral SuperTronic E is a 0W-30 high performance engine oil with Aral Synthetic Technology. For gasoline and diesel passenger cars i.e. Volvo, Honda and Renault, requiring engine oils according to ACEA A5/B5. Especially for extended drain intervals with many Volvo cars.

Application

Aral SuperTronic E 0W-30 is suitable for use where oils with the specifications according to ACEA A5/B5 are recommended. This unique formulation is strongly recommended for use in Volvo vehicles.

Advantages

- Excellent thermal and oxidation stability
- Increased protection against wear

Typical Characteristics

Name	Method	Units	Aral SuperTronic E 0W-30
Density @ 15C, Relative	ASTM D4052	g/ml	0.8420
Viscosity, Kinematic 100C	ASTM D445	mm²/s	10.6
Viscosity, Kinematic 40C	ASTM D445	mm²/s	56.9
Viscosity Index	ASTM D2270	None	180
Viscosity, CCS -35C (0W)	ASTM D5293	mPa.s (cP)	5685
Pour Point	ASTM D97	°C	-42
Flash Point, PMCC	ASTM D93	°C	209
Ash, Sulphated	ASTM D874	% w t	0.6

Performance

ACEA C2
API SP

Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

Aral, the Aral logo and related marks are trademarks of Aral Aktiengesellschaft, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Aral Aktiengesellschaft, Geschäftsbereich Schmierstoffe, Überseeallee 1, D-20457 Hamburg
01801-11 55 11
www.aral-lubricants.de