Documentation Settings



# assignment

#### **AUTHORIZATION**

Bearer Token

#### **Token**

<token>

# account

# **POST** register

http://127.0.0.1:8000/api/account/auth/register

#### **BODY** urlencoded

#### email

test@gmail.com

#### password

testtest

#### password2

testtest

Example Request register

```
curl --location --request POST 'http://127.0.0.1:8000/api/account/auth/register' \
--data-urlencode 'email=test@gmail.com' \
--data-urlencode 'password=testtest' \
--data-urlencode 'password2=testtest'
```

 $\equiv$ 

**Documentation Settings** 

http://127.0.0.1:8000/api/account/auth/login

#### **BODY** urlencoded

#### email

test@gmail.com

#### password

testtestn

Example Request login

```
curl --location --request POST 'http://127.0.0.1:8000/api/account/auth/login' \
--data-urlencode 'email=test@gmail.com' \
--data-urlencode 'password=testtestn'
```

### **POST** activate email

http://127.0.0.1:8000/api/account/auth/email-activation/Mw/bexqtc-9e5fc86ca6e8c5214007d57a57ceb14c

Example Request activate email

```
curl --location --request POST 'http://127.0.0.1:8000/api/account/auth/email-activation/Mw/bexqtc-9e5f
```

# **POST** send password reset email

http://127.0.0.1:8000/api/account/auth/send-reset-password-email

#### **BODY** urlencoded

#### email

 $\equiv$ 

**Documentation Settings** 

**Example Request** 

send password reset email

```
curl --location --request POST 'http://127.0.0.1:8000/api/account/auth/send-reset-password-email' \
--data-urlencode 'email=test@gmail.com'
```

## **POST** reset password link

http://127.0.0.1:8000/api/account/auth/reset-password/Mw/bexqz0-7342d4a66c90fd3b086b6f08958d2aef

#### **BODY** urlencoded

#### password

testtestn

#### password2

testtestn

Example Request reset password link

```
curl --location --request POST 'http://127.0.0.1:8000/api/account/auth/reset-password/Mw/bexqz0-7342d4
--data-urlencode 'password2=testtestn'
--data-urlencode 'password2=testtestn'
```

### **POST** refresh token

http://127.0.0.1:8000/api/account/auth/token/refresh

#### **BODY** urlencoded

#### refresh

eyJhbGciOiJIUzI1NiIsInR5cCl6IkpXVCJ9.eyJ0b2tlbl90eXBlIjoicmVmcmVzaClsImV4cCl6MTY2ODc4OTgxNSwiaWF0IjoxNjY3ND



**Documentation Settings** 

Example Request refresh token

curl --location --request POST 'http://127.0.0.1:8000/api/account/auth/token/refresh' \
--data-urlencode 'refresh=eyJhbGci0iJIUzI1NiIsInR5cCI6IkpXVCJ9.eyJ0b2tlbl90eXBlIjoicmVmcmVzaCIsImV4cCI

4

# settings

#### **AUTHORIZATION**

Bearer Token

This folder is using Bearer Token from collection assignment

# **PUT** update password

http://127.0.0.1:8000/api/account/user/changedpassword/

#### **AUTHORIZATION**

Bearer Token

This request is using Bearer Token from collection assignment

**BODY** urlencoded

old\_password

testtestn

new\_password

testtestnew

new\_password2

testtestnew

**Documentation Settings** 

```
\equiv
```

```
curl --location --request PUT 'http://127.0.0.1:8000/api/account/user/changedpassword/' \
--data-urlencode 'old_password=testtestn' \
--data-urlencode 'new_password=testtestnew' \
```